

MySQL 8.0 Error Message Reference

Abstract

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2025-04-28 (revision: 81812)

Table of Contents

Preface and Legal Notices	v
1 MySQL Error Reference	1
2 Server Error Message Reference	3
3 Client Error Message Reference	611
4 Global Error Message Reference	619
Index	627

Preface and Legal Notices

This is the MySQL 8.0 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.0.

Legal Notices

Copyright © 1997, 2025, Oracle and/or its affiliates.

License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC

International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Use of This Documentation

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, *Server Error Message Reference*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, *Client Error Message Reference*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, *Global Error Message Reference*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.0 Reference Manual](#).

Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER_CANT_CREATE_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER_CANT_CREATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER_CANT_CREATE_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

- Error number: [1007](#); Symbol: [ER_DB_CREATE_EXISTS](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s'; database exists

An attempt to create a database failed because the database already exists.

Drop the database first if you really want to replace an existing database, or add an `IF NOT EXISTS` clause to the `CREATE DATABASE` statement if to retain an existing database without having the statement produce an error.

- Error number: 1008; Symbol: `ER_DB_DROP_EXISTS`; SQLSTATE: `HY000`

Message: Can't drop database '%s'; database doesn't exist

- Error number: 1010; Symbol: `ER_DB_DROP_RMDIR`; SQLSTATE: `HY000`

Message: Error dropping database (can't rmdir '%s', errno: %d - %s)

- Error number: 1012; Symbol: `ER_CANT_FIND_SYSTEM_REC`; SQLSTATE: `HY000`

Message: Can't read record in system table

Returned by `InnoDB` for attempts to access `InnoDB INFORMATION_SCHEMA` tables when `InnoDB` is unavailable.

- Error number: 1013; Symbol: `ER_CANT_GET_STAT`; SQLSTATE: `HY000`

Message: Can't get status of '%s' (errno: %d - %s)

- Error number: 1015; Symbol: `ER_CANT_LOCK`; SQLSTATE: `HY000`

Message: Can't lock file (errno: %d - %s)

- Error number: 1016; Symbol: `ER_CANT_OPEN_FILE`; SQLSTATE: `HY000`

Message: Can't open file: '%s' (errno: %d - %s)

`InnoDB` reports this error when the table from the `InnoDB data files` cannot be found.

- Error number: 1017; Symbol: `ER_FILE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find file: '%s' (errno: %d - %s)

- Error number: 1018; Symbol: `ER_CANT_READ_DIR`; SQLSTATE: `HY000`

Message: Can't read dir of '%s' (errno: %d - %s)

- Error number: 1020; Symbol: `ER_CHECKREAD`; SQLSTATE: `HY000`

Message: Record has changed since last read in table '%s'

- Error number: 1022; Symbol: `ER_DUP_KEY`; SQLSTATE: `23000`

Message: Can't write; duplicate key in table '%s'

- Error number: 1024; Symbol: `ER_ERROR_ON_READ`; SQLSTATE: `HY000`

Message: Error reading file '%s' (errno: %d - %s)

- Error number: 1025; Symbol: `ER_ERROR_ON_RENAME`; SQLSTATE: `HY000`

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: 1026; Symbol: `ER_ERROR_ON_WRITE`; SQLSTATE: `HY000`

Message: Error writing file '%s' (errno: %d - %s)

- Error number: 1027; Symbol: `ER_FILE_USED`; SQLSTATE: `HY000`

Message: '%s' is locked against change

- Error number: 1028; Symbol: [ER_FILSORT_ABORT](#); SQLSTATE: HY000

Message: Sort aborted

[ER_FILSORT_ABORT](#) was removed after 8.0.18.

- Error number: 1030; Symbol: [ER_GET_ERRNO](#); SQLSTATE: HY000

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: 1031; Symbol: [ER_ILLEGAL HA](#); SQLSTATE: HY000

Message: Table storage engine for '%s' doesn't have this option

- Error number: 1032; Symbol: [ER_KEY_NOT_FOUND](#); SQLSTATE: HY000

Message: Can't find record in '%s'

- Error number: 1033; Symbol: [ER_NOT_FORM_FILE](#); SQLSTATE: HY000

Message: Incorrect information in file: '%s'

- Error number: 1034; Symbol: [ER_NOT_KEYFILE](#); SQLSTATE: HY000

Message: Incorrect key file for table '%s'; try to repair it

- Error number: 1035; Symbol: [ER_OLD_KEYFILE](#); SQLSTATE: HY000

Message: Old key file for table '%s'; repair it!

- Error number: 1036; Symbol: [ER_OPEN_AS_READONLY](#); SQLSTATE: HY000

Message: Table '%s' is read only

- Error number: 1037; Symbol: [ER_OUTOFMEMORY](#); SQLSTATE: HY001

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: 1038; Symbol: [ER_OUT_OF_SORTMEMORY](#); SQLSTATE: HY001

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: 1040; Symbol: [ER_CON_COUNT_ERROR](#); SQLSTATE: 08004

Message: Too many connections

- Error number: 1041; Symbol: [ER_OUT_OF_RESOURCES](#); SQLSTATE: HY000

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: 1042; Symbol: [ER_BAD_HOST_ERROR](#); SQLSTATE: 08S01

Message: Can't get hostname for your address

- Error number: 1043; Symbol: [ER_HANDSHAKE_ERROR](#); SQLSTATE: 08S01

Message: Bad handshake

- Error number: 1044; Symbol: [ER_DBACCESS_DENIED_ERROR](#); SQLSTATE: 42000
Message: Access denied for user '%s'@'%s' to database '%s'
- Error number: 1045; Symbol: [ER_ACCESS_DENIED_ERROR](#); SQLSTATE: 28000
Message: Access denied for user '%s'@'%s' (using password: %s)
- Error number: 1046; Symbol: [ER_NO_DB_ERROR](#); SQLSTATE: 3D000
Message: No database selected
- Error number: 1047; Symbol: [ER_UNKNOWN_COM_ERROR](#); SQLSTATE: 08S01
Message: Unknown command
- Error number: 1048; Symbol: [ER_BAD_NULL_ERROR](#); SQLSTATE: 23000
Message: Column '%s' cannot be null
- Error number: 1049; Symbol: [ER_BAD_DB_ERROR](#); SQLSTATE: 42000
Message: Unknown database '%s'
- Error number: 1050; Symbol: [ER_TABLE_EXISTS_ERROR](#); SQLSTATE: 42S01
Message: Table '%s' already exists
- Error number: 1051; Symbol: [ER_BAD_TABLE_ERROR](#); SQLSTATE: 42S02
Message: Unknown table '%s'
- Error number: 1052; Symbol: [ER_NON_UNIQ_ERROR](#); SQLSTATE: 23000
Message: Column '%s' in %s is ambiguous

%s = column name
%s = location of column (for example, "field list")

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: 1053; Symbol: [ER_SERVER_SHUTDOWN](#); SQLSTATE: 08S01
Message: Server shutdown in progress
- Error number: 1054; Symbol: [ER_BAD_FIELD_ERROR](#); SQLSTATE: 42S22

Message: Unknown column '%s' in '%s'

- Error number: [1055](#); Symbol: [ER_WRONG_FIELD_WITH_GROUP](#); SQLSTATE: 42000

Message: '%s' isn't in GROUP BY

- Error number: [1056](#); Symbol: [ER_WRONG_GROUP_FIELD](#); SQLSTATE: 42000

Message: Can't group on '%s'

- Error number: [1057](#); Symbol: [ER_WRONG_SUM_SELECT](#); SQLSTATE: 42000

Message: Statement has sum functions and columns in same statement

- Error number: [1058](#); Symbol: [ER_WRONG_VALUE_COUNT](#); SQLSTATE: 21S01

Message: Column count doesn't match value count

- Error number: [1059](#); Symbol: [ER_TOO_LONG_IDENT](#); SQLSTATE: 42000

Message: Identifier name '%s' is too long

- Error number: [1060](#); Symbol: [ER_DUP_FIELDNAME](#); SQLSTATE: 42S21

Message: Duplicate column name '%s'

- Error number: [1061](#); Symbol: [ER_DUP_KEYNAME](#); SQLSTATE: 42000

Message: Duplicate key name '%s'

- Error number: [1062](#); Symbol: [ER_DUP_ENTRY](#); SQLSTATE: 23000

Message: Duplicate entry '%s' for key %d

The message returned with this error uses the format string for [ER_DUP_ENTRY_WITH_KEY_NAME](#).

- Error number: [1063](#); Symbol: [ER_WRONG_FIELD_SPEC](#); SQLSTATE: 42000

Message: Incorrect column specifier for column '%s'

- Error number: [1064](#); Symbol: [ER_PARSE_ERROR](#); SQLSTATE: 42000

Message: %s near '%s' at line %d

- Error number: [1065](#); Symbol: [ER_EMPTY_QUERY](#); SQLSTATE: 42000

Message: Query was empty

- Error number: [1066](#); Symbol: [ER_NONUNIQ_TABLE](#); SQLSTATE: 42000

Message: Not unique table/alias: '%s'

- Error number: [1067](#); Symbol: [ER_INVALID_DEFAULT](#); SQLSTATE: 42000

Message: Invalid default value for '%s'

- Error number: [1068](#); Symbol: [ER_MULTIPLE_PRI_KEY](#); SQLSTATE: 42000

Message: Multiple primary key defined

- Error number: [1069](#); Symbol: [ER_TOO_MANY_KEYS](#); SQLSTATE: 42000

Message: Too many keys specified; max %d keys allowed

- Error number: [1070](#); Symbol: [ER_TOO_MANY_KEY_PARTS](#); SQLSTATE: 42000

-
- Message: Too many key parts specified; max %d parts allowed
- Error number: 1071; Symbol: [ER_TOO_LONG_KEY](#); SQLSTATE: 42000
Message: Specified key was too long; max key length is %d bytes
 - Error number: 1072; Symbol: [ER_KEY_COLUMN_DOES_NOT_EXISTS](#); SQLSTATE: 42000
Message: Key column '%s' doesn't exist in table
 - Error number: 1073; Symbol: [ER_BLOB_USED_AS_KEY](#); SQLSTATE: 42000
Message: BLOB column '%s' can't be used in key specification with the used table type
 - Error number: 1074; Symbol: [ER_TOO_BIG_FIELDLENGTH](#); SQLSTATE: 42000
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
 - Error number: 1075; Symbol: [ER_WRONG_AUTO_KEY](#); SQLSTATE: 42000
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
 - Error number: 1076; Symbol: [ER_READY](#); SQLSTATE: HY000
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
 - Error number: 1077; Symbol: [ER_NORMAL_SHUTDOWN](#); SQLSTATE: HY000
Message: %s: Normal shutdown
[ER_NORMAL_SHUTDOWN](#) was removed after 8.0.4.
 - Error number: 1079; Symbol: [ER_SHUTDOWN_COMPLETE](#); SQLSTATE: HY000
Message: %s: Shutdown complete
 - Error number: 1080; Symbol: [ER_FORCING_CLOSE](#); SQLSTATE: 08S01
Message: %s: Forcing close of thread %ld user: '%s'
 - Error number: 1081; Symbol: [ER_IPSOCK_ERROR](#); SQLSTATE: 08S01
Message: Can't create IP socket
 - Error number: 1082; Symbol: [ER_NO_SUCH_INDEX](#); SQLSTATE: 42S12
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
 - Error number: 1083; Symbol: [ER_WRONG_FIELD_TERMINATORS](#); SQLSTATE: 42000
Message: Field separator argument is not what is expected; check the manual
 - Error number: 1084; Symbol: [ER_BLOBS_AND_NO_TERMINATED](#); SQLSTATE: 42000
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
 - Error number: 1085; Symbol: [ER_TEXTFILE_NOT_READABLE](#); SQLSTATE: HY000
Message: The file '%s' must be in the database directory or be readable by all
 - Error number: 1086; Symbol: [ER_FILE_EXISTS_ERROR](#); SQLSTATE: HY000
Message: File '%s' already exists

-
- Error number: [1087](#); Symbol: [ER_LOAD_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
 - Error number: [1088](#); Symbol: [ER_ALTER_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld
 - Error number: [1089](#); Symbol: [ER_WRONG_SUB_KEY](#); SQLSTATE: [HY000](#)
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys
 - Error number: [1090](#); Symbol: [ER_CANT_REMOVE_ALL_FIELDS](#); SQLSTATE: [42000](#)
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
 - Error number: [1091](#); Symbol: [ER_CANT_DROP_FIELD_OR_KEY](#); SQLSTATE: [42000](#)
Message: Can't DROP '%s'; check that column/key exists
 - Error number: [1092](#); Symbol: [ER_INSERT_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld Warnings: %ld
 - Error number: [1093](#); Symbol: [ER_UPDATE_TABLE_USED](#); SQLSTATE: [HY000](#)
Message: You can't specify target table '%s' for update in FROM clause

This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived_merge](#) flag of the [optimizer_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
 - Error number: [1094](#); Symbol: [ER_NO_SUCH_THREAD](#); SQLSTATE: [HY000](#)
Message: Unknown thread id: %lu
 - Error number: [1095](#); Symbol: [ER_KILL_DENIED_ERROR](#); SQLSTATE: [HY000](#)
Message: You are not owner of thread %lu
 - Error number: [1096](#); Symbol: [ER_NO_TABLES_USED](#); SQLSTATE: [HY000](#)
Message: No tables used
 - Error number: [1097](#); Symbol: [ER_TOO_BIG_SET](#); SQLSTATE: [HY000](#)
Message: Too many strings for column %s and SET
 - Error number: [1098](#); Symbol: [ER_NO_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)
Message: Can't generate a unique log-filename %s.(1-999)
 - Error number: [1099](#); Symbol: [ER_TABLE_NOT_LOCKED_FOR_WRITE](#); SQLSTATE: [HY000](#)
Message: Table '%s' was locked with a READ lock and can't be updated
 - Error number: [1100](#); Symbol: [ER_TABLE_NOT_LOCKED](#); SQLSTATE: [HY000](#)
Message: Table '%s' was not locked with LOCK TABLES

-
- Error number: [1101](#); Symbol: [ER_BLOB_CANT_HAVE_DEFAULT](#); SQLSTATE: [42000](#)
Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
 - Error number: [1102](#); Symbol: [ER_WRONG_DB_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect database name '%s'
 - Error number: [1103](#); Symbol: [ER_WRONG_TABLE_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect table name '%s'
 - Error number: [1104](#); Symbol: [ER_TOO_BIG_SELECT](#); SQLSTATE: [42000](#)
Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=1 or SET MAX_JOIN_SIZE=# if the SELECT is okay
 - Error number: [1105](#); Symbol: [ER_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: Unknown error
 - Error number: [1106](#); Symbol: [ER_UNKNOWN_PROCEDURE](#); SQLSTATE: [42000](#)
Message: Unknown procedure '%s'
 - Error number: [1107](#); Symbol: [ER_WRONG_PARAMCOUNT_TO_PROCEDURE](#); SQLSTATE: [42000](#)
Message: Incorrect parameter count to procedure '%s'
 - Error number: [1108](#); Symbol: [ER_WRONG_PARAMETERS_TO_PROCEDURE](#); SQLSTATE: [HY000](#)
Message: Incorrect parameters to procedure '%s'
 - Error number: [1109](#); Symbol: [ER_UNKNOWN_TABLE](#); SQLSTATE: [42S02](#)
Message: Unknown table '%s' in %s
 - Error number: [1110](#); Symbol: [ER_FIELD_SPECIFIED_TWICE](#); SQLSTATE: [42000](#)
Message: Column '%s' specified twice
 - Error number: [1111](#); Symbol: [ER_INVALID_GROUP_FUNC_USE](#); SQLSTATE: [HY000](#)
Message: Invalid use of group function
 - Error number: [1112](#); Symbol: [ER_UNSUPPORTED_EXTENSION](#); SQLSTATE: [42000](#)
Message: Table '%s' uses an extension that doesn't exist in this MySQL version
 - Error number: [1113](#); Symbol: [ER_TABLE_MUST_HAVE_COLUMNS](#); SQLSTATE: [42000](#)
Message: A table must have at least 1 column
 - Error number: [1114](#); Symbol: [ER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)
Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.
 - Error number: [1115](#); Symbol: [ER_UNKNOWN_CHARACTER_SET](#); SQLSTATE: [42000](#)
Message: Unknown character set: '%s'
 - Error number: [1116](#); Symbol: [ER_TOO_MANY_TABLES](#); SQLSTATE: [HY000](#)

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: 1117; Symbol: `ER_TOO_MANY_FIELDS`; SQLSTATE: HY000

Message: Too many columns

- Error number: 1118; Symbol: `ER_TOO_BIG_ROW_SIZE`; SQLSTATE: 42000

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

- Error number: 1119; Symbol: `ER_STACK_OVERRUN`; SQLSTATE: HY000

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger stack if needed

- Error number: 1120; Symbol: `ER_WRONG_OUTER_JOIN`; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

`ER_WRONG_OUTER_JOIN` was removed after 8.0.0.

- Error number: 1120; Symbol: `ER_WRONG_OUTER_JOIN_UNUSED`; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

`ER_WRONG_OUTER_JOIN_UNUSED` was added in 8.0.1.

- Error number: 1121; Symbol: `ER_NULL_COLUMN_IN_INDEX`; SQLSTATE: 42000

Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler

- Error number: 1122; Symbol: `ER_CANT_FIND_UDF`; SQLSTATE: HY000

Message: Can't load function '%s'

- Error number: 1123; Symbol: `ER_CANT_INITIALIZE_UDF`; SQLSTATE: HY000

Message: Can't initialize function '%s'; %s

- Error number: 1124; Symbol: `ER_UDF_NO_PATHS`; SQLSTATE: HY000

Message: No paths allowed for shared library

- Error number: 1125; Symbol: `ER_UDF_EXISTS`; SQLSTATE: HY000

Message: Function '%s' already exists

- Error number: 1126; Symbol: `ER_CANT_OPEN_LIBRARY`; SQLSTATE: HY000

Message: Can't open shared library '%s' (errno: %d %s)

- Error number: 1127; Symbol: `ER_CANT_FIND_DL_ENTRY`; SQLSTATE: HY000

Message: Can't find symbol '%s' in library

- Error number: 1128; Symbol: `ER_FUNCTION_NOT_DEFINED`; SQLSTATE: HY000

Message: Function '%s' is not defined

- Error number: 1129; Symbol: `ER_HOST_IS_BLOCKED`; SQLSTATE: HY000

Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'

- Error number: 1130; Symbol: [ER_HOST_NOT_PRIVILEGED](#); SQLSTATE: HY000

Message: Host '%s' is not allowed to connect to this MySQL server

- Error number: 1131; Symbol: [ER_PASSWORD_ANONYMOUS_USER](#); SQLSTATE: 42000

Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords

- Error number: 1132; Symbol: [ER_PASSWORD_NOT_ALLOWED](#); SQLSTATE: 42000

Message: You must have privileges to update tables in the mysql database to be able to change passwords for others

- Error number: 1133; Symbol: [ER_PASSWORD_NO_MATCH](#); SQLSTATE: 42000

Message: Can't find any matching row in the user table

- Error number: 1134; Symbol: [ER_UPDATE_INFO](#); SQLSTATE: HY000

Message: Rows matched: %ld Changed: %ld Warnings: %ld

- Error number: 1135; Symbol: [ER_CANT_CREATE_THREAD](#); SQLSTATE: HY000

Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug

- Error number: 1136; Symbol: [ER_WRONG_VALUE_COUNT_ON_ROW](#); SQLSTATE: 21S01

Message: Column count doesn't match value count at row %ld

- Error number: 1137; Symbol: [ER_CANT_REOPEN_TABLE](#); SQLSTATE: HY000

Message: Can't reopen table: '%s'

- Error number: 1138; Symbol: [ER_INVALID_USE_OF_NULL](#); SQLSTATE: 22004

Message: Invalid use of NULL value

- Error number: 1139; Symbol: [ER_REGEXP_ERROR](#); SQLSTATE: 42000

Message: Got error '%s' from regexp

- Error number: 1140; Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS](#); SQLSTATE: 42000

Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause

- Error number: 1141; Symbol: [ER_NONEXISTING_GRANT](#); SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s'

- Error number: 1142; Symbol: [ER_TABLEACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: %s command denied to user '%s'@'%s' for table '%s'

- Error number: 1143; Symbol: [ER_COLUMNACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'

-
- Error number: [1144](#); Symbol: [ER_ILLEGAL_GRANT_FOR_TABLE](#); SQLSTATE: [42000](#)
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
 - Error number: [1145](#); Symbol: [ER_GRANT_WRONG_HOST_OR_USER](#); SQLSTATE: [42000](#)
Message: The host or user argument to GRANT is too long
 - Error number: [1146](#); Symbol: [ER_NO_SUCH_TABLE](#); SQLSTATE: [42S02](#)
Message: Table '%s.%s' doesn't exist
 - Error number: [1147](#); Symbol: [ER_NONEXISTING_TABLE_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
 - Error number: [1148](#); Symbol: [ER_NOT_ALLOWED_COMMAND](#); SQLSTATE: [42000](#)
Message: The used command is not allowed with this MySQL version
 - Error number: [1149](#); Symbol: [ER_SYNTAX_ERROR](#); SQLSTATE: [42000](#)
Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use
 - Error number: [1152](#); Symbol: [ER_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %ld to db: '%s' user: '%s' (%s)
 - Error number: [1153](#); Symbol: [ER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [08S01](#)
Message: Got a packet bigger than 'max_allowed_packet' bytes
 - Error number: [1154](#); Symbol: [ER_NET_READ_ERROR_FROM_PIPE](#); SQLSTATE: [08S01](#)
Message: Got a read error from the connection pipe
 - Error number: [1155](#); Symbol: [ER_NET_FCNTL_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error from fcntl()
 - Error number: [1156](#); Symbol: [ER_NET_PACKETS_OUT_OF_ORDER](#); SQLSTATE: [08S01](#)
Message: Got packets out of order
 - Error number: [1157](#); Symbol: [ER_NET_UNCOMPRESS_ERROR](#); SQLSTATE: [08S01](#)
Message: Couldn't uncompress communication packet
 - Error number: [1158](#); Symbol: [ER_NET_READ_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error reading communication packets
 - Error number: [1159](#); Symbol: [ER_NET_READ_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout reading communication packets
 - Error number: [1160](#); Symbol: [ER_NET_ERROR_ON_WRITE](#); SQLSTATE: [08S01](#)
Message: Got an error writing communication packets
 - Error number: [1161](#); Symbol: [ER_NET_WRITE_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout writing communication packets

-
- Error number: [1162](#); Symbol: [ER_TOO_LONG_STRING](#); SQLSTATE: [42000](#)
Message: Result string is longer than 'max_allowed_packet' bytes
 - Error number: [1163](#); Symbol: [ER_TABLE_CANT_HANDLE_BLOB](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support BLOB/TEXT columns
 - Error number: [1164](#); Symbol: [ER_TABLE_CANT_HANDLE_AUTO_INCREMENT](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support AUTO_INCREMENT columns
 - Error number: [1166](#); Symbol: [ER_WRONG_COLUMN_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect column name '%s'
 - Error number: [1167](#); Symbol: [ER_WRONG_KEY_COLUMN](#); SQLSTATE: [42000](#)
Message: The used storage engine can't index column '%s'
 - Error number: [1168](#); Symbol: [ER_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
 - Error number: [1169](#); Symbol: [ER_DUP_UNIQUE](#); SQLSTATE: [23000](#)
Message: Can't write, because of unique constraint, to table '%s'
 - Error number: [1170](#); Symbol: [ER_BLOB_KEY_WITHOUT_LENGTH](#); SQLSTATE: [42000](#)
Message: BLOB/TEXT column '%s' used in key specification without a key length
 - Error number: [1171](#); Symbol: [ER_PRIMARY_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
 - Error number: [1172](#); Symbol: [ER_TOO_MANY_ROWS](#); SQLSTATE: [42000](#)
Message: Result consisted of more than one row
 - Error number: [1173](#); Symbol: [ER_REQUIRES_PRIMARY_KEY](#); SQLSTATE: [42000](#)
Message: This table type requires a primary key
 - Error number: [1175](#); Symbol: [ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE](#); SQLSTATE: [HY000](#)
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
 - Error number: [1176](#); Symbol: [ER_KEY_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)
Message: Key '%s' doesn't exist in table '%s'
 - Error number: [1177](#); Symbol: [ER_CHECK_NO_SUCH_TABLE](#); SQLSTATE: [42000](#)
Message: Can't open table
 - Error number: [1178](#); Symbol: [ER_CHECK_NOT_IMPLEMENTED](#); SQLSTATE: [42000](#)
Message: The storage engine for the table doesn't support %s
 - Error number: [1179](#); Symbol: [ER_CANT_DO_THIS_DURING_AN_TRANSACTION](#); SQLSTATE: [25000](#)

Message: You are not allowed to execute this command in a transaction

- Error number: 1180; Symbol: [ER_ERROR_DURING_COMMIT](#); SQLSTATE: HY000

Message: Got error %d - '%s' during COMMIT

- Error number: 1181; Symbol: [ER_ERROR_DURING_ROLLBACK](#); SQLSTATE: HY000

Message: Got error %d - '%s' during ROLLBACK

- Error number: 1182; Symbol: [ER_ERROR_DURING_FLUSH_LOGS](#); SQLSTATE: HY000

Message: Got error %d during FLUSH_LOGS

- Error number: 1184; Symbol: [ER_NEW_ABORTING_CONNECTION](#); SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: 1188; Symbol: [ER_MASTER](#); SQLSTATE: HY000

Message: Error from master: '%s'

[ER_MASTER](#) was removed after 8.0.32.

- Error number: 1188; Symbol: [ER_SOURCE](#); SQLSTATE: HY000

Message: Error from source: '%s'

[ER_SOURCE](#) was added in 8.0.33.

- Error number: 1189; Symbol: [ER_MASTER_NET_READ](#); SQLSTATE: 08S01

Message: Net error reading from master

[ER_MASTER_NET_READ](#) was removed after 8.0.32.

- Error number: 1189; Symbol: [ER_SOURCE_NET_READ](#); SQLSTATE: 08S01

Message: Net error reading from source

[ER_SOURCE_NET_READ](#) was added in 8.0.33.

- Error number: 1190; Symbol: [ER_MASTER_NET_WRITE](#); SQLSTATE: 08S01

Message: Net error writing to master

[ER_MASTER_NET_WRITE](#) was removed after 8.0.32.

- Error number: 1190; Symbol: [ER_SOURCE_NET_WRITE](#); SQLSTATE: 08S01

Message: Net error writing to source

[ER_SOURCE_NET_WRITE](#) was added in 8.0.33.

- Error number: 1191; Symbol: [ER_FT_MATCHING_KEY_NOT_FOUND](#); SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

- Error number: 1192; Symbol: [ER_LOCK_OR_ACTIVE_TRANSACTION](#); SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: 1193; Symbol: [ER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: HY000

Message: Unknown system variable '%s'

- Error number: 1194; Symbol: [ER_CRASHED_ON_USAGE](#); SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

- Error number: 1195; Symbol: [ER_CRASHED_ON_REPAIR](#); SQLSTATE: HY000

Message: Table '%s' is marked as crashed and last (automatic?) repair failed

- Error number: 1196; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK](#); SQLSTATE: HY000

Message: Some non-transactional changed tables couldn't be rolled back

- Error number: 1197; Symbol: [ER_TRANS_CACHE_FULL](#); SQLSTATE: HY000

Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1199; Symbol: [ER_SLAVE_NOT_RUNNING](#); SQLSTATE: HY000

Message: This operation requires a running slave; configure slave and do START SLAVE

[ER_SLAVE_NOT_RUNNING](#) was removed after 8.0.32.

- Error number: 1199; Symbol: [ER_REPLICA_NOT_RUNNING](#); SQLSTATE: HY000

Message: This operation requires a running replica; configure replica and do START REPLICA

[ER_REPLICA_NOT_RUNNING](#) was added in 8.0.33.

- Error number: 1200; Symbol: [ER_BAD_SLAVE](#); SQLSTATE: HY000

Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO

[ER_BAD_SLAVE](#) was removed after 8.0.32.

- Error number: 1200; Symbol: [ER_BAD_REPLICA](#); SQLSTATE: HY000

Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO

[ER_BAD_REPLICA](#) was added in 8.0.33.

- Error number: 1201; Symbol: [ER_MASTER_INFO](#); SQLSTATE: HY000

Message: Could not initialize master info structure; more error messages can be found in the MySQL error log

[ER_MASTER_INFO](#) was removed after 8.0.32.

- Error number: 1201; Symbol: [ER_CONNECTION_METADATA](#); SQLSTATE: HY000

Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log

[ER_CONNECTION_METADATA](#) was added in 8.0.33.

- Error number: 1202; Symbol: [ER_SLAVE_THREAD](#); SQLSTATE: HY000

Message: Could not create slave thread; check system resources

[ER_SLAVE_THREAD](#) was removed after 8.0.32.

-
- Error number: [1202](#); Symbol: [ER_REPLICA_THREAD](#); SQLSTATE: [HY000](#)
Message: Could not create replica thread; check system resources
[ER_REPLICA_THREAD](#) was added in 8.0.33.
 - Error number: [1203](#); Symbol: [ER_TOO_MANY_USER_CONNECTIONS](#); SQLSTATE: [42000](#)
Message: User %s already has more than 'max_user_connections' active connections
 - Error number: [1204](#); Symbol: [ER_SET_CONSTANTS_ONLY](#); SQLSTATE: [HY000](#)
Message: You may only use constant expressions with SET
 - Error number: [1205](#); Symbol: [ER_LOCK_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: Lock wait timeout exceeded; try restarting transaction
[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb_lock_wait_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.
 - Error number: [1206](#); Symbol: [ER_LOCK_TABLE_FULL](#); SQLSTATE: [HY000](#)
Message: The total number of locks exceeds the lock table size
[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb_buffer_pool_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.
 - Error number: [1207](#); Symbol: [ER_READ_ONLY_TRANSACTION](#); SQLSTATE: [25000](#)
Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction
 - Error number: [1210](#); Symbol: [ER_WRONG_ARGUMENTS](#); SQLSTATE: [HY000](#)
Message: Incorrect arguments to %s
 - Error number: [1211](#); Symbol: [ER_NO_PERMISSION_TO_CREATE_USER](#); SQLSTATE: [42000](#)
Message: '%s'@'%s' is not allowed to create new users
 - Error number: [1213](#); Symbol: [ER_LOCK_DEADLOCK](#); SQLSTATE: [40001](#)
Message: Deadlock found when trying to get lock; try restarting transaction
[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES](#), [SELECT ... FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.
 - Error number: [1214](#); Symbol: [ER_TABLE_CANT_HANDLE_FT](#); SQLSTATE: [HY000](#)
Message: The used table type doesn't support FULLTEXT indexes
-

-
- Error number: 1215; Symbol: `ER_CANNOT_ADD_FOREIGN`; SQLSTATE: `HY000`
Message: Cannot add foreign key constraint
 - Error number: 1216; Symbol: `ER_NO_REFERENCED_ROW`; SQLSTATE: `23000`
Message: Cannot add or update a child row: a foreign key constraint fails
`InnoDB` reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
 - Error number: 1217; Symbol: `ER_ROW_IS_REFERENCED`; SQLSTATE: `23000`
Message: Cannot delete or update a parent row: a foreign key constraint fails
`InnoDB` reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: 1218; Symbol: `ER_CONNECT_TO_MASTER`; SQLSTATE: `08S01`
Message: Error connecting to master: %s
`ER_CONNECT_TO_MASTER` was removed after 8.0.32.
 - Error number: 1218; Symbol: `ER_CONNECT_TO_SOURCE`; SQLSTATE: `08S01`
Message: Error connecting to source: %s
`ER_CONNECT_TO_SOURCE` was added in 8.0.33.
 - Error number: 1220; Symbol: `ER_ERROR_WHEN_EXECUTING_COMMAND`; SQLSTATE: `HY000`
Message: Error when executing command %s: %s
 - Error number: 1221; Symbol: `ER_WRONG_USAGE`; SQLSTATE: `HY000`
Message: Incorrect usage of %s and %s
 - Error number: 1222; Symbol: `ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT`; SQLSTATE: `21000`
Message: The used SELECT statements have a different number of columns
 - Error number: 1223; Symbol: `ER_CANT_UPDATE_WITH_READLOCK`; SQLSTATE: `HY000`
Message: Can't execute the query because you have a conflicting read lock
 - Error number: 1224; Symbol: `ER_MIXING_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: Mixing of transactional and non-transactional tables is disabled
 - Error number: 1225; Symbol: `ER_DUP_ARGUMENT`; SQLSTATE: `HY000`
Message: Option '%s' used twice in statement
 - Error number: 1226; Symbol: `ER_USER_LIMIT_REACHED`; SQLSTATE: `42000`
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
 - Error number: 1227; Symbol: `ER_SPECIFIC_ACCESS_DENIED_ERROR`; SQLSTATE: `42000`
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
 - Error number: 1228; Symbol: `ER_LOCAL_VARIABLE`; SQLSTATE: `HY000`
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL

-
- Error number: [1229](#); Symbol: [ER_GLOBAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
 - Error number: [1230](#); Symbol: [ER_NO_DEFAULT](#); SQLSTATE: [42000](#)
Message: Variable '%s' doesn't have a default value
 - Error number: [1231](#); Symbol: [ER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Variable '%s' can't be set to the value of '%s'
 - Error number: [1232](#); Symbol: [ER_WRONG_TYPE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Incorrect argument type to variable '%s'
 - Error number: [1233](#); Symbol: [ER_VAR_CANT_BE_READ](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can only be set, not read
 - Error number: [1234](#); Symbol: [ER_CANT_USE_OPTION_HERE](#); SQLSTATE: [42000](#)
Message: Incorrect usage/placement of '%s'
 - Error number: [1235](#); Symbol: [ER_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)
Message: This version of MySQL doesn't yet support '%s'
 - Error number: [1236](#); Symbol: [ER_MASTER_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from master when reading data from binary log: '%s'
[ER_MASTER_FATAL_ERROR_READING_BINLOG](#) was removed after 8.0.32.
 - Error number: [1236](#); Symbol: [ER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from source when reading data from binary log: '%s'
[ER_SOURCE_FATAL_ERROR_READING_BINLOG](#) was added in 8.0.33.
 - Error number: [1237](#); Symbol: [ER_SLAVE_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Slave SQL thread ignored the query because of replicate-*-table rules
[ER_SLAVE_IGNORED_TABLE](#) was removed after 8.0.32.
 - Error number: [1237](#); Symbol: [ER_REPLICA_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread ignored the query because of replicate-*-table rules
[ER_REPLICA_IGNORED_TABLE](#) was added in 8.0.33.
 - Error number: [1238](#); Symbol: [ER_INCORRECT_GLOBAL_LOCAL_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a %s variable
 - Error number: [1239](#); Symbol: [ER_WRONG_FK_DEF](#); SQLSTATE: [42000](#)
Message: Incorrect foreign key definition for '%s': %s
 - Error number: [1240](#); Symbol: [ER_KEY_REF_DO_NOT_MATCH_TABLE_REF](#); SQLSTATE: [HY000](#)
Message: Key reference and table reference don't match
 - Error number: [1241](#); Symbol: [ER_OPERAND_COLUMNS](#); SQLSTATE: [21000](#)

Message: Operand should contain %d column(s)

- Error number: 1242; Symbol: `ER_SUBQUERY_NO_1_ROW`; SQLSTATE: 21000

Message: Subquery returns more than 1 row

- Error number: 1243; Symbol: `ER_UNKNOWN_STMT_HANDLER`; SQLSTATE: HY000

Message: Unknown prepared statement handler (%.*s) given to %s

- Error number: 1244; Symbol: `ER_CORRUPT_HELP_DB`; SQLSTATE: HY000

Message: Help database is corrupt or does not exist

- Error number: 1246; Symbol: `ER_AUTO_CONVERT`; SQLSTATE: HY000

Message: Converting column '%s' from %s to %s

- Error number: 1247; Symbol: `ER_ILLEGAL_REFERENCE`; SQLSTATE: 42S22

Message: Reference '%s' not supported (%s)

- Error number: 1248; Symbol: `ER_DERIVED_MUST_HAVE_ALIAS`; SQLSTATE: 42000

Message: Every derived table must have its own alias

- Error number: 1249; Symbol: `ER_SELECT_REDUCED`; SQLSTATE: 01000

Message: Select %u was reduced during optimization

- Error number: 1250; Symbol: `ER_TABLENAME_NOT_ALLOWED_HERE`; SQLSTATE: 42000

Message: Table '%s' from one of the SELECTs cannot be used in %s

- Error number: 1251; Symbol: `ER_NOT_SUPPORTED_AUTH_MODE`; SQLSTATE: 08004

Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client

- Error number: 1252; Symbol: `ER_SPATIAL_CANT_HAVE_NULL`; SQLSTATE: 42000

Message: All parts of a SPATIAL index must be NOT NULL

- Error number: 1253; Symbol: `ER_COLLATION_CHARSET_MISMATCH`; SQLSTATE: 42000

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- Error number: 1256; Symbol: `ER_TOO_BIG_FOR_UNCOMPRESS`; SQLSTATE: HY000

Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)

- Error number: 1257; Symbol: `ER_ZLIB_Z_MEM_ERROR`; SQLSTATE: HY000

Message: ZLIB: Not enough memory

- Error number: 1258; Symbol: `ER_ZLIB_Z_BUF_ERROR`; SQLSTATE: HY000

Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)

- Error number: 1259; Symbol: `ER_ZLIB_Z_DATA_ERROR`; SQLSTATE: HY000

Message: ZLIB: Input data corrupted

-
- Error number: [1260](#); Symbol: [ER_CUT_VALUE_GROUP_CONCAT](#); SQLSTATE: [HY000](#)
Message: Row %u was cut by GROUP_CONCAT()
 - Error number: [1261](#); Symbol: [ER_WARN_TOO_FEW_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld doesn't contain data for all columns
 - Error number: [1262](#); Symbol: [ER_WARN_TOO_MANY_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld was truncated; it contained more data than there were input columns
 - Error number: [1263](#); Symbol: [ER_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [22004](#)
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
 - Error number: [1264](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)
Message: Out of range value for column '%s' at row %ld
 - Error number: [1265](#); Symbol: [WARN_DATA_TRUNCATED](#); SQLSTATE: [01000](#)
Message: Data truncated for column '%s' at row %ld
 - Error number: [1266](#); Symbol: [ER_WARN_USING_OTHER_HANDLER](#); SQLSTATE: [HY000](#)
Message: Using storage engine %s for table '%s'
 - Error number: [1267](#); Symbol: [ER_CANT_AGGREGATE_2COLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
 - Error number: [1269](#); Symbol: [ER_REVOKE_GRANTS](#); SQLSTATE: [HY000](#)
Message: Can't revoke all privileges for one or more of the requested users
 - Error number: [1270](#); Symbol: [ER_CANT_AGGREGATE_3COLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'
 - Error number: [1271](#); Symbol: [ER_CANT_AGGREGATE_NCOLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations for operation '%s'
 - Error number: [1272](#); Symbol: [ER_VARIABLE_IS_NOT_STRUCT](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is not a variable component (can't be used as XXXX.variable_name)
 - Error number: [1273](#); Symbol: [ER_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)
Message: Unknown collation: '%s'
 - Error number: [1274](#); Symbol: [ER_SLAVE_IGNORED_SSL_PARAMS](#); SQLSTATE: [HY000](#)
Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started
[ER_SLAVE_IGNORED_SSL_PARAMS](#) was removed after 8.0.32.
 - Error number: [1274](#); Symbol: [ER_REPLICA_IGNORED_SSL_PARAMS](#); SQLSTATE: [HY000](#)
Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

[ER_REPLICA_IGNORED_SSL_PARAMS](#) was added in 8.0.33.

- Error number: [1275](#); Symbol: [ER_SERVER_IS_IN_SECURE_AUTH_MODE](#); SQLSTATE: [HY000](#)

Message: Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please change the password to the new format

[ER_SERVER_IS_IN_SECURE_AUTH_MODE](#) was removed after 8.0.15.

- Error number: [1276](#); Symbol: [ER_WARN_FIELD_RESOLVED](#); SQLSTATE: [HY000](#)

Message: Field or reference '%s%s%s%s%s' of SELECT #%d was resolved in SELECT #%d

- Error number: [1277](#); Symbol: [ER_BAD_SLAVE_UNTIL_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL

[ER_BAD_SLAVE_UNTIL_COND](#) was removed after 8.0.32.

- Error number: [1277](#); Symbol: [ER_BAD_REPLICA_UNTIL_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

[ER_BAD_REPLICA_UNTIL_COND](#) was added in 8.0.33.

- Error number: [1278](#); Symbol: [ER_MISSING_SKIP_SLAVE](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart

[ER_MISSING_SKIP_SLAVE](#) was removed after 8.0.32.

- Error number: [1278](#); Symbol: [ER_MISSING_SKIP_REPLICA](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

[ER_MISSING_SKIP_REPLICA](#) was added in 8.0.33.

- Error number: [1279](#); Symbol: [ER_UNTIL_COND_IGNORED](#); SQLSTATE: [HY000](#)

Message: SQL thread is not to be started so UNTIL options are ignored

- Error number: [1280](#); Symbol: [ER_WRONG_NAME_FOR_INDEX](#); SQLSTATE: [42000](#)

Message: Incorrect index name '%s'

- Error number: [1281](#); Symbol: [ER_WRONG_NAME_FOR_CATALOG](#); SQLSTATE: [42000](#)

Message: Incorrect catalog name '%s'

- Error number: [1282](#); Symbol: [ER_WARN_QC_RESIZE](#); SQLSTATE: [HY000](#)

Message: Query cache failed to set size %lu; new query cache size is %lu

[ER_WARN_QC_RESIZE](#) was removed after 8.0.2.

- Error number: [1283](#); Symbol: [ER_BAD_FT_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be part of FULLTEXT index

-
- Error number: [1284](#); Symbol: [ER_UNKNOWN_KEY_CACHE](#); SQLSTATE: [HY000](#)
Message: Unknown key cache '%s'
 - Error number: [1285](#); Symbol: [ER_WARN_HOSTNAME_WONT_WORK](#); SQLSTATE: [HY000](#)
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work
 - Error number: [1286](#); Symbol: [ER_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [42000](#)
Message: Unknown storage engine '%s'
 - Error number: [1287](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
 - Error number: [1288](#); Symbol: [ER_NON_UPDATABLE_TABLE](#); SQLSTATE: [HY000](#)
Message: The target table %s of the %s is not updatable
 - Error number: [1289](#); Symbol: [ER_FEATURE_DISABLED](#); SQLSTATE: [HY000](#)
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
 - Error number: [1290](#); Symbol: [ER_OPTION_PREVENTS_STATEMENT](#); SQLSTATE: [HY000](#)
Message: The MySQL server is running with the %s option so it cannot execute this statement
 - Error number: [1291](#); Symbol: [ER_DUPLICATED_VALUE_IN_TYPE](#); SQLSTATE: [HY000](#)
Message: Column '%s' has duplicated value '%s' in %s
 - Error number: [1292](#); Symbol: [ER_TRUNCATED_WRONG_VALUE](#); SQLSTATE: [22007](#)
Message: Truncated incorrect %s value: '%s'
 - Error number: [1294](#); Symbol: [ER_INVALID_ON_UPDATE](#); SQLSTATE: [HY000](#)
Message: Invalid ON UPDATE clause for '%s' column
 - Error number: [1295](#); Symbol: [ER_UNSUPPORTED_PS](#); SQLSTATE: [HY000](#)
Message: This command is not supported in the prepared statement protocol yet
 - Error number: [1296](#); Symbol: [ER_GET_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got error %d '%s' from %s
 - Error number: [1297](#); Symbol: [ER_GET_TEMPORARY_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got temporary error %d '%s' from %s
 - Error number: [1298](#); Symbol: [ER_UNKNOWN_TIME_ZONE](#); SQLSTATE: [HY000](#)
Message: Unknown or incorrect time zone: '%s'
 - Error number: [1299](#); Symbol: [ER_WARN_INVALID_TIMESTAMP](#); SQLSTATE: [HY000](#)
Message: Invalid TIMESTAMP value in column '%s' at row %ld
 - Error number: [1300](#); Symbol: [ER_INVALID_CHARACTER_STRING](#); SQLSTATE: [HY000](#)
Message: Invalid %s character string: '%s'

-
- Error number: 1301; Symbol: `ER_WARN_ALLOWED_PACKET_OVERFLOWED`; SQLSTATE: `HY000`
Message: Result of %s() was larger than max_allowed_packet (%ld) - truncated
 - Error number: 1302; Symbol: `ER_CONFLICTING_DECLARATIONS`; SQLSTATE: `HY000`
Message: Conflicting declarations: '%s%s' and '%s%s'
 - Error number: 1303; Symbol: `ER_SP_NO_RECURSIVE_CREATE`; SQLSTATE: `2F003`
Message: Can't create a %s from within another stored routine
 - Error number: 1304; Symbol: `ER_SP_ALREADY_EXISTS`; SQLSTATE: `42000`
Message: %s %s already exists
 - Error number: 1305; Symbol: `ER_SP_DOES_NOT_EXIST`; SQLSTATE: `42000`
Message: %s %s does not exist
 - Error number: 1306; Symbol: `ER_SP_DROP_FAILED`; SQLSTATE: `HY000`
Message: Failed to DROP %s %s
 - Error number: 1307; Symbol: `ER_SP_STORE_FAILED`; SQLSTATE: `HY000`
Message: Failed to CREATE %s %s
 - Error number: 1308; Symbol: `ER_SP_LILABEL_MISMATCH`; SQLSTATE: `42000`
Message: %s with no matching label: %s
 - Error number: 1309; Symbol: `ER_SP_LABEL_REDEFINE`; SQLSTATE: `42000`
Message: Redefining label %s
 - Error number: 1310; Symbol: `ER_SP_LABEL_MISMATCH`; SQLSTATE: `42000`
Message: End-label %s without match
 - Error number: 1311; Symbol: `ER_SP_UNINIT_VAR`; SQLSTATE: `01000`
Message: Referring to uninitialized variable %s
 - Error number: 1312; Symbol: `ER_SP_BADSELECT`; SQLSTATE: `0A000`
Message: PROCEDURE %s can't return a result set in the given context
 - Error number: 1313; Symbol: `ER_SP_BADRETURN`; SQLSTATE: `42000`
Message: RETURN is only allowed in a FUNCTION
 - Error number: 1314; Symbol: `ER_SP_BADSTATEMENT`; SQLSTATE: `0A000`
Message: %s is not allowed in stored procedures
 - Error number: 1315; Symbol: `ER_UPDATE_LOG_DEPRECATED_IGNORED`; SQLSTATE: `42000`
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.
 - Error number: 1316; Symbol: `ER_UPDATE_LOG_DEPRECATED_TRANSLATED`; SQLSTATE: `42000`
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.

-
- Error number: 1317; Symbol: `ER_QUERY_INTERRUPTED`; SQLSTATE: 70100
Message: Query execution was interrupted
 - Error number: 1318; Symbol: `ER_SP_WRONG_NO_OF_ARGS`; SQLSTATE: 42000
Message: Incorrect number of arguments for %s %s; expected %u, got %u
 - Error number: 1319; Symbol: `ER_SP_COND_MISMATCH`; SQLSTATE: 42000
Message: Undefined CONDITION: %s
 - Error number: 1320; Symbol: `ER_SP_NORETURN`; SQLSTATE: 42000
Message: No RETURN found in FUNCTION %s
 - Error number: 1321; Symbol: `ER_SP_NORETURNEND`; SQLSTATE: 2F005
Message: FUNCTION %s ended without RETURN
 - Error number: 1322; Symbol: `ER_SP_BAD_CURSOR_QUERY`; SQLSTATE: 42000
Message: Cursor statement must be a SELECT
 - Error number: 1323; Symbol: `ER_SP_BAD_CURSOR_SELECT`; SQLSTATE: 42000
Message: Cursor SELECT must not have INTO
 - Error number: 1324; Symbol: `ER_SP_CURSOR_MISMATCH`; SQLSTATE: 42000
Message: Undefined CURSOR: %s
 - Error number: 1325; Symbol: `ER_SP_CURSOR_ALREADY_OPEN`; SQLSTATE: 24000
Message: Cursor is already open
 - Error number: 1326; Symbol: `ER_SP_CURSOR_NOT_OPEN`; SQLSTATE: 24000
Message: Cursor is not open
 - Error number: 1327; Symbol: `ER_SP_UNDECLARED_VAR`; SQLSTATE: 42000
Message: Undeclared variable: %s
 - Error number: 1328; Symbol: `ER_SP_WRONG_NO_OF_FETCH_ARGS`; SQLSTATE: HY000
Message: Incorrect number of FETCH variables
 - Error number: 1329; Symbol: `ER_SP_FETCH_NO_DATA`; SQLSTATE: 02000
Message: No data - zero rows fetched, selected, or processed
 - Error number: 1330; Symbol: `ER_SP_DUP_PARAM`; SQLSTATE: 42000
Message: Duplicate parameter: %s
 - Error number: 1331; Symbol: `ER_SP_DUP_VAR`; SQLSTATE: 42000
Message: Duplicate variable: %s
 - Error number: 1332; Symbol: `ER_SP_DUP_COND`; SQLSTATE: 42000
Message: Duplicate condition: %s
 - Error number: 1333; Symbol: `ER_SP_DUP_CURS`; SQLSTATE: 42000

Message: Duplicate cursor: %s

- Error number: 1334; Symbol: [ER_SP_CANT_ALTER](#); SQLSTATE: HY000

Message: Failed to ALTER %s %s

- Error number: 1335; Symbol: [ER_SP_SUBSELECT_NYI](#); SQLSTATE: 0A000

Message: Subquery value not supported

- Error number: 1336; Symbol: [ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: 0A000

Message: %s is not allowed in stored function or trigger

- Error number: 1337; Symbol: [ER_SP_VARCOND_AFTER_CURSHNDLR](#); SQLSTATE: 42000

Message: Variable or condition declaration after cursor or handler declaration

- Error number: 1338; Symbol: [ER_SP_CURSOR_AFTER_HANDLER](#); SQLSTATE: 42000

Message: Cursor declaration after handler declaration

- Error number: 1339; Symbol: [ER_SP_CASE_NOT_FOUND](#); SQLSTATE: 20000

Message: Case not found for CASE statement

- Error number: 1340; Symbol: [ER_FPARSER_TOO_BIG_FILE](#); SQLSTATE: HY000

Message: Configuration file '%s' is too big

- Error number: 1341; Symbol: [ER_FPARSER_BAD_HEADER](#); SQLSTATE: HY000

Message: Malformed file type header in file '%s'

- Error number: 1342; Symbol: [ER_FPARSER_EOF_IN_COMMENT](#); SQLSTATE: HY000

Message: Unexpected end of file while parsing comment '%s'

- Error number: 1343; Symbol: [ER_FPARSER_ERROR_IN_PARAMETER](#); SQLSTATE: HY000

Message: Error while parsing parameter '%s' (line: '%s')

- Error number: 1344; Symbol: [ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER](#); SQLSTATE: HY000

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: 1345; Symbol: [ER_VIEW_NO_EXPLAIN](#); SQLSTATE: HY000

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: 1347; Symbol: [ER_WRONG_OBJECT](#); SQLSTATE: HY000

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION_SCHEMA](#) table that is implemented as a view on data dictionary tables.

- Error number: 1348; Symbol: [ER_NONUPDATEABLE_COLUMN](#); SQLSTATE: HY000

Message: Column '%s' is not updatable

- Error number: 1350; Symbol: [ER_VIEW_SELECT_CLAUSE](#); SQLSTATE: HY000

Message: View's SELECT contains a '%s' clause

- Error number: 1351; Symbol: [ER_VIEW_SELECT_VARIABLE](#); SQLSTATE: HY000

Message: View's SELECT contains a variable or parameter

- Error number: 1352; Symbol: [ER_VIEW_SELECT_TMPTABLE](#); SQLSTATE: HY000

Message: View's SELECT refers to a temporary table '%s'

- Error number: 1353; Symbol: [ER_VIEW_WRONG_LIST](#); SQLSTATE: HY000

Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts

- Error number: 1354; Symbol: [ER_WARN_VIEW_MERGE](#); SQLSTATE: HY000

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: 1355; Symbol: [ER_WARN_VIEW_WITHOUT_KEY](#); SQLSTATE: HY000

Message: View being updated does not have complete key of underlying table in it

- Error number: 1356; Symbol: [ER_VIEW_INVALID](#); SQLSTATE: HY000

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer invoker of view lack rights to use them

- Error number: 1357; Symbol: [ER_SP_NO_DROP_SP](#); SQLSTATE: HY000

Message: Can't drop or alter a %s from within another stored routine

- Error number: 1359; Symbol: [ER_TRG_ALREADY_EXISTS](#); SQLSTATE: HY000

Message: Trigger already exists

- Error number: 1360; Symbol: [ER_TRG_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: Trigger does not exist

- Error number: 1361; Symbol: [ER_TRG_ON_VIEW_OR_TEMP_TABLE](#); SQLSTATE: HY000

Message: Trigger's '%s' is view or temporary table

- Error number: 1362; Symbol: [ER_TRG_CANT_CHANGE_ROW](#); SQLSTATE: HY000

Message: Updating of %s row is not allowed in %strigger

- Error number: 1363; Symbol: [ER_TRG_NO_SUCH_ROW_IN_TRG](#); SQLSTATE: HY000

Message: There is no %s row in %s trigger

- Error number: 1364; Symbol: [ER_NO_DEFAULT_FOR_FIELD](#); SQLSTATE: HY000

Message: Field '%s' doesn't have a default value

- Error number: 1365; Symbol: [ER_DIVISION_BY_ZERO](#); SQLSTATE: 22012

Message: Division by 0

- Error number: 1366; Symbol: [ER_TRUNCATED_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: HY000

Message: Incorrect %s value: '%s' for column '%s' at row %ld

-
- Error number: 1367; Symbol: [ER_ILLEGAL_VALUE_FOR_TYPE](#); SQLSTATE: 22007
Message: Illegal %s '%s' value found during parsing
 - Error number: 1368; Symbol: [ER_VIEW_NONUPD_CHECK](#); SQLSTATE: HY000
Message: CHECK OPTION on non-updatable view '%s.%s'
 - Error number: 1369; Symbol: [ER_VIEW_CHECK_FAILED](#); SQLSTATE: HY000
Message: CHECK OPTION failed '%s.%s'
 - Error number: 1370; Symbol: [ER_PROCACCESS_DENIED_ERROR](#); SQLSTATE: 42000
Message: %s command denied to user '%s'@'%s' for routine '%s'
 - Error number: 1371; Symbol: [ER_RELAY_LOG_FAIL](#); SQLSTATE: HY000
Message: Failed purging old relay logs: %s
 - Error number: 1373; Symbol: [ER_UNKNOWN_TARGET_BINLOG](#); SQLSTATE: HY000
Message: Target log not found in binlog index
 - Error number: 1374; Symbol: [ER_IO_ERR_LOG_INDEX_READ](#); SQLSTATE: HY000
Message: I/O error reading log index file
 - Error number: 1375; Symbol: [ER_BINLOG_PURGE_PROHIBITED](#); SQLSTATE: HY000
Message: Server configuration does not permit binlog purge
 - Error number: 1376; Symbol: [ER_FSEEK_FAIL](#); SQLSTATE: HY000
Message: Failed on fseek()
 - Error number: 1377; Symbol: [ER_BINLOG_PURGE_FATAL_ERR](#); SQLSTATE: HY000
Message: Fatal error during log purge
 - Error number: 1378; Symbol: [ER_LOG_IN_USE](#); SQLSTATE: HY000
Message: A purgeable log is in use, will not purge
 - Error number: 1379; Symbol: [ER_LOG_PURGE_UNKNOWN_ERR](#); SQLSTATE: HY000
Message: Unknown error during log purge
 - Error number: 1380; Symbol: [ER_RELAY_LOG_INIT](#); SQLSTATE: HY000
Message: Failed initializing relay log position: %s
 - Error number: 1381; Symbol: [ER_NO_BINARY_LOGGING](#); SQLSTATE: HY000
Message: You are not using binary logging
 - Error number: 1382; Symbol: [ER_RESERVED_SYNTAX](#); SQLSTATE: HY000
Message: The '%s' syntax is reserved for purposes internal to the MySQL server
 - Error number: 1390; Symbol: [ER_PS_MANY_PARAM](#); SQLSTATE: HY000
Message: Prepared statement contains too many placeholders
 - Error number: 1391; Symbol: [ER_KEY_PART_0](#); SQLSTATE: HY000

Message: Key part '%s' length cannot be 0

- Error number: 1392; Symbol: [ER_VIEW_CHECKSUM](#); SQLSTATE: HY000

Message: View text checksum failed

- Error number: 1393; Symbol: [ER_VIEW_MULTIUPDATE](#); SQLSTATE: HY000

Message: Can not modify more than one base table through a join view '%s.%s'

- Error number: 1394; Symbol: [ER_VIEW_NO_INSERT_FIELD_LIST](#); SQLSTATE: HY000

Message: Can not insert into join view '%s.%s' without fields list

- Error number: 1395; Symbol: [ER_VIEW_DELETE_MERGE_VIEW](#); SQLSTATE: HY000

Message: Can not delete from join view '%s.%s'

- Error number: 1396; Symbol: [ER_CANNOT_USER](#); SQLSTATE: HY000

Message: Operation %s failed for %s

- Error number: 1397; Symbol: [ER_XAER_NOTA](#); SQLSTATE: XAE04

Message: XAER_NOTA: Unknown XID

- Error number: 1398; Symbol: [ER_XAER_INVAL](#); SQLSTATE: XAE05

Message: XAER_INVAL: Invalid arguments (or unsupported command)

- Error number: 1399; Symbol: [ER_XAER_RMFAIL](#); SQLSTATE: XAE07

Message: XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state

- Error number: 1400; Symbol: [ER_XAER_OUTSIDE](#); SQLSTATE: XAE09

Message: XAER_OUTSIDE: Some work is done outside global transaction

- Error number: 1401; Symbol: [ER_XAER_RMERR](#); SQLSTATE: XAE03

Message: XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency

- Error number: 1402; Symbol: [ER_XA_RBROLLBACK](#); SQLSTATE: XA100

Message: XA_RBROLLBACK: Transaction branch was rolled back

- Error number: 1403; Symbol: [ER_NONEXISTING_PROC_GRANT](#); SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'

- Error number: 1404; Symbol: [ER_PROC_AUTO_GRANT_FAIL](#); SQLSTATE: HY000

Message: Failed to grant EXECUTE and ALTER ROUTINE privileges

- Error number: 1405; Symbol: [ER_PROC_AUTO_REVOKE_FAIL](#); SQLSTATE: HY000

Message: Failed to revoke all privileges to dropped routine

- Error number: 1406; Symbol: [ER_DATA_TOO_LONG](#); SQLSTATE: 22001

Message: Data too long for column '%s' at row %ld

-
- Error number: 1407; Symbol: ER_SP_BAD_SQLSTATE; SQLSTATE: 42000
Message: Bad SQLSTATE: '%s'
 - Error number: 1408; Symbol: ER_STARTUP; SQLSTATE: HY000
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s
 - Error number: 1409; Symbol: ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR; SQLSTATE: HY000
Message: Can't load value from file with fixed size rows to variable
 - Error number: 1410; Symbol: ER_CANT_CREATE_USER_WITH_GRANT; SQLSTATE: 42000
Message: You are not allowed to create a user with GRANT
 - Error number: 1411; Symbol: ER_WRONG_VALUE_FOR_TYPE; SQLSTATE: HY000
Message: Incorrect %s value: '%s' for function %s
 - Error number: 1412; Symbol: ER_TABLE_DEF_CHANGED; SQLSTATE: HY000
Message: Table definition has changed, please retry transaction
 - Error number: 1413; Symbol: ER_SP_DUP_HANDLER; SQLSTATE: 42000
Message: Duplicate handler declared in the same block
 - Error number: 1414; Symbol: ER_SP_NOT_VAR_ARG; SQLSTATE: 42000
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
 - Error number: 1415; Symbol: ER_SP_NO_RETSET; SQLSTATE: 0A000
Message: Not allowed to return a result set from a %s
 - Error number: 1416; Symbol: ER_CANT_CREATE_GEOMETRY_OBJECT; SQLSTATE: 22003
Message: Cannot get geometry object from data you send to the GEOMETRY field
 - Error number: 1418; Symbol: ER_BINLOG_UNSAFE_ROUTINE; SQLSTATE: HY000
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: 1419; Symbol: ER_BINLOG_CREATE_ROUTINE_NEED_SUPER; SQLSTATE: HY000
Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: 1421; Symbol: ER_STMT_HAS_NO_OPEN_CURSOR; SQLSTATE: HY000
Message: The statement (%lu) has no open cursor.
 - Error number: 1422; Symbol: ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG; SQLSTATE: HY000
Message: Explicit or implicit commit is not allowed in stored function or trigger.
 - Error number: 1423; Symbol: ER_NO_DEFAULT_FOR_VIEW_FIELD; SQLSTATE: HY000
Message: Field of view '%s.%s' underlying table doesn't have a default value

-
- Error number: [1424](#); Symbol: [ER_SP_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: Recursive stored functions and triggers are not allowed.
 - Error number: [1425](#); Symbol: [ER_TOO_BIG_SCALE](#); SQLSTATE: [42000](#)
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
 - Error number: [1426](#); Symbol: [ER_TOO_BIG_PRECISION](#); SQLSTATE: [42000](#)
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
 - Error number: [1427](#); Symbol: [ER_M_BIGGER_THAN_D](#); SQLSTATE: [42000](#)
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
 - Error number: [1428](#); Symbol: [ER_WRONG_LOCK_OF_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)
Message: You can't combine write-locking of system tables with other tables or lock types
 - Error number: [1429](#); Symbol: [ER_CONNECT_TO_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)
Message: Unable to connect to foreign data source: %s
 - Error number: [1430](#); Symbol: [ER_QUERY_ON_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)
Message: There was a problem processing the query on the foreign data source. Data source error: %s
 - Error number: [1431](#); Symbol: [ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST](#); SQLSTATE: [HY000](#)
Message: The foreign data source you are trying to reference does not exist. Data source error: %s
 - Error number: [1432](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE](#); SQLSTATE: [HY000](#)
Message: Can't create federated table. The data source connection string '%s' is not in the correct format
 - Error number: [1433](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID](#); SQLSTATE: [HY000](#)
Message: The data source connection string '%s' is not in the correct format
 - Error number: [1435](#); Symbol: [ER_TRG_IN_WRONG_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Trigger in wrong schema
 - Error number: [1436](#); Symbol: [ER_STACK_OVERRUN_NEED_MORE](#); SQLSTATE: [HY000](#)
Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread_stack=#' to specify a bigger stack.
 - Error number: [1437](#); Symbol: [ER_TOO_LONG_BODY](#); SQLSTATE: [42000](#)
Message: Routine body for '%s' is too long
 - Error number: [1438](#); Symbol: [ER_WARN_CANT_DROP_DEFAULT_KEYCACHE](#); SQLSTATE: [HY000](#)
Message: Cannot drop default keycache
 - Error number: [1439](#); Symbol: [ER_TOO_BIG_DISPLAYWIDTH](#); SQLSTATE: [42000](#)
Message: Display width out of range for column '%s' (max = %lu)

-
- Error number: 1440; Symbol: [ER_XAER_DUPID](#); SQLSTATE: XAE08
Message: XAER_DUPID: The XID already exists
 - Error number: 1441; Symbol: [ER_DATETIME_FUNCTION_OVERFLOW](#); SQLSTATE: 22008
Message: Datetime function: %s field overflow
 - Error number: 1442; Symbol: [ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG](#); SQLSTATE: HY000
Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.
 - Error number: 1443; Symbol: [ER_VIEW_PREVENT_UPDATE](#); SQLSTATE: HY000
Message: The definition of table '%s' prevents operation %s on table '%s'.
 - Error number: 1444; Symbol: [ER_PS_NO_RECURSION](#); SQLSTATE: HY000
Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner
 - Error number: 1445; Symbol: [ER_SP_CANT_SET_AUTOCOMMIT](#); SQLSTATE: HY000
Message: Not allowed to set autocommit from a stored function or trigger
 - Error number: 1447; Symbol: [ER_VIEW_FRM_NO_USER](#); SQLSTATE: HY000
Message: View '%s'. '%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!
 - Error number: 1448; Symbol: [ER_VIEW_OTHER_USER](#); SQLSTATE: HY000
Message: You need the SUPER privilege for creation view with '%s'@'%s' definer
 - Error number: 1449; Symbol: [ER_NO_SUCH_USER](#); SQLSTATE: HY000
Message: The user specified as a definer ('%s'@'%s') does not exist
 - Error number: 1450; Symbol: [ER_FORBID_SCHEMA_CHANGE](#); SQLSTATE: HY000
Message: Changing schema from '%s' to '%s' is not allowed.
 - Error number: 1451; Symbol: [ER_ROW_IS_REFERENCED_2](#); SQLSTATE: 23000
Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: 1452; Symbol: [ER_NO_REFERENCED_ROW_2](#); SQLSTATE: 23000
Message: Cannot add or update a child row: a foreign key constraint fails (%s)
[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
 - Error number: 1453; Symbol: [ER_SP_BAD_VAR_SHADOW](#); SQLSTATE: 42000
Message: Variable '%s' must be quoted with `...`, or renamed
 - Error number: 1454; Symbol: [ER_TRG_NO_DEFINER](#); SQLSTATE: HY000

Message: No definer attribute for trigger '%s'. '%s'. It's disallowed to create trigger without definer.

- Error number: 1455; Symbol: [ER_OLD_FILE_FORMAT](#); SQLSTATE: HY000

Message: '%s' has an old format, you should re-create the '%s' object(s)

- Error number: 1456; Symbol: [ER_SP_RECURSION_LIMIT](#); SQLSTATE: HY000

Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s

- Error number: 1458; Symbol: [ER_SP_WRONG_NAME](#); SQLSTATE: 42000

Message: Incorrect routine name '%s'

- Error number: 1459; Symbol: [ER_TABLE_NEEDS_UPGRADE](#); SQLSTATE: HY000

Message: Table upgrade required. Please do "REPAIR TABLE '%s'" or dump/reload to fix it!

- Error number: 1460; Symbol: [ER_SP_NO_AGGREGATE](#); SQLSTATE: 42000

Message: AGGREGATE is not supported for stored functions

- Error number: 1461; Symbol: [ER_MAX_PREPARED_STMT_COUNT_REACHED](#); SQLSTATE: 42000

Message: Can't create more than max_prepared_stmt_count statements (current value: %lu)

- Error number: 1462; Symbol: [ER_VIEW_RECURSIVE](#); SQLSTATE: HY000

Message: '%s'. '%s' contains view recursion

- Error number: 1463; Symbol: [ER_NON_GROUPING_FIELD_USED](#); SQLSTATE: 42000

Message: Non-grouping field '%s' is used in %s clause

- Error number: 1464; Symbol: [ER_TABLE_CANT_HANDLE_SPKEYS](#); SQLSTATE: HY000

Message: The used table type doesn't support SPATIAL indexes

- Error number: 1465; Symbol: [ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA](#); SQLSTATE: HY000

Message: Triggers can not be created on system tables

- Error number: 1466; Symbol: [ER_REMOVED_SPACES](#); SQLSTATE: HY000

Message: Leading spaces are removed from name '%s'

- Error number: 1467; Symbol: [ER_AUTOINC_READ_FAILED](#); SQLSTATE: HY000

Message: Failed to read auto-increment value from storage engine

- Error number: 1468; Symbol: [ER_USERNAME](#); SQLSTATE: HY000

Message: user name

- Error number: 1469; Symbol: [ER_HOSTNAME](#); SQLSTATE: HY000

Message: host name

- Error number: 1470; Symbol: [ER_WRONG_STRING_LENGTH](#); SQLSTATE: HY000

Message: String '%s' is too long for %s (should be no longer than %d)

- Error number: 1471; Symbol: [ER_NON_INSERTABLE_TABLE](#); SQLSTATE: HY000

Message: The target table %s of the %s is not insertable-into

- Error number: 1472; Symbol: [ER_ADMIN_WRONG_MRG_TABLE](#); SQLSTATE: HY000

Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist

- Error number: 1473; Symbol: [ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT](#); SQLSTATE: HY000

Message: Too high level of nesting for select

- Error number: 1474; Symbol: [ER_NAME_BECOMES_EMPTY](#); SQLSTATE: HY000

Message: Name '%s' has become "

- Error number: 1475; Symbol: [ER_AMBIGUOUS_FIELD_TERM](#); SQLSTATE: HY000

Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY

- Error number: 1476; Symbol: [ER_FOREIGN_SERVER_EXISTS](#); SQLSTATE: HY000

Message: The foreign server, %s, you are trying to create already exists.

- Error number: 1477; Symbol: [ER_FOREIGN_SERVER_DOESNT_EXIST](#); SQLSTATE: HY000

Message: The foreign server name you are trying to reference does not exist. Data source error: %s

- Error number: 1478; Symbol: [ER_ILLEGAL_HA_CREATE_OPTION](#); SQLSTATE: HY000

Message: Table storage engine '%s' does not support the create option '%s'

- Error number: 1479; Symbol: [ER_PARTITION_REQUIRES_VALUES_ERROR](#); SQLSTATE: HY000

Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition

- Error number: 1480; Symbol: [ER_PARTITION_WRONG_VALUES_ERROR](#); SQLSTATE: HY000

Message: Only %s PARTITIONING can use VALUES %s in partition definition

- Error number: 1481; Symbol: [ER_PARTITION_MAXVALUE_ERROR](#); SQLSTATE: HY000

Message: MAXVALUE can only be used in last partition definition

- Error number: 1484; Symbol: [ER_PARTITION_WRONG_NO_PART_ERROR](#); SQLSTATE: HY000

Message: Wrong number of partitions defined, mismatch with previous setting

- Error number: 1485; Symbol: [ER_PARTITION_WRONG_NO_SUBPART_ERROR](#); SQLSTATE: HY000

Message: Wrong number of subpartitions defined, mismatch with previous setting

- Error number: 1486; Symbol: [ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR](#); SQLSTATE: HY000

Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed

- Error number: 1488; Symbol: [ER_FIELD_NOT_FOUND_PART_ERROR](#); SQLSTATE: HY000

Message: Field in list of fields for partition function not found in table

- Error number: 1490; Symbol: [ER_INCONSISTENT_PARTITION_INFO_ERROR](#); SQLSTATE: HY000

-
- Message: The partition info in the frm file is not consistent with what can be written into the frm file
- Error number: 1491; Symbol: `ER_PARTITION_FUNC_NOT_ALLOWED_ERROR`; SQLSTATE: HY000
Message: The %s function returns the wrong type
 - Error number: 1492; Symbol: `ER_PARTITIONS_MUST_BE_DEFINED_ERROR`; SQLSTATE: HY000
Message: For %s partitions each partition must be defined
 - Error number: 1493; Symbol: `ER_RANGE_NOT_INCREASING_ERROR`; SQLSTATE: HY000
Message: VALUES LESS THAN value must be strictly increasing for each partition
 - Error number: 1494; Symbol: `ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR`; SQLSTATE: HY000
Message: VALUES value must be of same type as partition function
 - Error number: 1495; Symbol: `ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR`; SQLSTATE: HY000
Message: Multiple definition of same constant in list partitioning
 - Error number: 1496; Symbol: `ER_PARTITION_ENTRY_ERROR`; SQLSTATE: HY000
Message: Partitioning can not be used stand-alone in query
 - Error number: 1497; Symbol: `ER_MIX_HANDLER_ERROR`; SQLSTATE: HY000
Message: The mix of handlers in the partitions is not allowed in this version of MySQL
 - Error number: 1498; Symbol: `ER_PARTITION_NOT_DEFINED_ERROR`; SQLSTATE: HY000
Message: For the partitioned engine it is necessary to define all %s
 - Error number: 1499; Symbol: `ER_TOO_MANY_PARTITIONS_ERROR`; SQLSTATE: HY000
Message: Too many partitions (including subpartitions) were defined
 - Error number: 1500; Symbol: `ER_SUBPARTITION_ERROR`; SQLSTATE: HY000
Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
 - Error number: 1501; Symbol: `ER_CANT_CREATE_HANDLER_FILE`; SQLSTATE: HY000
Message: Failed to create specific handler file
 - Error number: 1502; Symbol: `ER_BLOB_FIELD_IN_PART_FUNC_ERROR`; SQLSTATE: HY000
Message: A BLOB field is not allowed in partition function
 - Error number: 1503; Symbol: `ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF`; SQLSTATE: HY000
Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).
 - Error number: 1504; Symbol: `ER_NO_PARTS_ERROR`; SQLSTATE: HY000
Message: Number of %s = 0 is not an allowed value
 - Error number: 1505; Symbol: `ER_PARTITION_MGMT_ON_NONPARTITIONED`; SQLSTATE: HY000

Message: Partition management on a not partitioned table is not possible

- Error number: 1506; Symbol: `ER_FOREIGN_KEY_ON_PARTITIONED`; SQLSTATE: HY000

Message: Foreign keys are not yet supported in conjunction with partitioning

- Error number: 1507; Symbol: `ER_DROP_PARTITION_NON_EXISTENT`; SQLSTATE: HY000

Message: Error in list of partitions to %s

- Error number: 1508; Symbol: `ER_DROP_LAST_PARTITION`; SQLSTATE: HY000

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: `ER_COALESCE_ONLY_ON_HASH_PARTITION`; SQLSTATE: HY000

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: `ER_REORG_HASH_ONLY_ON_SAME_NO`; SQLSTATE: HY000

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

- Error number: 1511; Symbol: `ER_REORG_NO_PARAM_ERROR`; SQLSTATE: HY000

Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS

- Error number: 1512; Symbol: `ER_ONLY_ON_RANGE_LIST_PARTITION`; SQLSTATE: HY000

Message: %s PARTITION can only be used on RANGE/LIST partitions

- Error number: 1513; Symbol: `ER_ADD_PARTITION_SUBPART_ERROR`; SQLSTATE: HY000

Message: Trying to Add partition(s) with wrong number of subpartitions

- Error number: 1514; Symbol: `ER_ADD_PARTITION_NO_NEW_PARTITION`; SQLSTATE: HY000

Message: At least one partition must be added

- Error number: 1515; Symbol: `ER_COALESCE_PARTITION_NO_PARTITION`; SQLSTATE: HY000

Message: At least one partition must be coalesced

- Error number: 1516; Symbol: `ER_REORG_PARTITION_NOT_EXIST`; SQLSTATE: HY000

Message: More partitions to reorganize than there are partitions

- Error number: 1517; Symbol: `ER_SAME_NAME_PARTITION`; SQLSTATE: HY000

Message: Duplicate partition name %s

- Error number: 1518; Symbol: `ER_NO_BINLOG_ERROR`; SQLSTATE: HY000

Message: It is not allowed to shut off binlog on this command

- Error number: 1519; Symbol: `ER_CONSECUTIVE_REORG_PARTITIONS`; SQLSTATE: HY000

Message: When reorganizing a set of partitions they must be in consecutive order

- Error number: 1520; Symbol: `ER_REORG_OUTSIDE_RANGE`; SQLSTATE: HY000

Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range

-
- Error number: 1521; Symbol: ER_PARTITION_FUNCTION_FAILURE; SQLSTATE: HY000
Message: Partition function not supported in this version for this handler
 - Error number: 1523; Symbol: ER_LIMITED_PART_RANGE; SQLSTATE: HY000
Message: The %s handler only supports 32 bit integers in VALUES
 - Error number: 1524; Symbol: ER_PLUGIN_IS_NOT_LOADED; SQLSTATE: HY000
Message: Plugin '%s' is not loaded
 - Error number: 1525; Symbol: ER_WRONG_VALUE; SQLSTATE: HY000
Message: Incorrect %s value: '%s'
 - Error number: 1526; Symbol: ER_NO_PARTITION_FOR_GIVEN_VALUE; SQLSTATE: HY000
Message: Table has no partition for value %s
 - Error number: 1527; Symbol: ER_FILEGROUP_OPTION_ONLY_ONCE; SQLSTATE: HY000
Message: It is not allowed to specify %s more than once
 - Error number: 1528; Symbol: ER_CREATE_FILEGROUP_FAILED; SQLSTATE: HY000
Message: Failed to create %s
 - Error number: 1529; Symbol: ER_DROP_FILEGROUP_FAILED; SQLSTATE: HY000
Message: Failed to drop %s
 - Error number: 1530; Symbol: ER_TABLESPACE_AUTO_EXTEND_ERROR; SQLSTATE: HY000
Message: The handler doesn't support autoextend of tablespaces
 - Error number: 1531; Symbol: ER_WRONG_SIZE_NUMBER; SQLSTATE: HY000
Message: A size parameter was incorrectly specified, either number or on the form 10M
 - Error number: 1532; Symbol: ER_SIZE_OVERFLOW_ERROR; SQLSTATE: HY000
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
 - Error number: 1533; Symbol: ER_ALTER_FILEGROUP_FAILED; SQLSTATE: HY000
Message: Failed to alter: %s
 - Error number: 1534; Symbol: ER_BINLOG_ROW_LOGGING_FAILED; SQLSTATE: HY000
Message: Writing one row to the row-based binary log failed
 - Error number: 1537; Symbol: ER_EVENT_ALREADY_EXISTS; SQLSTATE: HY000
Message: Event '%s' already exists
 - Error number: 1539; Symbol: ER_EVENT_DOES_NOT_EXIST; SQLSTATE: HY000
Message: Unknown event '%s'
 - Error number: 1542; Symbol: ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG; SQLSTATE: HY000
Message: INTERVAL is either not positive or too big

-
- Error number: 1543; Symbol: `ER_EVENT_ENDS_BEFORE_STARTS`; SQLSTATE: HY000

Message: ENDS is either invalid or before STARTS

- Error number: 1544; Symbol: `ER_EVENT_EXEC_TIME_IN_THE_PAST`; SQLSTATE: HY000

Message: Event execution time is in the past. Event has been disabled

- Error number: 1551; Symbol: `ER_EVENT_SAME_NAME`; SQLSTATE: HY000

Message: Same old and new event name

- Error number: 1553; Symbol: `ER_DROP_INDEX_FK`; SQLSTATE: HY000

Message: Cannot drop index '%s': needed in a foreign key constraint

InnoDB reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, InnoDB requires an index to exist on [foreign key](#) columns, so that `UPDATE` and `DELETE` operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of `CREATE TABLE`, `CREATE INDEX`, and `ALTER TABLE` statements.

When you drop an index, InnoDB checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. InnoDB prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: 1554; Symbol: `ER_WARN_DEPRECATED_SYNTAX_WITH_VER`; SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead

- Error number: 1556; Symbol: `ER_CANT_LOCK_LOG_TABLE`; SQLSTATE: HY000

Message: You can't use locks with log tables.

- Error number: 1557; Symbol: `ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED`; SQLSTATE: 23000

Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry

- Error number: 1558; Symbol: `ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE`; SQLSTATE: HY000

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 1559; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR`; SQLSTATE: HY000

Message: Cannot switch out of the row-based binary log format when the session has open temporary tables

`ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR` was removed after 8.0.12.

- Error number: 1560; Symbol: `ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT`; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

- Error number: 1562; Symbol: `ER_PARTITION_NO_TEMPORARY`; SQLSTATE: HY000

Message: Cannot create temporary table with partitions

-
- Error number: 1563; Symbol: [ER_PARTITION_CONST_DOMAIN_ERROR](#); SQLSTATE: HY000
Message: Partition constant is out of partition function domain
 - Error number: 1564; Symbol: [ER_PARTITION_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: This partition function is not allowed
 - Error number: 1565; Symbol: [ER_DDL_LOG_ERROR](#); SQLSTATE: HY000
Message: Error in DDL log
[ER_DDL_LOG_ERROR](#) was removed after 8.0.1.
 - Error number: 1566; Symbol: [ER_NULL_IN_VALUES_LESS_THAN](#); SQLSTATE: HY000
Message: Not allowed to use NULL value in VALUES LESS THAN
 - Error number: 1567; Symbol: [ER_WRONG_PARTITION_NAME](#); SQLSTATE: HY000
Message: Incorrect partition name
 - Error number: 1568; Symbol: [ER_CANT_CHANGE_TX_CHARACTERISTICS](#); SQLSTATE: 25001
Message: Transaction characteristics can't be changed while a transaction is in progress
 - Error number: 1569; Symbol: [ER_DUP_ENTRY_AUTOINCREMENT_CASE](#); SQLSTATE: HY000
Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for key '%s'
 - Error number: 1571; Symbol: [ER_EVENT_SET_VAR_ERROR](#); SQLSTATE: HY000
Message: Error during starting/stopping of the scheduler. Error code %u
 - Error number: 1572; Symbol: [ER_PARTITION_MERGE_ERROR](#); SQLSTATE: HY000
Message: Engine cannot be used in partitioned tables
 - Error number: 1575; Symbol: [ER_BASE64_DECODE_ERROR](#); SQLSTATE: HY000
Message: Decoding of base64 string failed
 - Error number: 1576; Symbol: [ER_EVENT_RECURSION_FORBIDDEN](#); SQLSTATE: HY000
Message: Recursion of EVENT DDL statements is forbidden when body is present
 - Error number: 1578; Symbol: [ER_ONLY_INTEGERS_ALLOWED](#); SQLSTATE: HY000
Message: Only integers allowed as number here
 - Error number: 1579; Symbol: [ER_UNSUPPORTED_LOG_ENGINE](#); SQLSTATE: HY000
Message: This storage engine cannot be used for log tables
 - Error number: 1580; Symbol: [ER_BAD_LOG_STATEMENT](#); SQLSTATE: HY000
Message: You cannot '%s' a log table if logging is enabled
 - Error number: 1581; Symbol: [ER_CANT_RENAME_LOG_TABLE](#); SQLSTATE: HY000
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
 - Error number: 1582; Symbol: [ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameter count in the call to native function '%s'

- Error number: 1583; Symbol: [ER_WRONG_PARAMETERS_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to native function '%s'

- Error number: 1584; Symbol: [ER_WRONG_PARAMETERS_TO_STORED_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to stored function %s

- Error number: 1585; Symbol: [ER_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a native function

- Error number: 1586; Symbol: [ER_DUP_ENTRY_WITH_KEY_NAME](#); SQLSTATE: 23000

Message: Duplicate entry '%s' for key '%s'

The format string for this error is also used with [ER_DUP_ENTRY](#).

- Error number: 1587; Symbol: [ER_BINLOG_PURGE_EMFILE](#); SQLSTATE: HY000

Message: Too many files opened, please execute the command again

- Error number: 1588; Symbol: [ER_EVENT_CANNOT_CREATE_IN_THE_PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.

- Error number: 1589; Symbol: [ER_EVENT_CANNOT ALTER IN THE PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.

- Error number: 1591; Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT](#); SQLSTATE: HY000

Message: Table has no partition for some existing values

- Error number: 1592; Symbol: [ER_BINLOG_UNSAFE_STATEMENT](#); SQLSTATE: HY000

Message: Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %s

- Error number: 1593; Symbol: [ER_BINLOG_FATAL_ERROR](#); SQLSTATE: HY000

Message: Fatal error: %s

[ER_BINLOG_FATAL_ERROR](#) was added in 8.0.11.

- Error number: 1598; Symbol: [ER_BINLOG_LOGGING_IMPOSSIBLE](#); SQLSTATE: HY000

Message: Binary logging not possible. Message: %s

- Error number: 1599; Symbol: [ER_VIEW_NO_CREATION_CTX](#); SQLSTATE: HY000

Message: View '%s'. '%s' has no creation context

- Error number: 1600; Symbol: [ER_VIEW_INVALID_CREATION_CTX](#); SQLSTATE: HY000

Message: Creation context of view '%s'. '%s' is invalid

- Error number: 1602; Symbol: [ER_TRG_CORRUPTED_FILE](#); SQLSTATE: HY000

Message: Corrupted TRG file for table `%s`.`%s`

- Error number: 1603; Symbol: [ER_TRG_NO_CREATION_CTX](#); SQLSTATE: HY000

Message: Triggers for table `%s`.`%s` have no creation context

- Error number: 1604; Symbol: [ER_TRG_INVALID_CREATION_CTX](#); SQLSTATE: HY000

Message: Trigger creation context of table `%s`.`%s` is invalid

- Error number: 1605; Symbol: [ER_EVENT_INVALID_CREATION_CTX](#); SQLSTATE: HY000

Message: Creation context of event `%s`.`%s` is invalid

- Error number: 1606; Symbol: [ER_TRG_CANT_OPEN_TABLE](#); SQLSTATE: HY000

Message: Cannot open table for trigger `%s`.`%s`

- Error number: 1609; Symbol: [ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT](#); SQLSTATE: HY000

Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.

- Error number: 1610; Symbol: [ER_SLAVE_CORRUPT_EVENT](#); SQLSTATE: HY000

Message: Corrupted replication event was detected

[ER_SLAVE_CORRUPT_EVENT](#) was removed after 8.0.32.

- Error number: 1610; Symbol: [ER_REPLICA_CORRUPT_EVENT](#); SQLSTATE: HY000

Message: Corrupted replication event was detected

[ER_REPLICA_CORRUPT_EVENT](#) was added in 8.0.33.

- Error number: 1612; Symbol: [ER_LOG_PURGE_NO_FILE](#); SQLSTATE: HY000

Message: Being purged log %s was not found

- Error number: 1613; Symbol: [ER_XA_RBTIMEOUT](#); SQLSTATE: XA106

Message: XA_RBTIMEOUT: Transaction branch was rolled back: took too long

- Error number: 1614; Symbol: [ER_XA_RBDEADLOCK](#); SQLSTATE: XA102

Message: XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected

- Error number: 1615; Symbol: [ER_NEED_REPREPARE](#); SQLSTATE: HY000

Message: Prepared statement needs to be re-prepared

- Error number: 1617; Symbol: [WARN_NO_MASTER_INFO](#); SQLSTATE: HY000

Message: The master info structure does not exist

[WARN_NO_MASTER_INFO](#) was removed after 8.0.32.

- Error number: 1617; Symbol: [WARN_NO_CONNECTION_METADATA](#); SQLSTATE: HY000

Message: The connection metadata structure does not exist

[WARN_NO_CONNECTION_METADATA](#) was added in 8.0.33.

-
- Error number: 1618; Symbol: [WARN_OPTION_IGNORED](#); SQLSTATE: HY000
Message: <%s> option ignored
 - Error number: 1619; Symbol: [ER_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: HY000
Message: Built-in plugins cannot be deleted
 - Error number: 1620; Symbol: [WARN_PLUGIN_BUSY](#); SQLSTATE: HY000
Message: Plugin is busy and will be uninstalled on shutdown
 - Error number: 1621; Symbol: [ER_VARIABLE_IS_READONLY](#); SQLSTATE: HY000
Message: %s variable '%s' is read-only. Use SET %s to assign the value
 - Error number: 1622; Symbol: [ER_WARN_ENGINE_TRANSACTION_ROLLBACK](#); SQLSTATE: HY000
Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted
 - Error number: 1624; Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE](#); SQLSTATE: HY000
Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

[ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE](#) was removed after 8.0.32.
 - Error number: 1624; Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE](#); SQLSTATE: HY000
Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

[ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE](#) was added in 8.0.33.
 - Error number: 1625; Symbol: [ER_NDB_REPLICATION_SCHEMA_ERROR](#); SQLSTATE: HY000
Message: Bad schema for mysql.ndb_replication table. Message: %s
 - Error number: 1626; Symbol: [ER_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: HY000
Message: Error in parsing conflict function. Message: %s
 - Error number: 1627; Symbol: [ER_EXCEPTIONS_WRITE_ERROR](#); SQLSTATE: HY000
Message: Write to exceptions table failed. Message: %s
 - Error number: 1628; Symbol: [ER_TOO_LONG_TABLE_COMMENT](#); SQLSTATE: HY000
Message: Comment for table '%s' is too long (max = %lu)
 - Error number: 1629; Symbol: [ER_TOO_LONG_FIELD_COMMENT](#); SQLSTATE: HY000
Message: Comment for field '%s' is too long (max = %lu)
 - Error number: 1630; Symbol: [ER_FUNC_INEXISTENT_NAME_COLLISION](#); SQLSTATE: 42000
Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual
 - Error number: 1631; Symbol: [ER_DATABASE_NAME](#); SQLSTATE: HY000

Message: Database

- Error number: 1632; Symbol: `ER_TABLE_NAME`; SQLSTATE: HY000

Message: Table

- Error number: 1633; Symbol: `ER_PARTITION_NAME`; SQLSTATE: HY000

Message: Partition

- Error number: 1634; Symbol: `ER_SUBPARTITION_NAME`; SQLSTATE: HY000

Message: Subpartition

- Error number: 1635; Symbol: `ER_TEMPORARY_NAME`; SQLSTATE: HY000

Message: Temporary

- Error number: 1636; Symbol: `ER_RENAMED_NAME`; SQLSTATE: HY000

Message: Renamed

- Error number: 1637; Symbol: `ER_TOO_MANY_CONCURRENT_TRXS`; SQLSTATE: HY000

Message: Too many active concurrent transactions

- Error number: 1638; Symbol: `WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED`; SQLSTATE: HY000

Message: Non-ASCII separator arguments are not fully supported

- Error number: 1639; Symbol: `ER_DEBUG_SYNC_TIMEOUT`; SQLSTATE: HY000

Message: debug sync point wait timed out

- Error number: 1640; Symbol: `ER_DEBUG_SYNC_HIT_LIMIT`; SQLSTATE: HY000

Message: debug sync point hit limit reached

- Error number: 1641; Symbol: `ER_DUP_SIGNAL_SET`; SQLSTATE: 42000

Message: Duplicate condition information item '%s'

- Error number: 1642; Symbol: `ER_SIGNAL_WARN`; SQLSTATE: 01000

Message: Unhandled user-defined warning condition

- Error number: 1643; Symbol: `ER_SIGNAL_NOT_FOUND`; SQLSTATE: 02000

Message: Unhandled user-defined not found condition

- Error number: 1644; Symbol: `ER_SIGNAL_EXCEPTION`; SQLSTATE: HY000

Message: Unhandled user-defined exception condition

- Error number: 1645; Symbol: `ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER`; SQLSTATE: 0K000

Message: RESIGNAL when handler not active

- Error number: 1646; Symbol: `ER_SIGNAL_BAD_CONDITION_TYPE`; SQLSTATE: HY000

Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE

- Error number: 1647; Symbol: `WARN_COND_ITEM_TRUNCATED`; SQLSTATE: HY000

Message: Data truncated for condition item '%s'

- Error number: 1648; Symbol: [ER_COND_ITEM_TOO_LONG](#); SQLSTATE: HY000

Message: Data too long for condition item '%s'

- Error number: 1649; Symbol: [ER_UNKNOWN_LOCALE](#); SQLSTATE: HY000

Message: Unknown locale: '%s'

- Error number: 1650; Symbol: [ER_SLAVE_IGNORE_SERVER_IDS](#); SQLSTATE: HY000

Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id

[ER_SLAVE_IGNORE_SERVER_IDS](#) was removed after 8.0.32.

- Error number: 1650; Symbol: [ER_REPLICA_IGNORE_SERVER_IDS](#); SQLSTATE: HY000

Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id

[ER_REPLICA_IGNORE_SERVER_IDS](#) was added in 8.0.33.

- Error number: 1651; Symbol: [ER_QUERY_CACHE_DISABLED](#); SQLSTATE: HY000

Message: Query cache is disabled; restart the server with query_cache_type=1 to enable it

[ER_QUERY_CACHE_DISABLED](#) was removed after 8.0.2.

- Error number: 1652; Symbol: [ER_SAME_NAME_PARTITION_FIELD](#); SQLSTATE: HY000

Message: Duplicate partition field name '%s'

- Error number: 1653; Symbol: [ER_PARTITION_COLUMN_LIST_ERROR](#); SQLSTATE: HY000

Message: Inconsistency in usage of column lists for partitioning

- Error number: 1654; Symbol: [ER_WRONG_TYPE_COLUMN_VALUE_ERROR](#); SQLSTATE: HY000

Message: Partition column values of incorrect type

- Error number: 1655; Symbol: [ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR](#); SQLSTATE: HY000

Message: Too many fields in '%s'

- Error number: 1656; Symbol: [ER_MAXVALUE_IN_VALUES_IN](#); SQLSTATE: HY000

Message: Cannot use MAXVALUE as value in VALUES IN

- Error number: 1657; Symbol: [ER_TOO_MANY_VALUES_ERROR](#); SQLSTATE: HY000

Message: Cannot have more than one value for this type of %s partitioning

- Error number: 1658; Symbol: [ER_ROW_SINGLE_PARTITION_FIELD_ERROR](#); SQLSTATE: HY000

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

- Error number: 1659; Symbol: [ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD](#); SQLSTATE: HY000

Message: Field '%s' is of a not allowed type for this type of partitioning

-
- Error number: 1660; Symbol: [ER_PARTITION_FIELDS_TOO_LONG](#); SQLSTATE: HY000
Message: The total length of the partitioning fields is too large
 - Error number: 1661; Symbol: [ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.
 - Error number: 1662; Symbol: [ER_BINLOG_ROW_MODE_AND_STMT_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.
 - Error number: 1663; Symbol: [ER_BINLOG_UNSAFE_AND_STMT_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s
 - Error number: 1664; Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.
 - Error number: 1665; Symbol: [ER_BINLOG_STMT_MODE_AND_ROW_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s
 - Error number: 1666; Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_MODE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG_FORMAT = STATEMENT.
 - Error number: 1667; Symbol: [ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.
 - Error number: 1668; Symbol: [ER_BINLOG_UNSAFE_LIMIT](#); SQLSTATE: HY000
Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.
 - Error number: 1670; Symbol: [ER_BINLOG_UNSAFE_SYSTEM_TABLE](#); SQLSTATE: HY000
Message: The statement is unsafe because it uses the general log, slow query log, or performance_schema table(s). This is unsafe because system tables may differ on replicas.
 - Error number: 1671; Symbol: [ER_BINLOG_UNSAFE_AUTOINC_COLUMNS](#); SQLSTATE: HY000
Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO_INCREMENT column. Inserted values cannot be logged correctly.
 - Error number: 1672; Symbol: [ER_BINLOG_UNSAFE_UDF](#); SQLSTATE: HY000
Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.
 - Error number: 1673; Symbol: [ER_BINLOG_UNSAFE_SYSTEM_VARIABLE](#); SQLSTATE: HY000

Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.

- Error number: 1674; Symbol: [ER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: HY000

Message: Statement is unsafe because it uses a system function that may return a different value on the replica.

- Error number: 1675; Symbol: [ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS](#); SQLSTATE: HY000

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.

- Error number: 1676; Symbol: [ER_MESSAGE_AND_STATEMENT](#); SQLSTATE: HY000

Message: %s Statement: %s

- Error number: 1677; Symbol: [ER_SLAVE_CONVERSION_FAILED](#); SQLSTATE: HY000

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

[ER_SLAVE_CONVERSION_FAILED](#) was removed after 8.0.4.

- Error number: 1678; Symbol: [ER_SLAVE_CANT_CREATE_CONVERSION](#); SQLSTATE: HY000

Message: Can't create conversion table for table '%s.%s'

[ER_SLAVE_CANT_CREATE_CONVERSION](#) was removed after 8.0.32.

- Error number: 1678; Symbol: [ER_REPLICA_CANT_CREATE_CONVERSION](#); SQLSTATE: HY000

Message: Can't create conversion table for table '%s.%s'

[ER_REPLICA_CANT_CREATE_CONVERSION](#) was added in 8.0.33.

- Error number: 1679; Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Cannot modify @@session.binlog_format inside a transaction

- Error number: 1680; Symbol: [ER_PATH_LENGTH](#); SQLSTATE: HY000

Message: The path specified for %s is too long.

- Error number: 1681; Symbol: [ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release.

- Error number: 1682; Symbol: [ER_WRONG_NATIVE_TABLE_STRUCTURE](#); SQLSTATE: HY000

Message: Native table '%s'.'%s' has the wrong structure

- Error number: 1683; Symbol: [ER_WRONG_PERFSCHEMA_USAGE](#); SQLSTATE: HY000

Message: Invalid performance_schema usage.

- Error number: 1684; Symbol: [ER_WARN_I_S_SKIPPED_TABLE](#); SQLSTATE: HY000

Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement

-
- Error number: 1685; Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)
Message: Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction
 - Error number: 1686; Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)
Message: Cannot change the binlog direct flag inside a stored function or trigger
 - Error number: 1687; Symbol: [ER_SPATIAL_MUST_HAVE_GEOM_COL](#); SQLSTATE: 42000
Message: A SPATIAL index may only contain a geometrical type column
 - Error number: 1688; Symbol: [ER_TOO_LONG_INDEX_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for index '%s' is too long (max = %lu)
 - Error number: 1689; Symbol: [ER_LOCK_ABORTED](#); SQLSTATE: [HY000](#)
Message: Wait on a lock was aborted due to a pending exclusive lock
 - Error number: 1690; Symbol: [ER_DATA_OUT_OF_RANGE](#); SQLSTATE: 22003
Message: %s value is out of range in '%s'
 - Error number: 1691; Symbol: [ER_WRONG_SPVAR_TYPE_IN_LIMIT](#); SQLSTATE: [HY000](#)
Message: A variable of a non-integer based type in LIMIT clause
[ER_WRONG_SPVAR_TYPE_IN_LIMIT](#) was removed after 8.0.21.
 - Error number: 1692; Symbol: [ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: [HY000](#)
Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.
 - Error number: 1693; Symbol: [ER_BINLOG_UNSAFE_MIXED_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.
 - Error number: 1694; Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: [HY000](#)
Message: Cannot modify @@session.sql_log_bin inside a transaction
 - Error number: 1695; Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: [HY000](#)
Message: Cannot change the sql_log_bin inside a stored function or trigger
 - Error number: 1696; Symbol: [ER_FAILED_READ_FROM_PAR_FILE](#); SQLSTATE: [HY000](#)
Message: Failed to read from the .par file
 - Error number: 1697; Symbol: [ER_VALUES_IS_NOT_INT_TYPE_ERROR](#); SQLSTATE: [HY000](#)
Message: VALUES value for partition '%s' must have type INT
 - Error number: 1698; Symbol: [ER_ACCESS_DENIED_NO_PASSWORD_ERROR](#); SQLSTATE: 28000
Message: Access denied for user '%s'@'%s'
 - Error number: 1699; Symbol: [ER_SET_PASSWORD_AUTH_PLUGIN](#); SQLSTATE: [HY000](#)

Message: SET PASSWORD has no significance for users authenticating via plugins

[ER_SET_PASSWORD_AUTH_PLUGIN](#) was removed after 8.0.28.

- Error number: [1701](#); Symbol: [ER_TRUNCATE_ILLEGAL_FK](#); SQLSTATE: [42000](#)

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: [1702](#); Symbol: [ER_PLUGIN_IS_PERMANENT](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is force_plus_permanent and can not be unloaded

- Error number: [1703](#); Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

[ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#) was removed after 8.0.32.

- Error number: [1703](#); Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

[ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#) was added in 8.0.33.

- Error number: [1704](#); Symbol: [ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period exceeds the value of `replica_net_timeout` seconds. A sensible value for the period should be less than the timeout.

[ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#) was removed after 8.0.32.

- Error number: [1704](#); Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period exceeds the value of `replica_net_timeout` seconds. A sensible value for the period should be less than the timeout.

[ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#) was added in 8.0.33.

- Error number: [1705](#); Symbol: [ER_STMT_CACHE_FULL](#); SQLSTATE: [HY000](#)

Message: Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1706](#); Symbol: [ER_MULTI_UPDATE_KEY_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: [1707](#); Symbol: [ER_TABLE_NEEDS_REBUILD](#); SQLSTATE: [HY000](#)

Message: Table rebuild required. Please do "ALTER TABLE `%s` FORCE" or dump/reload to fix it!

- Error number: [1708](#); Symbol: [WARN_OPTION_BELOW_LIMIT](#); SQLSTATE: [HY000](#)

Message: The value of '%s' should be no less than the value of '%s'

- Error number: [1709](#); Symbol: [ER_INDEX_COLUMN_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: 1710; Symbol: [ER_ERROR_IN_TRIGGER_BODY](#); SQLSTATE: HY000

Message: Trigger '%s' has an error in its body: '%s'

- Error number: 1711; Symbol: [ER_ERROR_IN_UNKNOWN_TRIGGER_BODY](#); SQLSTATE: HY000

Message: Unknown trigger has an error in its body: '%s'

- Error number: 1712; Symbol: [ER_INDEX_CORRUPT](#); SQLSTATE: HY000

Message: Index %s is corrupted

- Error number: 1713; Symbol: [ER_UNDO_RECORD_TOO_BIG](#); SQLSTATE: HY000

Message: Undo log record is too big.

- Error number: 1714; Symbol: [ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT](#); SQLSTATE: HY000

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1715; Symbol: [ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE](#); SQLSTATE: HY000

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.

- Error number: 1716; Symbol: [ER_BINLOG_UNSAFE_REPLACE_SELECT](#); SQLSTATE: HY000

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1717; Symbol: [ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT](#); SQLSTATE: HY000

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1718; Symbol: [ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT](#); SQLSTATE: HY000

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1719; Symbol: [ER_BINLOG_UNSAFE_UPDATE_IGNORE](#); SQLSTATE: HY000

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1720; Symbol: [ER_PLUGIN_NO_UNINSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

-
- Error number: 1721; Symbol: [ER_PLUGIN_NO_INSTALL](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
 - Error number: 1722; Symbol: [ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT](#); SQLSTATE: [HY000](#)
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
 - Error number: 1723; Symbol: [ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC](#); SQLSTATE: [HY000](#)
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.
 - Error number: 1724; Symbol: [ER_BINLOG_UNSAFE_INSERT_TWO_KEYS](#); SQLSTATE: [HY000](#)
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
 - Error number: 1725; Symbol: [ER_TABLE_IN_FK_CHECK](#); SQLSTATE: [HY000](#)
Message: Table is being used in foreign key check.
 - Error number: 1726; Symbol: [ER_UNSUPPORTED_ENGINE](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' does not support system tables. [%s.%s]
 - Error number: 1727; Symbol: [ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST](#); SQLSTATE: [HY000](#)
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
 - Error number: 1728; Symbol: [ER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)
Message: Cannot load from %s.%s. The table is probably corrupted
 - Error number: 1729; Symbol: [ER_MASTER_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value %s for the master delay exceeds the maximum %u
[ER_MASTER_DELAY_VALUE_OUT_OF_RANGE](#) was removed after 8.0.32.
 - Error number: 1729; Symbol: [ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value %s for the source delay exceeds the maximum %u
[ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE](#) was added in 8.0.33.
 - Error number: 1730; Symbol: [ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Only Format_description_log_event and row events are allowed in BINLOG statements (but %s was provided)
 - Error number: 1731; Symbol: [ER_PARTITION_EXCHANGE_DIFFERENT_OPTION](#); SQLSTATE: [HY000](#)
Message: Non matching attribute '%s' between partition and table

-
- Error number: 1732; Symbol: [ER_PARTITION_EXCHANGE_PART_TABLE](#); SQLSTATE: HY000
Message: Table to exchange with partition is partitioned: '%s'
 - Error number: 1733; Symbol: [ER_PARTITION_EXCHANGE_TEMP_TABLE](#); SQLSTATE: HY000
Message: Table to exchange with partition is temporary: '%s'
 - Error number: 1734; Symbol: [ER_PARTITION_INSTEAD_OF_SUBPARTITION](#); SQLSTATE: HY000
Message: Subpartitioned table, use subpartition instead of partition
 - Error number: 1735; Symbol: [ER_UNKNOWN_PARTITION](#); SQLSTATE: HY000
Message: Unknown partition '%s' in table '%s'
 - Error number: 1736; Symbol: [ER_TABLES_DIFFERENT_METADATA](#); SQLSTATE: HY000
Message: Tables have different definitions
 - Error number: 1737; Symbol: [ER_ROW_DOES_NOT_MATCH_PARTITION](#); SQLSTATE: HY000
Message: Found a row that does not match the partition
 - Error number: 1738; Symbol: [ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: HY000
Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.
 - Error number: 1739; Symbol: [ER_WARN_INDEX_NOT_APPLICABLE](#); SQLSTATE: HY000
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
 - Error number: 1740; Symbol: [ER_PARTITION_EXCHANGE_FOREIGN_KEY](#); SQLSTATE: HY000
Message: Table to exchange with partition has foreign key references: '%s'
 - Error number: 1742; Symbol: [ER_RPL_INFO_DATA_TOO_LONG](#); SQLSTATE: HY000
Message: Data for column '%s' too long
 - Error number: 1745; Symbol: [ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: HY000
Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.
 - Error number: 1746; Symbol: [ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT](#); SQLSTATE: HY000
Message: Can't update table '%s' while '%s' is being created.
 - Error number: 1747; Symbol: [ER_PARTITION_CLAUSE_ON_NONPARTITIONED](#); SQLSTATE: HY000
Message: PARTITION () clause on non partitioned table
 - Error number: 1748; Symbol: [ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET](#); SQLSTATE: HY000
Message: Found a row not matching the given partition set
 - Error number: 1750; Symbol: [ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE](#); SQLSTATE: HY000

Message: Failure while changing the type of replication repository: %s.

- Error number: 1751; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE](#); SQLSTATE: HY000

Message: The creation of some temporary tables could not be rolled back.

- Error number: 1752; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE](#); SQLSTATE: HY000

Message: Some temporary tables were dropped, but these operations could not be rolled back.

- Error number: 1753; Symbol: [ER_MTS_FEATURE_IS_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: %s is not supported in multi-threaded slave mode. %s

[ER_MTS_FEATURE_IS_NOT_SUPPORTED](#) was removed after 8.0.32.

- Error number: 1753; Symbol: [ER_MTA_FEATURE_IS_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: %s is not supported in multi-threaded replica mode. %s

[ER_MTA_FEATURE_IS_NOT_SUPPORTED](#) was added in 8.0.33.

- Error number: 1754; Symbol: [ER_MTS_UPDATED_DBS_GREATER_MAX](#); SQLSTATE: HY000

Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.

[ER_MTS_UPDATED_DBS_GREATER_MAX](#) was removed after 8.0.32.

- Error number: 1754; Symbol: [ER_MTA_UPDATED_DBS_GREATER_MAX](#); SQLSTATE: HY000

Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.

[ER_MTA_UPDATED_DBS_GREATER_MAX](#) was added in 8.0.33.

- Error number: 1755; Symbol: [ER_MTS_CANT_PARALLEL](#); SQLSTATE: HY000

Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.

[ER_MTS_CANT_PARALLEL](#) was removed after 8.0.32.

- Error number: 1755; Symbol: [ER_MTA_CANT_PARALLEL](#); SQLSTATE: HY000

Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.

[ER_MTA_CANT_PARALLEL](#) was added in 8.0.33.

- Error number: 1756; Symbol: [ER_MTS_INCONSISTENT_DATA](#); SQLSTATE: HY000

Message: %s

[ER_MTS_INCONSISTENT_DATA](#) was removed after 8.0.32.

- Error number: 1756; Symbol: [ER_MTA_INCONSISTENT_DATA](#); SQLSTATE: HY000

Message: %s

[ER_MTA_INCONSISTENT_DATA](#) was added in 8.0.33.

- Error number: [1757](#); Symbol: [ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING](#); SQLSTATE: [HY000](#)

Message: FULLTEXT index is not supported for partitioned tables.

- Error number: [1758](#); Symbol: [ER_DA_INVALID_CONDITION_NUMBER](#); SQLSTATE: [35000](#)

Message: Invalid condition number

- Error number: [1759](#); Symbol: [ER_INSECURE_PLAIN_TEXT](#); SQLSTATE: [HY000](#)

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.

- Error number: [1760](#); Symbol: [ER_INSECURE_CHANGE_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

[ER_INSECURE_CHANGE_MASTER](#) was removed after 8.0.32.

- Error number: [1760](#); Symbol: [ER_INSECURE_CHANGE_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

[ER_INSECURE_CHANGE_SOURCE](#) was added in 8.0.33.

- Error number: [1761](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'

- Error number: [1762](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table

- Error number: [1763](#); Symbol: [ER_SQLTHREAD_WITH_SECURE_SLAVE](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Slave SQL Thread is being started.

[ER_SQLTHREAD_WITH_SECURE_SLAVE](#) was removed after 8.0.32.

- Error number: [1763](#); Symbol: [ER_SQLTHREAD_WITH_SECURE_REPLICA](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.

[ER_SQLTHREAD_WITH_SECURE_REPLICA](#) was added in 8.0.33.

- Error number: [1764](#); Symbol: [ER_TABLE_HAS_NO_FT](#); SQLSTATE: [HY000](#)

Message: The table does not have FULLTEXT index to support this query

-
- Error number: 1765; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER`; SQLSTATE: HY000
Message: The system variable %s cannot be set in stored functions or triggers.
 - Error number: 1766; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION`; SQLSTATE: HY000
Message: The system variable %s cannot be set when there is an ongoing transaction.
 - Error number: 1769; Symbol: `ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION`; SQLSTATE: HY000
Message: The statement 'SET %s' cannot invoke a stored function.
 - Error number: 1770; Symbol: `ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL`; SQLSTATE: HY000
Message: The system variable @@SESSION.GTID_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID_NEXT_LIST is non-NULL.
 - Error number: 1772; Symbol: `ER_MALFORMED_GTID_SET_SPECIFICATION`; SQLSTATE: HY000
Message: Malformed GTID set specification '%s'.
 - Error number: 1773; Symbol: `ER_MALFORMED_GTID_SET_ENCODING`; SQLSTATE: HY000
Message: Malformed GTID set encoding.
 - Error number: 1774; Symbol: `ER_MALFORMED_GTID_SPECIFICATION`; SQLSTATE: HY000
Message: Malformed GTID specification '%s'.
 - Error number: 1775; Symbol: `ER_GNO_EXHAUSTED`; SQLSTATE: HY000
Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server_uuid.
 - Error number: 1776; Symbol: `ER_BAD_SLAVE_AUTO_POSITION`; SQLSTATE: HY000
Message: Parameters MASTER_LOG_FILE, MASTER_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when MASTER_AUTO_POSITION is active.
`ER_BAD_SLAVE_AUTO_POSITION` was removed after 8.0.32.
 - Error number: 1776; Symbol: `ER_BAD_REPLICA_AUTO_POSITION`; SQLSTATE: HY000
Message: Parameters SOURCE_LOG_FILE, SOURCE_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when SOURCE_AUTO_POSITION is active.
`ER_BAD_REPLICA_AUTO_POSITION` was added in 8.0.33.
 - Error number: 1777; Symbol: `ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF`; SQLSTATE: HY000
Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 1 cannot be executed because @@GLOBAL.GTID_MODE = OFF.
 - Error number: 1778; Symbol: `ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET`; SQLSTATE: HY000
Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

-
- Error number: 1779; Symbol: `ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: HY000
Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.
 - Error number: 1781; Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: HY000
Message: @@SESSION.GTID_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID_MODE = OFF.
 - Error number: 1782; Symbol: `ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON`; SQLSTATE: HY000
Message: @@SESSION.GTID_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID_MODE = ON.
 - Error number: 1783; Symbol: `ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: HY000
Message: @@SESSION.GTID_NEXT_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID_MODE = OFF.
 - Error number: 1785; Symbol: `ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE`; SQLSTATE: HY000
Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
 - Error number: 1786; Symbol: `ER_GTID_UNSAFE_CREATE_SELECT`; SQLSTATE: HY000
Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
 - Error number: 1787; Symbol: `ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION`; SQLSTATE: HY000
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

`ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION` was removed after 8.0.12.
 - Error number: 1788; Symbol: `ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME`; SQLSTATE: HY000
Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.
 - Error number: 1789; Symbol: `ER_MASTER_HAS_PURGED_REQUIRED_GTIDS`; SQLSTATE: HY000
Message: Cannot replicate because the master purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s

`ER_MASTER_HAS_PURGED_REQUIRED_GTIDS` was removed after 8.0.32.
 - Error number: 1789; Symbol: `ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS`; SQLSTATE: HY000
-

Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s

[ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS](#) was added in 8.0.33.

- Error number: [1790](#); Symbol: [ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

- Error number: [1791](#); Symbol: [ER_UNKNOWN_EXPLAIN_FORMAT](#); SQLSTATE: [HY000](#)

Message: Unknown EXPLAIN format name: '%s'

- Error number: [1792](#); Symbol: [ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION](#); SQLSTATE: [25006](#)

Message: Cannot execute statement in a READ ONLY transaction.

- Error number: [1793](#); Symbol: [ER_TOO_LONG_TABLE_PARTITION_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for table partition '%s' is too long (max = %lu)

- Error number: [1794](#); Symbol: [ER_SLAVE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.

[ER_SLAVE_CONFIGURATION](#) was removed after 8.0.32.

- Error number: [1794](#); Symbol: [ER_REPLICA_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.

[ER_REPLICA_CONFIGURATION](#) was added in 8.0.33.

- Error number: [1795](#); Symbol: [ER_INNODB_FT_LIMIT](#); SQLSTATE: [HY000](#)

Message: InnoDB presently supports one FULLTEXT index creation at a time

- Error number: [1796](#); Symbol: [ER_INNODB_NO_FT_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create FULLTEXT index on temporary InnoDB table

- Error number: [1797](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index

- Error number: [1798](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_INDEX](#); SQLSTATE: [HY000](#)

Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index

- Error number: [1799](#); Symbol: [ER_INNODB_ONLINE_LOG_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Creating index '%s' required more than 'innodb_online_alter_log_max_size' bytes of modification log. Please try again.

- Error number: [1800](#); Symbol: [ER_UNKNOWN_ALTER_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Unknown ALGORITHM '%s'

-
- Error number: 1801; Symbol: [ER_UNKNOWN_ALTER_LOCK](#); SQLSTATE: HY000
Message: Unknown LOCK type '%s'
 - Error number: 1802; Symbol: [ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS](#); SQLSTATE: HY000
Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.
[ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS](#) was removed after 8.0.32.
 - Error number: 1802; Symbol: [ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS](#); SQLSTATE: HY000
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICA or START REPLICA UNTIL.
[ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS](#) was added in 8.0.33.
 - Error number: 1803; Symbol: [ER_MTS_RECOVERY_FAILURE](#); SQLSTATE: HY000
Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.
[ER_MTS_RECOVERY_FAILURE](#) was removed after 8.0.32.
 - Error number: 1803; Symbol: [ER_MTA_RECOVERY_FAILURE](#); SQLSTATE: HY000
Message: Cannot recover after REPLICA errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.
[ER_MTA_RECOVERY_FAILURE](#) was added in 8.0.33.
 - Error number: 1804; Symbol: [ER_MTS_RESET_WORKERS](#); SQLSTATE: HY000
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.
[ER_MTS_RESET_WORKERS](#) was removed after 8.0.32.
 - Error number: 1804; Symbol: [ER_MTA_RESET_WORKERS](#); SQLSTATE: HY000
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.
[ER_MTA_RESET_WORKERS](#) was added in 8.0.33.
 - Error number: 1805; Symbol: [ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: HY000
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
 - Error number: 1806; Symbol: [ER_SLAVE_SILENT_RETRY_TRANSACTION](#); SQLSTATE: HY000
Message: Slave must silently retry current transaction
[ER_SLAVE_SILENT_RETRY_TRANSACTION](#) was removed after 8.0.32.
 - Error number: 1806; Symbol: [ER_REPLICA_SILENT_RETRY_TRANSACTION](#); SQLSTATE: HY000
Message: Replica must silently retry current transaction

`ER_REPLICA_SILENT_RETRY_TRANSACTION` was added in 8.0.33.

- Error number: `1807`; Symbol: `ER_DISCARD_FK_CHECKS_RUNNING`; SQLSTATE: `HY000`
Message: There is a foreign key check running on table '%s'. Cannot discard the table.
- Error number: `1808`; Symbol: `ER_TABLE_SCHEMA_MISMATCH`; SQLSTATE: `HY000`
Message: Schema mismatch (%s)
- Error number: `1809`; Symbol: `ER_TABLE_IN_SYSTEM_TABLESPACE`; SQLSTATE: `HY000`
Message: Table '%s' in system tablespace
- Error number: `1810`; Symbol: `ER_IO_READ_ERROR`; SQLSTATE: `HY000`
Message: IO Read error: (%lu, %s) %s
- Error number: `1811`; Symbol: `ER_IO_WRITE_ERROR`; SQLSTATE: `HY000`
Message: IO Write error: (%lu, %s) %s
- Error number: `1812`; Symbol: `ER_TABLESPACE_MISSING`; SQLSTATE: `HY000`
Message: Tablespace is missing for table %s.
- Error number: `1813`; Symbol: `ER_TABLESPACE_EXISTS`; SQLSTATE: `HY000`
Message: Tablespace '%s' exists.
- Error number: `1814`; Symbol: `ER_TABLESPACE_DISCARDED`; SQLSTATE: `HY000`
Message: Tablespace has been discarded for table '%s'
- Error number: `1815`; Symbol: `ER_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: Internal error: %s
- Error number: `1816`; Symbol: `ER_INNODEB_IMPORT_ERROR`; SQLSTATE: `HY000`
Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'
- Error number: `1817`; Symbol: `ER_INNODEB_INDEX_CORRUPT`; SQLSTATE: `HY000`
Message: Index corrupt: %s
- Error number: `1818`; Symbol: `ER_INVALID_YEAR_COLUMN_LENGTH`; SQLSTATE: `HY000`
Message: Invalid display width. Use YEAR instead.
- Error number: `1819`; Symbol: `ER_NOT_VALID_PASSWORD`; SQLSTATE: `HY000`
Message: Your password does not satisfy the current policy requirements
- Error number: `1820`; Symbol: `ER_MUST_CHANGE_PASSWORD`; SQLSTATE: `HY000`
Message: You must reset your password using ALTER USER statement before executing this statement.
- Error number: `1821`; Symbol: `ER_FK_NO_INDEX_CHILD`; SQLSTATE: `HY000`
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'

-
- Error number: [1822](#); Symbol: [ER_FK_NO_INDEX_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'
 - Error number: [1823](#); Symbol: [ER_FK_FAIL_ADD_SYSTEM](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint '%s' to system tables
 - Error number: [1824](#); Symbol: [ER_FK_CANNOT_OPEN_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to open the referenced table '%s'
 - Error number: [1825](#); Symbol: [ER_FK_INCORRECT_OPTION](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'
 - Error number: [1826](#); Symbol: [ER_FK_DUP_NAME](#); SQLSTATE: [HY000](#)
Message: Duplicate foreign key constraint name '%s'
 - Error number: [1827](#); Symbol: [ER_PASSWORD_FORMAT](#); SQLSTATE: [HY000](#)
Message: The password hash doesn't have the expected format.
 - Error number: [1828](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s'
 - Error number: [1829](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'
 - Error number: [1830](#); Symbol: [ER_FK_COLUMN_NOT_NULL](#); SQLSTATE: [HY000](#)
Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL
 - Error number: [1831](#); Symbol: [ER_DUP_INDEX](#); SQLSTATE: [HY000](#)
Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.
 - Error number: [1832](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s'
 - Error number: [1833](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
 - Error number: [1835](#); Symbol: [ER_MALFORMED_PACKET](#); SQLSTATE: [HY000](#)
Message: Malformed communication packet.
 - Error number: [1836](#); Symbol: [ER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Running in read-only mode
 - Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GROUP](#); SQLSTATE: [HY000](#)
Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.

`ER_GTID_NEXT_TYPE_UNDEFINED_GROUP` was removed after 8.0.4.

- Error number: 1837; Symbol: `ER_GTID_NEXT_TYPE_UNDEFINED_GTID`; SQLSTATE: HY000

Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.

`ER_GTID_NEXT_TYPE_UNDEFINED_GTID` was added in 8.0.11.

- Error number: 1838; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_SP`; SQLSTATE: HY000

Message: The system variable %s cannot be set in stored procedures.

- Error number: 1840; Symbol: `ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY`; SQLSTATE: HY000

Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.

- Error number: 1841; Symbol: `ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY`; SQLSTATE: HY000

Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).

- Error number: 1842; Symbol: `ER_GTID_PURGED_WAS_CHANGED`; SQLSTATE: HY000

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

- Error number: 1843; Symbol: `ER_GTID_EXECUTED_WAS_CHANGED`; SQLSTATE: HY000

Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.

- Error number: 1844; Symbol: `ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES`; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.

- Error number: 1845; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED`; SQLSTATE: 0A000

Message: %s is not supported for this operation. Try %s.

- Error number: 1846; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON`; SQLSTATE: 0A000

Message: %s is not supported. Reason: %s. Try %s.

- Error number: 1847; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY`; SQLSTATE: HY000

Message: COPY algorithm requires a lock

- Error number: 1848; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION`; SQLSTATE: HY000

Message: Partition specific operations do not yet support LOCK/ALGORITHM

- Error number: 1849; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME`; SQLSTATE: HY000

Message: Columns participating in a foreign key are renamed

-
- Error number: 1850; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE`; SQLSTATE: `HY000`
Message: Cannot change column type INPLACE
 - Error number: 1851; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK`; SQLSTATE: `HY000`
Message: Adding foreign keys needs foreign_key_checks=OFF
 - Error number: 1853; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK`; SQLSTATE: `HY000`
Message: Dropping a primary key is not allowed without also adding a new primary key
 - Error number: 1854; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC`; SQLSTATE: `HY000`
Message: Adding an auto-increment column requires a lock
 - Error number: 1855; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS`; SQLSTATE: `HY000`
Message: Cannot replace hidden FTS_DOC_ID with a user-visible one
 - Error number: 1856; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS`; SQLSTATE: `HY000`
Message: Cannot drop or rename FTS_DOC_ID
 - Error number: 1857; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS`; SQLSTATE: `HY000`
Message: Fulltext index creation requires a lock
 - Error number: 1858; Symbol: `ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE`; SQLSTATE: `HY000`
Message: sql_slave_skip_counter can not be set when the server is running with @@GLOBAL.GTID_MODE = ON. Instead, for each transaction that you want to skip, generate an empty transaction with the same GTID as the transaction
`ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE` was removed after 8.0.22.
 - Error number: 1859; Symbol: `ER_DUP_UNKNOWN_IN_INDEX`; SQLSTATE: `23000`
Message: Duplicate entry for key '%s'
 - Error number: 1860; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH`; SQLSTATE: `HY000`
Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.
 - Error number: 1861; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL`; SQLSTATE: `HY000`
Message: cannot silently convert NULL values, as required in this SQL_MODE
 - Error number: 1862; Symbol: `ER_MUST_CHANGE_PASSWORD_LOGIN`; SQLSTATE: `HY000`
Message: Your password has expired. To log in you must change it using a client that supports expired passwords.
 - Error number: 1863; Symbol: `ER_ROW_IN_WRONG_PARTITION`; SQLSTATE: `HY000`

Message: Found a row in wrong partition %s

- Error number: 1864; Symbol: `ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX`; SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica_pending_jobs_size_max.

`ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX` was removed after 8.0.32.

- Error number: 1864; Symbol: `ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX`; SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica_pending_jobs_size_max.

`ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX` was added in 8.0.33.

- Error number: 1866; Symbol: `ER_BINLOG_LOGICAL_CORRUPTION`; SQLSTATE: HY000

Message: The binary log file '%s' is logically corrupted: %s

- Error number: 1867; Symbol: `ER_WARN_PURGE_LOG_IN_USE`; SQLSTATE: HY000

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: 1868; Symbol: `ER_WARN_PURGE_LOG_IS_ACTIVE`; SQLSTATE: HY000

Message: file %s was not purged because it is the active log file.

- Error number: 1869; Symbol: `ER_AUTO_INCREMENT_CONFLICT`; SQLSTATE: HY000

Message: Auto-increment value in UPDATE conflicts with internally generated values

- Error number: 1870; Symbol: `WARN_ON_BLOCKHOLE_IN_RBR`; SQLSTATE: HY000

Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'

- Error number: 1871; Symbol: `ER_SLAVE_MI_INIT_REPOSITORY`; SQLSTATE: HY000

Message: Slave failed to initialize master info structure from the repository

`ER_SLAVE_MI_INIT_REPOSITORY` was removed after 8.0.32.

- Error number: 1871; Symbol: `ER_REPLICA_CM_INIT_REPOSITORY`; SQLSTATE: HY000

Message: Replica failed to initialize connection metadata structure from the repository

`ER_REPLICA_CM_INIT_REPOSITORY` was added in 8.0.33.

- Error number: 1872; Symbol: `ER_SLAVE_RLI_INIT_REPOSITORY`; SQLSTATE: HY000

Message: Slave failed to initialize relay log info structure from the repository

`ER_SLAVE_RLI_INIT_REPOSITORY` was removed after 8.0.32.

- Error number: 1872; Symbol: `ER_REPLICA_AM_INIT_REPOSITORY`; SQLSTATE: HY000

Message: Replica failed to initialize applier metadata structure from the repository

`ER_REPLICA_AM_INIT_REPOSITORY` was added in 8.0.33.

-
- Error number: 1873; Symbol: `ER_ACCESS_DENIED_CHANGE_USER_ERROR`; SQLSTATE: 28000
Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
 - Error number: 1874; Symbol: `ER_INNODB_READ_ONLY`; SQLSTATE: HY000
Message: InnoDB is in read only mode.
 - Error number: 1875; Symbol: `ER_STOP_SLAVE_SQL_THREAD_TIMEOUT`; SQLSTATE: HY000
Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
`ER_STOP_SLAVE_SQL_THREAD_TIMEOUT` was removed after 8.0.32.
 - Error number: 1875; Symbol: `ER_STOP_REPLICA_SQL_THREAD_TIMEOUT`; SQLSTATE: HY000
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
`ER_STOP_REPLICA_SQL_THREAD_TIMEOUT` was added in 8.0.33.
 - Error number: 1876; Symbol: `ER_STOP_SLAVE_IO_THREAD_TIMEOUT`; SQLSTATE: HY000
Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
`ER_STOP_SLAVE_IO_THREAD_TIMEOUT` was removed after 8.0.32.
 - Error number: 1876; Symbol: `ER_STOP_REPLICA_IO_THREAD_TIMEOUT`; SQLSTATE: HY000
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
`ER_STOP_REPLICA_IO_THREAD_TIMEOUT` was added in 8.0.33.
 - Error number: 1877; Symbol: `ER_TABLE_CORRUPT`; SQLSTATE: HY000
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
 - Error number: 1878; Symbol: `ER_TEMP_FILE_WRITE_FAILURE`; SQLSTATE: HY000
Message: Temporary file write failure.
 - Error number: 1879; Symbol: `ER_INNODB_FT_AUX_NOT_HEX_ID`; SQLSTATE: HY000
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
 - Error number: 1880; Symbol: `ER_OLD_TEMPORALS_UPGRADED`; SQLSTATE: HY000
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
 - Error number: 1881; Symbol: `ER_INNODB_FORCED_RECOVERY`; SQLSTATE: HY000
Message: Operation not allowed when innodb_force_recovery > 0.
 - Error number: 1882; Symbol: `ER_AES_INVALID_IV`; SQLSTATE: HY000
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
 - Error number: 1883; Symbol: `ER_PLUGIN_CANNOT_BE_UNINSTALLED`; SQLSTATE: HY000

Message: Plugin '%s' cannot be uninstalled now. %s

- Error number: 1884; Symbol: [ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP](#); SQLSTATE: HY000

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

[ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP](#) was removed after 8.0.4.

- Error number: 1884; Symbol: [ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#); SQLSTATE: HY000

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

[ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#) was added in 8.0.11.

- Error number: 1885; Symbol: [ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER](#); SQLSTATE: HY000

Message: Slave has more GTIDs than the master has, using the master's SERVER_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID_EXECUTED.

[ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER](#) was removed after 8.0.32.

- Error number: 1885; Symbol: [ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE](#); SQLSTATE: HY000

Message: Replica has more GTIDs than the source has, using the source's SERVER_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID_EXECUTED.

[ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE](#) was added in 8.0.33.

- Error number: 1886; Symbol: [ER_MISSING_KEY](#); SQLSTATE: HY000

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

[ER_MISSING_KEY](#) was added in 8.0.4.

- Error number: 1887; Symbol: [WARN_NAMED_PIPE_ACCESS_EVERYONE](#); SQLSTATE: HY000

Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.

[WARN_NAMED_PIPE_ACCESS_EVERYONE](#) was added in 8.0.17.

- Error number: 3000; Symbol: [ER_FILE_CORRUPT](#); SQLSTATE: HY000

Message: File %s is corrupted

-
- Error number: 3001; Symbol: [ER_ERROR_ON_MASTER](#); SQLSTATE: HY000

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL_REPLICA_SKIP_COUNTER=1; START SLAVE;. Query: '%s'

[ER_ERROR_ON_MASTER](#) was removed after 8.0.32.

- Error number: 3001; Symbol: [ER_ERROR_ON_SOURCE](#); SQLSTATE: HY000

Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL_REPLICA_SKIP_COUNTER=1; START REPLICA;. Query: '%s'

[ER_ERROR_ON_SOURCE](#) was added in 8.0.33.

- Error number: 3003; Symbol: [ER_STORAGE_ENGINE_NOT_LOADED](#); SQLSTATE: HY000

Message: Storage engine for table '%s'. '%s' is not loaded.

- Error number: 3004; Symbol: [ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: 0Z002

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: 3005; Symbol: [ER_WARN_LEGACY_SYNTAX_CONVERTED](#); SQLSTATE: HY000

Message: %s is no longer supported. The statement was converted to %s.

- Error number: 3006; Symbol: [ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN](#); SQLSTATE: HY000

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.

- Error number: 3007; Symbol: [ER_CANNOT_DISCARD_TEMPORARY_TABLE](#); SQLSTATE: HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: [ER_FK_DEPTH_EXCEEDED](#); SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: [ER_COL_COUNT_DoesNT_MATCH_PLEASE_UPDATE_V2](#); SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: [ER_WARN_TRIGGER_DOESNT_HAVE_CREATED](#); SQLSTATE: HY000

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: 3011; Symbol: [ER_REFERENCED_TRG_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: 3012; Symbol: [ER_EXPLAIN_NOT_SUPPORTED](#); SQLSTATE: HY000

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: 3013; Symbol: [ER_INVALID_FIELD_SIZE](#); SQLSTATE: HY000

Message: Invalid size for column '%s'.

- Error number: 3014; Symbol: [ER_MISSING_HA_CREATE_OPTION](#); SQLSTATE: HY000

Message: Table storage engine '%s' found required create option missing

- Error number: 3015; Symbol: [ER_ENGINE_OUT_OF_MEMORY](#); SQLSTATE: HY000

Message: Out of memory in storage engine '%s'.

- Error number: 3016; Symbol: [ER_PASSWORD_EXPIRE_ANONYMOUS_USER](#); SQLSTATE: HY000

Message: The password for anonymous user cannot be expired.

- Error number: 3017; Symbol: [ER_SLAVE_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD first

[ER_SLAVE_SQL_THREAD_MUST_STOP](#) was removed after 8.0.32.

- Error number: 3017; Symbol: [ER_REPLICA_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD first

[ER_REPLICA_SQL_THREAD_MUST_STOP](#) was added in 8.0.33.

- Error number: 3018; Symbol: [ER_NO_FT_MATERIALIZED_SUBQUERY](#); SQLSTATE: HY000

Message: Cannot create FULLTEXT index on materialized subquery

- Error number: 3019; Symbol: [ER_INNODB_UNDO_LOG_FULL](#); SQLSTATE: HY000

Message: Undo Log error: %s

- Error number: 3020; Symbol: [ER_INVALID_ARGUMENT_FOR_LOGARITHM](#); SQLSTATE: 2201E

Message: Invalid argument for logarithm

- Error number: 3021; Symbol: [ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO_THREAD FOR CHANNEL '%s' first.

[ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP](#) was removed after 8.0.32.

- Error number: 3021; Symbol: [ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running replica io thread; run STOP REPLICA IO_THREAD FOR CHANNEL '%s' first.

[ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP](#) was added in 8.0.33.

- Error number: 3022; Symbol: [ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO](#); SQLSTATE: HY000

Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until replica_open_temp_tables = 0.

- Error number: 3023; Symbol: [ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS](#); SQLSTATE: HY000

Message: CHANGE MASTER TO with a MASTER_LOG_FILE clause but no MASTER_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.

[ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS](#) was removed after 8.0.32.

- Error number: 3023; Symbol: [ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO with a SOURCE_LOG_FILE clause but no SOURCE_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.

[ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS](#) was added in 8.0.33.

- Error number: 3024; Symbol: [ER_QUERY_TIMEOUT](#); SQLSTATE: HY000

Message: Query execution was interrupted, maximum statement execution time exceeded

- Error number: 3025; Symbol: [ER_NON_RO_SELECT_DISABLE_TIMER](#); SQLSTATE: HY000

Message: Select is not a read only statement, disabling timer

- Error number: 3026; Symbol: [ER_DUP_LIST_ENTRY](#); SQLSTATE: HY000

Message: Duplicate entry '%s'.

- Error number: 3028; Symbol: [ERAggregate_order_for_union](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

- Error number: 3029; Symbol: [ERAggregate_order_non_agg_query](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

- Error number: 3030; Symbol: [ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR](#); SQLSTATE: HY000

Message: Slave worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well.

[ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR](#) was removed after 8.0.32.

- Error number: 3030; Symbol: [ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR](#); SQLSTATE: HY000

Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.

[ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR](#) was added in 8.0.33.

- Error number: 3031; Symbol: [ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER](#); SQLSTATE: HY000

Message: slave_preserve_commit_order is not supported %s.

[ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER](#) was removed after 8.0.25.

-
- Error number: 3031; Symbol: `ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER`; SQLSTATE: `HY000`
Message: replica_preserve_commit_order is not supported %s.
`ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER` was added in 8.0.26.
 - Error number: 3032; Symbol: `ER_SERVER_OFFLINE_MODE`; SQLSTATE: `HY000`
Message: The server is currently in offline mode
 - Error number: 3033; Symbol: `ER_GIS_DIFFERENT_SRIDS`; SQLSTATE: `HY000`
Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.
Geometry values passed as arguments to spatial functions must have the same SRID value.
 - Error number: 3034; Symbol: `ER_GIS_UNSUPPORTED_ARGUMENT`; SQLSTATE: `HY000`
Message: Calling geometry function %s with unsupported types of arguments.
A spatial function was called with a combination of argument types that the function does not support.
 - Error number: 3035; Symbol: `ER_GIS_UNKNOWN_ERROR`; SQLSTATE: `HY000`
Message: Unknown GIS error occurred in function %s.
 - Error number: 3036; Symbol: `ER_GIS_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`
Message: Unknown exception caught in GIS function %s.
 - Error number: 3037; Symbol: `ER_GIS_INVALID_DATA`; SQLSTATE: `22023`
Message: Invalid GIS data provided to function %s.
A spatial function was called with an argument not recognized as a valid geometry value.
 - Error number: 3038; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`
Message: The geometry has no data in function %s.
 - Error number: 3039; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`
Message: Unable to calculate centroid because geometry is empty in function %s.
 - Error number: 3040; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`
Message: Geometry overlay calculation error: geometry data is invalid in function %s.
 - Error number: 3041; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`
Message: Geometry turn info calculation error: geometry data is invalid in function %s.
 - Error number: 3042; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`
Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.
 - Error number: 3043; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`

Message: Unknown exception thrown in function %s.

- Error number: 3044; Symbol: [ER_STD_BAD_ALLOC_ERROR](#); SQLSTATE: HY000

Message: Memory allocation error: %s in function %s.

- Error number: 3045; Symbol: [ER_STD_DOMAIN_ERROR](#); SQLSTATE: HY000

Message: Domain error: %s in function %s.

- Error number: 3046; Symbol: [ER_STD_LENGTH_ERROR](#); SQLSTATE: HY000

Message: Length error: %s in function %s.

- Error number: 3047; Symbol: [ER_STD_INVALID_ARGUMENT](#); SQLSTATE: HY000

Message: Invalid argument error: %s in function %s.

- Error number: 3048; Symbol: [ER_STD_OUT_OF_RANGE_ERROR](#); SQLSTATE: HY000

Message: Out of range error: %s in function %s.

- Error number: 3049; Symbol: [ER_STD_OVERFLOW_ERROR](#); SQLSTATE: HY000

Message: Overflow error: %s in function %s.

- Error number: 3050; Symbol: [ER_STD_RANGE_ERROR](#); SQLSTATE: HY000

Message: Range error: %s in function %s.

- Error number: 3051; Symbol: [ER_STD_UNDERFLOW_ERROR](#); SQLSTATE: HY000

Message: Underflow error: %s in function %s.

- Error number: 3052; Symbol: [ER_STD_LOGIC_ERROR](#); SQLSTATE: HY000

Message: Logic error: %s in function %s.

- Error number: 3053; Symbol: [ER_STD_RUNTIME_ERROR](#); SQLSTATE: HY000

Message: Runtime error: %s in function %s.

- Error number: 3054; Symbol: [ER_STD_UNKNOWN_EXCEPTION](#); SQLSTATE: HY000

Message: Unknown exception: %s in function %s.

- Error number: 3055; Symbol: [ER_GIS_DATA_WRONG_ENDIANESS](#); SQLSTATE: HY000

Message: Geometry byte string must be little endian.

- Error number: 3056; Symbol: [ER_CHANGE_MASTER_PASSWORD_LENGTH](#); SQLSTATE: HY000

Message: The password provided for the replication user exceeds the maximum length of 32 characters

[ER_CHANGE_MASTER_PASSWORD_LENGTH](#) was removed after 8.0.32.

- Error number: 3056; Symbol: [ER_CHANGE_SOURCE_PASSWORD_LENGTH](#); SQLSTATE: HY000

Message: The password provided for the replication user exceeds the maximum length of 32 characters

[ER_CHANGE_SOURCE_PASSWORD_LENGTH](#) was added in 8.0.33.

-
- Error number: 3057; Symbol: [ER_USER_LOCK_WRONG_NAME](#); SQLSTATE: 42000
Message: Incorrect user-level lock name '%s'. The name is empty, NULL, or can not be expressed in the current character-set.
 - Error number: 3058; Symbol: [ER_USER_LOCK_DEADLOCK](#); SQLSTATE: HY000
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with [GET_LOCK](#).
 - Error number: 3059; Symbol: [ER_REPLACE_INACCESSIBLE_ROWS](#); SQLSTATE: HY000
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
 - Error number: 3060; Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS](#); SQLSTATE: HY000
Message: Do not support online operation on table with GIS index
 - Error number: 3061; Symbol: [ER_ILLEGAL_USER_VAR](#); SQLSTATE: 42000
Message: User variable name '%s' is illegal
 - Error number: 3062; Symbol: [ER_GTID_MODE_OFF](#); SQLSTATE: HY000
Message: Cannot %s when GTID_MODE = OFF.
 - Error number: 3064; Symbol: [ER_INCORRECT_TYPE](#); SQLSTATE: HY000
Message: Incorrect type for argument %s in function %s.
 - Error number: 3065; Symbol: [ER_FIELD_IN_ORDER_NOT_SELECT](#); SQLSTATE: HY000
Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
 - Error number: 3066; Symbol: [ERAggregate_IN_ORDER_NOT_SELECT](#); SQLSTATE: HY000
Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
 - Error number: 3067; Symbol: [ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN](#); SQLSTATE: HY000
Message: Supplied filter list contains a value which is not in the required format 'db_pattern.table_pattern'
 - Error number: 3068; Symbol: [ER_NET_OK_PACKET_TOO_LARGE](#); SQLSTATE: 08S01
Message: OK packet too large
 - Error number: 3069; Symbol: [ER_INVALID_JSON_DATA](#); SQLSTATE: HY000
Message: Invalid JSON data provided to function %s: %s
 - Error number: 3070; Symbol: [ER_INVALID_GEOJSON_MISSING_MEMBER](#); SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
 - Error number: 3071; Symbol: [ER_INVALID_GEOJSON_WRONG_TYPE](#); SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'

- Error number: 3072; Symbol: `ER_INVALID_GEOJSON_UNSPECIFIED`; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s

- Error number: 3073; Symbol: `ER_DIMENSION_UNSUPPORTED`; SQLSTATE: HY000

Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u

- Error number: 3074; Symbol: `ER_SLAVE_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Slave channel '%s' does not exist.

`ER_SLAVE_CHANNEL_DOES_NOT_EXIST` was removed after 8.0.32.

- Error number: 3074; Symbol: `ER_REPLICA_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Replica channel '%s' does not exist.

`ER_REPLICA_CHANNEL_DOES_NOT_EXIST` was added in 8.0.33.

- Error number: 3076; Symbol: `ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: HY000

Message: Couldn't create channel: Channel name is either invalid or too long.

`ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG` was removed after 8.0.32.

- Error number: 3076; Symbol: `ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: HY000

Message: Couldn't create channel: Channel name is either invalid or too long.

`ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG` was added in 8.0.33.

- Error number: 3077; Symbol: `ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: HY000

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.

`ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY` was removed after 8.0.32.

- Error number: 3077; Symbol: `ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: HY000

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.

`ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY` was added in 8.0.33.

- Error number: 3079; Symbol: `ER_SLAVE_MULTIPLE_CHANNELS_CMD`; SQLSTATE: HY000

Message: Multiple channels exist on the slave. Please provide channel name as an argument.

`ER_SLAVE_MULTIPLE_CHANNELS_CMD` was removed after 8.0.32.

- Error number: 3079; Symbol: `ER_REPLICA_MULTIPLE_CHANNELS_CMD`; SQLSTATE: HY000

Message: Multiple channels exist on the replica. Please provide channel name as an argument.

`ER_REPLICA_MULTIPLE_CHANNELS_CMD` was added in 8.0.33.

-
- Error number: 3080; Symbol: [ER_SLAVE_MAX_CHANNELS_EXCEEDED](#); SQLSTATE: HY000
Message: Maximum number of replication channels allowed exceeded.
[ER_SLAVE_MAX_CHANNELS_EXCEEDED](#) was removed after 8.0.32.
 - Error number: 3080; Symbol: [ER_REPLICA_MAX_CHANNELS_EXCEEDED](#); SQLSTATE: HY000
Message: Maximum number of replication channels allowed exceeded.
[ER_REPLICA_MAX_CHANNELS_EXCEEDED](#) was added in 8.0.33.
 - Error number: 3081; Symbol: [ER_SLAVE_CHANNEL_MUST_STOP](#); SQLSTATE: HY000
Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first
[ER_SLAVE_CHANNEL_MUST_STOP](#) was removed after 8.0.32.
 - Error number: 3081; Symbol: [ER_REPLICA_CHANNEL_MUST_STOP](#); SQLSTATE: HY000
Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL '%s' first
[ER_REPLICA_CHANNEL_MUST_STOP](#) was added in 8.0.33.
 - Error number: 3082; Symbol: [ER_SLAVE_CHANNEL_NOT_RUNNING](#); SQLSTATE: HY000
Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'
[ER_SLAVE_CHANNEL_NOT_RUNNING](#) was removed after 8.0.32.
 - Error number: 3082; Symbol: [ER_REPLICA_CHANNEL_NOT_RUNNING](#); SQLSTATE: HY000
Message: This operation requires running replication threads; configure replica and run START REPLICA FOR CHANNEL '%s'
[ER_REPLICA_CHANNEL_NOT_RUNNING](#) was added in 8.0.33.
 - Error number: 3083; Symbol: [ER_SLAVE_CHANNEL_WAS_RUNNING](#); SQLSTATE: HY000
Message: Replication thread(s) for channel '%s' are already running.
[ER_SLAVE_CHANNEL_WAS_RUNNING](#) was removed after 8.0.32.
 - Error number: 3083; Symbol: [ER_REPLICA_CHANNEL_WAS_RUNNING](#); SQLSTATE: HY000
Message: Replication thread(s) for channel '%s' are already running.
[ER_REPLICA_CHANNEL_WAS_RUNNING](#) was added in 8.0.33.
 - Error number: 3084; Symbol: [ER_SLAVE_CHANNEL_WAS_NOT_RUNNING](#); SQLSTATE: HY000
Message: Replication thread(s) for channel '%s' are already stopped.
[ER_SLAVE_CHANNEL_WAS_NOT_RUNNING](#) was removed after 8.0.32.
 - Error number: 3084; Symbol: [ER_REPLICA_CHANNEL_WAS_NOT_RUNNING](#); SQLSTATE: HY000
Message: Replication thread(s) for channel '%s' are already stopped.
[ER_REPLICA_CHANNEL_WAS_NOT_RUNNING](#) was added in 8.0.33.

-
- Error number: 3085; Symbol: [ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD FOR CHANNEL '%s' first.

[ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP](#) was removed after 8.0.32.
 - Error number: 3085; Symbol: [ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD FOR CHANNEL '%s' first.

[ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP](#) was added in 8.0.33.
 - Error number: 3086; Symbol: [ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER](#); SQLSTATE: HY000

Message: When sql_replica_skip_counter > 0, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL_THREAD]'. Value of sql_replica_skip_counter can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql_replica_skip_counter.

[ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER](#) was removed after 8.0.32.
 - Error number: 3086; Symbol: [ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER](#); SQLSTATE: HY000

Message: When sql_replica_skip_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICA [SQL_THREAD]'. Value of sql_replica_skip_counter can only be used by one SQL thread at a time. Please use 'START REPLICA [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql_replica_skip_counter.

[ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER](#) was added in 8.0.33.
 - Error number: 3087; Symbol: [ER_WRONG_FIELD_WITH_GROUP_V2](#); SQLSTATE: HY000

Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql_mode=only_full_group_by
 - Error number: 3088; Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2](#); SQLSTATE: HY000

Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql_mode=only_full_group_by
 - Error number: 3089; Symbol: [ER_WARN_DEPRECATED_SYSVAR_UPDATE](#); SQLSTATE: HY000

Message: Updating '%s' is deprecated. It will be made read-only in a future release.
 - Error number: 3090; Symbol: [ER_WARN_DEPRECATED_SQLMODE](#); SQLSTATE: HY000

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.
 - Error number: 3091; Symbol: [ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID](#); SQLSTATE: HY000

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID_NEXT='%s'; (3) DROP DATABASE '%s'.
 - Error number: 3092; Symbol: [ER_GROUP_REPLICATION_CONFIGURATION](#); SQLSTATE: HY000

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

- Error number: 3093; Symbol: `ER_GROUP_REPLICATION_RUNNING`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed since the group is already running.

- Error number: 3094; Symbol: `ER_GROUP_REPLICATION_APPLIER_INIT_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.

- Error number: 3095; Symbol: `ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

- Error number: 3096; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.

- Error number: 3097; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.

- Error number: 3098; Symbol: `ER_BEFORE_DML_VALIDATION_ERROR`; SQLSTATE: `HY000`

Message: The table does not comply with the requirements by an external plugin.

- Error number: 3099; Symbol: `ER_PREVENTS_VARIABLE_WITHOUT_RBR`; SQLSTATE: `HY000`

Message: Cannot change the value of variable %s without binary log format as ROW.

`transaction_write_set_extraction` option value is set and `binlog_format` is not ROW.

- Error number: 3100; Symbol: `ER_RUN_HOOK_ERROR`; SQLSTATE: `HY000`

Message: Error on observer while running replication hook '%s'.

- Error number: 3101; Symbol: `ER_TRANSACTION_ROLLBACK_DURING_COMMIT`; SQLSTATE: `40000`

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).

- Error number: 3102; Symbol: `ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Expression of generated column '%s' contains a disallowed function.

- Error number: 3103; Symbol: `ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN`; SQLSTATE: `HY000`

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

-
- Error number: 3104; Symbol: `ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN`; SQLSTATE: HY000
Message: Cannot define foreign key with %s clause on a generated column.
 - Error number: 3105; Symbol: `ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN`; SQLSTATE: HY000
Message: The value specified for generated column '%s' in table '%s' is not allowed.
 - Error number: 3106; Symbol: `ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN`; SQLSTATE: HY000
Message: '%s' is not supported for generated columns.
 - Error number: 3107; Symbol: `ER_GENERATED_COLUMN_NON_PRIOR`; SQLSTATE: HY000
Message: Generated column can refer only to generated columns defined prior to it.
To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.
 - Error number: 3108; Symbol: `ER_DEPENDENT_BY_GENERATED_COLUMN`; SQLSTATE: HY000
Message: Column '%s' has a generated column dependency.
You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.
 - Error number: 3109; Symbol: `ER_GENERATED_COLUMN_REF_AUTO_INC`; SQLSTATE: HY000
Message: Generated column '%s' cannot refer to auto-increment column.
 - Error number: 3110; Symbol: `ER_FEATURE_NOT_AVAILABLE`; SQLSTATE: HY000
Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'
 - Error number: 3111; Symbol: `ER_CANT_SET_GTID_MODE`; SQLSTATE: HY000
Message: SET @@GLOBAL.GTID_MODE = %s is not allowed because %s.
 - Error number: 3112; Symbol: `ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF`; SQLSTATE: HY000
Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID_MODE = OFF.
 - Error number: 3116; Symbol: `ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX`; SQLSTATE: HY000
Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.
`ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was renamed to `ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX`.
 - Error number: 3117; Symbol: `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`; SQLSTATE: HY000
Message: There are ongoing transactions that violate GTID consistency.
-

`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS`
was renamed to
`ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX`.

- Error number: 3118; Symbol: `ER_ACCOUNT_HAS_BEEN_LOCKED`; SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is locked.

The account was locked with `CREATE USER ... ACCOUNT LOCK` or `ALTER USER ... ACCOUNT LOCK`. An administrator can unlock it with `ALTER USER ... ACCOUNT UNLOCK`.

- Error number: 3119; Symbol: `ER_WRONG_TABLESPACE_NAME`; SQLSTATE: 42000

Message: Incorrect tablespace name '%s'

- Error number: 3120; Symbol: `ER_TABLESPACE_IS_NOT_EMPTY`; SQLSTATE: HY000

Message: Tablespace '%s' is not empty.

- Error number: 3121; Symbol: `ER_WRONG_FILE_NAME`; SQLSTATE: HY000

Message: Incorrect File Name '%s'.

- Error number: 3122; Symbol: `ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION`; SQLSTATE: HY000

Message: Inconsistent intersection points.

- Error number: 3123; Symbol: `ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR`; SQLSTATE: HY000

Message: Optimizer hint syntax error

- Error number: 3124; Symbol: `ER_WARN_BAD_MAX_EXECUTION_TIME`; SQLSTATE: HY000

Message: Unsupported MAX_EXECUTION_TIME

- Error number: 3125; Symbol: `ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME`; SQLSTATE: HY000

Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements only

The `MAX_EXECUTION_TIME` optimizer hint is supported only for `SELECT` statements.

- Error number: 3126; Symbol: `ER_WARN_CONFLICTING_HINT`; SQLSTATE: HY000

Message: Hint %s is ignored as conflicting/duplicated

- Error number: 3127; Symbol: `ER_WARN_UNKNOWN_QB_NAME`; SQLSTATE: HY000

Message: Query block name %s is not found for %s hint

- Error number: 3128; Symbol: `ER_UNRESOLVED_HINT_NAME`; SQLSTATE: HY000

Message: Unresolved name %s for %s hint

- Error number: 3129; Symbol: `ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE`; SQLSTATE: HY000

Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.

-
- Error number: 3130; Symbol: `ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Command not supported by pluggable protocols
 - Error number: 3131; Symbol: `ER_LOCKING_SERVICE_WRONG_NAME`; SQLSTATE: 42000

Message: Incorrect locking service lock name '%s'.

A locking service name was specified as `NULL`, the empty string, or a string longer than 64 characters. Namespace and lock names must be non-`NULL`, nonempty, and no more than 64 characters long.
 - Error number: 3132; Symbol: `ER_LOCKING_SERVICE_DEADLOCK`; SQLSTATE: `HY000`

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.
 - Error number: 3133; Symbol: `ER_LOCKING_SERVICE_TIMEOUT`; SQLSTATE: `HY000`

Message: Service lock wait timeout exceeded.
 - Error number: 3134; Symbol: `ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED`; SQLSTATE: `HY000`

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.
 - Error number: 3135; Symbol: `ER_SQL_MODE_MERGED`; SQLSTATE: `HY000`

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.
 - Error number: 3136; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_MISMATCH`; SQLSTATE: `HY000`

Message: Version token mismatch for %.*s. Correct value %.*s

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).
 - Error number: 3137; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND`; SQLSTATE: `HY000`

Message: Version token %.*s not found.

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).
 - Error number: 3138; Symbol: `ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID`; SQLSTATE: `HY000`

Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
 - Error number: 3139; Symbol: `ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: %s cannot be performed on channel '%s'.

`ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED` was removed after 8.0.32.
 - Error number: 3139; Symbol: `ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED`; SQLSTATE: `HY000`
-

Message: %s cannot be performed on channel '%s'.

[ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED](#) was added in 8.0.33.

- Error number: [3140](#); Symbol: [ER_INVALID_JSON_TEXT](#); SQLSTATE: [22032](#)

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

- Error number: [3141](#); Symbol: [ER_INVALID_JSON_TEXT_IN_PARAM](#); SQLSTATE: [22032](#)

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

- Error number: [3142](#); Symbol: [ER_INVALID_JSON_BINARY_DATA](#); SQLSTATE: [HY000](#)

Message: The JSON binary value contains invalid data.

- Error number: [3143](#); Symbol: [ER_INVALID_JSON_PATH](#); SQLSTATE: [42000](#)

Message: Invalid JSON path expression. The error is around character position %u.%s

- Error number: [3144](#); Symbol: [ER_INVALID_JSON_CHARSET](#); SQLSTATE: [22032](#)

Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

- Error number: [3145](#); Symbol: [ER_INVALID_JSON_CHARSET_IN_FUNCTION](#); SQLSTATE: [22032](#)

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

- Error number: [3146](#); Symbol: [ER_INVALID_TYPE_FOR_JSON](#); SQLSTATE: [22032](#)

Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

- Error number: [3147](#); Symbol: [ER_INVALID_CAST_TO_JSON](#); SQLSTATE: [22032](#)

Message: Cannot CAST value to JSON.

- Error number: [3148](#); Symbol: [ER_INVALID_JSON_PATH_CHARSET](#); SQLSTATE: [42000](#)

Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.

- Error number: [3149](#); Symbol: [ER_INVALID_JSON_PATH_WILDCARD](#); SQLSTATE: [42000](#)

Message: In this situation, path expressions may not contain the * and ** tokens or an array range.

- Error number: [3150](#); Symbol: [ER_JSON_VALUE_TOO_BIG](#); SQLSTATE: [22032](#)

Message: The JSON value is too big to be stored in a JSON column.

- Error number: [3151](#); Symbol: [ER_JSON_KEY_TOO_BIG](#); SQLSTATE: [22032](#)

Message: The JSON object contains a key name that is too long.

- Error number: [3152](#); Symbol: [ER_JSON_USED_AS_KEY](#); SQLSTATE: [42000](#)

Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.

- Error number: [3153](#); Symbol: [ER_JSON_VACUOUS_PATH](#); SQLSTATE: [42000](#)

Message: The path expression '\$' is not allowed in this context.

- Error number: [3154](#); Symbol: [ER_JSON_BAD_ONE_OR_ALL_ARG](#); SQLSTATE: [42000](#)

Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.

- Error number: 3155; Symbol: `ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE`; SQLSTATE: 22003

Message: Out of range JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3156; Symbol: `ER_INVALID_JSON_VALUE_FOR_CAST`; SQLSTATE: 22018

Message: Invalid JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3157; Symbol: `ER_JSON_DOCUMENT_TOO_DEEP`; SQLSTATE: 22032

Message: The JSON document exceeds the maximum depth.

- Error number: 3158; Symbol: `ER_JSON_DOCUMENT_NULL_KEY`; SQLSTATE: 22032

Message: JSON documents may not contain NULL member names.

- Error number: 3159; Symbol: `ER_SECURE_TRANSPORT_REQUIRED`; SQLSTATE: HY000

Message: Connections using insecure transport are prohibited while --require_secure_transport=ON.

With the `require_secure_transport` system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.

- Error number: 3160; Symbol: `ER_NO_SECURE_TRANSPORTS_CONFIGURED`; SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require_secure_transport=ON.

The `require_secure_transport` system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the `shared_memory` system variable to enable shared-memory connections.

- Error number: 3161; Symbol: `ER_DISABLED_STORAGE_ENGINE`; SQLSTATE: HY000

Message: Storage engine %s is disabled (Table creation is disallowed).

An attempt was made to create a table or tablespace using a storage engine listed in the value of the `disabled_storage_engines` system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.

- Error number: 3162; Symbol: `ER_USER_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Authorization ID %s does not exist.

- Error number: 3163; Symbol: `ER_USER_ALREADY_EXISTS`; SQLSTATE: HY000

Message: Authorization ID %s already exists.

- Error number: 3164; Symbol: `ER_AUDIT_API_ABORT`; SQLSTATE: HY000

Message: Aborted by Audit API ('%s';%d).

This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.

- Error number: 3165; Symbol: `ER_INVALID_JSON_PATH_ARRAY_CELL`; SQLSTATE: 42000

Message: A path expression is not a path to a cell in an array.

- Error number: 3166; Symbol: `ER_BUFPOOL_RESIZE_INPROGRESS`; SQLSTATE: HY000

Message: Another buffer pool resize is already in progress.

- Error number: 3167; Symbol: [ER_FEATURE_DISABLED_SEE_DOC](#); SQLSTATE: HY000

Message: The '%s' feature is disabled; see the documentation for '%s'

- Error number: 3168; Symbol: [ER_SERVER_ISNT_AVAILABLE](#); SQLSTATE: HY000

Message: Server isn't available

- Error number: 3169; Symbol: [ER_SESSION_WAS_KILLED](#); SQLSTATE: HY000

Message: Session was killed

- Error number: 3170; Symbol: [ER_CAPACITY_EXCEEDED](#); SQLSTATE: HY000

Message: Memory capacity of %llu bytes for '%s' exceeded. %s

- Error number: 3171; Symbol: [ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER](#); SQLSTATE: HY000

Message: Range optimization was not done for this query.

- Error number: 3173; Symbol: [ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID](#); SQLSTATE: HY000

Message: The client holds ownership of the GTID %s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.

- Error number: 3174; Symbol: [ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL](#); SQLSTATE: HY000

Message: Cannot add foreign key on the base column of indexed virtual column.

- Error number: 3175; Symbol: [ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT](#); SQLSTATE: HY000

Message: Cannot create index on virtual column whose base column has foreign constraint.

- Error number: 3176; Symbol: [ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: HY000

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.

- Error number: 3177; Symbol: [ER_LOCK_REFUSED_BY_ENGINE](#); SQLSTATE: HY000

Message: Lock acquisition refused by storage engine.

- Error number: 3178; Symbol: [ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN](#); SQLSTATE: HY000

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)

- Error number: 3179; Symbol: [ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE](#); SQLSTATE: HY000

Message: Master key rotation is not supported by storage engine.

- Error number: 3181; Symbol: [ER_MASTER_KEY_ROTATION_BINLOG_FAILED](#); SQLSTATE: HY000

Message: Write to binlog failed. However, master key rotation has been completed successfully.

-
- Error number: 3182; Symbol: `ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE`; SQLSTATE: HY000
Message: Storage engine is not available.
 - Error number: 3183; Symbol: `ER_TABLESPACE_CANNOT_ENCRYPT`; SQLSTATE: HY000
Message: This tablespace can't be encrypted.
 - Error number: 3184; Symbol: `ER_INVALID_ENCRYPTION_OPTION`; SQLSTATE: HY000
Message: Invalid encryption option.
 - Error number: 3185; Symbol: `ER_CANNOT_FIND_KEY_IN_KEYRING`; SQLSTATE: HY000
Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
 - Error number: 3186; Symbol: `ER_CAPACITY_EXCEEDED_IN_PARSER`; SQLSTATE: HY000
Message: Parser bailed out for this query.
 - Error number: 3187; Symbol: `ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE`; SQLSTATE: HY000
Message: Cannot alter encryption attribute by inplace algorithm.
 - Error number: 3188; Symbol: `ER_KEYRING_UDF_KEYRING_SERVICE_ERROR`; SQLSTATE: HY000
Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.
 - Error number: 3189; Symbol: `ER_USER_COLUMN_OLD_LENGTH`; SQLSTATE: HY000
Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.
 - Error number: 3190; Symbol: `ER_CANT_RESET_MASTER`; SQLSTATE: HY000
Message: RESET MASTER is not allowed because %s.
`ER_CANT_RESET_MASTER` was removed after 8.0.32.
 - Error number: 3190; Symbol: `ER_CANT_RESET_SOURCE`; SQLSTATE: HY000
Message: RESET SOURCE is not allowed because %s.
`ER_CANT_RESET_SOURCE` was added in 8.0.33.
 - Error number: 3191; Symbol: `ER_GROUP_REPLICATION_MAX_GROUP_SIZE`; SQLSTATE: HY000
Message: The START GROUP_REPLICATION command failed since the group already has 9 members.
 - Error number: 3192; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED`; SQLSTATE: HY000
Message: Cannot add foreign key on the base column of stored column.
 - Error number: 3193; Symbol: `ER_TABLE_REFERENCED`; SQLSTATE: HY000
Message: Cannot complete the operation because table is referenced by another connection.
 - Error number: 3197; Symbol: `ER_XA_RETRY`; SQLSTATE: HY000

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

[ER_XA_RETRY](#) was added in 8.0.2.

- Error number: 3198; Symbol: [ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#); SQLSTATE: HY000

Message: Function %s failed due to: %s.

[ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#) was added in 8.0.2.

- Error number: 3199; Symbol: [ER_BINLOG_UNSAFE_XA](#); SQLSTATE: HY000

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.

[ER_BINLOG_UNSAFE_XA](#) was added in 8.0.2.

- Error number: 3200; Symbol: [ER_UDF_ERROR](#); SQLSTATE: HY000

Message: %s UDF failed; %s

[ER_UDF_ERROR](#) was added in 8.0.4.

- Error number: 3201; Symbol: [ER_KEYRING_MIGRATION_FAILURE](#); SQLSTATE: HY000

Message: Can not perform keyring migration : %s

[ER_KEYRING_MIGRATION_FAILURE](#) was added in 8.0.4.

- Error number: 3202; Symbol: [ER_KEYRING_ACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

[ER_KEYRING_ACCESS_DENIED_ERROR](#) was added in 8.0.4.

- Error number: 3203; Symbol: [ER_KEYRING_MIGRATION_STATUS](#); SQLSTATE: HY000

Message: Keyring migration %s.

[ER_KEYRING_MIGRATION_STATUS](#) was added in 8.0.4.

- Error number: 3218; Symbol:

[ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE](#); SQLSTATE: HY000

Message: Invalid "max_array_length" argument value.

[ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE](#) was added in 8.0.11.

- Error number: 3231; Symbol: [ER_WRITE_SET_EXCEEDS_LIMIT](#); SQLSTATE: HY000

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group_replication_transaction_size_limit'.

[ER_WRITE_SET_EXCEEDS_LIMIT](#) was added in 8.0.23.

- Error number: 3235; Symbol: [ER_AES_INVALID_KDF_NAME](#); SQLSTATE: HY000

Message: KDF method name is not valid. Please use hkdf or pbkdf2_hmac method name

[ER_AES_INVALID_KDF_NAME](#) was added in 8.0.30.

- Error number: 3236; Symbol: [ER_AES_INVALID_KDF_ITERATIONS](#); SQLSTATE: HY000

Message: For KDF method pbkdf2_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

[ER_AES_INVALID_KDF_ITERATIONS](#) was added in 8.0.30.

- Error number: [3237](#); Symbol: [WARN_AES_KEY_SIZE](#); SQLSTATE: [HY000](#)

Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2_hmac should be used, please provide exact AES key size or use KDF methods for better security.

[WARN_AES_KEY_SIZE](#) was added in 8.0.30.

- Error number: [3238](#); Symbol: [ER_AES_INVALID_KDF_OPTION_SIZE](#); SQLSTATE: [HY000](#)

Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL

[ER_AES_INVALID_KDF_OPTION_SIZE](#) was added in 8.0.30.

- Error number: [3500](#); Symbol: [ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE](#); SQLSTATE: [HY000](#)

Message: CREATE TEMPORARY TABLE is not allowed with ROW_FORMAT=COMPRESSED or KEY_BLOCK_SIZE.

- Error number: [3501](#); Symbol: [ER_ACL_OPERATION_FAILED](#); SQLSTATE: [HY000](#)

Message: The ACL operation failed due to the following error from SE: errcode %d - %s

- Error number: [3502](#); Symbol: [ER_UNSUPPORTED_INDEX_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

- Error number: [3503](#); Symbol: [ER_NO_SUCH_DB](#); SQLSTATE: [42Y07](#)

Message: Database '%s' doesn't exist

- Error number: [3504](#); Symbol: [ER_TOO_BIG_ENUM](#); SQLSTATE: [HY000](#)

Message: Too many enumeration values for column %s.

- Error number: [3505](#); Symbol: [ER_TOO_LONG_SET_ENUM_VALUE](#); SQLSTATE: [HY000](#)

Message: Too long enumeration/set value for column %s.

- Error number: [3506](#); Symbol: [ER_INVALID_DD_OBJECT](#); SQLSTATE: [HY000](#)

Message: %s dictionary object is invalid. (%s)

- Error number: [3507](#); Symbol: [ER_UPDATING_DD_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to update %s dictionary object.

- Error number: [3508](#); Symbol: [ER_INVALID_DD_OBJECT_ID](#); SQLSTATE: [HY000](#)

Message: Dictionary object id (%lu) does not exist.

- Error number: [3509](#); Symbol: [ER_INVALID_DD_OBJECT_NAME](#); SQLSTATE: [HY000](#)

Message: Dictionary object name '%s' is invalid. (%s)

- Error number: [3510](#); Symbol: [ER_TABLESPACE_MISSING_WITH_NAME](#); SQLSTATE: [HY000](#)

Message: Tablespace %s doesn't exist.

- Error number: 3511; Symbol: [ER_TOO_LONG_ROUTINE_COMMENT](#); SQLSTATE: HY000

Message: Comment for routine '%s' is too long (max = %lu)

- Error number: 3512; Symbol: [ER_SP_LOAD_FAILED](#); SQLSTATE: HY000

Message: Failed to load routine '%s'.

- Error number: 3513; Symbol: [ER_INVALID_BITWISE_OPERANDS_SIZE](#); SQLSTATE: HY000

Message: Binary operands of bitwise operators must be of equal length

- Error number: 3514; Symbol: [ER_INVALID_BITWISEAggregate_OPERANDS_SIZE](#); SQLSTATE: HY000

Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function

- Error number: 3515; Symbol: [ER_WARN_UNSUPPORTED_HINT](#); SQLSTATE: HY000

Message: Hints aren't supported in %s

- Error number: 3516; Symbol: [ER_UNEXPECTED_GEOMETRY_TYPE](#); SQLSTATE: 22S01

Message: %s value is a geometry of unexpected type %s in %s.

- Error number: 3517; Symbol: [ER_SRS_PARSE_ERROR](#); SQLSTATE: SR002

Message: Can't parse the spatial reference system definition of SRID %u.

- Error number: 3518; Symbol: [ER_SRS_PROJ_PARAMETER_MISSING](#); SQLSTATE: SR003

Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.

- Error number: 3519; Symbol: [ER_WARN_SRS_NOT_FOUND](#); SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u.

- Error number: 3520; Symbol: [ER_SRS_NOT_CARTESIAN](#); SQLSTATE: 22S00

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.

- Error number: 3521; Symbol: [ER_SRS_NOT_CARTESIAN_UNDEFINED](#); SQLSTATE: SR001

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.

- Error number: 3522; Symbol: [ER_PK_INDEX_CANT_BE_INVISIBLE](#); SQLSTATE: HY000

Message: A primary key index cannot be invisible

- Error number: 3523; Symbol: [ER_UNKNOWN_AUTHID](#); SQLSTATE: HY000

Message: Unknown authorization ID `%s`@`%s`

- Error number: 3524; Symbol: [ER_FAILED_ROLE_GRANT](#); SQLSTATE: HY000

Message: Failed to grant %s` to %s

-
- Error number: 3525; Symbol: [ER_OPEN_ROLE_TABLES](#); SQLSTATE: HY000
Message: Failed to open the security system tables
 - Error number: 3526; Symbol: [ER_FAILED_DEFAULT_ROLES](#); SQLSTATE: HY000
Message: Failed to set default roles
 - Error number: 3527; Symbol: [ER_COMPONENTS_NO_SCHEME](#); SQLSTATE: HY000
Message: Cannot find schema in specified URN: '%s'.
 - Error number: 3528; Symbol: [ER_COMPONENTS_NO_SCHEME_SERVICE](#); SQLSTATE: HY000
Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.
 - Error number: 3529; Symbol: [ER_COMPONENTS_CANT_LOAD](#); SQLSTATE: HY000
Message: Cannot load component from specified URN: '%s'.
 - Error number: 3530; Symbol: [ER_ROLE_NOT_GRANTED](#); SQLSTATE: HY000
Message: '%s'@'%s' is not granted to '%s'@'%s'
 - Error number: 3531; Symbol: [ER_FAILED_REVOKE_ROLE](#); SQLSTATE: HY000
Message: Could not revoke role from '%s'@'%s'
 - Error number: 3532; Symbol: [ER_RENAME_ROLE](#); SQLSTATE: HY000
Message: Renaming of a role identifier is forbidden
 - Error number: 3533; Symbol: [ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: HY000
Message: Cannot acquire specified service implementation: '%s'.
 - Error number: 3534; Symbol: [ER_COMPONENTS_CANT_SATISFY_DEPENDENCY](#); SQLSTATE: HY000
Message: Cannot satisfy dependency for service '%s' required by component '%s'.
 - Error number: 3535; Symbol: [ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION](#); SQLSTATE: HY000
Message: Cannot register service implementation '%s' provided by component '%s'.
 - Error number: 3536; Symbol: [ER_COMPONENTS_LOAD_CANT_INITIALIZE](#); SQLSTATE: HY000
Message: Initialization method provided by component '%s' failed.
 - Error number: 3537; Symbol: [ER_COMPONENTS_UNLOAD_NOT_LOADED](#); SQLSTATE: HY000
Message: Component specified by URN '%s' to unload has not been loaded before.
 - Error number: 3538; Symbol: [ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE](#); SQLSTATE: HY000
Message: De-initialization method provided by component '%s' failed.
 - Error number: 3539; Symbol: [ER_COMPONENTS_CANT_RELEASE_SERVICE](#); SQLSTATE: HY000
Message: Release of previously acquired service implementation failed.

-
- Error number: 3540; Symbol: `ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE`; SQLSTATE: `HY000`
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
 - Error number: 3541; Symbol: `ER_COMPONENTS_CANT_UNLOAD`; SQLSTATE: `HY000`
Message: Cannot unload component from specified URN: '%s'.
 - Error number: 3542; Symbol: `ER_WARN_UNLOAD_THE_NOT_PERSISTED`; SQLSTATE: `HY000`
Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.
 - Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: `HY000`
Message: The mysql.component table is missing or has an incorrect definition.
 - Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: `HY000`
Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.
 - Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: `HY000`
Message: The component with specified URN: '%s' was specified in group more than once.
 - Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: `HY000`
Message: @@GLOBAL.GTID_PURGED cannot be changed: %s
 - Error number: 3547; Symbol: `ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES`; SQLSTATE: `HY000`
Message: Can not lock user management caches for processing.
 - Error number: 3548; Symbol: `ER_SRS_NOT_FOUND`; SQLSTATE: `SR001`
Message: There's no spatial reference system with SRID %u.
 - Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: `HY000`
Message: Variables cannot be persisted. Please retry.
 - Error number: 3550; Symbol: `ER_IS_QUERY_INVALID_CLAUSE`; SQLSTATE: `HY000`
Message: Information schema queries do not support the '%s' clause.
 - Error number: 3551; Symbol: `ER_UNABLE_TO_STORE_STATISTICS`; SQLSTATE: `HY000`
Message: Unable to store dynamic %s statistics into data dictionary.
 - Error number: 3552; Symbol: `ER_NO_SYSTEM_SCHEMA_ACCESS`; SQLSTATE: `HY000`
Message: Access to system schema '%s' is rejected.
 - Error number: 3553; Symbol: `ER_NO_SYSTEM_TABLESPACE_ACCESS`; SQLSTATE: `HY000`
Message: Access to system tablespace '%s' is rejected.
 - Error number: 3554; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`

Message: Access to %s '%s.%s' is rejected.

- Error number: 3555; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE](#); SQLSTATE: HY000

Message: data dictionary table

[ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE](#) was added in 8.0.1.

- Error number: 3556; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE](#); SQLSTATE: HY000

Message: system table

[ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE](#) was added in 8.0.1.

- Error number: 3557; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE](#); SQLSTATE: HY000

Message: table

[ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE](#) was added in 8.0.1.

- Error number: 3558; Symbol: [ER_INVALID_OPTION_KEY](#); SQLSTATE: 22023

Message: Invalid option key '%s' in function %s.

[ER_INVALID_OPTION_KEY](#) was added in 8.0.1.

- Error number: 3559; Symbol: [ER_INVALID_OPTION_VALUE](#); SQLSTATE: 22023

Message: Invalid value '%s' for option '%s' in function '%s'.

[ER_INVALID_OPTION_VALUE](#) was added in 8.0.1.

- Error number: 3560; Symbol: [ER_INVALID_OPTION_KEY_VALUE_PAIR](#); SQLSTATE: 22023

Message: The string '%s' is not a valid key %c value pair in function %s.

[ER_INVALID_OPTION_KEY_VALUE_PAIR](#) was added in 8.0.1.

- Error number: 3561; Symbol: [ER_INVALID_OPTION_START_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s starts with the invalid character '%c'.

[ER_INVALID_OPTION_START_CHARACTER](#) was added in 8.0.1.

- Error number: 3562; Symbol: [ER_INVALID_OPTION_END_CHARACTER](#); SQLSTATE: 22023

Message: The options argument in function %s ends with the invalid character '%c'.

[ER_INVALID_OPTION_END_CHARACTER](#) was added in 8.0.1.

- Error number: 3563; Symbol: [ER_INVALID_OPTION_CHARACTERS](#); SQLSTATE: 22023

Message: The options argument in function %s contains the invalid character sequence '%s'.

[ER_INVALID_OPTION_CHARACTERS](#) was added in 8.0.1.

- Error number: 3564; Symbol: [ER_DUPLICATE_OPTION_KEY](#); SQLSTATE: 22023

Message: Duplicate option key '%s' in function '%s'.

[ER_DUPLICATE_OPTION_KEY](#) was added in 8.0.1.

-
- Error number: 3565; Symbol: `ER_WARN_SRS_NOT_FOUND_AXIS_ORDER`; SQLSTATE: 01000
Message: There's no spatial reference system with SRID %u. The axis order is unknown.
`ER_WARN_SRS_NOT_FOUND_AXIS_ORDER` was added in 8.0.1.
 - Error number: 3566; Symbol: `ER_NO_ACCESS_TO_NATIVE_FCT`; SQLSTATE: HY000
Message: Access to native function '%s' is rejected.
`ER_NO_ACCESS_TO_NATIVE_FCT` was added in 8.0.1.
 - Error number: 3567; Symbol: `ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000
Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.
`ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE` was added in 8.0.1, removed after 8.0.32.
 - Error number: 3567; Symbol: `ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000
Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.
`ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE` was added in 8.0.33.
 - Error number: 3568; Symbol: `ER_UNRESOLVED_TABLE_LOCK`; SQLSTATE: HY000
Message: Unresolved table name %s in locking clause.
`ER_UNRESOLVED_TABLE_LOCK` was added in 8.0.1.
 - Error number: 3569; Symbol: `ER_DUPLICATE_TABLE_LOCK`; SQLSTATE: HY000
Message: Table %s appears in multiple locking clauses.
`ER_DUPLICATE_TABLE_LOCK` was added in 8.0.1.
 - Error number: 3570; Symbol: `ER_BINLOG_UNSAFE_SKIP_LOCKED`; SQLSTATE: HY000
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.
`ER_BINLOG_UNSAFE_SKIP_LOCKED` was added in 8.0.1.
 - Error number: 3571; Symbol: `ER_BINLOG_UNSAFE_NOWAIT`; SQLSTATE: HY000
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.
`ER_BINLOG_UNSAFE_NOWAIT` was added in 8.0.1.
 - Error number: 3572; Symbol: `ER_LOCK_NOWAIT`; SQLSTATE: HY000
Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.
`ER_LOCK_NOWAIT` was added in 8.0.1.
 - Error number: 3573; Symbol: `ER_CTE_RECURSIVE_REQUIRES_UNION`; SQLSTATE: HY000
Message: Recursive Common Table Expression '%s' should contain a UNION

`ER_CTE_RECURSIVE_REQUIRES_UNION` was added in 8.0.1.

- Error number: 3574; Symbol: `ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST`; SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones

`ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST` was added in 8.0.1.

- Error number: 3575; Symbol: `ER_CTE_RECURSIVE_FORBIDS_AGGREGATION`; SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block

`ER_CTE_RECURSIVE_FORBIDS_AGGREGATION` was added in 8.0.1.

- Error number: 3576; Symbol: `ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER`; SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints

`ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER` was added in 8.0.1.

- Error number: 3577; Symbol: `ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE`; SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery

`ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE` was added in 8.0.1.

- Error number: 3578; Symbol: `ER_SWITCH_TMP_ENGINE`; SQLSTATE: HY000

Message: '%s' requires @@internal_tmp_disk_storage_engine=InnoDB

`ER_SWITCH_TMP_ENGINE` was added in 8.0.1.

- Error number: 3579; Symbol: `ER_WINDOW_NO_SUCH_WINDOW`; SQLSTATE: HY000

Message: Window name '%s' is not defined.

`ER_WINDOW_NO_SUCH_WINDOW` was added in 8.0.2.

- Error number: 3580; Symbol: `ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH`; SQLSTATE: HY000

Message: There is a circularity in the window dependency graph.

`ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH` was added in 8.0.2.

- Error number: 3581; Symbol: `ER_WINDOW_NO_CHILD_PARTITIONING`; SQLSTATE: HY000

Message: A window which depends on another cannot define partitioning.

`ER_WINDOW_NO_CHILD_PARTITIONING` was added in 8.0.2.

- Error number: 3582; Symbol: `ER_WINDOW_NO_INHERIT_FRAME`; SQLSTATE: HY000

Message: Window '%s' has a frame definition, so cannot be referenced by another window.

`ER_WINDOW_NO_INHERIT_FRAME` was added in 8.0.2.

- Error number: 3583; Symbol: `ER_WINDOW_NO_REDEFINE_ORDER_BY`; SQLSTATE: HY000

Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.

`ER_WINDOW_NO_REDEFINE_ORDER_BY` was added in 8.0.2.

- Error number: 3584; Symbol: `ER_WINDOW_FRAME_START_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.

`ER_WINDOW_FRAME_START_ILLEGAL` was added in 8.0.2.

- Error number: 3585; Symbol: `ER_WINDOW_FRAME_END_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.

`ER_WINDOW_FRAME_END_ILLEGAL` was added in 8.0.2.

- Error number: 3586; Symbol: `ER_WINDOW_FRAME_ILLEGAL`; SQLSTATE: HY000

Message: Window '%s': frame start or end is negative, NULL or of non-integral type

`ER_WINDOW_FRAME_ILLEGAL` was added in 8.0.2.

- Error number: 3587; Symbol: `ER_WINDOW_RANGE_FRAME_ORDER_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type

`ER_WINDOW_RANGE_FRAME_ORDER_TYPE` was added in 8.0.2.

- Error number: 3588; Symbol: `ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.

`ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE` was added in 8.0.2.

- Error number: 3589; Symbol: `ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE`; SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

`ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE` was added in 8.0.2.

- Error number: 3590; Symbol: `ER_WINDOW_RANGE_BOUND_NOT_CONSTANT`; SQLSTATE: HY000

Message: Window '%s' has a non-constant frame bound.

`ER_WINDOW_RANGE_BOUND_NOT_CONSTANT` was added in 8.0.2.

- Error number: 3591; Symbol: `ER_WINDOW_DUPLICATE_NAME`; SQLSTATE: HY000

Message: Window '%s' is defined twice.

`ER_WINDOW_DUPLICATE_NAME` was added in 8.0.2.

- Error number: 3592; Symbol: `ER_WINDOW_ILLEGAL_ORDER_BY`; SQLSTATE: HY000

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.

`ER_WINDOW_ILLEGAL_ORDER_BY` was added in 8.0.2.

- Error number: 3593; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_USE`; SQLSTATE: HY000

Message: You cannot use the window function '%s' in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_USE` was added in 8.0.2.

- Error number: 3594; Symbol: `ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE`; SQLSTATE: HY000

Message: You cannot use the alias '%s' of an expression containing a window function in this context.'

`ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE` was added in 8.0.2.

- Error number: 3595; Symbol: `ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC`; SQLSTATE: HY000

Message: You cannot nest a window function in the specification of window '%s'.

`ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC` was added in 8.0.2.

- Error number: 3596; Symbol: `ER_WINDOW_ROWS_INTERVAL_USE`; SQLSTATE: HY000

Message: Window '%s': INTERVAL can only be used with RANGE frames.

`ER_WINDOW_ROWS_INTERVAL_USE` was added in 8.0.2.

- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER`; SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

`ER_WINDOW_NO_GROUP_ORDER` was added in 8.0.2, removed after 8.0.12.

- Error number: 3597; Symbol: `ER_WINDOW_NO_GROUP_ORDER_UNUSED`; SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

`ER_WINDOW_NO_GROUP_ORDER_UNUSED` was added in 8.0.13.

- Error number: 3598; Symbol: `ER_WINDOW_EXPLAIN_JSON`; SQLSTATE: HY000

Message: To get information about window functions use EXPLAIN FORMAT=JSON

`ER_WINDOW_EXPLAIN_JSON` was added in 8.0.2.

- Error number: 3599; Symbol: `ER_WINDOW_FUNCTION_IGNORES_FRAME`; SQLSTATE: HY000

Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition

`ER_WINDOW_FUNCTION_IGNORES_FRAME` was added in 8.0.2.

- Error number: 3600; Symbol: `ER_WINDOW_SE_NOT_ACCEPTABLE`; SQLSTATE: HY000

Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.

`ER_WINDOW_SE_NOT_ACCEPTABLE` was added in 8.0.2, removed after 8.0.3.

- Error number: 3600; Symbol: `ER_WL9236_NOW_UNUSED`; SQLSTATE: HY000

Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.

[ER_WL9236_NOW_UNUSED](#) was added in 8.0.4.

- Error number: 3601; Symbol: [ER_INVALID_NO_OF_ARGS](#); SQLSTATE: HY000

Message: Too many arguments for function %s: %lu; maximum allowed is %s.

[ER_INVALID_NO_OF_ARGS](#) was added in 8.0.1.

- Error number: 3602; Symbol: [ER_FIELD_IN_GROUPING_NOT_GROUP_BY](#); SQLSTATE: HY000

Message: Argument #%u of GROUPING function is not in GROUP BY

[ER_FIELD_IN_GROUPING_NOT_GROUP_BY](#) was added in 8.0.1.

- Error number: 3603; Symbol: [ER_TOO_LONG_TABLESPACE_COMMENT](#); SQLSTATE: HY000

Message: Comment for tablespace '%s' is too long (max = %lu)

[ER_TOO_LONG_TABLESPACE_COMMENT](#) was added in 8.0.1.

- Error number: 3604; Symbol: [ER_ENGINE_CANT_DROP_TABLE](#); SQLSTATE: HY000

Message: Storage engine can't drop table '%s'

[ER_ENGINE_CANT_DROP_TABLE](#) was added in 8.0.1.

- Error number: 3605; Symbol: [ER_ENGINE_CANT_DROP_MISSING_TABLE](#); SQLSTATE: HY000

Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.

[ER_ENGINE_CANT_DROP_MISSING_TABLE](#) was added in 8.0.1.

- Error number: 3606; Symbol: [ER_TABLESPACE_DUP_FILENAME](#); SQLSTATE: HY000

Message: Duplicate file name for tablespace '%s'

[ER_TABLESPACE_DUP_FILENAME](#) was added in 8.0.1.

- Error number: 3607; Symbol: [ER_DB_DROP_RMDIR2](#); SQLSTATE: HY000

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

[ER_DB_DROP_RMDIR2](#) was added in 8.0.1.

- Error number: 3608; Symbol: [ER_IMP_NO_FILES_MATCHED](#); SQLSTATE: HY000

Message: No SDI files matched the pattern '%s'

[ER_IMP_NO_FILES_MATCHED](#) was added in 8.0.1.

- Error number: 3609; Symbol: [ER_IMP_SCHEMA_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: Schema '%s', referenced in SDI, does not exist.

[ER_IMP_SCHEMA_DOES_NOT_EXIST](#) was added in 8.0.1.

- Error number: 3610; Symbol: [ER_IMP_TABLE_ALREADY_EXISTS](#); SQLSTATE: HY000

Message: Table '%s.%s', referenced in SDI, already exists.

`ER_IMP_TABLE_ALREADY_EXISTS` was added in 8.0.1.

- Error number: `3611`; Symbol: `ER_IMP_INCOMPATIBLE_MYSQLD_VERSION`; SQLSTATE: `HY000`
Message: Imported `mysqld_version` (%llu) is not compatible with current (%llu)

`ER_IMP_INCOMPATIBLE_MYSQLD_VERSION` was added in 8.0.1.

- Error number: `3612`; Symbol: `ER_IMP_INCOMPATIBLE_DD_VERSION`; SQLSTATE: `HY000`
Message: Imported `dd version` (%u) is not compatible with current (%u)

`ER_IMP_INCOMPATIBLE_DD_VERSION` was added in 8.0.1.

- Error number: `3613`; Symbol: `ER_IMP_INCOMPATIBLE_SDI_VERSION`; SQLSTATE: `HY000`
Message: Imported `sdi version` (%llu) is not compatible with current (%llu)

`ER_IMP_INCOMPATIBLE_SDI_VERSION` was added in 8.0.1.

- Error number: `3614`; Symbol: `ER_WARN_INVALID_HINT`; SQLSTATE: `HY000`
Message: Invalid number of arguments for hint %s

`ER_WARN_INVALID_HINT` was added in 8.0.1.

- Error number: `3615`; Symbol: `ER_VAR_DOES_NOT_EXIST`; SQLSTATE: `HY000`
Message: Variable %s does not exist in persisted config file

`ER_VAR_DOES_NOT_EXIST` was added in 8.0.1.

- Error number: `3616`; Symbol: `ER_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: `22S02`
Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

`ER_LONGITUDE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: `3617`; Symbol: `ER_LATITUDE_OUT_OF_RANGE`; SQLSTATE: `22S03`
Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

`ER_LATITUDE_OUT_OF_RANGE` was added in 8.0.1.

- Error number: `3618`; Symbol: `ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS`; SQLSTATE: `22S00`

Message: %s(%s) has not been implemented for geographic spatial reference systems.

`ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS` was added in 8.0.1.

- Error number: `3619`; Symbol: `ER_ILLEGAL_PRIVILEGE_LEVEL`; SQLSTATE: `HY000`
Message: Illegal privilege level specified for %s

`ER_ILLEGAL_PRIVILEGE_LEVEL` was added in 8.0.1.

- Error number: `3620`; Symbol: `ER_NO_SYSTEM_VIEW_ACCESS`; SQLSTATE: `HY000`
Message: Access to system view `INFORMATION_SCHEMA.%s` is rejected.

`ER_NO_SYSTEM_VIEW_ACCESS` was added in 8.0.2.

- Error number: `3621`; Symbol: `ER_COMPONENT_FILTER_FLABBERGASTED`; SQLSTATE: `HY000`

Message: The log-filter component "%s" got confused at "%s" ...

[ER_COMPONENT_FILTER_FLABBERGASTED](#) was added in 8.0.2.

- Error number: 3622; Symbol: [ER_PART_EXPR_TOO_LONG](#); SQLSTATE: HY000

Message: Partitioning expression is too long.

[ER_PART_EXPR_TOO_LONG](#) was added in 8.0.2.

- Error number: 3623; Symbol: [ER_UDF_DROP_DYNAMICALLY_REGISTERED](#); SQLSTATE: HY000

Message: DROP FUNCTION can't drop a dynamically registered user defined function

[ER_UDF_DROP_DYNAMICALLY_REGISTERED](#) was added in 8.0.2.

- Error number: 3624; Symbol: [ER_UNABLE_TO_STORE_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to store column statistics for column '%s' in table '%s'. '%s'

[ER_UNABLE_TO_STORE_COLUMN_STATISTICS](#) was added in 8.0.2.

- Error number: 3625; Symbol: [ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to update column statistics for column '%s' in table '%s'. '%s'

[ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS](#) was added in 8.0.2.

- Error number: 3626; Symbol: [ER_UNABLE_TO_DROP_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'

[ER_UNABLE_TO_DROP_COLUMN_STATISTICS](#) was added in 8.0.2.

- Error number: 3627; Symbol: [ER_UNABLE_TO_BUILD_HISTOGRAM](#); SQLSTATE: HY000

Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'

[ER_UNABLE_TO_BUILD_HISTOGRAM](#) was added in 8.0.2.

- Error number: 3628; Symbol: [ER_MANDATORY_ROLE](#); SQLSTATE: HY000

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory_roles.

[ER_MANDATORY_ROLE](#) was added in 8.0.2.

- Error number: 3629; Symbol: [ER_MISSING_TABLESPACE_FILE](#); SQLSTATE: HY000

Message: Tablespace '%s' does not have a file named '%s'

[ER_MISSING_TABLESPACE_FILE](#) was added in 8.0.3.

- Error number: 3630; Symbol: [ER_PERSIST_ONLY_ACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

[ER_PERSIST_ONLY_ACCESS_DENIED_ERROR](#) was added in 8.0.3.

- Error number: 3631; Symbol: [ER_CMD_NEED_SUPER](#); SQLSTATE: HY000

Message: You need the SUPER privilege for command '%s'

`ER_CMD_NEED_SUPER` was added in 8.0.3.

- Error number: 3632; Symbol: `ER_PATH_IN_DATADIR`; SQLSTATE: HY000

Message: Path is within the current data directory '%s'

`ER_PATH_IN_DATADIR` was added in 8.0.3.

- Error number: 3633; Symbol: `ER_DDL_IN_PROGRESS`; SQLSTATE: HY000

Message: Concurrent DDL is performed during the operation. Please try again.

`ER_DDL_IN_PROGRESS` was added in 8.0.3, removed after 8.0.16.

- Error number: 3633; Symbol: `ER_CLONE_DDL_IN_PROGRESS`; SQLSTATE: HY000

Message: Concurrent DDL is performed during clone operation. Please try again.

`ER_CLONE_DDL_IN_PROGRESS` was added in 8.0.17.

- Error number: 3634; Symbol: `ER_TOO_MANY_CONCURRENT_CLONES`; SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

`ER_TOO_MANY_CONCURRENT_CLONES` was added in 8.0.3, removed after 8.0.16.

- Error number: 3634; Symbol: `ER_CLONE_TOO_MANY_CONCURRENT_CLONES`; SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

`ER_CLONE_TOO_MANY_CONCURRENT_CLONES` was added in 8.0.17.

- Error number: 3635; Symbol: `ER_APPLIER_LOG_EVENT_VALIDATION_ERROR`; SQLSTATE: HY000

Message: The table in transaction %s does not comply with the requirements by an external plugin.

`ER_APPLIER_LOG_EVENT_VALIDATION_ERROR` was added in 8.0.3.

- Error number: 3636; Symbol: `ER_CTE_MAX_RECURSION_DEPTH`; SQLSTATE: HY000

Message: Recursive query aborted after %u iterations. Try increasing @@cte_max_recursion_depth to a larger value.

`ER_CTE_MAX_RECURSION_DEPTH` was added in 8.0.3.

- Error number: 3637; Symbol: `ER_NOT_HINT_UPDATABLE_VARIABLE`; SQLSTATE: HY000

Message: Variable %s cannot be set using SET_VAR hint.

`ER_NOT_HINT_UPDATABLE_VARIABLE` was added in 8.0.3.

- Error number: 3638; Symbol: `ER_CREDENTIALS_CONTRADICT_TO_HISTORY`; SQLSTATE: HY000

Message: Cannot use these credentials for '%.*s@%.*s' because they contradict the password history policy

`ER_CREDENTIALS_CONTRADICT_TO_HISTORY` was added in 8.0.3.

-
- Error number: 3639; Symbol: `ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID`; SQLSTATE: `HY000`

Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history

`ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID` was added in 8.0.3.

- Error number: 3640; Symbol: `ER_CLIENT_DOES_NOT_SUPPORT`; SQLSTATE: `HY000`

Message: The client doesn't support %s

`ER_CLIENT_DOES_NOT_SUPPORT` was added in 8.0.3.

- Error number: 3641; Symbol: `ER_I_S_SKIPPED_TABLESPACE`; SQLSTATE: `HY000`

Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement

`ER_I_S_SKIPPED_TABLESPACE` was added in 8.0.3.

- Error number: 3642; Symbol: `ER_TABLESPACE_ENGINE_MISMATCH`; SQLSTATE: `HY000`

Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'

`ER_TABLESPACE_ENGINE_MISMATCH` was added in 8.0.3.

- Error number: 3643; Symbol: `ER_WRONG_SRID_FOR_COLUMN`; SQLSTATE: `HY000`

Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.

`ER_WRONG_SRID_FOR_COLUMN` was added in 8.0.3.

- Error number: 3644; Symbol: `ER_CANNOT_ALTER_SRID_DUE_TO_INDEX`; SQLSTATE: `HY000`

Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.

`ER_CANNOT_ALTER_SRID_DUE_TO_INDEX` was added in 8.0.3.

- Error number: 3645; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED`; SQLSTATE: `HY000`

Message: When %s, the option `binlog_row_value_options=%s` will be ignored and updates will be written in full format to binary log.

`ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED` was added in 8.0.3.

- Error number: 3646; Symbol: `ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED`; SQLSTATE: `HY000`

Message: When %s, the option `log_bin_use_v1_row_events=1` will be ignored and row events will be written in new format to binary log.

`ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED` was added in 8.0.3.

-
- Error number: 3647; Symbol: `ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES`; SQLSTATE: HY000
Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.
`ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES` was added in 8.0.3.
 - Error number: 3648; Symbol: `ER_COULD_NOT_APPLY_JSON_DIFF`; SQLSTATE: HY000
Message: Could not apply JSON diff in table %.*s, column %s.
`ER_COULD_NOT_APPLY_JSON_DIFF` was added in 8.0.3.
 - Error number: 3649; Symbol: `ER_CORRUPTED_JSON_DIFF`; SQLSTATE: HY000
Message: Corrupted JSON diff for table %.*s, column %s.
`ER_CORRUPTED_JSON_DIFF` was added in 8.0.3.
 - Error number: 3650; Symbol: `ER_RESOURCE_GROUP_EXISTS`; SQLSTATE: HY000
Message: Resource Group '%s' exists
`ER_RESOURCE_GROUP_EXISTS` was added in 8.0.3.
 - Error number: 3651; Symbol: `ER_RESOURCE_GROUP_NOT_EXISTS`; SQLSTATE: HY000
Message: Resource Group '%s' does not exist.
`ER_RESOURCE_GROUP_NOT_EXISTS` was added in 8.0.3.
 - Error number: 3652; Symbol: `ER_INVALID_VCPU_ID`; SQLSTATE: HY000
Message: Invalid cpu id %u
`ER_INVALID_VCPU_ID` was added in 8.0.3.
 - Error number: 3653; Symbol: `ER_INVALID_VCPU_RANGE`; SQLSTATE: HY000
Message: Invalid VCPU range %u-%u
`ER_INVALID_VCPU_RANGE` was added in 8.0.3.
 - Error number: 3654; Symbol: `ER_INVALID_THREAD_PRIORITY`; SQLSTATE: HY000
Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].
`ER_INVALID_THREAD_PRIORITY` was added in 8.0.3.
 - Error number: 3655; Symbol: `ER_DISALLOWED_OPERATION`; SQLSTATE: HY000
Message: %s operation is disallowed on %s
`ER_DISALLOWED_OPERATION` was added in 8.0.3.
 - Error number: 3656; Symbol: `ER_RESOURCE_GROUP_BUSY`; SQLSTATE: HY000
Message: Resource group %s is busy.
`ER_RESOURCE_GROUP_BUSY` was added in 8.0.3.
 - Error number: 3657; Symbol: `ER_RESOURCE_GROUP_DISABLED`; SQLSTATE: HY000

Message: Resource group %s is disabled.

[ER_RESOURCE_GROUP_DISABLED](#) was added in 8.0.3.

- Error number: 3658; Symbol: [ER_FEATURE_UNSUPPORTED](#); SQLSTATE: HY000

Message: Feature %s is unsupported (%s).

[ER_FEATURE_UNSUPPORTED](#) was added in 8.0.3.

- Error number: 3659; Symbol: [ER_ATTRIBUTE_IGNORED](#); SQLSTATE: HY000

Message: Attribute %s is ignored (%s).

[ER_ATTRIBUTE_IGNORED](#) was added in 8.0.3.

- Error number: 3660; Symbol: [ER_INVALID_THREAD_ID](#); SQLSTATE: HY000

Message: Invalid thread id (%llu).

[ER_INVALID_THREAD_ID](#) was added in 8.0.3.

- Error number: 3661; Symbol: [ER_RESOURCE_GROUP_BIND_FAILED](#); SQLSTATE: HY000

Message: Unable to bind resource group %s with thread id (%llu).(%)s).

[ER_RESOURCE_GROUP_BIND_FAILED](#) was added in 8.0.3.

- Error number: 3662; Symbol: [ER_INVALID_USE_OF_FORCE_OPTION](#); SQLSTATE: HY000

Message: Option FORCE invalid as DISABLE option is not specified.

[ER_INVALID_USE_OF_FORCE_OPTION](#) was added in 8.0.3.

- Error number: 3663; Symbol: [ER_GROUP_REPLICATION_COMMAND_FAILURE](#); SQLSTATE: HY000

Message: The %s command encountered a failure. %s

[ER_GROUP_REPLICATION_COMMAND_FAILURE](#) was added in 8.0.4.

- Error number: 3664; Symbol: [ER_SDI_OPERATION_FAILED](#); SQLSTATE: HY000

Message: Failed to %s SDI '%s.%s' in tablespace '%s'.

[ER_SDI_OPERATION_FAILED](#) was added in 8.0.3.

- Error number: 3665; Symbol: [ER_MISSING_JSON_TABLE_VALUE](#); SQLSTATE: 22035

Message: Missing value for JSON_TABLE column '%s'

[ER_MISSING_JSON_TABLE_VALUE](#) was added in 8.0.4.

- Error number: 3666; Symbol: [ER_WRONG_JSON_TABLE_VALUE](#); SQLSTATE: 2203F

Message: Can't store an array or an object in the scalar JSON_TABLE column '%s'

[ER_WRONG_JSON_TABLE_VALUE](#) was added in 8.0.4.

- Error number: 3667; Symbol: [ER_TF_MUST_HAVE_ALIAS](#); SQLSTATE: 42000

Message: Every table function must have an alias

[ER_TF_MUST_HAVE_ALIAS](#) was added in 8.0.4.

-
- Error number: 3668; Symbol: [ER_TF_FORBIDDEN_JOIN_TYPE](#); SQLSTATE: HY000
Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'
[ER_TF_FORBIDDEN_JOIN_TYPE](#) was added in 8.0.4.
 - Error number: 3669; Symbol: [ER_JT_VALUE_OUT_OF_RANGE](#); SQLSTATE: 22003
Message: Value is out of range for JSON_TABLE's column '%s'
[ER_JT_VALUE_OUT_OF_RANGE](#) was added in 8.0.4.
 - Error number: 3670; Symbol: [ER_JT_MAX_NESTED_PATH](#); SQLSTATE: 42000
Message: More than supported %u NESTED PATHs were found in JSON_TABLE '%s'
[ER_JT_MAX_NESTED_PATH](#) was added in 8.0.4.
 - Error number: 3671; Symbol: [ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD](#); SQLSTATE: HY000
Message: The selected authentication method %.*s does not support password expiration
[ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD](#) was added in 8.0.4.
 - Error number: 3672; Symbol: [ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL](#); SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.
[ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL](#) was added in 8.0.4.
 - Error number: 3673; Symbol: [ER_BAD_NULL_ERROR_NOT_IGNORED](#); SQLSTATE: 23000
Message: Column '%s' cannot be null
[ER_BAD_NULL_ERROR_NOT_IGNORED](#) was added in 8.0.4.
 - Error number: 3674; Symbol: [WARN_USELESS_SPATIAL_INDEX](#); SQLSTATE: HY000
Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.
[WARN_USELESS_SPATIAL_INDEX](#) was added in 8.0.4.
 - Error number: 3675; Symbol: [ER_DISK_FULL_NOWAIT](#); SQLSTATE: HY000
Message: Create table/tablespace '%s' failed, as disk is full
[ER_DISK_FULL_NOWAIT](#) was added in 8.0.4.
 - Error number: 3676; Symbol: [ER_PARSE_ERROR_IN_DIGEST_FN](#); SQLSTATE: HY000
Message: Could not parse argument to digest function: "%s".
[ER_PARSE_ERROR_IN_DIGEST_FN](#) was added in 8.0.4.
 - Error number: 3677; Symbol: [ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN](#); SQLSTATE: HY000
Message: Could not parse argument to digest function.
[ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN](#) was added in 8.0.4.

-
- Error number: 3678; Symbol: `ER_SCHEMA_DIR_EXISTS`; SQLSTATE: `HY000`

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_EXISTS` was added in 8.0.4.

- Error number: 3679; Symbol: `ER_SCHEMA_DIR_MISSING`; SQLSTATE: `HY000`

Message: Schema directory '%s' does not exist

`ER_SCHEMA_DIR_MISSING` was added in 8.0.4.

- Error number: 3680; Symbol: `ER_SCHEMA_DIR_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to create schema directory '%s' (errno: %d - %s)

`ER_SCHEMA_DIR_CREATE_FAILED` was added in 8.0.4.

- Error number: 3681; Symbol: `ER_SCHEMA_DIR_UNKNOWN`; SQLSTATE: `HY000`

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

`ER_SCHEMA_DIR_UNKNOWN` was added in 8.0.4.

- Error number: 3682; Symbol: `ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326`; SQLSTATE: `22S00`

Message: Function %s is only defined for SRID 0 and SRID 4326.

`ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326` was added in 8.0.4.

- Error number: 3683; Symbol: `ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER`; SQLSTATE: `HY000`

Message: The option `expire_logs_days` and `binlog_expire_logs_seconds` cannot be used together. Please use `binlog_expire_logs_seconds` to set the expire time (`expire_logs_days` is deprecated)

`ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER` was added in 8.0.11.

- Error number: 3684; Symbol: `ER_REGEX_STRING_NOT_TERMINATED`; SQLSTATE: `HY000`

Message: An output string could not be zero-terminated because the length exceeds the buffer capacity.

`ER_REGEX_STRING_NOT_TERMINATED` was added in 8.0.4, removed after 8.0.4.

- Error number: 3684; Symbol: `ER_REGEX_BUFFER_OVERFLOW`; SQLSTATE: `HY000`

Message: The result string is larger than the result buffer.

`ER_REGEX_BUFFER_OVERFLOW` was added in 8.0.4.

- Error number: 3685; Symbol: `ER_REGEX_ILLEGAL_ARGUMENT`; SQLSTATE: `HY000`

Message: Illegal argument to a regular expression.

`ER_REGEX_ILLEGAL_ARGUMENT` was added in 8.0.4.

- Error number: 3686; Symbol: `ER_REGEX_INDEX_OUTOFBOUNDS_ERROR`; SQLSTATE: `HY000`

Message: Index out of bounds in regular expression search.

`ER_REGEX_INDEX_OUTOFBOUNDS_ERROR` was added in 8.0.4.

- Error number: 3687; Symbol: `ER_REGEX_INTERNAL_ERROR`; SQLSTATE: HY000

Message: Internal error in the regular expression library.

`ER_REGEX_INTERNAL_ERROR` was added in 8.0.4.

- Error number: 3688; Symbol: `ER_REGEX_RULE_SYNTAX`; SQLSTATE: HY000

Message: Syntax error in regular expression on line %u, character %u.

`ER_REGEX_RULE_SYNTAX` was added in 8.0.4.

- Error number: 3689; Symbol: `ER_REGEX_BAD_ESCAPE_SEQUENCE`; SQLSTATE: HY000

Message: Unrecognized escape sequence in regular expression.

`ER_REGEX_BAD_ESCAPE_SEQUENCE` was added in 8.0.4.

- Error number: 3690; Symbol: `ER_REGEX_UNIMPLEMENTED`; SQLSTATE: HY000

Message: The regular expression contains a feature that is not implemented in this library version.

`ER_REGEX_UNIMPLEMENTED` was added in 8.0.4.

- Error number: 3691; Symbol: `ER_REGEX_MISMATCHED_PAREN`; SQLSTATE: HY000

Message: Mismatched parenthesis in regular expression.

`ER_REGEX_MISMATCHED_PAREN` was added in 8.0.4.

- Error number: 3692; Symbol: `ER_REGEX_BAD_INTERVAL`; SQLSTATE: HY000

Message: Incorrect description of a {min,max} interval.

`ER_REGEX_BAD_INTERVAL` was added in 8.0.4.

- Error number: 3693; Symbol: `ER_REGEX_MAX_LT_MIN`; SQLSTATE: HY000

Message: The maximum is less than the minimum in a {min,max} interval.

`ER_REGEX_MAX_LT_MIN` was added in 8.0.4.

- Error number: 3694; Symbol: `ER_REGEX_INVALID_BACK_REF`; SQLSTATE: HY000

Message: Invalid back-reference in regular expression.

`ER_REGEX_INVALID_BACK_REF` was added in 8.0.4.

- Error number: 3695; Symbol: `ER_REGEX_LOOK_BEHIND_LIMIT`; SQLSTATE: HY000

Message: The look-behind assertion exceeds the limit in regular expression.

`ER_REGEX_LOOK_BEHIND_LIMIT` was added in 8.0.4.

- Error number: 3696; Symbol: `ER_REGEX_MISSING_CLOSE_BRACKET`; SQLSTATE: HY000

Message: The regular expression contains an unclosed bracket expression.

`ER_REGEX_MISSING_CLOSE_BRACKET` was added in 8.0.4.

- Error number: 3697; Symbol: `ER_REGEX_INVALID_RANGE`; SQLSTATE: HY000

Message: The regular expression contains an [x-y] character range where x comes after y.

[ER_REGEX_INVALID_RANGE](#) was added in 8.0.4.

- Error number: 3698; Symbol: [ER_REGEX_STACK_OVERFLOW](#); SQLSTATE: HY000

Message: Overflow in the regular expression backtrack stack.

[ER_REGEX_STACK_OVERFLOW](#) was added in 8.0.4.

- Error number: 3699; Symbol: [ER_REGEX_TIME_OUT](#); SQLSTATE: HY000

Message: Timeout exceeded in regular expression match.

[ER_REGEX_TIME_OUT](#) was added in 8.0.4.

- Error number: 3700; Symbol: [ER_REGEX_PATTERN_TOO_BIG](#); SQLSTATE: HY000

Message: The regular expression pattern exceeds limits on size or complexity.

[ER_REGEX_PATTERN_TOO_BIG](#) was added in 8.0.4.

- Error number: 3701; Symbol: [ER_CANT_SET_ERROR_LOG_SERVICE](#); SQLSTATE: HY000

Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.

[ER_CANT_SET_ERROR_LOG_SERVICE](#) was added in 8.0.4.

- Error number: 3702; Symbol: [ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE](#); SQLSTATE: HY000

Message: Setting an empty %s pipeline disables error logging!

[ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE](#) was added in 8.0.4.

- Error number: 3703; Symbol: [ER_COMPONENT_FILTER_DIAGNOSTICS](#); SQLSTATE: HY000

Message: filter %s: %s

[ER_COMPONENT_FILTER_DIAGNOSTICS](#) was added in 8.0.4.

- Error number: 3704; Symbol: [ER_INNODB_CANNOT_BE_IGNORED](#); SQLSTATE: HY000

Message: ignore-builtin-innodb is ignored and will be removed in future releases.

[ER_INNODB_CANNOT_BE_IGNORED](#) was added in 8.0.2, removed after 8.0.2.

- Error number: 3704; Symbol: [ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS](#); SQLSTATE: 22S00

Message: %s(%s) has not been implemented for Cartesian spatial reference systems.

[ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS](#) was added in 8.0.4.

- Error number: 3705; Symbol: [ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS](#); SQLSTATE: 22S00

Message: %s(%s) has not been implemented for projected spatial reference systems.

[ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS](#) was added in 8.0.4.

- Error number: 3706; Symbol: [ER_NONPOSITIVE_RADIUS](#); SQLSTATE: 22003

Message: Invalid radius provided to function %s: Radius must be greater than zero.

`ER_NONPOSITIVE_RADIUS` was added in 8.0.4.

- Error number: 3707; Symbol: `ER_RESTART_SERVER_FAILED`; SQLSTATE: HY000

Message: Restart server failed (%s).

`ER_RESTART_SERVER_FAILED` was added in 8.0.4.

- Error number: 3708; Symbol: `ER_SRS_MISSING_MANDATORY_ATTRIBUTE`; SQLSTATE: SR006

Message: Missing mandatory attribute %s.

`ER_SRS_MISSING_MANDATORY_ATTRIBUTE` was added in 8.0.4.

- Error number: 3709; Symbol: `ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS`; SQLSTATE: SR006

Message: Multiple definitions of attribute %s.

`ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS` was added in 8.0.4.

- Error number: 3710; Symbol: `ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006

Message: The spatial reference system name can't be an empty string or start or end with whitespace.

`ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.

- Error number: 3711; Symbol: `ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE`; SQLSTATE: SR006

Message: The organization name can't be an empty string or start or end with whitespace.

`ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE` was added in 8.0.4.

- Error number: 3712; Symbol: `ER_SRS_ID_ALREADY_EXISTS`; SQLSTATE: SR004

Message: There is already a spatial reference system with SRID %u.

`ER_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.

- Error number: 3713; Symbol: `ER_WARN_SRS_ID_ALREADY_EXISTS`; SQLSTATE: 01S00

Message: There is already a spatial reference system with SRID %u.

`ER_WARN_SRS_ID_ALREADY_EXISTS` was added in 8.0.4.

- Error number: 3714; Symbol: `ER_CANT_MODIFY_SRID_0`; SQLSTATE: SR000

Message: SRID 0 is not modifiable.

`ER_CANT_MODIFY_SRID_0` was added in 8.0.4.

- Error number: 3715; Symbol: `ER_WARN_RESERVED_SRID_RANGE`; SQLSTATE: 01S01

Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.

`ER_WARN_RESERVED_SRID_RANGE` was added in 8.0.4.

- Error number: 3716; Symbol: `ER_CANT_MODIFY_SRS_USED_BY_COLUMN`; SQLSTATE: SR005

Message: Can't modify SRID %u. There is at least one column depending on it.

[ER_CANT_MODIFY_SRS_USED_BY_COLUMN](#) was added in 8.0.4.

- Error number: 3717; Symbol: [ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE](#); SQLSTATE: SR006

Message: Invalid character in attribute %s.

[ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE](#) was added in 8.0.4.

- Error number: 3718; Symbol: [ER_SRS_ATTRIBUTE_STRING_TOO_LONG](#); SQLSTATE: SR006

Message: Attribute %s is too long. The maximum length is %u characters.

[ER_SRS_ATTRIBUTE_STRING_TOO_LONG](#) was added in 8.0.4.

- Error number: 3719; Symbol: [ER_DEPRECATED_UTF8_ALIAS](#); SQLSTATE: HY000

Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

[ER_DEPRECATED_UTF8_ALIAS](#) was added in 8.0.11.

- Error number: 3720; Symbol: [ER_DEPRECATED_NATIONAL](#); SQLSTATE: HY000

Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.

[ER_DEPRECATED_NATIONAL](#) was added in 8.0.11.

- Error number: 3721; Symbol: [ER_INVALID_DEFAULT_UTF8MB4_COLLATION](#); SQLSTATE: HY000

Message: Invalid default collation %s: utf8mb4_0900_ai_ci or utf8mb4_general_ci expected

[ER_INVALID_DEFAULT_UTF8MB4_COLLATION](#) was added in 8.0.11.

- Error number: 3722; Symbol: [ER_UNABLE_TO_COLLECT_LOG_STATUS](#); SQLSTATE: HY000

Message: Unable to collect information for column '%s': %s.

[ER_UNABLE_TO_COLLECT_LOG_STATUS](#) was added in 8.0.11.

- Error number: 3723; Symbol: [ER_RESERVED_TABLESPACE_NAME](#); SQLSTATE: HY000

Message: The table '%s' may not be created in the reserved tablespace '%s'.

[ER_RESERVED_TABLESPACE_NAME](#) was added in 8.0.11.

- Error number: 3724; Symbol: [ER_UNABLE_TO_SET_OPTION](#); SQLSTATE: HY000

Message: This option cannot be set %s.

[ER_UNABLE_TO_SET_OPTION](#) was added in 8.0.11.

- Error number: 3725; Symbol: [ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL](#); SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the master and the slave. The slave supports atomic DDL statements but the master does not, so the action taken by the slave and master might differ. Check that their states have not diverged before proceeding.

[ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL](#) was added in 8.0.11, removed after 8.0.32.

-
- Error number: 3725; Symbol: `ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL`; SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.

`ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL` was added in 8.0.33.

- Error number: 3726; Symbol: `ER_SRS_NOT_GEOGRAPHIC`; SQLSTATE: 22S00

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

`ER_SRS_NOT_GEOGRAPHIC` was added in 8.0.12.

- Error number: 3727; Symbol: `ER_POLYGON_TOO_LARGE`; SQLSTATE: 22023

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

`ER_POLYGON_TOO_LARGE` was added in 8.0.12.

- Error number: 3728; Symbol: `ER_SPATIAL_UNIQUE_INDEX`; SQLSTATE: HY000

Message: Spatial indexes can't be primary or unique indexes.

`ER_SPATIAL_UNIQUE_INDEX` was added in 8.0.12.

- Error number: 3729; Symbol: `ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX`; SQLSTATE: HY000

Message: The index type %s is not supported for spatial indexes.

`ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX` was added in 8.0.12.

- Error number: 3730; Symbol: `ER_FK_CANNOT_DROP_PARENT`; SQLSTATE: HY000

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

`ER_FK_CANNOT_DROP_PARENT` was added in 8.0.12.

- Error number: 3731; Symbol: `ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE`; SQLSTATE: 22S02

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].

`ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3732; Symbol: `ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE`; SQLSTATE: 22S03

Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

`ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE` was added in 8.0.12.

- Error number: 3733; Symbol: `ER_FK_CANNOT_USE_VIRTUAL_COLUMN`; SQLSTATE: HY000

Message: Foreign key '%s' uses virtual column '%s' which is not supported.

`ER_FK_CANNOT_USE_VIRTUAL_COLUMN` was added in 8.0.12.

-
- Error number: 3734; Symbol: [ER_FK_NO_COLUMN_PARENT](#); SQLSTATE: HY000
Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'
[ER_FK_NO_COLUMN_PARENT](#) was added in 8.0.12.
 - Error number: 3735; Symbol: [ER_CANT_SET_ERROR_SUPPRESSION_LIST](#); SQLSTATE: HY000
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.
[ER_CANT_SET_ERROR_SUPPRESSION_LIST](#) was added in 8.0.13.
 - Error number: 3736; Symbol: [ER_SRS_GEOGCS_INVALID_AXES](#); SQLSTATE: SR002
Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.
[ER_SRS_GEOGCS_INVALID_AXES](#) was added in 8.0.13.
 - Error number: 3737; Symbol: [ER_SRS_INVALID_SEMI_MAJOR_AXIS](#); SQLSTATE: SR002
Message: The length of the semi-major axis must be a positive number.
[ER_SRS_INVALID_SEMI_MAJOR_AXIS](#) was added in 8.0.13.
 - Error number: 3738; Symbol: [ER_SRS_INVALID_INVERSE_FLATTENING](#); SQLSTATE: SR002
Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.
[ER_SRS_INVALID_INVERSE_FLATTENING](#) was added in 8.0.13.
 - Error number: 3739; Symbol: [ER_SRS_INVALID_ANGULAR_UNIT](#); SQLSTATE: SR002
Message: The angular unit conversion factor must be a positive number.
[ER_SRS_INVALID_ANGULAR_UNIT](#) was added in 8.0.13.
 - Error number: 3740; Symbol: [ER_SRS_INVALID_PRIME_MERIDIAN](#); SQLSTATE: SR002
Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.
[ER_SRS_INVALID_PRIME_MERIDIAN](#) was added in 8.0.13.
 - Error number: 3741; Symbol: [ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED](#); SQLSTATE: 22S00
Message: Transformation from SRID %u is not supported.
[ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED](#) was added in 8.0.13.
 - Error number: 3742; Symbol: [ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED](#); SQLSTATE: 22S00
Message: Transformation to SRID %u is not supported.
[ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED](#) was added in 8.0.13.
 - Error number: 3743; Symbol: [ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84](#); SQLSTATE: 22S00
Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

[ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84](#) was added in 8.0.13.

- Error number: 3744; Symbol: [ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84](#); SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

[ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84](#) was added in 8.0.13.

- Error number: 3745; Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@session.binlog_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.

[ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: 3746; Symbol: [ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica_open_temp_tables = 0 and try again

[ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: 3747; Symbol: [ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICA SQL_THREAD and try again.

[ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT](#) was added in 8.0.13.

- Error number: 3748; Symbol: [ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.

[ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#) was added in 8.0.13.

- Error number: 3750; Symbol: [ER_TABLE_WITHOUT_PK](#); SQLSTATE: HY000

Message: Unable to create or change a table without a primary key, when the system variable 'sql_require_primary_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

[ER_TABLE_WITHOUT_PK](#) was added in 8.0.13.

- Error number: 3751; Symbol: [WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#); SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

[WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#) was added in 8.0.13, removed after 8.0.16.

- Error number: 3751; Symbol: [ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#); SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

[ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#) was added in 8.0.17.

- Error number: 3752; Symbol: [ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX](#); SQLSTATE: 22003

Message: Value is out of range for functional index '%s' at row %ld

[ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX](#) was added in 8.0.13.

- Error number: 3753; Symbol: [ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION](#); SQLSTATE: 42000

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

[ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION](#) was added in 8.0.13.

- Error number: 3754; Symbol: [ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT](#); SQLSTATE: HY000

Message: Functional index '%s' cannot refer to an auto-increment column.

[ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT](#) was added in 8.0.13.

- Error number: 3755; Symbol: [ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX](#); SQLSTATE: HY000

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.

[ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX](#) was added in 8.0.13.

- Error number: 3756; Symbol: [ER_FUNCTIONAL_INDEX_PRIMARY_KEY](#); SQLSTATE: HY000

Message: The primary key cannot be a functional index

[ER_FUNCTIONAL_INDEX_PRIMARY_KEY](#) was added in 8.0.13.

- Error number: 3757; Symbol: [ER_FUNCTIONAL_INDEX_ON_LOB](#); SQLSTATE: HY000

Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.

[ER_FUNCTIONAL_INDEX_ON_LOB](#) was added in 8.0.13.

- Error number: 3758; Symbol: [ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000

Message: Expression of functional index '%s' contains a disallowed function.

[ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED](#) was added in 8.0.13.

- Error number: 3759; Symbol: [ER_FULLTEXT_FUNCTIONAL_INDEX](#); SQLSTATE: HY000

Message: Fulltext functional index is not supported.

[ER_FULLTEXT_FUNCTIONAL_INDEX](#) was added in 8.0.13.

- Error number: 3760; Symbol: [ER_SPATIAL_FUNCTIONAL_INDEX](#); SQLSTATE: HY000

Message: Spatial functional index is not supported.

`ER_SPATIAL_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: 3761; Symbol: `ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX`; SQLSTATE: HY000

Message: The used storage engine cannot index the expression '%s'.

`ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX` was added in 8.0.13.

- Error number: 3762; Symbol: `ER_FUNCTIONAL_INDEX_ON_FIELD`; SQLSTATE: HY000

Message: Functional index on a column is not supported. Consider using a regular index instead.

`ER_FUNCTIONAL_INDEX_ON_FIELD` was added in 8.0.13.

- Error number: 3763; Symbol: `ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Expression of generated column '%s' contains a disallowed function: %s.

`ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.

- Error number: 3764; Symbol: `ER_GENERATED_COLUMN_ROW_VALUE`; SQLSTATE: HY000

Message: Expression of generated column '%s' cannot refer to a row value.

`ER_GENERATED_COLUMN_ROW_VALUE` was added in 8.0.13.

- Error number: 3765; Symbol: `ER_GENERATED_COLUMN_VARIABLES`; SQLSTATE: HY000

Message: Expression of generated column '%s' cannot refer user or system variables.

`ER_GENERATED_COLUMN_VARIABLES` was added in 8.0.13.

- Error number: 3766; Symbol: `ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE`; SQLSTATE: HY000

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

`ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE` was added in 8.0.13.

- Error number: 3767; Symbol: `ER_DEFAULT_VAL_GENERATED_NON_PRIOR`; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

`ER_DEFAULT_VAL_GENERATED_NON_PRIOR` was added in 8.0.13.

- Error number: 3768; Symbol: `ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC`; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

`ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC` was added in 8.0.13.

- Error number: 3769; Symbol: `ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function.

`ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.

-
- Error number: 3770; Symbol: `ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: HY000
Message: Default value expression of column '%s' contains a disallowed function: %s.
`ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.13.
 - Error number: 3771; Symbol: `ER_DEFAULT_VAL_GENERATED_ROW_VALUE`; SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer to a row value.
`ER_DEFAULT_VAL_GENERATED_ROW_VALUE` was added in 8.0.13.
 - Error number: 3772; Symbol: `ER_DEFAULT_VAL_GENERATED_VARIABLES`; SQLSTATE: HY000
Message: Default value expression of column '%s' cannot refer user or system variables.
`ER_DEFAULT_VAL_GENERATED_VARIABLES` was added in 8.0.13.
 - Error number: 3773; Symbol: `ER_DEFAULT_AS_VAL_GENERATED`; SQLSTATE: HY000
Message: DEFAULT function cannot be used with default value expressions
`ER_DEFAULT_AS_VAL_GENERATED` was added in 8.0.13.
 - Error number: 3774; Symbol: `ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED`; SQLSTATE: HY000
Message: '%s' is not supported for default value expressions.
`ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED` was added in 8.0.13.
 - Error number: 3775; Symbol: `ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION`; SQLSTATE: HY000
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
`ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION` was added in 8.0.13.
 - Error number: 3776; Symbol: `ER_FK_CANNOT_CHANGE_ENGINE`; SQLSTATE: HY000
Message: Cannot change table's storage engine because the table participates in a foreign key constraint.
`ER_FK_CANNOT_CHANGE_ENGINE` was added in 8.0.13.
 - Error number: 3777; Symbol: `ER_WARN_DEPRECATED_USER_SET_EXPR`; SQLSTATE: HY000
Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.
`ER_WARN_DEPRECATED_USER_SET_EXPR` was added in 8.0.13.
 - Error number: 3778; Symbol: `ER_WARN_DEPRECATED_UTF8MB3_COLLATION`; SQLSTATE: HY000
Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
`ER_WARN_DEPRECATED_UTF8MB3_COLLATION` was added in 8.0.13.
 - Error number: 3779; Symbol: `ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX`; SQLSTATE: HY000

Message: Nested comment syntax is deprecated and will be removed in a future release.

[ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX](#) was added in 8.0.13.

- Error number: 3780; Symbol: [ER_FK_INCOMPATIBLE_COLUMNS](#); SQLSTATE: HY000

Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.

[ER_FK_INCOMPATIBLE_COLUMNS](#) was added in 8.0.14.

- Error number: 3781; Symbol: [ER_GR_HOLD_WAIT_TIMEOUT](#); SQLSTATE: HY000

Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.

[ER_GR_HOLD_WAIT_TIMEOUT](#) was added in 8.0.14.

- Error number: 3782; Symbol: [ER_GR_HOLD_KILLED](#); SQLSTATE: HY000

Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.

[ER_GR_HOLD_KILLED](#) was added in 8.0.14.

- Error number: 3783; Symbol: [ER_GR_HOLD_MEMBER_STATUS_ERROR](#); SQLSTATE: HY000

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

[ER_GR_HOLD_MEMBER_STATUS_ERROR](#) was added in 8.0.14.

- Error number: 3784; Symbol: [ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#); SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

[ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#) was added in 8.0.14.

- Error number: 3785; Symbol: [ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#); SQLSTATE: HY000

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

[ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#) was added in 8.0.14.

- Error number: 3786; Symbol: [ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#); SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

[ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#) was added in 8.0.14.

- Error number: 3787; Symbol: [ER_RPL_ENCRYPTION_HEADER_ERROR](#); SQLSTATE: HY000

Message: Error reading a replication log encryption header: %s.

[ER_RPL_ENCRYPTION_HEADER_ERROR](#) was added in 8.0.14.

-
- Error number: 3788; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

`ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS` was added in 8.0.14.

- Error number: 3789; Symbol: `ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: HY000

Message: Key %s exists unexpected.

`ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED` was added in 8.0.14.

- Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY` was added in 8.0.14.

- Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY` was added in 8.0.14.

- Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: HY000

Message: Failed to change binlog_encryption value. %s.

`ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION` was added in 8.0.14.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

`ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: HY000

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

`ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE` was added in 8.0.14.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: HY000

Message: The option group_replication_consistency cannot be used on the current member state.

`ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED` was added in 8.0.14.

-
- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: `HY000`
Message: Error while waiting for group transactions commit on group_replication_consistency='BEFORE'.
`ER_GRP_TRX_CONSISTENCY_BEFORE` was added in 8.0.14.
 - Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: `HY000`
Message: Error while waiting for transactions with group_replication_consistency= 'AFTER' to commit.
`ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN` was added in 8.0.14.
 - Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.
`ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED` was added in 8.0.14.
 - Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: Expression of functional index '%s' cannot refer to a row value.
`ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED` was added in 8.0.14.
 - Error number: 3801; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: `HY000`
Message: Failed to encrypt content to write into binlog file: %s.
`ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT` was added in 8.0.14.
 - Error number: 3802; Symbol: `ER_PAGE_TRACKING_NOT_STARTED`; SQLSTATE: `HY000`
Message: Page Tracking is not started yet.
`ER_PAGE_TRACKING_NOT_STARTED` was added in 8.0.16.
 - Error number: 3803; Symbol: `ER_PAGE_TRACKING_RANGE_NOT_TRACKED`; SQLSTATE: `HY000`
Message: Tracking was not enabled for the LSN range specified
`ER_PAGE_TRACKING_RANGE_NOT_TRACKED` was added in 8.0.16.
 - Error number: 3804; Symbol: `ER_PAGE_TRACKING_CANNOT_PURGE`; SQLSTATE: `HY000`
Message: Cannot purge data when concurrent clone is in progress. Try later.
`ER_PAGE_TRACKING_CANNOT_PURGE` was added in 8.0.16.
 - Error number: 3805; Symbol: `ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY`; SQLSTATE: `HY000`
Message: Cannot rotate binary log master key when 'binlog-encryption' is off.
`ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY` was added in 8.0.16.
 - Error number: 3806; Symbol: `ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

[ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION](#) was added in 8.0.16.

- Error number: 3807; Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY](#); SQLSTATE: HY000

Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.

[ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY](#) was added in 8.0.16.

- Error number: 3808; Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS](#); SQLSTATE: HY000

Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

[ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS](#) was added in 8.0.16.

- Error number: 3809; Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG](#); SQLSTATE: HY000

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

[ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG](#) was added in 8.0.16.

- Error number: 3810; Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS](#); SQLSTATE: HY000

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

[ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS](#) was added in 8.0.16.

- Error number: 3811; Symbol: [ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#); SQLSTATE: HY000

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

[ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#) was added in 8.0.16.

- Error number: 3812; Symbol: [ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT](#); SQLSTATE: HY000

Message: An expression of non-boolean type specified to a check constraint '%s'.

[ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT](#) was added in 8.0.16.

-
- Error number: 3813; Symbol: `ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN`; SQLSTATE: `HY000`
Message: Column check constraint '%s' references other column.
`ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN` was added in 8.0.16.
 - Error number: 3814; Symbol: `ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' contains disallowed function: %s.
`ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.
 - Error number: 3815; Symbol: `ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' contains disallowed function.
`ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED` was added in 8.0.16.
 - Error number: 3816; Symbol: `ER_CHECK_CONSTRAINT_VARIABLES`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' cannot refer to a user or system variable.
`ER_CHECK_CONSTRAINT_VARIABLES` was added in 8.0.16.
 - Error number: 3817; Symbol: `ER_CHECK_CONSTRAINT_ROW_VALUE`; SQLSTATE: `HY000`
Message: Check constraint '%s' cannot refer to a row value.
`ER_CHECK_CONSTRAINT_ROW_VALUE` was added in 8.0.16.
 - Error number: 3818; Symbol: `ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN`; SQLSTATE: `HY000`
Message: Check constraint '%s' cannot refer to an auto-increment column.
`ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN` was added in 8.0.16.
 - Error number: 3819; Symbol: `ER_CHECK_CONSTRAINT_VIOLATED`; SQLSTATE: `HY000`
Message: Check constraint '%s' is violated.
`ER_CHECK_CONSTRAINT_VIOLATED` was added in 8.0.16.
 - Error number: 3820; Symbol: `ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN`; SQLSTATE: `HY000`
Message: Check constraint '%s' refers to non-existing column '%s'.
`ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN` was added in 8.0.16.
 - Error number: 3821; Symbol: `ER_CHECK_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`
Message: Check constraint '%s' is not found in the table.
`ER_CHECK_CONSTRAINT_NOT_FOUND` was added in 8.0.16.
 - Error number: 3822; Symbol: `ER_CHECK_CONSTRAINT_DUP_NAME`; SQLSTATE: `HY000`
Message: Duplicate check constraint name '%s'.
`ER_CHECK_CONSTRAINT_DUP_NAME` was added in 8.0.16.

-
- Error number: 3823; Symbol: `ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN`; SQLSTATE: HY000
Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.
`ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN` was added in 8.0.16.
 - Error number: 3824; Symbol: `WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB`; SQLSTATE: HY000
Message: Creating an unencrypted table in a database with default encryption enabled.
`WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB` was added in 8.0.16.
 - Error number: 3825; Symbol: `ER_INVALID_ENCRYPTION_REQUEST`; SQLSTATE: HY000
Message: Request to create %s table while using an %s tablespace.
`ER_INVALID_ENCRYPTION_REQUEST` was added in 8.0.16.
 - Error number: 3826; Symbol: `ER_CANNOT_SET_TABLE_ENCRYPTION`; SQLSTATE: HY000
Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.
`ER_CANNOT_SET_TABLE_ENCRYPTION` was added in 8.0.16.
 - Error number: 3827; Symbol: `ER_CANNOT_SET_DATABASE_ENCRYPTION`; SQLSTATE: HY000
Message: Database default encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
`ER_CANNOT_SET_DATABASE_ENCRYPTION` was added in 8.0.16.
 - Error number: 3828; Symbol: `ER_CANNOT_SET_TABLESPACE_ENCRYPTION`; SQLSTATE: HY000
Message: Tablespace encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
`ER_CANNOT_SET_TABLESPACE_ENCRYPTION` was added in 8.0.16.
 - Error number: 3829; Symbol: `ER_TABLESPACE_CANNOT_BE_ENCRYPTED`; SQLSTATE: HY000
Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.
`ER_TABLESPACE_CANNOT_BE_ENCRYPTED` was added in 8.0.16.
 - Error number: 3830; Symbol: `ER_TABLESPACE_CANNOT_BE_DECRYPTED`; SQLSTATE: HY000
Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.
`ER_TABLESPACE_CANNOT_BE_DECRYPTED` was added in 8.0.16.
 - Error number: 3831; Symbol: `ER_TABLESPACE_TYPE_UNKNOWN`; SQLSTATE: HY000
Message: Cannot determine the type of the tablespace named '%s'.
`ER_TABLESPACE_TYPE_UNKNOWN` was added in 8.0.16.
 - Error number: 3832; Symbol: `ER_TARGET_TABLESPACE_UNENCRYPTED`; SQLSTATE: HY000

Message: Source tablespace is encrypted but target tablespace is not.

[ER_TARGET_TABLESPACE_UNENCRYPTED](#) was added in 8.0.16.

- Error number: 3833; Symbol: [ER_CANNOT_USE_ENCRYPTION_CLAUSE](#); SQLSTATE: HY000

Message: ENCRYPTION clause is not valid for %s tablespace.

[ER_CANNOT_USE_ENCRYPTION_CLAUSE](#) was added in 8.0.16.

- Error number: 3834; Symbol: [ER_INVALID_MULTIPLE_CLAUSES](#); SQLSTATE: HY000

Message: Multiple %s clauses

[ER_INVALID_MULTIPLE_CLAUSES](#) was added in 8.0.16.

- Error number: 3835; Symbol: [ER_UNSUPPORTED_USE_OF_GRANT_AS](#); SQLSTATE: HY000

Message: GRANT ... AS is currently supported only for global privileges.

[ER_UNSUPPORTED_USE_OF_GRANT_AS](#) was added in 8.0.16.

- Error number: 3836; Symbol: [ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS](#); SQLSTATE: HY000

Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.

[ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS](#) was added in 8.0.16.

- Error number: 3837; Symbol: [ER_DEPENDENT_BY_FUNCTIONAL_INDEX](#); SQLSTATE: HY000

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.

[ER_DEPENDENT_BY_FUNCTIONAL_INDEX](#) was added in 8.0.17.

- Error number: 3838; Symbol: [ER_PLUGIN_NOT_EARLY](#); SQLSTATE: HY000

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

[ER_PLUGIN_NOT_EARLY](#) was added in 8.0.17.

- Error number: 3839; Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH](#); SQLSTATE: HY000

Message: Redo log archiving start prohibits path name in 'subdir' argument

[ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH](#) was added in 8.0.17.

- Error number: 3840; Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT](#); SQLSTATE: HY000

Message: Redo log archiving start timed out

[ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT](#) was added in 8.0.17.

- Error number: 3841; Symbol: [ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID](#); SQLSTATE: HY000

Message: Server variable 'innodb_redo_log_archive_dirs' is NULL or empty

[ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID](#) was added in 8.0.17.

-
- Error number: 3842; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND`; SQLSTATE: HY000
Message: Label '%s' not found in server variable 'innodb_redo_log_archive_dirs'
`ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND` was added in 8.0.17.
 - Error number: 3843; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY`; SQLSTATE: HY000
Message: Directory is empty after label '%s' in server variable 'innodb_redo_log_archive_dirs'
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY` was added in 8.0.17.
 - Error number: 3844; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR`; SQLSTATE: HY000
Message: Redo log archive directory '%s' does not exist or is not a directory
`ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR` was added in 8.0.17.
 - Error number: 3845; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH`; SQLSTATE: HY000
Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH` was added in 8.0.17.
 - Error number: 3846; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS`; SQLSTATE: HY000
Message: Redo log archive directory '%s' is accessible to all OS users
`ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS` was added in 8.0.17.
 - Error number: 3847; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE`; SQLSTATE: HY000
Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)
`ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE` was added in 8.0.17.
 - Error number: 3848; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE`; SQLSTATE: HY000
Message: Redo log archiving has been started on '%s' - Call `innodb_redo_log_archive_stop()` first
`ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE` was added in 8.0.17.
 - Error number: 3849; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE`; SQLSTATE: HY000
Message: Redo log archiving is not active
`ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE` was added in 8.0.17.
 - Error number: 3850; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FAILED`; SQLSTATE: HY000
Message: Redo log archiving failed: %s
`ER_INNODB_REDO_LOG_ARCHIVE_FAILED` was added in 8.0.17.
 - Error number: 3851; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_SESSION`; SQLSTATE: HY000
Message: Redo log archiving has not been started by this session
`ER_INNODB_REDO_LOG_ARCHIVE_SESSION` was added in 8.0.17.

-
- Error number: 3852; Symbol: [ER_STD_REGEX_ERROR](#); SQLSTATE: HY000
Message: Regex error: %s in function %s.
[ER_STD_REGEX_ERROR](#) was added in 8.0.17.
 - Error number: 3853; Symbol: [ER_INVALID_JSON_TYPE](#); SQLSTATE: 22032
Message: Invalid JSON type in argument %u to function %s; an %s is required.
[ER_INVALID_JSON_TYPE](#) was added in 8.0.17.
 - Error number: 3854; Symbol: [ER_CANNOT_CONVERT_STRING](#); SQLSTATE: HY000
Message: Cannot convert string '%s' from %s to %s
[ER_CANNOT_CONVERT_STRING](#) was added in 8.0.17.
 - Error number: 3855; Symbol: [ER_DEPENDENT_BY_PARTITION_FUNC](#); SQLSTATE: HY000
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.
[ER_DEPENDENT_BY_PARTITION_FUNC](#) was added in 8.0.17.
 - Error number: 3856; Symbol: [ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT](#); SQLSTATE: HY000
Message: AUTO_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO_INCREMENT from column '%s'.
[ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT](#) was added in 8.0.17.
 - Error number: 3857; Symbol: [ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP](#); SQLSTATE: HY000
Message: Cannot stop the slave SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.
[ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP](#) was added in 8.0.17, removed after 8.0.32.
 - Error number: 3857; Symbol: [ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP](#); SQLSTATE: HY000
Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.
[ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP](#) was added in 8.0.33.
 - Error number: 3858; Symbol: [ER_WARN_DEPRECATED_FLOAT_DIGITS](#); SQLSTATE: HY000
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.
[ER_WARN_DEPRECATED_FLOAT_DIGITS](#) was added in 8.0.17.
 - Error number: 3859; Symbol: [ER_WARN_DEPRECATED_FLOAT_UNSIGNED](#); SQLSTATE: HY000
Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.
[ER_WARN_DEPRECATED_FLOAT_UNSIGNED](#) was added in 8.0.17.
 - Error number: 3860; Symbol: [ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH](#); SQLSTATE: HY000

Message: Integer display width is deprecated and will be removed in a future release.

[ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH](#) was added in 8.0.17.

- Error number: [3861](#); Symbol: [ER_WARN_DEPRECATED_ZEROFILL](#); SQLSTATE: [HY000](#)

Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.

[ER_WARN_DEPRECATED_ZEROFILL](#) was added in 8.0.17.

- Error number: [3862](#); Symbol: [ER_CLONE_DONOR](#); SQLSTATE: [HY000](#)

Message: Clone Donor Error: %s.

[ER_CLONE_DONOR](#) was added in 8.0.17.

- Error number: [3863](#); Symbol: [ER_CLONE_PROTOCOL](#); SQLSTATE: [HY000](#)

Message: Clone received unexpected response from Donor : %s.

[ER_CLONE_PROTOCOL](#) was added in 8.0.17.

- Error number: [3864](#); Symbol: [ER_CLONE_DONOR_VERSION](#); SQLSTATE: [HY000](#)

Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.

[ER_CLONE_DONOR_VERSION](#) was added in 8.0.17.

- Error number: [3865](#); Symbol: [ER_CLONE_OS](#); SQLSTATE: [HY000](#)

Message: Clone Donor OS: %s is different from Recipient OS: %s.

[ER_CLONE_OS](#) was added in 8.0.17.

- Error number: [3866](#); Symbol: [ER_CLONE_PLATFORM](#); SQLSTATE: [HY000](#)

Message: Clone Donor platform: %s is different from Recipient platform: %s.

[ER_CLONE_PLATFORM](#) was added in 8.0.17.

- Error number: [3867](#); Symbol: [ER_CLONE_CHARSET](#); SQLSTATE: [HY000](#)

Message: Clone Donor collation: %s is unavailable in Recipient.

[ER_CLONE_CHARSET](#) was added in 8.0.17.

- Error number: [3868](#); Symbol: [ER_CLONE_CONFIG](#); SQLSTATE: [HY000](#)

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

[ER_CLONE_CONFIG](#) was added in 8.0.17.

- Error number: [3869](#); Symbol: [ER_CLONE_SYS_CONFIG](#); SQLSTATE: [HY000](#)

Message: Clone system configuration: %s

[ER_CLONE_SYS_CONFIG](#) was added in 8.0.17.

- Error number: [3870](#); Symbol: [ER_CLONE_PLUGIN_MATCH](#); SQLSTATE: [HY000](#)

Message: Clone Donor plugin %s is not active in Recipient.

[ER_CLONE_PLUGIN_MATCH](#) was added in 8.0.17.

-
- Error number: 3871; Symbol: [ER_CLONE_LOOPBACK](#); SQLSTATE: HY000
Message: Clone cannot use loop back connection while cloning into current data directory.
[ER_CLONE_LOOPBACK](#) was added in 8.0.17.
 - Error number: 3872; Symbol: [ER_CLONE_ENCRYPTION](#); SQLSTATE: HY000
Message: Clone needs SSL connection for encrypted table.
[ER_CLONE_ENCRYPTION](#) was added in 8.0.17.
 - Error number: 3873; Symbol: [ER_CLONE_DISK_SPACE](#); SQLSTATE: HY000
Message: Clone estimated database size is %s. Available space %s is not enough.
[ER_CLONE_DISK_SPACE](#) was added in 8.0.17.
 - Error number: 3874; Symbol: [ER_CLONE_IN_PROGRESS](#); SQLSTATE: HY000
Message: Concurrent clone in progress. Please try after clone is complete.
[ER_CLONE_IN_PROGRESS](#) was added in 8.0.17.
 - Error number: 3875; Symbol: [ER_CLONE_DISALLOWED](#); SQLSTATE: HY000
Message: The clone operation cannot be executed when %s.
[ER_CLONE_DISALLOWED](#) was added in 8.0.17.
 - Error number: 3876; Symbol: [ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER](#); SQLSTATE: HY000
Message: Cannot grant roles to an anonymous user.
[ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER](#) was added in 8.0.16.
 - Error number: 3877; Symbol: [ER_SECONDARY_ENGINE_PLUGIN](#); SQLSTATE: HY000
Message: %s
[ER_SECONDARY_ENGINE_PLUGIN](#) was added in 8.0.14.
 - Error number: 3878; Symbol: [ER_SECOND_PASSWORD_CANNOT_BE_EMPTY](#); SQLSTATE: HY000
Message: Empty password can not be retained as second password for user '%s'@'%s'.
[ER_SECOND_PASSWORD_CANNOT_BE_EMPTY](#) was added in 8.0.14.
 - Error number: 3879; Symbol: [ER_DB_ACCESS_DENIED](#); SQLSTATE: HY000
Message: Access denied for AuthId `%s`@`%s` to database '%s'.
[ER_DB_ACCESS_DENIED](#) was added in 8.0.16.
 - Error number: 3880; Symbol: [ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: HY000
Message: Cannot set mandatory_roles: AuthId `%s`@`%s` has '%s' privilege.
[ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#) was added in 8.0.17.
-

-
- Error number: 3881; Symbol: `ER_DA_RPL_GTID_TABLE_CANNOT_OPEN`; SQLSTATE: HY000
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
`ER_DA_RPL_GTID_TABLE_CANNOT_OPEN` was added in 8.0.17.
 - Error number: 3882; Symbol: `ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT`; SQLSTATE: SU001
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.
`ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT` was added in 8.0.14.
 - Error number: 3883; Symbol: `ER_DA_PLUGIN_INSTALL_ERROR`; SQLSTATE: HY000
Message: Error installing plugin '%s': %s
`ER_DA_PLUGIN_INSTALL_ERROR` was added in 8.0.17.
 - Error number: 3884; Symbol: `ER_NO_SESSION_TEMP`; SQLSTATE: HY000
Message: Storage engine could not allocate temporary tablespace for this session.
`ER_NO_SESSION_TEMP` was added in 8.0.13.
 - Error number: 3885; Symbol: `ER_DA_UNKNOWN_ERROR_NUMBER`; SQLSTATE: HY000
Message: Got unknown error: %d
`ER_DA_UNKNOWN_ERROR_NUMBER` was added in 8.0.17.
 - Error number: 3886; Symbol: `ER_COLUMN_CHANGE_SIZE`; SQLSTATE: HY000
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.
`ER_COLUMN_CHANGE_SIZE` was added in 8.0.14.
 - Error number: 3887; Symbol: `ER_REGEX_INVALID_CAPTURE_GROUP_NAME`; SQLSTATE: HY000
Message: A capture group has an invalid name.
`ER_REGEX_INVALID_CAPTURE_GROUP_NAME` was added in 8.0.11.
 - Error number: 3888; Symbol: `ER_DA_SSL_LIBRARY_ERROR`; SQLSTATE: HY000
Message: Failed to set up SSL because of the following SSL library error: %s
`ER_DA_SSL_LIBRARY_ERROR` was added in 8.0.17.
 - Error number: 3889; Symbol: `ER_SECONDARY_ENGINE`; SQLSTATE: HY000
Message: Secondary engine operation failed. %s.
`ER_SECONDARY_ENGINE` was added in 8.0.13.
 - Error number: 3890; Symbol: `ER_SECONDARY_ENGINE_DDL`; SQLSTATE: HY000
Message: DDLs on a table with a secondary engine defined are not allowed.
`ER_SECONDARY_ENGINE_DDL` was added in 8.0.13.

-
- Error number: 3891; Symbol: [ER_INCORRECT_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Incorrect current password. Specify the correct password which has to be replaced.
[ER_INCORRECT_CURRENT_PASSWORD](#) was added in 8.0.13.
 - Error number: 3892; Symbol: [ER_MISSING_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Current password needs to be specified in the REPLACE clause in order to change it.
[ER_MISSING_CURRENT_PASSWORD](#) was added in 8.0.13.
 - Error number: 3893; Symbol: [ER_CURRENT_PASSWORD_NOT_REQUIRED](#); SQLSTATE: HY000
Message: Do not specify the current password while changing it for other users.
[ER_CURRENT_PASSWORD_NOT_REQUIRED](#) was added in 8.0.13.
 - Error number: 3894; Symbol: [ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE](#); SQLSTATE: HY000
Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.
[ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE](#) was added in 8.0.14.
 - Error number: 3895; Symbol: [ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED](#); SQLSTATE: HY000
Message: Current password can not be retained for user '%s'@'%s' because new password is empty.
[ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED](#) was added in 8.0.14.
 - Error number: 3896; Symbol: [ER_PARTIAL_REVOKES_EXIST](#); SQLSTATE: HY000
Message: At least one partial revoke exists on a database. The system variable '@@partial_revokes' must be set to ON.
[ER_PARTIAL_REVOKES_EXIST](#) was added in 8.0.16.
 - Error number: 3897; Symbol: [ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE](#); SQLSTATE: HY000
Message: AuthId '%s'@'%s' is set as mandatory_roles. Cannot grant the '%s' privilege.
[ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE](#) was added in 8.0.16.
 - Error number: 3898; Symbol: [ER_XA_REPLICATION_FILTERS](#); SQLSTATE: HY000
Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.
[ER_XA_REPLICATION_FILTERS](#) was added in 8.0.12.
 - Error number: 3899; Symbol: [ER_UNSUPPORTED_SQL_MODE](#); SQLSTATE: HY000
Message: sql_mode=0x%08x is not supported.
[ER_UNSUPPORTED_SQL_MODE](#) was added in 8.0.11.
 - Error number: 3900; Symbol: [ER_REGEXP_INVALID_FLAG](#); SQLSTATE: HY000
Message: Invalid match mode flag in regular expression.

`ER_REGEX_INVALID_FLAG` was added in 8.0.12.

- Error number: 3901; Symbol: `ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS`; SQLSTATE: HY000

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.

`ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS` was added in 8.0.16.

- Error number: 3902; Symbol: `ER_UNIT_NOT_FOUND`; SQLSTATE: SU001

Message: There's no unit of measure named '%s'.

`ER_UNIT_NOT_FOUND` was added in 8.0.14.

- Error number: 3903; Symbol: `ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX`; SQLSTATE: 22018

Message: Invalid JSON value for CAST for functional index '%s'.

`ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3904; Symbol: `ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX`; SQLSTATE: 22003

Message: Out of range JSON value for CAST for functional index '%s'.

`ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX` was added in 8.0.16.

- Error number: 3905; Symbol: `ER_EXCEEDED_MV_KEYS_NUM`; SQLSTATE: HY000

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

`ER_EXCEEDED_MV_KEYS_NUM` was added in 8.0.16.

- Error number: 3906; Symbol: `ER_EXCEEDED_MV_KEYS_SPACE`; SQLSTATE: HY000

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

`ER_EXCEEDED_MV_KEYS_SPACE` was added in 8.0.16.

- Error number: 3907; Symbol: `ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG`; SQLSTATE: 22001

Message: Data too long for functional index '%s'.

`ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG` was added in 8.0.16.

- Error number: 3908; Symbol: `ER_WRONG_MVI_VALUE`; SQLSTATE: HY000

Message: Cannot store an array or an object in a scalar key part of the index '%s'.

`ER_WRONG_MVI_VALUE` was added in 8.0.16.

- Error number: 3909; Symbol: `ER_WARN_FUNC_INDEX_NOT_APPLICABLE`; SQLSTATE: HY000

Message: Cannot use functional index '%s' due to type or collation conversion.

`ER_WARN_FUNC_INDEX_NOT_APPLICABLE` was added in 8.0.16.

-
- Error number: 3910; Symbol: [ER_GRP_RPL_UDF_ERROR](#); SQLSTATE: HY000
Message: The function '%s' failed. %s
[ER_GRP_RPL_UDF_ERROR](#) was added in 8.0.13.
 - Error number: 3911; Symbol: [ER_UPDATE_GTID_PURGED_WITH_GR](#); SQLSTATE: HY000
Message: Cannot update GTID_PURGED with the Group Replication plugin running
[ER_UPDATE_GTID_PURGED_WITH_GR](#) was added in 8.0.12.
 - Error number: 3912; Symbol: [ER_GROUPING_ON_TIMESTAMP_IN_DST](#); SQLSTATE: HY000
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.
[ER_GROUPING_ON_TIMESTAMP_IN_DST](#) was added in 8.0.17.
 - Error number: 3913; Symbol: [ER_TABLE_NAME_CAUSES_TOO_LONG_PATH](#); SQLSTATE: HY000
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.
[ER_TABLE_NAME_CAUSES_TOO_LONG_PATH](#) was added in 8.0.4.
 - Error number: 3914; Symbol: [ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: HY000
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'
[ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE](#) was added in 8.0.16.
 - Error number: 3916; Symbol: [ER_DA_GRP_RPL_STARTED_AUTO_REJOIN](#); SQLSTATE: HY000
Message: Started auto-rejoin procedure attempt %lu of %lu
[ER_DA_GRP_RPL_STARTED_AUTO_REJOIN](#) was added in 8.0.17.
 - Error number: 3917; Symbol: [ER_SYSVAR_CHANGE_DURING_QUERY](#); SQLSTATE: HY000
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.
[ER_SYSVAR_CHANGE_DURING_QUERY](#) was added in 8.0.18.
 - Error number: 3918; Symbol: [ER_GLOBSTAT_CHANGE_DURING_QUERY](#); SQLSTATE: HY000
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.
[ER_GLOBSTAT_CHANGE_DURING_QUERY](#) was added in 8.0.18.
 - Error number: 3919; Symbol: [ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE](#); SQLSTATE: HY000
Message: The START GROUP_REPLICATION command failed to start its message service.
[ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE](#) was added in 8.0.18.
 - Error number: 3920; Symbol: [ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT](#); SQLSTATE: HY000
Message: Invalid MASTER_COMPRESSION_ALGORITHMS '%s' for channel '%s'.
[ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT](#) was added in 8.0.18, removed after 8.0.32.
-

-
- Error number: 3920; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid SOURCE_COMPRESSION_ALGORITHMS '%s' for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.33.
 - Error number: 3921; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid MASTER_ZSTD_COMPRESSION_LEVEL %u for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18, removed after 8.0.32.
 - Error number: 3921; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid SOURCE_ZSTD_COMPRESSION_LEVEL %u for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.33.
 - Error number: 3922; Symbol: `ER_WRONG_COMPRESSION_ALGORITHM_CLIENT`; SQLSTATE: `HY000`

Message: Invalid compression algorithm '%s'.

`ER_WRONG_COMPRESSION_ALGORITHM_CLIENT` was added in 8.0.18.
 - Error number: 3923; Symbol: `ER_WRONG_COMPRESSION_LEVEL_CLIENT`; SQLSTATE: `HY000`

Message: Invalid zstd compression level for algorithm '%s'.

`ER_WRONG_COMPRESSION_LEVEL_CLIENT` was added in 8.0.18.
 - Error number: 3924; Symbol: `ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: `HY000`

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.18, removed after 8.0.32.
 - Error number: 3924; Symbol: `ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT`; SQLSTATE: `HY000`

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

`ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT` was added in 8.0.33.
 - Error number: 3925; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS`; SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE_CHECKS_USER.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS` was added in 8.0.18.
 - Error number: 3926; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST` was added in 8.0.18.

- Error number: 3927; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: HY000

Message: Invalid, corrupted `PRIVILEGE_CHECKS_USER` was found in the replication configuration repository for channel '%s'. Use `CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER` to correct the configuration.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT` was added in 8.0.18.

- Error number: 3928; Symbol: `ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV`; SQLSTATE: HY000

Message: `PRIVILEGE_CHECKS_USER` for replication channel '%s' was set to '%s'@'%s', but this user does not have `REPLICATION_APPLIER` privilege.

`ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV` was added in 8.0.18.

- Error number: 3929; Symbol: `ER_WARN_DA_PRIVILEGE_NOT_REGISTERED`; SQLSTATE: HY000

Message: Dynamic privilege '%s' is not registered with the server.

`ER_WARN_DA_PRIVILEGE_NOT_REGISTERED` was added in 8.0.18.

- Error number: 3930; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_INVALID`; SQLSTATE: HY000

Message: Function '%s' failed because key is invalid.

`ER_CLIENT_KEYRING_UDF_KEY_INVALID` was added in 8.0.19.

- Error number: 3931; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID`; SQLSTATE: HY000

Message: Function '%s' failed because key type is invalid.

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID` was added in 8.0.19.

- Error number: 3932; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG`; SQLSTATE: HY000

Message: Function '%s' failed because key length is too long.

`ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG` was added in 8.0.19.

- Error number: 3933; Symbol: `ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG`; SQLSTATE: HY000

Message: Function '%s' failed because key type is too long.

`ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG` was added in 8.0.19.

- Error number: 3934; Symbol: `ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT`; SQLSTATE: HY000

Message: %s.

`ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT` was added in 8.0.19.

- Error number: 3935; Symbol: `ER_DA_UDF_INVALID_CHARSET_SPECIFIED`; SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

`ER_DA_UDF_INVALID_CHARSET_SPECIFIED` was added in 8.0.19.

- Error number: 3936; Symbol: `ER_DA_UDF_INVALID_CHARSET`; SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

`ER_DA_UDF_INVALID_CHARSET` was added in 8.0.19.

- Error number: 3937; Symbol: `ER_DA_UDF_INVALID_COLLATION`; SQLSTATE: HY000

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

`ER_DA_UDF_INVALID_COLLATION` was added in 8.0.19.

- Error number: 3938; Symbol: `ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE`; SQLSTATE: HY000

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

`ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE` was added in 8.0.19.

- Error number: 3939; Symbol: `ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME`; SQLSTATE: HY000

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

`ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME` was added in 8.0.19.

- Error number: 3940; Symbol: `ER_CONSTRAINT_NOT_FOUND`; SQLSTATE: HY000

Message: Constraint '%s' does not exist.

`ER_CONSTRAINT_NOT_FOUND` was added in 8.0.19.

- Error number: 3941; Symbol: `ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED`; SQLSTATE: HY000

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

`ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED` was added in 8.0.19.

- Error number: 3942; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS`; SQLSTATE: HY000

Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

`ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS` was added in 8.0.19.

- Error number: 3943; Symbol: `ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT`; SQLSTATE: HY000

Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

`ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT` was added in 8.0.19.

-
- Error number: 3944; Symbol: [ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)
Message: The query does not comply with variable `require_row_format` restrictions.
[ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT](#) was added in 8.0.19.
 - Error number: 3945; Symbol: [ER_REQUIRE_ROW_FORMAT_INVALID_VALUE](#); SQLSTATE: [HY000](#)
Message: The requested value %s is invalid for `REQUIRE_ROW_FORMAT`, must be either 0 or 1.
[ER_REQUIRE_ROW_FORMAT_INVALID_VALUE](#) was added in 8.0.19.
 - Error number: 3946; Symbol: [ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY](#); SQLSTATE: [HY000](#)
Message: Failed to acquire lock on user management service, unable to determine if role `%s` @ `%s` is mandatory
[ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY](#) was added in 8.0.19.
 - Error number: 3947; Symbol: [ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST](#); SQLSTATE: [HY000](#)
Message: Failed to acquire lock on user management service, unable to fetch mandatory role list
[ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST](#) was added in 8.0.19.
 - Error number: 3948; Symbol: [ER_CLIENT_LOCAL_FILES_DISABLED](#); SQLSTATE: [42000](#)
Message: Loading local data is disabled; this must be enabled on both the client and server sides
[ER_CLIENT_LOCAL_FILES_DISABLED](#) was added in 8.0.19.
 - Error number: 3949; Symbol: [ER_IMP_INCOMPATIBLE_CFG_VERSION](#); SQLSTATE: [HY000](#)
Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)
[ER_IMP_INCOMPATIBLE_CFG_VERSION](#) was added in 8.0.19.
 - Error number: 3950; Symbol: [ER_DA_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory
[ER_DA_OOM](#) was added in 8.0.19.
 - Error number: 3951; Symbol: [ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET](#); SQLSTATE: [HY000](#)
Message: Character set can be set only for the UDF argument type `STRING`.
[ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET](#) was added in 8.0.19.
 - Error number: 3952; Symbol: [ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET](#); SQLSTATE: [HY000](#)
Message: Character set can be set only for the UDF `RETURN` type `STRING`.
[ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET](#) was added in 8.0.19.
 - Error number: 3953; Symbol: [ER_MULTIPLE_INTO_CLAUSES](#); SQLSTATE: [HY000](#)
Message: Multiple `INTO` clauses in one query block.

`ER_MULTIPLE INTO CLAUSES` was added in 8.0.19.

- Error number: 3954; Symbol: `ER_MISPLACED INTO`; SQLSTATE: HY000

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

`ER_MISPLACED INTO` was added in 8.0.19.

- Error number: 3955; Symbol: `ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK`; SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

`ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK` was added in 8.0.19.

- Error number: 3956; Symbol: `ER_WARN_DEPRECATED_YEAR_UNSIGNED`; SQLSTATE: HY000

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

`ER_WARN_DEPRECATED_YEAR_UNSIGNED` was added in 8.0.19.

- Error number: 3957; Symbol: `ER_CLONE_NETWORK_PACKET`; SQLSTATE: HY000

Message: Clone needs max_allowed_packet value to be %u or more. Current value is %u

`ER_CLONE_NETWORK_PACKET` was added in 8.0.19.

- Error number: 3958; Symbol: `ER_SDI_OPERATION_FAILED_MISSING_RECORD`; SQLSTATE: HY000

Message: Failed to %s sdi for %s.%s in %s due to missing record.

`ER_SDI_OPERATION_FAILED_MISSING_RECORD` was added in 8.0.19.

- Error number: 3959; Symbol: `ER_DEPENDENT_BY_CHECK_CONSTRAINT`; SQLSTATE: HY000

Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.

`ER_DEPENDENT_BY_CHECK_CONSTRAINT` was added in 8.0.19.

- Error number: 3960; Symbol: `ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP`; SQLSTATE: HY000

Message: This operation cannot be performed while Group Replication is running; run STOP GROUP_REPLICATION first

`ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP` was added in 8.0.20.

- Error number: 3961; Symbol: `ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY`; SQLSTATE: HY000

Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.

`ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY` was added in 8.0.20.

-
- Error number: 3962; Symbol: [ER_WARN_DEPRECATED_INNER_INT0](#); SQLSTATE: HY000

Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.

[ER_WARN_DEPRECATED_INNER_INT0](#) was added in 8.0.20.

- Error number: 3963; Symbol: [ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL](#); SQLSTATE: HY000

Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.

[ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL](#) was added in 8.0.20.

- Error number: 3964; Symbol: [ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS](#); SQLSTATE: HY000

Message: SQL_CALC_FOUND_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.

[ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS](#) was added in 8.0.16.

- Error number: 3965; Symbol: [ER_WARN_DEPRECATED_FOUND_ROWS](#); SQLSTATE: HY000

Message: FOUND_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(*) instead.

[ER_WARN_DEPRECATED_FOUND_ROWS](#) was added in 8.0.16.

- Error number: 3966; Symbol: [ER_MISSING_JSON_VALUE](#); SQLSTATE: 22035

Message: No value was found by '%s' on the specified path.

[ER_MISSING_JSON_VALUE](#) was added in 8.0.21.

- Error number: 3967; Symbol: [ER_MULTIPLE_JSON_VALUES](#); SQLSTATE: 22034

Message: More than one value was found by '%s' on the specified path.

[ER_MULTIPLE_JSON_VALUES](#) was added in 8.0.21.

- Error number: 3968; Symbol: [ER_HOSTNAME_TOO_LONG](#); SQLSTATE: HY000

Message: Hostname cannot be longer than %d characters.

[ER_HOSTNAME_TOO_LONG](#) was added in 8.0.21.

- Error number: 3969; Symbol: [ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY](#); SQLSTATE: HY000

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

[ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY](#) was added in 8.0.21.

- Error number: 3970; Symbol: [ER_GROUP_REPLICATION_USER_EMPTY_MSG](#); SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the username provided for recovery channel is empty.

`ER_GROUP_REPLICATION_USER_EMPTY_MSG` was added in 8.0.21.

- Error number: 3971; Symbol: `ER_GROUP_REPLICATION_USER_MANDATORY_MSG`; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

`ER_GROUP_REPLICATION_USER_MANDATORY_MSG` was added in 8.0.21.

- Error number: 3972; Symbol: `ER_GROUP_REPLICATION_PASSWORD_LENGTH`; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

`ER_GROUP_REPLICATION_PASSWORD_LENGTH` was added in 8.0.21.

- Error number: 3973; Symbol: `ER_SUBQUERY_TRANSFORM_REJECTED`; SQLSTATE: HY000

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery_to_derived' on

`ER_SUBQUERY_TRANSFORM_REJECTED` was added in 8.0.21.

- Error number: 3974; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.

- Error number: 3975; Symbol: `ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: 3976; Symbol: `ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART`; SQLSTATE: HY000

Message: Variable '%s' cannot be set to the value of '%s'. %s

`ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART` was added in 8.0.21.

- Error number: 3977; Symbol: `ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION`; SQLSTATE: HY000

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

`ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION` was added in 8.0.21.

-
- Error number: 3978; Symbol: `ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT`; SQLSTATE: HY000

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

`ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT` was added in 8.0.21.
 - Error number: 3979; Symbol: `ER_NOT_ALLOWED_WITH_START_TRANSACTION`; SQLSTATE: HY000

Message: START TRANSACTION clause cannot be used %s

`ER_NOT_ALLOWED_WITH_START_TRANSACTION` was added in 8.0.21.
 - Error number: 3980; Symbol: `ER_INVALID_JSON_ATTRIBUTE`; SQLSTATE: HY000

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

`ER_INVALID_JSON_ATTRIBUTE` was added in 8.0.21.
 - Error number: 3981; Symbol: `ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED`; SQLSTATE: HY000

Message: Storage engine '%s' does not support ENGINE_ATTRIBUTE.

`ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED` was added in 8.0.21.
 - Error number: 3982; Symbol: `ER_INVALID_USER_ATTRIBUTE_JSON`; SQLSTATE: HY000

Message: The user attribute must be a valid JSON object

`ER_INVALID_USER_ATTRIBUTE_JSON` was added in 8.0.21.
 - Error number: 3983; Symbol: `ER_INNODB_REDO_DISABLED`; SQLSTATE: HY000

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

`ER_INNODB_REDO_DISABLED` was added in 8.0.21.
 - Error number: 3984; Symbol: `ER_INNODB_REDO_ARCHIVING_ENABLED`; SQLSTATE: HY000

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking innodb_redo_log_archive_stop()

`ER_INNODB_REDO_ARCHIVING_ENABLED` was added in 8.0.21.
 - Error number: 3985; Symbol: `ER_MDL_OUT_OF_RESOURCES`; SQLSTATE: HY000

Message: Not enough resources to complete lock request.

`ER_MDL_OUT_OF_RESOURCES` was added in 8.0.21.
 - Error number: 3986; Symbol: `ER_IMPLICIT_COMPARISON_FOR_JSON`; SQLSTATE: HY000

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with JSON_VALUE RETURNING

`ER_IMPLICIT_COMPARISON_FOR_JSON` was added in 8.0.21.
 - Error number: 3987; Symbol: `ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET`; SQLSTATE: HY000

Message: The function %s does not support the character set '%s'.

[ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET](#) was added in 8.0.21.

- Error number: 3988; Symbol: [ER_IMPOSSIBLE_STRING_CONVERSION](#); SQLSTATE: HY000

Message: Conversion from collation %s into %s impossible for %s

[ER_IMPOSSIBLE_STRING_CONVERSION](#) was added in 8.0.22.

- Error number: 3989; Symbol: [ER_SCHEMA_READ_ONLY](#); SQLSTATE: HY000

Message: Schema '%s' is in read only mode.

[ER_SCHEMA_READ_ONLY](#) was added in 8.0.22.

- Error number: 3990; Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF](#); SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when @@GLOBAL.GTID_MODE = ON.

[ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF](#) was added in 8.0.22.

- Error number: 3991; Symbol: [ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF](#); SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when SOURCE_AUTO_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.

[ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF](#) was added in 8.0.22.

- Error number: 3992; Symbol: [ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: HY000

Message: The @@GLOBAL.GTID_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

[ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF](#) was added in 8.0.22.

- Error number: 3993; Symbol: [ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

[ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF](#) was added in 8.0.22.

- Error number: 3994; Symbol: [ER_INVALID_PARAMETER_USE](#); SQLSTATE: HY000

Message: Invalid use of parameters in '%s'

[ER_INVALID_PARAMETER_USE](#) was added in 8.0.22.

- Error number: 3995; Symbol: [ER_CHARACTER_SET_MISMATCH](#); SQLSTATE: HY000

Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.

[ER_CHARACTER_SET_MISMATCH](#) was added in 8.0.22.

-
- Error number: 3996; Symbol: `ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED`; SQLSTATE: HY000
Message: Changing %s not supported on this platform. Falling back to the default.
`ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED` was added in 8.0.22.
 - Error number: 3997; Symbol: `ER_INVALID_TIME_ZONE_INTERVAL`; SQLSTATE: HY000
Message: Invalid time zone interval: '%s'
`ER_INVALID_TIME_ZONE_INTERVAL` was added in 8.0.22.
 - Error number: 3998; Symbol: `ER_INVALID_CAST`; SQLSTATE: HY000
Message: Cannot cast value to %s.
`ER_INVALID_CAST` was added in 8.0.22.
 - Error number: 3999; Symbol: `ER_HYPERGRAPH_NOT_SUPPORTED_YET`; SQLSTATE: 42000
Message: The hypergraph optimizer does not yet support '%s'
`ER_HYPERGRAPH_NOT_SUPPORTED_YET` was added in 8.0.22.
 - Error number: 4000; Symbol: `ER_WARN_HYPERGRAPH_EXPERIMENTAL`; SQLSTATE: HY000
Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.
`ER_WARN_HYPERGRAPH_EXPERIMENTAL` was added in 8.0.22.
 - Error number: 4001; Symbol: `ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED`; SQLSTATE: HY000
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.
`ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED` was added in 8.0.22.
 - Error number: 4002; Symbol: `ER_DA_ERROR_LOG_TABLE_DISABLED`; SQLSTATE: HY000
Message: None of the log-sinks selected in @@global.log_error_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance_schema.error_log. To change this, add a log-sink that supports the performance schema to @@global.log_error_services.
`ER_DA_ERROR_LOG_TABLE_DISABLED` was added in 8.0.22.
 - Error number: 4003; Symbol: `ER_DA_ERROR_LOG_MULTIPLE_FILTERS`; SQLSTATE: HY000
Message: @@global.log_error_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.
`ER_DA_ERROR_LOG_MULTIPLE_FILTERS` was added in 8.0.22.
 - Error number: 4004; Symbol: `ER_DA_CANT_OPEN_ERROR_LOG`; SQLSTATE: HY000
Message: Could not open file '%s' for error logging%s%s
`ER_DA_CANT_OPEN_ERROR_LOG` was added in 8.0.22.
 - Error number: 4005; Symbol: `ER_USER_REFERENCED_AS_DEFINER`; SQLSTATE: HY000

Message: User %s is referenced as a definer account in %s.

[ER_USER_REFERENCED_AS_DEFINER](#) was added in 8.0.22.

- Error number: 4006; Symbol: [ER_CANNOT_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: HY000

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

[ER_CANNOT_USER_REFERENCED_AS_DEFINER](#) was added in 8.0.22.

- Error number: 4007; Symbol: [ER_REGEX_NUMBER_TOO_BIG](#); SQLSTATE: HY000

Message: Decimal number in regular expression is too large.

[ER_REGEX_NUMBER_TOO_BIG](#) was added in 8.0.22.

- Error number: 4008; Symbol: [ER_SPVAR_NONINTEGER_TYPE](#); SQLSTATE: HY000

Message: The variable "%s" has a non-integer based type

[ER_SPVAR_NONINTEGER_TYPE](#) was added in 8.0.22.

- Error number: 4009; Symbol: [WARN_UNSUPPORTED_ACL_TABLES_READ](#); SQLSTATE: HY000

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

[WARN_UNSUPPORTED_ACL_TABLES_READ](#) was added in 8.0.22.

- Error number: 4010; Symbol: [ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL](#); SQLSTATE: HY000

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

[ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL](#) was added in 8.0.22.

- Error number: 4011; Symbol: [ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT](#); SQLSTATE: HY000

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

[ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT](#) was added in 8.0.23.

- Error number: 4012; Symbol: [ER_STARTING_REPLICA_MONITOR_IO_THREAD](#); SQLSTATE: HY000

Message: The Replica Monitor thread failed to start.

[ER_STARTING_REPLICA_MONITOR_IO_THREAD](#) was added in 8.0.23.

- Error number: 4013; Symbol: [ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON](#); SQLSTATE: HY000

Message: Replication cannot start%s with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID> as this server uses @@GLOBAL.GTID_MODE <> ON.

[ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON](#) was added in 8.0.23.

- Error number: 4014; Symbol: [ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION](#); SQLSTATE: HY000

Message: The options `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` and `SOURCE_AUTO_POSITION = 1` cannot be used together.

`ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION` was added in 8.0.23.

- Error number: 4015; Symbol: `ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON`; SQLSTATE: HY000

Message: `CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because `@@GLOBAL.GTID_MODE <> ON`.

`ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON` was added in 8.0.23.

- Error number: 4016; Symbol: `ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`; SQLSTATE: HY000

Message: The value of `sql_slave_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

`ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.23, removed after 8.0.25.

- Error number: 4016; Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`; SQLSTATE: HY000

Message: The value of `sql_replica_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

`ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON` was added in 8.0.26.

- Error number: 4017; Symbol: `ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID`; SQLSTATE: HY000

Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.

`ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID` was added in 8.0.23.

- Error number: 4018; Symbol: `ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS`; SQLSTATE: HY000

Message: `WAIT_UNTIL_SQL_THREAD_AFTER_GTIDS` cannot be used on a channel configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`

`ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS` was added in 8.0.23.

-
- Error number: 4019; Symbol:

`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID`; SQLSTATE: HY000

Message: The SQL_AFTER_GTIDS or SQL_BEFORE_GTIDS clauses for START REPLICA cannot be used when the replication channel is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>.

`ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID` was added in 8.0.23.

- Error number: 4020; Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: HY000

Message: Replication '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_group_name

`ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME` was added in 8.0.23.

- Error number: 4021; Symbol: `ER_CANT_USE_SAME_UUID_AS_GROUP_NAME`; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group_replication_group_name.

`ER_CANT_USE_SAME_UUID_AS_GROUP_NAME` was added in 8.0.23.

- Error number: 4022; Symbol: `ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING`; SQLSTATE: HY000

Message: The group_replication_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

`ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING` was added in 8.0.23.

- Error number: 4023; Symbol: `ER_INNO_DB_INVALID_AUTOEXTEND_SIZE_VALUE`; SQLSTATE: HY000

Message: AUTOEXTEND_SIZE should be a multiple of %uM

`ER_INNO_DB_INVALID_AUTOEXTEND_SIZE_VALUE` was added in 8.0.23.

- Error number: 4024; Symbol: `ER_INNO_DB_INCOMPATIBLE_WITH_TABLESPACE`; SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces

`ER_INNO_DB_INCOMPATIBLE_WITH_TABLESPACE` was added in 8.0.23.

- Error number: 4025; Symbol: `ER_INNO_DB_AUTOEXTEND_SIZE_OUT_OF_RANGE`; SQLSTATE: HY000

Message: AUTOEXTEND_SIZE value should be between %uM and %uM

`ER_INNO_DB_AUTOEXTEND_SIZE_OUT_OF_RANGE` was added in 8.0.23.

- Error number: 4026; Symbol: `ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE`; SQLSTATE: HY000

Message: AUTOEXTEND_SIZE clause is not valid for %s tablespace.

`ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE` was added in 8.0.23.

-
- Error number: 4027; Symbol: `ER_ROLE_GRANTED_TO_ITSELF`; SQLSTATE: HY000
Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop
`ER_ROLE_GRANTED_TO_ITSELF` was added in 8.0.23.
 - Error number: 4028; Symbol: `ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN`; SQLSTATE: HY000
Message: A table must have at least one visible column.
`ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN` was added in 8.0.23.
 - Error number: 4029; Symbol: `ER_INNODB_COMPRESSION_FAILURE`; SQLSTATE: HY000
Message: Compression failed with the following error : %s
`ER_INNODB_COMPRESSION_FAILURE` was added in 8.0.23.
 - Error number: 4030; Symbol: `ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE`; SQLSTATE: HY000
Message: The parameter network_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network_namespace parameter.
`ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE` was added in 8.0.23.
 - Error number: 4031; Symbol: `ER_CLIENT_INTERACTION_TIMEOUT`; SQLSTATE: HY000
Message: The client was disconnected by the server because of inactivity. See wait_timeout and interactive_timeout for configuring this behavior.
`ER_CLIENT_INTERACTION_TIMEOUT` was added in 8.0.24.
 - Error number: 4032; Symbol: `ER_INVALID_CAST_TO_GEOMETRY`; SQLSTATE: 22S01
Message: Invalid cast from %s to %s.
`ER_INVALID_CAST_TO_GEOMETRY` was added in 8.0.24.
 - Error number: 4033; Symbol: `ER_INVALID_CAST_POLYGON_RING_DIRECTION`; SQLSTATE: 22S04
Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.
`ER_INVALID_CAST_POLYGON_RING_DIRECTION` was added in 8.0.24.
 - Error number: 4034; Symbol: `ER_GIS_DIFFERENT_SRIDS_AGGREGATION`; SQLSTATE: 22S05
Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.
`ER_GIS_DIFFERENT_SRIDS_AGGREGATION` was added in 8.0.24.
 - Error number: 4035; Symbol: `ER_RELOAD_KEYRING_FAILURE`; SQLSTATE: HY000
Message: Keyring reload failed. Please check error log for more details.
`ER_RELOAD_KEYRING_FAILURE` was added in 8.0.24.
 - Error number: 4036; Symbol: `ER_SDI_GET_KEYS_INVALID_TABLESPACE`; SQLSTATE: HY000
Message: Tablespace '%s' is invalid for SDI operations.

`ER_SDI_GET_KEYS_INVALID_TABLESPACE` was added in 8.0.24.

- Error number: 4037; Symbol: `ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE`; SQLSTATE: `HY000`

Message: Value too long setting `SOURCE_COMPRESSION_ALGORITHMS` option to a %d chars long string for channel '%s'.

`ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE` was added in 8.0.24.

- Error number: 4038; Symbol: `ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI`; SQLSTATE: `HY000`

Message: A deprecated TLS version %s is enabled for channel %s. Please use TLSv1.2 or higher.

`ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_CLI` was added in 8.0.26, removed after 8.0.27.

- Error number: 4039; Symbol: `ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: CHANGE REPLICATION SOURCE TO `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` cannot be executed because the UUID value is equal to the `group_replication_view_change_uuid`.

`ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: 4040; Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Replication '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` where the UUID value is equal to the `group_replication_view_change_uuid`

`ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID` was added in 8.0.26.

- Error number: 4041; Symbol: `ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE`; SQLSTATE: `HY000`

Message: Unable to retrieve `group_replication_view_change_uuid` variable during server checks on replication operations.

`ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE` was added in 8.0.26.

- Error number: 4042; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS`; SQLSTATE: `HY000`

Message: Both `audit_log_max_size` and `audit_log_prune_seconds` are set to non-zero. `audit_log_max_size` takes precedence and `audit_log_prune_seconds` is ignored

`ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS` was added in 8.0.26.

- Error number: 4043; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE`; SQLSTATE: `HY000`

Message: `audit_log_rotate_on_size` is not granular enough for the value of `audit_log_max_size` supplied. Should be at least %d times smaller.

`ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE` was added in 8.0.26.

-
- Error number: 4044; Symbol: `ER_KERBEROS_CREATE_USER`; SQLSTATE: HY000

Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.

`ER_KERBEROS_CREATE_USER` was added in 8.0.26.
 - Error number: 4045; Symbol: `ER_INSTALL_PLUGIN_CONFLICT_CLIENT`; SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

`ER_INSTALL_PLUGIN_CONFLICT_CLIENT` was added in 8.0.26.
 - Error number: 4046; Symbol: `ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED`; SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

`ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED` was added in 8.0.26.
 - Error number: 4047; Symbol: `ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED`; SQLSTATE: HY000

Message: The until clause SQL_AFTER_MTS_GAPS is being used for channel '%s' when GTID_MODE = ON and SOURCE_AUTO_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL_BEFORE_GTIDS or SQL_AFTER_GTIDS until clause.

`ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED` was added in 8.0.26.
 - Error number: 4048; Symbol: `ER_INVALID_ASSIGNMENT_TARGET`; SQLSTATE: 42000

Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.

`ER_INVALID_ASSIGNMENT_TARGET` was added in 8.0.26.
 - Error number: 4049; Symbol: `ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY`; SQLSTATE: HY000

Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.

`ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY` was added in 8.0.26.
 - Error number: 4050; Symbol: `ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION`; SQLSTATE: HY000

Message: Unable to propagate the SOURCE_CONNECTION_AUTO_FAILOVER value for channel '%s' to group replication members. Please retry the operation.

`ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION` was added in 8.0.26.
 - Error number: 4051; Symbol: `ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON`; SQLSTATE: HY000

Message: audit_log_format_unix_timestamp is applicable only when audit_log_format = JSON.

`ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON` was added in 8.0.26.
-

-
- Error number: 4052; Symbol: `ER_INVALID_MFA_PLUGIN_SPECIFIED`; SQLSTATE: HY000
Message: Invalid plugin "%s" specified as %d factor during "%s".
`ER_INVALID_MFA_PLUGIN_SPECIFIED` was added in 8.0.27.
 - Error number: 4053; Symbol: `ER_IDENTIFIED_BY_UNSUPPORTED`; SQLSTATE: HY000
Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".
`ER_IDENTIFIED_BY_UNSUPPORTED` was added in 8.0.27.
 - Error number: 4054; Symbol: `ER_INVALID_PLUGIN_FOR_REGISTRATION`; SQLSTATE: HY000
Message: This operation is not supported for plugin "%s".
`ER_INVALID_PLUGIN_FOR_REGISTRATION` was added in 8.0.27.
 - Error number: 4055; Symbol: `ER_PLUGIN_REQUIRES_REGISTRATION`; SQLSTATE: HY000
Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --fido-register-factor command line option to do registration.
`ER_PLUGIN_REQUIRES_REGISTRATION` was added in 8.0.27.
 - Error number: 4056; Symbol: `ER_MFA_METHOD_EXISTS`; SQLSTATE: HY000
Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.
`ER_MFA_METHOD_EXISTS` was added in 8.0.27.
 - Error number: 4057; Symbol: `ER_MFA_METHOD_NOT_EXISTS`; SQLSTATE: HY000
Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.
`ER_MFA_METHOD_NOT_EXISTS` was added in 8.0.27.
 - Error number: 4058; Symbol: `ER_AUTHENTICATION_POLICY_MISMATCH`; SQLSTATE: HY000
Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication_policy system variable.
`ER_AUTHENTICATION_POLICY_MISMATCH` was added in 8.0.27.
 - Error number: 4059; Symbol: `ER_PLUGIN_REGISTRATION_DONE`; SQLSTATE: HY000
Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.
`ER_PLUGIN_REGISTRATION_DONE` was added in 8.0.27.
 - Error number: 4060; Symbol: `ER_INVALID_USER_FOR_REGISTRATION`; SQLSTATE: HY000
Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.
`ER_INVALID_USER_FOR_REGISTRATION` was added in 8.0.27.
 - Error number: 4061; Symbol: `ER_USER_REGISTRATION_FAILED`; SQLSTATE: HY000
Message: Authentication plugin's registration failed.

`ER_USER_REGISTRATION_FAILED` was added in 8.0.27.

- Error number: 4062; Symbol: `ER_MFA_METHODS_INVALID_ORDER`; SQLSTATE: HY000

Message: %d factor authentication method should be added before %d factor authentication method.

`ER_MFA_METHODS_INVALID_ORDER` was added in 8.0.27.

- Error number: 4063; Symbol: `ER_MFA_METHODS_IDENTICAL`; SQLSTATE: HY000

Message: Authentication factor should be different.

`ER_MFA_METHODS_IDENTICAL` was added in 8.0.27.

- Error number: 4064; Symbol: `ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER`; SQLSTATE: HY000

Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

`ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER` was added in 8.0.27.

- Error number: 4065; Symbol: `ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY`; SQLSTATE: HY000

Message: GTID_ONLY cannot be enabled for replication channel '%s'. You need GTID_MODE = ON, SOURCE_AUTO_POSITION = 1 and REQUIRE_ROW_FORMAT = 1.

`ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY` was added in 8.0.27.

- Error number: 4066; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY`; SQLSTATE: HY000

Message: REQUIRE_ROW_FORMAT cannot be disabled for replication channel '%s' when GTID_ONLY=1.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY` was added in 8.0.27.

- Error number: 4067; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY`; SQLSTATE: HY000

Message: SOURCE_AUTO_POSITION cannot be disabled for replication channel '%s' when GTID_ONLY=1.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY` was added in 8.0.27.

- Error number: 4068; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS`; SQLSTATE: HY000

Message: When disabling GTID_ONLY and SOURCE_AUTO_POSITION FOR CHANNEL '%s' you must provide SOURCE_LOG_FILE and SOURCE_LOG_POS as source positions are invalid.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS` was added in 8.0.27.

-
- Error number: 4069; Symbol:

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS`; SQLSTATE: HY000

Message: When disabling SOURCE_AUTO_POSITION FOR CHANNEL '%s' you must provide SOURCE_LOG_FILE and SOURCE_LOG_POS as source positions are invalid.

`ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS` was added in 8.0.27.

- Error number: 4070; Symbol:

`ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000

Message: When configuring a group replication channel you must do it when GTID_MODE = ON.

`ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.

- Error number: 4071; Symbol: `ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON`; SQLSTATE: HY000

Message: Replication cannot start%s with GTID_ONLY = 1 as this server uses @@GLOBAL.GTID_MODE <> ON.

`ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON` was added in 8.0.27.

- Error number: 4072; Symbol:

`ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS`; SQLSTATE: HY000

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

`ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS` was added in 8.0.27.

- Error number: 4073; Symbol: `ER_DA_SSL_FIPS_MODE_ERROR`; SQLSTATE: HY000

Message: SSL fips mode error: %s

`ER_DA_SSL_FIPS_MODE_ERROR` was added in 8.0.27.

- Error number: 4074; Symbol: `ER_VALUE_OUT_OF_RANGE`; SQLSTATE: HY000

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.

`ER_VALUE_OUT_OF_RANGE` was added in 8.0.27.

- Error number: 4075; Symbol: `ER_FULLTEXT_WITH_ROLLUP`; SQLSTATE: HY000

Message: MATCH does not support ROLLUP columns.

`ER_FULLTEXT_WITH_ROLLUP` was added in 8.0.28.

- Error number: 4076; Symbol: `ER_REGEXP_MISSING_RESOURCE`; SQLSTATE: HY000

Message: Missing locale resource in regular expression library.

`ER_REGEXP_MISSING_RESOURCE` was added in 8.0.28.

-
- Error number: 4077; Symbol: [ER_WARN_REGEXPT_USING_DEFAULT](#); SQLSTATE: HY000
Message: Regular expression library used default (root) locale.
[ER_WARN_REGEXPT_USING_DEFAULT](#) was added in 8.0.28.
 - Error number: 4078; Symbol: [ER_REGEXPT_MISSING_FILE](#); SQLSTATE: HY000
Message: Missing data file in regular expression library.
[ER_REGEXPT_MISSING_FILE](#) was added in 8.0.28.
 - Error number: 4079; Symbol: [ER_WARN_DEPRECATED_COLLATION](#); SQLSTATE: HY000
Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.
[ER_WARN_DEPRECATED_COLLATION](#) was added in 8.0.28.
 - Error number: 4080; Symbol: [ER_CONCURRENT_PROCEDURE_USAGE](#); SQLSTATE: HY000
Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.
[ER_CONCURRENT_PROCEDURE_USAGE](#) was added in 8.0.28.
 - Error number: 4081; Symbol: [ER_DA_GLOBAL_CONN_LIMIT](#); SQLSTATE: HY000
Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.
[ER_DA_GLOBAL_CONN_LIMIT](#) was added in 8.0.28.
 - Error number: 4082; Symbol: [ER_DA_CONN_LIMIT](#); SQLSTATE: HY000
Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.
[ER_DA_CONN_LIMIT](#) was added in 8.0.28.
 - Error number: 4083; Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE_INSTANT](#); SQLSTATE: HY000
Message: Need to rebuild the table to change column type
[ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE_INSTANT](#) was added in 8.0.28.
 - Error number: 4084; Symbol: [ER_WARN_SF_UDF_NAME_COLLISION](#); SQLSTATE: HY000
Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.
[ER_WARN_SF_UDF_NAME_COLLISION](#) was added in 8.0.28.
 - Error number: 4085; Symbol: [ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#); SQLSTATE: HY000
Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.
[ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#) was added in 8.0.28.
 - Error number: 4086; Symbol: [ER_TOO_MANY_WINDOWS](#); SQLSTATE: HY000

Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.

[ER_TOO_MANY_WINDOWS](#) was added in 8.0.28.

- Error number: 4087; Symbol: [ER_MYSQLBACKUP_CLIENT_MSG](#); SQLSTATE: HY000

Message: %s

[ER_MYSQLBACKUP_CLIENT_MSG](#) was added in 8.0.28.

- Error number: 4088; Symbol: [ER_COMMENT_CONTAINS_INVALID_STRING](#); SQLSTATE: HY000

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

[ER_COMMENT_CONTAINS_INVALID_STRING](#) was added in 8.0.28.

- Error number: 4089; Symbol: [ER_DEFINITION_CONTAINS_INVALID_STRING](#); SQLSTATE: HY000

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

[ER_DEFINITION_CONTAINS_INVALID_STRING](#) was added in 8.0.28.

- Error number: 4090; Symbol: [ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_NEXT](#); SQLSTATE: HY000

Message: Can't execute the given command when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

[ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_NEXT](#) was added in 8.0.28.

- Error number: 4091; Symbol: [ER_XA_TEMP_TABLE](#); SQLSTATE: HY000

Message: XA: Temporary tables cannot be accessed inside XA transactions when xa_detach_on_prepare=ON

[ER_XA_TEMP_TABLE](#) was added in 8.0.29.

- Error number: 4092; Symbol: [ER_INNODB_MAX_ROW_VERSION](#); SQLSTATE: HY000

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

[ER_INNODB_MAX_ROW_VERSION](#) was added in 8.0.29.

- Error number: 4093; Symbol: [ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE](#); SQLSTATE: HY000

Message: Column can't be added with ALGORITHM=INSTANT as after this max possible row size crosses max permissible row size. Try ALGORITHM=INPLACE/COPY.

[ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE](#) was added in 8.0.29, removed after 8.0.31.

- Error number: 4094; Symbol: [ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING](#); SQLSTATE: HY000

Message: All queries have been blocked while function 'group_replication_set_as_primary()' is executing. Please refer timeout parameter of function 'group_replication_set_as_primary()'.

[ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING](#) was added in 8.0.29.

-
- Error number: 4095; Symbol: `ER_WARN_DEPRECATED_DATETIME_DELIMITER`; SQLSTATE: `HY000`

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.

`ER_WARN_DEPRECATED_DATETIME_DELIMITER` was added in 8.0.29.
 - Error number: 4096; Symbol: `ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER`; SQLSTATE: `HY000`

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.

`ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER` was added in 8.0.29.
 - Error number: 4097; Symbol: `ER_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

`ER_CANNOT_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.
 - Error number: 4098; Symbol: `ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

`ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.
 - Error number: 4099; Symbol: `ER_WARN_TRG_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: Trigger '%s' already exists on the table '%s'. '%s'.

`ER_WARN_TRG_ALREADY_EXISTS` was added in 8.0.29.
 - Error number: 4100; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE`; SQLSTATE: `HY000`

Message: Trigger '%s'. '%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.

`ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE` was added in 8.0.29.
 - Error number: 4101; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION`; SQLSTATE: `HY000`

Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.

`ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION` was added in 8.0.29.
 - Error number: 4102; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN_ERROR`; SQLSTATE: `HY000`

Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.

`ER_SET_PASSWORD_AUTH_PLUGIN_ERROR` was added in 8.0.29.
 - Error number: 4105; Symbol: `ER_SRS_INVALID_LATITUDE_OF_ORIGIN`; SQLSTATE: `SR002`

Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.

[ER_SRS_INVALID_LATITUDE_OF_ORIGIN](#) was added in 8.0.30.

- Error number: [4106](#); Symbol: [ER_SRS_INVALID_LONGITUDE_OF_ORIGIN](#); SQLSTATE: [SR002](#)

Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.

[ER_SRS_INVALID_LONGITUDE_OF_ORIGIN](#) was added in 8.0.30.

- Error number: [4107](#); Symbol: [ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT](#); SQLSTATE: [SR002](#)

Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".

[ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT](#) was added in 8.0.30.

- Error number: [4108](#); Symbol: [ER_GIPK_COLUMN_EXISTS](#); SQLSTATE: [HY000](#)

Message: Failed to generate invisible primary key. Column 'my_row_id' already exists.

[ER_GIPK_COLUMN_EXISTS](#) was added in 8.0.30.

- Error number: [4109](#); Symbol: [ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS](#); SQLSTATE: [HY000](#)

Message: Failed to generate invisible primary key. Auto-increment column already exists.

[ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS](#) was added in 8.0.30.

- Error number: [4110](#); Symbol: [ER_GIPK_COLUMN_ALTER_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Altering generated invisible primary key column 'my_row_id' is not allowed.

[ER_GIPK_COLUMN_ALTER_NOT_ALLOWED](#) was added in 8.0.30.

- Error number: [4111](#); Symbol: [ER_DROP_PK_COLUMN_TO_DROP_GIPK](#); SQLSTATE: [HY000](#)

Message: Please drop primary key column to be able to drop generated invisible primary key.

[ER_DROP_PK_COLUMN_TO_DROP_GIPK](#) was added in 8.0.30.

- Error number: [4112](#); Symbol: [ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR](#); SQLSTATE: [HY000](#)

Message: Generating an invisible primary key for a table created using CREATE TABLE ... SELECT ... is disallowed when binlog_format=STATEMENT. It cannot be guaranteed that the SELECT retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use binlog_format=ROW or MIXED to execute this statement.

[ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR](#) was added in 8.0.30.

- Error number: [4113](#); Symbol: [ER_DA_EXPIRE_LOGS_DAYS_IGNORED](#); SQLSTATE: [HY000](#)

Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. To set one, first unset the other by setting it to 0.

[ER_DA_EXPIRE_LOGS_DAYS_IGNORED](#) was added in 8.0.30.

- Error number: [4114](#); Symbol: [ER_CTE_RECURSIVE_NOT_UNION](#); SQLSTATE: [HY000](#)

Message: Recursive table reference in EXCEPT or INTERSECT operand is not allowed.

[ER_CTE_RECURSIVE_NOT_UNION](#) was added in 8.0.31.

- Error number: [4115](#); Symbol: [ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)

Message: Error when trying to fetch information from security context object, when trying to connect the server.

[ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX](#) was added in 8.0.31.

- Error number: [4116](#); Symbol: [ER_COMMAND_SERVICE_BACKEND_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in command service backend interface, because of : "%s"

[ER_COMMAND_SERVICE_BACKEND_FAILED](#) was added in 8.0.31.

- Error number: [4117](#); Symbol: [ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

[ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#) was added in 8.0.31.

- Error number: [4118](#); Symbol: [ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE](#); SQLSTATE: [HY000](#)

Message: The 'SET GLOBAL group_replication_force_members=%s' command encountered a failure. %s

[ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE](#) was added in 8.0.31.

- Error number: [4119](#); Symbol: [ER_WARN_DEPRECATED_IDENT](#); SQLSTATE: [HY000](#)

Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.

[ER_WARN_DEPRECATED_IDENT](#) was added in 8.0.31.

- Error number: [4120](#); Symbol: [ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: Max number of duplicate rows in INTERSECT ALL exceeded.

[ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED](#) was added in 8.0.31.

- Error number: [4121](#); Symbol: [ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT](#); SQLSTATE: [HY000](#)

Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group

[ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT](#) was added in 8.0.31.

- Error number: [4122](#); Symbol: [ER_BAD_TIMESTAMP_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid timestamp format in %s udf

[ER_BAD_TIMESTAMP_FORMAT](#) was added in 8.0.31.

- Error number: [4123](#); Symbol: [ER_SHAPE_PREDICTION_UDF](#); SQLSTATE: [HY000](#)

Message: SHAPE_PREDICTION UDF %s got error because of %s.

[ER_SHAPE_PRIDITION_UDF](#) was added in 8.0.31.

- Error number: [4124](#); Symbol: [ER_SRS_INVALID_HEIGHT](#); SQLSTATE: [SR002](#)

Message: Height parameter must be non negative.

[ER_SRS_INVALID_HEIGHT](#) was added in 8.0.32.

- Error number: [4125](#); Symbol: [ER_SRS_INVALID_SCALING](#); SQLSTATE: [SR002](#)

Message: Scaling parameter must be non negative.

[ER_SRS_INVALID_SCALING](#) was added in 8.0.32.

- Error number: [4126](#); Symbol: [ER_SRS_INVALID_ZONE_WIDTH](#); SQLSTATE: [SR002](#)

Message: Zone width parameter must be an integer between 1-60.

[ER_SRS_INVALID_ZONE_WIDTH](#) was added in 8.0.32.

- Error number: [4127](#); Symbol: [ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A](#); SQLSTATE: [SR002](#)

Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).

[ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A](#) was added in 8.0.32.

- Error number: [4128](#); Symbol: [ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION](#); SQLSTATE: [HY000](#)

Message: The client is using a deprecated CLIENT_NO_SCHEMA client option. CLIENT_NO_SCHEMA will be removed in a future release.

[ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION](#) was added in 8.0.32.

- Error number: [4129](#); Symbol: [ER_TABLE_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is not empty.

[ER_TABLE_NOT_EMPTY](#) was added in 8.0.32.

- Error number: [4130](#); Symbol: [ER_TABLE_NO_PRIMARY_KEY](#); SQLSTATE: [HY000](#)

Message: Table '%s' has no primary key.

[ER_TABLE_NO_PRIMARY_KEY](#) was added in 8.0.32.

- Error number: [4131](#); Symbol: [ER_TABLE_IN_SHARED_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Table '%s' is in a shared tablespace.

[ER_TABLE_IN_SHARED_TABLESPACE](#) was added in 8.0.32.

- Error number: [4132](#); Symbol: [ER_INDEX_OTHER_THAN_PK](#); SQLSTATE: [HY000](#)

Message: Table '%s' has indexes other than primary key.

[ER_INDEX_OTHER_THAN_PK](#) was added in 8.0.32.

- Error number: [4133](#); Symbol: [ER_LOAD_BULK_DATA_UNSORTED](#); SQLSTATE: [HY000](#)

Message: [IN PRIMARY KEY ORDER] specified but data not sorted: LOAD BULK DATA into table '%s' failed: %s

[ER_LOAD_BULK_DATA_UNSORTED](#) was added in 8.0.32.

- Error number: [4134](#); Symbol: [ER_BULK_EXECUTOR_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk executor error: %s

[ER_BULK_EXECUTOR_ERROR](#) was added in 8.0.32.

- Error number: [4135](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk reader failed to initialize libcurl

[ER_BULK_READER_LIBCURL_INIT_FAILED](#) was added in 8.0.32.

- Error number: [4136](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got libcurl error: %s

[ER_BULK_READER_LIBCURL_ERROR](#) was added in 8.0.32.

- Error number: [4137](#); Symbol: [ER_BULK_READER_SERVER_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error response from server: %ld

[ER_BULK_READER_SERVER_ERROR](#) was added in 8.0.32.

- Error number: [4138](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error in communication with source server, check the error log for additional details.

[ER_BULK_READER_COMMUNICATION_ERROR](#) was added in 8.0.32.

- Error number: [4139](#); Symbol: [ER_BULK_LOAD_DATA_FAILED](#); SQLSTATE: [HY000](#)

Message: Bulk loader failed, mysql_load->load returned an error, check the error log for additional details.

[ER_BULK_LOAD_DATA_FAILED](#) was added in 8.0.32.

- Error number: [4140](#); Symbol: [ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER](#); SQLSTATE: [HY000](#)

Message: CSV column too big for leftover buffer.

[ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER](#) was added in 8.0.32.

- Error number: [4141](#); Symbol: [ER_BULK_LOADER_COMPONENT_ERROR](#); SQLSTATE: [HY000](#)

Message: Bulk loader component error: %s

[ER_BULK_LOADER_COMPONENT_ERROR](#) was added in 8.0.32.

- Error number: [4142](#); Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE](#); SQLSTATE: [HY000](#)

Message: The first file being loaded contained less lines than the ignore clause

[ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE](#) was added in 8.0.32.

-
- Error number: 4143; Symbol: `ER_BULK_PARSER_MISSING_ENCLOSED_BY`; SQLSTATE: HY000

Message: Missing ENCLOSED BY character at row %ld in file '%s'. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

`ER_BULK_PARSER_MISSING_ENCLOSED_BY` was added in 8.0.32.

- Error number: 4144; Symbol: `ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED`; SQLSTATE: HY000

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

`ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED` was added in 8.0.32.

- Error number: 4145; Symbol: `ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED`; SQLSTATE: HY000

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.

`ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED` was added in 8.0.32.

- Error number: 4146; Symbol: `ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT`; SQLSTATE: HY000

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

`ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT` was added in 8.0.32.

- Error number: 4147; Symbol: `ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR`; SQLSTATE: HY000

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

`ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR` was added in 8.0.32.

- Error number: 4148; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY`; SQLSTATE: HY000

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.

`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY` was added in 8.0.32.

- Error number: 4149; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE`; SQLSTATE: HY000

Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.

`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE` was added in 8.0.32.

- Error number: 4150; Symbol: `ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR`; SQLSTATE: HY000

Message: Unexpected characters after column terminator found at row %ld in file '%s'.

`ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR` was added in 8.0.32.

-
- Error number: 4151; Symbol: `ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE`; SQLSTATE: HY000

Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.

`ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE` was added in 8.0.32.
 - Error number: 4152; Symbol: `ER_LOAD_BULK_DATA_FAILED`; SQLSTATE: HY000

Message: LOAD BULK DATA into table '%s' failed: %s

`ER_LOAD_BULK_DATA_FAILED` was added in 8.0.32.
 - Error number: 4153; Symbol: `ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD`; SQLSTATE: HY000

Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

`ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD` was added in 8.0.32.
 - Error number: 4154; Symbol: `ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL`; SQLSTATE: HY000

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

`ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL` was added in 8.0.32.
 - Error number: 4155; Symbol: `ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR`; SQLSTATE: HY000

Message: On a Group Replication channel, setting REQUIRE_TABLE_PRIMARY_KEY_CHECK to 'GENERATE' is not allowed.

`ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR` was added in 8.0.32.
 - Error number: 4156; Symbol: `ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE`; SQLSTATE: HY000

Message: Cannot change the '%s' system variable in read-only mode.

`ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE` was added in 8.0.32.
 - Error number: 4157; Symbol: `ER_INNOBDB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE`; SQLSTATE: HY000

Message: Column can't be added or dropped with ALGORITHM=INSTANT as either max possible row size already crosses max permissible row size or may cross it after add. Try ALGORITHM=INPLACE/COPY.

`ER_INNOBDB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE` was added in 8.0.32.
 - Error number: 4158; Symbol: `ER_INNOBDB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS`; SQLSTATE: HY000

Message: Column can't be added to '%s' with ALGORITHM=INSTANT anymore. Please try ALGORITHM=INPLACE/COPY.

`ER_INNOBDB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS` was added in 8.0.32.
 - Error number: 4159; Symbol: `ER_CANT_SET_PERSISTED`; SQLSTATE: HY000

Message: Failed to set persisted options.

`ER_CANT_SET_PERSISTED` was added in 8.0.2.

- Error number: 4160; Symbol: `ER_INSTALL_COMPONENT_SET_NULL_VALUE`; SQLSTATE: HY000

Message: The value supplied for %s in the SET list cannot be null

`ER_INSTALL_COMPONENT_SET_NULL_VALUE` was added in 8.0.33.

- Error number: 4161; Symbol: `ER_INSTALL_COMPONENT_SET_UNUSED_VALUE`; SQLSTATE: HY000

Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)

`ER_INSTALL_COMPONENT_SET_UNUSED_VALUE` was added in 8.0.33.

- Error number: 4162; Symbol: `ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS`; SQLSTATE: HY000

Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

`ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS` was added in 8.0.33.

- Error number: 4163; Symbol: `ER_USER_LOCK_OVERLONG_NAME`; SQLSTATE: 42000

Message: User-level lock name '%s' should not exceed %d characters.

`ER_USER_LOCK_OVERLONG_NAME` was added in 8.0.34.

- Error number: 4164; Symbol: `ER_WARN_NO_SPACE_VERSION_COMMENT`; SQLSTATE: HY000

Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.

`ER_WARN_NO_SPACE_VERSION_COMMENT` was added in 8.0.34.

- Error number: 4165; Symbol: `ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS`; SQLSTATE: HY000

Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.

`ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS` was added in 8.0.34.

- Error number: 4166; Symbol: `ER_WARN_DEPRECATED_WITH_NOTE`; SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. %s

`ER_WARN_DEPRECATED_WITH_NOTE` was added in 8.0.35.

- Error number: 4167; Symbol: `ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY`; SQLSTATE: HY000

Message: Running recursive calls to SQL execution service is not supported

`ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY` was added in 8.0.43.

- Error number: MY-010000; Symbol: `ER_PARSER_TRACE`; SQLSTATE: XX999

Message: Parser saw: %s

[ER_PARSER_TRACE](#) was added in 8.0.2.

- Error number: [MY-010001](#); Symbol: [ER_BOOTSTRAP_CANT_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle bootstrap (errno: %d)

[ER_BOOTSTRAP_CANT_THREAD](#) was added in 8.0.2.

- Error number: [MY-010002](#); Symbol: [ER_TRIGGER_INVALID_VALUE](#); SQLSTATE: [HY000](#)

Message: Trigger for table '%s'. '%s': invalid %s value (%s).

[ER_TRIGGER_INVALID_VALUE](#) was added in 8.0.2.

- Error number: [MY-010003](#); Symbol: [ER_OPT_WRONG_TREE](#); SQLSTATE: [HY000](#)

Message: Wrong tree: %s

[ER_OPT_WRONG_TREE](#) was added in 8.0.2.

- Error number: [MY-010004](#); Symbol: [ER_DD_FAILSAFE](#); SQLSTATE: [HY000](#)

Message: Error: Invalid %s

[ER_DD_FAILSAFE](#) was added in 8.0.2.

- Error number: [MY-010005](#); Symbol: [ER_DD_NO_WRITES_NO_REPOPULATION](#); SQLSTATE: [HY000](#)

Message: Skip re-populating collations and character sets tables in %s%read-only mode.

[ER_DD_NO_WRITES_NO_REPOPULATION](#) was added in 8.0.2.

- Error number: [MY-010006](#); Symbol: [ER_DD_VERSION_FOUND](#); SQLSTATE: [HY000](#)

Message: Using data dictionary with version '%d'.

[ER_DD_VERSION_FOUND](#) was added in 8.0.2.

- Error number: [MY-010007](#); Symbol: [ER_DD_VERSION_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Installed data dictionary with version %d

[ER_DD_VERSION_INSTALLED](#) was added in 8.0.2.

- Error number: [MY-010008](#); Symbol: [ER_DD_VERSION_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Data Dictionary version '%d' not supported.

[ER_DD_VERSION_UNSUPPORTED](#) was added in 8.0.2.

- Error number: [MY-010009](#); Symbol: [ER_LOG_SYSLOG_FACILITY_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to set syslog facility to "%s", setting to "%s" (%d) instead.

[ER_LOG_SYSLOG_FACILITY_FAIL](#) was added in 8.0.2, removed after 8.0.12.

- Error number: [MY-010010](#); Symbol: [ER_LOG_SYSLOG_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!

[ER_LOG_SYSLOG_CANNOT_OPEN](#) was added in 8.0.2.

- Error number: [MY-010011](#); Symbol: [ER_LOG_SLOW_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: either restart the query logging by using "SET GLOBAL SLOW_QUERY_LOG=ON" or [ER_LOG_SLOW_CANNOT_OPEN](#) was added in 8.0.2.

- Error number: [MY-010012](#); Symbol: [ER_LOG_GENERAL_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: either restart the query logging by using "SET GLOBAL GENERAL_LOG=ON" or [ER_LOG_GENERAL_CANNOT_OPEN](#) was added in 8.0.2.

- Error number: [MY-010013](#); Symbol: [ER_LOG_CANNOT_WRITE](#); SQLSTATE: [HY000](#)

Message: Failed to write to %s: %s

[ER_LOG_CANNOT_WRITE](#) was added in 8.0.2.

- Error number: [MY-010014](#); Symbol: [ER_RPL_ZOMBIE_ENCOUNTERED](#); SQLSTATE: [HY000](#)

Message: While initializing dump thread for replica with %s <%s>, found a zombie dump thread with the same %s. Source is killing the zombie dump thread(%u).

[ER_RPL_ZOMBIE_ENCOUNTERED](#) was added in 8.0.2, removed after 8.0.40.

- Error number: [MY-010015](#); Symbol: [ER_RPL_GTID_TABLE_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.

[ER_RPL_GTID_TABLE_CANNOT_OPEN](#) was added in 8.0.2.

- Error number: [MY-010016](#); Symbol: [ER_SYSTEM_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: System schema directory does not exist.

[ER_SYSTEM_SCHEMA_NOT_FOUND](#) was added in 8.0.2.

- Error number: [MY-010017](#); Symbol: [ER_DD_INIT_UPGRADE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error in initializing dictionary, upgrade will do a cleanup and exit

[ER_DD_INIT_UPGRADE_FAILED](#) was added in 8.0.2.

- Error number: [MY-010018](#); Symbol: [ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION](#); SQLSTATE: [HY000](#)

Message: View '%s'. '%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').

[ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION](#) was added in 8.0.2.

- Error number: [MY-010019](#); Symbol: [ER_DD_VIEW_CANT_ALLOC_CHARSET](#); SQLSTATE: [HY000](#)

Message: Error in allocating memory for character set name for view %s.%s.

[ER_DD_VIEW_CANT_ALLOC_CHARSET](#) was added in 8.0.2.

- Error number: [MY-010020](#); Symbol: [ER_DD_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Data Dictionary initialization failed.

[ER_DD_INIT_FAILED](#) was added in 8.0.2.

-
- Error number: `MY-010021`; Symbol: `ER_DD_UPDATING_PLUGIN_MD_FAILED`; SQLSTATE: `HY000`
Message: Failed to update plugin metadata in dictionary tables.
`ER_DD_UPDATING_PLUGIN_MD_FAILED` was added in 8.0.2.
 - Error number: `MY-010022`; Symbol: `ER_DD_POPULATING_TABLES_FAILED`; SQLSTATE: `HY000`
Message: Failed to Populate DD tables.
`ER_DD_POPULATING_TABLES_FAILED` was added in 8.0.2.
 - Error number: `MY-010023`; Symbol: `ER_DD_VIEW_CANT_CREATE`; SQLSTATE: `HY000`
Message: Error in Creating View %s.%s
`ER_DD_VIEW_CANT_CREATE` was added in 8.0.2.
 - Error number: `MY-010024`; Symbol: `ER_DD_METADATA_NOT_FOUND`; SQLSTATE: `HY000`
Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.
`ER_DD_METADATA_NOT_FOUND` was added in 8.0.2.
 - Error number: `MY-010025`; Symbol: `ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN`; SQLSTATE: `HY000`
Message: Dictionary cache not empty at shutdown.
`ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN` was added in 8.0.2.
 - Error number: `MY-010026`; Symbol: `ER_DD_OBJECT_REMAINS`; SQLSTATE: `HY000`
Message: Dictionary objects used but not released.
`ER_DD_OBJECT_REMAINS` was added in 8.0.2.
 - Error number: `MY-010027`; Symbol: `ER_DD_OBJECT_REMAINS_IN_RELEASER`; SQLSTATE: `HY000`
Message: Dictionary objects left in default releaser.
`ER_DD_OBJECT_REMAINS_IN_RELEASER` was added in 8.0.2.
 - Error number: `MY-010028`; Symbol: `ER_DD_OBJECT_RELEASER_REMAINS`; SQLSTATE: `HY000`
Message: Dictionary object auto releaser not deleted
`ER_DD_OBJECT_RELEASER_REMAINS` was added in 8.0.2.
 - Error number: `MY-010029`; Symbol: `ER_DD_CANT_GET_OBJECT_KEY`; SQLSTATE: `HY000`
Message: Error: Unable to create primary object key
`ER_DD_CANT_GET_OBJECT_KEY` was added in 8.0.2.
 - Error number: `MY-010030`; Symbol: `ER_DD_CANT_CREATE_OBJECT_KEY`; SQLSTATE: `HY000`
Message: Error: Unable to create object key
`ER_DD_CANT_CREATE_OBJECT_KEY` was added in 8.0.2.
 - Error number: `MY-010031`; Symbol: `ER_CANT_CREATE_HANDLE_MGR_THREAD`; SQLSTATE: `HY000`

Message: Can't create handle_manager thread (errno= %d)

[ER_CANT_CREATE_HANDLE_MGR_THREAD](#) was added in 8.0.2.

- Error number: [MY-010032](#); Symbol: [ER_RPL_REPO_HAS_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

[ER_RPL_REPO_HAS_GAPS](#) was added in 8.0.2.

- Error number: [MY-010033](#); Symbol: [ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

[ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#) was added in 8.0.2.

- Error number: [MY-010034](#); Symbol: [ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: Changed ENFORCE_GTID_CONSISTENCY from %s to %s.

[ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#) was added in 8.0.2.

- Error number: [MY-010035](#); Symbol: [ER_CHANGED_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID_MODE from %s to %s.

[ER_CHANGED_GTID_MODE](#) was added in 8.0.2.

- Error number: [MY-010036](#); Symbol: [ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.

[ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#) was added in 8.0.2.

- Error number: [MY-010037](#); Symbol: [ER_DEBUG_SYNC_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s

[ER_DEBUG_SYNC_HIT](#) was added in 8.0.2.

- Error number: [MY-010038](#); Symbol: [ER_DEBUG_SYNC_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s

[ER_DEBUG_SYNC_EXECUTED](#) was added in 8.0.2.

- Error number: [MY-010039](#); Symbol: [ER_DEBUG_SYNC_THREAD_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s

[ER_DEBUG_SYNC_THREAD_MAX](#) was added in 8.0.2.

- Error number: [MY-010040](#); Symbol: [ER_DEBUG_SYNC_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

[ER_DEBUG_SYNC_OOM](#) was added in 8.0.2.

-
- Error number: [MY-010041](#); Symbol: [ER_CANT_INIT_TC_LOG](#); SQLSTATE: [HY000](#)
Message: Can't init tc log
[ER_CANT_INIT_TC_LOG](#) was added in 8.0.2.
 - Error number: [MY-010042](#); Symbol: [ER_EVENT_CANT_INIT_QUEUE](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Can't initialize the execution queue
[ER_EVENT_CANT_INIT_QUEUE](#) was added in 8.0.2.
 - Error number: [MY-010043](#); Symbol: [ER_EVENT_PURGING_QUEUE](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Purging the queue. %u events
[ER_EVENT_PURGING_QUEUE](#) was added in 8.0.2.
 - Error number: [MY-010044](#); Symbol: [ER_EVENT_LAST_EXECUTION](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Last execution of %s.%s. %s
[ER_EVENT_LAST_EXECUTION](#) was added in 8.0.2.
 - Error number: [MY-010045](#); Symbol: [ER_EVENT_MESSAGE_STACK](#); SQLSTATE: [HY000](#)
Message: %*s
[ER_EVENT_MESSAGE_STACK](#) was added in 8.0.2.
 - Error number: [MY-010046](#); Symbol: [ER_EVENT_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: [%s].[%s.%s] event execution failed.
[ER_EVENT_EXECUTION_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010047](#); Symbol: [ER_CANT_INIT_SCHEDULER_THREAD](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Cannot initialize the scheduler thread
[ER_CANT_INIT_SCHEDULER_THREAD](#) was added in 8.0.2.
 - Error number: [MY-010048](#); Symbol: [ER_SCHEDULER_STOPPED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Stopped
[ER_SCHEDULER_STOPPED](#) was added in 8.0.2.
 - Error number: [MY-010049](#); Symbol: [ER_CANT_CREATE_SCHEDULER_THREAD](#); SQLSTATE: [HY000](#)
Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)
[ER_CANT_CREATE_SCHEDULER_THREAD](#) was added in 8.0.2.
 - Error number: [MY-010050](#); Symbol: [ER_SCHEDULER_WAITING](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: Waiting for the scheduler thread to reply
[ER_SCHEDULER_WAITING](#) was added in 8.0.2.
 - Error number: [MY-010051](#); Symbol: [ER_SCHEDULER_STARTED](#); SQLSTATE: [HY000](#)
Message: Event Scheduler: scheduler thread started with id %u

`ER_SCHEDULER_STARTED` was added in 8.0.2.

- Error number: `MY-010052`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT`; SQLSTATE: `HY000`

Message: Event Scheduler: Serious error during getting next event to execute. Stopping

`ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT` was added in 8.0.2.

- Error number: `MY-010053`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER`; SQLSTATE: `HY000`

Message: Event_scheduler::execute_top: Can not create event worker thread (errno=%d). Stopping event scheduler

`ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER` was added in 8.0.2.

- Error number: `MY-010054`; Symbol: `ER_SCHEDULER_KILLING`; SQLSTATE: `HY000`

Message: Event Scheduler: Killing the scheduler thread, thread id %u

`ER_SCHEDULER_KILLING` was added in 8.0.2.

- Error number: `MY-010055`; Symbol: `ER_UNABLE_TO_RESOLVE_IP`; SQLSTATE: `HY000`

Message: IP address '%s' could not be resolved: %s

`ER_UNABLE_TO_RESOLVE_IP` was added in 8.0.2.

- Error number: `MY-010056`; Symbol: `ER_UNABLE_TO_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`

Message: Host name '%s' could not be resolved: %s

`ER_UNABLE_TO_RESOLVE_HOSTNAME` was added in 8.0.2.

- Error number: `MY-010057`; Symbol: `ER_HOSTNAME_RESEMBLES_IPV4`; SQLSTATE: `HY000`

Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.

`ER_HOSTNAME_RESEMBLES_IPV4` was added in 8.0.2.

- Error number: `MY-010058`; Symbol: `ER_HOSTNAME_DOESNT_RESOLVE_TO`; SQLSTATE: `HY000`

Message: Hostname '%s' does not resolve to '%s'.

`ER_HOSTNAME_DOESNT_RESOLVE_TO` was added in 8.0.2.

- Error number: `MY-010059`; Symbol: `ER_ADDRESSES_FOR_HOSTNAME_HEADER`; SQLSTATE: `HY000`

Message: Hostname '%s' has the following IP addresses:

`ER_ADDRESSES_FOR_HOSTNAME_HEADER` was added in 8.0.2.

- Error number: `MY-010060`; Symbol: `ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM`; SQLSTATE: `HY000`

Message: - %s

`ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM` was added in 8.0.2.

- Error number: `MY-010061`; Symbol: `ER_TRG_WITHOUT_DEFINER`; SQLSTATE: `HY000`

Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.

[ER_TRG_WITHOUT_DEFINER](#) was added in 8.0.2.

- Error number: [MY-010062](#); Symbol: [ER_TRG_NO_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)

Message: Client character set is missing for trigger of table %s. Using default character set.

[ER_TRG_NO_CLIENT_CHARSET](#) was added in 8.0.2.

- Error number: [MY-010063](#); Symbol: [ER_PARSING_VIEW](#); SQLSTATE: [HY000](#)

Message: Error in parsing view %s.%s

[ER_PARSING_VIEW](#) was added in 8.0.2.

- Error number: [MY-010064](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap components infrastructure.

[ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#) was added in 8.0.2.

- Error number: [MY-010065](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Failed to shutdown components infrastructure.

[ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#) was added in 8.0.2.

- Error number: [MY-010066](#); Symbol: [ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap persistent components loader.

[ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#) was added in 8.0.2.

- Error number: [MY-010067](#); Symbol: [ER_DEPART_WITH_GRACE](#); SQLSTATE: [HY000](#)

Message: Giving %d client threads a chance to die gracefully

[ER_DEPART_WITH_GRACE](#) was added in 8.0.2.

- Error number: [MY-010068](#); Symbol: [ER_CA_SELF_SIGNED](#); SQLSTATE: [HY000](#)

Message: CA certificate %s is self signed.

[ER_CA_SELF_SIGNED](#) was added in 8.0.2.

- Error number: [MY-010069](#); Symbol: [ER_SSL_LIBRARY_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to set up SSL because of the following SSL library error: %s

[ER_SSL_LIBRARY_ERROR](#) was added in 8.0.2.

- Error number: [MY-010070](#); Symbol: [ER_NO_THD_NO_UUID](#); SQLSTATE: [HY000](#)

Message: Failed to generate a server UUID because it is failed to allocate the THD.

[ER_NO_THD_NO_UUID](#) was added in 8.0.2.

-
- Error number: [MY-010071](#); Symbol: [ER_UUID_SALT](#); SQLSTATE: [HY000](#)
Message: Salting uuid generator variables, current_pid: %lu, server_start_time: %lu, bytes_sent: %llu,
[ER_UUID_SALT](#) was added in 8.0.2.
 - Error number: [MY-010072](#); Symbol: [ER_UUID_IS](#); SQLSTATE: [HY000](#)
Message: Generated uuid: '%s', server_start_time: %lu, bytes_sent: %llu
[ER_UUID_IS](#) was added in 8.0.2.
 - Error number: [MY-010073](#); Symbol: [ER_UUID_INVALID](#); SQLSTATE: [HY000](#)
Message: The server_uuid stored in auto.cnf file is not a valid UUID.
[ER_UUID_INVALID](#) was added in 8.0.2.
 - Error number: [MY-010074](#); Symbol: [ER_UUID_SCRUB](#); SQLSTATE: [HY000](#)
Message: Garbage characters found at the end of the server_uuid value in auto.cnf file. It should be of length '%d' (UUID_LENGTH). Clear it and restart the server.
[ER_UUID_SCRUB](#) was added in 8.0.2.
 - Error number: [MY-010075](#); Symbol: [ER_CREATING_NEW_UUID](#); SQLSTATE: [HY000](#)
Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.
[ER_CREATING_NEW_UUID](#) was added in 8.0.2.
 - Error number: [MY-010076](#); Symbol: [ER_CANT_CREATE_UUID](#); SQLSTATE: [HY000](#)
Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.
[ER_CANT_CREATE_UUID](#) was added in 8.0.2.
 - Error number: [MY-010077](#); Symbol: [ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Unknown/unsupported storage engine: %s
[ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE](#) was added in 8.0.2.
 - Error number: [MY-010078](#); Symbol: [ER_SECURE_AUTH_VALUE_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Unsupported value 0 for secure-auth
[ER_SECURE_AUTH_VALUE_UNSUPPORTED](#) was added in 8.0.2.
 - Error number: [MY-010079](#); Symbol: [ER_INVALID_INSTRUMENT](#); SQLSTATE: [HY000](#)
Message: Invalid instrument name or value for performance_schema_instrument '%s'
[ER_INVALID_INSTRUMENT](#) was added in 8.0.2.
 - Error number: [MY-010080](#); Symbol: [ER_INNODB_MANDATORY](#); SQLSTATE: [HY000](#)
Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

`ER_INNODB_MANDATORY` was added in 8.0.2.

- Error number: `MY-010082`; Symbol: `ER_OLD_PASSWORDS_NO_MIDDLE_GROUND`; SQLSTATE: `HY000`

Message: Invalid old_passwords mode: 1. Valid values are 2 and 0

`ER_OLD_PASSWORDS_NO_MIDDLE_GROUND` was added in 8.0.2, removed after 8.0.15.

- Error number: `MY-010083`; Symbol: `ER_VERBOSE_REQUIRES_HELP`; SQLSTATE: `HY000`

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

`ER_VERBOSE_REQUIRES_HELP` was added in 8.0.2.

- Error number: `MY-010084`; Symbol: `ER_POINTLESS_WITHOUT_SLOWLOG`; SQLSTATE: `HY000`

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

`ER_POINTLESS_WITHOUT_SLOWLOG` was added in 8.0.2.

- Error number: `MY-010085`; Symbol: `ER_WASTEFUL_NET_BUFFER_SIZE`; SQLSTATE: `HY000`

Message: net_buffer_length (%lu) is set to be larger than max_allowed_packet (%lu). Please rectify.

`ER_WASTEFUL_NET_BUFFER_SIZE` was added in 8.0.2.

- Error number: `MY-010086`; Symbol: `ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS`; SQLSTATE: `HY000`

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit_defaults_for_timestamp server option (see documentation for more details).

`ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS` was added in 8.0.2.

- Error number: `MY-010087`; Symbol: `ER_FT_BOOL_SYNTAX_INVALID`; SQLSTATE: `HY000`

Message: Invalid ft-boolean-syntax string: %s

`ER_FT_BOOL_SYNTAX_INVALID` was added in 8.0.2.

- Error number: `MY-010088`; Symbol: `ER_CREDENTIALLESS_AUTO_USER_BAD`; SQLSTATE: `HY000`

Message: 'NO_AUTO_CREATE_USER' sql mode was not set.

`ER_CREDENTIALLESS_AUTO_USER_BAD` was added in 8.0.2.

- Error number: `MY-010089`; Symbol: `ER_CONNECTION_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for connection handling

`ER_CONNECTION_HANDLING_OOM` was added in 8.0.2.

- Error number: `MY-010090`; Symbol: `ER_THREAD_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for thread handling

`ER_THREAD_HANDLING_OOM` was added in 8.0.2.

- Error number: `MY-010091`; Symbol: `ER_CANT_CREATE_TEST_FILE`; SQLSTATE: `HY000`

Message: Can't create test file %s

`ER_CANT_CREATE_TEST_FILE` was added in 8.0.2.

- Error number: `MY-010092`; Symbol: `ER_CANT_CREATE_PID_FILE`; SQLSTATE: `HY000`

Message: Can't start server: can't create PID file: %s

`ER_CANT_CREATE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010093`; Symbol: `ER_CANT_REMOVE_PID_FILE`; SQLSTATE: `HY000`

Message: Unable to delete pid file: %s

`ER_CANT_REMOVE_PID_FILE` was added in 8.0.2.

- Error number: `MY-010094`; Symbol: `ER_CANT_CREATE_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shutdown requests (errno= %d)

`ER_CANT_CREATE_SHUTDOWN_THREAD` was added in 8.0.2.

- Error number: `MY-010095`; Symbol: `ER_SEC_FILE_PRIV_CANT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

`ER_SEC_FILE_PRIV_CANT_ACCESS_DIR` was added in 8.0.2.

- Error number: `MY-010096`; Symbol: `ER_SEC_FILE_PRIV_IGNORED`; SQLSTATE: `HY000`

Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

`ER_SEC_FILE_PRIV_IGNORED` was added in 8.0.2.

- Error number: `MY-010097`; Symbol: `ER_SEC_FILE_PRIV_EMPTY`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

`ER_SEC_FILE_PRIV_EMPTY` was added in 8.0.2.

- Error number: `MY-010098`; Symbol: `ER_SEC_FILE_PRIV_NULL`; SQLSTATE: `HY000`

Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

`ER_SEC_FILE_PRIV_NULL` was added in 8.0.2.

- Error number: `MY-010099`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

`ER_SEC_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.2.

- Error number: `MY-010100`; Symbol: `ER_SEC_FILE_PRIV_CANT_STAT`; SQLSTATE: `HY000`

Message: Failed to get stat for directory pointed out by --secure-file-priv

`ER_SEC_FILE_PRIV_CANT_STAT` was added in 8.0.2.

-
- Error number: `MY-010101`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.

`ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS` was added in 8.0.2.
 - Error number: `MY-010102`; Symbol: `ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG`; SQLSTATE: `HY000`

Message: Value for --secure-file-priv is longer than maximum limit of %d

`ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG` was added in 8.0.2.
 - Error number: `MY-010103`; Symbol: `ER_CANT_CREATE_NAMED_PIPES_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle named pipes (errno= %d)

`ER_CANT_CREATE_NAMED_PIPES_THREAD` was added in 8.0.2.
 - Error number: `MY-010104`; Symbol: `ER_CANT_CREATE_TCPIP_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle TCP/IP (errno= %d)

`ER_CANT_CREATE_TCPIP_THREAD` was added in 8.0.2.
 - Error number: `MY-010105`; Symbol: `ER_CANT_CREATE_SHM_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shared memory (errno= %d)

`ER_CANT_CREATE_SHM_THREAD` was added in 8.0.2.
 - Error number: `MY-010106`; Symbol: `ER_CANT_CREATE_INTERRUPT_THREAD`; SQLSTATE: `HY000`

Message: Can't create interrupt-thread (error %d, errno: %d)

`ER_CANT_CREATE_INTERRUPT_THREAD` was added in 8.0.2.
 - Error number: `MY-010107`; Symbol: `ER_WRITABLE_CONFIG_REMOVED`; SQLSTATE: `HY000`

Message: World-writable config file '%s' has been removed.

`ER_WRITABLE_CONFIG_REMOVED` was added in 8.0.2.
 - Error number: `MY-010108`; Symbol: `ER_CORE_VALUES`; SQLSTATE: `HY000`

Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals

`ER_CORE_VALUES` was added in 8.0.2.
 - Error number: `MY-010109`; Symbol: `ER_WRONG_DATETIME_SPEC`; SQLSTATE: `HY000`

Message: Wrong date/time format specifier: %s

`ER_WRONG_DATETIME_SPEC` was added in 8.0.2.
 - Error number: `MY-010110`; Symbol: `ER_RPL_BINLOG_FILTERS_OOM`; SQLSTATE: `HY000`

Message: Could not allocate replication and binlog filters: %s

`ER_RPL_BINLOG_FILTERS_OOM` was added in 8.0.2.

-
- Error number: [MY-010111](#); Symbol: [ER_KEYCACHE_OOM](#); SQLSTATE: [HY000](#)
Message: Cannot allocate the keycache
[ER_KEYCACHE_OOM](#) was added in 8.0.2.
 - Error number: [MY-010112](#); Symbol: [ER_CONFIRMING_THE_FUTURE](#); SQLSTATE: [HY000](#)
Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.
[ER_CONFIRMING_THE_FUTURE](#) was added in 8.0.2.
 - Error number: [MY-010113](#); Symbol: [ER_BACK_IN_TIME](#); SQLSTATE: [HY000](#)
Message: Iteration %d: Obtained valid current time from system
[ER_BACK_IN_TIME](#) was added in 8.0.2.
 - Error number: [MY-010114](#); Symbol: [ER_FUTURE_DATE](#); SQLSTATE: [HY000](#)
Message: Iteration %d: Current time obtained from system is greater than 2038
[ER_FUTURE_DATE](#) was added in 8.0.2.
 - Error number: [MY-010115](#); Symbol: [ER_UNSUPPORTED_DATE](#); SQLSTATE: [HY000](#)
Message: This MySQL server doesn't support dates later then 2038
[ER_UNSUPPORTED_DATE](#) was added in 8.0.2.
 - Error number: [MY-010116](#); Symbol: [ER_STARTING_AS](#); SQLSTATE: [HY000](#)
Message: %s (mysqld %s) starting as process %lu
[ER_STARTING_AS](#) was added in 8.0.2.
 - Error number: [MY-010117](#); Symbol: [ER_SHUTTING_DOWN_SLAVE_THREADS](#); SQLSTATE: [HY000](#)
Message: Shutting down slave threads
[ER_SHUTTING_DOWN_SLAVE_THREADS](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010117](#); Symbol: [ER_SHUTTING_DOWN_REPLICA_THREADS](#); SQLSTATE: [HY000](#)
Message: Shutting down replica threads
[ER_SHUTTING_DOWN_REPLICA_THREADS](#) was added in 8.0.33.
 - Error number: [MY-010118](#); Symbol: [ER_DISCONNECTING_REMAINING_CLIENTS](#); SQLSTATE: [HY000](#)
Message: Forcefully disconnecting %d remaining clients
[ER_DISCONNECTING_REMAINING_CLIENTS](#) was added in 8.0.2.
 - Error number: [MY-010119](#); Symbol: [ER_ABORTING](#); SQLSTATE: [HY000](#)
Message: Aborting
[ER_ABORTING](#) was added in 8.0.2.
 - Error number: [MY-010120](#); Symbol: [ER_BINLOG_END](#); SQLSTATE: [HY000](#)

Message: Binlog end

[ER_BINLOG_END](#) was added in 8.0.2.

- Error number: [MY-010121](#); Symbol: [ER_CALL_ME_LOCALHOST](#); SQLSTATE: [HY000](#)

Message: gethostname failed, using '%s' as hostname

[ER_CALL_ME_LOCALHOST](#) was added in 8.0.2.

- Error number: [MY-010122](#); Symbol: [ER_USER_REQUIRES_ROOT](#); SQLSTATE: [HY000](#)

Message: One can only use the --user switch if running as root

[ER_USER_REQUIRES_ROOT](#) was added in 8.0.2.

- Error number: [MY-010123](#); Symbol: [ER_REALLY_RUN_AS_ROOT](#); SQLSTATE: [HY000](#)

Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!

[ER_REALLY_RUN_AS_ROOT](#) was added in 8.0.2.

- Error number: [MY-010124](#); Symbol: [ER_USER_WHAT_USER](#); SQLSTATE: [HY000](#)

Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!

[ER_USER_WHAT_USER](#) was added in 8.0.2.

- Error number: [MY-010125](#); Symbol: [ER_TRANSPORTS_WHAT_TRANSPORTS](#); SQLSTATE: [HY000](#)

Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.

[ER_TRANSPORTS_WHAT_TRANSPORTS](#) was added in 8.0.2.

- Error number: [MY-010126](#); Symbol: [ER_FAIL_SETGID](#); SQLSTATE: [HY000](#)

Message: setgid: %s

[ER_FAIL_SETGID](#) was added in 8.0.2.

- Error number: [MY-010127](#); Symbol: [ER_FAIL_SETUID](#); SQLSTATE: [HY000](#)

Message: setuid: %s

[ER_FAIL_SETUID](#) was added in 8.0.2.

- Error number: [MY-010128](#); Symbol: [ER_FAIL_SETREGID](#); SQLSTATE: [HY000](#)

Message: setregid: %s

[ER_FAIL_SETREGID](#) was added in 8.0.2.

- Error number: [MY-010129](#); Symbol: [ER_FAIL_SETREUID](#); SQLSTATE: [HY000](#)

Message: setreuid: %s

[ER_FAIL_SETREUID](#) was added in 8.0.2.

- Error number: [MY-010130](#); Symbol: [ER_FAIL_CHROOT](#); SQLSTATE: [HY000](#)

Message: chroot: %s

`ER_FAIL_CHROOT` was added in 8.0.2.

- Error number: `MY-010131`; Symbol: `ER_WIN_LISTEN_BUT_HOW`; SQLSTATE: `HY000`

Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS

`ER_WIN_LISTEN_BUT_HOW` was added in 8.0.2.

- Error number: `MY-010132`; Symbol: `ER_NOT_RIGHT_NOW`; SQLSTATE: `HY000`

Message: CTRL-C ignored during startup

`ER_NOT_RIGHT_NOW` was added in 8.0.2.

- Error number: `MY-010133`; Symbol: `ER_FIXING_CLIENT_CHARSET`; SQLSTATE: `HY000`

Message: '%s' can not be used as client character set. '%s' will be used as default client character set.

`ER_FIXING_CLIENT_CHARSET` was added in 8.0.2.

- Error number: `MY-010134`; Symbol: `ER_OOM`; SQLSTATE: `HY000`

Message: Out of memory

`ER_OOM` was added in 8.0.2.

- Error number: `MY-010135`; Symbol: `ER_FAILED_TO_LOCK_MEM`; SQLSTATE: `HY000`

Message: Failed to lock memory. Errno: %d

`ER_FAILED_TO_LOCK_MEM` was added in 8.0.2.

- Error number: `MY-010136`; Symbol: `ER_MYINIT_FAILED`; SQLSTATE: `HY000`

Message: my_init() failed.

`ER_MYINIT_FAILED` was added in 8.0.2.

- Error number: `MY-010137`; Symbol: `ER_BEG_INITFILE`; SQLSTATE: `HY000`

Message: Execution of init_file '%s' started.

`ER_BEG_INITFILE` was added in 8.0.2.

- Error number: `MY-010138`; Symbol: `ER_END_INITFILE`; SQLSTATE: `HY000`

Message: Execution of init_file '%s' ended.

`ER_END_INITFILE` was added in 8.0.2.

- Error number: `MY-010139`; Symbol: `ER_CHANGED_MAX_OPEN_FILES`; SQLSTATE: `HY000`

Message: Changed limits: max_open_files: %lu (requested %lu)

`ER_CHANGED_MAX_OPEN_FILES` was added in 8.0.2.

- Error number: `MY-010140`; Symbol: `ER_CANT_INCREASE_MAX_OPEN_FILES`; SQLSTATE: `HY000`

Message: Could not increase number of max_open_files to more than %lu (request: %lu)

`ER_CANT_INCREASE_MAX_OPEN_FILES` was added in 8.0.2.

- Error number: `MY-010141`; Symbol: `ER_CHANGED_MAX_CONNECTIONS`; SQLSTATE: `HY000`

Message: Changed limits: max_connections: %lu (requested %lu)

[ER_CHANGED_MAX_CONNECTIONS](#) was added in 8.0.2.

- Error number: MY-010142; Symbol: [ER_CHANGED_TABLE_OPEN_CACHE](#); SQLSTATE: HY000

Message: Changed limits: table_open_cache: %lu (requested %lu)

[ER_CHANGED_TABLE_OPEN_CACHE](#) was added in 8.0.2.

- Error number: MY-010143; Symbol: [ER_THE_USER_ABIDES](#); SQLSTATE: HY000

Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line

[ER_THE_USER_ABIDES](#) was added in 8.0.2.

- Error number: MY-010144; Symbol: [ER_RPL_CANT_ADD_DO_TABLE](#); SQLSTATE: HY000

Message: Could not add do table rule '%s'!

[ER_RPL_CANT_ADD_DO_TABLE](#) was added in 8.0.2.

- Error number: MY-010145; Symbol: [ER_RPL_CANT_ADD_IGNORE_TABLE](#); SQLSTATE: HY000

Message: Could not add ignore table rule '%s'!

[ER_RPL_CANT_ADD_IGNORE_TABLE](#) was added in 8.0.2.

- Error number: MY-010146; Symbol: [ER_TRACK_VARIABLES_BOGUS](#); SQLSTATE: HY000

Message: The variable session_track_system_variables either has duplicate values or invalid values.

[ER_TRACK_VARIABLES_BOGUS](#) was added in 8.0.2.

- Error number: MY-010147; Symbol: [ER_EXCESS_ARGUMENTS](#); SQLSTATE: HY000

Message: Too many arguments (first extra is '%s').

[ER_EXCESS_ARGUMENTS](#) was added in 8.0.2.

- Error number: MY-010148; Symbol: [ER_VERBOSE_HINT](#); SQLSTATE: HY000

Message: Use --verbose --help to get a list of available options!

[ER_VERBOSE_HINT](#) was added in 8.0.2.

- Error number: MY-010149; Symbol: [ER_CANT_READ_ERRMSG](#); SQLSTATE: HY000

Message: Unable to read errmsg.sys file

[ER_CANT_READ_ERRMSG](#) was added in 8.0.2.

- Error number: MY-010150; Symbol: [ER_CANT_INIT_DBS](#); SQLSTATE: HY000

Message: Can't init databases

[ER_CANT_INIT_DBS](#) was added in 8.0.2.

- Error number: MY-010151; Symbol: [ER_LOG_OUTPUT_CONTRADICTION](#); SQLSTATE: HY000

Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.

[ER_LOG_OUTPUT_CONTRADICTION](#) was added in 8.0.2.

-
- Error number: [MY-010152](#); Symbol: [ER_NO_CSV_NO_LOG_TABLES](#); SQLSTATE: [HY000](#)
Message: CSV engine is not present, falling back to the log files
[ER_NO_CSV_NO_LOG_TABLES](#) was added in 8.0.2.
 - Error number: [MY-010153](#); Symbol: [ER_RPL_REWRITEDB_MISSING_ARROW](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - missing '->'
[ER_RPL_REWRITEDB_MISSING_ARROW](#) was added in 8.0.2.
 - Error number: [MY-010154](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_FROM](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - empty FROM db!
[ER_RPL_REWRITEDB_EMPTY_FROM](#) was added in 8.0.2.
 - Error number: [MY-010155](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_TO](#); SQLSTATE: [HY000](#)
Message: Bad syntax in replicate-rewrite-db - empty TO db!
[ER_RPL_REWRITEDB_EMPTY_TO](#) was added in 8.0.2.
 - Error number: [MY-010156](#); Symbol: [ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE](#); SQLSTATE: [HY000](#)
Message: Although a path was specified for the %s, log tables are used. To enable logging to files use the --log-output=file option.
[ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE](#) was added in 8.0.2.
 - Error number: [MY-010157](#); Symbol: [ER_LOG_FILE_INVALID](#); SQLSTATE: [HY000](#)
Message: Invalid value for %s: %s
[ER_LOG_FILE_INVALID](#) was added in 8.0.2.
 - Error number: [MY-010158](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: The server option 'lower_case_table_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.
[ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED](#) was added in 8.0.2.
 - Error number: [MY-010159](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_2](#); SQLSTATE: [HY000](#)
Message: Setting lower_case_table_names=2 because file system for %s is case insensitive
[ER_LOWER_CASE_TABLE_NAMES_USING_2](#) was added in 8.0.2.
 - Error number: [MY-010160](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_0](#); SQLSTATE: [HY000](#)
Message: lower_case_table_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower_case_table_names to 0 to avoid future problems.
[ER_LOWER_CASE_TABLE_NAMES_USING_0](#) was added in 8.0.2.
 - Error number: [MY-010161](#); Symbol: [ER_NEED_LOG_BIN](#); SQLSTATE: [HY000](#)

Message: You need to use --log-bin to make %s work.

[ER_NEED_LOG_BIN](#) was added in 8.0.2.

- Error number: [MY-010162](#); Symbol: [ER_NEED_FILE_INSTEAD_OF_DIR](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a directory name, please specify a file name for %s option

[ER_NEED_FILE_INSTEAD_OF_DIR](#) was added in 8.0.2.

- Error number: [MY-010163](#); Symbol: [ER_LOG_BIN_BETTER_WITH_NAME](#); SQLSTATE: [HY000](#)

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

[ER_LOG_BIN_BETTER_WITH_NAME](#) was added in 8.0.2.

- Error number: [MY-010164](#); Symbol: [ER_BINLOG_NEEDS_SERVERID](#); SQLSTATE: [HY000](#)

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

[ER_BINLOG_NEEDS_SERVERID](#) was added in 8.0.2.

- Error number: [MY-010165](#); Symbol: [ER_RPL_CANT_MAKE_PATHS](#); SQLSTATE: [HY000](#)

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

[ER_RPL_CANT_MAKE_PATHS](#) was added in 8.0.2.

- Error number: [MY-010166](#); Symbol: [ER_CANT_INITIALIZE_GTID](#); SQLSTATE: [HY000](#)

Message: Failed to initialize GTID structures.

[ER_CANT_INITIALIZE_GTID](#) was added in 8.0.2.

- Error number: [MY-010167](#); Symbol: [ER_CANT_INITIALIZE_EARLY_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize early plugins.

[ER_CANT_INITIALIZE_EARLY_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010168](#); Symbol: [ER_CANT_INITIALIZE_BUILTIN_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize builtin plugins.

[ER_CANT_INITIALIZE_BUILTIN_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010169](#); Symbol: [ER_CANT_INITIALIZE_DYNAMIC_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize dynamic plugins.

[ER_CANT_INITIALIZE_DYNAMIC_PLUGINS](#) was added in 8.0.2.

- Error number: [MY-010170](#); Symbol: [ER_PERFSHEMA_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema disabled (reason: init failed).

`ER_PERFSCHEMA_INIT_FAILED` was added in 8.0.2.

- Error number: `MY-010171`; Symbol: `ER_STACKSIZE_UNEXPECTED`; SQLSTATE: `HY000`

Message: Asked for %lu thread stack, but got %ld

`ER_STACKSIZE_UNEXPECTED` was added in 8.0.2.

- Error number: `MY-010172`; Symbol: `ER_CANT_SET_DATADIR`; SQLSTATE: `HY000`

Message: failed to set datadir to %s

`ER_CANT_SET_DATADIR` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010173`; Symbol: `ER_CANT_STAT_DATADIR`; SQLSTATE: `HY000`

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group

`ER_CANT_STAT_DATADIR` was added in 8.0.2.

- Error number: `MY-010174`; Symbol: `ER_CANT_CHOWN_DATADIR`; SQLSTATE: `HY000`

Message: Can't change data directory owner to %s

`ER_CANT_CHOWN_DATADIR` was added in 8.0.2.

- Error number: `MY-010175`; Symbol: `ER_CANT_SET_UP_PERSISTED_VALUES`; SQLSTATE: `HY000`

Message: Setting persistent options failed.

`ER_CANT_SET_UP_PERSISTED_VALUES` was added in 8.0.2.

- Error number: `MY-010176`; Symbol: `ER_CANT_SAVE_GTIDS`; SQLSTATE: `HY000`

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the `mysql.gtid_executed` table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

`ER_CANT_SAVE_GTIDS` was added in 8.0.2.

- Error number: `MY-010177`; Symbol: `ER_AUTH_CANT_SET_DEFAULT_PLUGIN`; SQLSTATE: `HY000`

Message: Can't start server: Invalid value for `--default-authentication-plugin`

`ER_AUTH_CANT_SET_DEFAULT_PLUGIN` was added in 8.0.2.

- Error number: `MY-010178`; Symbol: `ER_CANT_JOIN_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Could not join %sthread. error:%d

`ER_CANT_JOIN_SHUTDOWN_THREAD` was added in 8.0.2.

- Error number: `MY-010179`; Symbol: `ER_CANT_HASH_DO_AND_IGNORE_RULES`; SQLSTATE: `HY000`

Message: An error occurred while building `do_table` and `ignore_table` rules to hashes for global replication filter.

`ER_CANT_HASH_DO_AND_IGNORE_RULES` was added in 8.0.2.

- Error number: `MY-010180`; Symbol: `ER_CANT_OPEN_CA`; SQLSTATE: `HY000`

Message: Error opening CA certificate file

[ER_CANT_OPEN_CA](#) was added in 8.0.2.

- Error number: [MY-010181](#); Symbol: [ER_CANT_ACCESS_CAPATH](#); SQLSTATE: [HY000](#)

Message: Error accessing directory pointed by --ssl-capath

[ER_CANT_ACCESS_CAPATH](#) was added in 8.0.2.

- Error number: [MY-010182](#); Symbol: [ER_SSL_TRYING_DATADIR_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

[ER_SSL_TRYING_DATADIR_DEFAULTS](#) was added in 8.0.2.

- Error number: [MY-010183](#); Symbol: [ER_AUTO_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create %s(file: '%s', errno %d)

[ER_AUTO_OPTIONS_FAILED](#) was added in 8.0.2.

- Error number: [MY-010184](#); Symbol: [ER_CANT_INIT_TIMER](#); SQLSTATE: [HY000](#)

Message: Failed to initialize timer component (errno %d).

[ER_CANT_INIT_TIMER](#) was added in 8.0.2.

- Error number: [MY-010185](#); Symbol: [ER_SERVERID_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: server-id configured is too large to represent with server-id-bits configured.

[ER_SERVERID_TOO_LARGE](#) was added in 8.0.2.

- Error number: [MY-010186](#); Symbol: [ER_DEFAULT_SE_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Default%s storage engine (%s) is not available

[ER_DEFAULT_SE_UNAVAILABLE](#) was added in 8.0.2.

- Error number: [MY-010187](#); Symbol: [ER_CANT_OPEN_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open file '%s' for error logging%s%s

[ER_CANT_OPEN_ERROR_LOG](#) was added in 8.0.2.

- Error number: [MY-010188](#); Symbol: [ER_INVALID_ERROR_LOG_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid log file name after expanding symlinks: '%s'

[ER_INVALID_ERROR_LOG_NAME](#) was added in 8.0.2.

- Error number: [MY-010189](#); Symbol: [ER_RPL_INFINITY_DENIED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.

[ER_RPL_INFINITY_DENIED](#) was added in 8.0.2.

-
- Error number: [MY-010190](#); Symbol: [ER_RPL_INFINITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.

[ER_RPL_INFINITY_IGNORED](#) was added in 8.0.2.

- Error number: [MY-010191](#); Symbol: [ER_NDB_TABLES_NOT_READY](#); SQLSTATE: [HY000](#)

Message: NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value

[ER_NDB_TABLES_NOT_READY](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010192](#); Symbol: [ER_TABLE_CHECK_INTACT](#); SQLSTATE: [HY000](#)

Message: %s

[ER_TABLE_CHECK_INTACT](#) was added in 8.0.2.

- Error number: [MY-010193](#); Symbol: [ER_DD_TABLESPACE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

[ER_DD_TABLESPACE_NOT_FOUND](#) was added in 8.0.2.

- Error number: [MY-010194](#); Symbol: [ER_DD_TRG_CONNECTION_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

[ER_DD_TRG_CONNECTION_COLLATION_MISSING](#) was added in 8.0.2.

- Error number: [MY-010195](#); Symbol: [ER_DD_TRG_DB_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Database collation is missing for trigger of table %s. Using Default character set.

[ER_DD_TRG_DB_COLLATION_MISSING](#) was added in 8.0.2.

- Error number: [MY-010196](#); Symbol: [ER_DD_TRG_DEFINER_OOM](#); SQLSTATE: [HY000](#)

Message: Error in Memory allocation for Definer %s for Trigger.

[ER_DD_TRG_DEFINER_OOM](#) was added in 8.0.2.

- Error number: [MY-010197](#); Symbol: [ER_DD_TRG_FILE_UNREADABLE](#); SQLSTATE: [HY000](#)

Message: Error in reading %s.TRG file.

[ER_DD_TRG_FILE_UNREADABLE](#) was added in 8.0.2.

- Error number: [MY-010198](#); Symbol: [ER_TRG_CANT_PARSE](#); SQLSTATE: [HY000](#)

Message: Error in parsing Triggers from %s.TRG file.

[ER_TRG_CANT_PARSE](#) was added in 8.0.2.

- Error number: [MY-010199](#); Symbol: [ER_DD_TRG_CANT_ADD](#); SQLSTATE: [HY000](#)

Message: Error in creating DD entry for Trigger %s.%s

[ER_DD_TRG_CANT_ADD](#) was added in 8.0.2.

- Error number: [MY-010200](#); Symbol: [ER_DD_CANT_RESOLVE_VIEW](#); SQLSTATE: [HY000](#)

Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use

[ER_DD_CANT_RESOLVE_VIEW](#) was added in 8.0.2.

- Error number: [MY-010201](#); Symbol: [ER_DD_VIEW_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)

Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.

[ER_DD_VIEW_WITHOUT_DEFINER](#) was added in 8.0.2.

- Error number: [MY-010202](#); Symbol: [ER_PLUGIN_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' init function returned error.

[ER_PLUGIN_INIT_FAILED](#) was added in 8.0.2.

- Error number: [MY-010203](#); Symbol: [ER_RPL_TRX_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization of transaction delegates failed. Please report a bug.

[ER_RPL_TRX_DELEGATES_INIT_FAILED](#) was added in 8.0.2.

- Error number: [MY-010204](#); Symbol: [ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization binlog storage delegates failed. Please report a bug.

[ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED](#) was added in 8.0.2.

- Error number: [MY-010205](#); Symbol: [ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization of binlog transmit delegates failed. Please report a bug.

[ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED](#) was added in 8.0.2.

- Error number: [MY-010206](#); Symbol: [ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Initialization binlog relay IO delegates failed. Please report a bug.

[ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED](#) was added in 8.0.2.

- Error number: [MY-010207](#); Symbol: [ER_RPL_PLUGIN_FUNCTION_FAILED](#); SQLSTATE: [HY000](#)

Message: Run function '...' in plugin '%s' failed

[ER_RPL_PLUGIN_FUNCTION_FAILED](#) was added in 8.0.2.

- Error number: [MY-010208](#); Symbol: [ER_SQL_HA_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: mysql_ha_read: Got error %d when reading table '%s'

[ER_SQL_HA_READ_FAILED](#) was added in 8.0.2.

- Error number: [MY-010209](#); Symbol: [ER_SR_BOGUS_VALUE](#); SQLSTATE: [HY000](#)

Message: Stored routine '%s'. '%s': invalid value in column %s.

[ER_SR_BOGUS_VALUE](#) was added in 8.0.2.

-
- Error number: [MY-010210](#); Symbol: [ER_SR_INVALID_CONTEXT](#); SQLSTATE: [HY000](#)
Message: Invalid creation context '%s.%s'.
[ER_SR_INVALID_CONTEXT](#) was added in 8.0.2.
 - Error number: [MY-010211](#); Symbol: [ER_READING_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Got error %d when reading table '%s'
[ER_READING_TABLE_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010212](#); Symbol: [ER_DES_FILE_WRONG_KEY](#); SQLSTATE: [HY000](#)
Message: load_des_file: Found wrong key_number: %c
[ER_DES_FILE_WRONG_KEY](#) was added in 8.0.2.
 - Error number: [MY-010214](#); Symbol: [ER_JSON_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.
[ER_JSON_PARSE_ERROR](#) was added in 8.0.2.
 - Error number: [MY-010215](#); Symbol: [ER_CONFIG_OPTION_WITHOUT_GROUP](#); SQLSTATE: [HY000](#)
Message: Found option without preceding group in config file
[ER_CONFIG_OPTION_WITHOUT_GROUP](#) was added in 8.0.2.
 - Error number: [MY-010216](#); Symbol: [ER_VALGRIND_DO_QUICK_LEAK_CHECK](#); SQLSTATE: [HY000](#)
Message: VALGRIND_DO_QUICK_LEAK_CHECK
[ER_VALGRIND_DO_QUICK_LEAK_CHECK](#) was added in 8.0.2.
 - Error number: [MY-010217](#); Symbol: [ER_VALGRIND_COUNT_LEAKS](#); SQLSTATE: [HY000](#)
Message: VALGRIND_COUNT_LEAKS reports %lu leaked bytes for query '%.*s'
[ER_VALGRIND_COUNT_LEAKS](#) was added in 8.0.2.
 - Error number: [MY-010218](#); Symbol: [ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY](#); SQLSTATE: [HY000](#)
Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.
[ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY](#) was added in 8.0.2.
 - Error number: [MY-010219](#); Symbol: [ER_UNKNOWN_ERROR_NUMBER](#); SQLSTATE: [HY000](#)
Message: Got unknown error: %d
[ER_UNKNOWN_ERROR_NUMBER](#) was added in 8.0.2.
 - Error number: [MY-010220](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_STRUCTURES](#); SQLSTATE: [HY000](#)
Message: Can't allocate memory for udf structures
[ER_UDF_CANT_ALLOC_FOR_STRUCTURES](#) was added in 8.0.2.
 - Error number: [MY-010221](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Can't alloc memory for udf function: '%s'

[ER_UDF_CANT_ALLOC_FOR_FUNCTION](#) was added in 8.0.2.

- Error number: [MY-010222](#); Symbol: [ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)

Message: Invalid row in mysql.func table for function '%s'

[ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE](#) was added in 8.0.2.

- Error number: [MY-010223](#); Symbol: [ER_UDF_CANT_OPEN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

[ER_UDF_CANT_OPEN_FUNCTION_TABLE](#) was added in 8.0.2.

- Error number: [MY-010224](#); Symbol: [ER_XA_RECOVER_FOUND_TRX_IN_SE](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transaction(s) in %s

[ER_XA_RECOVER_FOUND_TRX_IN_SE](#) was added in 8.0.2.

- Error number: [MY-010225](#); Symbol: [ER_XA_RECOVER_FOUND_XA_TRX](#); SQLSTATE: [HY000](#)

Message: Found %d prepared XA transactions

[ER_XA_RECOVER_FOUND_XA_TRX](#) was added in 8.0.2.

- Error number: [MY-010226](#); Symbol: [ER_XA_IGNOREING_XID](#); SQLSTATE: [HY000](#)

Message: ignore xid %s

[ER_XA_IGNOREING_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010227](#); Symbol: [ER_XA_COMMITTING_XID](#); SQLSTATE: [HY000](#)

Message: commit xid %s

[ER_XA_COMMITTING_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010228](#); Symbol: [ER_XA_ROLLING_BACK_XID](#); SQLSTATE: [HY000](#)

Message: rollback xid %s

[ER_XA_ROLLING_BACK_XID](#) was added in 8.0.2, removed after 8.0.29.

- Error number: [MY-010229](#); Symbol: [ER_XA_STARTING_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Starting XA crash recovery...

[ER_XA_STARTING_RECOVERY](#) was added in 8.0.2.

- Error number: [MY-010230](#); Symbol: [ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.

[ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#) was added in 8.0.2.

-
- Error number: [MY-010231](#); Symbol: [ER_XA_RECOVER_EXPLANATION](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

[ER_XA_RECOVER_EXPLANATION](#) was added in 8.0.2.

- Error number: [MY-010232](#); Symbol: [ER_XA_RECOVERY_DONE](#); SQLSTATE: [HY000](#)

Message: XA crash recovery finished.

[ER_XA_RECOVERY_DONE](#) was added in 8.0.2.

- Error number: [MY-010233](#); Symbol: [ER_TRX_GTID_COLLECT_REJECT](#); SQLSTATE: [HY000](#)

Message: Failed to collect GTID to send in the response packet!

[ER_TRX_GTID_COLLECT_REJECT](#) was added in 8.0.2.

- Error number: [MY-010234](#); Symbol: [ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL](#); SQLSTATE: [HY000](#)

Message: MYSQL.DEFAULT_ROLES couldn't be updated for authorization identifier %s

[ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL](#) was added in 8.0.2.

- Error number: [MY-010235](#); Symbol: [ER_SQL_USER_TABLE_CREATE_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER_SQL_USER_TABLE_CREATE_WARNING](#) was added in 8.0.2.

- Error number: [MY-010236](#); Symbol: [ER_SQL_USER_TABLE_ALTER_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

[ER_SQL_USER_TABLE_ALTER_WARNING](#) was added in 8.0.2.

- Error number: [MY-010237](#); Symbol: [ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR](#); SQLSTATE: [HY000](#)

Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!

[ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR](#) was added in 8.0.2.

- Error number: [MY-010238](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN_THREAD](#); SQLSTATE: [HY000](#)

Message: Got an error from thread_id=%u, %s:%d

[ER_MYISAM_CRASHED_ERROR_IN_THREAD](#) was added in 8.0.2.

- Error number: [MY-010239](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN](#); SQLSTATE: [HY000](#)

Message: Got an error from unknown thread, %s:%d

[ER_MYISAM_CRASHED_ERROR_IN](#) was added in 8.0.2.

-
- Error number: [MY-010240](#); Symbol: [ER_TOO_MANY_STORAGE_ENGINES](#); SQLSTATE: [HY000](#)
Message: Too many storage engines!
[ER_TOO_MANY_STORAGE_ENGINES](#) was added in 8.0.2.
 - Error number: [MY-010241](#); Symbol: [ER_SE_TYPECODE_CONFLICT](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' has conflicting typecode. Assigning value %d.
[ER_SE_TYPECODE_CONFLICT](#) was added in 8.0.2.
 - Error number: [MY-010242](#); Symbol: [ER_TRX_WRITE_SET_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory on transaction write set extraction
[ER_TRX_WRITE_SET_OOM](#) was added in 8.0.2.
 - Error number: [MY-010243](#); Symbol: [ER_HANDLERTON_OOM](#); SQLSTATE: [HY000](#)
Message: Unable to allocate memory for plugin '%s' handlerton.
[ER_HANDLERTON_OOM](#) was added in 8.0.2.
 - Error number: [MY-010244](#); Symbol: [ER_CONN_SHM_LISTENER](#); SQLSTATE: [HY000](#)
Message: Shared memory setting up listener
[ER_CONN_SHM_LISTENER](#) was added in 8.0.2.
 - Error number: [MY-010245](#); Symbol: [ER_CONN_SHM_CANT_CREATE_SERVICE](#); SQLSTATE: [HY000](#)
Message: Can't create shared memory service: %s. : %s
[ER_CONN_SHM_CANT_CREATE_SERVICE](#) was added in 8.0.2.
 - Error number: [MY-010246](#); Symbol: [ER_CONN_SHM_CANT_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Can't create shared memory connection: %s. : %s
[ER_CONN_SHM_CANT_CREATE_CONNECTION](#) was added in 8.0.2.
 - Error number: [MY-010247](#); Symbol: [ER_CONN_PIP_CANT_CREATE_EVENT](#); SQLSTATE: [HY000](#)
Message: Can't create event, last error=%u
[ER_CONN_PIP_CANT_CREATE_EVENT](#) was added in 8.0.2.
 - Error number: [MY-010248](#); Symbol: [ER_CONN_PIP_CANT_CREATE_PIPE](#); SQLSTATE: [HY000](#)
Message: Can't create new named pipe!: %s
[ER_CONN_PIP_CANT_CREATE_PIPE](#) was added in 8.0.2.
 - Error number: [MY-010249](#); Symbol: [ER_CONN_PER_THREAD_NO_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create thread to handle new connection(errno= %d)
[ER_CONN_PER_THREAD_NO_THREAD](#) was added in 8.0.2.
 - Error number: [MY-010250](#); Symbol: [ER_CONN_TCP_NO_SOCKET](#); SQLSTATE: [HY000](#)
Message: Failed to create a socket for %s '%s': errno: %d.

`ER_CONN_TCP_NO_SOCKET` was added in 8.0.2.

- Error number: `MY-010251`; Symbol: `ER_CONN_TCP_CREATED`; SQLSTATE: `HY000`

Message: Server socket created on IP: '%s'.

`ER_CONN_TCP_CREATED` was added in 8.0.2.

- Error number: `MY-010252`; Symbol: `ER_CONN_TCP_ADDRESS`; SQLSTATE: `HY000`

Message: Server hostname (bind-address): '%s'; port: %d

`ER_CONN_TCP_ADDRESS` was added in 8.0.2.

- Error number: `MY-010253`; Symbol: `ER_CONN_TCP_IPV6_AVAILABLE`; SQLSTATE: `HY000`

Message: IPv6 is available.

`ER_CONN_TCP_IPV6_AVAILABLE` was added in 8.0.2.

- Error number: `MY-010254`; Symbol: `ER_CONN_TCP_IPV6_UNAVAILABLE`; SQLSTATE: `HY000`

Message: IPv6 is not available.

`ER_CONN_TCP_IPV6_UNAVAILABLE` was added in 8.0.2.

- Error number: `MY-010255`; Symbol: `ER_CONN_TCP_ERROR_WITH_STRERROR`; SQLSTATE: `HY000`

Message: Can't create IP socket: %s

`ER_CONN_TCP_ERROR_WITH_STRERROR` was added in 8.0.2.

- Error number: `MY-010256`; Symbol: `ER_CONN_TCP_CANT_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`

Message: Can't start server: cannot resolve hostname!

`ER_CONN_TCP_CANT_RESOLVE_HOSTNAME` was added in 8.0.2.

- Error number: `MY-010257`; Symbol: `ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT`; SQLSTATE: `HY000`

Message: Do you already have another mysqld server running on port: %d ?

`ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT` was added in 8.0.2.

- Error number: `MY-010258`; Symbol: `ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET`; SQLSTATE: `HY000`

Message: Do you already have another mysqld server running on socket: %s ?

`ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET` was added in 8.0.2.

- Error number: `MY-010259`; Symbol: `ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE`; SQLSTATE: `HY000`

Message: Another process with pid %d is using unix socket file.

`ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE` was added in 8.0.2.

-
- Error number: `MY-010260`; Symbol: `ER_CONN_TCP_CANT_RESET_V6ONLY`; SQLSTATE: `HY000`
Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
`ER_CONN_TCP_CANT_RESET_V6ONLY` was added in 8.0.2.
 - Error number: `MY-010261`; Symbol: `ER_CONN_TCP_BIND_RETRY`; SQLSTATE: `HY000`
Message: Retrying bind on TCP/IP port %u
`ER_CONN_TCP_BIND_RETRY` was added in 8.0.2.
 - Error number: `MY-010262`; Symbol: `ER_CONN_TPC_BIND_FAIL`; SQLSTATE: `HY000`
Message: Can't start server: Bind on TCP/IP port: %s
`ER_CONN_TPC_BIND_FAIL` was added in 8.0.2, removed after 8.0.11.
 - Error number: `MY-010262`; Symbol: `ER_CONN_TCP_BIND_FAIL`; SQLSTATE: `HY000`
Message: Can't start server: Bind on TCP/IP port: %s
`ER_CONN_TCP_BIND_FAIL` was added in 8.0.12.
 - Error number: `MY-010263`; Symbol: `ER_CONN_TCP_IP_NOT_LOGGED`; SQLSTATE: `HY000`
Message: Fails to print out IP-address.
`ER_CONN_TCP_IP_NOT_LOGGED` was added in 8.0.2.
 - Error number: `MY-010264`; Symbol: `ER_CONN_TCP_RESOLVE_INFO`; SQLSTATE: `HY000`
Message: - '%s' resolves to '%s';
`ER_CONN_TCP_RESOLVE_INFO` was added in 8.0.2.
 - Error number: `MY-010265`; Symbol: `ER_CONN_TCP_START_FAIL`; SQLSTATE: `HY000`
Message: Can't start server: listen() on TCP/IP port: %s
`ER_CONN_TCP_START_FAIL` was added in 8.0.2.
 - Error number: `MY-010266`; Symbol: `ER_CONN_TCP_LISTEN_FAIL`; SQLSTATE: `HY000`
Message: listen() on TCP/IP failed with error %d
`ER_CONN_TCP_LISTEN_FAIL` was added in 8.0.2.
 - Error number: `MY-010267`; Symbol: `ER_CONN_UNIX_PATH_TOO_LONG`; SQLSTATE: `HY000`
Message: The socket file path is too long (> %u): %s
`ER_CONN_UNIX_PATH_TOO_LONG` was added in 8.0.2.
 - Error number: `MY-010268`; Symbol: `ER_CONN_UNIX_LOCK_FILE_FAIL`; SQLSTATE: `HY000`
Message: Unable to setup unix socket lock file.
`ER_CONN_UNIX_LOCK_FILE_FAIL` was added in 8.0.2.
 - Error number: `MY-010269`; Symbol: `ER_CONN_UNIX_NO_FD`; SQLSTATE: `HY000`
Message: Can't start server: UNIX Socket : %s

`ER_CONN_UNIX_NO_FD` was added in 8.0.2.

- Error number: `MY-010270`; Symbol: `ER_CONN_UNIX_NO_BIND_NO_START`; SQLSTATE: `HY000`

Message: Can't start server : Bind on unix socket: %s

`ER_CONN_UNIX_NO_BIND_NO_START` was added in 8.0.2.

- Error number: `MY-010271`; Symbol: `ER_CONN_UNIX_LISTEN_FAILED`; SQLSTATE: `HY000`

Message: listen() on Unix socket failed with error %d

`ER_CONN_UNIX_LISTEN_FAILED` was added in 8.0.2.

- Error number: `MY-010272`; Symbol: `ER_CONN_UNIX_LOCK_FILE_GIVING_UP`; SQLSTATE: `HY000`

Message: Unable to create unix socket lock file %s after retries.

`ER_CONN_UNIX_LOCK_FILE_GIVING_UP` was added in 8.0.2.

- Error number: `MY-010273`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CREATE`; SQLSTATE: `HY000`

Message: Could not create unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010274`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_OPEN`; SQLSTATE: `HY000`

Message: Could not open unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_OPEN` was added in 8.0.2.

- Error number: `MY-010275`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_READ`; SQLSTATE: `HY000`

Message: Could not read unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_CANT_READ` was added in 8.0.2.

- Error number: `MY-010276`; Symbol: `ER_CONN_UNIX_LOCK_FILE_EMPTY`; SQLSTATE: `HY000`

Message: Unix socket lock file is empty %s.

`ER_CONN_UNIX_LOCK_FILE_EMPTY` was added in 8.0.2.

- Error number: `MY-010277`; Symbol: `ER_CONN_UNIX_LOCK_FILE_PIDLESS`; SQLSTATE: `HY000`

Message: Invalid pid in unix socket lock file %s.

`ER_CONN_UNIX_LOCK_FILE_PIDLESS` was added in 8.0.2.

- Error number: `MY-010278`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_WRITE`; SQLSTATE: `HY000`

Message: Could not write unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_WRITE` was added in 8.0.2.

- Error number: `MY-010279`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_DELETE`; SQLSTATE: `HY000`

Message: Could not remove unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_DELETE` was added in 8.0.2.

- Error number: `MY-010280`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_SYNC`; SQLSTATE: `HY000`

Message: Could not sync unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_SYNC` was added in 8.0.2.

- Error number: `MY-010281`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE`; SQLSTATE: `HY000`

Message: Could not close unix socket lock file %s errno %d.

`ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE` was added in 8.0.2.

- Error number: `MY-010282`; Symbol: `ER_CONN_SOCKET_SELECT_FAILED`; SQLSTATE: `HY000`

Message: mysqld: Got error %d from select

`ER_CONN_SOCKET_SELECT_FAILED` was added in 8.0.2.

- Error number: `MY-010283`; Symbol: `ER_CONN_SOCKET_ACCEPT_FAILED`; SQLSTATE: `HY000`

Message: Error in accept: %s

`ER_CONN_SOCKET_ACCEPT_FAILED` was added in 8.0.2.

- Error number: `MY-010284`; Symbol: `ER_AUTH_RSA_CANT_FIND`; SQLSTATE: `HY000`

Message: RSA %s key file not found: %s. Some authentication plugins will not work.

`ER_AUTH_RSA_CANT_FIND` was added in 8.0.2.

- Error number: `MY-010285`; Symbol: `ER_AUTH_RSA_CANT_PARSE`; SQLSTATE: `HY000`

Message: Failure to parse RSA %s key (file exists): %s: %s

`ER_AUTH_RSA_CANT_PARSE` was added in 8.0.2.

- Error number: `MY-010286`; Symbol: `ER_AUTH_RSA_CANT_READ`; SQLSTATE: `HY000`

Message: Failure to read key file: %s

`ER_AUTH_RSA_CANT_READ` was added in 8.0.2.

- Error number: `MY-010287`; Symbol: `ER_AUTH_RSA_FILES_NOT_FOUND`; SQLSTATE: `HY000`

Message: RSA key files not found. Some authentication plugins will not work.

`ER_AUTH_RSA_FILES_NOT_FOUND` was added in 8.0.2.

- Error number: `MY-010288`; Symbol: `ER_CONN_ATTR_TRUNCATED`; SQLSTATE: `HY000`

Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s

`ER_CONN_ATTR_TRUNCATED` was added in 8.0.2.

-
- Error number: [MY-010289](#); Symbol: [ER_X509_CIPHERS_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 ciphers mismatch: should be '%s' but is '%s'
[ER_X509_CIPHERS_MISMATCH](#) was added in 8.0.2.
 - Error number: [MY-010290](#); Symbol: [ER_X509_ISSUER_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 issuer mismatch: should be '%s' but is '%s'
[ER_X509_ISSUER_MISMATCH](#) was added in 8.0.2.
 - Error number: [MY-010291](#); Symbol: [ER_X509_SUBJECT_MISMATCH](#); SQLSTATE: [HY000](#)
Message: X.509 subject mismatch: should be '%s' but is '%s'
[ER_X509_SUBJECT_MISMATCH](#) was added in 8.0.2.
 - Error number: [MY-010292](#); Symbol: [ER_AUTH_CANT_ACTIVATE_ROLE](#); SQLSTATE: [HY000](#)
Message: Failed to activate default role %s for %s
[ER_AUTH_CANT_ACTIVATE_ROLE](#) was added in 8.0.2.
 - Error number: [MY-010293](#); Symbol: [ER_X509_NEEDS_RSA_PRIVKEY](#); SQLSTATE: [HY000](#)
Message: Could not generate RSA private key required for X.509 certificate.
[ER_X509_NEEDS_RSA_PRIVKEY](#) was added in 8.0.2.
 - Error number: [MY-010294](#); Symbol: [ER_X509_CANT_WRITE_KEY](#); SQLSTATE: [HY000](#)
Message: Could not write key file: %s
[ER_X509_CANT_WRITE_KEY](#) was added in 8.0.2.
 - Error number: [MY-010295](#); Symbol: [ER_X509_CANT_CHMOD_KEY](#); SQLSTATE: [HY000](#)
Message: Could not set file permission for %s
[ER_X509_CANT_CHMOD_KEY](#) was added in 8.0.2.
 - Error number: [MY-010296](#); Symbol: [ER_X509_CANT_READ_CA_KEY](#); SQLSTATE: [HY000](#)
Message: Could not read CA key file: %s
[ER_X509_CANT_READ_CA_KEY](#) was added in 8.0.2.
 - Error number: [MY-010297](#); Symbol: [ER_X509_CANT_READ_CA_CERT](#); SQLSTATE: [HY000](#)
Message: Could not read CA certificate file: %s
[ER_X509_CANT_READ_CA_CERT](#) was added in 8.0.2.
 - Error number: [MY-010298](#); Symbol: [ER_X509_CANT_CREATE_CERT](#); SQLSTATE: [HY000](#)
Message: Could not generate X.509 certificate.
[ER_X509_CANT_CREATE_CERT](#) was added in 8.0.2.
 - Error number: [MY-010299](#); Symbol: [ER_X509_CANT_WRITE_CERT](#); SQLSTATE: [HY000](#)
Message: Could not write certificate file: %s
[ER_X509_CANT_WRITE_CERT](#) was added in 8.0.2.

-
- Error number: `MY-010300`; Symbol: `ER_AUTH_CANT_CREATE_RSA_PAIR`; SQLSTATE: `HY000`
Message: Could not generate RSA Private/Public key pair
`ER_AUTH_CANT_CREATE_RSA_PAIR` was added in 8.0.2.
 - Error number: `MY-010301`; Symbol: `ER_AUTH_CANT_WRITE_PRIVKEY`; SQLSTATE: `HY000`
Message: Could not write private key file: %s
`ER_AUTH_CANT_WRITE_PRIVKEY` was added in 8.0.2.
 - Error number: `MY-010302`; Symbol: `ER_AUTH_CANT_WRITE_PUBKEY`; SQLSTATE: `HY000`
Message: Could not write public key file: %s
`ER_AUTH_CANT_WRITE_PUBKEY` was added in 8.0.2.
 - Error number: `MY-010303`; Symbol: `ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION`; SQLSTATE: `HY000`
Message: Skipping generation of SSL certificates as options related to SSL are specified.
`ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION` was added in 8.0.2.
 - Error number: `MY-010304`; Symbol: `ER_AUTH_USING_EXISTING_CERTS`; SQLSTATE: `HY000`
Message: Skipping generation of SSL certificates as certificate files are present in data directory.
`ER_AUTH_USING_EXISTING_CERTS` was added in 8.0.2.
 - Error number: `MY-010305`; Symbol: `ER_AUTH_CERTS_SAVED_TO_DATADIR`; SQLSTATE: `HY000`
Message: Auto generated SSL certificates are placed in data directory.
`ER_AUTH_CERTS_SAVED_TO_DATADIR` was added in 8.0.2.
 - Error number: `MY-010306`; Symbol: `ER_AUTH_CERT_GENERATION_DISABLED`; SQLSTATE: `HY000`
Message: Skipping generation of SSL certificates as `--auto_generate_certs` is set to OFF.
`ER_AUTH_CERT_GENERATION_DISABLED` was added in 8.0.2.
 - Error number: `MY-010307`; Symbol: `ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION`; SQLSTATE: `HY000`
Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.
`ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION` was added in 8.0.2.
 - Error number: `MY-010308`; Symbol: `ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT`; SQLSTATE: `HY000`
Message: Skipping generation of RSA key pair through %s as key files are present in data directory.
`ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT` was added in 8.0.2.
 - Error number: `MY-010309`; Symbol: `ER_AUTH_KEYS_SAVED_TO_DATADIR`; SQLSTATE: `HY000`
Message: Auto generated RSA key files through %s are placed in data directory.
`ER_AUTH_KEYS_SAVED_TO_DATADIR` was added in 8.0.2.

-
- Error number: [MY-010310](#); Symbol: [ER_AUTH_KEY_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair as %s is set to OFF.
[ER_AUTH_KEY_GENERATION_DISABLED](#) was added in 8.0.2.
 - Error number: [MY-010311](#); Symbol: [ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'proxies_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010312](#); Symbol: [ER_AUTHCACHE_PLUGIN_MISSING](#); SQLSTATE: [HY000](#)
Message: The plugin '%.s' used to authenticate user '%s'@'%.s' is not loaded. Nobody can currently login using this account.
[ER_AUTHCACHE_PLUGIN_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010313](#); Symbol: [ER_AUTHCACHE_PLUGIN_CONFIG](#); SQLSTATE: [HY000](#)
Message: The plugin '%s' is used to authenticate user '%s'@'%.s', %s configured. Nobody can currently login using this account.
[ER_AUTHCACHE_PLUGIN_CONFIG](#) was added in 8.0.2.
 - Error number: [MY-010314](#); Symbol: [ER_AUTHCACHE_ROLE_TABLES_DODGY](#); SQLSTATE: [HY000](#)
Message: Could not load mysql.role_edges and mysql.default_roles tables. ACL DDLs will not work unless mysql_upgrade is executed.
[ER_AUTHCACHE_ROLE_TABLES_DODGY](#) was added in 8.0.2, removed after 8.0.4.
 - Error number: [MY-010315](#); Symbol: [ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.
[ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010316](#); Symbol: [ER_AUTHCACHE_USER_TABLE_DODGY](#); SQLSTATE: [HY000](#)
Message: Fatal error: Could not read the column 'authentication_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.
[ER_AUTHCACHE_USER_TABLE_DODGY](#) was added in 8.0.2.
 - Error number: [MY-010317](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.
[ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#) was added in 8.0.2.
 - Error number: [MY-010318](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.
[ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#) was added in 8.0.2.

-
- Error number: [MY-010319](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Found invalid password for user: '%s@%s'; Ignoring user

[ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#) was added in 8.0.2.
 - Error number: [MY-010320](#); Symbol: [ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.

[ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#) was added in 8.0.2.
 - Error number: [MY-010321](#); Symbol: [ER_NO_SUPER_WITHOUT_USER_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

[ER_NO_SUPER_WITHOUT_USER_PLUGIN](#) was added in 8.0.2.
 - Error number: [MY-010322](#); Symbol: [ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)

Message: Found an entry in the 'db' table with empty database name; Skipped

[ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#) was added in 8.0.2.
 - Error number: [MY-010323](#); Symbol: [ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.

[ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010324](#); Symbol: [ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower_case_table_names is set. It will not be possible to remove this privilege using REVOKE.

[ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#) was added in 8.0.2.
 - Error number: [MY-010325](#); Symbol: [ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING](#); SQLSTATE: [HY000](#)

Message: The system table mysql.proxies_priv is missing. Please perform the MySQL upgrade procedure.

[ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010326](#); Symbol: [ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)

Message: Fatal error: Can't open and lock privilege tables: %s

[ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#) was added in 8.0.2.

-
- Error number: [MY-010327](#); Symbol: [ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#); SQLSTATE: [HY000](#)

Message: Fatal: can't initialize grant subsystem - '%s'

[ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#) was added in 8.0.2.
 - Error number: [MY-010328](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

[ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010329](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s' ignored, bad routine type

[ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#) was added in 8.0.2.
 - Error number: [MY-010330](#); Symbol: [ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'tables_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

[ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE](#) was added in 8.0.2.
 - Error number: [MY-010331](#); Symbol: [ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE](#); SQLSTATE: [HY000](#)

Message: Failed to add %s in extra_users. Binary log entry may miss some of the users.

[ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE](#) was added in 8.0.2.
 - Error number: [MY-010332](#); Symbol: [ER_DD_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary schema '%s' does not exist.

[ER_DD_SCHEMA_NOT_FOUND](#) was added in 8.0.2.
 - Error number: [MY-010333](#); Symbol: [ER_DD_TABLE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary table '%s' does not exist.

[ER_DD_TABLE_NOT_FOUND](#) was added in 8.0.2.
 - Error number: [MY-010334](#); Symbol: [ER_DD_SE_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine

[ER_DD_SE_INIT_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010335](#); Symbol: [ER_DD_ABORTING_PARTIAL_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

[ER_DD_ABORTING_PARTIAL_UPGRADE](#) was added in 8.0.2.
 - Error number: [MY-010336](#); Symbol: [ER_DD_FRM_EXISTS_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Found .frm file with same name as one of the Dictionary Tables.

`ER_DD_FRM_EXISTS_FOR_TABLE` was added in 8.0.2.

- Error number: `MY-010337`; Symbol: `ER_DD_CREATED_FOR_UPGRADE`; SQLSTATE: `HY000`

Message: Created Data Dictionary for upgrade

`ER_DD_CREATED_FOR_UPGRADE` was added in 8.0.2.

- Error number: `MY-010338`; Symbol: `ER_ERRMSG_CANT_FIND_FILE`; SQLSTATE: `HY000`

Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.

`ER_ERRMSG_CANT_FIND_FILE` was added in 8.0.2.

- Error number: `MY-010339`; Symbol: `ER_ERRMSG_LOADING_55_STYLE`; SQLSTATE: `HY000`

Message: Using pre 5.5 semantics to load error messages from %s. If this is not intended, refer to the documentation for valid usage of --lc-messages-dir and --language parameters.

`ER_ERRMSG_LOADING_55_STYLE` was added in 8.0.2.

- Error number: `MY-010340`; Symbol: `ER_ERRMSG_MISSING_IN_FILE`; SQLSTATE: `HY000`

Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!

`ER_ERRMSG_MISSING_IN_FILE` was added in 8.0.2.

- Error number: `MY-010341`; Symbol: `ER_ERRMSG_OOM`; SQLSTATE: `HY000`

Message: Not enough memory for messagefile '%s'

`ER_ERRMSG_OOM` was added in 8.0.2.

- Error number: `MY-010342`; Symbol: `ER_ERRMSG_CANT_READ`; SQLSTATE: `HY000`

Message: Can't read from messagefile '%s'

`ER_ERRMSG_CANT_READ` was added in 8.0.2.

- Error number: `MY-010343`; Symbol: `ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD` was added in 8.0.2.

- Error number: `MY-010344`; Symbol: `ER_TABLE_INCOMPATIBLE_YEAR_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

`ER_TABLE_INCOMPATIBLE_YEAR_FIELD` was added in 8.0.2.

- Error number: `MY-010345`; Symbol: `ER_INVALID_CHARSET_AND_DEFAULT_IS_MB`; SQLSTATE: `HY000`

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

`ER_INVALID_CHARSET_AND_DEFAULT_IS_MB` was added in 8.0.2.

- Error number: `MY-010346`; Symbol: `ER_TABLE_WRONG_KEY_DEFINITION`; SQLSTATE: `HY000`

Message: Found wrong key definition in %s; Please do "ALTER TABLE `%(table)s` FORCE " to fix it!

`ER_TABLE_WRONG_KEY_DEFINITION` was added in 8.0.2.

- Error number: `MY-010347`; Symbol: `ER_CANT_OPEN_FRM_FILE`; SQLSTATE: `HY000`

Message: Unable to open file %s

`ER_CANT_OPEN_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010348`; Symbol: `ER_CANT_READ_FRM_FILE`; SQLSTATE: `HY000`

Message: Error in reading file %s

`ER_CANT_READ_FRM_FILE` was added in 8.0.2.

- Error number: `MY-010349`; Symbol: `ER_TABLE_CREATED_WITH_DIFFERENT_VERSION`; SQLSTATE: `HY000`

Message: Table '%s' was created with a different version of MySQL and cannot be read

`ER_TABLE_CREATED_WITH_DIFFERENT_VERSION` was added in 8.0.2.

- Error number: `MY-010350`; Symbol: `ER_VIEW_UNPARSABLE`; SQLSTATE: `HY000`

Message: Unable to read view %s

`ER_VIEW_UNPARSABLE` was added in 8.0.2.

- Error number: `MY-010351`; Symbol: `ER_FILE_TYPE_UNKNOWN`; SQLSTATE: `HY000`

Message: File %s has unknown type in its header.

`ER_FILE_TYPE_UNKNOWN` was added in 8.0.2.

- Error number: `MY-010352`; Symbol: `ER_INVALID_INFO_IN_FRM`; SQLSTATE: `HY000`

Message: Incorrect information in file %s

`ER_INVALID_INFO_IN_FRM` was added in 8.0.2.

- Error number: `MY-010353`; Symbol: `ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES`; SQLSTATE: `HY000`

Message: Can't open and lock privilege tables: %s

`ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES` was added in 8.0.2.

- Error number: `MY-010354`; Symbol: `ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS`; SQLSTATE: `HY000`

Message: Plugin '%s' cannot subscribe to MYSQL_AUDIT_AUTHORIZATION events. Currently not supported.

`ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS` was added in 8.0.2.

- Error number: `MY-010355`; Symbol: `ER_AUDIT_PLUGIN_HAS_INVALID_DATA`; SQLSTATE: `HY000`

Message: Plugin '%s' has invalid data.

`ER_AUDIT_PLUGIN_HAS_INVALID_DATA` was added in 8.0.2.

- Error number: `MY-010356`; Symbol: `ER_TZ_OOM_INITIALIZING_TIME_ZONES`; SQLSTATE: `HY000`

Message: Fatal error: OOM while initializing time zones

`ER_TZ_OOM_INITIALIZING_TIME_ZONES` was added in 8.0.2.

- Error number: `MY-010357`; Symbol: `ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE`; SQLSTATE: `HY000`

Message: Can't open and lock time zone table: %s trying to live without them

`ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE` was added in 8.0.2.

- Error number: `MY-010358`; Symbol: `ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Out of memory while loading mysql.time_zone_leap_second table

`ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010359`; Symbol: `ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: While loading mysql.time_zone_leap_second table: too much leaps

`ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010360`; Symbol: `ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Error while loading mysql.time_zone_leap_second table

`ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE` was added in 8.0.2.

- Error number: `MY-010361`; Symbol: `ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE`; SQLSTATE: `HY000`

Message: Fatal error: Illegal or unknown default time zone '%s'

`ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010362`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%.*s'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010363`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%u'

`ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID` was added in 8.0.2.

- Error number: `MY-010364`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: too big transition type id

`ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE` was added in 8.0.2.

- Error number: `MY-010365`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: not enough room for abbreviations

`ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE` was added in 8.0.2.

- Error number: `MY-010366`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table

`ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010367`; Symbol: `ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: too much transitions

`ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS` was added in 8.0.2.

- Error number: `MY-010368`; Symbol: `ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: bad transition type id

`ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE` was added in 8.0.2.

- Error number: `MY-010369`; Symbol: `ER_TZ_TRANSITION_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table

`ER_TZ_TRANSITION_TABLE_LOAD_ERROR` was added in 8.0.2.

- Error number: `MY-010370`; Symbol: `ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE`; SQLSTATE: `HY000`

Message: loading time zone without transition types

`ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE` was added in 8.0.2.

- Error number: `MY-010371`; Symbol: `ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION`; SQLSTATE: `HY000`

Message: Out of memory while loading time zone description

`ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION` was added in 8.0.2.

- Error number: `MY-010372`; Symbol: `ER_TZ_CANT_BUILD_MKTIME_MAP`; SQLSTATE: `HY000`

Message: Unable to build mktime map for time zone

`ER_TZ_CANT_BUILD_MKTIME_MAP` was added in 8.0.2.

-
- Error number: `MY-010373`; Symbol: `ER_TZ_OOM_WHILE_LOADING_TIME_ZONE`; SQLSTATE: `HY000`

Message: Out of memory while loading time zone

`ER_TZ_OOM_WHILE_LOADING_TIME_ZONE` was added in 8.0.2.
 - Error number: `MY-010374`; Symbol: `ER_TZ_OOM_WHILE_SETTING_TIME_ZONE`; SQLSTATE: `HY000`

Message: Fatal error: Out of memory while setting new time zone

`ER_TZ_OOM_WHILE_SETTING_TIME_ZONE` was added in 8.0.2.
 - Error number: `MY-010375`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD`; SQLSTATE: `HY000`

Message: Slave SQL thread is stopped because UNTIL condition is bad(%s:%llu).

`ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010375`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD`; SQLSTATE: `HY000`

Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).

`ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD` was added in 8.0.33.
 - Error number: `MY-010376`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED`; SQLSTATE: `HY000`

Message: Slave SQL thread stopped because it reached its UNTIL position %llu

`ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010376`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED`; SQLSTATE: `HY000`

Message: Replica SQL thread stopped because it reached its UNTIL position %llu

`ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED` was added in 8.0.33.
 - Error number: `MY-010377`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED`; SQLSTATE: `HY000`

Message: Slave SQL thread stopped because UNTIL SQL_BEFORE_GTIDS %s is already applied

`ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010377`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED`; SQLSTATE: `HY000`

Message: Replica SQL thread stopped because UNTIL SQL_BEFORE_GTIDS %s is already applied

`ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED` was added in 8.0.33.
 - Error number: `MY-010378`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED`; SQLSTATE: `HY000`

Message: Slave SQL thread stopped because it reached UNTIL SQL_BEFORE_GTIDS %s

`ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010378`; Symbol:

`ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED`; SQLSTATE: `HY000`

Message: Replica SQL thread stopped because it reached UNTIL SQL_BEFORE_GTIDS %s

`ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED` was added in 8.0.33.

- Error number: `MY-010379`; Symbol:

`ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED`; SQLSTATE: `HY000`

Message: Slave SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

`ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010379`; Symbol:

`ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED`; SQLSTATE: `HY000`

Message: Replica SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

`ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED` was added in 8.0.33.

- Error number: `MY-010380`; Symbol: `ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED`; SQLSTATE: `HY000`

Message: Slave SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous slave session.

`ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010380`; Symbol:

`ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED`; SQLSTATE: `HY000`

Message: Replica SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous replica session.

`ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED` was added in 8.0.33.

- Error number: `MY-010381`; Symbol: `ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED`; SQLSTATE: `HY000`

Message: Group Replication plugin is not installed.

`ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED` was added in 8.0.2.

- Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`

Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.

`ER_GTID_ALREADY_ADDED_BY_USER` was added in 8.0.2.

- Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Failed to delete the row: '%s' from the gtid_executed table.

`ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE` was added in 8.0.2.

-
- Error number: MY-010384; Symbol: ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE; SQLSTATE: HY000

Message: Failed to compress the gtid_executed table.

ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE was added in 8.0.2.
 - Error number: MY-010385; Symbol: ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM; SQLSTATE: HY000

Message: Failed to compress the gtid_executed table, because it is failed to allocate the THD.

ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM was added in 8.0.2.
 - Error number: MY-010386; Symbol: ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION; SQLSTATE: HY000

Message: Failed to initialize thread attribute when creating compression thread.

ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION was added in 8.0.2.
 - Error number: MY-010387; Symbol: ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD; SQLSTATE: HY000

Message: Can not create thread to compress gtid_executed table (errno= %d)

ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD was added in 8.0.2.
 - Error number: MY-010388; Symbol: ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD; SQLSTATE: HY000

Message: Could not join gtid_executed table compression thread. error:%d

ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD was added in 8.0.2.
 - Error number: MY-010389; Symbol: ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR; SQLSTATE: HY000

Message: Can't start server : Initialize security descriptor: %s

ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR was added in 8.0.2.
 - Error number: MY-010390; Symbol: ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR; SQLSTATE: HY000

Message: Can't start server : Set security descriptor: %s

ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR was added in 8.0.2.
 - Error number: MY-010391; Symbol: ER_NPIPE_PIPE_ALREADY_IN_USE; SQLSTATE: HY000

Message: Can't start server : Named Pipe "%s" already in use.

ER_NPIPE_PIPE_ALREADY_IN_USE was added in 8.0.2.

-
- Error number: MY-010392; Symbol:

ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_ON_START; SQLSTATE: HY000

Message: NDB Slave : At SQL thread start applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu. Check slave positioning.

ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_ON_START was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010393; Symbol: ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS; SQLSTATE: HY000

Message: NDB Slave : SQL thread stopped as applying epoch %llu/%llu (%llu) from Master ServerId %u which is lower than previously applied epoch %llu/%llu (%llu). Group Master Log : %s Group Master Log Pos : %llu

ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010394; Symbol: ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH; SQLSTATE: HY000

Message: NDB Slave : SQL thread stopped as attempted to reapply already committed epoch %llu/%llu (%llu) from server id %u. Group Master Log : %s Group Master Log Pos : %llu.

ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010395; Symbol: ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED; SQLSTATE: HY000

Message: NDB Slave : SQL thread stopped as attempting to apply new epoch %llu/%llu (%llu) while lower received epoch %llu/%llu (%llu) has not been committed. Master server id : %u. Group Master Log : %s Group Master Log Pos : %llu.

ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010396; Symbol: ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN; SQLSTATE: HY000

Message: NDB Slave: missing data for %s timestamp column %u.

ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010397; Symbol: ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO; SQLSTATE: HY000

Message: NDB Slave: Table %s.%s logging exceptions to %s.%s

ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010398; Symbol: ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION; SQLSTATE: HY000

Message: NDB Slave: Table %s.%s : %s, low epoch resolution

ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010399; Symbol: ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE; SQLSTATE: HY000

Message: Found unexpected field type %u

`ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010400`; Symbol: `ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO`; SQLSTATE: `HY000`

Message: Failed to create NdbInfo

`ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010401`; Symbol: `ER_NDB_INFO_FAILED_TO_INIT_NDBINFO`; SQLSTATE: `HY000`

Message: Failed to init NdbInfo

`ER_NDB_INFO_FAILED_TO_INIT_NDBINFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010402`; Symbol: `ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS`; SQLSTATE: `HY000`

Message: `ndb_serialize_cond`: Unexpected mismatch of found and expected number of function arguments %u

`ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010403`; Symbol: `ER_NDB_CLUSTER_SCHEMA_INFO`; SQLSTATE: `HY000`

Message: %s - %s.%s

`ER_NDB_CLUSTER_SCHEMA_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010404`; Symbol: `ER_NDB_CLUSTER_GENERIC_MESSAGE`; SQLSTATE: `HY000`

Message: %s

`ER_NDB_CLUSTER_GENERIC_MESSAGE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010405`; Symbol: `ER_RPL_CANT_OPEN_INFO_TABLE`; SQLSTATE: `HY000`

Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.

`ER_RPL_CANT_OPEN_INFO_TABLE` was added in 8.0.2.

- Error number: `MY-010406`; Symbol: `ER_RPL_CANT_SCAN_INFO_TABLE`; SQLSTATE: `HY000`

Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.

`ER_RPL_CANT_SCAN_INFO_TABLE` was added in 8.0.2.

- Error number: `MY-010407`; Symbol: `ER_RPL_CORRUPTED_INFO_TABLE`; SQLSTATE: `HY000`

Message: Corrupted table %s.%s. Check out table definition.

`ER_RPL_CORRUPTED_INFO_TABLE` was added in 8.0.2.

- Error number: `MY-010408`; Symbol: `ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE`; SQLSTATE: `HY000`

Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.

`ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE` was added in 8.0.2.

-
- Error number: `MY-010409`; Symbol: `ER_RPL_WORKER_ID_IS`; SQLSTATE: `HY000`
Message: Choosing worker id %lu, the following is going to be %lu
`ER_RPL_WORKER_ID_IS` was added in 8.0.2.
 - Error number: `MY-010410`; Symbol: `ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX`; SQLSTATE: `HY000`
Message: Transaction is tagged with inconsistent logical timestamps: sequence_number (%lld) <= last_committed (%lld)
`ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX` was added in 8.0.2.
 - Error number: `MY-010411`; Symbol: `ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX`; SQLSTATE: `HY000`
Message: Transaction's sequence number is inconsistent with that of a preceding one: sequence_number (%lld) <= previous sequence_number (%lld)
`ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX` was added in 8.0.2.
 - Error number: `MY-010412`; Symbol: `ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES`; SQLSTATE: `HY000`
Message: For the creation of replication channels the connection metadata and applier metadata repositories must be set to TABLE
`ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES` was added in 8.0.2.
 - Error number: `MY-010413`; Symbol: `ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID`; SQLSTATE: `HY000`
Message: For the creation of replication channels the server id must be different from 0
`ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID` was added in 8.0.2.
 - Error number: `MY-010414`; Symbol: `ER_RPL_REPO_SHOULD_BE_TABLE`; SQLSTATE: `HY000`
Message: Replica: Wrong repository. Repository should be TABLE
`ER_RPL_REPO_SHOULD_BE_TABLE` was added in 8.0.2.
 - Error number: `MY-010415`; Symbol: `ER_RPL_ERROR_CREATING_MASTER_INFO`; SQLSTATE: `HY000`
Message: Error creating master info: %s.
`ER_RPL_ERROR_CREATING_MASTER_INFO` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010415`; Symbol: `ER_RPL_ERROR_CREATING_CONNECTION_METADATA`; SQLSTATE: `HY000`
Message: Error creating connection metadata: %s.
`ER_RPL_ERROR_CREATING_CONNECTION_METADATA` was added in 8.0.33.
 - Error number: `MY-010416`; Symbol: `ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE`; SQLSTATE: `HY000`
Message: Error changing the type of master info's repository: %s.
`ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE` was added in 8.0.2, removed after 8.0.32.

-
- Error number: [MY-010416](#); Symbol: [ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REPO_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of connection metadata's repository: %s.

[ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REPO_TYPE](#) was added in 8.0.33.
 - Error number: [MY-010417](#); Symbol: [ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED_DUE_TO_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay_log_info_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED_DUE_TO_GAPS](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010417](#); Symbol: [ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE_FAILED_DUE_TO_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay_log_info_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

[ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE_FAILED_DUE_TO_GAPS](#) was added in 8.0.33.
 - Error number: [MY-010418](#); Symbol: [ER_RPL_ERROR_CREATING_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: Error creating relay log info: %s.

[ER_RPL_ERROR_CREATING_RELAY_LOG_INFO](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010418](#); Symbol: [ER_RPL_ERROR_CREATING_APPLIER_METADATA](#); SQLSTATE: [HY000](#)

Message: Error creating applier metadata: %s.

[ER_RPL_ERROR_CREATING_APPLIER_METADATA](#) was added in 8.0.33.
 - Error number: [MY-010419](#); Symbol: [ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of relay log info's repository: %s.

[ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010419](#); Symbol: [ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE](#); SQLSTATE: [HY000](#)

Message: Error changing the type of applier metadata's repository: %s.

[ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE](#) was added in 8.0.33.
 - Error number: [MY-010420](#); Symbol: [ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not delete from Slave Workers info repository.

[ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKERS_INFO_REPOSITORY](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010420](#); Symbol: [ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not delete from Replica Workers info repository.

[ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY](#) was added in 8.0.33.

- Error number: [MY-010421](#); Symbol: [ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not store the reset Slave Worker state into the slave info repository.

[ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO_REPOSITORY](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010421](#); Symbol: [ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not store the reset Replica Worker state into the replica info repository.

[ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY](#) was added in 8.0.33.

- Error number: [MY-010422](#); Symbol: [ER_RPL_ERROR_CHECKING_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Error in checking %s repository info type of %s.

[ER_RPL_ERROR_CHECKING_REPOSITORY](#) was added in 8.0.2.

- Error number: [MY-010423](#); Symbol: [ER_RPL_SLAVE_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Slave: %s

[ER_RPL_SLAVE_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010423](#); Symbol: [ER_RPL_REPLICA_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Replica: %s

[ER_RPL_REPLICA_GENERIC_MESSAGE](#) was added in 8.0.33.

- Error number: [MY-010424](#); Symbol: [ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST](#); SQLSTATE: [HY000](#)

Message: Slave: Could not create channel list

[ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010424](#); Symbol: [ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST](#); SQLSTATE: [HY000](#)

Message: Replica: Could not create channel list

[ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST](#) was added in 8.0.33.

-
- Error number: MY-010425; Symbol:

`ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES`; SQLSTATE: HY000

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

`ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES` was added in 8.0.2.

- Error number: MY-010426; Symbol:

`ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE`; SQLSTATE: HY000

Message: Slave: Failed to initialize the master info structure for channel '%s'; its record may still be present in 'mysql.slave_master_info' table, consider deleting it.

`ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: MY-010426; Symbol:

`ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: HY000

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

`ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: MY-010427; Symbol:

`ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE`; SQLSTATE: HY000

Message: Failed to initialize the master info structure%s

`ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRUCTURE` was added in 8.0.2, removed after 8.0.32.

- Error number: MY-010427; Symbol:

`ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: HY000

Message: Failed to initialize the connection metadata structure%s

`ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE` was added in 8.0.33.

- Error number: MY-010428; Symbol:

`ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO`; SQLSTATE: HY000

Message: Slave: Failed to create a channel from master info table repository.

`ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: MY-010428; Symbol:

`ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA`; SQLSTATE: HY000

Message: Replica: Failed to create a channel from connection metadata repository.

`ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA` was added in 8.0.33.

-
- Error number: `MY-010429`; Symbol: `ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a new info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE` was added in 8.0.2.
 - Error number: `MY-010430`; Symbol: `ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a cache on info file (file '%s')

`ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE` was added in 8.0.2.
 - Error number: `MY-010431`; Symbol: `ER_RPL_FAILED_TO_OPEN_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to open the existing info file (file '%s', errno %d)

`ER_RPL_FAILED_TO_OPEN_INFO_FILE` was added in 8.0.2.
 - Error number: `MY-010432`; Symbol: `ER_RPL_GTID_MEMORY_FINALY_AVAILABLE`; SQLSTATE: `HY000`

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

`ER_RPL_GTID_MEMORY_FINALY_AVAILABLE` was added in 8.0.2.
 - Error number: `MY-010433`; Symbol: `ER_SERVER_COST_UNKNOWN_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Unknown cost constant "%s" in mysql.server_cost table

`ER_SERVER_COST_UNKNOWN_COST_CONSTANT` was added in 8.0.2.
 - Error number: `MY-010434`; Symbol: `ER_SERVER_COST_INVALID_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Invalid value for cost constant "%s" in mysql.server_cost table: %.1f

`ER_SERVER_COST_INVALID_COST_CONSTANT` was added in 8.0.2.
 - Error number: `MY-010435`; Symbol: `ER_ENGINE_COST_UNKNOWN_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Unknown cost constant "%s" in mysql.engine_cost table

`ER_ENGINE_COST_UNKNOWN_COST_CONSTANT` was added in 8.0.2.
 - Error number: `MY-010436`; Symbol: `ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE`; SQLSTATE: `HY000`

Message: Unknown storage engine "%s" in mysql.engine_cost table

`ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE` was added in 8.0.2.
 - Error number: `MY-010437`; Symbol: `ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE`; SQLSTATE: `HY000`

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine_cost table

`ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE` was added in 8.0.2.

-
- Error number: [MY-010438](#); Symbol: [ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine_cost table: %.1f

[ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#) was added in 8.0.2.
 - Error number: [MY-010439](#); Symbol: [ER_SERVER_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.server_cost table.

[ER_SERVER_COST_FAILED_TO_READ](#) was added in 8.0.2.
 - Error number: [MY-010440](#); Symbol: [ER_ENGINE_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.engine_cost table.

[ER_ENGINE_COST_FAILED_TO_READ](#) was added in 8.0.2.
 - Error number: [MY-010441](#); Symbol: [ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open optimizer cost constant tables

[ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#) was added in 8.0.2.
 - Error number: [MY-010442](#); Symbol: [ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: Unsupported non-ignorable event fed into the event stream.

[ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#) was added in 8.0.2.
 - Error number: [MY-010443](#); Symbol: [ER_RPL_GTID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: GTID_LOG_EVENT or ANONYMOUS_GTID_LOG_EVENT is not expected in an event stream %s.

[ER_RPL_GTID_LOG_EVENT_IN_STREAM](#) was added in 8.0.2.
 - Error number: [MY-010444](#); Symbol: [ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.

[ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#) was added in 8.0.2.
 - Error number: [MY-010445](#); Symbol: [ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(COMMIT or ROLLBACK) or XID_LOG_EVENT is not expected in an event stream %s.

[ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#) was added in 8.0.2.

-
- Error number: MY-010446; Symbol: ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM; SQLSTATE: HY000

Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.

ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM was added in 8.0.2.

- Error number: MY-010447; Symbol: ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER; SQLSTATE: HY000

Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.

ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER was added in 8.0.2.

- Error number: MY-010448; Symbol: ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE; SQLSTATE: HY000

Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.

ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE was added in 8.0.2.

- Error number: MY-010449; Symbol: ER_EVENT_ERROR_DURING_COMPILATION; SQLSTATE: HY000

Message: Event Scheduler: %serror during compilation of %s.%s

ER_EVENT_ERROR_DURING_COMPILATION was added in 8.0.2.

- Error number: MY-010450; Symbol: ER_EVENT_DROPPING; SQLSTATE: HY000

Message: Event Scheduler: Dropping %s.%s

ER_EVENT_DROPPING was added in 8.0.2.

- Error number: MY-010451; Symbol: ER_NDB_SCHEMA_GENERIC_MESSAGE; SQLSTATE: HY000

Message: Ndb schema[%s.%s]: %s

ER_NDB_SCHEMA_GENERIC_MESSAGE was added in 8.0.2, removed after 8.0.13.

- Error number: MY-010452; Symbol: ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR; SQLSTATE: HY000

Message: In RBR mode, Replica received incompatible DECIMAL field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing ALTER command for column Name: %s.%s.%s.

ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR was added in 8.0.2.

- Error number: MY-010453; Symbol: ER_INIT_ROOT_WITHOUT_PASSWORD; SQLSTATE: HY000

Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.

ER_INIT_ROOT_WITHOUT_PASSWORD was added in 8.0.2.

- Error number: MY-010454; Symbol: ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT; SQLSTATE: HY000

Message: A temporary password is generated for root@localhost: %s

ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT was added in 8.0.2.

-
- Error number: MY-010455; Symbol: ER_INIT_CANT_OPEN_BOOTSTRAP_FILE; SQLSTATE: HY000
Message: Failed to open the bootstrap file %s
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE was added in 8.0.2.
 - Error number: MY-010456; Symbol: ER_INIT_BOOTSTRAP_COMPLETE; SQLSTATE: HY000
Message: Bootstrapping complete
ER_INIT_BOOTSTRAP_COMPLETE was added in 8.0.2.
 - Error number: MY-010457; Symbol: ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE; SQLSTATE: HY000
Message: --initialize specified but the data directory has files in it. Aborting.
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE was added in 8.0.2.
 - Error number: MY-010458; Symbol: ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE; SQLSTATE: HY000
Message: --initialize specified on an existing data directory.
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE was added in 8.0.2.
 - Error number: MY-010459; Symbol: ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE; SQLSTATE: HY000
Message: --initialize specified but the data directory exists and the path is too long. Aborting.
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE was added in 8.0.2.
 - Error number: MY-010460; Symbol: ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE; SQLSTATE: HY000
Message: --initialize specified but the data directory exists and is not writable. Aborting.
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE was added in 8.0.2.
 - Error number: MY-010461; Symbol: ER_INIT_CREATING_DD; SQLSTATE: HY000
Message: Creating the data directory %s
ER_INIT_CREATING_DD was added in 8.0.2.
 - Error number: MY-010462; Symbol: ER_RPL_BINLOG_STARTING_DUMP; SQLSTATE: HY000
Message: Start binlog_dump to source_thread_id(%u) replica_server(%u), pos(%s, %llu)
ER_RPL_BINLOG_STARTING_DUMP was added in 8.0.2.
 - Error number: MY-010463; Symbol: ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT; SQLSTATE: HY000
Message: master sends heartbeat message
ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT was added in 8.0.2, removed after 8.0.32.
 - Error number: MY-010463; Symbol: ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT; SQLSTATE: HY000
Message: source sends heartbeat message
-

`ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT` was added in 8.0.33.

- Error number: `MY-010464`; Symbol:

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO`; SQLSTATE: `HY000`

Message: the rest of heartbeat info skipped ...

`ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO` was added in 8.0.2.

- Error number: `MY-010465`; Symbol:

`ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT`; SQLSTATE: `HY000`

Message: Master is configured to log replication events with checksum, but will not send such events to slaves that cannot process them

`ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010465`; Symbol:

`ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT`; SQLSTATE: `HY000`

Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them

`ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT` was added in 8.0.33.

- Error number: `MY-010466`; Symbol: `ER_NDB_QUERY_FAILED`; SQLSTATE: `HY000`

Message: NDB: Query '%s' failed, error: %d: %s

`ER_NDB_QUERY_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010467`; Symbol: `ER_KILLING_THREAD`; SQLSTATE: `HY000`

Message: Killing thread %lu

`ER_KILLING_THREAD` was added in 8.0.2.

- Error number: `MY-010468`; Symbol: `ER_DETACHING_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

`ER_DETACHING_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010469`; Symbol: `ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Failed to detach the session.

`ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010470`; Symbol: `ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`

Message: Closed forcefully %u session%s left opened by plugin %s

`ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN` was added in 8.0.2.

- Error number: `MY-010471`; Symbol: `ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS`; SQLSTATE: `HY000`

Message: Failed to decrement the number of threads

[ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS](#) was added in 8.0.2.

- Error number: [MY-010472](#); Symbol: [ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#); SQLSTATE: [HY000](#)

Message: Plugin %s did not deinitialize %u threads

[ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#) was added in 8.0.2.

- Error number: [MY-010473](#); Symbol: [ER_KILLED_THREADS_OF_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Killed %u threads of plugin %s

[ER_KILLED_THREADS_OF_PLUGIN](#) was added in 8.0.2.

- Error number: [MY-010474](#); Symbol: [ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: NDB Slave : Could not determine maximum replicated epoch from %s.%s at Slave start, error %u %s

[ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010475](#); Symbol: [ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO](#); SQLSTATE: [HY000](#)

Message: NDB Slave : MaxReplicatedEpoch set to %llu (%u/%u) at Slave start

[ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010476](#); Symbol: [ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: NodeID is %lu, management server '%s:%lu'

[ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010477](#); Symbol: [ER_NDB_DISCONNECT_INFO](#); SQLSTATE: [HY000](#)

Message: tid %u: node[%u] transaction_hint=%u, transaction_no_hint=%u

[ER_NDB_DISCONNECT_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010478](#); Symbol: [ER_NDB_COLUMN_DEFAULTS_DIFFER](#); SQLSTATE: [HY000](#)

Message: NDB Internal error: Default values differ for column %u, ndb_default: %d

[ER_NDB_COLUMN_DEFAULTS_DIFFER](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010479](#); Symbol: [ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT](#); SQLSTATE: [HY000](#)

Message: NDB Internal error: Column %u has native default, but shouldn't. Flags=%u, type=%u

[ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010480](#); Symbol: [ER_NDB_FIELD_INFO](#); SQLSTATE: [HY000](#)

Message: field[name: '%s', type: %u, real_type: %u, flags: 0x%x, is_null: %d]

[ER_NDB_FIELD_INFO](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010481](#); Symbol: [ER_NDB_COLUMN_INFO](#); SQLSTATE: [HY000](#)
Message: `ndbCol[name: '%s', type: %u, column_no: %d, nullable: %d]`
[ER_NDB_COLUMN_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010482](#); Symbol: [ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER](#); SQLSTATE: [HY000](#)
Message: `fix_unique_index_attr_order: my_malloc(%u) failure`
[ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010483](#); Symbol: [ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE](#); SQLSTATE: [HY000](#)
Message: `NDB Slave : Malformed event received on table %s cannot parse. Stopping Slave.`
[ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010484](#); Symbol: [ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE](#); SQLSTATE: [HY000](#)
Message: `NDB Slave : Conflict function %s defined on table %s requires ndb_slave_conflict_role variable to be set. Stopping slave.`
[ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010485](#); Symbol: [ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_IDS](#); SQLSTATE: [HY000](#)
Message: `NDB Slave : Transactional conflict detection defined on table %s, but events received without transaction ids. Check --ndb-log-transaction-id setting on upstream Cluster.`
[ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_IDS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010486](#); Symbol: [ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION](#); SQLSTATE: [HY000](#)
Message: `NDB Slave : Binlog event on table %s missing info necessary for conflict detection. Check binlog format options on upstream cluster.`
[ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DETECTION](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010487](#); Symbol: [ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE](#); SQLSTATE: [HY000](#)
Message: `Error %lu in readAutoIncrementValue(): %s`
[ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010488](#); Symbol: [ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT](#); SQLSTATE: [HY000](#)
Message: `found uncommitted autocommit+rbwr transaction, commit status: %d`
[ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010489](#); Symbol: [ER_NDB_SLAVE_TOO_MANY_RETRIES](#); SQLSTATE: [HY000](#)

Message: Ndb slave retried transaction %u time(s) in vain. Giving up.

[ER_NDB_SLAVE_TOO_MANY_RETRIES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010490](#); Symbol: [ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO](#); SQLSTATE: [HY000](#)

Message: Error %lu in ::update_create_info(): %s

[ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010491](#); Symbol: [ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE](#); SQLSTATE: [HY000](#)

Message: NDB: allocating table share for %s failed

[ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010492](#); Symbol: [ER_NDB_BINLOG_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: (%d)%s

[ER_NDB_BINLOG_ERROR_INFO_FROM_DA](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010493](#); Symbol: [ER_NDB_BINLOG_CREATE_TABLE_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: CREATE TABLE Event: %s

[ER_NDB_BINLOG_CREATE_TABLE_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010494](#); Symbol: [ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATIONS](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: FAILED CREATE TABLE event operations. Event: %s

[ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATIONS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010495](#); Symbol: [ER_NDB_BINLOG_RENAME_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: RENAME Event: %s

[ER_NDB_BINLOG_RENAME_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010496](#); Symbol: [ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DURING_RENAME](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: FAILED create event operations during RENAME. Event %s

[ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DURING_RENAME](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010497](#); Symbol: [ER_NDB_UNEXPECTED_RENAME_TYPE](#); SQLSTATE: [HY000](#)

Message: Unexpected rename case detected, sql_command: %d

[ER_NDB_UNEXPECTED_RENAME_TYPE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010498](#); Symbol: [ER_NDB_ERROR_IN_GET_AUTO_INCREMENT](#); SQLSTATE: [HY000](#)

Message: Error %lu in ::get_auto_increment(): %s

[ER_NDB_ERROR_IN_GET_AUTO_INCREMENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010499](#); Symbol: [ER_NDB_CREATING_SHARE_IN_OPEN](#); SQLSTATE: [HY000](#)

Message: Calling ndbcluster_create_binlog_setup(%s) in ::open

[ER_NDB_CREATING_SHARE_IN_OPEN](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010500](#); Symbol: [ER_NDB_TABLE_OPENED_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: table '%s' opened read only

[ER_NDB_TABLE_OPENED_READ_ONLY](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010501](#); Symbol: [ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED](#); SQLSTATE: [HY000](#)

Message: NDB: '--initialize' -> ndbcluster plugin disabled

[ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010502](#); Symbol: [ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED](#); SQLSTATE: [HY000](#)

Message: NDB: Changed global value of binlog_format from STATEMENT to MIXED

[ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010503](#); Symbol: [ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB_SHARE: trailing share %s, released by close_cached_tables

[ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHED_TABLES](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010504](#); Symbol: [ER_NDB_SHARE_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: NDB_SHARE: %s already exists use_count=%d. Moving away for safety, but possible memleak.

[ER_NDB_SHARE_ALREADY_EXISTS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010505](#); Symbol: [ER_NDB_HANDLE_TRAILING_SHARE_INFO](#); SQLSTATE: [HY000](#)

Message: handle_trailing_share: %s use_count: %u

[ER_NDB_HANDLE_TRAILING_SHARE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010506](#); Symbol: [ER_NDB_CLUSTER_GET_SHARE_INFO](#); SQLSTATE: [HY000](#)

Message: ndbcluster_get_share: %s use_count: %u

[ER_NDB_CLUSTER_GET_SHARE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010507](#); Symbol: [ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO](#); SQLSTATE: [HY000](#)

Message: ndbcluster_real_free_share: %s use_count: %u

[ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010508](#); Symbol: [ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED](#); SQLSTATE: [HY000](#)

Message: ndbcluster_real_free_share: %s, still open - ignored 'free' (leaked?)

[ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010509](#); Symbol: [ER_NDB_CLUSTER_FREE_SHARE_INFO](#); SQLSTATE: [HY000](#)

Message: ndbcluster_free_share: %s use_count: %u

[ER_NDB_CLUSTER_FREE_SHARE_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010510](#); Symbol: [ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO](#); SQLSTATE: [HY000](#)

Message: ndbcluster_mark_share_dropped: %s use_count: %u

[ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010511](#); Symbol: [ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE](#); SQLSTATE: [HY000](#)

Message: ndbcluster_mark_share_dropped: destroys share %s

[ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING_SHARE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010512](#); Symbol: [ER_NDB_CLUSTER_OOM_THD_NDB](#); SQLSTATE: [HY000](#)

Message: Could not allocate Thd_ndb object

[ER_NDB_CLUSTER_OOM_THD_NDB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010513](#); Symbol: [ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Ndb tables initially read only.

[ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010514](#); Symbol: [ER_NDB_UTIL_THREAD_OOM](#); SQLSTATE: [HY000](#)

Message: ndb util thread: malloc failure, query cache not maintained properly

[ER_NDB_UTIL_THREAD_OOM](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010515](#); Symbol: [ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK](#); SQLSTATE: [HY000](#)

Message: Trying to set ndb_recv_thread_cpu_mask to illegal value = %s, ignored

[ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010516](#); Symbol: [ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK](#); SQLSTATE: [HY000](#)

Message: Trying to set too many CPU's in `ndb_recv_thread_cpu_mask`, ignored this variable, erroneous value = %s

`ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CPU_MASK` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010517`; Symbol: `ER_DEBUG_CHECK_SHARES_OPEN`; SQLSTATE: `HY000`

Message: `debug_check_shares` open:

`ER_DEBUG_CHECK_SHARES_OPEN` was added in 8.0.2.

- Error number: `MY-010518`; Symbol: `ER_DEBUG_CHECK_SHARES_INFO`; SQLSTATE: `HY000`

Message: %s.%s: state: %s(%u) use_count: %u

`ER_DEBUG_CHECK_SHARES_INFO` was added in 8.0.2.

- Error number: `MY-010519`; Symbol: `ER_DEBUG_CHECK_SHARES_DROPPED`; SQLSTATE: `HY000`

Message: `debug_check_shares` dropped:

`ER_DEBUG_CHECK_SHARES_DROPPED` was added in 8.0.2.

- Error number: `MY-010520`; Symbol: `ER_INVALID_OR_OLD_TABLE_OR_DB_NAME`; SQLSTATE: `HY000`

Message: Invalid (old?) table or database name '%s'

`ER_INVALID_OR_OLD_TABLE_OR_DB_NAME` was added in 8.0.2.

- Error number: `MY-010521`; Symbol: `ER_TC_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`

Message: Recovering after a crash using %s

`ER_TC_RECOVERING_AFTER_CRASH_USING` was added in 8.0.2.

- Error number: `MY-010522`; Symbol: `ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`

Message: Cannot perform automatic crash recovery when `--tc-heuristic-recover` is used

`ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER` was added in 8.0.2.

- Error number: `MY-010523`; Symbol: `ER_TC_BAD_MAGIC_IN_TC_LOG`; SQLSTATE: `HY000`

Message: Bad magic header in tc log

`ER_TC_BAD_MAGIC_IN_TC_LOG` was added in 8.0.2.

- Error number: `MY-010524`; Symbol: `ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY`; SQLSTATE: `HY000`

Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol

`ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY` was added in 8.0.2.

-
- Error number: [MY-010525](#); Symbol: [ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with --tc-heuristic-recover={commit|rollback}

[ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS](#) was added in 8.0.2.
 - Error number: [MY-010526](#); Symbol: [ER_TC_HEURISTIC_RECOVERY_MODE](#); SQLSTATE: [HY000](#)

Message: Heuristic crash recovery mode

[ER_TC_HEURISTIC_RECOVERY_MODE](#) was added in 8.0.2.
 - Error number: [MY-010527](#); Symbol: [ER_TC_HEURISTIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Heuristic crash recovery failed

[ER_TC_HEURISTIC_RECOVERY_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010528](#); Symbol: [ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: Please restart mysqld without --tc-heuristic-recover

[ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER](#) was added in 8.0.2.
 - Error number: [MY-010529](#); Symbol:
[ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Failed to create or recover replication info repositories.

[ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010529](#); Symbol:
[ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES](#); SQLSTATE: [HY000](#)

Message: Failed to create or recover replication info repositories.

[ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES](#) was added in 8.0.33.
 - Error number: [MY-010530](#); Symbol:
[ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE MASTER TO MASTER_AUTO_POSITION = 0 FOR CHANNEL '%s', or change GTID_MODE to some value other than OFF, before starting the slave receiver thread.

[ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010530](#); Symbol:
[ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 FOR CHANNEL '%s', or change GTID_MODE to some value other than OFF, before starting the replica receiver thread.

`ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF` was added in 8.0.33.

- Error number: `MY-010531`; Symbol: `ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Slave: Could not start slave for channel '%s'. operation discontinued

`ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010531`; Symbol: `ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Replica: Could not start replica for channel '%s'. operation discontinued

`ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL` was added in 8.0.33.

- Error number: `MY-010532`; Symbol: `ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Slave: Could not stop slave for channel '%s' operation discontinued

`ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010532`; Symbol: `ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL`; SQLSTATE: `HY000`

Message: Replica: Could not stop replica for channel '%s' operation discontinued

`ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL` was added in 8.0.33.

- Error number: `MY-010533`; Symbol: `ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Could not locate rotate event from the master.

`ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010533`; Symbol: `ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Could not locate rotate event from the source.

`ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE` was added in 8.0.33.

- Error number: `MY-010534`; Symbol: `ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Error reading events from relay log: %d

`ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG` was added in 8.0.2.

- Error number: `MY-010535`; Symbol: `ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Error while freeing IO_CACHE object

`ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE` was added in 8.0.2, removed after 8.0.12.

- Error number: `MY-010536`; Symbol: `ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL`; SQLSTATE: `HY000`

Message: Relay log recovery skipped for group replication channel.

`ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL` was added in 8.0.2.

- Error number: `MY-010537`; Symbol: `ER_RPL_RECOVERY_ERROR`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: %s

`ER_RPL_RECOVERY_ERROR` was added in 8.0.2.

- Error number: `MY-010538`; Symbol: `ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

`ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX` was added in 8.0.2.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_MASTER_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from master pos %ld and file %s%. Previous relay log pos and relay log file had been set to %ld, %s respectively.

`ER_RPL_RECOVERY_FILE_MASTER_POS_INFO` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010539`; Symbol: `ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO`; SQLSTATE: `HY000`

Message: Recovery from source pos %ld and file %s%. Previous relay log pos and relay log file had been set to %ld, %s respectively.

`ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO` was added in 8.0.33.

- Error number: `MY-010540`; Symbol: `ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION`; SQLSTATE: `HY000`

Message: Error during --relay-log-recovery: replicate_same_server_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.

`ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION` was added in 8.0.2.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTS recovery: starting coordinator thread to fill MTS gaps.

`ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010541`; Symbol: `ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR`; SQLSTATE: `HY000`

Message: MTA recovery: starting coordinator thread to fill MTA gaps.

`ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR` was added in 8.0.33.

- Error number: `MY-010542`; Symbol: `ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR`; SQLSTATE: `HY000`

Message: MTS recovery: failed to start the coordinator thread. Check the error log for additional details.

`ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR` was added in 8.0.2, removed after 8.0.32.

-
- Error number: [MY-010542](#); Symbol: [ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.

[ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR](#) was added in 8.0.33.
 - Error number: [MY-010543](#); Symbol: [ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: MTS recovery: automatic recovery failed. Either the slave server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the slave side error and restart the slave server or consider using RESET SLAVE.

[ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010543](#); Symbol: [ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICA.

[ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED](#) was added in 8.0.33.
 - Error number: [MY-010544](#); Symbol: [ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay_log_pos %s).

[ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010544](#); Symbol: [ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay_log_pos %s).

[ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG](#) was added in 8.0.33.
 - Error number: [MY-010545](#); Symbol: [ER_RPL_MTS_RECOVERY_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTS recovery: completed successfully.

[ER_RPL_MTS_RECOVERY_SUCCESSFUL](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010545](#); Symbol: [ER_RPL_MTA_RECOVERY_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTA recovery: completed successfully.

[ER_RPL_MTA_RECOVERY_SUCCESSFUL](#) was added in 8.0.33.
 - Error number: [MY-010546](#); Symbol: [ER_RPL_SERVER_ID_MISSING](#); SQLSTATE: [HY000](#)

Message: Server id not set, will not start replica%s

[ER_RPL_SERVER_ID_MISSING](#) was added in 8.0.2.
 - Error number: [MY-010547](#); Symbol: [ER_RPL_CANT_CREATE_SLAVE_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create slave thread%s.

[ER_RPL_CANT_CREATE_SLAVE_THREAD](#) was added in 8.0.2, removed after 8.0.32.

-
- Error number: `MY-010547`; Symbol: `ER_RPL_CANT_CREATE_REPLICA_THREAD`; SQLSTATE: `HY000`

Message: Can't create replica thread%s.

`ER_RPL_CANT_CREATE_REPLICA_THREAD` was added in 8.0.33.
 - Error number: `MY-010548`; Symbol: `ER_RPL_SLAVE_IO_THREAD_WAS_KILLED`; SQLSTATE: `HY000`

Message: The slave IO thread%s was killed while executing initialization query '%s'

`ER_RPL_SLAVE_IO_THREAD_WAS_KILLED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010548`; Symbol: `ER_RPL_REPLICA_IO_THREAD_WAS_KILLED`; SQLSTATE: `HY000`

Message: The replica IO thread%s was killed while executing initialization query '%s'

`ER_RPL_REPLICA_IO_THREAD_WAS_KILLED` was added in 8.0.33.
 - Error number: `MY-010549`; Symbol: `ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED`; SQLSTATE: `HY000`

Message: The master's UUID has changed, although this should not happen unless you have changed it manually. The old UUID was %s.

`ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010550`; Symbol: `ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50`; SQLSTATE: `HY000`

Message: Found a master with MySQL server version older than 5.0. With checksums enabled on the slave, replication might not work correctly. To ensure correct replication, restart the slave server with `--replica_sql_verify_checksum=0`.

`ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_50` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010550`; Symbol: `ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PRE_50`; SQLSTATE: `HY000`

Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with `--replica_sql_verify_checksum=0`.

`ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PRE_50` was added in 8.0.33.
 - Error number: `MY-010551`; Symbol: `ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS`; SQLSTATE: `HY000`

Message: "SELECT UNIX_TIMESTAMP()" failed on master, do not trust column Seconds_Behind_Master of SHOW SLAVE STATUS. Error: %s (%d)

`ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010551`; Symbol: `ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS`; SQLSTATE: `HY000`

Message: "SELECT UNIX_TIMESTAMP()" failed on source, do not trust column Seconds_Behind_Source of SHOW REPLICA STATUS. Error: %s (%d)

`ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS` was added in 8.0.33.
-

-
- Error number: [MY-010552](#); Symbol: [ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to flush master info file.

[ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010552](#); Symbol: [ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS](#); SQLSTATE: [HY000](#)

Message: Failed to flush connection metadata repository.

[ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS](#) was added in 8.0.33.
 - Error number: [MY-010553](#); Symbol: [ER_RPL_SLAVE_REPORT_HOST_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_host is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_HOST_TOO_LONG](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010553](#); Symbol: [ER_RPL_REPLICA_REPORT_HOST_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

[ER_RPL_REPLICA_REPORT_HOST_TOO_LONG](#) was added in 8.0.33.
 - Error number: [MY-010554](#); Symbol: [ER_RPL_SLAVE_REPORT_USER_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_user is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_USER_TOO_LONG](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010554](#); Symbol: [ER_RPL_REPLICA_REPORT_USER_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

[ER_RPL_REPLICA_REPORT_USER_TOO_LONG](#) was added in 8.0.33.
 - Error number: [MY-010555](#); Symbol: [ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_password is %zu. It is larger than the max length(%d), so this slave cannot be registered to the master%s.

[ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010555](#); Symbol: [ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

[ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG](#) was added in 8.0.33.
 - Error number: [MY-010556](#); Symbol: [ER_RPL_SLAVE_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: Error on %s: %d %s, will retry in %d secs

[ER_RPL_SLAVE_ERROR_RETRYING](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010556](#); Symbol: [ER_RPL_REPLICA_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: Error on %s: %d %s, will retry in %d secs

[ER_RPL_REPLICA_ERROR_RETRYING](#) was added in 8.0.33.

- Error number: [MY-010557](#); Symbol: [ER_RPL_SLAVE_ERROR_READING_FROM_SERVER](#); SQLSTATE: [HY000](#)

Message: Error reading packet from server%s: %s (server_errno=%d)

[ER_RPL_SLAVE_ERROR_READING_FROM_SERVER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010557](#); Symbol: [ER_RPL_REPLICA_ERROR_READING_FROM_SERVER](#); SQLSTATE: [HY000](#)

Message: Error reading packet from server%s: %s (server_errno=%d)

[ER_RPL_REPLICA_ERROR_READING_FROM_SERVER](#) was added in 8.0.33.

- Error number: [MY-010558](#); Symbol: [ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER](#); SQLSTATE: [HY000](#)

Message: Slave%s: received end packet from server due to dump thread being killed on master. Dump threads are killed for example during master shutdown, explicitly by a user, or when the master receives a binlog send request from a duplicate server UUID <%s> : Error %s

[ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010558](#); Symbol: [ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE](#); SQLSTATE: [HY000](#)

Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s

[ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE](#) was added in 8.0.33.

- Error number: [MY-010559](#); Symbol: [ER_RPL_MTS_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded slave statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

[ER_RPL_MTS_STATISTICS](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010559](#); Symbol: [ER_RPL_MTA_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

[ER_RPL_MTA_STATISTICS](#) was added in 8.0.33.

-
- Error number: `MY-010560`; Symbol: `ER_RPL_MTS_RECOVERY_COMPLETE`; SQLSTATE: `HY000`
Message: Slave%s: MTS Recovery has completed at relay log %s, position %llu master log %s, position %llu.
`ER_RPL_MTS_RECOVERY_COMPLETE` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010560`; Symbol: `ER_RPL_MTA_RECOVERY_COMPLETE`; SQLSTATE: `HY000`
Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.
`ER_RPL_MTA_RECOVERY_COMPLETE` was added in 8.0.33.
 - Error number: `MY-010561`; Symbol: `ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION`; SQLSTATE: `HY000`
Message: Error initializing relay log position%s: %s
`ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010561`; Symbol: `ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION`; SQLSTATE: `HY000`
Message: Error initializing relay log position%s: %s
`ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION` was added in 8.0.33.
 - Error number: `MY-010562`; Symbol: `ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STARTED`; SQLSTATE: `HY000`
Message: Slave I/O thread%s: connected to master '%s@%s:%d', replication started in log '%s' at position %s
`ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STARTED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010563`; Symbol: `ER_RPL_SLAVE_IO_THREAD_KILLED`; SQLSTATE: `HY000`
Message: Slave I/O thread%s killed while connecting to master
`ER_RPL_SLAVE_IO_THREAD_KILLED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010563`; Symbol: `ER_RPL_REPLICA_IO_THREAD_KILLED`; SQLSTATE: `HY000`
Message: Replica I/O thread%s killed while connecting to source
`ER_RPL_REPLICA_IO_THREAD_KILLED` was added in 8.0.33.
 - Error number: `MY-010564`; Symbol: `ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER`; SQLSTATE: `HY000`
Message: Slave I/O thread couldn't register on master
`ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010564`; Symbol: `ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE`; SQLSTATE: `HY000`
Message: Replica I/O thread couldn't register on source
`ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE` was added in 8.0.33.

-
- Error number: `MY-010565`; Symbol: `ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD`; SQLSTATE: `HY000`

Message: Forcing to reconnect slave I/O thread%s

`ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010565`; Symbol: `ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD`; SQLSTATE: `HY000`

Message: Forcing to reconnect replica I/O thread%s

`ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD` was added in 8.0.33.
 - Error number: `MY-010566`; Symbol: `ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP`; SQLSTATE: `HY000`

Message: Failed on request_dump()%s

`ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010566`; Symbol: `ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP`; SQLSTATE: `HY000`

Message: Failed on request_dump()%s

`ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP` was added in 8.0.33.
 - Error number: `MY-010567`; Symbol: `ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET`; SQLSTATE: `HY000`

Message: Log entry on master is longer than slave_max_allowed_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of slave_max_allowed_packet

`ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET` was added in 8.0.2, removed after 8.0.25.
 - Error number: `MY-010567`; Symbol: `ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET`; SQLSTATE: `HY000`

Message: Log entry on source is longer than replica_max_allowed_packet (%lu) on replica. If the entry is correct, restart the server with a higher value of replica_max_allowed_packet

`ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET` was added in 8.0.26.
 - Error number: `MY-010568`; Symbol: `ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM`; SQLSTATE: `HY000`

Message: Stopping slave I/O thread due to out-of-memory error from master

`ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010568`; Symbol: `ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM`; SQLSTATE: `HY000`

Message: Stopping replica I/O thread due to out-of-memory error from source

`ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM` was added in 8.0.33.
 - Error number: `MY-010569`; Symbol: `ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Slave I/O thread aborted while waiting for relay log space

`ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010569`; Symbol:

`ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Replica I/O thread aborted while waiting for relay log space

`ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE` was added in 8.0.33.

- Error number: `MY-010570`; Symbol: `ER_RPL_SLAVE_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Slave I/O thread exiting%s, read up to log '%s', position %s

`ER_RPL_SLAVE_IO_THREAD_EXITING` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010570`; Symbol: `ER_RPL_REPLICA_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Replica I/O thread exiting%s, read up to log '%s', position %s

`ER_RPL_REPLICA_IO_THREAD_EXITING` was added in 8.0.33.

- Error number: `MY-010571`; Symbol: `ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER`; SQLSTATE: `HY000`

Message: Failed during slave worker initialization%s

`ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010571`; Symbol: `ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER`; SQLSTATE: `HY000`

Message: Failed during replica worker initialization%s

`ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER` was added in 8.0.33.

- Error number: `MY-010572`; Symbol:

`ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER`; SQLSTATE: `HY000`

Message: Slave: MTS group recovery relay log info based on Worker-Id %lu, group_relay_log_name %s, group_relay_log_pos %llu group_master_log_name %s, group_master_log_pos %llu

`ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_WORKER` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010572`; Symbol:

`ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_WORKER`; SQLSTATE: `HY000`

Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group_relay_log_name %s, group_relay_log_pos %llu group_source_log_name %s, group_source_log_pos %llu

`ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_WORKER` was added in 8.0.33.

- Error number: `MY-010573`; Symbol: `ER_RPL_ERROR_LOOKING_FOR_LOG`; SQLSTATE: `HY000`

Message: Error looking for %s.

`ER_RPL_ERROR_LOOKING_FOR_LOG` was added in 8.0.2.

-
- Error number: [MY-010574](#); Symbol: [ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: Slave: MTS group recovery relay log info group_master_log_name %s, event_master_log_pos %llu.

[ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010574](#); Symbol: [ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA](#); SQLSTATE: [HY000](#)

Message: Replica: MTA group recovery applier metadata group_source_log_name %s, event_source_log_pos %llu.

[ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA](#) was added in 8.0.33.
 - Error number: [MY-010575](#); Symbol: [ER_RPL_CANT_FIND_FOLLOWUP_FILE](#); SQLSTATE: [HY000](#)

Message: Error looking for file after %s.

[ER_RPL_CANT_FIND_FOLLOWUP_FILE](#) was added in 8.0.2.
 - Error number: [MY-010576](#); Symbol: [ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta_checkpoint_period

[ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010576](#); Symbol: [ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta_checkpoint_period

[ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT](#) was added in 8.0.33.
 - Error number: [MY-010577](#); Symbol: [ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed during slave worker thread creation%s

[ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010577](#); Symbol: [ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s

[ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED](#) was added in 8.0.33.
 - Error number: [MY-010578](#); Symbol: [ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)

Message: Failed during slave worker thread creation%s (errno= %d)

[ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010578](#); Symbol: [ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s (errno= %d)

`ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO` was added in 8.0.33.

- Error number: `MY-010579`; Symbol: `ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH`; SQLSTATE: `HY000`

Message: Failed to init partitions hash

`ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010579`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH`; SQLSTATE: `HY000`

Message: Failed to init partitions hash

`ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH` was added in 8.0.33.

- Error number: `MY-010580`; Symbol: `ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Slave SQL thread : NDB : Tables not available after %lu seconds. Consider increasing --ndb-wait-setup value

`ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010581`; Symbol: `ER_RPL_SLAVE_SQL_THREAD_STARTING`; SQLSTATE: `HY000`

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

`ER_RPL_SLAVE_SQL_THREAD_STARTING` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010581`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_STARTING`; SQLSTATE: `HY000`

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

`ER_RPL_REPLICA_SQL_THREAD_STARTING` was added in 8.0.33.

- Error number: `MY-010582`; Symbol: `ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED`; SQLSTATE: `HY000`

Message: 'SQL_REPLICA_SKIP_COUNTER=%ld' executed at relay_log_file='%s', relay_log_pos='%ld', master_log_name='%s', master_log_pos='%ld' and new position at relay_log_file='%s', relay_log_pos='%ld', master_log_name='%s', master_log_pos='%ld'

`ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010582`; Symbol: `ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED`; SQLSTATE: `HY000`

Message: 'SQL_REPLICA_SKIP_COUNTER=%ld' executed at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld' and new position at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld'

`ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED` was added in 8.0.33.

- Error number: `MY-010583`; Symbol: `ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

Message: Slave (additional info): %s Error_code: MY-%06d

`ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010583`; Symbol: `ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

Message: Replica (additional info): %s Error_code: MY-%06d

`ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA` was added in 8.0.33.

- Error number: `MY-010584`; Symbol: `ER_RPL_SLAVE_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

Message: Slave: %s Error_code: MY-%06d

`ER_RPL_SLAVE_ERROR_INFO_FROM_DA` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010584`; Symbol: `ER_RPL_REPLICA_ERROR_INFO_FROM_DA`; SQLSTATE: `HY000`

Message: Replica: %s Error_code: MY-%06d

`ER_RPL_REPLICA_ERROR_INFO_FROM_DA` was added in 8.0.33.

- Error number: `MY-010585`; Symbol: `ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY`; SQLSTATE: `HY000`

Message: Error loading user-defined library, slave SQL thread aborted. Install the missing library, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

`ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIBRARY` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010585`; Symbol: `ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARY`; SQLSTATE: `HY000`

Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

`ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARY` was added in 8.0.33.

- Error number: `MY-010586`; Symbol: `ER_RPL_SLAVE_ERROR_RUNNING_QUERY`; SQLSTATE: `HY000`

Message: Error running query, slave SQL thread aborted. Fix the problem, and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

`ER_RPL_SLAVE_ERROR_RUNNING_QUERY` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010586`; Symbol: `ER_RPL_REPLICA_ERROR_RUNNING_QUERY`; SQLSTATE: `HY000`

Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

`ER_RPL_REPLICA_ERROR_RUNNING_QUERY` was added in 8.0.33.

- Error number: `MY-010587`; Symbol: `ER_RPL_SLAVE_SQL_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Slave SQL thread%s exiting, replication stopped in log '%s' at position %s

`ER_RPL_SLAVE_SQL_THREAD_EXITING` was added in 8.0.2, removed after 8.0.32.

-
- Error number: [MY-010587](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s

[ER_RPL_REPLICA_SQL_THREAD_EXITING](#) was added in 8.0.33.
 - Error number: [MY-010588](#); Symbol: [ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER](#); SQLSTATE: [HY000](#)

Message: Read invalid event from master: '%s', master could be corrupt but a more likely cause of this is a bug

[ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010588](#); Symbol: [ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE](#); SQLSTATE: [HY000](#)

Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug

[ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE](#) was added in 8.0.33.
 - Error number: [MY-010589](#); Symbol: [ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as its configuration is invalid.

[ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010589](#); Symbol: [ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as its configuration is invalid.

[ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#) was added in 8.0.33.
 - Error number: [MY-010590](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from master '%s' binary log file, at position %llu.

[ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010590](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.

[ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#) was added in 8.0.33.
 - Error number: [MY-010591](#); Symbol: [ER_RPL_SLAVE_CANT_USE_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to master.

[ER_RPL_SLAVE_CANT_USE_CHARSET](#) was added in 8.0.2, removed after 8.0.32.

-
- Error number: [MY-010591](#); Symbol: [ER_RPL_REPLICA_CANT_USE_CHARSET](#); SQLSTATE: [HY000](#)

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.

[ER_RPL_REPLICA_CANT_USE_CHARSET](#) was added in 8.0.33.
 - Error number: [MY-010592](#); Symbol: [ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_RESUMED](#); SQLSTATE: [HY000](#)

Message: Slave%s: connected to master '%s@%s:%d', replication resumed in log '%s' at position %s

[ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_RESUMED](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010592](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION_RESUMED](#); SQLSTATE: [HY000](#)

Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s

[ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION_RESUMED](#) was added in 8.0.33.
 - Error number: [MY-010593](#); Symbol: [ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

[ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010593](#); Symbol: [ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is active

[ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE](#) was added in 8.0.33.
 - Error number: [MY-010594](#); Symbol: [ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is not active

[ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010594](#); Symbol: [ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE](#); SQLSTATE: [HY000](#)

Message: next log '%s' is not active

[ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE](#) was added in 8.0.33.
 - Error number: [MY-010595](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread%s: I/O error reading event (errno: %d cur_log->error: %d)

[ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT](#) was added in 8.0.2, removed after 8.0.32.
-

- Error number: MY-010595; Symbol: `ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: HY000

Message: Replica SQL thread%s: I/O error reading event (errno: %d cur_log->error: %d)

`ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT` was added in 8.0.33.
- Error number: MY-010596; Symbol: `ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: HY000

Message: Error reading relay log event%s: %s

`ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.2, removed after 8.0.32.
- Error number: MY-010596; Symbol: `ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: HY000

Message: Error reading relay log event%s: %s

`ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS` was added in 8.0.33.
- Error number: MY-010597; Symbol: `ER_SLAVE_CHANGE_MASTER_TO_EXECUTED`; SQLSTATE: HY000

Message: 'CHANGE MASTER TO%s executed'. Previous state master_host='%s', master_port=%u, master_log_file='%s', master_log_pos= %ld, master_bind='%s'. New state master_host='%s', master_port= %u, master_log_file='%s', master_log_pos= %ld, master_bind='%s'.

`ER_SLAVE_CHANGE_MASTER_TO_EXECUTED` was added in 8.0.2, removed after 8.0.32.
- Error number: MY-010597; Symbol: `ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED`; SQLSTATE: HY000

Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'. New state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'.

`ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED` was added in 8.0.33.
- Error number: MY-010598; Symbol: `ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE_OTHER_THAN_FILE`; SQLSTATE: HY000

Message: Slave: Cannot create new master info structure when repositories are of type FILE. Convert slave repositories to TABLE to replicate from multiple sources.

`ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS_TYPE_OTHER_THAN_FILE` was added in 8.0.2, removed after 8.0.32.
- Error number: MY-010598; Symbol: `ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_FILE`; SQLSTATE: HY000

Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.

`ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_FILE` was added in 8.0.33.
- Error number: MY-010599; Symbol: `ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX`; SQLSTATE: HY000

Message: log %s listed in the index, but failed to stat.

`ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX` was added in 8.0.2.

-
- Error number: `MY-010600`; Symbol: `ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Could not find first log while counting relay log space.

`ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE` was added in 8.0.2.
 - Error number: `MY-010601`; Symbol: `ER_SLAVE_CANT_USE_TMPDIR`; SQLSTATE: `HY000`

Message: Unable to use slave's temporary directory '%s'.

`ER_SLAVE_CANT_USE_TMPDIR` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010601`; Symbol: `ER_REPLICA_CANT_USE_TMPDIR`; SQLSTATE: `HY000`

Message: Unable to use replica's temporary directory '%s'.

`ER_REPLICA_CANT_USE_TMPDIR` was added in 8.0.33.
 - Error number: `MY-010602`; Symbol: `ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`

Message: Path '%s' is a directory name, please specify a file name for --relay-log option.

`ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY` was added in 8.0.2.
 - Error number: `MY-010603`; Symbol: `ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`

Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.

`ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY` was added in 8.0.2.
 - Error number: `MY-010604`; Symbol: `ER_RPL_PLEASE_USE_OPTION_RELAY_LOG`; SQLSTATE: `HY000`

Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.

`ER_RPL_PLEASE_USE_OPTION_RELAY_LOG` was added in 8.0.2.
 - Error number: `MY-010605`; Symbol: `ER_RPL_OPEN_INDEX_FILE_FAILED`; SQLSTATE: `HY000`

Message: Failed in open_index_file() called from Relay_log_info::rli_init_info().

`ER_RPL_OPEN_INDEX_FILE_FAILED` was added in 8.0.2.
 - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO`; SQLSTATE: `HY000`

Message: Failed in init_gtid_sets() called from Relay_log_info::rli_init_info().

`ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO`; SQLSTATE: `HY000`

Message: Failed in init_gtid_sets() called from Relay_log_info::rli_init_info().

`ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO` was added in 8.0.33.

-
- Error number: [MY-010607](#); Symbol: [ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO](#); SQLSTATE: [HY000](#)

Message: Failed in open_log() called from Relay_log_info::rli_init_info().

[ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO](#) was added in 8.0.2, removed after 8.0.32.
 - Error number: [MY-010607](#); Symbol: [ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO](#); SQLSTATE: [HY000](#)

Message: Failed in open_log() called from Relay_log_info::rli_init_info().

[ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO](#) was added in 8.0.33.
 - Error number: [MY-010608](#); Symbol: [ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error writing relay log configuration.

[ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION](#) was added in 8.0.2.
 - Error number: [MY-010609](#); Symbol: [ER_NDB_OOM_GET_NDB_BLOBS_VALUE](#); SQLSTATE: [HY000](#)

Message: get_ndb_blobs_value: my_malloc(%u) failed

[ER_NDB_OOM_GET_NDB_BLOBS_VALUE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010610](#); Symbol: [ER_NDB_THREAD_TIMED_OUT](#); SQLSTATE: [HY000](#)

Message: NDB: Thread id %u timed out (30s) waiting for epoch %u/%u to be handled. Progress : %u/%u -> %u/%u.

[ER_NDB_THREAD_TIMED_OUT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010611](#); Symbol: [ER_NDB_TABLE_IS_NOT_DISTRIBUTED](#); SQLSTATE: [HY000](#)

Message: NDB: Inconsistency detected in distributed privilege tables. Table '%s.%s' is not distributed

[ER_NDB_TABLE_IS_NOT_DISTRIBUTED](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010612](#); Symbol: [ER_NDB_CREATING_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB: Creating %s.%s

[ER_NDB_CREATING_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010613](#); Symbol: [ER_NDB_FLUSHING_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: NDB: Flushing %s.%s

[ER_NDB_FLUSHING_TABLE_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010614](#); Symbol: [ER_NDB_CLEANING_STRAY_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB: Cleaning stray tables from database '%s'

[ER_NDB_CLEANING_STRAY_TABLES](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010615](#); Symbol: [ER_NDB_DISCOVERED_MISSING_DB](#); SQLSTATE: [HY000](#)

Message: NDB: Discovered missing database '%s'

[ER_NDB_DISCOVERED_MISSING_DB](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010616](#); Symbol: [ER_NDB_DISCOVERED_REMAINING_DB](#); SQLSTATE: [HY000](#)
Message: NDB: Discovered remaining database '%s'
[ER_NDB_DISCOVERED_REMAINING_DB](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010617](#); Symbol: [ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY](#); SQLSTATE: [HY000](#)
Message: NDB: ndbcluster_find_all_databases retry: %u - %s
[ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010618](#); Symbol: [ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL](#); SQLSTATE: [HY000](#)
Message: NDB: ndbcluster_find_all_databases fail: %u - %s
[ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010619](#); Symbol: [ER_NDB_SKIPPING_SETUP_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB: skipping setup table %s.%s, in state %d
[ER_NDB_SKIPPING_SETUP_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010620](#); Symbol: [ER_NDB_FAILED_TO_SET_UP_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB: failed to setup table %s.%s, error: %d, %s
[ER_NDB_FAILED_TO_SET_UP_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010621](#); Symbol: [ER_NDB_MISSING_FRM_DISCOVERING](#); SQLSTATE: [HY000](#)
Message: NDB: missing frm for %s.%s, discovering...
[ER_NDB_MISSING_FRM_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010622](#); Symbol: [ER_NDB_MISMATCH_IN_FRM_DISCOVERING](#); SQLSTATE: [HY000](#)
Message: NDB: mismatch in frm for %s.%s, discovering...
[ER_NDB_MISMATCH_IN_FRM_DISCOVERING](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010623](#); Symbol: [ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS](#); SQLSTATE: [HY000](#)
Message: ndb_binlog_setup: Clean up leftovers
[ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010624](#); Symbol: [ER_NDB_WAITING_INFO](#); SQLSTATE: [HY000](#)
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector
proc_info: %s
[ER_NDB_WAITING_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010625](#); Symbol: [ER_NDB_WAITING_INFO_WITH_MAP](#); SQLSTATE: [HY000](#)
Message: NDB %s: waiting max %u sec for %s %s. epochs: (%u/%u,%u/%u,%u/%u) injector
proc_info: %s map: %x%08x

`ER_NDB_WAITING_INFO_WITH_MAP` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010626`; Symbol: `ER_NDB_TIMEOUT_WHILE_DISTRIBUTING`; SQLSTATE: `HY000`

Message: NDB %s: distributing %s timed out. Ignoring...

`ER_NDB_TIMEOUT_WHILE_DISTRIBUTING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010627`; Symbol: `ER_NDB_NOT_WAITING_FOR_DISTRIBUTING`; SQLSTATE: `HY000`

Message: NDB %s: not waiting for distributing %s

`ER_NDB_NOT_WAITING_FOR_DISTRIBUTING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010628`; Symbol: `ER_NDB_DISTRIBUTED_INFO`; SQLSTATE: `HY000`

Message: NDB: distributed %s.%s(%u/%u) type: %s(%u) query: '%s' to %x%08x

`ER_NDB_DISTRIBUTED_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010629`; Symbol: `ER_NDB_DISTRIBUTION_COMPLETE`; SQLSTATE: `HY000`

Message: NDB: distribution of %s.%s(%u/%u) type: %s(%u) query: '%s' - complete!

`ER_NDB_DISTRIBUTION_COMPLETE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010630`; Symbol: `ER_NDB_SCHEMA_DISTRIBUTION_FAILED`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d failed, subscriber bitmask %x%08x

`ER_NDB_SCHEMA_DISTRIBUTION_FAILED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010631`; Symbol: `ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d reports subscribe from node %d, subscriber bitmask %x%08x

`ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010632`; Symbol: `ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE`; SQLSTATE: `HY000`

Message: NDB Schema dist: Data node: %d reports unsubscribe from node %d, subscriber bitmask %x%08x

`ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010633`; Symbol: `ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB Binlog: Could not discover table '%s.%s' from binlog schema event '%s' from node %d. my_errno: %d

`ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010634](#); Symbol: [ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE](#); SQLSTATE: [HY000](#)
Message: NDB: unknown value for binlog signalling 0x%X, %s not logged
[ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010635](#); Symbol: [ER_NDB_BINLOG_REPLY_TO](#); SQLSTATE: [HY000](#)
Message: NDB: reply to %s.%s(%u/%u) from %s to %x%08x
[ER_NDB_BINLOG_REPLY_TO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010636](#); Symbol: [ER_NDB_BINLOG_CANT_RELEASE_SLOCK](#); SQLSTATE: [HY000](#)
Message: NDB: Could not release slock on '%s.%s', Error code: %d Message: %s
[ER_NDB_BINLOG_CANT_RELEASE_SLOCK](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010637](#); Symbol: [ER_NDB_CANT_FIND_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB schema: Could not find table '%s.%s' in NDB
[ER_NDB_CANT_FIND_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010638](#); Symbol: [ER_NDB_DISCARDING_EVENT_NO_OBJ](#); SQLSTATE: [HY000](#)
Message: NDB: Discarding event...no obj: %s (%u/%u)
[ER_NDB_DISCARDING_EVENT_NO_OBJ](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010639](#); Symbol: [ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH](#); SQLSTATE: [HY000](#)
Message: NDB: Discarding event...key: %s non matching id/version [%u/%u] != [%u/%u]
[ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010640](#); Symbol: [ER_NDB_CLEAR_SLOCK_INFO](#); SQLSTATE: [HY000](#)
Message: NDB: CLEAR_SLOCK key: %s(%u/%u) %x%08x, from %s to %x%08x
[ER_NDB_CLEAR_SLOCK_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010641](#); Symbol: [ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: Skipping locally defined table '%s.%s' from binlog schema event '%s' from node %d.
[ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010642](#); Symbol: [ER_NDB_BINLOG_ONLINE_ALTER_RENAME](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: handling online alter/rename
[ER_NDB_BINLOG_ONLINE_ALTER_RENAME](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010643](#); Symbol: [ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: Failed to re-open shadow table %s.%s

`ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010644`; Symbol: `ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE`; SQLSTATE: `HY000`

Message: NDB Binlog: handling online alter/rename done

`ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010645`; Symbol: `ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping drop of locally defined table '%s.%s' from binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010646`; Symbol: `ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping renaming locally defined table '%s.%s' from binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010647`; Symbol: `ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES`; SQLSTATE: `HY000`

Message: NDB Binlog: Skipping drop database '%s' since it contained local tables binlog schema event '%s' from node %d.

`ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_LOCAL_TABLES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010648`; Symbol: `ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_PRIVILEGES`; SQLSTATE: `HY000`

Message: Got dist_priv event: %s, flushing privileges

`ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING_PRIVILEGES` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010649`; Symbol: `ER_NDB_BINLOG_GOT_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB: got schema event on %s.%s(%u/%u) query: '%s' type: %s(%d) node: %u slock: %x %08x

`ER_NDB_BINLOG_GOT_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010650`; Symbol: `ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION`; SQLSTATE: `HY000`

Message: NDB schema: Skipping old schema operation(RENAME_TABLE_NEW) on %s.%s

`ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010651`; Symbol: `ER_NDB_CLUSTER_FAILURE`; SQLSTATE: `HY000`

Message: NDB Schema dist: cluster failure at epoch %u/%u.

`ER_NDB_CLUSTER_FAILURE` was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010652](#); Symbol: [ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndb tables initially read only on reconnect.

[ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010653](#); Symbol: [ER_NDB_IGNOREING_UNKNOWN_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Schema dist: unknown event %u, ignoring...

[ER_NDB_IGNOREING_UNKNOWN_EVENT](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010654](#); Symbol: [ER_NDB_BINLOG_OPENING_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Opening ndb_binlog_index: %d, '%s'

[ER_NDB_BINLOG_OPENING_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010655](#); Symbol: [ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to lock table ndb_binlog_index

[ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010656](#); Symbol: [ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Injecting random write failure

[ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010657](#); Symbol: [ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb_binlog_index for epoch %u/%u orig_server_id %u orig_epoch %u/%u with error %d.

[ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010658](#); Symbol: [ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Writing row (%s) to ndb_binlog_index - %s

[ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010659](#); Symbol: [ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed committing transaction to ndb_binlog_index with error %d.

[ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010660](#); Symbol: [ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED_AFTER_KILL](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Failed writing to ndb_binlog_index table while retrying after kill during shutdown

[ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED_AFTER_KILL](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010661](#); Symbol: [ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT](#); SQLSTATE: [HY000](#)

Message: NDB: server id set to zero - changes logged to bin log with server id zero will be logged with another server id by slave mysqlds

[ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010662](#); Symbol: [ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: NDB: server id provided is too large to be represented in opt_server_id_bits or is reserved

[ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010663](#); Symbol: [ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRES_V2_ROW_EVENTS](#); SQLSTATE: [HY000](#)

Message: NDB: --ndb-log-transaction-id requires v2 Binlog row events but server is using v1.

[ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRES_V2_ROW_EVENTS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010664](#); Symbol: [ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_FULL_USE_WRITE](#); SQLSTATE: [HY000](#)

Message: NDB: ndb-log-apply-status forcing %s.%s to FULL USE_WRITE

[ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING_FULL_USE_WRITE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010665](#); Symbol: [ER_NDB_BINLOG_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: %s

[ER_NDB_BINLOG_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010666](#); Symbol: [ER_NDB_CONFLICT_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_NDB_CONFLICT_GENERIC_MESSAGE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010667](#); Symbol: [ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010668](#); Symbol: [ER_NDB_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: NDB Slave: Table %s.%s : Parse error on conflict fn : %s
[ER_NDB_CONFLICT_FN_PARSE_ERROR](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010669](#); Symbol: [ER_NDB_CONFLICT_FN_SETUP_ERROR](#); SQLSTATE: [HY000](#)
Message: NDB Slave: Table %s.%s : %s
[ER_NDB_CONFLICT_FN_SETUP_ERROR](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010670](#); Symbol: [ER_NDB_BINLOG_FAILED_TO_GET_TABLE](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: Failed to get table %s from ndb: %s, %d
[ER_NDB_BINLOG_FAILED_TO_GET_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010671](#); Symbol: [ER_NDB_BINLOG_NOT_LOGGING](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: NOT logging %s
[ER_NDB_BINLOG_NOT_LOGGING](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010672](#); Symbol: [ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: FAILED CREATE (DISCOVER) TABLE Event: %s
[ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010673](#); Symbol: [ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: CREATE (DISCOVER) TABLE Event: %s
[ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010674](#); Symbol: [ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: DISCOVER TABLE Event: %s
[ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010675](#); Symbol: [ER_NDB_BINLOG_BLOB_REQUIRES_PK](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: logging of table %s with BLOB attribute and no PK is not supported
[ER_NDB_BINLOG_BLOB_REQUIRES_PK](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010676](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: Unable to create event in database. Event: %s Error Code: %d Message: %s
[ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010677](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_DROP](#); SQLSTATE: [HY000](#)
Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop failed. Event: %s Error Code: %d Message: %s

[ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_DROP](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010678](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to create event in database. Attempt to correct with drop ok, but create failed. Event: %s Error Code: %d Message: %s

[ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010679](#); Symbol: [ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: discover reusing old ev op

[ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010680](#); Symbol: [ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation failed for %s

[ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010681](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_BLOB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Creating NdbEventOperation blob field %u handles failed (code=%d) for %s

[ER_NDB_BINLOG_CANT_CREATE_BLOB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010682](#); Symbol: [ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: ndbevent->execute failed for %s; %d %s

[ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010683](#); Symbol: [ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: logging %s (%s,%s)

[ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010684](#); Symbol: [ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Unable to drop event in database. Event: %s Error Code: %d Message: %s

[ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010685](#); Symbol: [ER_NDB_TIMED_OUT_IN_DROP_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB %s: %s timed out. Ignoring...

[ER_NDB_TIMED_OUT_IN_DROP_TABLE](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010686](#); Symbol: [ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: unhandled error %d for table %s

[ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010687](#); Symbol: [ER_NDB_BINLOG_CLUSTER_FAILURE](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster failure for %s at epoch %u/%u.

[ER_NDB_BINLOG_CLUSTER_FAILURE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010688](#); Symbol: [ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: unknown non data event %d for %s. Ignoring...

[ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010689](#); Symbol: [ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_METADATA](#); SQLSTATE: [HY000](#)

Message: NDB: Binlog Injector discarding row event meta data as server is using v1 row events. (%u %x)

[ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT_METADATA](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010690](#); Symbol: [ER_NDB_REMAINING_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: remove_all_event_operations: Remaining open tables:

[ER_NDB_REMAINING_OPEN_TABLES](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010691](#); Symbol: [ER_NDB_REMAINING_OPEN_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s, use_count: %u

[ER_NDB_REMAINING_OPEN_TABLE_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010692](#); Symbol: [ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE](#); SQLSTATE: [HY000](#)

Message: NDB: Could not get apply status share

[ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010693](#); Symbol: [ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Server shutdown detected while waiting for ndbcluster to start...

[ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010694](#); Symbol: [ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER_SUGGESTED](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: cluster has been restarted --initial or with older filesystem.
ndb_latest_handled_binlog_epoch: %u/%u, while current epoch: %u/%u. RESET MASTER should be issued. Resetting ndb_latest_handled_binlog_epoch.
-

`ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER_SUGGESTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010695`; Symbol: `ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED`; SQLSTATE: `HY000`

Message: NDB Binlog: cluster has reconnected. Changes to the database that occurred while disconnected will not be in the binlog

`ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010696`; Symbol: `ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH`; SQLSTATE: `HY000`

Message: NDB Binlog: starting log at epoch %u/%u

`ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010697`; Symbol: `ER_NDB_BINLOG_NDB_TABLES_WRITABLE`; SQLSTATE: `HY000`

Message: NDB Binlog: ndb tables writable

`ER_NDB_BINLOG_NDB_TABLES_WRITABLE` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010698`; Symbol: `ER_NDB_BINLOG_SHUTDOWN_DETECTED`; SQLSTATE: `HY000`

Message: NDB Binlog: Server shutdown detected...

`ER_NDB_BINLOG_SHUTDOWN_DETECTED` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010699`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING`; SQLSTATE: `HY000`

Message: NDB Binlog: Just lost schema connection, hanging around

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010700`; Symbol: `ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING`; SQLSTATE: `HY000`

Message: NDB Binlog: ...and on our way

`ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONTINUING` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010701`; Symbol: `ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT`; SQLSTATE: `HY000`

Message: NDB: error %lu (%s) on handling binlog schema event

`ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010702`; Symbol: `ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW`; SQLSTATE: `HY000`

Message: NDB Binlog: Failed to inject apply status write row

`ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW` was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010703](#); Symbol: [ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during ROLLBACK of GCI %u/%u. Error: %d

[ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010704](#); Symbol: [ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Error during COMMIT of GCI. Error: %d

[ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010705](#); Symbol: [ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: latest transaction in epoch %u/%u not in binlog as latest handled epoch is %u/%u

[ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010706](#); Symbol: [ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: Release extra share references

[ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCES](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010707](#); Symbol: [ER_NDB_BINLOG_REMAINING_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: NDB Binlog: remaining open tables:

[ER_NDB_BINLOG_REMAINING_OPEN_TABLES](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010708](#); Symbol: [ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: %s.%s state: %u use_count: %u

[ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010709](#); Symbol: [ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Parent doesn't point at parent

[ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT](#) was added in 8.0.2.
 - Error number: [MY-010710](#); Symbol: [ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Root should be black

[ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK](#) was added in 8.0.2.
 - Error number: [MY-010711](#); Symbol: [ER_TREE_CORRUPT_2_CONSECUTIVE_REDS](#); SQLSTATE: [HY000](#)

Message: Wrong tree: Found two red in a row

`ER_TREE_CORRUPT_2_CONSECUTIVE_REDS` was added in 8.0.2.

- Error number: `MY-010712`; Symbol: `ER_TREE_CORRUPT_RIGHT_IS_LEFT`; SQLSTATE: `HY000`

Message: Wrong tree: Found right == left

`ER_TREE_CORRUPT_RIGHT_IS_LEFT` was added in 8.0.2.

- Error number: `MY-010713`; Symbol: `ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT`; SQLSTATE: `HY000`

Message: Wrong tree: Incorrect black-count: %d - %d

`ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT` was added in 8.0.2.

- Error number: `MY-010714`; Symbol: `ER_WRONG_COUNT_FOR_ORIGIN`; SQLSTATE: `HY000`

Message: Use_count: Wrong count %lu for origin %p

`ER_WRONG_COUNT_FOR_ORIGIN` was added in 8.0.2.

- Error number: `MY-010715`; Symbol: `ER_WRONG_COUNT_FOR_KEY`; SQLSTATE: `HY000`

Message: Use_count: Wrong count for key at %p, %lu should be %lu

`ER_WRONG_COUNT_FOR_KEY` was added in 8.0.2.

- Error number: `MY-010716`; Symbol: `ER_WRONG_COUNT_OF_ELEMENTS`; SQLSTATE: `HY000`

Message: Wrong number of elements: %u (should be %u) for tree at %p

`ER_WRONG_COUNT_OF_ELEMENTS` was added in 8.0.2.

- Error number: `MY-010717`; Symbol: `ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading slave worker configuration

`ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010717`; Symbol: `ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading replica worker configuration

`ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION` was added in 8.0.33.

- Error number: `MY-010718`; Symbol: `ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing slave worker configuration

`ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010719`; Symbol: `ER_RPL_FAILED_TO_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to open relay log %s, error: %s

`ER_RPL_FAILED_TO_OPEN_RELAY_LOG` was added in 8.0.2.

-
- Error number: `MY-010720`; Symbol: `ER_RPL_WORKER_CANT_READ_RELAY_LOG`; SQLSTATE: `HY000`

Message: Error when worker read relay log events, relay log name %s, position %llu

`ER_RPL_WORKER_CANT_READ_RELAY_LOG` was added in 8.0.2.
 - Error number: `MY-010721`; Symbol: `ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG`; SQLSTATE: `HY000`

Message: Failed to find next relay log when retrying the transaction, current relay log is %s

`ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG` was added in 8.0.2.
 - Error number: `MY-010722`; Symbol: `ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`

Message: Multi-threaded slave: Coordinator has waited %lu times hitting replica_pending_jobs_size_max; current event size = %zu.

`ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED` was added in 8.0.2, removed after 8.0.32.
 - Error number: `MY-010722`; Symbol: `ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`

Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica_pending_jobs_size_max; current event size = %zu.

`ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED` was added in 8.0.33.
 - Error number: `MY-010723`; Symbol: `ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES`; SQLSTATE: `HY000`

Message: Failed to write the DROP statement for temporary tables to binary log

`ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES` was added in 8.0.2.
 - Error number: `MY-010724`; Symbol: `ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE`; SQLSTATE: `HY000`

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM '%s'.' '%s'' to the binary log

`ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE` was added in 8.0.2.
 - Error number: `MY-010725`; Symbol: `ER_FAILED_TO_REPAIR_TABLE`; SQLSTATE: `HY000`

Message: Couldn't repair table: %s.%s

`ER_FAILED_TO_REPAIR_TABLE` was added in 8.0.2.
 - Error number: `MY-010726`; Symbol: `ER_FAILED_TO_REMOVE_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Could not remove temporary table: '%s', error: %d

`ER_FAILED_TO_REMOVE_TEMP_TABLE` was added in 8.0.2.
 - Error number: `MY-010727`; Symbol: `ER_SYSTEM_TABLE_NOT_TRANSACTIONAL`; SQLSTATE: `HY000`

Message: System table '%.*s' is expected to be transactional.

`ER_SYSTEM_TABLE_NOT_TRANSACTIONAL` was added in 8.0.2.
-

-
- Error number: `MY-010728`; Symbol: `ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing master configuration.

`ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010728`; Symbol: `ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error writing source configuration.

`ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION` was added in 8.0.33.

- Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_MASTER_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading master configuration.

`ER_RPL_ERROR_READING_MASTER_CONFIGURATION` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_SOURCE_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading source configuration.

`ER_RPL_ERROR_READING_SOURCE_CONFIGURATION` was added in 8.0.33.

- Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED`; SQLSTATE: `HY000`

Message: SSL information in the master info file are ignored because this MySQL slave was compiled without SSL support.

`ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED`; SQLSTATE: `HY000`

Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.

`ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED` was added in 8.0.33.

- Error number: `MY-010731`; Symbol: `ER_PLUGIN_FAILED_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' of type %s failed deinitialization

`ER_PLUGIN_FAILED_DEINITIALIZATION` was added in 8.0.2.

- Error number: `MY-010732`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' has ref_count=%d after deinitialization.

`ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION` was added in 8.0.2.

- Error number: `MY-010733`; Symbol: `ER_PLUGIN_SHUTTING_DOWN_PLUGIN`; SQLSTATE: `HY000`

Message: Shutting down plugin '%s'

`ER_PLUGIN_SHUTTING_DOWN_PLUGIN` was added in 8.0.2.

-
- Error number: [MY-010734](#); Symbol: [ER_PLUGIN_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' registration as a %s failed.
[ER_PLUGIN_REGISTRATION_FAILED](#) was added in 8.0.2.
 - Error number: [MY-010735](#); Symbol: [ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.
[ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE](#) was added in 8.0.2.
 - Error number: [MY-010736](#); Symbol: [ER_PLUGIN_CANT_LOAD](#); SQLSTATE: [HY000](#)
Message: Couldn't load plugin named '%s' with soname '%s'.
[ER_PLUGIN_CANT_LOAD](#) was added in 8.0.2.
 - Error number: [MY-010737](#); Symbol: [ER_PLUGIN_LOAD_PARAMETER_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: plugin-load parameter too long
[ER_PLUGIN_LOAD_PARAMETER_TOO_LONG](#) was added in 8.0.2.
 - Error number: [MY-010738](#); Symbol: [ER_PLUGIN_FORCING_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' will be forced to shutdown
[ER_PLUGIN_FORCING_SHUTDOWN](#) was added in 8.0.2.
 - Error number: [MY-010739](#); Symbol: [ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' has ref_count=%d after shutdown.
[ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN](#) was added in 8.0.2.
 - Error number: [MY-010740](#); Symbol: [ER_PLUGIN_UNKNOWN_VARIABLE_TYPE](#); SQLSTATE: [HY000](#)
Message: Unknown variable type code 0x%x in plugin '%s'.
[ER_PLUGIN_UNKNOWN_VARIABLE_TYPE](#) was added in 8.0.2.
 - Error number: [MY-010741](#); Symbol: [ER_PLUGIN_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Server variable %s of plugin %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag
[ER_PLUGIN_VARIABLE_SET_READ_ONLY](#) was added in 8.0.2.
 - Error number: [MY-010742](#); Symbol: [ER_PLUGIN_VARIABLE_MISSING_NAME](#); SQLSTATE: [HY000](#)
Message: Missing variable name in plugin '%s'.
[ER_PLUGIN_VARIABLE_MISSING_NAME](#) was added in 8.0.2.
 - Error number: [MY-010743](#); Symbol: [ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL](#); SQLSTATE: [HY000](#)
Message: Thread local variable '%s' not allocated in plugin '%s'.

`ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL` was added in 8.0.2.

- Error number: `MY-010744`; Symbol: `ER_PLUGIN_OOM`; SQLSTATE: `HY000`

Message: Out of memory for plugin '%s'.

`ER_PLUGIN_OOM` was added in 8.0.2.

- Error number: `MY-010745`; Symbol: `ER_PLUGIN_BAD_OPTIONS`; SQLSTATE: `HY000`

Message: Bad options for plugin '%s'.

`ER_PLUGIN_BAD_OPTIONS` was added in 8.0.2.

- Error number: `MY-010746`; Symbol: `ER_PLUGIN_PARSING_OPTIONS_FAILED`; SQLSTATE: `HY000`

Message: Parsing options for plugin '%s' failed.

`ER_PLUGIN_PARSING_OPTIONS_FAILED` was added in 8.0.2.

- Error number: `MY-010747`; Symbol: `ER_PLUGIN_DISABLED`; SQLSTATE: `HY000`

Message: Plugin '%s' is disabled.

`ER_PLUGIN_DISABLED` was added in 8.0.2.

- Error number: `MY-010748`; Symbol: `ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES`; SQLSTATE: `HY000`

Message: Plugin '%s' has conflicting system variables

`ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES` was added in 8.0.2.

- Error number: `MY-010749`; Symbol: `ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS`; SQLSTATE: `HY000`

Message: Setting persistent options for plugin '%s' failed.

`ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS` was added in 8.0.2.

- Error number: `MY-010750`; Symbol: `ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR`; SQLSTATE: `HY000`

Message: Failed on my_net_write, writing to stderr instead: %s

`ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR` was added in 8.0.2.

- Error number: `MY-010751`; Symbol: `ER_RETRYING_REPAIR_WITHOUT_QUICK`; SQLSTATE: `HY000`

Message: Retrying repair of: '%s' without quick

`ER_RETRYING_REPAIR_WITHOUT_QUICK` was added in 8.0.2.

- Error number: `MY-010752`; Symbol: `ER_RETRYING_REPAIR_WITH_KEYCACHE`; SQLSTATE: `HY000`

Message: Retrying repair of: '%s' with keycache

`ER_RETRYING_REPAIR_WITH_KEYCACHE` was added in 8.0.2.

- Error number: `MY-010753`; Symbol: `ER_FOUND_ROWS_WHILE_REPAIRING`; SQLSTATE: `HY000`

Message: Found %s of %s rows when repairing '%s'

[ER_FOUND_ROWS_WHILE_REPAIRING](#) was added in 8.0.2.

- Error number: [MY-010754](#); Symbol: [ER_ERROR_DURING_OPTIMIZE_TABLE](#); SQLSTATE: [HY000](#)

Message: Warning: Optimize table got errno %d on %s.%s, retrying

[ER_ERROR_DURING_OPTIMIZE_TABLE](#) was added in 8.0.2.

- Error number: [MY-010755](#); Symbol: [ER_ERROR_ENABLING_KEYS](#); SQLSTATE: [HY000](#)

Message: Warning: Enabling keys got errno %d on %s.%s, retrying

[ER_ERROR_ENABLING_KEYS](#) was added in 8.0.2.

- Error number: [MY-010756](#); Symbol: [ER_CHECKING_TABLE](#); SQLSTATE: [HY000](#)

Message: Checking table: '%s'

[ER_CHECKING_TABLE](#) was added in 8.0.2.

- Error number: [MY-010757](#); Symbol: [ER_RECOVERING_TABLE](#); SQLSTATE: [HY000](#)

Message: Recovering table: '%s'

[ER_RECOVERING_TABLE](#) was added in 8.0.2.

- Error number: [MY-010758](#); Symbol: [ER_CANT_CREATE_TABLE_SHARE_FROM_FRM](#); SQLSTATE: [HY000](#)

Message: Error in creating TABLE_SHARE from %s.frm file.

[ER_CANT_CREATE_TABLE_SHARE_FROM_FRM](#) was added in 8.0.2.

- Error number: [MY-010759](#); Symbol: [ER_CANT_LOCK_TABLE](#); SQLSTATE: [HY000](#)

Message: Unable to acquire lock on %s.%s

[ER_CANT_LOCK_TABLE](#) was added in 8.0.2.

- Error number: [MY-010760](#); Symbol: [ER_CANT_ALLOC_TABLE_OBJECT](#); SQLSTATE: [HY000](#)

Message: Error in allocation memory for TABLE object.

[ER_CANT_ALLOC_TABLE_OBJECT](#) was added in 8.0.2.

- Error number: [MY-010761](#); Symbol: [ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Error in creating handler object for table %s.%s

[ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE](#) was added in 8.0.2.

- Error number: [MY-010762](#); Symbol: [ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: Error in setting handler reference for table %s.%s

[ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE](#) was added in 8.0.2.

-
- Error number: MY-010763; Symbol: ER_CANT_LOCK_TABLESPACE; SQLSTATE: HY000
Message: Unable to acquire lock on tablespace name %s
ER_CANT_LOCK_TABLESPACE was added in 8.0.2.
 - Error number: MY-010764; Symbol: ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD; SQLSTATE: HY000
Message: Error in processing generated columns for table %s.%s
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD was added in 8.0.2.
 - Error number: MY-010765; Symbol: ER_DD_ERROR_CREATING_ENTRY; SQLSTATE: HY000
Message: Error in Creating DD entry for %s.%s
ER_DD_ERROR_CREATING_ENTRY was added in 8.0.2.
 - Error number: MY-010766; Symbol: ER_DD_CANT_FETCH_TABLE_DATA; SQLSTATE: HY000
Message: Error in fetching %s.%s table data from dictionary
ER_DD_CANT_FETCH_TABLE_DATA was added in 8.0.2.
 - Error number: MY-010767; Symbol: ER_DD_CANT_FIX_SE_DATA; SQLSTATE: HY000
Message: Error in fixing SE data for %s.%s
ER_DD_CANT_FIX_SE_DATA was added in 8.0.2.
 - Error number: MY-010768; Symbol: ER_DD_CANT_CREATE_SP; SQLSTATE: HY000
Message: Error in creating stored program '%s.%s'
ER_DD_CANT_CREATE_SP was added in 8.0.2.
 - Error number: MY-010769; Symbol: ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET; SQLSTATE: HY000
Message: Unable to open db.opt file %s. Using default Character set.
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET was added in 8.0.2.
 - Error number: MY-010770; Symbol: ER_CANT_CREATE_CACHE_FOR_DB_OPT; SQLSTATE: HY000
Message: Unable to initialize IO cache to open db.opt file %s.
ER_CANT_CREATE_CACHE_FOR_DB_OPT was added in 8.0.2.
 - Error number: MY-010771; Symbol: ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT; SQLSTATE: HY000
Message: Unable to identify the charset in %s. Using default character set.
ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT was added in 8.0.2.
 - Error number: MY-010772; Symbol: ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET; SQLSTATE: HY000
Message: db.opt file not found for %s database. Using default Character set.
ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET was added in 8.0.2.

-
- Error number: `MY-010773`; Symbol: `ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.time_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD` was added in 8.0.2.

- Error number: `MY-010774`; Symbol: `ER_EVENT_CANT_FIND_TIMEZONE`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_FIND_TIMEZONE` was added in 8.0.2.

- Error number: `MY-010775`; Symbol: `ER_EVENT_CANT_GET_CHARSET`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.character_set_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_CHARSET` was added in 8.0.2.

- Error number: `MY-010776`; Symbol: `ER_EVENT_CANT_GET_COLLATION`; SQLSTATE: `HY000`

Message: Event '%s'. '%s': invalid value in column mysql.event.collation_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_GET_COLLATION` was added in 8.0.2.

- Error number: `MY-010777`; Symbol: `ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT`; SQLSTATE: `HY000`

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.

`ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT` was added in 8.0.2.

- Error number: `MY-010778`; Symbol: `ER_CANT_PARSE_STORED_ROUTINE_BODY`; SQLSTATE: `HY000`

Message: Parsing '%s.%s' routine body failed.%s

`ER_CANT_PARSE_STORED_ROUTINE_BODY` was added in 8.0.2.

-
- Error number: [MY-010779](#); Symbol: [ER_CANT_OPEN_TABLE_MYSQL_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.proc](#) system table and migrates its contents to the internal data dictionary.

[ER_CANT_OPEN_TABLE_MYSQL_PROC](#) was added in 8.0.2.

- Error number: [MY-010780](#); Symbol: [ER_CANT_READ_TABLE_MYSQL_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the [mysql.proc](#) system table and migrates its contents to the internal data dictionary.

[ER_CANT_READ_TABLE_MYSQL_PROC](#) was added in 8.0.2.

- Error number: [MY-010781](#); Symbol: [ER_FILE_EXISTS_DURING_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

[ER_FILE_EXISTS_DURING_UPGRADE](#) was added in 8.0.2.

- Error number: [MY-010782](#); Symbol: [ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unable to open the data directory %s during clean up after upgrade failed

[ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE](#) was added in 8.0.2.

- Error number: [MY-010783](#); Symbol: [ER_CANT_SET_PATH_FOR](#); SQLSTATE: [HY000](#)

Message: Failed to set path %s

[ER_CANT_SET_PATH_FOR](#) was added in 8.0.2.

- Error number: [MY-010784](#); Symbol: [ER_CANT_OPEN_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to open dir %s

[ER_CANT_OPEN_DIR](#) was added in 8.0.2.

- Error number: [MY-010785](#); Symbol: [ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Found empty nodeid specified in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010786](#); Symbol: [ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Could not parse '%s' in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.

-
- Error number: [MY-010787](#); Symbol: [ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Invalid nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010788](#); Symbol: [ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: Found duplicate nodeid %d in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010789](#); Symbol: [ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: The size of the cluster connection pool must be equal to the number of nodeids in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010790](#); Symbol: [ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#); SQLSTATE: [HY000](#)

Message: NDB: The nodeid specified by --ndb-nodeid must be equal to the first nodeid in --ndb-cluster-connection-pool-nodeids='%s'.

[ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010791](#); Symbol: [ER_NDB_USING_NODEID](#); SQLSTATE: [HY000](#)

Message: NDB: using nodeid %u

[ER_NDB_USING_NODEID](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010792](#); Symbol: [ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb cluster connection

[ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010793](#); Symbol: [ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT](#); SQLSTATE: [HY000](#)

Message: NDB: failed to allocate global ndb object

[ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010794](#); Symbol: [ER_NDB_USING_NODEID_LIST](#); SQLSTATE: [HY000](#)

Message: NDB[%u]: using nodeid %u

`ER_NDB_USING_NODEID_LIST` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010795`; Symbol: `ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION`; SQLSTATE: `HY000`

Message: NDB[%u]: failed to allocate cluster connect object

`ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010796`; Symbol: `ER_NDB_STARTING_CONNECT_THREAD`; SQLSTATE: `HY000`

Message: NDB[%u]: starting connect thread

`ER_NDB_STARTING_CONNECT_THREAD` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010797`; Symbol: `ER_NDB_NODE_INFO`; SQLSTATE: `HY000`

Message: NDB[%u]: NodeID: %d, %s

`ER_NDB_NODE_INFO` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010798`; Symbol: `ER_NDB_CANT_START_CONNECT_THREAD`; SQLSTATE: `HY000`

Message: NDB[%u]: failed to start connect thread

`ER_NDB_CANT_START_CONNECT_THREAD` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010799`; Symbol: `ER_NDB_GENERIC_ERROR`; SQLSTATE: `HY000`

Message: NDB: error (%u) %s

`ER_NDB_GENERIC_ERROR` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010800`; Symbol: `ER_NDB_CPU_MASK_TOO_SHORT`; SQLSTATE: `HY000`

Message: Ignored receive thread CPU mask, mask too short, %u CPUs needed in mask, only %u CPUs provided

`ER_NDB_CPU_MASK_TOO_SHORT` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010801`; Symbol: `ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG`; SQLSTATE: `HY000`

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

`ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG` was added in 8.0.2.

- Error number: `MY-010802`; Symbol: `ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB`; SQLSTATE: `HY000`

Message: Event Scheduler: Error while loading from disk.

`ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB` was added in 8.0.2.

- Error number: `MY-010803`; Symbol: `ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT`; SQLSTATE: `HY000`

Message: Event Scheduler: Error getting event object.

`ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT` was added in 8.0.2.

-
- Error number: [MY-010804](#); Symbol: [ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

[ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE](#) was added in 8.0.2.

- Error number: [MY-010805](#); Symbol: [ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s

[ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT](#) was added in 8.0.2.

- Error number: [MY-010806](#); Symbol: [ER_EVENT_UNABLE_TO_DROP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to drop event %s from schema %s

[ER_EVENT_UNABLE_TO_DROP_EVENT](#) was added in 8.0.2.

- Error number: [MY-010807](#); Symbol: [ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while attaching to session thread during the group commit phase.

[ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_AVAILABLE](#) was added in 8.0.2, removed after 8.0.13.

- Error number: [MY-010808](#); Symbol: [ER_BINLOG_CANT_RESIZE_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file

[ER_BINLOG_CANT_RESIZE_CACHE](#) was added in 8.0.2.

- Error number: [MY-010809](#); Symbol: [ER_BINLOG_FILE_BEING_READ_NOT_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u

[ER_BINLOG_FILE_BEING_READ_NOT_PURGED](#) was added in 8.0.2.

- Error number: [MY-010810](#); Symbol: [ER_BINLOG_IO_ERROR_READING_HEADER](#); SQLSTATE: [HY000](#)

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

[ER_BINLOG_IO_ERROR_READING_HEADER](#) was added in 8.0.2.

- Error number: [MY-010811](#); Symbol: [ER_BINLOG_CANT_OPEN_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open log (file '%s', errno %d)

[ER_BINLOG_CANT_OPEN_LOG](#) was added in 8.0.2, removed after 8.0.12.

- Error number: [MY-010812](#); Symbol: [ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to create a cache on log (file '%s')

[ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG](#) was added in 8.0.2, removed after 8.0.12.

-
- Error number: [MY-010813](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.

[ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED](#) was added in 8.0.2.

- Error number: [MY-010814](#); Symbol: [ER_BINLOG_FILE_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.

[ER_BINLOG_FILE_NAME_TOO_LONG](#) was added in 8.0.2.

- Error number: [MY-010815](#); Symbol: [ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW](#); SQLSTATE: [HY000](#)

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.

[ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW](#) was added in 8.0.2.

- Error number: [MY-010816](#); Symbol: [ER_BINLOG_CANT_OPEN_FOR_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

[ER_BINLOG_CANT_OPEN_FOR_LOGGING](#) was added in 8.0.2.

- Error number: [MY-010817](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_index_file failed to sync the index file.

[ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE](#) was added in 8.0.2.

- Error number: [MY-010818](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from relaylog: %d

[ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG](#) was added in 8.0.2.

- Error number: [MY-010819](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved_Gtid_Set and/or IO thread transaction parser state.

[ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010819](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved_Gtid_Set and/or IO thread transaction parser state.

[ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA](#) was added in 8.0.33.

-
- Error number: [MY-010820](#); Symbol: [ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from binary log: %d

[ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG](#) was added in 8.0.2.
 - Error number: [MY-010821](#); Symbol: [ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO](#); SQLSTATE: [HY000](#)

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

[ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO](#) was added in 8.0.2.
 - Error number: [MY-010822](#); Symbol: [ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open failed to generate new file name.

[ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME](#) was added in 8.0.2.
 - Error number: [MY-010823](#); Symbol: [ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open failed to sync the index file.

[ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN](#) was added in 8.0.2.
 - Error number: [MY-010824](#); Symbol: [ER_BINLOG_CANT_USE_FOR_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

[ER_BINLOG_CANT_USE_FOR_LOGGING](#) was added in 8.0.2.
 - Error number: [MY-010825](#); Symbol: [ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to close the index file.

[ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.
 - Error number: [MY-010826](#); Symbol: [ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.

[ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.
 - Error number: [MY-010827](#); Symbol: [ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING](#); SQLSTATE: [HY000](#)

Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.

[ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING](#) was added in 8.0.2.
 - Error number: [MY-010828](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING](#); SQLSTATE: [HY000](#)

Message: After rebuilding the index file %s: Failed to open the index file.

[ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING](#) was added in 8.0.2.

-
- Error number: [MY-010829](#); Symbol: [ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::add_log_to_index failed to append log file name: %s, to crash safe index file.

[ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX](#) was added in 8.0.2.
 - Error number: [MY-010830](#); Symbol: [ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES](#); SQLSTATE: [HY000](#)

Message: Failed to locate old binlog or relay log files

[ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES](#) was added in 8.0.2.
 - Error number: [MY-010831](#); Symbol: [ER_BINLOG_CANT_DELETE_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to delete file '%s'

[ER_BINLOG_CANT_DELETE_FILE](#) was added in 8.0.2.
 - Error number: [MY-010832](#); Symbol: [ER_BINLOG_CANT_SET_TMP_INDEX_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::set_crash_safe_index_file_name failed to set file name.

[ER_BINLOG_CANT_SET_TMP_INDEX_NAME](#) was added in 8.0.2.
 - Error number: [MY-010833](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_crash_safe_index_file failed to open temporary index file.

[ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE](#) was added in 8.0.2.
 - Error number: [MY-010834](#); Symbol: [ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX](#); SQLSTATE: [HY000](#)

Message: next log error: %d offset: %s log: %s included: %d

[ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX](#) was added in 8.0.2, removed after 8.0.12.
 - Error number: [MY-010835](#); Symbol: [ER_BINLOG_CANT_OPEN_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to open the crash safe index file.

[ER_BINLOG_CANT_OPEN_TMP_INDEX](#) was added in 8.0.2.
 - Error number: [MY-010836](#); Symbol: [ER_BINLOG_CANT_COPY_INDEX_TO_TMP](#); SQLSTATE: [HY000](#)

Message: %s failed to copy index file to crash safe index file.

[ER_BINLOG_CANT_COPY_INDEX_TO_TMP](#) was added in 8.0.2.
 - Error number: [MY-010837](#); Symbol: [ER_BINLOG_CANT_CLOSE_TMP_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to close the crash safe index file.

[ER_BINLOG_CANT_CLOSE_TMP_INDEX](#) was added in 8.0.2.
 - Error number: [MY-010838](#); Symbol: [ER_BINLOG_CANT_MOVE_TMP_TO_INDEX](#); SQLSTATE: [HY000](#)

Message: %s failed to move crash safe index file to index file.

[ER_BINLOG_CANT_MOVE_TMP_TO_INDEX](#) was added in 8.0.2.

- Error number: [MY-010839](#); Symbol: [ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs was called with file %s not listed in the index.

[ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX](#) was added in 8.0.2.

- Error number: [MY-010840](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to sync the index file.

[ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE](#) was added in 8.0.2.

- Error number: [MY-010841](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to copy %s to register file.

[ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE](#) was added in 8.0.2.

- Error number: [MY-010842](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to flush register file.

[ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE](#) was added in 8.0.2.

- Error number: [MY-010843](#); Symbol: [ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to update the index file

[ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE](#) was added in 8.0.2.

- Error number: [MY-010844](#); Symbol: [ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_logs failed to process registered files that would be purged.

[ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG](#) was added in 8.0.2.

- Error number: [MY-010845](#); Symbol: [ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::set_purge_index_file_name failed to set file name.

[ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME](#) was added in 8.0.2.

- Error number: [MY-010846](#); Symbol: [ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::open_purge_index_file failed to open register file.

[ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE](#) was added in 8.0.2.

- Error number: [MY-010847](#); Symbol: [ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_index_entry failed to reinit register file for read

[ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE](#) was added in 8.0.2.

- Error number: [MY-010848](#); Symbol: [ER_BINLOG_FAILED_TO_READ_REGISTER_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL_BIN_LOG::purge_index_entry error %d reading from register file.

[ER_BINLOG_FAILED_TO_READ_REGISTER_FILE](#) was added in 8.0.2.

- Error number: [MY-010849](#); Symbol: [ER_CANT_STAT_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to execute mysql_file_stat on file '%s'

[ER_CANT_STAT_FILE](#) was added in 8.0.2.

- Error number: [MY-010850](#); Symbol: [ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES](#); SQLSTATE: [HY000](#)

Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files

[ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES](#) was added in 8.0.2.

- Error number: [MY-010851](#); Symbol: [ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX](#); SQLSTATE: [HY000](#)

Message: Failed to delete file '%s' and read the binlog index file

[ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX](#) was added in 8.0.2.

- Error number: [MY-010852](#); Symbol: [ER_BINLOG_FAILED_TO_DELETE_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to delete log file '%s'

[ER_BINLOG_FAILED_TO_DELETE_LOG_FILE](#) was added in 8.0.2.

- Error number: [MY-010853](#); Symbol: [ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES](#); SQLSTATE: [HY000](#)

Message: %s An incident event has been written to the binary log which will stop the slaves.

[ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES](#) was added in 8.0.2, removed after 8.0.32.

- Error number: [MY-010853](#); Symbol: [ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS](#); SQLSTATE: [HY000](#)

Message: %s An incident event has been written to the binary log which will stop the replicas.

[ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS](#) was added in 8.0.33.

- Error number: [MY-010854](#); Symbol: [ER_BINLOG_CANT_FIND_LOG_IN_INDEX](#); SQLSTATE: [HY000](#)

Message: find_log_pos() failed (error: %d)

[ER_BINLOG_CANT_FIND_LOG_IN_INDEX](#) was added in 8.0.2.

- Error number: [MY-010855](#); Symbol: [ER_BINLOG_RECOVERING_AFTER_CRASH_USING](#); SQLSTATE: [HY000](#)

Message: Recovering after a crash using %s

[ER_BINLOG_RECOVERING_AFTER_CRASH_USING](#) was added in 8.0.2.

- Error number: [MY-010856](#); Symbol: [ER_BINLOG_CANT_OPEN_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the crashed binlog file when source server is recovering it.

[ER_BINLOG_CANT_OPEN_CRASHED_BINLOG](#) was added in 8.0.2.

- Error number: [MY-010857](#); Symbol: [ER_BINLOG_CANT_TRIM_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)

Message: Failed to trim the crashed binlog file when source server is recovering it.

[ER_BINLOG_CANT_TRIM_CRASHED_BINLOG](#) was added in 8.0.2.

- Error number: [MY-010858](#); Symbol: [ER_BINLOG_CRASHED_BINLOG_TRIMMED](#); SQLSTATE: [HY000](#)

Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.

[ER_BINLOG_CRASHED_BINLOG_TRIMMED](#) was added in 8.0.2.

- Error number: [MY-010859](#); Symbol: [ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG](#); SQLSTATE: [HY000](#)

Message: Failed to clear LOG_EVENT_BINLOG_IN_USE_F for the crashed binlog file when source server is recovering it.

[ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG](#) was added in 8.0.2.

- Error number: [MY-010860](#); Symbol: [ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK](#); SQLSTATE: [HY000](#)

Message: Failed to run 'after_sync' hooks

[ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK](#) was added in 8.0.2.

- Error number: [MY-010861](#); Symbol: [ER_TURNING_LOGGING_OFF_FOR_THE_DURATION](#); SQLSTATE: [HY000](#)

Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

[ER_TURNING_LOGGING_OFF_FOR_THE_DURATION](#) was added in 8.0.2.

- Error number: [MY-010862](#); Symbol: [ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK](#); SQLSTATE: [HY000](#)

Message: Failed to run 'after_flush' hooks

[ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK](#) was added in 8.0.2.

- Error number: [MY-010863](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete (or rename) binary log and start mysqld with --tc-heuristic-recover={commit|rollback}

[ER_BINLOG_CRASH_RECOVERY_FAILED](#) was added in 8.0.2, removed after 8.0.29.

-
- Error number: [MY-010864](#); Symbol: [ER_BINLOG_WARNING_SUPPRESSED](#); SQLSTATE: [HY000](#)
Message: The following warning was suppressed %d times during the last %d seconds in the error log
[ER_BINLOG_WARNING_SUPPRESSED](#) was added in 8.0.2.
 - Error number: [MY-010865](#); Symbol: [ER_NDB_LOG_ENTRY](#); SQLSTATE: [HY000](#)
Message: NDB: %s
[ER_NDB_LOG_ENTRY](#) was added in 8.0.2.
 - Error number: [MY-010866](#); Symbol: [ER_NDB_LOG_ENTRY_WITH_PREFIX](#); SQLSTATE: [HY000](#)
Message: NDB %s: %s
[ER_NDB_LOG_ENTRY_WITH_PREFIX](#) was added in 8.0.2.
 - Error number: [MY-010867](#); Symbol: [ER_NDB_BINLOG_CANT_CREATE_PURGE_THD](#); SQLSTATE: [HY000](#)
Message: NDB: Unable to purge %s.%s File=%s (failed to setup thd)
[ER_NDB_BINLOG_CANT_CREATE_PURGE_THD](#) was added in 8.0.2, removed after 8.0.13.
 - Error number: [MY-010868](#); Symbol: [ER_INNOBDB_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)
Message: Unknown collation #%lu.
[ER_INNOBDB_UNKNOWN_COLLATION](#) was added in 8.0.2.
 - Error number: [MY-010869](#); Symbol: [ER_INNOBDB_INVALID_LOG_GROUP_HOME_DIR](#); SQLSTATE: [HY000](#)
Message: syntax error in innodb_log_group_home_dir
[ER_INNOBDB_INVALID_LOG_GROUP_HOME_DIR](#) was added in 8.0.2.
 - Error number: [MY-010870](#); Symbol: [ER_INNOBDB_INVALID_INNOBDB_UNDO_DIRECTORY](#); SQLSTATE: [HY000](#)
Message: syntax error in innodb_undo_directory
[ER_INNOBDB_INVALID_INNOBDB_UNDO_DIRECTORY](#) was added in 8.0.2.
 - Error number: [MY-010871](#); Symbol: [ER_INNOBDB_ILLEGAL_COLON_IN_POOL](#); SQLSTATE: [HY000](#)
Message: InnoDB: innodb_buffer_pool_filename cannot have colon (:) in the file name.
[ER_INNOBDB_ILLEGAL_COLON_IN_POOL](#) was added in 8.0.2.
 - Error number: [MY-010872](#); Symbol: [ER_INNOBDB_INVALID_PAGE_SIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB: Invalid page size=%lu.
[ER_INNOBDB_INVALID_PAGE_SIZE](#) was added in 8.0.2.
 - Error number: [MY-010873](#); Symbol: [ER_INNOBDB_DIRTY_WATER_MARK_NOT_LOW](#); SQLSTATE: [HY000](#)
Message: InnoDB: innodb_max_dirty_pages_pct_lwm cannot be set higher than innodb_max_dirty_pages_pct. Setting innodb_max_dirty_pages_pct_lwm to %lf

`ER_INNODB_DIRTY_WATER_MARK_NOT_LOW` was added in 8.0.2.

- Error number: `MY-010874`; Symbol: `ER_INNODB_IO_CAPACITY_EXCEEDS_MAX`; SQLSTATE: `HY000`

Message: InnoDB: innodb_io_capacity cannot be set higher than innodb_io_capacity_max. Setting innodb_io_capacity to %lu

`ER_INNODB_IO_CAPACITY_EXCEEDS_MAX` was added in 8.0.2.

- Error number: `MY-010875`; Symbol: `ER_INNODB_FILES_SAME`; SQLSTATE: `HY000`

Message: %s and %s file names seem to be the same.

`ER_INNODB_FILES_SAME` was added in 8.0.2.

- Error number: `MY-010876`; Symbol: `ER_INNODB_UNREGISTERED_TRX_ACTIVE`; SQLSTATE: `HY000`

Message: Transaction not registered for MySQL 2PC, but transaction is active

`ER_INNODB_UNREGISTERED_TRX_ACTIVE` was added in 8.0.2.

- Error number: `MY-010877`; Symbol: `ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK`; SQLSTATE: `HY000`

Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.

`ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK` was added in 8.0.2.

- Error number: `MY-010878`; Symbol: `ER_INNODB_TRX_XLATION_TABLE_OOM`; SQLSTATE: `HY000`

Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size:%lu

`ER_INNODB_TRX_XLATION_TABLE_OOM` was added in 8.0.2.

- Error number: `MY-010879`; Symbol: `ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD`; SQLSTATE: `HY000`

Message: Cannot find index %s in InnoDB index dictionary.

`ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD` was added in 8.0.2.

- Error number: `MY-010880`; Symbol: `ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS`; SQLSTATE: `HY000`

Message: Found index %s whose column info does not match that of MySQL.

`ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS` was added in 8.0.2.

- Error number: `MY-010881`; Symbol: `ER_INNODB_CANT_OPEN_TABLE`; SQLSTATE: `HY000`

Message: Failed to open table %s.

`ER_INNODB_CANT_OPEN_TABLE` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010882`; Symbol: `ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR`; SQLSTATE: `HY000`

Message: Build InnoDB index translation table for Table %s failed

`ER_INNOODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR` was added in 8.0.2.

- Error number: `MY-010883`; Symbol: `ER_INNOODB_PK_NOT_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!

`ER_INNOODB_PK_NOT_IN_MYSQL` was added in 8.0.2.

- Error number: `MY-010884`; Symbol: `ER_INNOODB_PK_ONLY_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.

`ER_INNOODB_PK_ONLY_IN_MYSQL` was added in 8.0.2.

- Error number: `MY-010885`; Symbol: `ER_INNOODB_CLUSTERED_INDEX_PRIVATE`; SQLSTATE: `HY000`

Message: Table %s key_used_on_scan is %lu even though there is no primary key inside InnoDB.

`ER_INNOODB_CLUSTERED_INDEX_PRIVATE` was added in 8.0.2.

- Error number: `MY-010886`; Symbol: `ER_INNOODB_PARTITION_TABLE_LOWERCASED`; SQLSTATE: `HY000`

Message: Partition table %s opened after converting to lower case. The table may have been moved from a case-insensitive file system. Please recreate the table in the current file system.

`ER_INNOODB_PARTITION_TABLE_LOWERCASED` was added in 8.0.2, removed after 8.0.18.

- Error number: `MY-010887`; Symbol: `ER_ERRMSG_REPLACEMENT_DODGY`; SQLSTATE: `HY000`

Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.

`ER_ERRMSG_REPLACEMENT_DODGY` was added in 8.0.2.

- Error number: `MY-010888`; Symbol: `ER_ERRMSG_REPLACEMENTS_FAILED`; SQLSTATE: `HY000`

Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.

`ER_ERRMSG_REPLACEMENTS_FAILED` was added in 8.0.2.

- Error number: `MY-010889`; Symbol: `ER_NPIPE_CANT_CREATE`; SQLSTATE: `HY000`

Message: %s: %s

`ER_NPIPE_CANT_CREATE` was added in 8.0.2.

- Error number: `MY-010890`; Symbol: `ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX`; SQLSTATE: `HY000`

Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s

`ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX` was added in 8.0.2.

- Error number: `MY-010891`; Symbol: `ER_AUDIT_CANT_ABORT_COMMAND`; SQLSTATE: `HY000`

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

`ER_AUDIT_CANT_ABORT_COMMAND` was added in 8.0.2.

- Error number: `MY-010892`; Symbol: `ER_AUDIT_CANT_ABORT_EVENT`; SQLSTATE: `HY000`

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

`ER_AUDIT_CANT_ABORT_EVENT` was added in 8.0.2.

- Error number: `MY-010893`; Symbol: `ER_AUDIT_WARNING`; SQLSTATE: `HY000`

Message: %s. The trigger error was (%d) [%s]: %s

`ER_AUDIT_WARNING` was added in 8.0.2.

- Error number: `MY-010894`; Symbol: `ER_NDB_NUMBER_OF_CHANNELS`; SQLSTATE: `HY000`

Message: Slave SQL: Configuration with number of replication masters = %u' is not supported when applying to Ndb

`ER_NDB_NUMBER_OF_CHANNELS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010895`; Symbol: `ER_NDB_SLAVE_PARALLEL_WORKERS`; SQLSTATE: `HY000`

Message: Slave SQL: Configuration 'slave_parallel_workers = %lu' is not supported when applying to Ndb

`ER_NDB_SLAVE_PARALLEL_WORKERS` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010896`; Symbol: `ER_NDB_DISTRIBUTING_ERR`; SQLSTATE: `HY000`

Message: NDB %s: distributing %s err: %u

`ER_NDB_DISTRIBUTING_ERR` was added in 8.0.2, removed after 8.0.13.

- Error number: `MY-010897`; Symbol: `ER_RPL_SLAVE_INSECURE_CHANGE_MASTER`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

`ER_RPL_SLAVE_INSECURE_CHANGE_MASTER` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-010897`; Symbol: `ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE`; SQLSTATE: `HY000`

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

`ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE` was added in 8.0.33.

- Error number: `MY-010898`; Symbol: `ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: FLUSH RELAY LOGS cannot be performed on channel '%s'.

`ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED` was added in 8.0.4, removed after 8.0.15.

- Error number: `MY-010899`; Symbol: `ER_RPL_SLAVE_INCORRECT_CHANNEL`; SQLSTATE: `HY000`

Message: Slave channel '%s' does not exist.

[ER_RPL_SLAVE_INCORRECT_CHANNEL](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010899](#); Symbol: [ER_RPL_REPLICA_INCORRECT_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica channel '%s' does not exist.

[ER_RPL_REPLICA_INCORRECT_CHANNEL](#) was added in 8.0.33.

- Error number: [MY-010900](#); Symbol: [ER_FAILED_TO_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library.

[ER_FAILED_TO_FIND_DL_ENTRY](#) was added in 8.0.4.

- Error number: [MY-010901](#); Symbol: [ER_FAILED_TO_OPEN_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s).

[ER_FAILED_TO_OPEN_SHARED_LIBRARY](#) was added in 8.0.4.

- Error number: [MY-010902](#); Symbol: [ER_THREAD_PRIORITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

[ER_THREAD_PRIORITY_IGNORED](#) was added in 8.0.4.

- Error number: [MY-010903](#); Symbol: [ER_BINLOG_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.

[ER_BINLOG_CACHE_SIZE_TOO_LARGE](#) was added in 8.0.4.

- Error number: [MY-010904](#); Symbol: [ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

[ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE](#) was added in 8.0.4.

- Error number: [MY-010905](#); Symbol: [ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999).

[ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE](#) was added in 8.0.4.

- Error number: [MY-010906](#); Symbol: [ER_FAILED_TO_READ_FILE](#); SQLSTATE: [HY000](#)

Message: Error reading file '%s' (errno: %d - %s)

[ER_FAILED_TO_READ_FILE](#) was added in 8.0.4.

- Error number: [MY-010907](#); Symbol: [ER_FAILED_TO_WRITE_TO_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

`ER_FAILED_TO_WRITE_TO_FILE` was added in 8.0.4.

- Error number: `MY-010908`; Symbol: `ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT`; SQLSTATE: `HY000`

Message: %s Statement: %s

`ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT` was added in 8.0.4.

- Error number: `MY-010909`; Symbol: `ER_FORCE_CLOSE_THREAD`; SQLSTATE: `HY000`

Message: %s: Forcing close of thread %ld user: '%s'.

`ER_FORCE_CLOSE_THREAD` was added in 8.0.4.

- Error number: `MY-010910`; Symbol: `ER_SERVER_SHUTDOWN_COMPLETE`; SQLSTATE: `HY000`

Message: %s: Shutdown complete (mysqld %s) %s.

`ER_SERVER_SHUTDOWN_COMPLETE` was added in 8.0.4.

- Error number: `MY-010911`; Symbol: `ER_RPL_CANT_HAVE_SAME_BASENAME`; SQLSTATE: `HY000`

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

`ER_RPL_CANT_HAVE_SAME_BASENAME` was added in 8.0.3.

- Error number: `MY-010912`; Symbol: `ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: `HY000`

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

`ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON` was added in 8.0.4.

- Error number: `MY-010913`; Symbol: `ER_WARN_NO_SERVERID_SPECIFIED`; SQLSTATE: `HY000`

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

`ER_WARN_NO_SERVERID_SPECIFIED` was added in 8.0.3.

- Error number: `MY-010914`; Symbol: `ER_ABORTING_USER_CONNECTION`; SQLSTATE: `HY000`

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

`ER_ABORTING_USER_CONNECTION` was added in 8.0.4.

- Error number: `MY-010915`; Symbol: `ER_SQL_MODE_MERGED_WITH_STRICT_MODE`; SQLSTATE: `HY000`

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

`ER_SQL_MODE_MERGED_WITH_STRICT_MODE` was added in 8.0.4.

- Error number: `MY-010916`; Symbol: `ER_GTID_PURGED_WAS_UPDATED`; SQLSTATE: `HY000`

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

`ER_GTID_PURGED_WAS_UPDATED` was added in 8.0.4.

-
- Error number: [MY-010917](#); Symbol: [ER_GTID_EXECUTED_WAS_UPDATED](#); SQLSTATE: [HY000](#)
Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.
[ER_GTID_EXECUTED_WAS_UPDATED](#) was added in 8.0.4.
 - Error number: [MY-010918](#); Symbol: [ER_DEPRECATED_MSG_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.
[ER_DEPRECATED_MSG_WITH_REPLACEMENT](#) was added in 8.0.4.
 - Error number: [MY-010919](#); Symbol: [ER_TRG_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)
Message: Triggers for table '%s`.`%s`' have no creation context
[ER_TRG_CREATION_CTX_NOT_SET](#) was added in 8.0.4.
 - Error number: [MY-010920](#); Symbol: [ER_FILE_HAS_OLD_FORMAT](#); SQLSTATE: [HY000](#)
Message: '%s' has an old format, you should re-create the '%s' object(s)
[ER_FILE_HAS_OLD_FORMAT](#) was added in 8.0.4.
 - Error number: [MY-010921](#); Symbol: [ER_VIEW_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)
Message: View '%s`.`%s`' has no creation context
[ER_VIEW_CREATION_CTX_NOT_SET](#) was added in 8.0.4.
 - Error number: [MY-010923](#); Symbol: [ER_TABLE_UPGRADE_REQUIRED](#); SQLSTATE: [HY000](#)
Message: Table upgrade required. Please do "REPAIR TABLE '%s'" or dump/reload to fix it!
[ER_TABLE_UPGRADE_REQUIRED](#) was added in 8.0.4.
 - Error number: [MY-010924](#); Symbol: [ER_GET_ERRNO_FROM_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Got error %d - '%s' from storage engine.
[ER_GET_ERRNO_FROM_STORAGE_ENGINE](#) was added in 8.0.4.
 - Error number: [MY-010925](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s'
[ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#) was added in 8.0.4.
 - Error number: [MY-010926](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s' (using password: %s)
[ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#) was added in 8.0.4.
 - Error number: [MY-010927](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s'. Account is locked.
[ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#) was added in 8.0.4.

-
- Error number: [MY-010928](#); Symbol: [ER_MUST_CHANGE_EXPIRED_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Your password has expired. To log in you must change it using a client that supports expired passwords.
[ER_MUST_CHANGE_EXPIRED_PASSWORD](#) was added in 8.0.4, removed after 8.0.28.
 - Error number: [MY-010929](#); Symbol: [ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' does not support system tables. [%s.%s].
[ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE](#) was added in 8.0.4.
 - Error number: [MY-010930](#); Symbol: [ER_FILESORT_TERMINATED](#); SQLSTATE: [HY000](#)
Message: Sort aborted
[ER_FILESORT_TERMINATED](#) was added in 8.0.4, removed after 8.0.18.
 - Error number: [MY-010931](#); Symbol: [ER_SERVER_STARTUP_MSG](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.
[ER_SERVER_STARTUP_MSG](#) was added in 8.0.4.
 - Error number: [MY-010932](#); Symbol: [ER_FAILED_TO_FIND_LOCALE_NAME](#); SQLSTATE: [HY000](#)
Message: Unknown locale: '%s'.
[ER_FAILED_TO_FIND_LOCALE_NAME](#) was added in 8.0.4.
 - Error number: [MY-010933](#); Symbol: [ER_FAILED_TO_FIND_COLLATION_NAME](#); SQLSTATE: [HY000](#)
Message: Unknown collation: '%s'.
[ER_FAILED_TO_FIND_COLLATION_NAME](#) was added in 8.0.4.
 - Error number: [MY-010934](#); Symbol: [ER_SERVER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)
Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space
[ER_SERVER_OUT_OF_RESOURCES](#) was added in 8.0.4.
 - Error number: [MY-010935](#); Symbol: [ER_SERVER_OUTOFMEMORY](#); SQLSTATE: [HY000](#)
Message: Out of memory; restart server and try again (needed %d bytes)
[ER_SERVER_OUTOFMEMORY](#) was added in 8.0.4.
 - Error number: [MY-010936](#); Symbol: [ER_INVALID_COLLATION_FOR_CHARSET](#); SQLSTATE: [HY000](#)
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'
[ER_INVALID_COLLATION_FOR_CHARSET](#) was added in 8.0.4.
 - Error number: [MY-010937](#); Symbol: [ER_CANT_START_ERROR_LOG_SERVICE](#); SQLSTATE: [HY000](#)
Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

`ER_CANT_START_ERROR_LOG_SERVICE` was added in 8.0.4.

- Error number: `MY-010938`; Symbol: `ER_CREATING_NEW_UUID_FIRST_START`; SQLSTATE: `HY000`

Message: Generating a new UUID: %s.

`ER_CREATING_NEW_UUID_FIRST_START` was added in 8.0.4.

- Error number: `MY-010939`; Symbol: `ER_FAILED_TO_GET_ABSOLUTE_PATH`; SQLSTATE: `HY000`

Message: Failed to get absolute path of program executable %s

`ER_FAILED_TO_GET_ABSOLUTE_PATH` was added in 8.0.4.

- Error number: `MY-010940`; Symbol: `ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap performance schema components infrastructure.

`ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010941`; Symbol: `ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`

Message: Failed to deinit performance schema components infrastructure.

`ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN` was added in 8.0.4.

- Error number: `MY-010942`; Symbol: `ER_DUP_FD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Could not open duplicate fd for %s: %s.

`ER_DUP_FD_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010943`; Symbol: `ER_SYSTEM_VIEW_INIT_FAILED`; SQLSTATE: `HY000`

Message: System views initialization failed.

`ER_SYSTEM_VIEW_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010944`; Symbol: `ER_RESOURCE_GROUP_POST_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource group post initialization failed.

`ER_RESOURCE_GROUP_POST_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010945`; Symbol: `ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: Resource Group subsystem initialization failed.

`ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010946`; Symbol: `ER_FAILED_START_MYSQLD_DAEMON`; SQLSTATE: `HY000`

Message: Failed to start mysqld daemon. Check mysqld error log.

`ER_FAILED_START_MYSQLD_DAEMON` was added in 8.0.4.

- Error number: `MY-010947`; Symbol: `ER_CANNOT_CHANGE_TO_ROOT_DIR`; SQLSTATE: `HY000`

Message: Cannot change to root directory: %s.

`ER_CANNOT_CHANGE_TO_ROOT_DIR` was added in 8.0.4.

- Error number: `MY-010948`; Symbol: `ER_PERSISTENT_PRIVILEGES_BOOTSTRAP`; SQLSTATE: `HY000`

Message: Failed to bootstrap persistent privileges.

`ER_PERSISTENT_PRIVILEGES_BOOTSTRAP` was added in 8.0.4.

- Error number: `MY-010949`; Symbol: `ER_BASEDIR_SET_TO`; SQLSTATE: `HY000`

Message: Basedir set to %s.

`ER_BASEDIR_SET_TO` was added in 8.0.4.

- Error number: `MY-010950`; Symbol: `ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED`; SQLSTATE: `HY000`

Message: Could not add wild do table rule '%s'!

`ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED` was added in 8.0.4.

- Error number: `MY-010951`; Symbol: `ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED`; SQLSTATE: `HY000`

Message: Could not add wild ignore table rule '%s'!

`ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED` was added in 8.0.4.

- Error number: `MY-010952`; Symbol: `ER_PRIVILEGE_SYSTEM_INIT_FAILED`; SQLSTATE: `HY000`

Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

`ER_PRIVILEGE_SYSTEM_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010953`; Symbol: `ER_CANNOT_SET_LOG_ERROR_SERVICES`; SQLSTATE: `HY000`

Message: Cannot set services "%s" requested in --log-error-services, using defaults.

`ER_CANNOT_SET_LOG_ERROR_SERVICES` was added in 8.0.4.

- Error number: `MY-010954`; Symbol: `ER_PERFSCHEMA_TABLES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Performance schema tables initialization failed.

`ER_PERFSCHEMA_TABLES_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-010955`; Symbol: `ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPEDENCY_TRACKING`; SQLSTATE: `HY000`

Message: The transaction_write_set_extraction must be set to %s when binlog_transaction_dependency_tracking is %s.

`ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DEPEDENCY_TRACKING` was added in 8.0.4.

-
- Error number: [MY-010956](#); Symbol: [ER_INVALID_REPLICATION_TIMESTAMPS](#); SQLSTATE: [HY000](#)

Message: Invalid replication timestamps: original commit timestamp is more recent than the immediate commit timestamp. This may be an issue if delayed replication is active. Make sure that servers have their clocks set to the correct time. No further message will be emitted until after timestamps become valid again.

[ER_INVALID_REPLICATION_TIMESTAMPS](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-010957](#); Symbol: [ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL](#); SQLSTATE: [HY000](#)

Message: The replication timestamps have returned to normal values.

[ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-010958](#); Symbol: [ER_BINLOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: %s.

[ER_BINLOG_FILE_OPEN_FAILED](#) was added in 8.0.4.

- Error number: [MY-010959](#); Symbol: [ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write an incident event into stmt_cache.

[ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED](#) was added in 8.0.4.

- Error number: [MY-010960](#); Symbol: [ER_SLAVE_RELAY_LOG_TRUNCATE_INFO](#); SQLSTATE: [HY000](#)

Message: Relaylog file %s size was %llu, but was truncated at %llu.

[ER_SLAVE_RELAY_LOG_TRUNCATE_INFO](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010960](#); Symbol: [ER_REPLICA_RELAY_LOG_TRUNCATE_INFO](#); SQLSTATE: [HY000](#)

Message: Relaylog file %s size was %llu, but was truncated at %llu.

[ER_REPLICA_RELAY_LOG_TRUNCATE_INFO](#) was added in 8.0.33.

- Error number: [MY-010961](#); Symbol: [ER_SLAVE_RELAY_LOG_PURGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to purge relay log files. %s:%s.

[ER_SLAVE_RELAY_LOG_PURGE_FAILED](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-010961](#); Symbol: [ER_REPLICA_RELAY_LOG_PURGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to purge relay log files. %s:%s.

[ER_REPLICA_RELAY_LOG_PURGE_FAILED](#) was added in 8.0.33.

- Error number: [MY-010962](#); Symbol: [ER_RPL_SLAVE_FILTER_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave: failed in creating filter for channel '%s'.

[ER_RPL_SLAVE_FILTER_CREATE_FAILED](#) was added in 8.0.4, removed after 8.0.32.

-
- Error number: [MY-010962](#); Symbol: [ER_RPL_REPLICA_FILTER_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica: failed in creating filter for channel '%s'.

[ER_RPL_REPLICA_FILTER_CREATE_FAILED](#) was added in 8.0.33.
 - Error number: [MY-010963](#); Symbol: [ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED](#); SQLSTATE: [HY000](#)

Message: Slave: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

[ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-010963](#); Symbol: [ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED](#); SQLSTATE: [HY000](#)

Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.

[ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED](#) was added in 8.0.33.
 - Error number: [MY-010964](#); Symbol: [ER_RPL_SLAVE_RESET_FILTER_OPTIONS](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER_RPL_SLAVE_RESET_FILTER_OPTIONS](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-010964](#); Symbol: [ER_RPL_REPLICA_RESET_FILTER_OPTIONS](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER_RPL_REPLICA_RESET_FILTER_OPTIONS](#) was added in 8.0.33.
 - Error number: [MY-010965](#); Symbol: [ER_MISSING_GRANT_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: The system table mysql.global_grants is missing. Please perform the MySQL upgrade procedure.

[ER_MISSING_GRANT_SYSTEM_TABLE](#) was added in 8.0.4.
 - Error number: [MY-010966](#); Symbol: [ER_MISSING_ACL_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: ACL table mysql.%.*s missing. Some operations may fail.

[ER_MISSING_ACL_SYSTEM_TABLE](#) was added in 8.0.4.
 - Error number: [MY-010967](#); Symbol: [ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role %s@%s: Anonymous authorization IDs are not allowed as roles.

[ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#) was added in 8.0.4.
 - Error number: [MY-010968](#); Symbol: [ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)

Message: Can't set mandatory_role: There's no such authorization ID %s@%s.

`ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE` was added in 8.0.4.

- Error number: `MY-010969`; Symbol: `ER_WRITE_ROW_TO_PARTITION_FAILED`; SQLSTATE: `HY000`

Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.

`ER_WRITE_ROW_TO_PARTITION_FAILED` was added in 8.0.4.

- Error number: `MY-010970`; Symbol: `ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED`; SQLSTATE: `HY000`

Message: Skipped updating resource group metadata in InnoDB read only mode.

`ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED` was added in 8.0.4.

- Error number: `MY-010971`; Symbol: `ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA`; SQLSTATE: `HY000`

Message: Failed to persist resource group %s to Data Dictionary.

`ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA` was added in 8.0.4.

- Error number: `MY-010972`; Symbol: `ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Failed to deserialize resource group %s.

`ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010973`; Symbol: `ER_FAILED_TO_UPDATE_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Update of resource group %s failed.

`ER_FAILED_TO_UPDATE_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010974`; Symbol: `ER_RESOURCE_GROUP_VALIDATION_FAILED`; SQLSTATE: `HY000`

Message: Validation of resource group %s failed. Resource group is disabled.

`ER_RESOURCE_GROUP_VALIDATION_FAILED` was added in 8.0.4.

- Error number: `MY-010975`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Unable to allocate memory for Resource Group %s.

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010976`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH`; SQLSTATE: `HY000`

Message: Failed to allocate memory for resource group hash.

`ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH` was added in 8.0.4.

- Error number: `MY-010977`; Symbol: `ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP`; SQLSTATE: `HY000`

Message: Failed to add resource group %s to resource group map.

`ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP` was added in 8.0.4.

- Error number: `MY-010978`; Symbol: `ER_RESOURCE_GROUP_IS_DISABLED`; SQLSTATE: `HY000`
Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).

`ER_RESOURCE_GROUP_IS_DISABLED` was added in 8.0.4.

- Error number: `MY-010979`; Symbol: `ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER`; SQLSTATE: `HY000`

Message: Unable to apply resource group controller %s.

`ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER` was added in 8.0.4.

- Error number: `MY-010980`; Symbol: `ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.

`ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP` was added in 8.0.4.

- Error number: `MY-010981`; Symbol: `ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED`; SQLSTATE: `HY000`

Message: PFS %s notification function registration failed.

`ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED` was added in 8.0.4.

- Error number: `MY-010982`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).

`ER_RES_GRP_SET_THR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).

`ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED` was added in 8.0.4.

- Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`

Message: Unbind thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED` was added in 8.0.4.

- Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`

Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).

`ER_RES_GRP_SET_THREAD_PRIORITY_FAILED` was added in 8.0.4.

- Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`

Message: Unable to determine `CAP_SYS_NICE` capability.

`ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY` was added in 8.0.4.

- Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`

Message: %s failed: Failed to get handle for thread %llu.

`ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE` was added in 8.0.4.

- Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Retrieval of thread priority unsupported on %s.

`ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED` was added in 8.0.4.

- Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`

Message: Unable to determine the number of CPUs.

`ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT` was added in 8.0.4.

- Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Resource group feature shall not be available. Incompatible thread handling option.

`ER_RES_GRP_FEATURE_NOT_AVAILABLE` was added in 8.0.4.

- Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

`ER_RES_GRP_INVALID_THREAD_PRIORITY` was added in 8.0.4.

- Error number: `MY-010992`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for cpuid %u failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED` was added in 8.0.4.

- Error number: `MY-010993`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for thread %llu with cpu id %u (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED` was added in 8.0.4.

- Error number: `MY-010994`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: %s failed: processor_affinity failed (error code %d - %s).

`ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED` was added in 8.0.4.

- Error number: `MY-010995`; Symbol: `ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED`; SQLSTATE: `HY000`

Message: Error in renaming mysql_index_stats.ibd.

`ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED` was added in 8.0.4.

- Error number: `MY-010996`; Symbol: `ER_DD_UPGRADE_DD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Error in opening data directory %s.

`ER_DD_UPGRADE_DD_OPEN_FAILED` was added in 8.0.4.

- Error number: `MY-010997`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES`; SQLSTATE: `HY000`

Message: Error in fetching list of tablespaces.

`ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES` was added in 8.0.4.

- Error number: `MY-010998`; Symbol: `ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in acquiring Tablespace for SDI insertion %s.

`ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE` was added in 8.0.4.

- Error number: `MY-010999`; Symbol: `ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE`; SQLSTATE: `HY000`

Message: Error in resolving Engine name for tablespace %s with engine %s.

`ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE` was added in 8.0.4.

- Error number: `MY-011000`; Symbol: `ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in creating SDI for %s tablespace.

`ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE` was added in 8.0.4.

- Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in storing SDI for %s tablespace.

`ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE` was added in 8.0.4.

- Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`

Message: Error in fetching list of tables.

`ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES` was added in 8.0.4.

- Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`

Message: Finished populating Data Dictionary tables with data.

`ER_DD_UPGRADE_DD_POPULATED` was added in 8.0.4.

- Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

`ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED` was added in 8.0.4.

-
- Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`

Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

`ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED` was added in 8.0.4.
 - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`

Message: Got error %d from SE while migrating tablespaces.

`ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED` was added in 8.0.4.
 - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`

Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.

`ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS` was added in 8.0.4.
 - Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`

Message: Finished migrating TABLE statistics data.

`ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED` was added in 8.0.4.
 - Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`

Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.

`ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS` was added in 8.0.4.
 - Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`

Message: Finished migrating INDEX statistics data.

`ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED` was added in 8.0.4.
 - Error number: `MY-011011`; Symbol: `ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR`; SQLSTATE: `HY000`

Message: Failed to find valid data directory.

`ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR` was added in 8.0.4.
 - Error number: `MY-011012`; Symbol: `ER_DD_UPGRADE_START`; SQLSTATE: `HY000`

Message: Starting upgrade of data directory.

`ER_DD_UPGRADE_START` was added in 8.0.4.
 - Error number: `MY-011013`; Symbol: `ER_DD_UPGRADE_FAILED_INIT_DD_SE`; SQLSTATE: `HY000`

Message: Failed to initialize DD Storage Engine.

`ER_DD_UPGRADE_FAILED_INIT_DD_SE` was added in 8.0.4.
 - Error number: `MY-011014`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT` was added in 8.0.4.

- Error number: `MY-011015`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Upgrade will continue and start the server.

`ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE` was added in 8.0.4.

- Error number: `MY-011016`; Symbol: `ER_DD_UPGRADE_SE_LOGS_FAILED`; SQLSTATE: `HY000`

Message: Error in upgrading engine logs.

`ER_DD_UPGRADE_SE_LOGS_FAILED` was added in 8.0.4.

- Error number: `MY-011017`; Symbol: `ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED`; SQLSTATE: `HY000`

Message: Error in updating SDI information.

`ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED` was added in 8.0.4.

- Error number: `MY-011018`; Symbol: `ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE`; SQLSTATE: `HY000`

Message: Skip updating %s metadata in InnoDB read-only mode.

`ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE` was added in 8.0.4.

- Error number: `MY-011019`; Symbol: `ER_CREATED_SYSTEM_WITH_VERSION`; SQLSTATE: `HY000`

Message: Created system views with I_S version %d.

`ER_CREATED_SYSTEM_WITH_VERSION` was added in 8.0.4.

- Error number: `MY-011020`; Symbol: `ER_UNKNOWN_ERROR_DETECTED_IN_SE`; SQLSTATE: `HY000`

Message: Unknown error detected %d in handler.

`ER_UNKNOWN_ERROR_DETECTED_IN_SE` was added in 8.0.4.

- Error number: `MY-011021`; Symbol: `ER_READ_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Error in Log_event::read_log_event(): '%s', data_len: %lu, event_type: %d.

`ER_READ_LOG_EVENT_FAILED` was added in 8.0.4.

- Error number: `MY-011022`; Symbol: `ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG`; SQLSTATE: `HY000`

Message: The row data is greater than 4GB, which is too big to write to the binary log.

`ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG` was added in 8.0.4.

- Error number: `MY-011023`; Symbol: `ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY`; SQLSTATE: `HY000`

Message: Unable to construct DROP EVENT SQL query string.

`ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY` was added in 8.0.4.

-
- Error number: [MY-011024](#); Symbol: [ER_FAILED_TO_BINLOG_DROP_EVENT](#); SQLSTATE: [HY000](#)
Message: Unable to binlog drop event %s.%s.
[ER_FAILED_TO_BINLOG_DROP_EVENT](#) was added in 8.0.4.
 - Error number: [MY-011025](#); Symbol: [ER_FAILED_TO_START_SLAVE_THREAD](#); SQLSTATE: [HY000](#)
Message: Failed to start slave threads for channel '%s'.
[ER_FAILED_TO_START_SLAVE_THREAD](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011025](#); Symbol: [ER_FAILED_TO_START_REPLICA_THREAD](#); SQLSTATE: [HY000](#)
Message: Failed to start replica threads for channel '%s'.
[ER_FAILED_TO_START_REPLICA_THREAD](#) was added in 8.0.33.
 - Error number: [MY-011026](#); Symbol: [ER_RPL_IO_THREAD_KILLED](#); SQLSTATE: [HY000](#)
Message: %s%s.
[ER_RPL_IO_THREAD_KILLED](#) was added in 8.0.4.
 - Error number: [MY-011027](#); Symbol: [ER_SLAVE_RECONNECT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed registering on master, reconnecting to try again, log '%s' at position %s. %s.
[ER_SLAVE_RECONNECT_FAILED](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011027](#); Symbol: [ER_REPLICA_RECONNECT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.
[ER_REPLICA_RECONNECT_FAILED](#) was added in 8.0.33.
 - Error number: [MY-011028](#); Symbol: [ER_SLAVE_KILLED_AFTER_RECONNECT](#); SQLSTATE: [HY000](#)
Message: Slave I/O thread killed during or after reconnect.
[ER_SLAVE_KILLED_AFTER_RECONNECT](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011028](#); Symbol: [ER_REPLICA_KILLED_AFTER_RECONNECT](#); SQLSTATE: [HY000](#)
Message: Replica I/O thread killed during or after reconnect.
[ER_REPLICA_KILLED_AFTER_RECONNECT](#) was added in 8.0.33.
 - Error number: [MY-011029](#); Symbol: [ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS](#); SQLSTATE: [HY000](#)
Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.
[ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS](#) was added in 8.0.4, removed after 8.0.32.

-
- Error number: [MY-011029](#); Symbol: [ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

[ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS](#) was added in 8.0.33.

- Error number: [MY-011030](#); Symbol: [ER_FAILED_TO_ADD_RPL_FILTER](#); SQLSTATE: [HY000](#)

Message: Failed to add a replication filter into filter map for channel '%s'.

[ER_FAILED_TO_ADD_RPL_FILTER](#) was added in 8.0.4.

- Error number: [MY-011031](#); Symbol: [ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

[ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL](#) was added in 8.0.4.

- Error number: [MY-011032](#); Symbol: [ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL](#); SQLSTATE: [HY000](#)

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

[ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL](#) was added in 8.0.4.

- Error number: [MY-011033](#); Symbol: [ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building do_table and ignore_table rules to hashes for per-channel filter.

[ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES](#) was added in 8.0.4.

- Error number: [MY-011034](#); Symbol: [ER_CLONE_PLUGIN_NOT_LOADED](#); SQLSTATE: [HY000](#)

Message: Clone plugin not loaded.

[ER_CLONE_PLUGIN_NOT_LOADED](#) was added in 8.0.4, removed after 8.0.16.

- Error number: [MY-011034](#); Symbol: [ER_CLONE_PLUGIN_NOT_LOADED_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone plugin cannot be loaded.

[ER_CLONE_PLUGIN_NOT_LOADED_TRACE](#) was added in 8.0.17.

- Error number: [MY-011035](#); Symbol: [ER_CLONE_HANDLER_EXISTS](#); SQLSTATE: [HY000](#)

Message: Clone Handler exists.

[ER_CLONE_HANDLER_EXISTS](#) was added in 8.0.4, removed after 8.0.16.

- Error number: [MY-011035](#); Symbol: [ER_CLONE_HANDLER_EXIST_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone Handler exists.

[ER_CLONE_HANDLER_EXIST_TRACE](#) was added in 8.0.17.

-
- Error number: MY-011036; Symbol: ER_FAILED_TO_CREATE_CLONE_HANDLER; SQLSTATE: HY000
Message: Could not create Clone Handler.
ER_FAILED_TO_CREATE_CLONE_HANDLER was added in 8.0.4, removed after 8.0.16.
 - Error number: MY-011036; Symbol: ER_CLONE_CREATE_HANDLER_FAIL_TRACE; SQLSTATE: HY000
Message: Could not create Clone Handler.
ER_CLONE_CREATE_HANDLER_FAIL_TRACE was added in 8.0.17.
 - Error number: MY-011037; Symbol: ER_CYCLE_TIMER_IS_NOT_AVAILABLE; SQLSTATE: HY000
Message: The CYCLE timer is not available. WAIT events in the performance_schema will not be timed.
ER_CYCLE_TIMER_IS_NOT_AVAILABLE was added in 8.0.4.
 - Error number: MY-011038; Symbol: ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE; SQLSTATE: HY000
Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE was added in 8.0.4.
 - Error number: MY-011039; Symbol: ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE; SQLSTATE: HY000
Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.
ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE was added in 8.0.4.
 - Error number: MY-011040; Symbol: ER_PFS_MALLOC_ARRAY_OVERFLOW; SQLSTATE: HY000
Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.
ER_PFS_MALLOC_ARRAY_OVERFLOW was added in 8.0.4.
 - Error number: MY-011041; Symbol: ER_PFS_MALLOC_ARRAY_OOM; SQLSTATE: HY000
Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.
ER_PFS_MALLOC_ARRAY_OOM was added in 8.0.4.
 - Error number: MY-011042; Symbol: ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO; SQLSTATE: HY000
Message: InnoDB could not find index %s key no %u for table %s through its index translation table.
ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO was added in 8.0.4.
 - Error number: MY-011043; Symbol: ER_INNODB_FAILED_TO_FIND_IDX; SQLSTATE: HY000
Message: Cannot find index %s in InnoDB index translation table.
ER_INNODB_FAILED_TO_FIND_IDX was added in 8.0.4.
 - Error number: MY-011044; Symbol: ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE; SQLSTATE: HY000

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

`ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE` was added in 8.0.4.

- Error number: `MY-011045`; Symbol: `ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED`; SQLSTATE: `HY000`

Message: InnoDB: change_active_index(%u) failed.

`ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED` was added in 8.0.4.

- Error number: `MY-011046`; Symbol: `ER_INNODB_DIFF_IN_REF_LEN`; SQLSTATE: `HY000`

Message: Stored ref len is %lu, but table ref len is %lu.

`ER_INNODB_DIFF_IN_REF_LEN` was added in 8.0.4.

- Error number: `MY-011047`; Symbol: `ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD`; SQLSTATE: `HY000`

Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.

`ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD` was added in 8.0.4.

- Error number: `MY-011048`; Symbol: `ER_INNODB_CANNOT_CREATE_TABLE`; SQLSTATE: `HY000`

Message: Cannot create table %s.

`ER_INNODB_CANNOT_CREATE_TABLE` was added in 8.0.4.

- Error number: `MY-011049`; Symbol: `ER_INNODB_INTERNAL_INDEX`; SQLSTATE: `HY000`

Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.

`ER_INNODB_INTERNAL_INDEX` was added in 8.0.4.

- Error number: `MY-011050`; Symbol: `ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL`; SQLSTATE: `HY000`

Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.

`ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL` was added in 8.0.4.

- Error number: `MY-011051`; Symbol: `ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL`; SQLSTATE: `HY000`

Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?

`ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL` was added in 8.0.4.

- Error number: `MY-011052`; Symbol: `ER_INNODB_IDX_COLUMN_CNT_DIFF`; SQLSTATE: `HY000`

Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?

`ER_INNODB_IDX_COLUMN_CNT_DIFF` was added in 8.0.4.

- Error number: `MY-011053`; Symbol: `ER_INNODB_USE_MONITOR_GROUP_NAME`; SQLSTATE: `HY000`

Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.

`ER_INNOODB_USE_MONITOR_GROUP_NAME` was added in 8.0.4.

- Error number: `MY-011054`; Symbol: `ER_INNOODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED`; SQLSTATE: `HY000`

Message: Default value is not defined for this set option. Please specify correct counter or module name.

`ER_INNOODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED` was added in 8.0.4.

- Error number: `MY-011055`; Symbol: `ER_INNOODB_MONITOR_IS_ENABLED`; SQLSTATE: `HY000`

Message: InnoDB: Monitor %s is already enabled.

`ER_INNOODB_MONITOR_IS_ENABLED` was added in 8.0.4.

- Error number: `MY-011056`; Symbol: `ER_INNOODB_INVALID_MONITOR_COUNTER_NAME`; SQLSTATE: `HY000`

Message: Invalid monitor counter : %s.

`ER_INNOODB_INVALID_MONITOR_COUNTER_NAME` was added in 8.0.4.

- Error number: `MY-011057`; Symbol: `ER_WIN_LOAD_LIBRARY_FAILED`; SQLSTATE: `HY000`

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

`ER_WIN_LOAD_LIBRARY_FAILED` was added in 8.0.4.

- Error number: `MY-011058`; Symbol: `ER_PARTITION_HANDLER_ADMIN_MSG`; SQLSTATE: `HY000`

Message: %s.

`ER_PARTITION_HANDLER_ADMIN_MSG` was added in 8.0.4.

- Error number: `MY-011059`; Symbol: `ER_RPL_RLI_INIT_INFO_MSG`; SQLSTATE: `HY000`

Message: %s.

`ER_RPL_RLI_INIT_INFO_MSG` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011059`; Symbol: `ER_RPL_AM_INIT_INFO_MSG`; SQLSTATE: `HY000`

Message: %s.

`ER_RPL_AM_INIT_INFO_MSG` was added in 8.0.33.

- Error number: `MY-011060`; Symbol: `ER_DD_UPGRADE_TABLE_INTACT_ERROR`; SQLSTATE: `HY000`

Message: %s.

`ER_DD_UPGRADE_TABLE_INTACT_ERROR` was added in 8.0.4.

- Error number: `MY-011061`; Symbol: `ER_SERVER_INIT_COMPILED_IN_COMMANDS`; SQLSTATE: `HY000`

Message: %s.

`ER_SERVER_INIT_COMPILED_IN_COMMANDS` was added in 8.0.4.

-
- Error number: `MY-011062`; Symbol: `ER_MYISAM_CHECK_METHOD_ERROR`; SQLSTATE: `HY000`
Message: %s.
`ER_MYISAM_CHECK_METHOD_ERROR` was added in 8.0.4.
 - Error number: `MY-011063`; Symbol: `ER_MYISAM_CRASHED_ERROR`; SQLSTATE: `HY000`
Message: %s.
`ER_MYISAM_CRASHED_ERROR` was added in 8.0.4.
 - Error number: `MY-011064`; Symbol: `ER_WAITPID_FAILED`; SQLSTATE: `HY000`
Message: Unable to wait for process %ld.
`ER_WAITPID_FAILED` was added in 8.0.4.
 - Error number: `MY-011065`; Symbol: `ER_FAILED_TO_FIND_MYSQLD_STATUS`; SQLSTATE: `HY000`
Message: Unable to determine if daemon is running: %s (rc=%d).
`ER_FAILED_TO_FIND_MYSQLD_STATUS` was added in 8.0.4.
 - Error number: `MY-011066`; Symbol: `ER_INNODB_ERROR_LOGGER_MSG`; SQLSTATE: `HY000`
Message: %s
`ER_INNODB_ERROR_LOGGER_MSG` was added in 8.0.4.
 - Error number: `MY-011067`; Symbol: `ER_INNODB_ERROR_LOGGER_FATAL_MSG`; SQLSTATE: `HY000`
Message: [FATAL] InnoDB: %s
`ER_INNODB_ERROR_LOGGER_FATAL_MSG` was added in 8.0.4.
 - Error number: `MY-011068`; Symbol: `ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT`; SQLSTATE: `HY000`
Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.
`ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT` was added in 8.0.4.
 - Error number: `MY-011069`; Symbol: `ER_DEPRECATED_SYNTAX_NO_REPLACEMENT`; SQLSTATE: `HY000`
Message: The syntax '%s' is deprecated and will be removed in a future release.
`ER_DEPRECATED_SYNTAX_NO_REPLACEMENT` was added in 8.0.4.
 - Error number: `MY-011070`; Symbol: `ER_DEPRECATED_MSG_NO_REPLACEMENT`; SQLSTATE: `HY000`
Message: '%s' is deprecated and will be removed in a future release.
`ER_DEPRECATED_MSG_NO_REPLACEMENT` was added in 8.0.4.
 - Error number: `MY-011071`; Symbol: `ER_LOG_PRINTF_MSG`; SQLSTATE: `HY000`
Message: %s
`ER_LOG_PRINTF_MSG` was added in 8.0.4.

-
- Error number: [MY-011072](#); Symbol: [ER_BINLOG_LOGGING_NOT_POSSIBLE](#); SQLSTATE: [HY000](#)
Message: Binary logging not possible. Message: %s.
[ER_BINLOG_LOGGING_NOT_POSSIBLE](#) was added in 8.0.4.
 - Error number: [MY-011073](#); Symbol: [ER_FAILED_TO_SET_PERSISTED_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Failed to set persisted options.
[ER_FAILED_TO_SET_PERSISTED_OPTIONS](#) was added in 8.0.4.
 - Error number: [MY-011074](#); Symbol: [ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot acquire specified service implementation: '%s'.
[ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#) was added in 8.0.4.
 - Error number: [MY-011075](#); Symbol: [ER_RES_GRP_INVALID_VCPU_RANGE](#); SQLSTATE: [HY000](#)
Message: Invalid VCPU range %u-%u.
[ER_RES_GRP_INVALID_VCPU_RANGE](#) was added in 8.0.4.
 - Error number: [MY-011076](#); Symbol: [ER_RES_GRP_INVALID_VCPU_ID](#); SQLSTATE: [HY000](#)
Message: Invalid cpu id %u.
[ER_RES_GRP_INVALID_VCPU_ID](#) was added in 8.0.4.
 - Error number: [MY-011077](#); Symbol: [ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#); SQLSTATE: [HY000](#)
Message: Got error %d during FLUSH_LOGS.
[ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#) was added in 8.0.4.
 - Error number: [MY-011078](#); Symbol: [ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#); SQLSTATE: [HY000](#)
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
[ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#) was added in 8.0.4.
 - Error number: [MY-011079](#); Symbol: [ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER](#); SQLSTATE: [HY000](#)
Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.
[ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER](#) was added in 8.0.4, removed after 8.0.4.
 - Error number: [MY-011079](#); Symbol: [ER_EXPIRE_LOGS_DAYS_IGNORED](#); SQLSTATE: [HY000](#)
Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.
[ER_EXPIRE_LOGS_DAYS_IGNORED](#) was added in 8.0.4.

-
- Error number: [MY-011080](#); Symbol: [ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: malformed or very old relay log which does not have FormatDescriptor.

[ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#) was added in 8.0.4.
 - Error number: [MY-011081](#); Symbol: [ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.

[ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#) was added in 8.0.4.
 - Error number: [MY-011082](#); Symbol: [ER_TABLE_NEEDS_DUMP_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Table upgrade required for '%s`.`%s`. Please dump/reload table to fix it!

[ER_TABLE_NEEDS_DUMP_UPGRADE](#) was added in 8.0.4.
 - Error number: [MY-011083](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Error in updating version number in %s tablespace.

[ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#) was added in 8.0.4.
 - Error number: [MY-011084](#); Symbol: [ER_KEYRING_MIGRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Keyring migration failed.

[ER_KEYRING_MIGRATION_FAILED](#) was added in 8.0.4.
 - Error number: [MY-011085](#); Symbol: [ER_KEYRING_MIGRATION_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: Keyring migration successful.

[ER_KEYRING_MIGRATION_SUCCESSFUL](#) was added in 8.0.4.
 - Error number: [MY-011086](#); Symbol: [ER_RESTART_RECEIVED_INFO](#); SQLSTATE: [HY000](#)

Message: Received RESTART from user %s. Restarting mysqld (Version: %s).

[ER_RESTART_RECEIVED_INFO](#) was added in 8.0.4.
 - Error number: [MY-011087](#); Symbol: [ER_LCTN_CHANGED](#); SQLSTATE: [HY000](#)

Message: Different lower_case_table_names settings for server ('%u') and data dictionary ('%u').

[ER_LCTN_CHANGED](#) was added in 8.0.4.
 - Error number: [MY-011088](#); Symbol: [ER_DD_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Data dictionary initializing version '%u'.

[ER_DD_INITIALIZE](#) was added in 8.0.4.
 - Error number: [MY-011089](#); Symbol: [ER_DD_RESTART](#); SQLSTATE: [HY000](#)

Message: Data dictionary restarting version '%u'.

[ER_DD_RESTART](#) was added in 8.0.4.

-
- Error number: [MY-011090](#); Symbol: [ER_DD_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Data dictionary upgrading from version '%u' to '%u'.
[ER_DD_UPGRADE](#) was added in 8.0.4.
 - Error number: [MY-011091](#); Symbol: [ER_DD_UPGRADE_OFF](#); SQLSTATE: [HY000](#)
Message: Data dictionary upgrade prohibited by the command line option '--no_dd_upgrade'.
[ER_DD_UPGRADE_OFF](#) was added in 8.0.4.
 - Error number: [MY-011092](#); Symbol: [ER_DD_UPGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Upgrading the data dictionary from dictionary version '%u' is not supported.
[ER_DD_UPGRADE_VERSION_NOT_SUPPORTED](#) was added in 8.0.4.
 - Error number: [MY-011093](#); Symbol: [ER_DD_UPGRADE_SCHEMA_UNAVAILABLE](#); SQLSTATE: [HY000](#)
Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.
[ER_DD_UPGRADE_SCHEMA_UNAVAILABLE](#) was added in 8.0.4.
 - Error number: [MY-011094](#); Symbol: [ER_DD_MINOR_DOWNGRADE](#); SQLSTATE: [HY000](#)
Message: Data dictionary minor downgrade from version '%u' to '%u'.
[ER_DD_MINOR_DOWNGRADE](#) was added in 8.0.4.
 - Error number: [MY-011095](#); Symbol: [ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.
[ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED](#) was added in 8.0.4.
 - Error number: [MY-011096](#); Symbol: [ER_DD_NO_VERSION_FOUND](#); SQLSTATE: [HY000](#)
Message: No data dictionary version number found.
[ER_DD_NO_VERSION_FOUND](#) was added in 8.0.4.
 - Error number: [MY-011097](#); Symbol: [ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM](#); SQLSTATE: [HY000](#)
Message: Thread pool not supported, requires a minimum of %s.
[ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM](#) was added in 8.0.4.
 - Error number: [MY-011098](#); Symbol: [ER_THREAD_POOL_SIZE_TOO_LOW](#); SQLSTATE: [HY000](#)
Message: thread_pool_size=0 means thread pool disabled, Allowed range of thread_pool_size is %d-%d.
[ER_THREAD_POOL_SIZE_TOO_LOW](#) was added in 8.0.4.
 - Error number: [MY-011099](#); Symbol: [ER_THREAD_POOL_SIZE_TOO_HIGH](#); SQLSTATE: [HY000](#)
Message: thread_pool_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread_pool_size is %d-%d.

`ER_THREAD_POOL_SIZE_TOO_HIGH` was added in 8.0.4.

- Error number: `MY-011100`; Symbol: `ER_THREAD_POOL_ALGORITHM_INVALID`; SQLSTATE: `HY000`

Message: `thread_pool_algorithm` can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

`ER_THREAD_POOL_ALGORITHM_INVALID` was added in 8.0.4.

- Error number: `MY-011101`; Symbol: `ER_THREAD_POOL_INVALID_STALL_LIMIT`; SQLSTATE: `HY000`

Message: `thread_pool_stall_limit` can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

`ER_THREAD_POOL_INVALID_STALL_LIMIT` was added in 8.0.4.

- Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`

Message: Invalid value of `thread_pool_prio_kickup_timer` specified. Value of `thread_pool_prio_kickup_timer` should be in range 0-4294967294.

`ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER` was added in 8.0.4.

- Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`

Message: `thread_pool_max_unused_threads` cannot be set higher than %d.

`ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID` was added in 8.0.4.

- Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to instantiate the connection handler object.

`ER_THREAD_POOL_CON_HANDLER_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize thread pool plugin.

`ER_THREAD_POOL_INIT_FAILED` was added in 8.0.4.

- Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`

Message: Can't setup connection teardown thread-specific data.

`ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA` was added in 8.0.4.

- Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`

Message: Creation of connect handler thread failed.

`ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD` was added in 8.0.4.

-
- Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`
Message: Failed to create thd and authenticate connection.
`ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN` was added in 8.0.4.
 - Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`
Message: Failed to process connection event.
`ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT` was added in 8.0.4.
 - Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`
Message: Can't create pool thread (error %d, errno: %d).
`ER_THREAD_POOL_FAILED_TO_CREATE_POOL` was added in 8.0.4.
 - Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`
Message: %.*s.
`ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS` was added in 8.0.4.
 - Error number: `MY-011113`; Symbol: `ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`
Message: tp_group_low_level_init() failed.
`ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED` was added in 8.0.4.
 - Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`
Message: Rearm failed even after 30 seconds, can't continue without notify socket.
`ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED` was added in 8.0.4.
 - Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`
Message: %s: %s buffer is too small
`ER_THREAD_POOL_BUFFER_TOO_SMALL` was added in 8.0.4.
 - Error number: `MY-011116`; Symbol: `ER_MECAB_NOT_SUPPORTED`; SQLSTATE: `HY000`
Message: Mecab v%s is not supported, the lowest version supported is v%s.
`ER_MECAB_NOT_SUPPORTED` was added in 8.0.4.
 - Error number: `MY-011117`; Symbol: `ER_MECAB_NOT_VERIFIED`; SQLSTATE: `HY000`
Message: Mecab v%s is not verified, the highest version supported is v%s.
`ER_MECAB_NOT_VERIFIED` was added in 8.0.4.
 - Error number: `MY-011118`; Symbol: `ER_MECAB_CREATING_MODEL`; SQLSTATE: `HY000`
Message: Mecab: Trying createModel(%s).

`ER_MECAB_CREATING_MODEL` was added in 8.0.4.

- Error number: `MY-011119`; Symbol: `ER_MECAB_FAILED_TO_CREATE_MODEL`; SQLSTATE: `HY000`

Message: Mecab: createModel() failed: %s.

`ER_MECAB_FAILED_TO_CREATE_MODEL` was added in 8.0.4.

- Error number: `MY-011120`; Symbol: `ER_MECAB_FAILED_TO_CREATE_TRIGGER`; SQLSTATE: `HY000`

Message: Mecab: createTagger() failed: %s.

`ER_MECAB_FAILED_TO_CREATE_TRIGGER` was added in 8.0.4.

- Error number: `MY-011121`; Symbol: `ER_MECAB_UNSUPPORTED_CHARSET`; SQLSTATE: `HY000`

Message: Mecab: Unsupported dictionary charset %s.

`ER_MECAB_UNSUPPORTED_CHARSET` was added in 8.0.4.

- Error number: `MY-011122`; Symbol: `ER_MECAB_CHARSET_LOADED`; SQLSTATE: `HY000`

Message: Mecab: Loaded dictionary charset is %s.

`ER_MECAB_CHARSET_LOADED` was added in 8.0.4.

- Error number: `MY-011123`; Symbol: `ER_MECAB_PARSE_FAILED`; SQLSTATE: `HY000`

Message: Mecab: parse() failed: %s.

`ER_MECAB_PARSE_FAILED` was added in 8.0.4.

- Error number: `MY-011124`; Symbol: `ER_MECAB_OOM_WHILE_PARSING_TEXT`; SQLSTATE: `HY000`

Message: Mecab: parse() failed: out of memory.

`ER_MECAB_OOM_WHILE_PARSING_TEXT` was added in 8.0.4.

- Error number: `MY-011125`; Symbol: `ER_MECAB_CREATE_LATTICE_FAILED`; SQLSTATE: `HY000`

Message: Mecab: createLattice() failed: %s.

`ER_MECAB_CREATE_LATTICE_FAILED` was added in 8.0.4.

- Error number: `MY-011126`; Symbol: `ER_SEMISYNC_TRACE_ENTER_FUNC`; SQLSTATE: `HY000`

Message: ---> %s enter.

`ER_SEMISYNC_TRACE_ENTER_FUNC` was added in 8.0.4.

- Error number: `MY-011127`; Symbol: `ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE`; SQLSTATE: `HY000`

Message: <--- %s exit (%d).

`ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE` was added in 8.0.4.

-
- Error number: MY-011128; Symbol: ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE; SQLSTATE: HY000
Message: <--- %s exit (%s).
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE was added in 8.0.4.
 - Error number: MY-011129; Symbol: ER_SEMISYNC_TRACE_EXIT; SQLSTATE: HY000
Message: <--- %s exit.
ER_SEMISYNC_TRACE_EXIT was added in 8.0.4.
 - Error number: MY-011130; Symbol: ER_SEMISYNC_RPL_INIT_FOR_TRX; SQLSTATE: HY000
Message: Semi-sync replication initialized for transactions.
ER_SEMISYNC_RPL_INIT_FOR_TRX was added in 8.0.4.
 - Error number: MY-011131; Symbol: ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE; SQLSTATE: HY000
Message: %s: transaction node allocation failed for: (%s, %lu).
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE was added in 8.0.4.
 - Error number: MY-011132; Symbol: ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER; SQLSTATE: HY000
Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER was added in 8.0.4.
 - Error number: MY-011133; Symbol: ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY; SQLSTATE: HY000
Message: %s: insert (%s, %lu) in entry(%u).
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY was added in 8.0.4.
 - Error number: MY-011134; Symbol: ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY; SQLSTATE: HY000
Message: %s: probe (%s, %lu) in entry(%u).
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY was added in 8.0.4.
 - Error number: MY-011135; Symbol: ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES; SQLSTATE: HY000
Message: %s: cleared all nodes.
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES was added in 8.0.4.
 - Error number: MY-011136; Symbol: ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS; SQLSTATE: HY000
Message: %s: cleared %d nodes back until pos (%s, %lu).
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS was added in 8.0.4.
 - Error number: MY-011137; Symbol: ER_SEMISYNC_REPLY_MAGIC_NO_ERROR; SQLSTATE: HY000

Message: Read semi-sync reply magic number error.

`ER_SEMISYNC_REPLY_MAGIC_NO_ERROR` was added in 8.0.4.

- Error number: `MY-011138`; Symbol: `ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL`; SQLSTATE: `HY000`

Message: Read semi-sync reply length error: packet is too small.

`ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL` was added in 8.0.4.

- Error number: `MY-011139`; Symbol: `ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Read semi-sync reply binlog file length too large.

`ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE` was added in 8.0.4.

- Error number: `MY-011140`; Symbol: `ER_SEMISYNC_SERVER_REPLY`; SQLSTATE: `HY000`

Message: %s: Got reply(%s, %lu) from server %u.

`ER_SEMISYNC_SERVER_REPLY` was added in 8.0.4.

- Error number: `MY-011141`; Symbol: `ER_SEMISYNC_FUNCTION_CALLED_TWICE`; SQLSTATE: `HY000`

Message: %s called twice.

`ER_SEMISYNC_FUNCTION_CALLED_TWICE` was added in 8.0.4.

- Error number: `MY-011142`; Symbol: `ER_SEMISYNC_RPL_ENABLED_ON_MASTER`; SQLSTATE: `HY000`

Message: Semi-sync replication enabled on the master.

`ER_SEMISYNC_RPL_ENABLED_ON_MASTER` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011142`; Symbol: `ER_SEMISYNC_RPL_ENABLED_ON_SOURCE`; SQLSTATE: `HY000`

Message: Semi-sync replication enabled on the source.

`ER_SEMISYNC_RPL_ENABLED_ON_SOURCE` was added in 8.0.33.

- Error number: `MY-011143`; Symbol: `ER_SEMISYNC_MASTER_OOM`; SQLSTATE: `HY000`

Message: Cannot allocate memory to enable semi-sync on the master.

`ER_SEMISYNC_MASTER_OOM` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011143`; Symbol: `ER_SEMISYNC_SOURCE_OOM`; SQLSTATE: `HY000`

Message: Cannot allocate memory to enable semi-sync on the source.

`ER_SEMISYNC_SOURCE_OOM` was added in 8.0.33.

- Error number: `MY-011144`; Symbol: `ER_SEMISYNC_DISABLED_ON_MASTER`; SQLSTATE: `HY000`

Message: Semi-sync replication disabled on the master.

`ER_SEMISYNC_DISABLED_ON_MASTER` was added in 8.0.4, removed after 8.0.32.

-
- Error number: [MY-011144](#); Symbol: [ER_SEMISYNC_DISABLED_ON_SOURCE](#); SQLSTATE: [HY000](#)
Message: Semi-sync replication disabled on the source.
[ER_SEMISYNC_DISABLED_ON_SOURCE](#) was added in 8.0.33.
 - Error number: [MY-011145](#); Symbol: [ER_SEMISYNC_FORCED_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.
[ER_SEMISYNC_FORCED_SHUTDOWN](#) was added in 8.0.4.
 - Error number: [MY-011146](#); Symbol: [ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS](#); SQLSTATE: [HY000](#)
Message: %s: Got reply at (%s, %lu).
[ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011146](#); Symbol: [ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS](#); SQLSTATE: [HY000](#)
Message: %s: Got reply at (%s, %lu).
[ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS](#) was added in 8.0.33.
 - Error number: [MY-011147](#); Symbol: [ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS](#); SQLSTATE: [HY000](#)
Message: %s: signal all waiting threads.
[ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011147](#); Symbol: [ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS](#); SQLSTATE: [HY000](#)
Message: %s: signal all waiting threads.
[ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS](#) was added in 8.0.33.
 - Error number: [MY-011148](#); Symbol: [ER_SEMISYNC_MASTER_TRX_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: wait pos (%s, %lu), repl(%d).
[ER_SEMISYNC_MASTER_TRX_WAIT_POS](#) was added in 8.0.4, removed after 8.0.32.
 - Error number: [MY-011148](#); Symbol: [ER_SEMISYNC_SOURCE_TRX_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: wait pos (%s, %lu), repl(%d).
[ER_SEMISYNC_SOURCE_TRX_WAIT_POS](#) was added in 8.0.33.
 - Error number: [MY-011149](#); Symbol: [ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD](#); SQLSTATE: [HY000](#)
Message: %s: Binlog reply is ahead (%s, %lu).
[ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD](#) was added in 8.0.4.
 - Error number: [MY-011150](#); Symbol: [ER_SEMISYNC_MOVE_BACK_WAIT_POS](#); SQLSTATE: [HY000](#)
Message: %s: move back wait position (%s, %lu).

`ER_SEMISYNC_MOVE_BACK_WAIT_POS` was added in 8.0.4.

- Error number: `MY-011151`; Symbol: `ER_SEMISYNC_INIT_WAIT_POS`; SQLSTATE: `HY000`

Message: %s: init wait position (%s, %lu).

`ER_SEMISYNC_INIT_WAIT_POS` was added in 8.0.4.

- Error number: `MY-011152`; Symbol: `ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT`; SQLSTATE: `HY000`

Message: %s: wait %lu ms for binlog sent (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT` was added in 8.0.4.

- Error number: `MY-011153`; Symbol: `ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEOUT`; SQLSTATE: `HY000`

Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.

`ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEOUT` was added in 8.0.4.

- Error number: `MY-011154`; Symbol: `ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED`; SQLSTATE: `HY000`

Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).

`ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED` was added in 8.0.4.

- Error number: `MY-011155`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_OFF`; SQLSTATE: `HY000`

Message: Semi-sync replication switched OFF.

`ER_SEMISYNC_RPL_SWITCHED_OFF` was added in 8.0.4.

- Error number: `MY-011156`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_ON`; SQLSTATE: `HY000`

Message: Semi-sync replication switched ON at (%s, %lu).

`ER_SEMISYNC_RPL_SWITCHED_ON` was added in 8.0.4.

- Error number: `MY-011157`; Symbol: `ER_SEMISYNC_NO_SPACE_IN_THE_PKT`; SQLSTATE: `HY000`

Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.

`ER_SEMISYNC_NO_SPACE_IN_THE_PKT` was added in 8.0.4.

- Error number: `MY-011158`; Symbol: `ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO`; SQLSTATE: `HY000`

Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).

`ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO` was added in 8.0.4.

- Error number: `MY-011159`; Symbol: `ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE`; SQLSTATE: `HY000`

Message: Semi-sync failed to insert tranx_node for binlog file: %s, position: %lu.

`ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE` was added in 8.0.4.

- Error number: `MY-011160`; Symbol: `ER_SEMISYNC_TRX_SKIPPED_AT_POS`; SQLSTATE: `HY000`

Message: %s: Transaction skipped at (%s, %lu).

[ER_SEMISYNC_TRX_SKIPPED_AT_POS](#) was added in 8.0.4.

- Error number: [MY-011161](#); Symbol: [ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH](#); SQLSTATE: [HY000](#)

Message: Semi-sync master failed on `net_flush()` before waiting for replica reply.

[ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011161](#); Symbol: [ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH](#); SQLSTATE: [HY000](#)

Message: Semi-sync source failed on `net_flush()` before waiting for replica reply.

[ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH](#) was added in 8.0.33.

- Error number: [MY-011162](#); Symbol: [ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER](#); SQLSTATE: [HY000](#)

Message: The received ack is smaller than `m_greatest_ack`.

[ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER](#) was added in 8.0.4.

- Error number: [MY-011163](#); Symbol: [ER_SEMISYNC_ADD_ACK_TO_SLOT](#); SQLSTATE: [HY000](#)

Message: Add the ack into slot %u.

[ER_SEMISYNC_ADD_ACK_TO_SLOT](#) was added in 8.0.4.

- Error number: [MY-011164](#); Symbol: [ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK](#); SQLSTATE: [HY000](#)

Message: Update an existing ack in slot %u.

[ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK](#) was added in 8.0.4, removed after 8.0.32.

- Error number: [MY-011164](#); Symbol: [ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK](#); SQLSTATE: [HY000](#)

Message: Update an existing ack in slot %u.

[ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK](#) was added in 8.0.33.

- Error number: [MY-011165](#); Symbol: [ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)

Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno=%d).

[ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD](#) was added in 8.0.4.

- Error number: [MY-011166](#); Symbol: [ER_SEMISYNC_STARTING_ACK_RECEIVER_THD](#); SQLSTATE: [HY000](#)

Message: Starting ack receiver thread.

[ER_SEMISYNC_STARTING_ACK_RECEIVER_THD](#) was added in 8.0.4.

- Error number: [MY-011167](#); Symbol: [ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET](#); SQLSTATE: [HY000](#)

Message: Failed to wait on semi-sync dump sockets, error: `errno=%d`.

`ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET` was added in 8.0.4.

- Error number: `MY-011168`; Symbol: `ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD`; SQLSTATE: `HY000`

Message: Stopping ack receiver thread.

`ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD` was added in 8.0.4.

- Error number: `MY-011169`; Symbol: `ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER`; SQLSTATE: `HY000`

Message: Failed to register slave to semi-sync ACK receiver thread.

`ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011169`; Symbol: `ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER`; SQLSTATE: `HY000`

Message: Failed to register replica to semi-sync ACK receiver thread.

`ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER` was added in 8.0.33.

- Error number: `MY-011170`; Symbol: `ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE`; SQLSTATE: `HY000`

Message: Start %s binlog_dump to slave (server_id: %d), pos(%s, %lu).

`ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011170`; Symbol: `ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`

Message: Start %s binlog_dump to replica (server_id: %d), pos(%s, %lu).

`ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA` was added in 8.0.33.

- Error number: `MY-011171`; Symbol: `ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE`; SQLSTATE: `HY000`

Message: Stop %s binlog_dump to slave (server_id: %d).

`ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011171`; Symbol: `ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`

Message: Stop %s binlog_dump to replica (server_id: %d).

`ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA` was added in 8.0.33.

- Error number: `MY-011172`; Symbol: `ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED`; SQLSTATE: `HY000`

Message: unregister_trans_observer failed.

`ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED` was added in 8.0.4.

- Error number: `MY-011173`; Symbol: `ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED`; SQLSTATE: `HY000`

Message: unregister_binlog_storage_observer failed.

`ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED` was added in 8.0.4.

- Error number: `MY-011174`; Symbol: `ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED`; SQLSTATE: `HY000`

Message: `unregister_binlog_transmit_observer` failed.

`ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED` was added in 8.0.4.

- Error number: `MY-011175`; Symbol: `ER_SEMISYNC_UNREGISTERED_REPLICATOR`; SQLSTATE: `HY000`

Message: `unregister_replicator` OK.

`ER_SEMISYNC_UNREGISTERED_REPLICATOR` was added in 8.0.4.

- Error number: `MY-011176`; Symbol: `ER_SEMISYNC_SOCKET_FD_TOO_LARGE`; SQLSTATE: `HY000`

Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD_SETSIZE).

`ER_SEMISYNC_SOCKET_FD_TOO_LARGE` was added in 8.0.4.

- Error number: `MY-011177`; Symbol: `ER_SEMISYNC_SLAVE_REPLY`; SQLSTATE: `HY000`

Message: %s: reply - %d.

`ER_SEMISYNC_SLAVE_REPLY` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011177`; Symbol: `ER_SEMISYNC_REPLICA_REPLY`; SQLSTATE: `HY000`

Message: %s: reply - %d.

`ER_SEMISYNC_REPLICA_REPLY` was added in 8.0.33.

- Error number: `MY-011178`; Symbol: `ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT`; SQLSTATE: `HY000`

Message: Missing magic number for semi-sync packet, packet len: %lu.

`ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT` was added in 8.0.4.

- Error number: `MY-011179`; Symbol: `ER_SEMISYNC_SLAVE_START`; SQLSTATE: `HY000`

Message: Slave I/O thread: Start %s replication to master '%s@%s:%d' in log '%s' at position %lu.

`ER_SEMISYNC_SLAVE_START` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011179`; Symbol: `ER_SEMISYNC_REPLICA_START`; SQLSTATE: `HY000`

Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.

`ER_SEMISYNC_REPLICA_START` was added in 8.0.33.

- Error number: `MY-011180`; Symbol: `ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO`; SQLSTATE: `HY000`

Message: %s: reply (%s, %lu).

`ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011180`; Symbol: `ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO`; SQLSTATE: `HY000`

Message: %s: reply (%s, %lu).

`ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO` was added in 8.0.33.

- Error number: `MY-011181`; Symbol: `ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED`; SQLSTATE: `HY000`

Message: Semi-sync slave `net_flush()` reply failed.

`ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011181`; Symbol: `ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED`; SQLSTATE: `HY000`

Message: Semi-sync replica `net_flush()` reply failed.

`ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED` was added in 8.0.33.

- Error number: `MY-011182`; Symbol: `ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED`; SQLSTATE: `HY000`

Message: Semi-sync slave send reply failed: %s (%d).

`ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011182`; Symbol: `ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED`; SQLSTATE: `HY000`

Message: Semi-sync replica send reply failed: %s (%d).

`ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED` was added in 8.0.33.

- Error number: `MY-011183`; Symbol: `ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER`; SQLSTATE: `HY000`

Message: Execution failed on master: %s; error %d

`ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011183`; Symbol: `ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE`; SQLSTATE: `HY000`

Message: Execution failed on source: %s; error %d

`ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE` was added in 8.0.33.

- Error number: `MY-011184`; Symbol: `ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER`; SQLSTATE: `HY000`

Message: Master server does not support semi-sync, fallback to asynchronous replication

`ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011184`; Symbol: `ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE`; SQLSTATE: `HY000`

Message: Source server does not support semi-sync, fallback to asynchronous replication

`ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE` was added in 8.0.33.

- Error number: `MY-011185`; Symbol: `ER_SEMISYNC_SLAVE_SET_FAILED`; SQLSTATE: `HY000`

Message: Set '`rpl_semi_sync_replica=1`' on master failed

`ER_SEMISYNC_SLAVE_SET_FAILED` was added in 8.0.4, removed after 8.0.32.

- Error number: `MY-011185`; Symbol: `ER_SEMISYNC_REPLICA_SET_FAILED`; SQLSTATE: `HY000`

Message: Set 'rpl_semi_sync_replica=1' on source failed

`ER_SEMISYNC_REPLICA_SET_FAILED` was added in 8.0.33.

- Error number: `MY-011186`; Symbol: `ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD`; SQLSTATE: `HY000`

Message: Failed to stop ack receiver thread on my_thread_join, errno(%d).

`ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD` was added in 8.0.4.

- Error number: `MY-011187`; Symbol: `ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES`; SQLSTATE: `HY000`

Message: Failed to read the firewall tables

`ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES` was added in 8.0.4.

- Error number: `MY-011188`; Symbol: `ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES`; SQLSTATE: `HY000`

Message: Failed to register dynamic privileges

`ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES` was added in 8.0.4.

- Error number: `MY-011189`; Symbol: `ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED`; SQLSTATE: `HY000`

Message: Statement was truncated and not recorded: %s

`ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED` was added in 8.0.4.

- Error number: `MY-011190`; Symbol: `ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT`; SQLSTATE: `HY000`

Message: Statement with no text was not recorded

`ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT` was added in 8.0.4.

- Error number: `MY-011191`; Symbol: `ER_FIREWALL_SUSPICIOUS_STMT`; SQLSTATE: `HY000`

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

`ER_FIREWALL_SUSPICIOUS_STMT` was added in 8.0.4.

- Error number: `MY-011192`; Symbol: `ER_FIREWALL_ACCESS_DENIED`; SQLSTATE: `HY000`

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

`ER_FIREWALL_ACCESS_DENIED` was added in 8.0.4.

- Error number: `MY-011193`; Symbol: `ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE`; SQLSTATE: `HY000`

Message: Skipped unknown user mode '%s'

`ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE` was added in 8.0.4.

- Error number: `MY-011194`; Symbol: `ER_FIREWALL_RELOADING_CACHE`; SQLSTATE: `HY000`

Message: Reloading cache from disk

[ER_FIREWALL_RELOADING_CACHE](#) was added in 8.0.4.

- Error number: [MY-011195](#); Symbol: [ER_FIREWALL_RESET_FOR_USER](#); SQLSTATE: [HY000](#)

Message: FIREWALL RESET for '%s'

[ER_FIREWALL_RESET_FOR_USER](#) was added in 8.0.4.

- Error number: [MY-011196](#); Symbol: [ER_FIREWALL_STATUS_FLUSHED](#); SQLSTATE: [HY000](#)

Message: Counters are reset to zero

[ER_FIREWALL_STATUS_FLUSHED](#) was added in 8.0.4.

- Error number: [MY-011197](#); Symbol: [ER_KEYRING_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_KEYRING_LOGGER_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011198](#); Symbol: [ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED](#); SQLSTATE: [HY000](#)

Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.

[ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED](#) was added in 8.0.4.

- Error number: [MY-011199](#); Symbol: [ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST](#); SQLSTATE: [HY000](#)

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

[ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST](#) was added in 8.0.4.

- Error number: [MY-011200](#); Symbol: [ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES](#); SQLSTATE: [HY000](#)

Message: Cannot set audit_log_policy simultaneously with either audit_log_connection_policy or audit_log_statement_policy, setting audit_log_connection_policy and audit_log_statement_policy based on audit_log_policy.

[ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES](#) was added in 8.0.4.

- Error number: [MY-011201](#); Symbol: [ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED](#); SQLSTATE: [HY000](#)

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

[ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED](#) was added in 8.0.4.

- Error number: [MY-011202](#); Symbol: [ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR](#); SQLSTATE: [HY000](#)

Message: Could not access '%s' directory.

[ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR](#) was added in 8.0.4.

- Error number: [MY-011203](#); Symbol: [ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED](#); SQLSTATE: [HY000](#)

Message: Could not rename file from '%s' to '%s'.

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED` was added in 8.0.4.

- Error number: `MY-011204`; Symbol: `ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: File '%s' should not exist. It may be incomplete. The server crashed.

`ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS` was added in 8.0.4.

- Error number: `MY-011205`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

`ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY` was added in 8.0.4.

- Error number: `MY-011206`; Symbol: `ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED`; SQLSTATE: `HY000`

Message: Incomplete file renamed from '%s' to '%s'.

`ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED` was added in 8.0.4.

- Error number: `MY-011207`; Symbol: `ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE`; SQLSTATE: `HY000`

Message: Error writing file '%s' (errno: %d - %s).

`ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE` was added in 8.0.4.

- Error number: `MY-011208`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION`; SQLSTATE: `HY000`

Message: Could not initialize audit log file encryption.

`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION` was added in 8.0.4.

- Error number: `MY-011209`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION`; SQLSTATE: `HY000`

Message: Could not initialize audit log file compression.

`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION` was added in 8.0.4.

- Error number: `MY-011210`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE`; SQLSTATE: `HY000`

Message: Could not create '%s' file for audit logging.

`ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE` was added in 8.0.4.

- Error number: `MY-011211`; Symbol: `ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH`; SQLSTATE: `HY000`

Message: Audit log file (%s) must be manually renamed before `audit_log_flush` is set to true.

`ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH` was added in 8.0.4.

- Error number: `MY-011212`; Symbol: `ER_AUDIT_LOG_FILTER_RESULT_MSG`; SQLSTATE: `HY000`

Message: %s

[ER_AUDIT_LOG_FILTER_RESULT_MSG](#) was added in 8.0.4.

- Error number: [MY-011213](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON event. Event not accessible.

[ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE](#) was added in 8.0.4.

- Error number: [MY-011214](#); Symbol: [ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

[ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL](#) was added in 8.0.4.

- Error number: [MY-011215](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open JSON file for reading. Reading next file if exists.

[ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE](#) was added in 8.0.4.

- Error number: [MY-011216](#); Symbol: [ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: JSON file parsing error. Reading next file if exists

[ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR](#) was added in 8.0.4.

- Error number: [MY-011217](#); Symbol: [ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT](#); SQLSTATE: [HY000](#)

Message: Invalid column count in the '%s.%s' table.

[ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-011218](#); Symbol: [ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION](#); SQLSTATE: [HY000](#)

Message: Invalid column definition of the '%s.%s' table.

[ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION](#) was added in 8.0.4, removed after 8.0.25.

- Error number: [MY-011219](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS](#); SQLSTATE: [HY000](#)

Message: Could not store field of the %s table.

[ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS](#) was added in 8.0.4.

- Error number: [MY-011220](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not update %s table.

[ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE](#) was added in 8.0.4.

- Error number: [MY-011221](#); Symbol: [ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not insert into %s table.

`ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE` was added in 8.0.4.

- Error number: `MY-011222`; Symbol:
`ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE`; SQLSTATE: `HY000`

Message: Could not delete from %s table.

`ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE` was added in 8.0.4.

- Error number: `MY-011223`; Symbol:
`ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ`; SQLSTATE: `HY000`

Message: Could not initialize %s table for reading.

`ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ` was added in 8.0.4.

- Error number: `MY-011224`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE`; SQLSTATE: `HY000`

Message: Could not read %s table.

`ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE` was added in 8.0.4.

- Error number: `MY-011225`; Symbol:
`ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING`; SQLSTATE: `HY000`

Message: Could not close %s table reading.

`ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING` was added in 8.0.4.

- Error number: `MY-011226`; Symbol:
`ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Both user and host columns of %s table cannot be empty.

`ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY` was added in 8.0.4.

- Error number: `MY-011227`; Symbol:
`ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Filtername column of %s table cannot be empty.

`ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY` was added in 8.0.4.

- Error number: `MY-011228`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED`; SQLSTATE: `HY000`

Message: Dictionary file not specified

`ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED` was added in 8.0.4.

- Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; SQLSTATE: `HY000`

Message: Dictionary file not loaded

`ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED` was added in 8.0.4.

- Error number: `MY-011230`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_TOO_BIG`; SQLSTATE: `HY000`

Message: Dictionary file size exceeded MAX_DICTIONARY_FILE_LENGTH, not loaded

ER_VALIDATE_PWD_DICT_FILE_TOO_BIG was added in 8.0.4.

- Error number: MY-011231; Symbol: ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE; SQLSTATE: HY000

Message: Exception while reading the dictionary file

ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE was added in 8.0.4.

- Error number: MY-011232; Symbol: ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX; SQLSTATE: HY000

Message: Can't retrieve the %s from the security context

ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX was added in 8.0.4.

- Error number: MY-011233; Symbol: ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX; SQLSTATE: HY000

Message: Can't retrieve the security context

ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX was added in 8.0.4.

- Error number: MY-011234; Symbol: ER_VALIDATE_PWD_LENGTH_CHANGED; SQLSTATE: HY000

Message: Effective value of validate_password_length is changed. New value is %d

ER_VALIDATE_PWD_LENGTH_CHANGED was added in 8.0.4.

- Error number: MY-011235; Symbol: ER_REWRITER_QUERY_ERROR_MSG; SQLSTATE: HY000

Message: %s

ER_REWRITER_QUERY_ERROR_MSG was added in 8.0.4.

- Error number: MY-011236; Symbol: ER_REWRITER_QUERY_FAILED; SQLSTATE: HY000

Message: Rewritten query failed to parse:%s

ER_REWRITER_QUERY_FAILED was added in 8.0.4.

- Error number: MY-011237; Symbol: ER_XPLUGIN_STARTUP_FAILED; SQLSTATE: HY000

Message: Startup failed with error "%s"

ER_XPLUGIN_STARTUP_FAILED was added in 8.0.4.

- Error number: MY-011238; Symbol: ER_XPLUGIN_SERVER_EXITING; SQLSTATE: HY000

Message: Exiting

ER_XPLUGIN_SERVER_EXITING was added in 8.0.4, removed after 8.0.12.

- Error number: MY-011239; Symbol: ER_XPLUGIN_SERVER_EXITED; SQLSTATE: HY000

Message: Exit done

ER_XPLUGIN_SERVER_EXITED was added in 8.0.4, removed after 8.0.12.

- Error number: MY-011240; Symbol: ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER; SQLSTATE: HY000

Message: Using SSL configuration from MySQL Server

[ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER](#) was added in 8.0.4.

- Error number: [MY-011241](#); Symbol: [ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX](#); SQLSTATE: [HY000](#)

Message: Using SSL configuration from Mysqlx Plugin

[ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX](#) was added in 8.0.4.

- Error number: [MY-011242](#); Symbol: [ER_XPLUGIN_FAILED_TO_USE_SSL_CONF](#); SQLSTATE: [HY000](#)

Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

[ER_XPLUGIN_FAILED_TO_USE_SSL_CONF](#) was added in 8.0.4.

- Error number: [MY-011243](#); Symbol: [ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Using %s for TLS connections

[ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION](#) was added in 8.0.4.

- Error number: [MY-011244](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN](#); SQLSTATE: [HY000](#)

Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation

[ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN](#) was added in 8.0.4.

- Error number: [MY-011245](#); Symbol: [ER_XPLUGIN_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_XPLUGIN_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011246](#); Symbol: [ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING](#); SQLSTATE: [HY000](#)

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

[ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING](#) was added in 8.0.4.

- Error number: [MY-011247](#); Symbol: [ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH](#); SQLSTATE: [HY000](#)

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem

[ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH](#) was added in 8.0.4.

- Error number: [MY-011248](#); Symbol: [ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption

[ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL](#) was added in 8.0.4.

- Error number: [MY-011249](#); Symbol: [ER_SHA_PWD_RSA_KEY_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: RSA key cipher length of %u is too long. Max value is %u

[ER_SHA_PWD_RSA_KEY_TOO_LONG](#) was added in 8.0.4.

- Error number: [MY-011250](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables

[ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES](#) was added in 8.0.4.

- Error number: [MY-011251](#); Symbol: [ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table

[ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE](#) was added in 8.0.4.

- Error number: [MY-011252](#); Symbol: [ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011253](#); Symbol: [ER_CONN_CONTROL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_CONN_CONTROL_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011254](#); Symbol: [ER_GRP_RPL_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_GRP_RPL_ERROR_MSG](#) was added in 8.0.4.

- Error number: [MY-011255](#); Symbol: [ER_SHA_PWD_SALT_FOR_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Password salt for user '%s' is corrupt

[ER_SHA_PWD_SALT_FOR_USER_CORRUPT](#) was added in 8.0.4.

- Error number: [MY-011256](#); Symbol: [ER_SYS_VAR_COMPONENT_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for component system variable '%s'.

[ER_SYS_VAR_COMPONENT_OOM](#) was added in 8.0.4.

- Error number: [MY-011257](#); Symbol: [ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: variable %s of component %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag.

[ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY](#) was added in 8.0.4.

- Error number: [MY-011258](#); Symbol: [ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE](#); SQLSTATE: [HY000](#)

Message: Unknown variable type code 0x%x in component '%s'.

`ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE` was added in 8.0.4.

- Error number: `MY-011259`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS`; SQLSTATE: `HY000`

Message: Parsing options for variable '%s' failed.

`ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS` was added in 8.0.4.

- Error number: `MY-011260`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT`; SQLSTATE: `HY000`

Message: Setting persistent options for component variable '%s' failed.

`ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT` was added in 8.0.4.

- Error number: `MY-011261`; Symbol: `ER_COMPONENT_FILTER_CONFUSED`; SQLSTATE: `HY000`

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

`ER_COMPONENT_FILTER_CONFUSED` was added in 8.0.4.

- Error number: `MY-011262`; Symbol: `ER_STOP_SLAVE_IO_THREAD_DISK_SPACE`; SQLSTATE: `HY000`

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

`ER_STOP_SLAVE_IO_THREAD_DISK_SPACE` was added in 8.0.2, removed after 8.0.32.

- Error number: `MY-011262`; Symbol: `ER_STOP_REPLICA_IO_THREAD_DISK_SPACE`; SQLSTATE: `HY000`

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

`ER_STOP_REPLICA_IO_THREAD_DISK_SPACE` was added in 8.0.33.

- Error number: `MY-011263`; Symbol: `ER_LOG_FILE_CANNOT_OPEN`; SQLSTATE: `HY000`

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

`ER_LOG_FILE_CANNOT_OPEN` was added in 8.0.2.

- Error number: `MY-011268`; Symbol: `ER_PERSIST_OPTION_STATUS`; SQLSTATE: `HY000`

Message: Configuring persisted options failed: "%s".

`ER_PERSIST_OPTION_STATUS` was added in 8.0.11.

- Error number: `MY-011269`; Symbol: `ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS`; SQLSTATE: `HY000`

Message: The storage engine '%s' does not provide dynamic table statistics

`ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS` was added in 8.0.11.

- Error number: `MY-011272`; Symbol: `ER_SSL_FIPS_MODE_ERROR`; SQLSTATE: `HY000`

Message: SSL fips mode error: %s

`ER_SSL_FIPS_MODE_ERROR` was added in 8.0.11.

- Error number: `MY-011273`; Symbol: `ER_CONN_INIT_CONNECT_IGNORED`; SQLSTATE: `HY000`
Message: init_connect variable is ignored for user: %s host: %s due to expired password.

`ER_CONN_INIT_CONNECT_IGNORED` was added in 8.0.11.

- Error number: `MY-011275`; Symbol: `ER_REWRITER_OOM`; SQLSTATE: `HY000`
Message: Out of memory.

`ER_REWRITER_OOM` was added in 8.0.11.

- Error number: `MY-011276`; Symbol: `ER_REWRITER_TABLE_MALFORMED_ERROR`; SQLSTATE: `HY000`
Message: Wrong column count or names when loading rules.

`ER_REWRITER_TABLE_MALFORMED_ERROR` was added in 8.0.11.

- Error number: `MY-011277`; Symbol: `ER_REWRITER_LOAD_FAILED`; SQLSTATE: `HY000`
Message: Some rules failed to load.

`ER_REWRITER_LOAD_FAILED` was added in 8.0.11.

- Error number: `MY-011278`; Symbol: `ER_REWRITER_READ_FAILED`; SQLSTATE: `HY000`
Message: Got error from storage engine while refreshing rewrite rules.

`ER_REWRITER_READ_FAILED` was added in 8.0.11.

- Error number: `MY-011279`; Symbol: `ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED`; SQLSTATE: `HY000`
Message: Failed to initialize Connection_event_coordinator

`ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011280`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED`; SQLSTATE: `HY000`
Message: Failed to update connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED` was added in 8.0.11.

- Error number: `MY-011281`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED`; SQLSTATE: `HY000`
Message: Failed to reset connection delay triggered stats

`ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED` was added in 8.0.11.

- Error number: `MY-011282`; Symbol: `ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE`; SQLSTATE: `HY000`
Message: Unexpected option type for connection delay.

`ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE` was added in 8.0.11.

- Error number: `MY-011283`; Symbol: `ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize Connection_delay_action

ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED was added in 8.0.11.

- Error number: MY-011284; Symbol: ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY; SQLSTATE: HY000

Message: Could not set %s delay for connection delay.

ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY was added in 8.0.11.

- Error number: MY-011285; Symbol: ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH; SQLSTATE: HY000

Message: Failed to update connection delay hash for account : %s

ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH was added in 8.0.11.

- Error number: MY-011286; Symbol: ER_XPLUGIN_FORCE_STOP_CLIENT; SQLSTATE: HY000

Message: %s: Force stopping client because exception occurred: %s

ER_XPLUGIN_FORCE_STOP_CLIENT was added in 8.0.11.

- Error number: MY-011287; Symbol: ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED; SQLSTATE: HY000

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED was added in 8.0.11.

- Error number: MY-011288; Symbol: ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED; SQLSTATE: HY000

Message: Error allocating Buffer_page: %s

ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED was added in 8.0.11.

- Error number: MY-011289; Symbol: ER_XPLUGIN_DETECTED_HANGING_CLIENTS; SQLSTATE: HY000

Message: Detected %u hanging client(s)

ER_XPLUGIN_DETECTED_HANGING_CLIENTS was added in 8.0.11.

- Error number: MY-011290; Symbol: ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT; SQLSTATE: HY000

Message: Error accepting client

ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT was added in 8.0.11.

- Error number: MY-011291; Symbol: ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT; SQLSTATE: HY000

Message: Internal error scheduling client for execution

ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT was added in 8.0.11.

- Error number: MY-011292; Symbol: ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES; SQLSTATE: HY000

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

`ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES` was added in 8.0.11.

- Error number: `MY-011293`; Symbol: `ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED`; SQLSTATE: `HY000`

Message: `srv_session_init_thread` returned error

`ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED` was added in 8.0.11.

- Error number: `MY-011294`; Symbol: `ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT`; SQLSTATE: `HY000`

Message: Unable to use user `mysql.session` account when connecting the server for internal plugin requests.

`ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT` was added in 8.0.11.

- Error number: `MY-011295`; Symbol: `ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION`; SQLSTATE: `HY000`

Message: For more information, please see the X Plugin User Account section in the MySQL documentation

`ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION` was added in 8.0.11.

- Error number: `MY-011296`; Symbol: `ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD`; SQLSTATE: `HY000`

Message: `%s`: Unexpected exception dispatching command: `%s`

`ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD` was added in 8.0.11.

- Error number: `MY-011297`; Symbol: `ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER`; SQLSTATE: `HY000`

Message: Exception in post: `%s`

`ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER` was added in 8.0.11.

- Error number: `MY-011298`; Symbol: `ER_XPLUGIN_TASK_SCHEDULING_FAILED`; SQLSTATE: `HY000`

Message: Internal error scheduling task

`ER_XPLUGIN_TASK_SCHEDULING_FAILED` was added in 8.0.11.

- Error number: `MY-011299`; Symbol: `ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP`; SQLSTATE: `HY000`

Message: Exception in event loop: "`%s`": `%s`

`ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP` was added in 8.0.11.

- Error number: `MY-011300`; Symbol: `ER_XPLUGIN_LISTENER_SETUP_FAILED`; SQLSTATE: `HY000`

Message: Setup of `%s` failed, `%s`

`ER_XPLUGIN_LISTENER_SETUP_FAILED` was added in 8.0.11.

- Error number: `MY-011301`; Symbol: `ER_XPLUING_NET_STARTUP_FAILED`; SQLSTATE: `HY000`

Message: `%s`

`ER_XPLUING_NET_STARTUP_FAILED` was added in 8.0.11.

- Error number: `MY-011302`; Symbol: `ER_XPLUGIN_FAILED_AT_SSL_CONF`; SQLSTATE: `HY000`
Message: Failed at SSL configuration: "%s"

`ER_XPLUGIN_FAILED_AT_SSL_CONF` was added in 8.0.11.

- Error number: `MY-011303`; Symbol: `ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED`; SQLSTATE: `HY000`

Message: Error during SSL handshake for client connection (%i)

`ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011304`; Symbol: `ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED`; SQLSTATE: `HY000`

Message: %s: Error during SSL handshake

`ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011305`; Symbol: `ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN`; SQLSTATE: `HY000`

Message: %s: Error creating session for connection from %s

`ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN` was added in 8.0.11.

- Error number: `MY-011306`; Symbol: `ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION`; SQLSTATE: `HY000`

Message: %s: Error initializing session for connection: %s

`ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION` was added in 8.0.11.

- Error number: `MY-011307`; Symbol: `ER_XPLUGIN_MESSAGE_TOO_LONG`; SQLSTATE: `HY000`

Message: %s: Message of size %u received, exceeding the limit of %i

`ER_XPLUGIN_MESSAGE_TOO_LONG` was added in 8.0.11.

- Error number: `MY-011308`; Symbol: `ER_XPLUGIN_UNINITIALIZED_MESSAGE`; SQLSTATE: `HY000`

Message: Message is not properly initialized: %s

`ER_XPLUGIN_UNINITIALIZED_MESSAGE` was added in 8.0.11.

- Error number: `MY-011309`; Symbol: `ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS`; SQLSTATE: `HY000`

Message: Unable to set minimal number of workers to %u; actual value is %i

`ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS` was added in 8.0.11.

- Error number: `MY-011310`; Symbol: `ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION`; SQLSTATE: `HY000`

Message: Unable to accept connection, disconnecting client

`ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION` was added in 8.0.11.

-
- Error number: `MY-011311`; Symbol: `ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED`; SQLSTATE: `HY000`

Message: All I/O interfaces are disabled, X Protocol won't be accessible

`ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED` was added in 8.0.11.
 - Error number: `MY-011312`; Symbol: `ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT`; SQLSTATE: `HY000`

Message: %s: Invalid message %i received during client initialization

`ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011313`; Symbol: `ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN`; SQLSTATE: `HY000`

Message: %s: closing client because of shutdown (state: %i)

`ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011314`; Symbol: `ER_XPLUGIN_ERROR_READING_SOCKET`; SQLSTATE: `HY000`

Message: %s: Error reading from socket %s (%i)

`ER_XPLUGIN_ERROR_READING_SOCKET` was added in 8.0.11.
 - Error number: `MY-011315`; Symbol: `ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY`; SQLSTATE: `HY000`

Message: %s: peer disconnected while reading message body

`ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY` was added in 8.0.11.
 - Error number: `MY-011316`; Symbol: `ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION`; SQLSTATE: `HY000`

Message: client_id:%s - %s while reading from socket, closing connection

`ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION` was added in 8.0.11.
 - Error number: `MY-011317`; Symbol: `ER_XPLUGIN_INVALID_AUTH_METHOD`; SQLSTATE: `HY000`

Message: %s.%u: Invalid authentication method %s

`ER_XPLUGIN_INVALID_AUTH_METHOD` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011318`; Symbol: `ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION`; SQLSTATE: `HY000`

Message: %s: Unexpected message of type %i received during authentication

`ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011319`; Symbol: `ER_XPLUGIN_ERROR_WRITING_TO_CLIENT`; SQLSTATE: `HY000`

Message: Error writing to client: %s (%i)

`ER_XPLUGIN_ERROR_WRITING_TO_CLIENT` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011320`; Symbol: `ER_XPLUGIN_SCHEDULER_STARTED`; SQLSTATE: `HY000`

Message: Scheduler "%s" started.

[ER_XPLUGIN_SCHEDULER_STARTED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011321](#); Symbol: [ER_XPLUGIN_SCHEDULER_STOPPED](#); SQLSTATE: [HY000](#)

Message: Scheduler "%s" stopped.

[ER_XPLUGIN_SCHEDULER_STOPPED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011322](#); Symbol: [ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR](#); SQLSTATE: [HY000](#)

Message: Please see the MySQL documentation for '%s' system variables to fix the error

[ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011323](#); Symbol: [ER_XPLUGIN_LISTENER_STATUS_MSG](#); SQLSTATE: [HY000](#)

Message: X Plugin ready for connections. %s

[ER_XPLUGIN_LISTENER_STATUS_MSG](#) was added in 8.0.11.

- Error number: [MY-011324](#); Symbol: [ER_XPLUGIN_RETRYING_BIND_ON_PORT](#); SQLSTATE: [HY000](#)

Message: Retrying `bind()` on TCP/IP port %i

[ER_XPLUGIN_RETRYING_BIND_ON_PORT](#) was added in 8.0.11.

- Error number: [MY-011325](#); Symbol: [ER_XPLUGIN_SHUTDOWN_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: Shutdown triggered by mysqld abort flag

[ER_XPLUGIN_SHUTDOWN_TRIGGERED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011326](#); Symbol: [ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS](#); SQLSTATE: [HY000](#)

Message: Using %s account for authentication which has all required permissions

[ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011327](#); Symbol: [ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS](#); SQLSTATE: [HY000](#)

Message: Using existing %s account for authentication. Incomplete grants will be fixed

[ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS](#) was added in 8.0.11.

- Error number: [MY-011328](#); Symbol: [ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Server starts handling incoming connections

[ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011329](#); Symbol: [ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Stopped handling incoming connections

`ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011330`; Symbol: `ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION`; SQLSTATE: `HY000`

Message: %s: Could not interrupt client session

`ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011331`; Symbol: `ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED`; SQLSTATE: `HY000`

Message: %s: release triggered by timeout in state:%i

`ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011332`; Symbol: `ER_XPLUGIN_IPv6_AVAILABLE`; SQLSTATE: `HY000`

Message: IPv6 is available

`ER_XPLUGIN_IPv6_AVAILABLE` was added in 8.0.11.

- Error number: `MY-011333`; Symbol: `ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED`; SQLSTATE: `HY000`

Message: UNIX socket not configured

`ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011334`; Symbol: `ER_XPLUGIN_CLIENT_KILL_MSG`; SQLSTATE: `HY000`

Message: Kill client: %i %s

`ER_XPLUGIN_CLIENT_KILL_MSG` was added in 8.0.11.

- Error number: `MY-011335`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Could not get security context for session

`ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX` was added in 8.0.11.

- Error number: `MY-011336`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT`; SQLSTATE: `HY000`

Message: Unable to switch security context to root

`ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011337`; Symbol: `ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION`; SQLSTATE: `HY000`

Message: Error closing SQL session

`ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION` was added in 8.0.11.

- Error number: `MY-011338`; Symbol: `ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing admin command %s: %s

`ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD` was added in 8.0.11.

- Error number: `MY-011339`; Symbol: `ER_XPLUGIN_EMPTY_ADMIN_CMD`; SQLSTATE: `HY000`

Message: Error executing empty admin command

`ER_XPLUGIN_EMPTY_ADMIN_CMD` was added in 8.0.11.

- Error number: `MY-011340`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_SYS_VAR`; SQLSTATE: `HY000`

Message: Unable to retrieve system variable `'%s'`

`ER_XPLUGIN_FAILED_TO_GET_SYS_VAR` was added in 8.0.11.

- Error number: `MY-011341`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT`; SQLSTATE: `HY000`

Message: Unable to get creation stmt for collection `'%s'`; query result size: `%lu`

`ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT` was added in 8.0.11.

- Error number: `MY-011342`; Symbol: `ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO`; SQLSTATE: `HY000`

Message: Unable to get engine info for collection `'%s'`; creation stmt: `%s`

`ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO` was added in 8.0.11.

- Error number: `MY-011343`; Symbol: `ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA`; SQLSTATE: `HY000`

Message: Error getting result data: `%s`

`ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011344`; Symbol: `ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD`; SQLSTATE: `HY000`

Message: Capability expired password failed with error: `%s`

`ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD` was added in 8.0.11, removed after 8.0.12.

- Error number: `MY-011345`; Symbol: `ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG`; SQLSTATE: `HY000`

Message: Failed to set `SO_REUSEADDR` flag (error: `%d`).

`ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG` was added in 8.0.11.

- Error number: `MY-011346`; Symbol: `ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION`; SQLSTATE: `HY000`

Message: Could not open internal MySQL session

`ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION` was added in 8.0.11.

- Error number: `MY-011347`; Symbol: `ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT`; SQLSTATE: `HY000`

Message: Unable to switch context to user `%s`

`ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT` was added in 8.0.11.

-
- Error number: MY-011348; Symbol: ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF; SQLSTATE: HY000

Message: Can't unregister '%s' user defined function

ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF was added in 8.0.11.

- Error number: MY-011349; Symbol: ER_XPLUGIN_GET_PEER_ADDRESS_FAILED; SQLSTATE: HY000

Message: %s: get peer address failed, can't resolve IP to hostname

ER_XPLUGIN_GET_PEER_ADDRESS_FAILED was added in 8.0.11, removed after 8.0.12.

- Error number: MY-011350; Symbol: ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED; SQLSTATE: HY000

Message: Capability client interactive failed with error: %s

ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED was added in 8.0.11, removed after 8.0.12.

- Error number: MY-011351; Symbol: ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG; SQLSTATE: HY000

Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG was added in 8.0.11.

- Error number: MY-011352; Symbol: ER_KEYRING_INVALID_KEY_TYPE; SQLSTATE: HY000

Message: Invalid key type

ER_KEYRING_INVALID_KEY_TYPE was added in 8.0.11.

- Error number: MY-011353; Symbol: ER_KEYRING_INVALID_KEY_LENGTH; SQLSTATE: HY000

Message: Invalid key length for given block cipher

ER_KEYRING_INVALID_KEY_LENGTH was added in 8.0.11.

- Error number: MY-011354; Symbol: ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR; SQLSTATE: HY000

Message: Could not create keyring directory. The keyring_file will stay unusable until correct path to the keyring directory gets provided

ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR was added in 8.0.11.

- Error number: MY-011355; Symbol: ER_KEYRING_FILE_INIT_FAILED; SQLSTATE: HY000

Message: keyring_file initialization failure. Please check if the keyring_file_data points to readable keyring file or keyring file can be created in the specified location. The keyring_file will stay unusable until correct path to the keyring file gets provided

ER_KEYRING_FILE_INIT_FAILED was added in 8.0.11.

-
- Error number: MY-011356; Symbol: ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT; SQLSTATE: HY000
Message: keyring_file initialization failure due to internal exception inside the plugin.
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT was added in 8.0.11.
 - Error number: MY-011357; Symbol: ER_KEYRING_FAILED_TO_GENERATE_KEY; SQLSTATE: HY000
Message: Failed to generate a key due to internal exception inside keyring_file plugin
ER_KEYRING_FAILED_TO_GENERATE_KEY was added in 8.0.11.
 - Error number: MY-011358; Symbol: ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY; SQLSTATE: HY000
Message: Error while %s key: invalid key_type
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY was added in 8.0.11.
 - Error number: MY-011359; Symbol: ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID; SQLSTATE: HY000
Message: Error while %s key: key_id cannot be empty
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID was added in 8.0.11.
 - Error number: MY-011360; Symbol: ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR; SQLSTATE: HY000
Message: Failed to %s due to internal exception inside %s plugin
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR was added in 8.0.11.
 - Error number: MY-011361; Symbol: ER_KEYRING_INCORRECT_FILE; SQLSTATE: HY000
Message: Incorrect Keyring file
ER_KEYRING_INCORRECT_FILE was added in 8.0.11.
 - Error number: MY-011362; Symbol: ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE; SQLSTATE: HY000
Message: Found malformed keyring backup file - removing it
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE was added in 8.0.11.
 - Error number: MY-011363; Symbol: ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE; SQLSTATE: HY000
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE was added in 8.0.11.
 - Error number: MY-011364; Symbol: ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE; SQLSTATE: HY000
Message: Error while flushing in-memory keyring into keyring file
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE was added in 8.0.11.
 - Error number: MY-011365; Symbol: ER_KEYRING_FAILED_TO_GET_FILE_STAT; SQLSTATE: HY000

Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s

`ER_KEYRING_FAILED_TO_GET_FILE_STAT` was added in 8.0.11.

- Error number: `MY-011366`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_FILE`; SQLSTATE: `HY000`

Message: Could not remove file %s OS returned this error: %s

`ER_KEYRING_FAILED_TO_REMOVE_FILE` was added in 8.0.11.

- Error number: `MY-011367`; Symbol: `ER_KEYRING_FAILED_TO_TRUNCATE_FILE`; SQLSTATE: `HY000`

Message: Could not truncate file %s. OS returned this error: %s

`ER_KEYRING_FAILED_TO_TRUNCATE_FILE` was added in 8.0.11.

- Error number: `MY-011368`; Symbol: `ER_KEYRING_UNKNOWN_ERROR`; SQLSTATE: `HY000`

Message: Unknown error %d

`ER_KEYRING_UNKNOWN_ERROR` was added in 8.0.11.

- Error number: `MY-011369`; Symbol: `ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA`; SQLSTATE: `HY000`

Message: keyring_file_data cannot be set to new value as the keyring file cannot be created/ accessed in the provided path

`ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA` was added in 8.0.11.

- Error number: `MY-011370`; Symbol: `ER_KEYRING_FILE_IO_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_KEYRING_FILE_IO_ERROR` was added in 8.0.11.

- Error number: `MY-011371`; Symbol: `ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT`; SQLSTATE: `HY000`

Message: Error while loading keyring content. The keyring might be malformed

`ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT` was added in 8.0.11.

- Error number: `MY-011372`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring

`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING` was added in 8.0.11.

- Error number: `MY-011373`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP`; SQLSTATE: `HY000`

Message: Could not flush keys to keyring's backup

`ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP` was added in 8.0.11.

- Error number: `MY-011374`; Symbol: `ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`

Message: Error while fetching key: key_id cannot be empty

`ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID` was added in 8.0.11.

- Error number: `MY-011375`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID`; SQLSTATE: `HY000`

Message: Error while removing key: key_id cannot be empty

`ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID` was added in 8.0.11.

- Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`

Message: For keyring_okv to be initialized, please point keyring_okv_conf_dir variable to a directory with Oracle Key Vault configuration file and ssl materials

`ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED` was added in 8.0.11.

- Error number: `MY-011377`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure. Please check that the keyring_okv_conf_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF` was added in 8.0.11.

- Error number: `MY-011378`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: keyring_okv initialization failure due to internal exception inside the plugin

`ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011379`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_TYPE`; SQLSTATE: `HY000`

Message: Invalid key type

`ER_KEYRING_OKV_INVALID_KEY_TYPE` was added in 8.0.11.

- Error number: `MY-011380`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`

Message: Invalid key length for given block cipher

`ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER` was added in 8.0.11.

- Error number: `MY-011381`; Symbol: `ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring_okv plugin

`ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

-
- Error number: MY-011382; Symbol: ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY; SQLSTATE: HY000

Message: Could not find entry for server in configuration file %s

ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY was added in 8.0.11.
 - Error number: MY-011383; Symbol: ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY; SQLSTATE: HY000

Message: Could not find entry for standby server in configuration file %s

ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY was added in 8.0.11.
 - Error number: MY-011384; Symbol: ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE; SQLSTATE: HY000

Message: Could not parse the %s file provided

ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE was added in 8.0.11.
 - Error number: MY-011385; Symbol: ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID; SQLSTATE: HY000

Message: Could not load keys' uids from the OKV server

ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID was added in 8.0.11.
 - Error number: MY-011386; Symbol: ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER; SQLSTATE: HY000

Message: Could not initialize ssl layer

ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER was added in 8.0.11.
 - Error number: MY-011387; Symbol: ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT; SQLSTATE: HY000

Message: Could not initialize OKV client

ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT was added in 8.0.11.
 - Error number: MY-011388; Symbol: ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED; SQLSTATE: HY000

Message: Could not connect to the OKV server

ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED was added in 8.0.11.
 - Error number: MY-011389; Symbol: ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY; SQLSTATE: HY000

Message: Could not remove the key

ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY was added in 8.0.11.
 - Error number: MY-011390; Symbol: ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE; SQLSTATE: HY000

Message: Could not add attribute, attribute_name=%s attribute value=%s

ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE was added in 8.0.11.
-

-
- Error number: MY-011391; Symbol: ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY; SQLSTATE: HY000

Message: Could not generate the key.

ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY was added in 8.0.11.

- Error number: MY-011392; Symbol: ER_KEYRING_OKV_FAILED_TO_STORE_KEY; SQLSTATE: HY000

Message: Could not store the key.

ER_KEYRING_OKV_FAILED_TO_STORE_KEY was added in 8.0.11.

- Error number: MY-011393; Symbol: ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS; SQLSTATE: HY000

Message: Could not activate the key.

ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS was added in 8.0.11.

- Error number: MY-011394; Symbol: ER_KEYRING_OKV_FAILED_TO_FETCH_KEY; SQLSTATE: HY000

Message: Could not fetch generated key

ER_KEYRING_OKV_FAILED_TO_FETCH_KEY was added in 8.0.11.

- Error number: MY-011395; Symbol: ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY; SQLSTATE: HY000

Message: Could not store/generate the key - failed to set key attribute x-key-ready

ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY was added in 8.0.11.

- Error number: MY-011396; Symbol: ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE; SQLSTATE: HY000

Message: Could not retrieve key signature from custom attributes

ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE was added in 8.0.11.

- Error number: MY-011397; Symbol: ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY; SQLSTATE: HY000

Message: Could not retrieve key from OKV

ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY was added in 8.0.11.

- Error number: MY-011398; Symbol: ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE; SQLSTATE: HY000

Message: Error loading trust store

ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE was added in 8.0.11.

- Error number: MY-011399; Symbol: ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE; SQLSTATE: HY000

Message: Error setting the certificate file.

ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE was added in 8.0.11.

-
- Error number: MY-011400; Symbol: ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE; SQLSTATE: HY000

Message: Error setting the key file.

ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE was added in 8.0.11.

- Error number: MY-011401; Symbol: ER_KEYRING_OKV_KEY_MISMATCH; SQLSTATE: HY000

Message: Private key does not match the certificate public key

ER_KEYRING_OKV_KEY_MISMATCH was added in 8.0.11.

- Error number: MY-011402; Symbol: ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE; SQLSTATE: HY000

Message: Incorrect Keyring file

ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE was added in 8.0.11.

- Error number: MY-011403; Symbol: ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED; SQLSTATE: HY000

Message: Keyring_encrypted_file decryption failed. Please verify --keyring-encrypted-file-password option value.

ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED was added in 8.0.11.

- Error number: MY-011404; Symbol: ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE; SQLSTATE: HY000

Message: Found malformed keyring backup file - removing it

ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE was added in 8.0.11.

- Error number: MY-011405; Symbol: ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING; SQLSTATE: HY000

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING was added in 8.0.11.

- Error number: MY-011406; Symbol: ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING; SQLSTATE: HY000

Message: Error while flushing in-memory keyring into keyring file

ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING was added in 8.0.11.

- Error number: MY-011407; Symbol: ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED; SQLSTATE: HY000

Message: Keyring_encrypted_file encryption failed. Please verify --keyring-encrypted-file-password option value.

ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED was added in 8.0.11.

-
- Error number: [MY-011408](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR](#); SQLSTATE: [HY000](#)

Message: `keyring_encrypted_file_data` cannot be set to new value as the keyring file cannot be created/accessed in the provided path

[ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR](#) was added in 8.0.11.

- Error number: [MY-011409](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR](#); SQLSTATE: [HY000](#)

Message: Could not create keyring directory The `keyring_encrypted_file` will stay unusable until correct path to the keyring directory gets provided

[ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR](#) was added in 8.0.11.

- Error number: [MY-011410](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID](#); SQLSTATE: [HY000](#)

Message: The `keyring_encrypted_file_password` must be set to a valid value.

[ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID](#) was added in 8.0.11.

- Error number: [MY-011411](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Too long `keyring_encrypted_file_password` value.

[ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG](#) was added in 8.0.11.

- Error number: [MY-011412](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE](#); SQLSTATE: [HY000](#)

Message: `keyring_encrypted_file` initialization failure. Please check if the `keyring_encrypted_file_data` points to readable keyring file or keyring file can be created in the specified location or password to decrypt keyring file is correct.

[ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE](#) was added in 8.0.11.

- Error number: [MY-011413](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: `keyring_encrypted_file` initialization failure due to internal exception inside the plugin

[ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.

- Error number: [MY-011414](#); Symbol: [ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside `keyring_encrypted_file` plugin

[ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.

- Error number: [MY-011415](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID](#); SQLSTATE: [HY000](#)

Message: `keyring_aws_cmk_id` cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID` was added in 8.0.11.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: keyring_aws_region cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

`ER_KEYRING_AWS_FAILED_TO_SET_REGION` was added in 8.0.11.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key id from keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key from keyring_aws configuration file: %s. OS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE` was added in 8.0.11.

- Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to keyring aws configuration file cannot be empty

`ER_KEYRING_AWS_INVALID_CONF_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to keyring_aws storage file cannot be empty.

`ER_KEYRING_AWS_INVALID_DATA_FILE_PATH` was added in 8.0.11.

- Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`

Message: Unable to create/access keyring directory.

`ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR` was added in 8.0.11.

-
- Error number: [MY-011423](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to create/access keyring_aws storage file. Please check if keyring_aws_data_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.

[ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE](#) was added in 8.0.11.
 - Error number: [MY-011424](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:

[ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR](#) was added in 8.0.11.
 - Error number: [MY-011425](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE](#); SQLSTATE: [HY000](#)

Message: Could not access keyring_aws storage file in the path provided. Please check if the keyring_aws directory can be accessed by MySQL Server

[ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE](#) was added in 8.0.11.
 - Error number: [MY-011426](#); Symbol: [ER_KEYRING_AWS_CMK_ID_NOT_SET](#); SQLSTATE: [HY000](#)

Message: keyring_aws_cmk_id has to be set

[ER_KEYRING_AWS_CMK_ID_NOT_SET](#) was added in 8.0.11.
 - Error number: [MY-011427](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE](#); SQLSTATE: [HY000](#)

Message: Could not get AWS KMS credentials from the configuration file

[ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE](#) was added in 8.0.11.
 - Error number: [MY-011428](#); Symbol: [ER_KEYRING_AWS_INIT_FAILURE](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure.

[ER_KEYRING_AWS_INIT_FAILURE](#) was added in 8.0.11.
 - Error number: [MY-011429](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: keyring_aws initialization failure due to internal exception inside the plugin

[ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR](#) was added in 8.0.11.
 - Error number: [MY-011430](#); Symbol: [ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER](#); SQLSTATE: [HY000](#)

Message: Invalid key length for given block cipher

[ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER](#) was added in 8.0.11.
 - Error number: [MY-011431](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to generate a key due to internal exception inside keyring_file plugin

`ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR` was added in 8.0.11.

- Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`

Message: Incorrect Keyring file

`ER_KEYRING_AWS_INCORRECT_FILE` was added in 8.0.11.

- Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Found malformed keyring backup file - removing it

`ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

`ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE` was added in 8.0.11.

- Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`

Message: Error while flushing in-memory keyring into keyring file

`ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE` was added in 8.0.11.

- Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`

Message: Wrong region

`ER_KEYRING_AWS_INCORRECT_REGION` was added in 8.0.11.

- Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`

Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS` was added in 8.0.11.

- Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`

Message: Could not generate a new key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY` was added in 8.0.11.

- Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not encrypt key. AWS KMS returned this error: %s

`ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY` was added in 8.0.11.

- Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not re-encrypt key. AWS KMS returned this error: %s

[ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY](#) was added in 8.0.11.

- Error number: [MY-011441](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY](#); SQLSTATE: [HY000](#)

Message: Could not decrypt key. AWS KMS returned this error: %s

[ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY](#) was added in 8.0.11.

- Error number: [MY-011442](#); Symbol: [ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK](#); SQLSTATE: [HY000](#)

Message: Could not rotate the CMK. AWS KMS returned this error: %s

[ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK](#) was added in 8.0.11.

- Error number: [MY-011443](#); Symbol: [ER_GRP_RPL_GTID_ALREADY_USED](#); SQLSTATE: [HY000](#)

Message: The requested GTID '%s:%ld' was already used, the transaction will rollback.

[ER_GRP_RPL_GTID_ALREADY_USED](#) was added in 8.0.11.

- Error number: [MY-011444](#); Symbol: [ER_GRP_RPL_APPLIER_THD_KILLED](#); SQLSTATE: [HY000](#)

Message: The group replication applier thread was killed.

[ER_GRP_RPL_APPLIER_THD_KILLED](#) was added in 8.0.11.

- Error number: [MY-011445](#); Symbol: [ER_GRP_RPL_EVENT_HANDLING_ERROR](#); SQLSTATE: [HY000](#)

Message: Error at event handling! Got error: %d.

[ER_GRP_RPL_EVENT_HANDLING_ERROR](#) was added in 8.0.11.

- Error number: [MY-011446](#); Symbol: [ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO](#); SQLSTATE: [HY000](#)

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

[ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO](#) was added in 8.0.11.

- Error number: [MY-011447](#); Symbol: [ER_GRP_RPL_CERTIFICATE_SIZE_ERROR](#); SQLSTATE: [HY000](#)

Message: An error occurred when trying to reduce the Certification information size for transmission.

[ER_GRP_RPL_CERTIFICATE_SIZE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011448](#); Symbol: [ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline applier cache!

[ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011449](#); Symbol: [ER_GRP_RPL_UNBLOCK_WAITING_THD](#); SQLSTATE: [HY000](#)

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

`ER_GRP_RPL_UNBLOCK_WAITING_THD` was added in 8.0.11.

- Error number: `MY-011450`; Symbol: `ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED`; SQLSTATE: `HY000`

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

`ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED` was added in 8.0.11.

- Error number: `MY-011451`; Symbol: `ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED`; SQLSTATE: `HY000`

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

`ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED` was added in 8.0.11.

- Error number: `MY-011452`; Symbol: `ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR`; SQLSTATE: `HY000`

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

`ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR` was added in 8.0.11.

- Error number: `MY-011453`; Symbol: `ER_GRP_RPL_ERROR_STOPPING_CHANNELS`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. %s

`ER_GRP_RPL_ERROR_STOPPING_CHANNELS` was added in 8.0.11.

- Error number: `MY-011454`; Symbol: `ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG`; SQLSTATE: `HY000`

Message: Error sending single primary message informing that primary did apply relay logs.

`ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG` was added in 8.0.11.

- Error number: `MY-011455`; Symbol: `ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR`; SQLSTATE: `HY000`

Message: Error updating transaction snapshot version after transaction being positively certified.

`ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR` was added in 8.0.11.

- Error number: `MY-011456`; Symbol: `ER_GRP_RPL_SIDNO_FETCH_ERROR`; SQLSTATE: `HY000`

Message: Error fetching transaction sidno after transaction being positively certified.

`ER_GRP_RPL_SIDNO_FETCH_ERROR` was added in 8.0.11.

- Error number: `MY-011457`; Symbol: `ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED`; SQLSTATE: `HY000`

Message: Broadcast of committed transactions message failed.

`ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED` was added in 8.0.11.

- Error number: `MY-011458`; Symbol: `ER_GRP_RPL_GROUP_NAME_PARSE_ERROR`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_group_name during the Certification module initialization.

[ER_GRP_RPL_GROUP_NAME_PARSE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011459](#); Symbol: [ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to add the group_sid in the group_gtid_sid_map during the Certification module initialization.

[ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR](#) was added in 8.0.11.

- Error number: [MY-011460](#); Symbol: [ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating group_gtid_executed GTID set during the Certification module initialization.

[ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR](#) was added in 8.0.11.

- Error number: [MY-011461](#); Symbol: [ER_GRP_RPL_DONOR_TRANS_INFO_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.

[ER_GRP_RPL_DONOR_TRANS_INFO_ERROR](#) was added in 8.0.11.

- Error number: [MY-011462](#); Symbol: [ER_GRP_RPL_SERVER_CONN_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when establishing a server connection during the Certification module initialization.

[ER_GRP_RPL_SERVER_CONN_ERROR](#) was added in 8.0.11.

- Error number: [MY-011463](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.

[ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET](#) was added in 8.0.11.

- Error number: [MY-011464](#); Symbol: [ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the server GTID EXECUTED set to the group_gtid_execute during the Certification module initialization.

[ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR](#) was added in 8.0.11.

- Error number: [MY-011465](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.

[ER_GRP_RPL_ERROR_FETCHING_GTID_SET](#) was added in 8.0.11.

-
- Error number: `MY-011466`; Symbol: `ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error while adding the member retrieved set to the group_gtid_executed during the Certification module initialization.

`ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR` was added in 8.0.11.
 - Error number: `MY-011467`; Symbol: `ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE`; SQLSTATE: `HY000`

Message: Error during Certification module initialization.

`ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE` was added in 8.0.11.
 - Error number: `MY-011468`; Symbol: `ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR`; SQLSTATE: `HY000`

Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance_schema.replication_group_member_stats.last_conflict_free_transaction.

`ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR` was added in 8.0.11.
 - Error number: `MY-011469`; Symbol: `ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR`; SQLSTATE: `HY000`

Message: Error updating transaction snapshot version reference for internal storage.

`ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR` was added in 8.0.11.
 - Error number: `MY-011470`; Symbol: `ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR`; SQLSTATE: `HY000`

Message: Error fetching transaction sidno while adding to the group_gtid_executed set.

`ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR` was added in 8.0.11.
 - Error number: `MY-011471`; Symbol: `ER_GRP_RPL_ERROR_VERIFYING_SIDNO`; SQLSTATE: `HY000`

Message: Error while ensuring the sidno be present in the group_gtid_executed.

`ER_GRP_RPL_ERROR_VERIFYING_SIDNO` was added in 8.0.11.
 - Error number: `MY-011472`; Symbol: `ER_GRP_RPL_CANT_GENERATE_GTID`; SQLSTATE: `HY000`

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group_replication_group_name.

`ER_GRP_RPL_CANT_GENERATE_GTID` was added in 8.0.11.
 - Error number: `MY-011473`; Symbol: `ER_GRP_RPL_INVALID_GTID_SET`; SQLSTATE: `HY000`

Message: Invalid stable transactions set.

`ER_GRP_RPL_INVALID_GTID_SET` was added in 8.0.11.
 - Error number: `MY-011474`; Symbol: `ER_GRP_RPL_UPDATE_GTID_SET_ERROR`; SQLSTATE: `HY000`

Message: Error updating stable transactions set.

`ER_GRP_RPL_UPDATE_GTID_SET_ERROR` was added in 8.0.11.

-
- Error number: `MY-011475`; Symbol: `ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS`; SQLSTATE: `HY000`

Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.

`ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011476`; Symbol: `ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED`; SQLSTATE: `HY000`

Message: Skipping the computation of the `Transactions_committed_all_members` field as an older instance of this computation is still ongoing.

`ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED` was added in 8.0.11, removed after 8.0.26.

- Error number: `MY-011477`; Symbol: `ER_GRP_RPL_NULL_PACKET`; SQLSTATE: `HY000`

Message: Null packet on certifier's queue.

`ER_GRP_RPL_NULL_PACKET` was added in 8.0.11.

- Error number: `MY-011478`; Symbol: `ER_GRP_RPL_CANT_READ_GTID`; SQLSTATE: `HY000`

Message: Error reading GTIDs from the message.

`ER_GRP_RPL_CANT_READ_GTID` was added in 8.0.11.

- Error number: `MY-011479`; Symbol: `ER_GRP_RPL_PROCESS_GTID_SET_ERROR`; SQLSTATE: `HY000`

Message: Error processing stable transactions set.

`ER_GRP_RPL_PROCESS_GTID_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011480`; Symbol: `ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR`; SQLSTATE: `HY000`

Message: Error processing intersection of stable transactions set.

`ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011481`; Symbol: `ER_GRP_RPL_SET_STABLE_TRANS_ERROR`; SQLSTATE: `HY000`

Message: Error setting stable transactions set.

`ER_GRP_RPL_SET_STABLE_TRANS_ERROR` was added in 8.0.11.

- Error number: `MY-011482`; Symbol: `ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED`; SQLSTATE: `HY000`

Message: Error reading group `gtid_extracted` from the `View_change_log_event`.

`ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED` was added in 8.0.11.

- Error number: `MY-011483`; Symbol: `ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM`; SQLSTATE: `HY000`

Message: Error reading the write set item '%s' from the `View_change_log_event`.

`ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM` was added in 8.0.11.

-
- Error number: [MY-011484](#); Symbol: [ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during certification_info initialization.

[ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#) was added in 8.0.11.
 - Error number: [MY-011485](#); Symbol: [ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Primary had applied all relay logs, disabled conflict detection.

[ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#) was added in 8.0.11.
 - Error number: [MY-011486](#); Symbol: [ER_GRP_RPL_MSG_DISCARDED](#); SQLSTATE: [HY000](#)

Message: Message received while the plugin is not ready, message discarded.

[ER_GRP_RPL_MSG_DISCARDED](#) was added in 8.0.11.
 - Error number: [MY-011487](#); Symbol: [ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#); SQLSTATE: [HY000](#)

Message: Message received without a proper group replication applier.

[ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#) was added in 8.0.11.
 - Error number: [MY-011488](#); Symbol: [ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing message in Certifier.

[ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#) was added in 8.0.11.
 - Error number: [MY-011489](#); Symbol: [ER_GRP_RPL_SRV_NOT_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was not declared online since it is on status %s.

[ER_GRP_RPL_SRV_NOT_ONLINE](#) was added in 8.0.11.
 - Error number: [MY-011490](#); Symbol: [ER_GRP_RPL_SRV_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was declared online within the replication group.

[ER_GRP_RPL_SRV_ONLINE](#) was added in 8.0.11.
 - Error number: [MY-011491](#); Symbol: [ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#); SQLSTATE: [HY000](#)

Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.

[ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#) was added in 8.0.11.
 - Error number: [MY-011492](#); Symbol: [ER_GRP_RPL_MEM_ONLINE](#); SQLSTATE: [HY000](#)

Message: The member with address %s:%u was declared online within the replication group.

[ER_GRP_RPL_MEM_ONLINE](#) was added in 8.0.11.
 - Error number: [MY-011493](#); Symbol: [ER_GRP_RPL_MEM_UNREACHABLE](#); SQLSTATE: [HY000](#)

Message: Member with address %s:%u has become unreachable.

`ER_GRP_RPL_MEM_UNREACHABLE` was added in 8.0.11.

- Error number: `MY-011494`; Symbol: `ER_GRP_RPL_MEM_REACHABLE`; SQLSTATE: `HY000`

Message: Member with address %s:%u is reachable again.

`ER_GRP_RPL_MEM_REACHABLE` was added in 8.0.11.

- Error number: `MY-011495`; Symbol: `ER_GRP_RPL_SRV_BLOCKED`; SQLSTATE: `HY000`

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.

`ER_GRP_RPL_SRV_BLOCKED` was added in 8.0.11.

- Error number: `MY-011496`; Symbol: `ER_GRP_RPL_SRV_BLOCKED_FOR_SECS`; SQLSTATE: `HY000`

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.

`ER_GRP_RPL_SRV_BLOCKED_FOR_SECS` was added in 8.0.11.

- Error number: `MY-011497`; Symbol: `ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED`; SQLSTATE: `HY000`

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.

`ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED` was added in 8.0.11.

- Error number: `MY-011498`; Symbol: `ER_GRP_RPL_MEMBER_CONTACT_RESTORED`; SQLSTATE: `HY000`

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

`ER_GRP_RPL_MEMBER_CONTACT_RESTORED` was added in 8.0.11.

- Error number: `MY-011499`; Symbol: `ER_GRP_RPL_MEMBER_REMOVED`; SQLSTATE: `HY000`

Message: Members removed from the group: %s

`ER_GRP_RPL_MEMBER_REMOVED` was added in 8.0.11.

- Error number: `MY-011500`; Symbol: `ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`

Message: Primary server with address %s left the group. Electing new Primary.

`ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP` was added in 8.0.11.

- Error number: `MY-011501`; Symbol: `ER_GRP_RPL_MEMBER_ADDED`; SQLSTATE: `HY000`

Message: Members joined the group: %s

`ER_GRP_RPL_MEMBER_ADDED` was added in 8.0.11.

- Error number: `MY-011502`; Symbol: `ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR`; SQLSTATE: `HY000`

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

[ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR](#) was added in 8.0.11.

- Error number: [MY-011503](#); Symbol: [ER_GRP_RPL_MEMBER_CHANGE](#); SQLSTATE: [HY000](#)

Message: Group membership changed to %s on view %s.

[ER_GRP_RPL_MEMBER_CHANGE](#) was added in 8.0.11.

- Error number: [MY-011504](#); Symbol: [ER_GRP_RPL_MEMBER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Group membership changed: This member has left the group.

[ER_GRP_RPL_MEMBER_LEFT_GRP](#) was added in 8.0.11.

- Error number: [MY-011505](#); Symbol: [ER_GRP_RPL_MEMBER_EXPELLED](#); SQLSTATE: [HY000](#)

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

[ER_GRP_RPL_MEMBER_EXPELLED](#) was added in 8.0.11.

- Error number: [MY-011506](#); Symbol: [ER_GRP_RPL_SESSION_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to open session to (re)set read only mode. Skipping.

[ER_GRP_RPL_SESSION_OPEN_FAILED](#) was added in 8.0.11.

- Error number: [MY-011507](#); Symbol: [ER_GRP_RPL_NEW_PRIMARY_ELECTED](#); SQLSTATE: [HY000](#)

Message: A new primary with address %s:%u was elected. %s

[ER_GRP_RPL_NEW_PRIMARY_ELECTED](#) was added in 8.0.11.

- Error number: [MY-011508](#); Symbol: [ER_GRP_RPL_DISABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to disable super read only flag. Try to disable it manually

[ER_GRP_RPL_DISABLE_READ_ONLY_FAILED](#) was added in 8.0.11.

- Error number: [MY-011509](#); Symbol: [ER_GRP_RPL_ENABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to set super read only flag. Try to set it manually.

[ER_GRP_RPL_ENABLE_READ_ONLY_FAILED](#) was added in 8.0.11.

- Error number: [MY-011510](#); Symbol: [ER_GRP_RPL_SRV_PRIMARY_MEM](#); SQLSTATE: [HY000](#)

Message: This server is working as primary member.

[ER_GRP_RPL_SRV_PRIMARY_MEM](#) was added in 8.0.11.

- Error number: [MY-011511](#); Symbol: [ER_GRP_RPL_SRV_SECONDARY_MEM](#); SQLSTATE: [HY000](#)

Message: This server is working as secondary member with primary member address %s:%u.

[ER_GRP_RPL_SRV_SECONDARY_MEM](#) was added in 8.0.11.

-
- Error number: MY-011512; Symbol: ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM; SQLSTATE: HY000

Message: Unable to set any member as primary. No suitable candidate.

ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM was added in 8.0.11.

- Error number: MY-011513; Symbol: ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR; SQLSTATE: HY000

Message: Error when activating super_read_only mode on start. The member will now exit the group.

ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR was added in 8.0.11.

- Error number: MY-011514; Symbol: ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE; SQLSTATE: HY000

Message: Group contains %lu members which is greater than group_replication_auto_increment_increment value of %lu. This can lead to a higher transactional abort rate.

ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE was added in 8.0.11.

- Error number: MY-011515; Symbol: ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM; SQLSTATE: HY000

Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.

ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM was added in 8.0.11.

- Error number: MY-011516; Symbol: ER_GRP_RPL_MEMBER_ALREADY_EXISTS; SQLSTATE: HY000

Message: There is already a member with server_uuid %s. The member will now exit the group.

ER_GRP_RPL_MEMBER_ALREADY_EXISTS was added in 8.0.11.

- Error number: MY-011517; Symbol: ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR; SQLSTATE: HY000

Message: Error when extracting information for group change. Operations and checks made to group joiners may be incomplete.

ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR was added in 8.0.11, removed after 8.0.26.

- Error number: MY-011518; Symbol: ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR; SQLSTATE: HY000

Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.

ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR was added in 8.0.11.

- Error number: MY-011519; Symbol: ER_GRP_RPL_GTID_SET_EXTRACT_ERROR; SQLSTATE: HY000

Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.

ER_GRP_RPL_GTID_SET_EXTRACT_ERROR was added in 8.0.11.

-
- Error number: [MY-011520](#); Symbol: [ER_GRP_RPL_START_FAILED](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

[ER_GRP_RPL_START_FAILED](#) was added in 8.0.11.

- Error number: [MY-011521](#); Symbol: [ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is incompatible with the group.

[ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#) was added in 8.0.11.

- Error number: [MY-011522](#); Symbol: [ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#); SQLSTATE: [HY000](#)

Message: The member contains transactions not present in the group. The member will now exit the group.

[ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#) was added in 8.0.11.

- Error number: [MY-011523](#); Symbol: [ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.

[ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011524](#); Symbol: [ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: Member version is lower than some group member, but since option 'group_replication_allow_local_lower_version_join' is enabled, member will be allowed to join.

[ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011525](#); Symbol: [ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing local GTID sets when comparing this member transactions against the group.

[ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#) was added in 8.0.11.

- Error number: [MY-011526](#); Symbol: [ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s

[ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#) was added in 8.0.11.

- Error number: [MY-011527](#); Symbol: [ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_gtid_assignment_block_size option value '%llu' different from the group '%llu'. The member will now exit the group.

[ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#) was added in 8.0.11.

-
- Error number: MY-011528; Symbol:

ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP; SQLSTATE: HY000

Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.

ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP was added in 8.0.11.

- Error number: MY-011529; Symbol:

ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG; SQLSTATE: HY000

Message: The member configuration is not compatible with the group configuration. Variables such as group_replication_single_primary_mode or group_replication_enforce_update_everywhere_checks must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).

ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG was added in 8.0.11.

- Error number: MY-011530; Symbol: ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR; SQLSTATE: HY000

Message: Error stopping all replication channels while server was leaving the group. %s

ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR was added in 8.0.11.

- Error number: MY-011531; Symbol: ER_GRP_RPL_PURGE_APPLIER_LOGS; SQLSTATE: HY000

Message: Detected previous RESET SOURCE invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.

ER_GRP_RPL_PURGE_APPLIER_LOGS was added in 8.0.11.

- Error number: MY-011532; Symbol: ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR; SQLSTATE: HY000

Message: Unknown error occurred while resetting applier's module logs.

ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR was added in 8.0.11.

- Error number: MY-011533; Symbol: ER_GRP_RPL_APPLIER_THD_SETUP_ERROR; SQLSTATE: HY000

Message: Failed to setup the group replication applier thread.

ER_GRP_RPL_APPLIER_THD_SETUP_ERROR was added in 8.0.11.

- Error number: MY-011534; Symbol: ER_GRP_RPL_APPLIER_THD_START_ERROR; SQLSTATE: HY000

Message: Error while starting the group replication applier thread

ER_GRP_RPL_APPLIER_THD_START_ERROR was added in 8.0.11.

- Error number: MY-011535; Symbol: ER_GRP_RPL_APPLIER_THD_STOP_ERROR; SQLSTATE: HY000

Message: Failed to stop the group replication applier thread.

ER_GRP_RPL_APPLIER_THD_STOP_ERROR was added in 8.0.11.

-
- Error number: [MY-011536](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction data containing required transaction info for applier

[ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011537](#); Symbol: [ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-011537](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN](#) was added in 8.0.33.
 - Error number: [MY-011538](#); Symbol: [ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER_GRP_RPL_SLAVE_IO_THD_ON_SECONDARY_MEMBER](#) was added in 8.0.11.
 - Error number: [MY-011539](#); Symbol: [ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-011539](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

[ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN](#) was added in 8.0.33.
 - Error number: [MY-011540](#); Symbol: [ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-011540](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

[ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER](#) was added in 8.0.33.

-
- Error number: [MY-011541](#); Symbol: [ER_GRP_RPL_NEEDS_INNODB_TABLE](#); SQLSTATE: [HY000](#)
Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.
[ER_GRP_RPL_NEEDS_INNODB_TABLE](#) was added in 8.0.11.
 - Error number: [MY-011542](#); Symbol: [ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#); SQLSTATE: [HY000](#)
Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.
[ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#) was added in 8.0.11.
 - Error number: [MY-011543](#); Symbol: [ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.
[ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED](#) was added in 8.0.11.
 - Error number: [MY-011544](#); Symbol: [ER_GRP_RPL_AUTO_INC_RESET](#); SQLSTATE: [HY000](#)
Message: group_replication_auto_increment_increment is reset to %lu
[ER_GRP_RPL_AUTO_INC_RESET](#) was added in 8.0.11.
 - Error number: [MY-011545](#); Symbol: [ER_GRP_RPL_AUTO_INC_OFFSET_RESET](#); SQLSTATE: [HY000](#)
Message: auto_increment_offset is reset to %lu
[ER_GRP_RPL_AUTO_INC_OFFSET_RESET](#) was added in 8.0.11.
 - Error number: [MY-011546](#); Symbol: [ER_GRP_RPL_AUTO_INC_SET](#); SQLSTATE: [HY000](#)
Message: group_replication_auto_increment_increment is set to %lu
[ER_GRP_RPL_AUTO_INC_SET](#) was added in 8.0.11.
 - Error number: [MY-011547](#); Symbol: [ER_GRP_RPL_AUTO_INC_OFFSET_SET](#); SQLSTATE: [HY000](#)
Message: auto_increment_offset is set to %lu
[ER_GRP_RPL_AUTO_INC_OFFSET_SET](#) was added in 8.0.11.
 - Error number: [MY-011548](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch transaction context containing required transaction info for certification
[ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011549](#); Symbol: [ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch Format_description_log_event containing required server info for applier
[ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011550](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Transaction_context_log_event containing required transaction info for certification

ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED was added in 8.0.11.

- Error number: MY-011551; Symbol: ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED; SQLSTATE: HY000

Message: Failed to read snapshot version from transaction context event required for certification

ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED was added in 8.0.11.

- Error number: MY-011552; Symbol: ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED; SQLSTATE: HY000

Message: Failed to fetch Gtid_log_event containing required transaction info for certification

ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED was added in 8.0.11.

- Error number: MY-011553; Symbol: ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED; SQLSTATE: HY000

Message: Unable to update certification result on server side, thread_id: %lu

ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED was added in 8.0.11.

- Error number: MY-011554; Symbol: ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for local transactions

ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED was added in 8.0.11.

- Error number: MY-011555; Symbol: ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group_gtid_executed set when no gtid was provided for local transactions

ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED was added in 8.0.11.

- Error number: MY-011556; Symbol: ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED; SQLSTATE: HY000

Message: Failed to notify certification outcome

ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED was added in 8.0.11.

- Error number: MY-011557; Symbol: ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for remote transactions

ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED was added in 8.0.11.

- Error number: MY-011558; Symbol: ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group_gtid_executed set when gtid was not provided for remote transactions

`ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED` was added in 8.0.11.

- Error number: `MY-011559`; Symbol: `ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch View_change_log_event containing required info for certification

`ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011560`; Symbol: `ER_GRP_RPL_CONTACT_WITH_SRV_FAILED`; SQLSTATE: `HY000`

Message: Error when contacting the server to ensure the proper logging of a group change in the binlog

`ER_GRP_RPL_CONTACT_WITH_SRV_FAILED` was added in 8.0.11, removed after 8.0.31.

- Error number: `MY-011561`; Symbol: `ER_GRP_RPL_SRV_WAIT_TIME_OUT`; SQLSTATE: `HY000`

Message: Timeout when waiting for the server to execute local transactions in order assure the group change proper logging

`ER_GRP_RPL_SRV_WAIT_TIME_OUT` was added in 8.0.11, removed after 8.0.31.

- Error number: `MY-011562`; Symbol: `ER_GRP_RPL_FETCH_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Log_event containing required server info for applier

`ER_GRP_RPL_FETCH_LOG_EVENT_FAILED` was added in 8.0.11.

- Error number: `MY-011563`; Symbol: `ER_GRP_RPL_START_GRP_RPL_FAILED`; SQLSTATE: `HY000`

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `--initialize`, `--initialize-insecure` or `--upgrade=MINIMAL` on a server upgrade.

`ER_GRP_RPL_START_GRP_RPL_FAILED` was added in 8.0.11.

- Error number: `MY-011564`; Symbol: `ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations

`ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL` was added in 8.0.11.

- Error number: `MY-011565`; Symbol: `ER_GRP_RPL_SUPER_READ_ON`; SQLSTATE: `HY000`

Message: Setting super_read_only=ON.

`ER_GRP_RPL_SUPER_READ_ON` was added in 8.0.11.

- Error number: `MY-011566`; Symbol: `ER_GRP_RPL_SUPER_READ_OFF`; SQLSTATE: `HY000`

Message: Setting super_read_only=OFF.

`ER_GRP_RPL_SUPER_READ_OFF` was added in 8.0.11.

- Error number: `MY-011567`; Symbol: `ER_GRP_RPL_KILLED_SESSION_ID`; SQLSTATE: `HY000`

Message: killed session id: %d status: %d

`ER_GRP_RPL_KILLED_SESSION_ID` was added in 8.0.11.

-
- Error number: `MY-011568`; Symbol: `ER_GRP_RPL_KILLED_FAILED_ID`; SQLSTATE: `HY000`
Message: killed failed id: %d failed: %d
`ER_GRP_RPL_KILLED_FAILED_ID` was added in 8.0.11.
 - Error number: `MY-011569`; Symbol: `ER_GRP_RPL_INTERNAL_QUERY`; SQLSTATE: `HY000`
Message: Internal query: %s result in error. Error number: %ld
`ER_GRP_RPL_INTERNAL_QUERY` was added in 8.0.11.
 - Error number: `MY-011570`; Symbol: `ER_GRP_RPL_COPY_FROM_EMPTY_STRING`; SQLSTATE: `HY000`
Message: Error copying from empty string
`ER_GRP_RPL_COPY_FROM_EMPTY_STRING` was added in 8.0.11.
 - Error number: `MY-011571`; Symbol: `ER_GRP_RPL_QUERY_FAIL`; SQLSTATE: `HY000`
Message: Query execution resulted in failure. errno: %d
`ER_GRP_RPL_QUERY_FAIL` was added in 8.0.11.
 - Error number: `MY-011572`; Symbol: `ER_GRP_RPL_CREATE_SESSION_UNABLE`; SQLSTATE: `HY000`
Message: Unable to create a session for executing the queries on the server
`ER_GRP_RPL_CREATE_SESSION_UNABLE` was added in 8.0.11.
 - Error number: `MY-011573`; Symbol: `ER_GRP_RPL_MEMBER_NOT_FOUND`; SQLSTATE: `HY000`
Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection
`ER_GRP_RPL_MEMBER_NOT_FOUND` was added in 8.0.11.
 - Error number: `MY-011574`; Symbol: `ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED`; SQLSTATE: `HY000`
Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.
`ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED` was added in 8.0.11.
 - Error number: `MY-011575`; Symbol: `ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY`; SQLSTATE: `HY000`
Message: All donors left. Aborting group replication incremental recovery.
`ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY` was added in 8.0.11.
 - Error number: `MY-011576`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR`; SQLSTATE: `HY000`
Message: Establishing group recovery connection with a possible donor. Attempt %d/%d
`ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR` was added in 8.0.11.
 - Error number: `MY-011577`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR`; SQLSTATE: `HY000`

Message: Retrying group recovery connection with another donor. Attempt %d/%d

[ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR](#) was added in 8.0.11.

- Error number: [MY-011578](#); Symbol: [ER_GRP_RPL_NO_VALID_DONOR](#); SQLSTATE: [HY000](#)

Message: No valid donors exist in the group, retrying

[ER_GRP_RPL_NO_VALID_DONOR](#) was added in 8.0.11.

- Error number: [MY-011579](#); Symbol: [ER_GRP_RPL_CONFIG_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when configuring the asynchronous recovery channel connection to the donor.

[ER_GRP_RPL_CONFIG_RECOVERY](#) was added in 8.0.11.

- Error number: [MY-011580](#); Symbol: [ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR](#); SQLSTATE: [HY000](#)

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

[ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR](#) was added in 8.0.11.

- Error number: [MY-011581](#); Symbol: [ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

[ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL](#) was added in 8.0.11.

- Error number: [MY-011582](#); Symbol: [ER_GRP_RPL_DONOR_SERVER_CONN](#); SQLSTATE: [HY000](#)

Message: There was an error when connecting to the donor server. Please check that group_replication_recovery channel credentials and all MEMBER_HOST column values of performance_schema.replication_group_members table are correct and DNS resolvable.

[ER_GRP_RPL_DONOR_SERVER_CONN](#) was added in 8.0.11.

- Error number: [MY-011583](#); Symbol: [ER_GRP_RPL_CHECK_STATUS_TABLE](#); SQLSTATE: [HY000](#)

Message: For details please check performance_schema.replication_connection_status table and error log messages of Replica I/O for channel group_replication_recovery.

[ER_GRP_RPL_CHECK_STATUS_TABLE](#) was added in 8.0.11.

- Error number: [MY-011584](#); Symbol: [ER_GRP_RPL_STARTING_GRP_REC](#); SQLSTATE: [HY000](#)

Message: Error while starting the group replication incremental recovery receiver/applier threads

[ER_GRP_RPL_STARTING_GRP_REC](#) was added in 8.0.11.

- Error number: [MY-011585](#); Symbol: [ER_GRP_RPL_DONOR_CONN_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Terminating existing group replication donor connection and purging the corresponding logs.

[ER_GRP_RPL_DONOR_CONN_TERMINATION](#) was added in 8.0.11.

- Error number: [MY-011586](#); Symbol: [ER_GRP_RPL_STOPPING_GRP_REC](#); SQLSTATE: [HY000](#)

Message: Error when stopping the group replication incremental recovery's donor connection

`ER_GRP_RPL_STOPPING_GRP_REC` was added in 8.0.11.

- Error number: `MY-011587`; Symbol: `ER_GRP_RPL_PURGE_REC`; SQLSTATE: `HY000`

Message: Error when purging the group replication recovery's relay logs

`ER_GRP_RPL_PURGE_REC` was added in 8.0.11.

- Error number: `MY-011588`; Symbol:
`ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER`; SQLSTATE: `HY000`

Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.

`ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER` was added in 8.0.11.

- Error number: `MY-011589`; Symbol:
`ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER`; SQLSTATE: `HY000`

Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.

`ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER` was added in 8.0.11.

- Error number: `MY-011590`; Symbol:
`ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT`; SQLSTATE: `HY000`

Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

`ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT` was added in 8.0.11.

- Error number: `MY-011591`; Symbol:
`ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011592`; Symbol:
`ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

`ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION` was added in 8.0.11.

- Error number: `MY-011593`; Symbol:
`ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH`; SQLSTATE: `HY000`

Message: No memory to generate write identification hash

`ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH` was added in 8.0.11.

-
- Error number: [MY-011594](#); Symbol: [ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED](#); SQLSTATE: [HY000](#)

Message: Base 64 encoding of the write identification hash failed

[ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011595](#); Symbol: [ER_GRP_RPL_INVALID_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Binlog format should be ROW for Group Replication

[ER_GRP_RPL_INVALID_BINLOG_FORMAT](#) was added in 8.0.11.
 - Error number: [MY-011596](#); Symbol: [ER_GRP_RPL_BINLOG_CHECKSUM_SET](#); SQLSTATE: [HY000](#)

Message: binlog_checksum should be NONE for Group Replication

[ER_GRP_RPL_BINLOG_CHECKSUM_SET](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-011597](#); Symbol: [ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET](#); SQLSTATE: [HY000](#)

Message: A transaction_write_set_extraction algorithm should be selected when running Group Replication

[ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET](#) was added in 8.0.11.
 - Error number: [MY-011598](#); Symbol: [ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION](#); SQLSTATE: [HY000](#)

Message: Transaction isolation level (tx_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication

[ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION](#) was added in 8.0.11.
 - Error number: [MY-011599](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is stopping.

[ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING](#) was added in 8.0.11.
 - Error number: [MY-011600](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.

[ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING](#) was added in 8.0.11.
 - Error number: [MY-011601](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin

[ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE](#) was added in 8.0.11.

-
- Error number: `MY-011602`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin

`ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE` was added in 8.0.11.
 - Error number: `MY-011603`; Symbol: `ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION`; SQLSTATE: `HY000`

Message: We can only use one cache type at a time on session %u

`ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION` was added in 8.0.11.
 - Error number: `MY-011604`; Symbol: `ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ`; SQLSTATE: `HY000`

Message: Failed to reinit binlog cache log for read on session %u

`ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ` was added in 8.0.11.
 - Error number: `MY-011605`; Symbol: `ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT`; SQLSTATE: `HY000`

Message: Failed to create the context of the current transaction on session %u

`ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT` was added in 8.0.11.
 - Error number: `MY-011606`; Symbol: `ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET`; SQLSTATE: `HY000`

Message: Failed to extract the set of items written during the execution of the current transaction on session %u

`ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET` was added in 8.0.11.
 - Error number: `MY-011607`; Symbol: `ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET`; SQLSTATE: `HY000`

Message: Failed to gather the set of items written during the execution of the current transaction on session %u

`ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET` was added in 8.0.11.
 - Error number: `MY-011608`; Symbol: `ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT`; SQLSTATE: `HY000`

Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust group_replication_transaction_size_limit option.

`ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT` was added in 8.0.11.
 - Error number: `MY-011609`; Symbol: `ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_FAILED`; SQLSTATE: `HY000`

Message: Error while re-initializing an internal cache, for read operations, on session %u

`ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ_FAILED` was added in 8.0.11, removed after 8.0.12.
 - Error number: `MY-011610`; Symbol: `ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED`; SQLSTATE: `HY000`
-

Message: Error while appending data to an internal cache on session %u

[ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing binary log cache on session %u

[ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011611](#); Symbol: [ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while writing to transaction message on session %u

[ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED](#) was added in 8.0.13.

- Error number: [MY-011612](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u

[ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION](#) was added in 8.0.11.

- Error number: [MY-011613](#); Symbol: [ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED](#); SQLSTATE: [HY000](#)

Message: Error broadcasting transaction to the group on session %u. Message is too big.

[ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED](#) was added in 8.0.11.

- Error number: [MY-011614](#); Symbol: [ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while broadcasting the transaction to the group on session %u

[ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED](#) was added in 8.0.11.

- Error number: [MY-011615](#); Symbol: [ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION](#); SQLSTATE: [HY000](#)

Message: Error while waiting for conflict detection procedure to finish on session %u

[ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION](#) was added in 8.0.11.

- Error number: [MY-011616](#); Symbol: [ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error while re-initializing an internal cache, for write operations, on session %u

[ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE_FAILED](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-011617](#); Symbol: [ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication commit cache on session %u

[ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE](#) was added in 8.0.11, removed after 8.0.12.

-
- Error number: [MY-011618](#); Symbol: [ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication commit cache for write on session %u

[ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE_FAILED](#) was added in 8.0.11, removed after 8.0.12.
 - Error number: [MY-011619](#); Symbol: [ER_GRP_RPL_PREV_REC_SESSION_RUNNING](#); SQLSTATE: [HY000](#)

Message: A previous recovery session is still running. Please stop the group replication plugin and wait for it to stop

[ER_GRP_RPL_PREV_REC_SESSION_RUNNING](#) was added in 8.0.11, removed after 8.0.22.
 - Error number: [MY-011620](#); Symbol: [ER_GRP_RPL_FATAL_REC_PROCESS](#); SQLSTATE: [HY000](#)

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.

[ER_GRP_RPL_FATAL_REC_PROCESS](#) was added in 8.0.11.
 - Error number: [MY-011621](#); Symbol: [ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s

[ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL](#) was added in 8.0.11, removed after 8.0.17.
 - Error number: [MY-011622](#); Symbol: [ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS](#); SQLSTATE: [HY000](#)

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

[ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS](#) was added in 8.0.11.
 - Error number: [MY-011623](#); Symbol: [ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE](#); SQLSTATE: [HY000](#)

Message: Only one server alive. Declaring this server as online within the replication group

[ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE](#) was added in 8.0.11.
 - Error number: [MY-011624](#); Symbol: [ER_GRP_RPL_CERTIFICATION_REC_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error when processing certification information in the incremental recovery process

[ER_GRP_RPL_CERTIFICATION_REC_PROCESS](#) was added in 8.0.11.
 - Error number: [MY-011625](#); Symbol: [ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC](#); SQLSTATE: [HY000](#)

Message: Unable to ensure the execution of group transactions received during recovery.

[ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC](#) was added in 8.0.11.
 - Error number: [MY-011626](#); Symbol: [ER_GRP_RPL_WHILE_SENDING_MSG_REC](#); SQLSTATE: [HY000](#)

Message: Error while sending message in the group replication incremental recovery process.

`ER_GRP_RPL_WHILE_SENDING_MSG_REC` was added in 8.0.11.

- Error number: `MY-011627`; Symbol: `ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY`; SQLSTATE: `HY000`

Message: Unable to read the server value for the `super_read_only` variable.

`ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY` was added in 8.0.11, removed after 8.0.31.

- Error number: `MY-011628`; Symbol: `ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY`; SQLSTATE: `HY000`

Message: Unable to read the server values for the `read_only` and `super_read_only` variables.

`ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY` was added in 8.0.11.

- Error number: `MY-011629`; Symbol: `ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE`; SQLSTATE: `HY000`

Message: Unable to reset the server read mode settings. Try to reset them manually.

`ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE` was added in 8.0.11.

- Error number: `MY-011630`; Symbol: `ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS`; SQLSTATE: `HY000`

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.

`ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS` was added in 8.0.11.

- Error number: `MY-011631`; Symbol: `ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS`; SQLSTATE: `HY000`

Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service

`ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS` was added in 8.0.11.

- Error number: `MY-011632`; Symbol: `ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY`; SQLSTATE: `HY000`

Message: This server is working as secondary member with primary member address %s:%u.

`ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-011633`; Symbol: `ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID`; SQLSTATE: `HY000`

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `server_id=0`. Please, restart the server with `server_id` larger than 0.

`ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID` was added in 8.0.11.

- Error number: `MY-011634`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY`; SQLSTATE: `HY000`

Message: `group_replication_force_members` must be empty on group start. Current value: '%s'

`ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY` was added in 8.0.11.

- Error number: `MY-011635`; Symbol: `ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START`; SQLSTATE: `HY000`

Message: It was not possible to guarantee the initialization of plugin structures on server start

`ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START` was added in 8.0.11.

- Error number: `MY-011636`; Symbol:
`ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Could not enable the server read only mode and guarantee a safe recovery execution

`ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE` was added in 8.0.11.

- Error number: `MY-011637`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Error on group communication engine initialization

`ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE` was added in 8.0.11.

- Error number: `MY-011638`; Symbol:
`ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS`; SQLSTATE: `HY000`

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

`ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS` was added in 8.0.11.

- Error number: `MY-011639`; Symbol:
`ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Error on group communication engine start

`ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE` was added in 8.0.11.

- Error number: `MY-011640`; Symbol: `ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP`; SQLSTATE: `HY000`

Message: Timeout on wait for view after joining group

`ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP` was added in 8.0.11.

- Error number: `MY-011641`; Symbol:
`ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE`; SQLSTATE: `HY000`

Message: Error calling group communication interfaces

`ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE` was added in 8.0.11.

- Error number: `MY-011642`; Symbol:
`ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP`; SQLSTATE: `HY000`

Message: Member server_uuid is incompatible with the group. Server_uuid %s matches group_replication_group_name %s.

`ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP` was added in 8.0.11.

-
- Error number: [MY-011643](#); Symbol: [ER_GRP_RPL_MEMBER_CONF_INFO](#); SQLSTATE: [HY000](#)
Message: Member configuration: member_id: %lu; member_uuid: "%s"; single-primary mode: "%s"; group_replication_auto_increment_increment: %lu; group_replication_view_change_uuid: "%s";
[ER_GRP_RPL_MEMBER_CONF_INFO](#) was added in 8.0.11.
 - Error number: [MY-011644](#); Symbol: [ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP](#); SQLSTATE: [HY000](#)
Message: Unable to confirm whether the server has left the group or not. Check performance_schema.replication_group_members to check group membership information.
[ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP](#) was added in 8.0.11.
 - Error number: [MY-011645](#); Symbol: [ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING](#); SQLSTATE: [HY000](#)
Message: Skipping leave operation: concurrent attempt to leave the group is on-going.
[ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING](#) was added in 8.0.11.
 - Error number: [MY-011646](#); Symbol: [ER_GRP_RPL_SERVER_ALREADY_LEFT](#); SQLSTATE: [HY000](#)
Message: Skipping leave operation: member already left the group.
[ER_GRP_RPL_SERVER_ALREADY_LEFT](#) was added in 8.0.11.
 - Error number: [MY-011647](#); Symbol: [ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE](#); SQLSTATE: [HY000](#)
Message: Going to wait for view modification
[ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE](#) was added in 8.0.11.
 - Error number: [MY-011648](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details
[ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_SHUTDOWN](#) was added in 8.0.11.
 - Error number: [MY-011649](#); Symbol: [ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE](#); SQLSTATE: [HY000](#)
Message: Requesting to leave the group despite of not being a member
[ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE](#) was added in 8.0.11.
 - Error number: [MY-011650](#); Symbol: [ER_GRP_RPL_IS_STOPPING](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' is stopping.
[ER_GRP_RPL_IS_STOPPING](#) was added in 8.0.11.
 - Error number: [MY-011651](#); Symbol: [ER_GRP_RPL_IS_STOPPED](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' has been stopped.
[ER_GRP_RPL_IS_STOPPED](#) was added in 8.0.11.
 - Error number: [MY-011652](#); Symbol: [ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.

[ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN](#) was added in 8.0.11.

- Error number: [MY-011653](#); Symbol: [ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details

[ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#) was added in 8.0.11.

- Error number: [MY-011654](#); Symbol: [ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication applier termination.

[ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#) was added in 8.0.11.

- Error number: [MY-011655](#); Symbol: [ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#); SQLSTATE: [HY000](#)

Message: Unexpected failure while shutting down registry module!

[ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#) was added in 8.0.11.

- Error number: [MY-011656](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_HANDLER](#); SQLSTATE: [HY000](#)

Message: Failure during Group Replication handler initialization

[ER_GRP_RPL_FAILED_TO_INIT_HANDLER](#) was added in 8.0.11.

- Error number: [MY-011657](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the server state observers

[ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER](#) was added in 8.0.11.

- Error number: [MY-011658](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the transactions state observers

[ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER](#) was added in 8.0.11.

- Error number: [MY-011659](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the binlog state observers

[ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER](#) was added in 8.0.11.

-
- Error number: MY-011660; Symbol: ER_GRP_RPL_FAILED_TO_START_ON_BOOT; SQLSTATE: HY000

Message: Unable to start Group Replication on boot

ER_GRP_RPL_FAILED_TO_START_ON_BOOT was added in 8.0.11.
 - Error number: MY-011661; Symbol: ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL; SQLSTATE: HY000

Message: Failure when stopping Group Replication on plugin uninstall

ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL was added in 8.0.11.
 - Error number: MY-011662; Symbol: ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER; SQLSTATE: HY000

Message: Failure when unregistering the server state observers

ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER was added in 8.0.11.
 - Error number: MY-011663; Symbol: ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER; SQLSTATE: HY000

Message: Failure when unregistering the transactions state observers

ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER was added in 8.0.11.
 - Error number: MY-011664; Symbol: ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER; SQLSTATE: HY000

Message: Failure when unregistering the binlog state observers

ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER was added in 8.0.11.
 - Error number: MY-011665; Symbol: ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED; SQLSTATE: HY000

Message: All Group Replication server observers have been successfully unregistered

ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED was added in 8.0.11.
 - Error number: MY-011666; Symbol: ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME; SQLSTATE: HY000

Message: Unable to parse the group_replication_group_name.

ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME was added in 8.0.11.
 - Error number: MY-011667; Symbol: ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP; SQLSTATE: HY000

Message: Unable to parse the group_replication_group_name.

ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP was added in 8.0.11.

-
- Error number: [MY-011668](#); Symbol: [ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

[ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN](#) was added in 8.0.11.
 - Error number: [MY-011669](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the Group Replication applier module.

[ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE](#) was added in 8.0.11.
 - Error number: [MY-011670](#); Symbol: [ER_GRP_RPL_APPLIER_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Group Replication applier module successfully initialized!

[ER_GRP_RPL_APPLIER_INITIALIZED](#) was added in 8.0.11.
 - Error number: [MY-011671](#); Symbol: [ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO](#); SQLSTATE: [HY000](#)

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"; server_key_file: "%s"; server_cert_file: "%s"; client_key_file: "%s"; client_cert_file: "%s"; ca_file: "%s"; ca_path: "%s"; cipher: "%s"; tls_version: "%s"; tls_ciphersuites: "%s"; crl_file: "%s"; crl_path: "%s"; ssl_fips_mode: "%s"

[ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO](#) was added in 8.0.11.
 - Error number: [MY-011672](#); Symbol: [ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD](#); SQLSTATE: [HY000](#)

Message: MySQL server does not have SSL support and group_replication_ssl_mode is "%s", START GROUP_REPLICATION will abort

[ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD](#) was added in 8.0.11.
 - Error number: [MY-011673](#); Symbol: [ER_GRP_RPL_SSL_DISABLED](#); SQLSTATE: [HY000](#)

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"

[ER_GRP_RPL_SSL_DISABLED](#) was added in 8.0.11.
 - Error number: [MY-011674](#); Symbol: [ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unable to initialize the group communication engine

[ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE](#) was added in 8.0.11.
 - Error number: [MY-011675](#); Symbol: [ER_GRP_RPL_BINLOG_DISABLED](#); SQLSTATE: [HY000](#)

Message: Binlog must be enabled for Group Replication

[ER_GRP_RPL_BINLOG_DISABLED](#) was added in 8.0.11.
 - Error number: [MY-011676](#); Symbol: [ER_GRP_RPL_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Gtid mode should be ON for Group Replication

`ER_GRP_RPL_GTID_MODE_OFF` was added in 8.0.11.

- Error number: `MY-011677`; Symbol: `ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET`; SQLSTATE: `HY000`

Message: `LOG_SLAVE_UPDATES` should be ON for Group Replication

`ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET` was added in 8.0.11, removed after 8.0.25.

- Error number: `MY-011677`; Symbol: `ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET`; SQLSTATE: `HY000`

Message: `LOG_REPLICA_UPDATES` should be ON for Group Replication

`ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET` was added in 8.0.26.

- Error number: `MY-011678`; Symbol: `ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE`; SQLSTATE: `HY000`

Message: Extraction of transaction write sets requires a hash algorithm configuration. Please, double check that the parameter `transaction-write-set-extraction` is set to a valid algorithm.

`ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION_VALUE` was added in 8.0.11.

- Error number: `MY-011679`; Symbol: `ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Relay log info repository must be set to TABLE

`ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011679`; Symbol: `ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Applier metadata repository must be set to TABLE

`ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE` was added in 8.0.33.

- Error number: `MY-011680`; Symbol: `ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Master info repository must be set to TABLE.

`ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011680`; Symbol: `ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE`; SQLSTATE: `HY000`

Message: Connection metadata repository must be set to TABLE.

`ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE` was added in 8.0.33.

- Error number: `MY-011681`; Symbol: `ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER`; SQLSTATE: `HY000`

Message: In order to use parallel applier on Group Replication, parameter `replica-parallel-type` must be set to 'LOGICAL_CLOCK'.

`ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER` was added in 8.0.11.

-
- Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Group Replication requires slave-preserve-commit-order to be set to ON when using more than 1 applier threads.

[ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET](#) was added in 8.0.11, removed after 8.0.25.

- Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

[ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#) was added in 8.0.26.

- Error number: [MY-011683](#); Symbol: [ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#); SQLSTATE: [HY000](#)

Message: It is not allowed to run single primary mode with 'group_replication_enforce_update_everywhere_checks' enabled.

[ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#) was added in 8.0.11.

- Error number: [MY-011684](#); Symbol: [ER_GRP_RPL_MODULE_TERMINATE_ERROR](#); SQLSTATE: [HY000](#)

Message: error_message: %s

[ER_GRP_RPL_MODULE_TERMINATE_ERROR](#) was added in 8.0.11.

- Error number: [MY-011685](#); Symbol: [ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name option is mandatory

[ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#) was added in 8.0.11.

- Error number: [MY-011686](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID, its length is too big

[ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#) was added in 8.0.11.

- Error number: [MY-011687](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_group_name '%s' is not a valid UUID

[ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#) was added in 8.0.11.

- Error number: [MY-011688](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_quota cannot be larger than group_replication_flow_control_max_quota

[ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#) was added in 8.0.11.

-
- Error number: [MY-011689](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_min_recovery_quota cannot be larger than group_replication_flow_control_max_quota

[ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#) was added in 8.0.11.
 - Error number: [MY-011690](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#); SQLSTATE: [HY000](#)

Message: group_replication_flow_control_max_quota cannot be smaller than group_replication_flow_control_min_quota or group_replication_flow_control_min_recovery_quota

[ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#) was added in 8.0.11.
 - Error number: [MY-011691](#); Symbol: [ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#); SQLSTATE: [HY000](#)

Message: The given value for recovery ssl option 'group_replication_%s' is invalid as its length is beyond the limit

[ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#) was added in 8.0.11.
 - Error number: [MY-011692](#); Symbol: [ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET](#); SQLSTATE: [HY000](#)

Message: There is one group_replication_force_members operation already ongoing

[ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET](#) was added in 8.0.11, removed after 8.0.30.
 - Error number: [MY-011693](#); Symbol: [ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: group_replication_force_members can only be updated when Group Replication is running and a majority of the members are unreachable

[ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED](#) was added in 8.0.11, removed after 8.0.30.
 - Error number: [MY-011694](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#); SQLSTATE: [HY000](#)

Message: Initialized group communication with configuration: group_replication_group_name: '%s'; group_replication_local_address: '%s'; group_replication_group_seeds: '%s'; group_replication_bootstrap_group: '%s'; group_replication_poll_spin_loops: %lu; group_replication_compression_threshold: %lu; group_replication_ip_allowlist: '%s'; group_replication_communication_debug_options: '%s'; group_replication_member_expel_timeout: '%lu'; group_replication_communication_max_message_size: %lu; group_replication_message_cache_size: %lu; group_replication_communication_stack: '%lu'

[ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#) was added in 8.0.11.
 - Error number: [MY-011695](#); Symbol: [ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#); SQLSTATE: [HY000](#)

Message: Unknown group replication applier pipeline requested

[ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#) was added in 8.0.11.

-
- Error number: [MY-011696](#); Symbol: [ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#); SQLSTATE: [HY000](#)

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d

[ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#) was added in 8.0.11.
 - Error number: [MY-011697](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: One of the group replication applier handlers is null due to an initialization error

[ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#) was added in 8.0.11.
 - Error number: [MY-011698](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler, marked as unique, is already in use.

[ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#) was added in 8.0.11.
 - Error number: [MY-011699](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#); SQLSTATE: [HY000](#)

Message: A group replication applier handler role, that was marked as unique, is already in use.

[ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#) was added in 8.0.11.
 - Error number: [MY-011700](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER](#); SQLSTATE: [HY000](#)

Message: Error on group replication applier handler initialization

[ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER](#) was added in 8.0.11.
 - Error number: [MY-011701](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD](#); SQLSTATE: [HY000](#)

Message: Error when initializing a session thread for internal server connection.

[ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD](#) was added in 8.0.11.
 - Error number: [MY-011702](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server communication session is not initialized

[ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED](#) was added in 8.0.11.
 - Error number: [MY-011703](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.

[ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED](#) was added in 8.0.11.
 - Error number: [MY-011704](#); Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

[ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY](#) was added in 8.0.11.

- Error number: MY-011705; Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE](#); SQLSTATE: HY000

Message: Error running internal SQL query: %s. Internal failure.

[ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE](#) was added in 8.0.11.

- Error number: MY-011706; Symbol: [ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE](#); SQLSTATE: HY000

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

[ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE](#) was added in 8.0.11.

- Error number: MY-011707; Symbol: [ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX](#); SQLSTATE: HY000

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

[ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX](#) was added in 8.0.11.

- Error number: MY-011708; Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER](#); SQLSTATE: HY000

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.

[ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER](#) was added in 8.0.11.

- Error number: MY-011709; Symbol: [ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER](#); SQLSTATE: HY000

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX_CONNECTIONS. Server error: %i.

[ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER](#) was added in 8.0.11.

- Error number: MY-011710; Symbol: [ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN](#); SQLSTATE: HY000

Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s

[ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN](#) was added in 8.0.11.

- Error number: MY-011711; Symbol: [ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER](#); SQLSTATE: HY000

Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group_replication_unreachable_majority_timeout option.

[ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER](#) was added in 8.0.11.

-
- Error number: MY-011712; Symbol: `ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS`; SQLSTATE: HY000
Message: The server was automatically set into read only mode after an error was detected.
`ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS` was added in 8.0.11.
 - Error number: MY-011713; Symbol: `ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION`; SQLSTATE: HY000
Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s
`ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION` was added in 8.0.11.
 - Error number: MY-011714; Symbol: `ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED`; SQLSTATE: HY000
Message: Failure in group communication engine '%s' initialization
`ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED` was added in 8.0.11.
 - Error number: MY-011715; Symbol: `ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED`; SQLSTATE: HY000
Message: Unable to set the group communication engine logger
`ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED` was added in 8.0.11.
 - Error number: MY-011716; Symbol: `ER_GRP_RPL_DEBUG_OPTIONS`; SQLSTATE: HY000
Message: Current debug options are: '%s'.
`ER_GRP_RPL_DEBUG_OPTIONS` was added in 8.0.11.
 - Error number: MY-011717; Symbol: `ER_GRP_RPL_INVALID_DEBUG_OPTIONS`; SQLSTATE: HY000
Message: Some debug options in '%s' are not valid.
`ER_GRP_RPL_INVALID_DEBUG_OPTIONS` was added in 8.0.11.
 - Error number: MY-011718; Symbol: `ER_GRP_RPL_EXIT_GRP_GCS_ERROR`; SQLSTATE: HY000
Message: Error calling group communication interfaces while trying to leave the group
`ER_GRP_RPL_EXIT_GRP_GCS_ERROR` was added in 8.0.11.
 - Error number: MY-011719; Symbol: `ER_GRP_RPL_GRP_MEMBER_OFFLINE`; SQLSTATE: HY000
Message: Member is not ONLINE, it is not possible to force a new group membership
`ER_GRP_RPL_GRP_MEMBER_OFFLINE` was added in 8.0.11.
 - Error number: MY-011720; Symbol: `ER_GRP_RPL_GCS_INTERFACE_ERROR`; SQLSTATE: HY000
Message: Error calling group communication interfaces
`ER_GRP_RPL_GCS_INTERFACE_ERROR` was added in 8.0.11.
 - Error number: MY-011721; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR`; SQLSTATE: HY000
Message: Error setting group_replication_force_members value '%s' on group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR` was added in 8.0.11.

- Error number: `MY-011722`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_SET`; SQLSTATE: `HY000`

Message: The group_replication_force_members value '%s' was set in the group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_SET` was added in 8.0.11.

- Error number: `MY-011723`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT`; SQLSTATE: `HY000`

Message: Timeout on wait for view after setting group_replication_force_members value '%s' into group communication interfaces

`ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT` was added in 8.0.11.

- Error number: `MY-011724`; Symbol: `ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG`; SQLSTATE: `HY000`

Message: Broadcast of committed transactions message failed. Message is too big.

`ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG` was added in 8.0.11.

- Error number: `MY-011725`; Symbol: `ER_GRP_RPL_SEND_STATS_ERROR`; SQLSTATE: `HY000`

Message: Error while sending stats message

`ER_GRP_RPL_SEND_STATS_ERROR` was added in 8.0.11.

- Error number: `MY-011726`; Symbol: `ER_GRP_RPL_MEMBER_STATS_INFO`; SQLSTATE: `HY000`

Message: Flow control - update member stats: %s stats certifier_queue %d, applier_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d

`ER_GRP_RPL_MEMBER_STATS_INFO` was added in 8.0.11.

- Error number: `MY-011727`; Symbol: `ER_GRP_RPL_FLOW_CONTROL_STATS`; SQLSTATE: `HY000`

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld

`ER_GRP_RPL_FLOW_CONTROL_STATS` was added in 8.0.11.

- Error number: `MY-011728`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT`; SQLSTATE: `HY000`

Message: Unable to convert a packet into an event on the applier. Error: %s

`ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT` was added in 8.0.11.

- Error number: `MY-011729`; Symbol: `ER_GRP_RPL_PIPELINE_CREATE_FAILED`; SQLSTATE: `HY000`

Message: Failed to create group replication pipeline cache.

`ER_GRP_RPL_PIPELINE_CREATE_FAILED` was added in 8.0.11.

- Error number: `MY-011730`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE`; SQLSTATE: `HY000`

Message: Failed to reinit group replication pipeline cache for write.

`ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE` was added in 8.0.11.

- Error number: `MY-011731`; Symbol: `ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET`; SQLSTATE: `HY000`

Message: Unable to convert the event into a packet on the applier. Error: %s

`ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET` was added in 8.0.11.

- Error number: `MY-011732`; Symbol: `ER_GRP_RPL_PIPELINE_FLUSH_FAIL`; SQLSTATE: `HY000`

Message: Failed to flush group replication pipeline cache.

`ER_GRP_RPL_PIPELINE_FLUSH_FAIL` was added in 8.0.11.

- Error number: `MY-011733`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ`; SQLSTATE: `HY000`

Message: Failed to reinit group replication pipeline cache for read.

`ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ` was added in 8.0.11.

- Error number: `MY-011734`; Symbol: `ER_GRP_RPL_STOP_REP_CHANNEL`; SQLSTATE: `HY000`

Message: Error stopping all replication channels while server was leaving the group. Got error: %d. Please check the error log for more details.

`ER_GRP_RPL_STOP_REP_CHANNEL` was added in 8.0.11, removed after 8.0.17.

- Error number: `MY-011735`; Symbol: `ER_GRP_RPL_GCS_GR_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_GRP_RPL_GCS_GR_ERROR_MSG` was added in 8.0.11.

- Error number: `MY-011736`; Symbol: `ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED`; SQLSTATE: `HY000`

Message: The slave IO thread of channel '%s' is unblocked as the member is declared ONLINE now.

`ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011736`; Symbol: `ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED`; SQLSTATE: `HY000`

Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.

`ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED` was added in 8.0.33.

- Error number: `MY-011737`; Symbol: `ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT`; SQLSTATE: `HY000`

Message: The slave IO thread of channel '%s' will error out as the member failed to come ONLINE.

`ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT` was added in 8.0.11, removed after 8.0.32.

- Error number: `MY-011737`; Symbol: `ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT`; SQLSTATE: `HY000`

Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.

`ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT` was added in 8.0.33.

-
- Error number: [MY-011738](#); Symbol: [ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)

Message: The slave applier thread of channel '%s' is unblocked as the member is declared ONLINE now.

[ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011738](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)

Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.

[ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED](#) was added in 8.0.33.

- Error number: [MY-011739](#); Symbol: [ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)

Message: The slave applier thread of channel '%s' will error out as the member failed to come ONLINE.

[ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-011739](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)

Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.

[ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT](#) was added in 8.0.33.

- Error number: [MY-011740](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION](#); SQLSTATE: [HY000](#)

Message: LDAP authentication initialize: failed to create/ get connection from the pool.

[ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011741](#); Symbol: [ER_LDAP_AUTH_DEINIT_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication de_initialize Failed

[ER_LDAP_AUTH_DEINIT_FAILED](#) was added in 8.0.11.

- Error number: [MY-011742](#); Symbol: [ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH](#); SQLSTATE: [HY000](#)

Message: Skipping group search, No group attribute mentioned

[ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH](#) was added in 8.0.11.

- Error number: [MY-011743](#); Symbol: [ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO](#); SQLSTATE: [HY000](#)

Message: Pool max size is 0, connection pool is disabled

[ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO](#) was added in 8.0.11.

- Error number: [MY-011744](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR](#); SQLSTATE: [HY000](#)

Message: Connection pool initialization, failed to create LDAP object creator

`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR` was added in 8.0.11.

- Error number: `MY-011745`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT`; SQLSTATE: `HY000`

Message: Connection pool initialization, failed to create LDAP object

`ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT` was added in 8.0.11.

- Error number: `MY-011746`; Symbol: `ER_LDAP_AUTH_TLS_CONF`; SQLSTATE: `HY000`

Message: LDAP TLS configuration

`ER_LDAP_AUTH_TLS_CONF` was added in 8.0.11.

- Error number: `MY-011747`; Symbol: `ER_LDAP_AUTH_TLS_CONNECTION`; SQLSTATE: `HY000`

Message: LDAP TLS connection

`ER_LDAP_AUTH_TLS_CONNECTION` was added in 8.0.11.

- Error number: `MY-011748`; Symbol: `ER_LDAP_AUTH_CONN_POOL_NOT_CREATED`; SQLSTATE: `HY000`

Message: LDAP pool is not created.

`ER_LDAP_AUTH_CONN_POOL_NOT_CREATED` was added in 8.0.11.

- Error number: `MY-011749`; Symbol: `ER_LDAP_AUTH_CONN_POOL_INITIALIZING`; SQLSTATE: `HY000`

Message: LDAP pool is initializing

`ER_LDAP_AUTH_CONN_POOL_INITIALIZING` was added in 8.0.11.

- Error number: `MY-011750`; Symbol: `ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING`; SQLSTATE: `HY000`

Message: LDAP pool is de-initializing

`ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING` was added in 8.0.11.

- Error number: `MY-011751`; Symbol: `ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED`; SQLSTATE: `HY000`

Message: Pool max size old and new values are 0

`ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED` was added in 8.0.11.

- Error number: `MY-011752`; Symbol: `ER_LDAP_AUTH_POOL_REINITIALIZING`; SQLSTATE: `HY000`

Message: LDAP pool is re-initializing

`ER_LDAP_AUTH_POOL_REINITIALIZING` was added in 8.0.11.

- Error number: `MY-011753`; Symbol: `ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET`; SQLSTATE: `HY000`

Message: Plug-in has failed to write the packet.

`ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET` was added in 8.0.11.

-
- Error number: [MY-011754](#); Symbol: [ER_LDAP_AUTH_SETTING_USERNAME](#); SQLSTATE: [HY000](#)
Message: Setting LDAP user name as : %s
[ER_LDAP_AUTH_SETTING_USERNAME](#) was added in 8.0.11.
 - Error number: [MY-011755](#); Symbol: [ER_LDAP_AUTH_USER_AUTH_DATA](#); SQLSTATE: [HY000](#)
Message: User authentication data: %s size: %lu
[ER_LDAP_AUTH_USER_AUTH_DATA](#) was added in 8.0.11.
 - Error number: [MY-011756](#); Symbol: [ER_LDAP_AUTH_INFO_FOR_USER](#); SQLSTATE: [HY000](#)
Message: User is authenticated as: %s external user: %s
[ER_LDAP_AUTH_INFO_FOR_USER](#) was added in 8.0.11.
 - Error number: [MY-011757](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO](#); SQLSTATE: [HY000](#)
Message: Group search information base DN: %s scope: %d filter: %s attribute: %s
[ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO](#) was added in 8.0.11.
 - Error number: [MY-011758](#); Symbol: [ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL](#); SQLSTATE: [HY000](#)
Message: Special handling for group search, {GA} found
[ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL](#) was added in 8.0.11.
 - Error number: [MY-011759](#); Symbol: [ER_LDAP_AUTH_GRP_IS_FULLL_DN](#); SQLSTATE: [HY000](#)
Message: Group search special handling, group full DN found.
[ER_LDAP_AUTH_GRP_IS_FULLL_DN](#) was added in 8.0.11.
 - Error number: [MY-011760](#); Symbol: [ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP](#); SQLSTATE: [HY000](#)
Message: User %s is not member of any group.
[ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP](#) was added in 8.0.11.
 - Error number: [MY-011761](#); Symbol: [ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP](#); SQLSTATE: [HY000](#)
Message: User %s is member of more than one group
[ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP](#) was added in 8.0.11.
 - Error number: [MY-011762](#); Symbol: [ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES](#); SQLSTATE: [HY000](#)
Message: For user %s has multiple user group names. Please check if group attribute name is correct
[ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES](#) was added in 8.0.11.
 - Error number: [MY-011763](#); Symbol: [ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME](#); SQLSTATE: [HY000](#)
Message: Searched group name: %s

`ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME` was added in 8.0.11.

- Error number: `MY-011764`; Symbol: `ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP`; SQLSTATE: `HY000`

Message: LDAP authentication object creation time_stamp: %s dn: %s

`ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP` was added in 8.0.11.

- Error number: `MY-011765`; Symbol: `ER_LDAP_AUTH_CERTIFICATE_NAME`; SQLSTATE: `HY000`

Message: Certificate name: %s

`ER_LDAP_AUTH_CERTIFICATE_NAME` was added in 8.0.11.

- Error number: `MY-011766`; Symbol: `ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT`; SQLSTATE: `HY000`

Message: Failed to pool de-initialized: pool is already reconstructing

`ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT` was added in 8.0.11.

- Error number: `MY-011767`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is already initialized

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING` was added in 8.0.11.

- Error number: `MY-011768`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is initializing

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE` was added in 8.0.11.

- Error number: `MY-011769`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE`; SQLSTATE: `HY000`

Message: Pool initialization failed: pool is de-initializing

`ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE` was added in 8.0.11.

- Error number: `MY-011770`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized: pool is already reconstructing

`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE` was added in 8.0.11.

- Error number: `MY-011771`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL`; SQLSTATE: `HY000`

Message: Failed to pool deinitialized : pool is not ready

`ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL` was added in 8.0.11.

-
- Error number: [MY-011772](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY](#); SQLSTATE: [HY000](#)

Message: [Ldap_connection_pool::get](#): Failed to return connection as plug-in is not ready/initializing/de-initializing

[ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY](#) was added in 8.0.11.
 - Error number: [MY-011773](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Connection pool has failed to initialize

[ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011774](#); Symbol: [ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT](#); SQLSTATE: [HY000](#)

Message: [Ldap_connection_pool::get](#) LDAP maximum connection allowed size is reached. Increase the maximum limit.

[ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT](#) was added in 8.0.11.
 - Error number: [MY-011775](#); Symbol: [ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED](#); SQLSTATE: [HY000](#)

Message: Set max pool size failed.

[ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED](#) was added in 8.0.11.
 - Error number: [MY-011776](#); Symbol: [ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to read the packet from client

[ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#) was added in 8.0.11.
 - Error number: [MY-011777](#); Symbol: [ER_LDAP_AUTH_CREATING_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)

Message: [Ldap_authentication::initialize](#): creating new LDAP connection.

[ER_LDAP_AUTH_CREATING_LDAP_CONNECTION](#) was added in 8.0.11.
 - Error number: [MY-011778](#); Symbol: [ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL](#); SQLSTATE: [HY000](#)

Message: [Ldap_authentication::initialize](#): getting connection from pool.

[ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL](#) was added in 8.0.11.
 - Error number: [MY-011779](#); Symbol: [ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL](#); SQLSTATE: [HY000](#)

Message: [Ldap_authentication::de_initialize](#) putting back connection in the pool

[ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL](#) was added in 8.0.11.

-
- Error number: [MY-011780](#); Symbol: [ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: `Ldap_authentication::search_user_group` no group attribute found
[ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND](#) was added in 8.0.11.
 - Error number: [MY-011781](#); Symbol: [ER_LDAP_AUTH_LDAP_INFO_NULL](#); SQLSTATE: [HY000](#)
Message: `Ldap_connexion_pool::put` ldap info null
[ER_LDAP_AUTH_LDAP_INFO_NULL](#) was added in 8.0.11.
 - Error number: [MY-011782](#); Symbol: [ER_LDAP_AUTH_FREEING_CONNECTION](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::put` connection is freeing.
[ER_LDAP_AUTH_FREEING_CONNECTION](#) was added in 8.0.11.
 - Error number: [MY-011783](#); Symbol: [ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::put` connection in pushed in the pool
[ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL](#) was added in 8.0.11.
 - Error number: [MY-011784](#); Symbol: [ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_creator::Ldap_connection_creator`
[ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER](#) was added in 8.0.11.
 - Error number: [MY-011785](#); Symbol: [ER_LDAP_AUTH_STARTING_TLS](#); SQLSTATE: [HY000](#)
Message: starting TLS
[ER_LDAP_AUTH_STARTING_TLS](#) was added in 8.0.11.
 - Error number: [MY-011786](#); Symbol: [ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::get: (ldap_info == NULL)|| (*ldap_info)`
[ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL](#) was added in 8.0.11.
 - Error number: [MY-011787](#); Symbol: [ER_LDAP_AUTH_DELETING_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::deinit: deleting connection key %s`
[ER_LDAP_AUTH_DELETING_CONNECTION_KEY](#) was added in 8.0.11.
 - Error number: [MY-011788](#); Symbol: [ER_LDAP_AUTH_POOLED_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::get` pooled connection key: %s
[ER_LDAP_AUTH_POOLED_CONNECTION_KEY](#) was added in 8.0.11.
 - Error number: [MY-011789](#); Symbol: [ER_LDAP_AUTH_CREATE_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: `Ldap_connection_pool::get` create connection key: %s

`ER_LDAP_AUTH_CREATE_CONNECTION_KEY` was added in 8.0.11.

- Error number: `MY-011790`; Symbol: `ER_LDAP_AUTH_COMMUNICATION_HOST_INFO`; SQLSTATE: `HY000`

Message: LDAP communication host %s port %u

`ER_LDAP_AUTH_COMMUNICATION_HOST_INFO` was added in 8.0.11.

- Error number: `MY-011791`; Symbol: `ER_LDAP_AUTH_METHOD_TO_CLIENT`; SQLSTATE: `HY000`

Message: Sending authentication method to client : %s

`ER_LDAP_AUTH_METHOD_TO_CLIENT` was added in 8.0.11.

- Error number: `MY-011792`; Symbol: `ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT`; SQLSTATE: `HY000`

Message: SASL request received from mysql client: %s

`ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT` was added in 8.0.11.

- Error number: `MY-011793`; Symbol: `ER_LDAP_AUTH_SASL_PROCESS_SASL`; SQLSTATE: `HY000`

Message: Ldap_sasl_authentication::process_sasl rc: %s

`ER_LDAP_AUTH_SASL_PROCESS_SASL` was added in 8.0.11.

- Error number: `MY-011794`; Symbol: `ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO`; SQLSTATE: `HY000`

Message: Ldap_sasl_authentication::process_sasl sasl bind succeed. dn: %s method: %s server credential: %s

`ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO` was added in 8.0.11.

- Error number: `MY-011795`; Symbol: `ER_LDAP_AUTH_STARTED_FOR_USER`; SQLSTATE: `HY000`

Message: LDAP authentication started for user name: %s

`ER_LDAP_AUTH_STARTED_FOR_USER` was added in 8.0.11.

- Error number: `MY-011796`; Symbol: `ER_LDAP_AUTH_DISTINGUISHED_NAME`; SQLSTATE: `HY000`

Message: %s

`ER_LDAP_AUTH_DISTINGUISHED_NAME` was added in 8.0.11.

- Error number: `MY-011797`; Symbol: `ER_LDAP_AUTH_INIT_FAILED`; SQLSTATE: `HY000`

Message: LDAP authentication initialize is failed with: %s

`ER_LDAP_AUTH_INIT_FAILED` was added in 8.0.11.

- Error number: `MY-011798`; Symbol: `ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED`; SQLSTATE: `HY000`

Message: LDAP authentication failed or group retrieval failed: %s

`ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED` was added in 8.0.11.

- Error number: `MY-011799`; Symbol: `ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED`; SQLSTATE: `HY000`

Message: Search user group has failed: %s

[ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED](#) was added in 8.0.11.

- Error number: [MY-011800](#); Symbol: [ER_LDAP_AUTH_USER_BIND_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP user bind has failed: %s

[ER_LDAP_AUTH_USER_BIND_FAILED](#) was added in 8.0.11.

- Error number: [MY-011801](#); Symbol: [ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Connection pool get: Failed to create LDAP connection. %s

[ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011802](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to create new LDAP connection: %s

[ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011803](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to establish TLS connection: %s

[ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#) was added in 8.0.11.

- Error number: [MY-011804](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_SEARCH_DN](#); SQLSTATE: [HY000](#)

Message: Failed to search user full dn: %s

[ER_LDAP_AUTH_FAILED_TO_SEARCH_DN](#) was added in 8.0.11.

- Error number: [MY-011805](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_pool::reinit

[ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER](#) was added in 8.0.11.

- Error number: [MY-011806](#); Symbol: [ER_SYSTEMD_NOTIFY_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The path '%s', from the NOTIFY_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF_UNIX socket.

[ER_SYSTEMD_NOTIFY_PATH_TOO_LONG](#) was added in 8.0.11.

- Error number: [MY-011807](#); Symbol: [ER_SYSTEMD_NOTIFY_CONNECT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to connect to systemd notification socket named %s. Error: '%s'

[ER_SYSTEMD_NOTIFY_CONNECT_FAILED](#) was added in 8.0.11.

- Error number: [MY-011808](#); Symbol: [ER_SYSTEMD_NOTIFY_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write '%s' to systemd notification. Error: '%s'

`ER_SYSTEMD_NOTIFY_WRITE_FAILED` was added in 8.0.11.

- Error number: `MY-011809`; Symbol: `ER_FOUND_MISSING_GTIDS`; SQLSTATE: `HY000`

Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

`ER_FOUND_MISSING_GTIDS` was added in 8.0.11.

- Error number: `MY-011810`; Symbol: `ER_PID_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.

`ER_PID_FILE_PRIV_DIRECTORY_INSECURE` was added in 8.0.11.

- Error number: `MY-011811`; Symbol: `ER_CANT_CHECK_PID_PATH`; SQLSTATE: `HY000`

Message: Can't start server: can't check PID filepath: %s

`ER_CANT_CHECK_PID_PATH` was added in 8.0.11.

- Error number: `MY-011812`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate_password status variables registration failed.

`ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011813`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: validate_password status variables unregistration failed.

`ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011814`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Dictionary file open failed

`ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED` was added in 8.0.11.

- Error number: `MY-011815`; Symbol: `ER_VALIDATE_PWD_COULD_BE_NULL`; SQLSTATE: `HY000`

Message: given password string could be null

`ER_VALIDATE_PWD_COULD_BE_NULL` was added in 8.0.11.

- Error number: `MY-011816`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string to lower case

`ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED` was added in 8.0.11.

- Error number: `MY-011817`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: failed to convert the password string into a buffer

`ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED` was added in 8.0.11.

- Error number: `MY-011818`; Symbol: `ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED`; SQLSTATE: `HY000`

Message: memory allocation failed for string handler

`ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED` was added in 8.0.11.

- Error number: `MY-011819`; Symbol: `ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED`; SQLSTATE: `HY000`

Message: Since the `validate_password_policy` is mentioned as Strong, dictionary file must be specified

`ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED` was added in 8.0.11.

- Error number: `MY-011820`; Symbol: `ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED`; SQLSTATE: `HY000`

Message: `convert_to_buffer` service failed

`ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED` was added in 8.0.11.

- Error number: `MY-011821`; Symbol: `ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: %s variable registration failed.

`ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011822`; Symbol: `ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: %s variable unregistration failed.

`ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED` was added in 8.0.11.

- Error number: `MY-011823`; Symbol: `ER_KEYRING_MIGRATION_EXTRA_OPTIONS`; SQLSTATE: `HY000`

Message: Please specify options specific to keyring migration. Any additional options can be ignored.
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.

`ER_KEYRING_MIGRATION_EXTRA_OPTIONS` was added in 8.0.11.

- Error number: `MY-011825`; Symbol: `ER_IB_MSG_0`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_0` was added in 8.0.11.

- Error number: `MY-011826`; Symbol: `ER_IB_MSG_1`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1` was added in 8.0.11.

- Error number: `MY-011827`; Symbol: `ER_IB_MSG_2`; SQLSTATE: `HY000`

Message: %s

[ER_IB_MSG_2](#) was added in 8.0.11.

- Error number: [MY-011828](#); Symbol: [ER_IB_MSG_3](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_3](#) was added in 8.0.11.

- Error number: [MY-011829](#); Symbol: [ER_IB_MSG_4](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_4](#) was added in 8.0.11.

- Error number: [MY-011830](#); Symbol: [ER_IB_MSG_5](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_5](#) was added in 8.0.11.

- Error number: [MY-011831](#); Symbol: [ER_IB_MSG_6](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_6](#) was added in 8.0.11.

- Error number: [MY-011832](#); Symbol: [ER_IB_MSG_7](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_7](#) was added in 8.0.11.

- Error number: [MY-011833](#); Symbol: [ER_IB_MSG_8](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_8](#) was added in 8.0.11.

- Error number: [MY-011834](#); Symbol: [ER_IB_MSG_9](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_9](#) was added in 8.0.11.

- Error number: [MY-011835](#); Symbol: [ER_IB_MSG_10](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_10](#) was added in 8.0.11.

- Error number: [MY-011836](#); Symbol: [ER_IB_MSG_11](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_11](#) was added in 8.0.11.

- Error number: [MY-011837](#); Symbol: [ER_IB_MSG_12](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_12](#) was added in 8.0.11.

- Error number: [MY-011838](#); Symbol: [ER_IB_MSG_13](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_13](#) was added in 8.0.11.

- Error number: [MY-011839](#); Symbol: [ER_IB_MSG_14](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_14](#) was added in 8.0.11.

- Error number: [MY-011840](#); Symbol: [ER_IB_MSG_15](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_15](#) was added in 8.0.11.

- Error number: [MY-011841](#); Symbol: [ER_IB_MSG_16](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_16](#) was added in 8.0.11.

- Error number: [MY-011842](#); Symbol: [ER_IB_MSG_17](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_17](#) was added in 8.0.11.

- Error number: [MY-011843](#); Symbol: [ER_IB_MSG_18](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_18](#) was added in 8.0.11.

- Error number: [MY-011844](#); Symbol: [ER_IB_MSG_19](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_19](#) was added in 8.0.11.

- Error number: [MY-011845](#); Symbol: [ER_IB_MSG_20](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_20](#) was added in 8.0.11.

- Error number: [MY-011846](#); Symbol: [ER_IB_MSG_21](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_21](#) was added in 8.0.11.

- Error number: [MY-011847](#); Symbol: [ER_IB_MSG_22](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_22](#) was added in 8.0.11.

- Error number: [MY-011848](#); Symbol: [ER_IB_MSG_23](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_23](#) was added in 8.0.11.

-
- Error number: [MY-011849](#); Symbol: [ER_IB_MSG_24](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_24](#) was added in 8.0.11.
 - Error number: [MY-011850](#); Symbol: [ER_IB_MSG_25](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_25](#) was added in 8.0.11.
 - Error number: [MY-011851](#); Symbol: [ER_IB_MSG_26](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_26](#) was added in 8.0.11.
 - Error number: [MY-011852](#); Symbol: [ER_IB_MSG_27](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_27](#) was added in 8.0.11.
 - Error number: [MY-011853](#); Symbol: [ER_IB_MSG_28](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_28](#) was added in 8.0.11.
 - Error number: [MY-011854](#); Symbol: [ER_IB_MSG_29](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_29](#) was added in 8.0.11.
 - Error number: [MY-011855](#); Symbol: [ER_IB_MSG_30](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_30](#) was added in 8.0.11.
 - Error number: [MY-011856](#); Symbol: [ER_IB_MSG_31](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_31](#) was added in 8.0.11.
 - Error number: [MY-011857](#); Symbol: [ER_IB_MSG_32](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_32](#) was added in 8.0.11.
 - Error number: [MY-011858](#); Symbol: [ER_IB_MSG_33](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_33](#) was added in 8.0.11.
 - Error number: [MY-011859](#); Symbol: [ER_IB_MSG_34](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_34](#) was added in 8.0.11.

-
- Error number: [MY-011860](#); Symbol: [ER_IB_MSG_35](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_35](#) was added in 8.0.11.
 - Error number: [MY-011861](#); Symbol: [ER_IB_MSG_36](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_36](#) was added in 8.0.11.
 - Error number: [MY-011862](#); Symbol: [ER_IB_MSG_37](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_37](#) was added in 8.0.11.
 - Error number: [MY-011863](#); Symbol: [ER_IB_MSG_38](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_38](#) was added in 8.0.11.
 - Error number: [MY-011864](#); Symbol: [ER_IB_MSG_39](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_39](#) was added in 8.0.11.
 - Error number: [MY-011865](#); Symbol: [ER_IB_MSG_40](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_40](#) was added in 8.0.11.
 - Error number: [MY-011866](#); Symbol: [ER_IB_MSG_41](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_41](#) was added in 8.0.11.
 - Error number: [MY-011867](#); Symbol: [ER_IB_MSG_42](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_42](#) was added in 8.0.11.
 - Error number: [MY-011868](#); Symbol: [ER_IB_MSG_43](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_43](#) was added in 8.0.11.
 - Error number: [MY-011869](#); Symbol: [ER_IB_MSG_44](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_44](#) was added in 8.0.11.
 - Error number: [MY-011870](#); Symbol: [ER_IB_MSG_45](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_45](#) was added in 8.0.11.

-
- Error number: [MY-011871](#); Symbol: [ER_IB_MSG_46](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_46](#) was added in 8.0.11.
 - Error number: [MY-011872](#); Symbol: [ER_IB_MSG_47](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_47](#) was added in 8.0.11.
 - Error number: [MY-011873](#); Symbol: [ER_IB_MSG_48](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_48](#) was added in 8.0.11.
 - Error number: [MY-011874](#); Symbol: [ER_IB_MSG_49](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_49](#) was added in 8.0.11.
 - Error number: [MY-011875](#); Symbol: [ER_IB_MSG_50](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_50](#) was added in 8.0.11.
 - Error number: [MY-011876](#); Symbol: [ER_IB_MSG_51](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_51](#) was added in 8.0.11.
 - Error number: [MY-011877](#); Symbol: [ER_IB_MSG_52](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_52](#) was added in 8.0.11.
 - Error number: [MY-011878](#); Symbol: [ER_IB_MSG_53](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_53](#) was added in 8.0.11.
 - Error number: [MY-011879](#); Symbol: [ER_IB_MSG_54](#); SQLSTATE: [HY000](#)
Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,
%s,...,%s) failed with %s
[ER_IB_MSG_54](#) was added in 8.0.11.
 - Error number: [MY-011880](#); Symbol: [ER_IB_MSG_55](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_55](#) was added in 8.0.11.
 - Error number: [MY-011881](#); Symbol: [ER_IB_MSG_56](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_56](#) was added in 8.0.11.

- Error number: [MY-011882](#); Symbol: [ER_IB_MSG_57](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_57](#) was added in 8.0.11.

- Error number: [MY-011883](#); Symbol: [ER_IB_MSG_58](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_58](#) was added in 8.0.11.

- Error number: [MY-011884](#); Symbol: [ER_IB_MSG_59](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_59](#) was added in 8.0.11.

- Error number: [MY-011885](#); Symbol: [ER_IB_MSG_60](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_60](#) was added in 8.0.11.

- Error number: [MY-011886](#); Symbol: [ER_IB_MSG_61](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_61](#) was added in 8.0.11.

- Error number: [MY-011887](#); Symbol: [ER_IB_MSG_62](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_62](#) was added in 8.0.11.

- Error number: [MY-011888](#); Symbol: [ER_IB_MSG_63](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_63](#) was added in 8.0.11.

- Error number: [MY-011889](#); Symbol: [ER_IB_MSG_64](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_64](#) was added in 8.0.11.

- Error number: [MY-011890](#); Symbol: [ER_IB_MSG_65](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_65](#) was added in 8.0.11.

- Error number: [MY-011891](#); Symbol: [ER_IB_MSG_66](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_66](#) was added in 8.0.11.

- Error number: [MY-011892](#); Symbol: [ER_IB_MSG_67](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_67](#) was added in 8.0.11.

- Error number: [MY-011893](#); Symbol: [ER_IB_MSG_68](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_68](#) was added in 8.0.11.

- Error number: [MY-011894](#); Symbol: [ER_IB_MSG_69](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_69](#) was added in 8.0.11.

- Error number: [MY-011895](#); Symbol: [ER_IB_MSG_70](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_70](#) was added in 8.0.11.

- Error number: [MY-011896](#); Symbol: [ER_IB_MSG_71](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_71](#) was added in 8.0.11.

- Error number: [MY-011897](#); Symbol: [ER_IB_MSG_72](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_72](#) was added in 8.0.11.

- Error number: [MY-011898](#); Symbol: [ER_IB_MSG_73](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_73](#) was added in 8.0.11.

- Error number: [MY-011899](#); Symbol: [ER_IB_MSG_74](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_74](#) was added in 8.0.11.

- Error number: [MY-011900](#); Symbol: [ER_IB_MSG_75](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_75](#) was added in 8.0.11.

- Error number: [MY-011901](#); Symbol: [ER_IB_MSG_76](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_76](#) was added in 8.0.11.

- Error number: [MY-011902](#); Symbol: [ER_IB_MSG_77](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_77](#) was added in 8.0.11.

-
- Error number: [MY-011903](#); Symbol: [ER_IB_MSG_78](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_78](#) was added in 8.0.11.
 - Error number: [MY-011904](#); Symbol: [ER_IB_MSG_79](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_79](#) was added in 8.0.11.
 - Error number: [MY-011905](#); Symbol: [ER_IB_MSG_80](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_80](#) was added in 8.0.11.
 - Error number: [MY-011906](#); Symbol: [ER_IB_MSG_81](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_81](#) was added in 8.0.11.
 - Error number: [MY-011907](#); Symbol: [ER_IB_MSG_82](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_82](#) was added in 8.0.11.
 - Error number: [MY-011908](#); Symbol: [ER_IB_MSG_83](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_83](#) was added in 8.0.11, removed after 8.0.41.
 - Error number: [MY-011908](#); Symbol: [ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Page still fixed or dirty at shutdown. %s
[ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN](#) was added in 8.0.42.
 - Error number: [MY-011909](#); Symbol: [ER_IB_MSG_84](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_84](#) was added in 8.0.11.
 - Error number: [MY-011910](#); Symbol: [ER_IB_MSG_85](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_85](#) was added in 8.0.11.
 - Error number: [MY-011911](#); Symbol: [ER_IB_MSG_86](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_86](#) was added in 8.0.11.
 - Error number: [MY-011912](#); Symbol: [ER_IB_MSG_87](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_87](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011913](#); Symbol: [ER_IB_MSG_88](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_88](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011914](#); Symbol: [ER_IB_MSG_89](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_89](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011915](#); Symbol: [ER_IB_MSG_90](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_90](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011916](#); Symbol: [ER_IB_MSG_91](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_91](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011917](#); Symbol: [ER_IB_MSG_92](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_92](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011918](#); Symbol: [ER_IB_MSG_93](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_93](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011919](#); Symbol: [ER_IB_MSG_94](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_94](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-011920](#); Symbol: [ER_IB_MSG_95](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_95](#) was added in 8.0.11.

- Error number: [MY-011921](#); Symbol: [ER_IB_MSG_96](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_96](#) was added in 8.0.11.

- Error number: [MY-011922](#); Symbol: [ER_IB_MSG_97](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_97](#) was added in 8.0.11.

- Error number: [MY-011923](#); Symbol: [ER_IB_MSG_98](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_98](#) was added in 8.0.11.

- Error number: [MY-011924](#); Symbol: [ER_IB_MSG_99](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_99](#) was added in 8.0.11.

- Error number: [MY-011925](#); Symbol: [ER_IB_MSG_100](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_100](#) was added in 8.0.11.

- Error number: [MY-011926](#); Symbol: [ER_IB_MSG_101](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_101](#) was added in 8.0.11.

- Error number: [MY-011927](#); Symbol: [ER_IB_MSG_102](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_102](#) was added in 8.0.11.

- Error number: [MY-011928](#); Symbol: [ER_IB_MSG_103](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_103](#) was added in 8.0.11.

- Error number: [MY-011929](#); Symbol: [ER_IB_MSG_104](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_104](#) was added in 8.0.11.

- Error number: [MY-011930](#); Symbol: [ER_IB_MSG_105](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_105](#) was added in 8.0.11.

- Error number: [MY-011931](#); Symbol: [ER_IB_MSG_106](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_106](#) was added in 8.0.11.

- Error number: [MY-011932](#); Symbol: [ER_IB_MSG_107](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_107](#) was added in 8.0.11.

- Error number: [MY-011933](#); Symbol: [ER_IB_MSG_108](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_108](#) was added in 8.0.11.

-
- Error number: [MY-011934](#); Symbol: [ER_IB_MSG_109](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_109](#) was added in 8.0.11.
 - Error number: [MY-011935](#); Symbol: [ER_IB_MSG_110](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_110](#) was added in 8.0.11.
 - Error number: [MY-011936](#); Symbol: [ER_IB_MSG_111](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_111](#) was added in 8.0.11.
 - Error number: [MY-011937](#); Symbol: [ER_IB_MSG_112](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_112](#) was added in 8.0.11.
 - Error number: [MY-011938](#); Symbol: [ER_IB_MSG_113](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_113](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011939](#); Symbol: [ER_IB_MSG_114](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_114](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011940](#); Symbol: [ER_IB_MSG_115](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_115](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011941](#); Symbol: [ER_IB_MSG_116](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_116](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011942](#); Symbol: [ER_IB_MSG_117](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_117](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011943](#); Symbol: [ER_IB_MSG_118](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_118](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-011944](#); Symbol: [ER_IB_MSG_119](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_119](#) was added in 8.0.11.

-
- Error number: [MY-011945](#); Symbol: [ER_IB_MSG_120](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_120](#) was added in 8.0.11.
 - Error number: [MY-011946](#); Symbol: [ER_IB_MSG_121](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_121](#) was added in 8.0.11.
 - Error number: [MY-011947](#); Symbol: [ER_IB_MSG_122](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_122](#) was added in 8.0.11.
 - Error number: [MY-011948](#); Symbol: [ER_IB_MSG_123](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_123](#) was added in 8.0.11.
 - Error number: [MY-011949](#); Symbol: [ER_IB_MSG_124](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_124](#) was added in 8.0.11.
 - Error number: [MY-011950](#); Symbol: [ER_IB_MSG_125](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_125](#) was added in 8.0.11.
 - Error number: [MY-011951](#); Symbol: [ER_IB_MSG_126](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_126](#) was added in 8.0.11.
 - Error number: [MY-011952](#); Symbol: [ER_IB_MSG_127](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_127](#) was added in 8.0.11.
 - Error number: [MY-011953](#); Symbol: [ER_IB_MSG_128](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_128](#) was added in 8.0.11.
 - Error number: [MY-011954](#); Symbol: [ER_IB_MSG_129](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_129](#) was added in 8.0.11.
 - Error number: [MY-011955](#); Symbol: [ER_IB_MSG_130](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_130](#) was added in 8.0.11.

-
- Error number: [MY-011956](#); Symbol: [ER_IB_MSG_131](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_131](#) was added in 8.0.11.
 - Error number: [MY-011957](#); Symbol: [ER_IB_MSG_132](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_132](#) was added in 8.0.11.
 - Error number: [MY-011958](#); Symbol: [ER_IB_MSG_133](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_133](#) was added in 8.0.11.
 - Error number: [MY-011959](#); Symbol: [ER_IB_MSG_134](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_134](#) was added in 8.0.11.
 - Error number: [MY-011960](#); Symbol: [ER_IB_MSG_135](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_135](#) was added in 8.0.11.
 - Error number: [MY-011961](#); Symbol: [ER_IB_MSG_136](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_136](#) was added in 8.0.11.
 - Error number: [MY-011962](#); Symbol: [ER_IB_MSG_137](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_137](#) was added in 8.0.11.
 - Error number: [MY-011963](#); Symbol: [ER_IB_MSG_138](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_138](#) was added in 8.0.11.
 - Error number: [MY-011964](#); Symbol: [ER_IB_MSG_139](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_139](#) was added in 8.0.11.
 - Error number: [MY-011965](#); Symbol: [ER_IB_MSG_140](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_140](#) was added in 8.0.11.
 - Error number: [MY-011966](#); Symbol: [ER_IB_MSG_141](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_141](#) was added in 8.0.11.

-
- Error number: [MY-011967](#); Symbol: [ER_IB_MSG_142](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_142](#) was added in 8.0.11.
 - Error number: [MY-011968](#); Symbol: [ER_IB_MSG_143](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_143](#) was added in 8.0.11.
 - Error number: [MY-011969](#); Symbol: [ER_IB_MSG_144](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_144](#) was added in 8.0.11.
 - Error number: [MY-011970](#); Symbol: [ER_IB_MSG_145](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_145](#) was added in 8.0.11.
 - Error number: [MY-011971](#); Symbol: [ER_IB_MSG_146](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_146](#) was added in 8.0.11.
 - Error number: [MY-011972](#); Symbol: [ER_IB_MSG_147](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_147](#) was added in 8.0.11.
 - Error number: [MY-011973](#); Symbol: [ER_IB_MSG_148](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_148](#) was added in 8.0.11.
 - Error number: [MY-011974](#); Symbol: [ER_IB_MSG_149](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_149](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011974](#); Symbol: [ER_IB_CLONE_INTERNAL](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_INTERNAL](#) was added in 8.0.17.
 - Error number: [MY-011975](#); Symbol: [ER_IB_MSG_150](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_150](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011975](#); Symbol: [ER_IB_CLONE_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_TIMEOUT](#) was added in 8.0.17.

-
- Error number: [MY-011976](#); Symbol: [ER_IB_MSG_151](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_151](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011976](#); Symbol: [ER_IB_CLONE_STATUS_FILE](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_STATUS_FILE](#) was added in 8.0.17.
 - Error number: [MY-011977](#); Symbol: [ER_IB_MSG_152](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_152](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011977](#); Symbol: [ER_IB_CLONE_SQL](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_SQL](#) was added in 8.0.17.
 - Error number: [MY-011978](#); Symbol: [ER_IB_MSG_153](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_153](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011978](#); Symbol: [ER_IB_CLONE_VALIDATE](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_VALIDATE](#) was added in 8.0.17.
 - Error number: [MY-011979](#); Symbol: [ER_IB_MSG_154](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_154](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011979](#); Symbol: [ER_IB_CLONE_PUNCH_HOLE](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_PUNCH_HOLE](#) was added in 8.0.17.
 - Error number: [MY-011980](#); Symbol: [ER_IB_MSG_155](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_155](#) was added in 8.0.11, removed after 8.0.16.
 - Error number: [MY-011980](#); Symbol: [ER_IB_CLONE_GTID_PERSIST](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_CLONE_GTID_PERSIST](#) was added in 8.0.17.
 - Error number: [MY-011981](#); Symbol: [ER_IB_MSG_156](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_156](#) was added in 8.0.11.

-
- Error number: [MY-011982](#); Symbol: [ER_IB_MSG_157](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_157](#) was added in 8.0.11.
 - Error number: [MY-011983](#); Symbol: [ER_IB_MSG_158](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_158](#) was added in 8.0.11.
 - Error number: [MY-011984](#); Symbol: [ER_IB_MSG_159](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_159](#) was added in 8.0.11.
 - Error number: [MY-011985](#); Symbol: [ER_IB_MSG_160](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_160](#) was added in 8.0.11.
 - Error number: [MY-011986](#); Symbol: [ER_IB_MSG_161](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_161](#) was added in 8.0.11.
 - Error number: [MY-011987](#); Symbol: [ER_IB_MSG_162](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_162](#) was added in 8.0.11.
 - Error number: [MY-011988](#); Symbol: [ER_IB_MSG_163](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_163](#) was added in 8.0.11.
 - Error number: [MY-011989](#); Symbol: [ER_IB_MSG_164](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_164](#) was added in 8.0.11.
 - Error number: [MY-011990](#); Symbol: [ER_IB_MSG_165](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_165](#) was added in 8.0.11.
 - Error number: [MY-011991](#); Symbol: [ER_IB_MSG_166](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_166](#) was added in 8.0.11.
 - Error number: [MY-011992](#); Symbol: [ER_IB_MSG_167](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_167](#) was added in 8.0.11.

-
- Error number: [MY-011993](#); Symbol: [ER_IB_MSG_168](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_168](#) was added in 8.0.11.
 - Error number: [MY-011994](#); Symbol: [ER_IB_MSG_169](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_169](#) was added in 8.0.11.
 - Error number: [MY-011995](#); Symbol: [ER_IB_MSG_170](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_170](#) was added in 8.0.11.
 - Error number: [MY-011996](#); Symbol: [ER_IB_MSG_171](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_171](#) was added in 8.0.11.
 - Error number: [MY-011997](#); Symbol: [ER_IB_MSG_172](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_172](#) was added in 8.0.11.
 - Error number: [MY-011998](#); Symbol: [ER_IB_MSG_173](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_173](#) was added in 8.0.11.
 - Error number: [MY-011999](#); Symbol: [ER_IB_MSG_174](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_174](#) was added in 8.0.11.
 - Error number: [MY-012000](#); Symbol: [ER_IB_MSG_175](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_175](#) was added in 8.0.11.
 - Error number: [MY-012001](#); Symbol: [ER_IB_MSG_176](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_176](#) was added in 8.0.11.
 - Error number: [MY-012002](#); Symbol: [ER_IB_MSG_177](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_177](#) was added in 8.0.11.
 - Error number: [MY-012003](#); Symbol: [ER_IB_MSG_178](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_178](#) was added in 8.0.11.

-
- Error number: [MY-012004](#); Symbol: [ER_IB_MSG_179](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_179](#) was added in 8.0.11.
 - Error number: [MY-012005](#); Symbol: [ER_IB_MSG_180](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_180](#) was added in 8.0.11.
 - Error number: [MY-012006](#); Symbol: [ER_IB_MSG_181](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_181](#) was added in 8.0.11, removed after 8.0.31.
 - Error number: [MY-012006](#); Symbol: [ER_IB_LONG_AHI_DISABLE_WAIT](#); SQLSTATE: [HY000](#)
Message: Waited for %u secs for hash index ref_count (%zu) to drop to 0. index: "%s" table: "%s"
[ER_IB_LONG_AHI_DISABLE_WAIT](#) was added in 8.0.32.
 - Error number: [MY-012007](#); Symbol: [ER_IB_MSG_182](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_182](#) was added in 8.0.11.
 - Error number: [MY-012008](#); Symbol: [ER_IB_MSG_183](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_183](#) was added in 8.0.11.
 - Error number: [MY-012009](#); Symbol: [ER_IB_MSG_184](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_184](#) was added in 8.0.11.
 - Error number: [MY-012010](#); Symbol: [ER_IB_MSG_185](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_185](#) was added in 8.0.11.
 - Error number: [MY-012011](#); Symbol: [ER_IB_MSG_186](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_186](#) was added in 8.0.11.
 - Error number: [MY-012012](#); Symbol: [ER_IB_MSG_187](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_187](#) was added in 8.0.11.
 - Error number: [MY-012013](#); Symbol: [ER_IB_MSG_188](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_188](#) was added in 8.0.11.

-
- Error number: [MY-012014](#); Symbol: [ER_IB_MSG_189](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_189](#) was added in 8.0.11.
 - Error number: [MY-012015](#); Symbol: [ER_IB_MSG_190](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_190](#) was added in 8.0.11.
 - Error number: [MY-012016](#); Symbol: [ER_IB_MSG_191](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_191](#) was added in 8.0.11.
 - Error number: [MY-012017](#); Symbol: [ER_IB_MSG_192](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_192](#) was added in 8.0.11.
 - Error number: [MY-012018](#); Symbol: [ER_IB_MSG_193](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_193](#) was added in 8.0.11.
 - Error number: [MY-012019](#); Symbol: [ER_IB_MSG_194](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_194](#) was added in 8.0.11.
 - Error number: [MY-012020](#); Symbol: [ER_IB_MSG_195](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_195](#) was added in 8.0.11.
 - Error number: [MY-012021](#); Symbol: [ER_IB_MSG_196](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_196](#) was added in 8.0.11.
 - Error number: [MY-012022](#); Symbol: [ER_IB_MSG_197](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_197](#) was added in 8.0.11.
 - Error number: [MY-012023](#); Symbol: [ER_IB_MSG_198](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_198](#) was added in 8.0.11.
 - Error number: [MY-012024](#); Symbol: [ER_IB_MSG_199](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_199](#) was added in 8.0.11.

-
- Error number: [MY-012025](#); Symbol: [ER_IB_MSG_200](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_200](#) was added in 8.0.11.
 - Error number: [MY-012026](#); Symbol: [ER_IB_MSG_201](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_201](#) was added in 8.0.11.
 - Error number: [MY-012027](#); Symbol: [ER_IB_MSG_202](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_202](#) was added in 8.0.11.
 - Error number: [MY-012028](#); Symbol: [ER_IB_MSG_203](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_203](#) was added in 8.0.11.
 - Error number: [MY-012029](#); Symbol: [ER_IB_MSG_204](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_204](#) was added in 8.0.11.
 - Error number: [MY-012030](#); Symbol: [ER_IB_MSG_205](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_205](#) was added in 8.0.11.
 - Error number: [MY-012031](#); Symbol: [ER_IB_MSG_206](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_206](#) was added in 8.0.11.
 - Error number: [MY-012032](#); Symbol: [ER_IB_MSG_207](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_207](#) was added in 8.0.11.
 - Error number: [MY-012033](#); Symbol: [ER_IB_MSG_208](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_208](#) was added in 8.0.11.
 - Error number: [MY-012034](#); Symbol: [ER_IB_MSG_209](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_209](#) was added in 8.0.11.
 - Error number: [MY-012035](#); Symbol: [ER_IB_MSG_210](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_210](#) was added in 8.0.11.

-
- Error number: [MY-012036](#); Symbol: [ER_IB_MSG_211](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_211](#) was added in 8.0.11.
 - Error number: [MY-012037](#); Symbol: [ER_IB_MSG_212](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_212](#) was added in 8.0.11.
 - Error number: [MY-012038](#); Symbol: [ER_IB_MSG_213](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_213](#) was added in 8.0.11.
 - Error number: [MY-012039](#); Symbol: [ER_IB_MSG_214](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_214](#) was added in 8.0.11.
 - Error number: [MY-012040](#); Symbol: [ER_IB_MSG_215](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_215](#) was added in 8.0.11.
 - Error number: [MY-012041](#); Symbol: [ER_IB_MSG_216](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_216](#) was added in 8.0.11.
 - Error number: [MY-012042](#); Symbol: [ER_IB_MSG_217](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_217](#) was added in 8.0.11.
 - Error number: [MY-012043](#); Symbol: [ER_IB_MSG_218](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_218](#) was added in 8.0.11.
 - Error number: [MY-012044](#); Symbol: [ER_IB_MSG_219](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_219](#) was added in 8.0.11.
 - Error number: [MY-012045](#); Symbol: [ER_IB_MSG_220](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_220](#) was added in 8.0.11.
 - Error number: [MY-012046](#); Symbol: [ER_IB_MSG_221](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_221](#) was added in 8.0.11.

-
- Error number: [MY-012047](#); Symbol: [ER_IB_MSG_222](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_222](#) was added in 8.0.11.
 - Error number: [MY-012048](#); Symbol: [ER_IB_MSG_223](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_223](#) was added in 8.0.11.
 - Error number: [MY-012049](#); Symbol: [ER_IB_MSG_224](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_224](#) was added in 8.0.11.
 - Error number: [MY-012050](#); Symbol: [ER_IB_MSG_225](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_225](#) was added in 8.0.11.
 - Error number: [MY-012051](#); Symbol: [ER_IB_MSG_226](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_226](#) was added in 8.0.11.
 - Error number: [MY-012052](#); Symbol: [ER_IB_MSG_227](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_227](#) was added in 8.0.11.
 - Error number: [MY-012053](#); Symbol: [ER_IB_MSG_228](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_228](#) was added in 8.0.11.
 - Error number: [MY-012054](#); Symbol: [ER_IB_MSG_229](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_229](#) was added in 8.0.11.
 - Error number: [MY-012055](#); Symbol: [ER_IB_MSG_230](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_230](#) was added in 8.0.11.
 - Error number: [MY-012056](#); Symbol: [ER_IB_MSG_231](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_231](#) was added in 8.0.11.
 - Error number: [MY-012057](#); Symbol: [ER_IB_MSG_232](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_232](#) was added in 8.0.11.

-
- Error number: [MY-012058](#); Symbol: [ER_IB_MSG_233](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_233](#) was added in 8.0.11.
 - Error number: [MY-012059](#); Symbol: [ER_IB_MSG_234](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_234](#) was added in 8.0.11.
 - Error number: [MY-012060](#); Symbol: [ER_IB_MSG_235](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_235](#) was added in 8.0.11.
 - Error number: [MY-012061](#); Symbol: [ER_IB_MSG_236](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_236](#) was added in 8.0.11.
 - Error number: [MY-012062](#); Symbol: [ER_IB_MSG_237](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_237](#) was added in 8.0.11.
 - Error number: [MY-012063](#); Symbol: [ER_IB_MSG_238](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_238](#) was added in 8.0.11.
 - Error number: [MY-012064](#); Symbol: [ER_IB_MSG_239](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_239](#) was added in 8.0.11.
 - Error number: [MY-012065](#); Symbol: [ER_IB_MSG_240](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_240](#) was added in 8.0.11.
 - Error number: [MY-012066](#); Symbol: [ER_IB_MSG_241](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_241](#) was added in 8.0.11.
 - Error number: [MY-012067](#); Symbol: [ER_IB_MSG_242](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_242](#) was added in 8.0.11.
 - Error number: [MY-012068](#); Symbol: [ER_IB_MSG_243](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_243](#) was added in 8.0.11.

-
- Error number: [MY-012069](#); Symbol: [ER_IB_MSG_244](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_244](#) was added in 8.0.11.
 - Error number: [MY-012070](#); Symbol: [ER_IB_MSG_245](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_245](#) was added in 8.0.11.
 - Error number: [MY-012071](#); Symbol: [ER_IB_MSG_246](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_246](#) was added in 8.0.11.
 - Error number: [MY-012072](#); Symbol: [ER_IB_MSG_247](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_247](#) was added in 8.0.11.
 - Error number: [MY-012073](#); Symbol: [ER_IB_MSG_248](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_248](#) was added in 8.0.11.
 - Error number: [MY-012074](#); Symbol: [ER_IB_MSG_249](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_249](#) was added in 8.0.11.
 - Error number: [MY-012075](#); Symbol: [ER_IB_MSG_250](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_250](#) was added in 8.0.11.
 - Error number: [MY-012076](#); Symbol: [ER_IB_MSG_251](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_251](#) was added in 8.0.11.
 - Error number: [MY-012077](#); Symbol: [ER_IB_MSG_252](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_252](#) was added in 8.0.11.
 - Error number: [MY-012078](#); Symbol: [ER_IB_MSG_253](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_253](#) was added in 8.0.11.
 - Error number: [MY-012079](#); Symbol: [ER_IB_MSG_254](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_254](#) was added in 8.0.11.

-
- Error number: [MY-012080](#); Symbol: [ER_IB_MSG_255](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_255](#) was added in 8.0.11.
 - Error number: [MY-012081](#); Symbol: [ER_IB_MSG_256](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_256](#) was added in 8.0.11.
 - Error number: [MY-012082](#); Symbol: [ER_IB_MSG_257](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_257](#) was added in 8.0.11.
 - Error number: [MY-012083](#); Symbol: [ER_IB_MSG_258](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_258](#) was added in 8.0.11.
 - Error number: [MY-012084](#); Symbol: [ER_IB_MSG_259](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_259](#) was added in 8.0.11.
 - Error number: [MY-012085](#); Symbol: [ER_IB_MSG_260](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_260](#) was added in 8.0.11.
 - Error number: [MY-012086](#); Symbol: [ER_IB_MSG_261](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_261](#) was added in 8.0.11.
 - Error number: [MY-012087](#); Symbol: [ER_IB_MSG_262](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_262](#) was added in 8.0.11.
 - Error number: [MY-012088](#); Symbol: [ER_IB_MSG_263](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_263](#) was added in 8.0.11.
 - Error number: [MY-012089](#); Symbol: [ER_IB_MSG_264](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_264](#) was added in 8.0.11.
 - Error number: [MY-012090](#); Symbol: [ER_IB_MSG_265](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_265](#) was added in 8.0.11.

-
- Error number: [MY-012091](#); Symbol: [ER_IB_MSG_266](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_266](#) was added in 8.0.11.
 - Error number: [MY-012092](#); Symbol: [ER_IB_MSG_267](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_267](#) was added in 8.0.11.
 - Error number: [MY-012093](#); Symbol: [ER_IB_MSG_268](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_268](#) was added in 8.0.11.
 - Error number: [MY-012094](#); Symbol: [ER_IB_MSG_269](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_269](#) was added in 8.0.11.
 - Error number: [MY-012095](#); Symbol: [ER_IB_MSG_270](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_270](#) was added in 8.0.11.
 - Error number: [MY-012096](#); Symbol: [ER_IB_MSG_271](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_271](#) was added in 8.0.11.
 - Error number: [MY-012097](#); Symbol: [ER_IB_MSG_272](#); SQLSTATE: [HY000](#)
Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!
[ER_IB_MSG_272](#) was added in 8.0.11.
 - Error number: [MY-012098](#); Symbol: [ER_IB_MSG_273](#); SQLSTATE: [HY000](#)
Message: Can't read encryption key from file %s!
[ER_IB_MSG_273](#) was added in 8.0.11.
 - Error number: [MY-012099](#); Symbol: [ER_IB_MSG_274](#); SQLSTATE: [HY000](#)
Message: Cannot close file %s, because n_pending_flushes %zu
[ER_IB_MSG_274](#) was added in 8.0.11, removed after 8.0.27.
 - Error number: [MY-012100](#); Symbol: [ER_IB_MSG_275](#); SQLSTATE: [HY000](#)
Message: Cannot close file %s, because modification count %lld != flush count %lld
[ER_IB_MSG_275](#) was added in 8.0.11, removed after 8.0.27.
 - Error number: [MY-012101](#); Symbol: [ER_IB_MSG_276](#); SQLSTATE: [HY000](#)
Message: Cannot close file %s, because it is in use
[ER_IB_MSG_276](#) was added in 8.0.11, removed after 8.0.27.

-
- Error number: [MY-012102](#); Symbol: [ER_IB_MSG_277](#); SQLSTATE: [HY000](#)
Message: Open file list len in shard %zu is %llu
[ER_IB_MSG_277](#) was added in 8.0.11, removed after 8.0.27.
 - Error number: [MY-012103](#); Symbol: [ER_IB_MSG_278](#); SQLSTATE: [HY000](#)
Message: Tablespace %s, waiting for IO to stop for %lld seconds
[ER_IB_MSG_278](#) was added in 8.0.11.
 - Error number: [MY-012104](#); Symbol: [ER_IB_MSG_279](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_279](#) was added in 8.0.11, removed after 8.0.27.
 - Error number: [MY-012105](#); Symbol: [ER_IB_MSG_280](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_280](#) was added in 8.0.11.
 - Error number: [MY-012106](#); Symbol: [ER_IB_MSG_281](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_281](#) was added in 8.0.11.
 - Error number: [MY-012107](#); Symbol: [ER_IB_MSG_282](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_282](#) was added in 8.0.11.
 - Error number: [MY-012108](#); Symbol: [ER_IB_MSG_283](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_283](#) was added in 8.0.11.
 - Error number: [MY-012109](#); Symbol: [ER_IB_MSG_284](#); SQLSTATE: [HY000](#)
Message: You must raise the value of innodb_open_files in my.cnf! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.
[ER_IB_MSG_284](#) was added in 8.0.11.
 - Error number: [MY-012110](#); Symbol: [ER_IB_MSG_285](#); SQLSTATE: [HY000](#)
Message: Max tablespace id is too high, %lu
[ER_IB_MSG_285](#) was added in 8.0.11.
 - Error number: [MY-012111](#); Symbol: [ER_IB_MSG_286](#); SQLSTATE: [HY000](#)
Message: Trying to access missing tablespace %lu
[ER_IB_MSG_286](#) was added in 8.0.11, removed after 8.0.27.

-
- Error number: [MY-012111](#); Symbol: [ER_IB_WARN_ACCESSING_NONEXISTINC_SPACE](#); SQLSTATE: [HY000](#)

Message: Trying to access missing tablespace %lu

[ER_IB_WARN_ACCESSING_NONEXISTINC_SPACE](#) was added in 8.0.28.
 - Error number: [MY-012112](#); Symbol: [ER_IB_MSG_287](#); SQLSTATE: [HY000](#)

Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.

[ER_IB_MSG_287](#) was added in 8.0.11.
 - Error number: [MY-012113](#); Symbol: [ER_IB_MSG_288](#); SQLSTATE: [HY000](#)

Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

[ER_IB_MSG_288](#) was added in 8.0.11.
 - Error number: [MY-012114](#); Symbol: [ER_IB_MSG_289](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_289](#) was added in 8.0.11.
 - Error number: [MY-012115](#); Symbol: [ER_IB_MSG_290](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu because it is not found in the tablespace memory cache.

[ER_IB_MSG_290](#) was added in 8.0.11, removed after 8.0.17.
 - Error number: [MY-012116](#); Symbol: [ER_IB_MSG_291](#); SQLSTATE: [HY000](#)

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s

[ER_IB_MSG_291](#) was added in 8.0.11.
 - Error number: [MY-012117](#); Symbol: [ER_IB_MSG_292](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

[ER_IB_MSG_292](#) was added in 8.0.11.
 - Error number: [MY-012118](#); Symbol: [ER_IB_MSG_293](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

[ER_IB_MSG_293](#) was added in 8.0.11.
 - Error number: [MY-012119](#); Symbol: [ER_IB_MSG_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

[ER_IB_MSG_294](#) was added in 8.0.11.
 - Error number: [MY-012120](#); Symbol: [ER_IB_MSG_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

[ER_IB_MSG_295](#) was added in 8.0.11.

-
- Error number: [MY-012121](#); Symbol: [ER_IB_MSG_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

[ER_IB_MSG_296](#) was added in 8.0.11.

- Error number: [MY-012122](#); Symbol: [ER_IB_MSG_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

[ER_IB_MSG_297](#) was added in 8.0.11.

- Error number: [MY-012123](#); Symbol: [ER_IB_MSG_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER_IB_MSG_298](#) was added in 8.0.11.

- Error number: [MY-012124](#); Symbol: [ER_IB_MSG_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

[ER_IB_MSG_299](#) was added in 8.0.11.

- Error number: [MY-012125](#); Symbol: [ER_IB_MSG_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

[ER_IB_MSG_300](#) was added in 8.0.11.

- Error number: [MY-012126](#); Symbol: [ER_IB_MSG_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

[ER_IB_MSG_301](#) was added in 8.0.11.

- Error number: [MY-012127](#); Symbol: [ER_IB_MSG_302](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER_IB_MSG_302](#) was added in 8.0.11, removed after 8.0.16.

- Error number: [MY-012127](#); Symbol: [ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

[ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#) was added in 8.0.17.

- Error number: [MY-012128](#); Symbol: [ER_IB_MSG_303](#); SQLSTATE: [HY000](#)

Message: posix_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file

system supports this function. Refer to your operating system documentation for operating system error code information.

[ER_IB_MSG_303](#) was added in 8.0.11.

- Error number: [MY-012129](#); Symbol: [ER_IB_MSG_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

[ER_IB_MSG_304](#) was added in 8.0.11.

- Error number: [MY-012130](#); Symbol: [ER_IB_MSG_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

[ER_IB_MSG_305](#) was added in 8.0.11.

- Error number: [MY-012131](#); Symbol: [ER_IB_MSG_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for '%s'. %s

[ER_IB_MSG_306](#) was added in 8.0.11.

- Error number: [MY-012132](#); Symbol: [ER_IB_MSG_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

[ER_IB_MSG_307](#) was added in 8.0.11.

- Error number: [MY-012133](#); Symbol: [ER_IB_MSG_308](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_308](#) was added in 8.0.11.

- Error number: [MY-012134](#); Symbol: [ER_IB_MSG_309](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_309](#) was added in 8.0.11.

- Error number: [MY-012135](#); Symbol: [ER_IB_MSG_310](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_310](#) was added in 8.0.11.

- Error number: [MY-012136](#); Symbol: [ER_IB_MSG_311](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_311](#) was added in 8.0.11.

- Error number: [MY-012137](#); Symbol: [ER_IB_MSG_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

[ER_IB_MSG_312](#) was added in 8.0.11.

-
- Error number: [MY-012138](#); Symbol: [ER_IB_MSG_313](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_313](#) was added in 8.0.11.
 - Error number: [MY-012139](#); Symbol: [ER_IB_MSG_314](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_314](#) was added in 8.0.11.
 - Error number: [MY-012140](#); Symbol: [ER_IB_MSG_315](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_315](#) was added in 8.0.11.
 - Error number: [MY-012141](#); Symbol: [ER_IB_MSG_316](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_316](#) was added in 8.0.11.
 - Error number: [MY-012142](#); Symbol: [ER_IB_MSG_317](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_317](#) was added in 8.0.11.
 - Error number: [MY-012143](#); Symbol: [ER_IB_MSG_318](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_318](#) was added in 8.0.11.
 - Error number: [MY-012144](#); Symbol: [ER_IB_MSG_319](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_319](#) was added in 8.0.11.
 - Error number: [MY-012145](#); Symbol: [ER_IB_MSG_320](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_320](#) was added in 8.0.11.
 - Error number: [MY-012146](#); Symbol: [ER_IB_MSG_321](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_321](#) was added in 8.0.11.
 - Error number: [MY-012147](#); Symbol: [ER_IB_MSG_322](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_322](#) was added in 8.0.11.
 - Error number: [MY-012148](#); Symbol: [ER_IB_MSG_323](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_323](#) was added in 8.0.11.

-
- Error number: [MY-012149](#); Symbol: [ER_IB_MSG_324](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_324](#) was added in 8.0.11.
 - Error number: [MY-012150](#); Symbol: [ER_IB_MSG_325](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_325](#) was added in 8.0.11.
 - Error number: [MY-012151](#); Symbol: [ER_IB_MSG_326](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_326](#) was added in 8.0.11.
 - Error number: [MY-012152](#); Symbol: [ER_IB_MSG_327](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_327](#) was added in 8.0.11, removed after 8.0.27.
 - Error number: [MY-012153](#); Symbol: [ER_IB_MSG_328](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_328](#) was added in 8.0.11.
 - Error number: [MY-012154](#); Symbol: [ER_IB_MSG_329](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_329](#) was added in 8.0.11.
 - Error number: [MY-012155](#); Symbol: [ER_IB_MSG_330](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_330](#) was added in 8.0.11.
 - Error number: [MY-012156](#); Symbol: [ER_IB_MSG_331](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_331](#) was added in 8.0.11.
 - Error number: [MY-012157](#); Symbol: [ER_IB_MSG_332](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_332](#) was added in 8.0.11.
 - Error number: [MY-012158](#); Symbol: [ER_IB_MSG_333](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_333](#) was added in 8.0.11.
 - Error number: [MY-012159](#); Symbol: [ER_IB_MSG_334](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_334](#) was added in 8.0.11.

-
- Error number: [MY-012160](#); Symbol: [ER_IB_MSG_335](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_335](#) was added in 8.0.11.
 - Error number: [MY-012161](#); Symbol: [ER_IB_MSG_336](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_336](#) was added in 8.0.11.
 - Error number: [MY-012162](#); Symbol: [ER_IB_MSG_337](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_337](#) was added in 8.0.11.
 - Error number: [MY-012163](#); Symbol: [ER_IB_MSG_338](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_338](#) was added in 8.0.11.
 - Error number: [MY-012164](#); Symbol: [ER_IB_MSG_339](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_339](#) was added in 8.0.11.
 - Error number: [MY-012165](#); Symbol: [ER_IB_MSG_340](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_340](#) was added in 8.0.11.
 - Error number: [MY-012166](#); Symbol: [ER_IB_MSG_341](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_341](#) was added in 8.0.11.
 - Error number: [MY-012167](#); Symbol: [ER_IB_MSG_342](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_342](#) was added in 8.0.11.
 - Error number: [MY-012168](#); Symbol: [ER_IB_MSG_343](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_343](#) was added in 8.0.11.
 - Error number: [MY-012169](#); Symbol: [ER_IB_MSG_344](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_344](#) was added in 8.0.11.
 - Error number: [MY-012170](#); Symbol: [ER_IB_MSG_345](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_345](#) was added in 8.0.11.

-
- Error number: [MY-012171](#); Symbol: [ER_IB_MSG_346](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_346](#) was added in 8.0.11.
 - Error number: [MY-012172](#); Symbol: [ER_IB_MSG_347](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_347](#) was added in 8.0.11.
 - Error number: [MY-012173](#); Symbol: [ER_IB_MSG_348](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_348](#) was added in 8.0.11.
 - Error number: [MY-012174](#); Symbol: [ER_IB_MSG_349](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_349](#) was added in 8.0.11.
 - Error number: [MY-012175](#); Symbol: [ER_IB_MSG_350](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_350](#) was added in 8.0.11.
 - Error number: [MY-012176](#); Symbol: [ER_IB_MSG_351](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_351](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012177](#); Symbol: [ER_IB_MSG_352](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_352](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012177](#); Symbol: [ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#); SQLSTATE: [HY000](#)
Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb_directories.
[ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#) was added in 8.0.21.
 - Error number: [MY-012178](#); Symbol: [ER_IB_MSG_353](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_353](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012179](#); Symbol: [ER_IB_MSG_354](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_354](#) was added in 8.0.11.
-

-
- Error number: [MY-012180](#); Symbol: [ER_IB_MSG_355](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_355](#) was added in 8.0.11.
 - Error number: [MY-012181](#); Symbol: [ER_IB_MSG_356](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_356](#) was added in 8.0.11.
 - Error number: [MY-012182](#); Symbol: [ER_IB_MSG_357](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_357](#) was added in 8.0.11.
 - Error number: [MY-012183](#); Symbol: [ER_IB_MSG_358](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_358](#) was added in 8.0.11.
 - Error number: [MY-012184](#); Symbol: [ER_IB_MSG_359](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_359](#) was added in 8.0.11.
 - Error number: [MY-012185](#); Symbol: [ER_IB_MSG_360](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_360](#) was added in 8.0.11.
 - Error number: [MY-012186](#); Symbol: [ER_IB_MSG_361](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_361](#) was added in 8.0.11.
 - Error number: [MY-012187](#); Symbol: [ER_IB_MSG_362](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_362](#) was added in 8.0.11.
 - Error number: [MY-012188](#); Symbol: [ER_IB_MSG_363](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_363](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012189](#); Symbol: [ER_IB_MSG_364](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_364](#) was added in 8.0.11.
 - Error number: [MY-012190](#); Symbol: [ER_IB_MSG_365](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_365](#) was added in 8.0.11.

-
- Error number: [MY-012191](#); Symbol: [ER_IB_MSG_366](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_366](#) was added in 8.0.11, removed after 8.0.18.
 - Error number: [MY-012191](#); Symbol: [ER_IB_MSG_IGNORE_SCAN_PATH](#); SQLSTATE: [HY000](#)
Message: Scan path '%s' is ignored because %s
[ER_IB_MSG_IGNORE_SCAN_PATH](#) was added in 8.0.19.
 - Error number: [MY-012192](#); Symbol: [ER_IB_MSG_367](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_367](#) was added in 8.0.11.
 - Error number: [MY-012193](#); Symbol: [ER_IB_MSG_368](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_368](#) was added in 8.0.11.
 - Error number: [MY-012194](#); Symbol: [ER_IB_MSG_369](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_369](#) was added in 8.0.11.
 - Error number: [MY-012195](#); Symbol: [ER_IB_MSG_370](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_370](#) was added in 8.0.11.
 - Error number: [MY-012196](#); Symbol: [ER_IB_MSG_371](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_371](#) was added in 8.0.11.
 - Error number: [MY-012197](#); Symbol: [ER_IB_MSG_372](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_372](#) was added in 8.0.11.
 - Error number: [MY-012198](#); Symbol: [ER_IB_MSG_373](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_373](#) was added in 8.0.11.
 - Error number: [MY-012199](#); Symbol: [ER_IB_MSG_374](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_374](#) was added in 8.0.11.
 - Error number: [MY-012200](#); Symbol: [ER_IB_MSG_375](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_375](#) was added in 8.0.11.

-
- Error number: [MY-012201](#); Symbol: [ER_IB_MSG_376](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_376](#) was added in 8.0.11.
 - Error number: [MY-012202](#); Symbol: [ER_IB_MSG_377](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_377](#) was added in 8.0.11.
 - Error number: [MY-012203](#); Symbol: [ER_IB_MSG_378](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_378](#) was added in 8.0.11.
 - Error number: [MY-012204](#); Symbol: [ER_IB_MSG_379](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_379](#) was added in 8.0.11.
 - Error number: [MY-012205](#); Symbol: [ER_IB_MSG_380](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_380](#) was added in 8.0.11.
 - Error number: [MY-012206](#); Symbol: [ER_IB_MSG_381](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_381](#) was added in 8.0.11.
 - Error number: [MY-012207](#); Symbol: [ER_IB_MSG_382](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_382](#) was added in 8.0.11.
 - Error number: [MY-012208](#); Symbol: [ER_IB_MSG_383](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_383](#) was added in 8.0.11.
 - Error number: [MY-012209](#); Symbol: [ER_IB_MSG_384](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_384](#) was added in 8.0.11.
 - Error number: [MY-012210](#); Symbol: [ER_IB_MSG_385](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_385](#) was added in 8.0.11.
 - Error number: [MY-012211](#); Symbol: [ER_IB_MSG_386](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_386](#) was added in 8.0.11.

-
- Error number: [MY-012212](#); Symbol: [ER_IB_MSG_387](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_387](#) was added in 8.0.11.
 - Error number: [MY-012213](#); Symbol: [ER_IB_MSG_388](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_388](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012213](#); Symbol: [ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#); SQLSTATE: [HY000](#)
Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.
[ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#) was added in 8.0.21.
 - Error number: [MY-012214](#); Symbol: [ER_IB_MSG_389](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_389](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012214](#); Symbol: [ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR](#); SQLSTATE: [HY000](#)
Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.
[ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR](#) was added in 8.0.21.
 - Error number: [MY-012215](#); Symbol: [ER_IB_MSG_390](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_390](#) was added in 8.0.11.
 - Error number: [MY-012216](#); Symbol: [ER_IB_MSG_391](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_391](#) was added in 8.0.11.
 - Error number: [MY-012217](#); Symbol: [ER_IB_MSG_392](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_392](#) was added in 8.0.11.
 - Error number: [MY-012218](#); Symbol: [ER_IB_MSG_393](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_393](#) was added in 8.0.11.
 - Error number: [MY-012219](#); Symbol: [ER_IB_MSG_394](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_394](#) was added in 8.0.11.

-
- Error number: [MY-012220](#); Symbol: [ER_IB_MSG_395](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_395](#) was added in 8.0.11.
 - Error number: [MY-012221](#); Symbol: [ER_IB_MSG_396](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_396](#) was added in 8.0.11.
 - Error number: [MY-012222](#); Symbol: [ER_IB_MSG_397](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_397](#) was added in 8.0.11.
 - Error number: [MY-012223](#); Symbol: [ER_IB_MSG_398](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_398](#) was added in 8.0.11.
 - Error number: [MY-012224](#); Symbol: [ER_IB_MSG_399](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_399](#) was added in 8.0.11.
 - Error number: [MY-012225](#); Symbol: [ER_IB_MSG_400](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_400](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012226](#); Symbol: [ER_IB_MSG_401](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_401](#) was added in 8.0.11.
 - Error number: [MY-012227](#); Symbol: [ER_IB_MSG_402](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_402](#) was added in 8.0.11.
 - Error number: [MY-012228](#); Symbol: [ER_IB_MSG_403](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_403](#) was added in 8.0.11.
 - Error number: [MY-012229](#); Symbol: [ER_IB_MSG_404](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_404](#) was added in 8.0.11.
 - Error number: [MY-012230](#); Symbol: [ER_IB_MSG_405](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_405](#) was added in 8.0.11.

-
- Error number: [MY-012231](#); Symbol: [ER_IB_MSG_406](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_406](#) was added in 8.0.11.
 - Error number: [MY-012232](#); Symbol: [ER_IB_MSG_407](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_407](#) was added in 8.0.11.
 - Error number: [MY-012233](#); Symbol: [ER_IB_MSG_408](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_408](#) was added in 8.0.11.
 - Error number: [MY-012234](#); Symbol: [ER_IB_MSG_409](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_409](#) was added in 8.0.11.
 - Error number: [MY-012235](#); Symbol: [ER_IB_MSG_410](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_410](#) was added in 8.0.11.
 - Error number: [MY-012236](#); Symbol: [ER_IB_MSG_411](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_411](#) was added in 8.0.11.
 - Error number: [MY-012237](#); Symbol: [ER_IB_MSG_412](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_412](#) was added in 8.0.11.
 - Error number: [MY-012238](#); Symbol: [ER_IB_MSG_413](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_413](#) was added in 8.0.11.
 - Error number: [MY-012239](#); Symbol: [ER_IB_MSG_414](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_414](#) was added in 8.0.11.
 - Error number: [MY-012240](#); Symbol: [ER_IB_MSG_415](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_415](#) was added in 8.0.11.
 - Error number: [MY-012241](#); Symbol: [ER_IB_MSG_416](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_416](#) was added in 8.0.11.

-
- Error number: [MY-012242](#); Symbol: [ER_IB_MSG_417](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_417](#) was added in 8.0.11.
 - Error number: [MY-012243](#); Symbol: [ER_IB_MSG_418](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_418](#) was added in 8.0.11.
 - Error number: [MY-012244](#); Symbol: [ER_IB_MSG_419](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_419](#) was added in 8.0.11.
 - Error number: [MY-012245](#); Symbol: [ER_IB_MSG_420](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_420](#) was added in 8.0.11.
 - Error number: [MY-012246](#); Symbol: [ER_IB_MSG_421](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_421](#) was added in 8.0.11.
 - Error number: [MY-012247](#); Symbol: [ER_IB_MSG_422](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_422](#) was added in 8.0.11.
 - Error number: [MY-012248](#); Symbol: [ER_IB_MSG_423](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_423](#) was added in 8.0.11.
 - Error number: [MY-012249](#); Symbol: [ER_IB_MSG_424](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_424](#) was added in 8.0.11.
 - Error number: [MY-012250](#); Symbol: [ER_IB_MSG_425](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_425](#) was added in 8.0.11.
 - Error number: [MY-012251](#); Symbol: [ER_IB_MSG_426](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_426](#) was added in 8.0.11.
 - Error number: [MY-012252](#); Symbol: [ER_IB_MSG_427](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_427](#) was added in 8.0.11.

-
- Error number: [MY-012253](#); Symbol: [ER_IB_MSG_428](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_428](#) was added in 8.0.11.
 - Error number: [MY-012254](#); Symbol: [ER_IB_MSG_429](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_429](#) was added in 8.0.11.
 - Error number: [MY-012255](#); Symbol: [ER_IB_MSG_430](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_430](#) was added in 8.0.11.
 - Error number: [MY-012256](#); Symbol: [ER_IB_MSG_431](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_431](#) was added in 8.0.11.
 - Error number: [MY-012257](#); Symbol: [ER_IB_MSG_432](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_432](#) was added in 8.0.11.
 - Error number: [MY-012258](#); Symbol: [ER_IB_MSG_433](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_433](#) was added in 8.0.11.
 - Error number: [MY-012259](#); Symbol: [ER_IB_MSG_434](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_434](#) was added in 8.0.11.
 - Error number: [MY-012260](#); Symbol: [ER_IB_MSG_435](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_435](#) was added in 8.0.11.
 - Error number: [MY-012261](#); Symbol: [ER_IB_MSG_436](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_436](#) was added in 8.0.11.
 - Error number: [MY-012262](#); Symbol: [ER_IB_MSG_437](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_437](#) was added in 8.0.11.
 - Error number: [MY-012263](#); Symbol: [ER_IB_MSG_438](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_438](#) was added in 8.0.11.

-
- Error number: [MY-012264](#); Symbol: [ER_IB_MSG_439](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_439](#) was added in 8.0.11.
 - Error number: [MY-012265](#); Symbol: [ER_IB_MSG_440](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_440](#) was added in 8.0.11.
 - Error number: [MY-012266](#); Symbol: [ER_IB_MSG_441](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_441](#) was added in 8.0.11.
 - Error number: [MY-012267](#); Symbol: [ER_IB_MSG_442](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_442](#) was added in 8.0.11.
 - Error number: [MY-012268](#); Symbol: [ER_IB_MSG_443](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_443](#) was added in 8.0.11.
 - Error number: [MY-012269](#); Symbol: [ER_IB_MSG_444](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_444](#) was added in 8.0.11, removed after 8.0.36.
 - Error number: [MY-012270](#); Symbol: [ER_IB_MSG_445](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_445](#) was added in 8.0.11.
 - Error number: [MY-012271](#); Symbol: [ER_IB_MSG_446](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_446](#) was added in 8.0.11.
 - Error number: [MY-012272](#); Symbol: [ER_IB_MSG_447](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_447](#) was added in 8.0.11.
 - Error number: [MY-012273](#); Symbol: [ER_IB_MSG_448](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_448](#) was added in 8.0.11.
 - Error number: [MY-012274](#); Symbol: [ER_IB_MSG_449](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_449](#) was added in 8.0.11.

-
- Error number: [MY-012275](#); Symbol: [ER_IB_MSG_450](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_450](#) was added in 8.0.11.
 - Error number: [MY-012276](#); Symbol: [ER_IB_MSG_451](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_451](#) was added in 8.0.11.
 - Error number: [MY-012277](#); Symbol: [ER_IB_MSG_452](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_452](#) was added in 8.0.11.
 - Error number: [MY-012278](#); Symbol: [ER_IB_MSG_453](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_453](#) was added in 8.0.11.
 - Error number: [MY-012279](#); Symbol: [ER_IB_MSG_454](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_454](#) was added in 8.0.11.
 - Error number: [MY-012280](#); Symbol: [ER_IB_MSG_455](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_455](#) was added in 8.0.11.
 - Error number: [MY-012281](#); Symbol: [ER_IB_MSG_456](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_456](#) was added in 8.0.11.
 - Error number: [MY-012282](#); Symbol: [ER_IB_MSG_457](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_457](#) was added in 8.0.11.
 - Error number: [MY-012283](#); Symbol: [ER_IB_MSG_458](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_458](#) was added in 8.0.11.
 - Error number: [MY-012284](#); Symbol: [ER_IB_MSG_459](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_459](#) was added in 8.0.11.
 - Error number: [MY-012285](#); Symbol: [ER_IB_MSG_460](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_460](#) was added in 8.0.11.

-
- Error number: [MY-012286](#); Symbol: [ER_IB_MSG_461](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_461](#) was added in 8.0.11.
 - Error number: [MY-012287](#); Symbol: [ER_IB_MSG_462](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_462](#) was added in 8.0.11.
 - Error number: [MY-012288](#); Symbol: [ER_IB_MSG_463](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_463](#) was added in 8.0.11.
 - Error number: [MY-012289](#); Symbol: [ER_IB_MSG_464](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_464](#) was added in 8.0.11.
 - Error number: [MY-012290](#); Symbol: [ER_IB_MSG_465](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_465](#) was added in 8.0.11.
 - Error number: [MY-012291](#); Symbol: [ER_IB_MSG_466](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_466](#) was added in 8.0.11.
 - Error number: [MY-012292](#); Symbol: [ER_IB_MSG_467](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_467](#) was added in 8.0.11.
 - Error number: [MY-012293](#); Symbol: [ER_IB_MSG_468](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_468](#) was added in 8.0.11.
 - Error number: [MY-012294](#); Symbol: [ER_IB_MSG_469](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_469](#) was added in 8.0.11.
 - Error number: [MY-012295](#); Symbol: [ER_IB_MSG_470](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_470](#) was added in 8.0.11.
 - Error number: [MY-012296](#); Symbol: [ER_IB_MSG_471](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_471](#) was added in 8.0.11.

-
- Error number: [MY-012297](#); Symbol: [ER_IB_MSG_472](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_472](#) was added in 8.0.11.
 - Error number: [MY-012298](#); Symbol: [ER_IB_MSG_473](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_473](#) was added in 8.0.11.
 - Error number: [MY-012299](#); Symbol: [ER_IB_MSG_474](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_474](#) was added in 8.0.11.
 - Error number: [MY-012300](#); Symbol: [ER_IB_MSG_475](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_475](#) was added in 8.0.11.
 - Error number: [MY-012301](#); Symbol: [ER_IB_MSG_476](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_476](#) was added in 8.0.11.
 - Error number: [MY-012302](#); Symbol: [ER_IB_MSG_477](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_477](#) was added in 8.0.11.
 - Error number: [MY-012303](#); Symbol: [ER_IB_MSG_478](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_478](#) was added in 8.0.11.
 - Error number: [MY-012304](#); Symbol: [ER_IB_MSG_479](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_479](#) was added in 8.0.11.
 - Error number: [MY-012305](#); Symbol: [ER_IB_MSG_480](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_480](#) was added in 8.0.11.
 - Error number: [MY-012306](#); Symbol: [ER_IB_MSG_481](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_481](#) was added in 8.0.11.
 - Error number: [MY-012307](#); Symbol: [ER_IB_MSG_482](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_482](#) was added in 8.0.11.

-
- Error number: [MY-012308](#); Symbol: [ER_IB_MSG_483](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_483](#) was added in 8.0.11.
 - Error number: [MY-012309](#); Symbol: [ER_IB_MSG_484](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_484](#) was added in 8.0.11.
 - Error number: [MY-012310](#); Symbol: [ER_IB_MSG_485](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_485](#) was added in 8.0.11.
 - Error number: [MY-012311](#); Symbol: [ER_IB_MSG_486](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_486](#) was added in 8.0.11.
 - Error number: [MY-012312](#); Symbol: [ER_IB_MSG_487](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_487](#) was added in 8.0.11.
 - Error number: [MY-012313](#); Symbol: [ER_IB_MSG_488](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_488](#) was added in 8.0.11.
 - Error number: [MY-012314](#); Symbol: [ER_IB_MSG_489](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_489](#) was added in 8.0.11.
 - Error number: [MY-012315](#); Symbol: [ER_IB_MSG_490](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_490](#) was added in 8.0.11.
 - Error number: [MY-012316](#); Symbol: [ER_IB_MSG_491](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_491](#) was added in 8.0.11.
 - Error number: [MY-012317](#); Symbol: [ER_IB_MSG_492](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_492](#) was added in 8.0.11.
 - Error number: [MY-012318](#); Symbol: [ER_IB_MSG_493](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_493](#) was added in 8.0.11.

-
- Error number: [MY-012319](#); Symbol: [ER_IB_MSG_494](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_494](#) was added in 8.0.11.
 - Error number: [MY-012320](#); Symbol: [ER_IB_MSG_495](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_495](#) was added in 8.0.11.
 - Error number: [MY-012321](#); Symbol: [ER_IB_MSG_496](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_496](#) was added in 8.0.11.
 - Error number: [MY-012322](#); Symbol: [ER_IB_MSG_497](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_497](#) was added in 8.0.11.
 - Error number: [MY-012323](#); Symbol: [ER_IB_MSG_498](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_498](#) was added in 8.0.11.
 - Error number: [MY-012324](#); Symbol: [ER_IB_MSG_499](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_499](#) was added in 8.0.11.
 - Error number: [MY-012325](#); Symbol: [ER_IB_MSG_500](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_500](#) was added in 8.0.11.
 - Error number: [MY-012326](#); Symbol: [ER_IB_MSG_501](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_501](#) was added in 8.0.11.
 - Error number: [MY-012327](#); Symbol: [ER_IB_MSG_502](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_502](#) was added in 8.0.11.
 - Error number: [MY-012328](#); Symbol: [ER_IB_MSG_503](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_503](#) was added in 8.0.11.
 - Error number: [MY-012329](#); Symbol: [ER_IB_MSG_504](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_504](#) was added in 8.0.11.

-
- Error number: [MY-012330](#); Symbol: [ER_IB_MSG_505](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_505](#) was added in 8.0.11.
 - Error number: [MY-012331](#); Symbol: [ER_IB_MSG_506](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_506](#) was added in 8.0.11.
 - Error number: [MY-012332](#); Symbol: [ER_IB_MSG_507](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_507](#) was added in 8.0.11.
 - Error number: [MY-012333](#); Symbol: [ER_IB_MSG_508](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_508](#) was added in 8.0.11.
 - Error number: [MY-012334](#); Symbol: [ER_IB_MSG_509](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_509](#) was added in 8.0.11.
 - Error number: [MY-012335](#); Symbol: [ER_IB_MSG_510](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_510](#) was added in 8.0.11.
 - Error number: [MY-012336](#); Symbol: [ER_IB_MSG_511](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_511](#) was added in 8.0.11.
 - Error number: [MY-012337](#); Symbol: [ER_IB_MSG_512](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_512](#) was added in 8.0.11.
 - Error number: [MY-012338](#); Symbol: [ER_IB_MSG_513](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_513](#) was added in 8.0.11.
 - Error number: [MY-012339](#); Symbol: [ER_IB_MSG_514](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_514](#) was added in 8.0.11.
 - Error number: [MY-012340](#); Symbol: [ER_IB_MSG_515](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_515](#) was added in 8.0.11.

-
- Error number: [MY-012341](#); Symbol: [ER_IB_MSG_516](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_516](#) was added in 8.0.11.
 - Error number: [MY-012342](#); Symbol: [ER_IB_MSG_517](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_517](#) was added in 8.0.11.
 - Error number: [MY-012343](#); Symbol: [ER_IB_MSG_518](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_518](#) was added in 8.0.11.
 - Error number: [MY-012344](#); Symbol: [ER_IB_MSG_519](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_519](#) was added in 8.0.11.
 - Error number: [MY-012345](#); Symbol: [ER_IB_MSG_520](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_520](#) was added in 8.0.11.
 - Error number: [MY-012346](#); Symbol: [ER_IB_MSG_521](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_521](#) was added in 8.0.11.
 - Error number: [MY-012347](#); Symbol: [ER_IB_MSG_522](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_522](#) was added in 8.0.11.
 - Error number: [MY-012348](#); Symbol: [ER_IB_MSG_523](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_523](#) was added in 8.0.11.
 - Error number: [MY-012349](#); Symbol: [ER_IB_MSG_524](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_524](#) was added in 8.0.11.
 - Error number: [MY-012350](#); Symbol: [ER_IB_MSG_525](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_525](#) was added in 8.0.11.
 - Error number: [MY-012351](#); Symbol: [ER_IB_MSG_526](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_526](#) was added in 8.0.11.

-
- Error number: [MY-012352](#); Symbol: [ER_IB_MSG_527](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_527](#) was added in 8.0.11.
 - Error number: [MY-012353](#); Symbol: [ER_IB_MSG_528](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_528](#) was added in 8.0.11, removed after 8.0.18.
 - Error number: [MY-012354](#); Symbol: [ER_IB_MSG_529](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_529](#) was added in 8.0.11, removed after 8.0.18.
 - Error number: [MY-012355](#); Symbol: [ER_IB_MSG_530](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_530](#) was added in 8.0.11.
 - Error number: [MY-012356](#); Symbol: [ER_IB_MSG_531](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_531](#) was added in 8.0.11.
 - Error number: [MY-012357](#); Symbol: [ER_IB_MSG_532](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_532](#) was added in 8.0.11.
 - Error number: [MY-012358](#); Symbol: [ER_IB_MSG_533](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_533](#) was added in 8.0.11.
 - Error number: [MY-012359](#); Symbol: [ER_IB_MSG_534](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_534](#) was added in 8.0.11.
 - Error number: [MY-012360](#); Symbol: [ER_IB_MSG_535](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_535](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012361](#); Symbol: [ER_IB_MSG_536](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_536](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012362](#); Symbol: [ER_IB_MSG_537](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_537](#) was added in 8.0.11.

-
- Error number: [MY-012363](#); Symbol: [ER_IB_MSG_538](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_538](#) was added in 8.0.11.
 - Error number: [MY-012364](#); Symbol: [ER_IB_MSG_539](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_539](#) was added in 8.0.11.
 - Error number: [MY-012365](#); Symbol: [ER_IB_MSG_540](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_540](#) was added in 8.0.11.
 - Error number: [MY-012366](#); Symbol: [ER_IB_MSG_541](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_541](#) was added in 8.0.11.
 - Error number: [MY-012367](#); Symbol: [ER_IB_MSG_542](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_542](#) was added in 8.0.11.
 - Error number: [MY-012368](#); Symbol: [ER_IB_MSG_543](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_543](#) was added in 8.0.11.
 - Error number: [MY-012369](#); Symbol: [ER_IB_MSG_544](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_544](#) was added in 8.0.11.
 - Error number: [MY-012370](#); Symbol: [ER_IB_MSG_545](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_545](#) was added in 8.0.11.
 - Error number: [MY-012371](#); Symbol: [ER_IB_MSG_546](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_546](#) was added in 8.0.11.
 - Error number: [MY-012372](#); Symbol: [ER_IB_MSG_547](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_547](#) was added in 8.0.11.
 - Error number: [MY-012373](#); Symbol: [ER_IB_MSG_548](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_548](#) was added in 8.0.11.

-
- Error number: [MY-012374](#); Symbol: [ER_IB_MSG_549](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_549](#) was added in 8.0.11.
 - Error number: [MY-012375](#); Symbol: [ER_IB_MSG_550](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_550](#) was added in 8.0.11.
 - Error number: [MY-012376](#); Symbol: [ER_IB_MSG_551](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_551](#) was added in 8.0.11.
 - Error number: [MY-012377](#); Symbol: [ER_IB_MSG_552](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_552](#) was added in 8.0.11.
 - Error number: [MY-012378](#); Symbol: [ER_IB_MSG_553](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_553](#) was added in 8.0.11.
 - Error number: [MY-012379](#); Symbol: [ER_IB_MSG_554](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_554](#) was added in 8.0.11.
 - Error number: [MY-012380](#); Symbol: [ER_IB_MSG_555](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_555](#) was added in 8.0.11.
 - Error number: [MY-012381](#); Symbol: [ER_IB_MSG_556](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_556](#) was added in 8.0.11.
 - Error number: [MY-012382](#); Symbol: [ER_IB_MSG_557](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_557](#) was added in 8.0.11.
 - Error number: [MY-012383](#); Symbol: [ER_IB_MSG_558](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_558](#) was added in 8.0.11.
 - Error number: [MY-012384](#); Symbol: [ER_IB_MSG_559](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_559](#) was added in 8.0.11.

-
- Error number: [MY-012385](#); Symbol: [ER_IB_MSG_560](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_560](#) was added in 8.0.11.
 - Error number: [MY-012386](#); Symbol: [ER_IB_MSG_561](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_561](#) was added in 8.0.11.
 - Error number: [MY-012387](#); Symbol: [ER_IB_MSG_562](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_562](#) was added in 8.0.11.
 - Error number: [MY-012388](#); Symbol: [ER_IB_MSG_563](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_563](#) was added in 8.0.11.
 - Error number: [MY-012389](#); Symbol: [ER_IB_MSG_564](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_564](#) was added in 8.0.11.
 - Error number: [MY-012390](#); Symbol: [ER_IB_MSG_565](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_565](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012390](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s
[ER_IB_MSG_INVALID_LOCATION_FOR_TABLE](#) was added in 8.0.21.
 - Error number: [MY-012391](#); Symbol: [ER_IB_MSG_566](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_566](#) was added in 8.0.11.
 - Error number: [MY-012392](#); Symbol: [ER_IB_MSG_567](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_567](#) was added in 8.0.11.
 - Error number: [MY-012393](#); Symbol: [ER_IB_MSG_568](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_568](#) was added in 8.0.11.
 - Error number: [MY-012394](#); Symbol: [ER_IB_MSG_569](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_569](#) was added in 8.0.11.

- Error number: [MY-012395](#); Symbol: [ER_IB_MSG_570](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_570](#) was added in 8.0.11.

- Error number: [MY-012396](#); Symbol: [ER_IB_MSG_571](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_571](#) was added in 8.0.11.

- Error number: [MY-012397](#); Symbol: [ER_IB_MSG_572](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_572](#) was added in 8.0.11, removed after 8.0.18.

- Error number: [MY-012398](#); Symbol: [ER_IB_MSG_573](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_573](#) was added in 8.0.11.

- Error number: [MY-012399](#); Symbol: [ER_IB_MSG_574](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_574](#) was added in 8.0.11.

- Error number: [MY-012400](#); Symbol: [ER_IB_MSG_575](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_575](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012401](#); Symbol: [ER_IB_MSG_576](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_576](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012402](#); Symbol: [ER_IB_MSG_577](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_577](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012403](#); Symbol: [ER_IB_MSG_578](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_578](#) was added in 8.0.11.

- Error number: [MY-012404](#); Symbol: [ER_IB_MSG_579](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_579](#) was added in 8.0.11.

- Error number: [MY-012405](#); Symbol: [ER_IB_MSG_580](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_580](#) was added in 8.0.11.

- Error number: [MY-012406](#); Symbol: [ER_IB_MSG_581](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_581](#) was added in 8.0.11.

- Error number: [MY-012407](#); Symbol: [ER_IB_MSG_582](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_582](#) was added in 8.0.11.

- Error number: [MY-012408](#); Symbol: [ER_IB_MSG_583](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_583](#) was added in 8.0.11.

- Error number: [MY-012409](#); Symbol: [ER_IB_MSG_584](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_584](#) was added in 8.0.11.

- Error number: [MY-012410](#); Symbol: [ER_IB_MSG_585](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_585](#) was added in 8.0.11.

- Error number: [MY-012411](#); Symbol: [ER_IB_MSG_586](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_586](#) was added in 8.0.11.

- Error number: [MY-012412](#); Symbol: [ER_IB_MSG_587](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_587](#) was added in 8.0.11.

- Error number: [MY-012413](#); Symbol: [ER_IB_MSG_588](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_588](#) was added in 8.0.11.

- Error number: [MY-012414](#); Symbol: [ER_IB_MSG_589](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_589](#) was added in 8.0.11.

- Error number: [MY-012415](#); Symbol: [ER_IB_MSG_590](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_590](#) was added in 8.0.11.

-
- Error number: [MY-012416](#); Symbol: [ER_IB_MSG_591](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_591](#) was added in 8.0.11.
 - Error number: [MY-012417](#); Symbol: [ER_IB_MSG_592](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_592](#) was added in 8.0.11.
 - Error number: [MY-012418](#); Symbol: [ER_IB_MSG_593](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_593](#) was added in 8.0.11.
 - Error number: [MY-012419](#); Symbol: [ER_IB_MSG_594](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_594](#) was added in 8.0.11.
 - Error number: [MY-012420](#); Symbol: [ER_IB_MSG_595](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_595](#) was added in 8.0.11.
 - Error number: [MY-012421](#); Symbol: [ER_IB_MSG_596](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_596](#) was added in 8.0.11.
 - Error number: [MY-012422](#); Symbol: [ER_IB_MSG_597](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_597](#) was added in 8.0.11.
 - Error number: [MY-012423](#); Symbol: [ER_IB_MSG_598](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_598](#) was added in 8.0.11.
 - Error number: [MY-012424](#); Symbol: [ER_IB_MSG_599](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_599](#) was added in 8.0.11.
 - Error number: [MY-012425](#); Symbol: [ER_IB_MSG_600](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_600](#) was added in 8.0.11.
 - Error number: [MY-012426](#); Symbol: [ER_IB_MSG_601](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_601](#) was added in 8.0.11.

-
- Error number: [MY-012427](#); Symbol: [ER_IB_MSG_602](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_602](#) was added in 8.0.11.
 - Error number: [MY-012428](#); Symbol: [ER_IB_MSG_603](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_603](#) was added in 8.0.11.
 - Error number: [MY-012429](#); Symbol: [ER_IB_MSG_604](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_604](#) was added in 8.0.11.
 - Error number: [MY-012430](#); Symbol: [ER_IB_MSG_605](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_605](#) was added in 8.0.11.
 - Error number: [MY-012431](#); Symbol: [ER_IB_MSG_606](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_606](#) was added in 8.0.11.
 - Error number: [MY-012432](#); Symbol: [ER_IB_MSG_607](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_607](#) was added in 8.0.11.
 - Error number: [MY-012433](#); Symbol: [ER_IB_MSG_608](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_608](#) was added in 8.0.11.
 - Error number: [MY-012434](#); Symbol: [ER_IB_MSG_609](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_609](#) was added in 8.0.11.
 - Error number: [MY-012435](#); Symbol: [ER_IB_MSG_610](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_610](#) was added in 8.0.11.
 - Error number: [MY-012436](#); Symbol: [ER_IB_MSG_611](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_611](#) was added in 8.0.11.
 - Error number: [MY-012437](#); Symbol: [ER_IB_MSG_612](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_612](#) was added in 8.0.11.

-
- Error number: [MY-012438](#); Symbol: [ER_IB_MSG_613](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_613](#) was added in 8.0.11.
 - Error number: [MY-012439](#); Symbol: [ER_IB_MSG_614](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_614](#) was added in 8.0.11.
 - Error number: [MY-012440](#); Symbol: [ER_IB_MSG_615](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_615](#) was added in 8.0.11.
 - Error number: [MY-012441](#); Symbol: [ER_IB_MSG_616](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_616](#) was added in 8.0.11.
 - Error number: [MY-012442](#); Symbol: [ER_IB_MSG_617](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_617](#) was added in 8.0.11.
 - Error number: [MY-012443](#); Symbol: [ER_IB_MSG_618](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_618](#) was added in 8.0.11.
 - Error number: [MY-012444](#); Symbol: [ER_IB_MSG_619](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_619](#) was added in 8.0.11.
 - Error number: [MY-012445](#); Symbol: [ER_IB_MSG_620](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_620](#) was added in 8.0.11.
 - Error number: [MY-012446](#); Symbol: [ER_IB_MSG_621](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_621](#) was added in 8.0.11.
 - Error number: [MY-012447](#); Symbol: [ER_IB_MSG_622](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_622](#) was added in 8.0.11.
 - Error number: [MY-012448](#); Symbol: [ER_IB_MSG_623](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_623](#) was added in 8.0.11.

-
- Error number: [MY-012449](#); Symbol: [ER_IB_MSG_624](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_624](#) was added in 8.0.11.
 - Error number: [MY-012450](#); Symbol: [ER_IB_MSG_625](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_625](#) was added in 8.0.11.
 - Error number: [MY-012451](#); Symbol: [ER_IB_MSG_626](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_626](#) was added in 8.0.11.
 - Error number: [MY-012452](#); Symbol: [ER_IB_MSG_627](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_627](#) was added in 8.0.11.
 - Error number: [MY-012453](#); Symbol: [ER_IB_MSG_628](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_628](#) was added in 8.0.11.
 - Error number: [MY-012454](#); Symbol: [ER_IB_MSG_629](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_629](#) was added in 8.0.11.
 - Error number: [MY-012455](#); Symbol: [ER_IB_MSG_630](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_630](#) was added in 8.0.11.
 - Error number: [MY-012456](#); Symbol: [ER_IB_MSG_631](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_631](#) was added in 8.0.11.
 - Error number: [MY-012457](#); Symbol: [ER_IB_MSG_632](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_632](#) was added in 8.0.11.
 - Error number: [MY-012458](#); Symbol: [ER_IB_MSG_633](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_633](#) was added in 8.0.11.
 - Error number: [MY-012459](#); Symbol: [ER_IB_MSG_634](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_634](#) was added in 8.0.11.

-
- Error number: [MY-012460](#); Symbol: [ER_IB_MSG_635](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_635](#) was added in 8.0.11.

- Error number: [MY-012461](#); Symbol: [ER_IB_MSG_636](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).

[ER_IB_MSG_636](#) was added in 8.0.11.

- Error number: [MY-012462](#); Symbol: [ER_IB_MSG_637](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_637](#) was added in 8.0.11.

- Error number: [MY-012463](#); Symbol: [ER_IB_MSG_638](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_638](#) was added in 8.0.11.

- Error number: [MY-012464](#); Symbol: [ER_IB_MSG_639](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.

[ER_IB_MSG_639](#) was added in 8.0.11.

- Error number: [MY-012465](#); Symbol: [ER_IB_MSG_640](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_640](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012466](#); Symbol: [ER_IB_MSG_641](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_641](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012467](#); Symbol: [ER_IB_MSG_642](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_642](#) was added in 8.0.11.

- Error number: [MY-012468](#); Symbol: [ER_IB_MSG_643](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_643](#) was added in 8.0.11.

- Error number: [MY-012469](#); Symbol: [ER_IB_MSG_644](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_644](#) was added in 8.0.11.

-
- Error number: [MY-012470](#); Symbol: [ER_IB_MSG_645](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_645](#) was added in 8.0.11.
 - Error number: [MY-012471](#); Symbol: [ER_IB_MSG_646](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_646](#) was added in 8.0.11.
 - Error number: [MY-012472](#); Symbol: [ER_IB_MSG_647](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_647](#) was added in 8.0.11.
 - Error number: [MY-012473](#); Symbol: [ER_IB_MSG_648](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_648](#) was added in 8.0.11.
 - Error number: [MY-012474](#); Symbol: [ER_IB_MSG_649](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_649](#) was added in 8.0.11.
 - Error number: [MY-012475](#); Symbol: [ER_IB_MSG_650](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_650](#) was added in 8.0.11.
 - Error number: [MY-012476](#); Symbol: [ER_IB_MSG_651](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_651](#) was added in 8.0.11.
 - Error number: [MY-012477](#); Symbol: [ER_IB_MSG_652](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_652](#) was added in 8.0.11.
 - Error number: [MY-012478](#); Symbol: [ER_IB_MSG_653](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_653](#) was added in 8.0.11, removed after 8.0.15.
 - Error number: [MY-012478](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#) was added in 8.0.16.
 - Error number: [MY-012479](#); Symbol: [ER_IB_MSG_654](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_654](#) was added in 8.0.11.

- Error number: [MY-012480](#); Symbol: [ER_IB_MSG_655](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_655](#) was added in 8.0.11.

- Error number: [MY-012481](#); Symbol: [ER_IB_MSG_656](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_656](#) was added in 8.0.11.

- Error number: [MY-012482](#); Symbol: [ER_IB_MSG_657](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_657](#) was added in 8.0.11.

- Error number: [MY-012483](#); Symbol: [ER_IB_MSG_658](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_658](#) was added in 8.0.11.

- Error number: [MY-012484](#); Symbol: [ER_IB_MSG_659](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_659](#) was added in 8.0.11.

- Error number: [MY-012485](#); Symbol: [ER_IB_MSG_660](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_660](#) was added in 8.0.11.

- Error number: [MY-012486](#); Symbol: [ER_IB_MSG_661](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_661](#) was added in 8.0.11.

- Error number: [MY-012487](#); Symbol: [ER_IB_MSG_662](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_662](#) was added in 8.0.11.

- Error number: [MY-012488](#); Symbol: [ER_IB_MSG_663](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_663](#) was added in 8.0.11.

- Error number: [MY-012489](#); Symbol: [ER_IB_MSG_664](#); SQLSTATE: [HY000](#)

Message: The transaction log size is too large for innodb_log_buffer_size (%lu >= %lu / 2). Trying to extend it.

[ER_IB_MSG_664](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012490](#); Symbol: [ER_IB_MSG_665](#); SQLSTATE: [HY000](#)

Message: innodb_log_buffer_size was extended to %lu bytes.

[ER_IB_MSG_665](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012491](#); Symbol: [ER_IB_MSG_666](#); SQLSTATE: [HY000](#)

Message: The transaction log files are too small for the single transaction log (size=%lu). So, the last checkpoint age might exceed the log group capacity %llu.

[ER_IB_MSG_666](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012492](#); Symbol: [ER_IB_MSG_667](#); SQLSTATE: [HY000](#)

Message: The age of the last checkpoint is %llu, which exceeds the log group capacity %llu.

[ER_IB_MSG_667](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012493](#); Symbol: [ER_IB_MSG_668](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. ib_logfiles are too small for innodb_thread_concurrency %lu. The combined size of ib_logfiles should be bigger than 200 kB * innodb_thread_concurrency. To get mysqld to start up, set innodb_thread_concurrency in my.cnf to a lower value, for example, to 8. After an ERROR-FREE shutdown of mysqld you can adjust the size of ib_logfiles. %s

[ER_IB_MSG_668](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012494](#); Symbol: [ER_IB_MSG_669](#); SQLSTATE: [HY000](#)

Message: Redo log was encrypted, but keyring plugin is not loaded.

[ER_IB_MSG_669](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012495](#); Symbol: [ER_IB_MSG_670](#); SQLSTATE: [HY000](#)

Message: Read redo log encryption metadata successful.

[ER_IB_MSG_670](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012496](#); Symbol: [ER_IB_MSG_671](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace encryption metadata.

[ER_IB_MSG_671](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012497](#); Symbol: [ER_IB_MSG_672](#); SQLSTATE: [HY000](#)

Message: Cannot read the encryption information in log file header, please check if keyring plugin loaded and the key file exists.

[ER_IB_MSG_672](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012498](#); Symbol: [ER_IB_MSG_673](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.

[ER_IB_MSG_673](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012499](#); Symbol: [ER_IB_MSG_674](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER_IB_MSG_674](#) was added in 8.0.11, removed after 8.0.13.

-
- Error number: [MY-012500](#); Symbol: [ER_IB_MSG_675](#); SQLSTATE: [HY000](#)
Message: Can't set redo log tablespace to be encrypted.
[ER_IB_MSG_675](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012501](#); Symbol: [ER_IB_MSG_676](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled.
[ER_IB_MSG_676](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012502](#); Symbol: [ER_IB_MSG_677](#); SQLSTATE: [HY000](#)
Message: Flush Waiting for archiver to to catch up lag LSN: %llu
[ER_IB_MSG_677](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012503](#); Symbol: [ER_IB_MSG_678](#); SQLSTATE: [HY000](#)
Message: Flush overwriting data to archive - wait too long (1 minute) lag LSN: %llu
[ER_IB_MSG_678](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012504](#); Symbol: [ER_IB_MSG_679](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_679](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012505](#); Symbol: [ER_IB_MSG_680](#); SQLSTATE: [HY000](#)
Message: Starting shutdown...
[ER_IB_MSG_680](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012506](#); Symbol: [ER_IB_MSG_681](#); SQLSTATE: [HY000](#)
Message: Waiting for %s to exit
[ER_IB_MSG_681](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012507](#); Symbol: [ER_IB_MSG_682](#); SQLSTATE: [HY000](#)
Message: Waiting for %lu active transactions to finish
[ER_IB_MSG_682](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012508](#); Symbol: [ER_IB_MSG_683](#); SQLSTATE: [HY000](#)
Message: Waiting for master thread to be suspended
[ER_IB_MSG_683](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012509](#); Symbol: [ER_IB_MSG_684](#); SQLSTATE: [HY000](#)
Message: Waiting for page_cleaner to finish flushing of buffer pool
[ER_IB_MSG_684](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012510](#); Symbol: [ER_IB_MSG_685](#); SQLSTATE: [HY000](#)
Message: Pending checkpoint_writes: %lu. Pending log flush writes: %lu.
[ER_IB_MSG_685](#) was added in 8.0.11, removed after 8.0.13.

-
- Error number: [MY-012511](#); Symbol: [ER_IB_MSG_686](#); SQLSTATE: [HY000](#)
Message: Waiting for %lu buffer page I/Os to complete
[ER_IB_MSG_686](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012512](#); Symbol: [ER_IB_MSG_687](#); SQLSTATE: [HY000](#)
Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!
[ER_IB_MSG_687](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012513](#); Symbol: [ER_IB_MSG_688](#); SQLSTATE: [HY000](#)
Message: Background thread %s woke up during shutdown
[ER_IB_MSG_688](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012514](#); Symbol: [ER_IB_MSG_689](#); SQLSTATE: [HY000](#)
Message: Waiting for archiver to finish archiving page and log
[ER_IB_MSG_689](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012515](#); Symbol: [ER_IB_MSG_690](#); SQLSTATE: [HY000](#)
Message: Background thread %s woke up during shutdown
[ER_IB_MSG_690](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012516](#); Symbol: [ER_IB_MSG_691](#); SQLSTATE: [HY000](#)
Message: Waiting for dirty buffer pages to be flushed
[ER_IB_MSG_691](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012517](#); Symbol: [ER_IB_MSG_692](#); SQLSTATE: [HY000](#)
Message: Log sequence number at shutdown %llu is lower than at startup %llu!
[ER_IB_MSG_692](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012518](#); Symbol: [ER_IB_MSG_693](#); SQLSTATE: [HY000](#)
Message: Waiting for archiver to finish archiving page and log
[ER_IB_MSG_693](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-012519](#); Symbol: [ER_IB_MSG_694](#); SQLSTATE: [HY000](#)
Message: ##### CORRUPT LOG RECORD FOUND #####
[ER_IB_MSG_694](#) was added in 8.0.11.
 - Error number: [MY-012520](#); Symbol: [ER_IB_MSG_695](#); SQLSTATE: [HY000](#)
Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu
[ER_IB_MSG_695](#) was added in 8.0.11.
-

-
- Error number: [MY-012521](#); Symbol: [ER_IB_MSG_696](#); SQLSTATE: [HY000](#)
Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:
[ER_IB_MSG_696](#) was added in 8.0.11.
 - Error number: [MY-012522](#); Symbol: [ER_IB_MSG_697](#); SQLSTATE: [HY000](#)
Message: Set innodb_force_recovery to ignore this error.
[ER_IB_MSG_697](#) was added in 8.0.11.
 - Error number: [MY-012523](#); Symbol: [ER_IB_MSG_698](#); SQLSTATE: [HY000](#)
Message: The log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
[ER_IB_MSG_698](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012523](#); Symbol: [ER_IB_MSG_LOG_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
[ER_IB_MSG_LOG_CORRUPT](#) was added in 8.0.30.
 - Error number: [MY-012524](#); Symbol: [ER_IB_MSG_699](#); SQLSTATE: [HY000](#)
Message: %llu pages with log records were left unprocessed!
[ER_IB_MSG_699](#) was added in 8.0.11.
 - Error number: [MY-012525](#); Symbol: [ER_IB_MSG_700](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_700](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012525](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s
[ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED](#) was added in 8.0.30.
 - Error number: [MY-012526](#); Symbol: [ER_IB_MSG_701](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_701](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012526](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Upgrade is not supported after a crash or shutdown with innodb_fast_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s
[ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN](#) was added in 8.0.30.
 - Error number: [MY-012527](#); Symbol: [ER_IB_MSG_702](#); SQLSTATE: [HY000](#)

Message: Invalid redo log header checksum.

[ER_IB_MSG_702](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012528](#); Symbol: [ER_IB_MSG_703](#); SQLSTATE: [HY000](#)

Message: Unsupported redo log format (%lu). The redo log was created before MySQL 5.7.9

[ER_IB_MSG_703](#) was added in 8.0.11, removed after 8.0.13.

- Error number: [MY-012529](#); Symbol: [ER_IB_MSG_704](#); SQLSTATE: [HY000](#)

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.3.

[ER_IB_MSG_704](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012529](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30](#); SQLSTATE: [HY000](#)

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.

[ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30](#) was added in 8.0.30.

- Error number: [MY-012530](#); Symbol: [ER_IB_MSG_705](#); SQLSTATE: [HY000](#)

Message: Unknown redo log format (%lu). Please follow the instructions at %s upgrading-downgrading.html.

[ER_IB_MSG_705](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012530](#); Symbol: [ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s

[ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN](#) was added in 8.0.30.

- Error number: [MY-012531](#); Symbol: [ER_IB_MSG_706](#); SQLSTATE: [HY000](#)

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

[ER_IB_MSG_706](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012531](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

[ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND](#) was added in 8.0.30.

- Error number: [MY-012532](#); Symbol: [ER_IB_MSG_707](#); SQLSTATE: [HY000](#)

Message: Applying a batch of %llu redo log records ...

[ER_IB_MSG_707](#) was added in 8.0.11.

- Error number: [MY-012533](#); Symbol: [ER_IB_MSG_708](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_708](#) was added in 8.0.11.

-
- Error number: [MY-012534](#); Symbol: [ER_IB_MSG_709](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_709](#) was added in 8.0.11.
 - Error number: [MY-012535](#); Symbol: [ER_IB_MSG_710](#); SQLSTATE: [HY000](#)
Message: Apply batch completed!
[ER_IB_MSG_710](#) was added in 8.0.11.
 - Error number: [MY-012536](#); Symbol: [ER_IB_MSG_711](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_711](#) was added in 8.0.11.
 - Error number: [MY-012537](#); Symbol: [ER_IB_MSG_712](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_712](#) was added in 8.0.11.
 - Error number: [MY-012538](#); Symbol: [ER_IB_MSG_713](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_713](#) was added in 8.0.11.
 - Error number: [MY-012539](#); Symbol: [ER_IB_MSG_714](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_714](#) was added in 8.0.11.
 - Error number: [MY-012540](#); Symbol: [ER_IB_MSG_715](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_715](#) was added in 8.0.11.
 - Error number: [MY-012541](#); Symbol: [ER_IB_MSG_716](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_716](#) was added in 8.0.11.
 - Error number: [MY-012542](#); Symbol: [ER_IB_MSG_717](#); SQLSTATE: [HY000](#)
Message: An optimized(without redo logging) DDL operation has been performed. All modified pages may not have been flushed to the disk yet. This offline backup may not be consistent
[ER_IB_MSG_717](#) was added in 8.0.11.
 - Error number: [MY-012543](#); Symbol: [ER_IB_MSG_718](#); SQLSTATE: [HY000](#)
Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.
[ER_IB_MSG_718](#) was added in 8.0.11.

-
- Error number: [MY-012544](#); Symbol: [ER_IB_MSG_719](#); SQLSTATE: [HY000](#)

Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.

[ER_IB_MSG_719](#) was added in 8.0.11.

- Error number: [MY-012545](#); Symbol: [ER_IB_MSG_720](#); SQLSTATE: [HY000](#)

Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.

[ER_IB_MSG_720](#) was added in 8.0.11.

- Error number: [MY-012546](#); Symbol: [ER_IB_MSG_721](#); SQLSTATE: [HY000](#)

Message: Recovery skipped, --innodb-read-only set!

[ER_IB_MSG_721](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012546](#); Symbol: [ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Recovery skipped, --innodb-read-only set!

[ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE](#) was added in 8.0.30.

- Error number: [MY-012547](#); Symbol: [ER_IB_MSG_722](#); SQLSTATE: [HY000](#)

Message: Log scan progressed past the checkpoint LSN %llu.

[ER_IB_MSG_722](#) was added in 8.0.11.

- Error number: [MY-012548](#); Symbol: [ER_IB_MSG_723](#); SQLSTATE: [HY000](#)

Message: Log parsing buffer overflow. Recovery may have failed! Please set log_buffer_size to a value higher than %lu.

[ER_IB_MSG_723](#) was added in 8.0.11.

- Error number: [MY-012549](#); Symbol: [ER_IB_MSG_724](#); SQLSTATE: [HY000](#)

Message: Set innodb_force_recovery to ignore this error.

[ER_IB_MSG_724](#) was added in 8.0.11.

- Error number: [MY-012550](#); Symbol: [ER_IB_MSG_725](#); SQLSTATE: [HY000](#)

Message: Doing recovery: scanned up to log sequence number %llu

[ER_IB_MSG_725](#) was added in 8.0.11.

- Error number: [MY-012551](#); Symbol: [ER_IB_MSG_726](#); SQLSTATE: [HY000](#)

Message: Database was not shutdown normally!

[ER_IB_MSG_726](#) was added in 8.0.11.

- Error number: [MY-012552](#); Symbol: [ER_IB_MSG_727](#); SQLSTATE: [HY000](#)

Message: Starting crash recovery.

[ER_IB_MSG_727](#) was added in 8.0.11.

-
- Error number: [MY-012553](#); Symbol: [ER_IB_MSG_728](#); SQLSTATE: [HY000](#)
Message: The user has set SRV_FORCE_NO_LOG_REDO on, skipping log redo
[ER_IB_MSG_728](#) was added in 8.0.11.
 - Error number: [MY-012554](#); Symbol: [ER_IB_MSG_729](#); SQLSTATE: [HY000](#)
Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!
[ER_IB_MSG_729](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012554](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!
[ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE](#) was added in 8.0.30.
 - Error number: [MY-012555](#); Symbol: [ER_IB_MSG_730](#); SQLSTATE: [HY000](#)
Message: The log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.
[ER_IB_MSG_730](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012555](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_MEB](#); SQLSTATE: [HY000](#)
Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.
[ER_IB_MSG_LOG_FILES_CREATED_BY_MEB](#) was added in 8.0.30.
 - Error number: [MY-012556](#); Symbol: [ER_IB_MSG_731](#); SQLSTATE: [HY000](#)
Message: Opening cloned database
[ER_IB_MSG_731](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012556](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE](#); SQLSTATE: [HY000](#)
Message: Opening cloned database
[ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE](#) was added in 8.0.30.
 - Error number: [MY-012557](#); Symbol: [ER_IB_MSG_732](#); SQLSTATE: [HY000](#)
Message: Redo log is from an earlier version, v%lu.
[ER_IB_MSG_732](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012557](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD](#); SQLSTATE: [HY000](#)
Message: Redo log is from an earlier version, v%lu.
[ER_IB_MSG_LOG_FORMAT_OLD](#) was added in 8.0.30.
 - Error number: [MY-012558](#); Symbol: [ER_IB_MSG_733](#); SQLSTATE: [HY000](#)
Message: Redo log format v%lu not supported. Current supported format is v%lu.
[ER_IB_MSG_733](#) was added in 8.0.11, removed after 8.0.29.

-
- Error number: [MY-012558](#); Symbol: [ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Redo log format v%lu not supported. Current supported format is v%lu.

[ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED](#) was added in 8.0.30, removed after 8.0.32.
 - Error number: [MY-012559](#); Symbol: [ER_IB_MSG_734](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right ib_logfiles to start up the database? Log sequence number in the ib_logfiles is %llu, less than the log sequence number in the first system tablespace file header, %llu.

[ER_IB_MSG_734](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012559](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEAN_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.

[ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEAN_SHUTDOWN](#) was added in 8.0.30.
 - Error number: [MY-012560](#); Symbol: [ER_IB_MSG_735](#); SQLSTATE: [HY000](#)

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the ib_logfiles!

[ER_IB_MSG_735](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012560](#); Symbol: [ER_IB_MSG_RECOVERY_IS_NEEDED](#); SQLSTATE: [HY000](#)

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!

[ER_IB_MSG_RECOVERY_IS_NEEDED](#) was added in 8.0.30.
 - Error number: [MY-012561](#); Symbol: [ER_IB_MSG_736](#); SQLSTATE: [HY000](#)

Message: Can't initiate database recovery, running in read-only-mode.

[ER_IB_MSG_736](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012561](#); Symbol: [ER_IB_MSG_RECOVERY_IN_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: Can't initiate database recovery, running in read-only-mode.

[ER_IB_MSG_RECOVERY_IN_READ_ONLY](#) was added in 8.0.30.
 - Error number: [MY-012562](#); Symbol: [ER_IB_MSG_737](#); SQLSTATE: [HY000](#)

Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!

[ER_IB_MSG_737](#) was added in 8.0.11.
 - Error number: [MY-012563](#); Symbol: [ER_IB_MSG_738](#); SQLSTATE: [HY000](#)

Message: Waiting for recv_writer to finish flushing of buffer pool

[ER_IB_MSG_738](#) was added in 8.0.11.
 - Error number: [MY-012564](#); Symbol: [ER_IB_MSG_739](#); SQLSTATE: [HY000](#)

Message: Recovery parsing buffer extended to %zu.

[ER_IB_MSG_739](#) was added in 8.0.11.

- Error number: [MY-012565](#); Symbol: [ER_IB_MSG_740](#); SQLSTATE: [HY000](#)

Message: Out of memory while resizing recovery parsing buffer.

[ER_IB_MSG_740](#) was added in 8.0.11.

- Error number: [MY-012566](#); Symbol: [ER_IB_MSG_741](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_741](#) was added in 8.0.11.

- Error number: [MY-012567](#); Symbol: [ER_IB_MSG_742](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_742](#) was added in 8.0.11.

- Error number: [MY-012568](#); Symbol: [ER_IB_MSG_743](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_743](#) was added in 8.0.11.

- Error number: [MY-012569](#); Symbol: [ER_IB_MSG_744](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_744](#) was added in 8.0.11.

- Error number: [MY-012570](#); Symbol: [ER_IB_MSG_745](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_745](#) was added in 8.0.11.

- Error number: [MY-012571](#); Symbol: [ER_IB_MSG_746](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_746](#) was added in 8.0.11.

- Error number: [MY-012572](#); Symbol: [ER_IB_MSG_747](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_747](#) was added in 8.0.11.

- Error number: [MY-012573](#); Symbol: [ER_IB_MSG_748](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_748](#) was added in 8.0.11.

- Error number: [MY-012574](#); Symbol: [ER_IB_MSG_749](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_749](#) was added in 8.0.11.

-
- Error number: [MY-012575](#); Symbol: [ER_IB_MSG_750](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_750](#) was added in 8.0.11.
 - Error number: [MY-012576](#); Symbol: [ER_IB_MSG_751](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_751](#) was added in 8.0.11.
 - Error number: [MY-012577](#); Symbol: [ER_IB_MSG_752](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_752](#) was added in 8.0.11.
 - Error number: [MY-012578](#); Symbol: [ER_IB_MSG_753](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_753](#) was added in 8.0.11.
 - Error number: [MY-012579](#); Symbol: [ER_IB_MSG_754](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_754](#) was added in 8.0.11.
 - Error number: [MY-012580](#); Symbol: [ER_IB_MSG_755](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_755](#) was added in 8.0.11.
 - Error number: [MY-012581](#); Symbol: [ER_IB_MSG_756](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_756](#) was added in 8.0.11.
 - Error number: [MY-012582](#); Symbol: [ER_IB_MSG_757](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_757](#) was added in 8.0.11.
 - Error number: [MY-012583](#); Symbol: [ER_IB_MSG_758](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_758](#) was added in 8.0.11.
 - Error number: [MY-012584](#); Symbol: [ER_IB_MSG_759](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_759](#) was added in 8.0.11.
 - Error number: [MY-012585](#); Symbol: [ER_IB_MSG_760](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_760](#) was added in 8.0.11.

-
- Error number: [MY-012586](#); Symbol: [ER_IB_MSG_761](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_761](#) was added in 8.0.11.
 - Error number: [MY-012587](#); Symbol: [ER_IB_MSG_762](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_762](#) was added in 8.0.11.
 - Error number: [MY-012588](#); Symbol: [ER_IB_MSG_763](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_763](#) was added in 8.0.11.
 - Error number: [MY-012589](#); Symbol: [ER_IB_MSG_764](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_764](#) was added in 8.0.11.
 - Error number: [MY-012590](#); Symbol: [ER_IB_MSG_765](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_765](#) was added in 8.0.11.
 - Error number: [MY-012591](#); Symbol: [ER_IB_MSG_766](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_766](#) was added in 8.0.11.
 - Error number: [MY-012592](#); Symbol: [ER_IB_MSG_767](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_767](#) was added in 8.0.11.
 - Error number: [MY-012593](#); Symbol: [ER_IB_MSG_768](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_768](#) was added in 8.0.11.
 - Error number: [MY-012594](#); Symbol: [ER_IB_MSG_769](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_769](#) was added in 8.0.11.
 - Error number: [MY-012595](#); Symbol: [ER_IB_MSG_770](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_770](#) was added in 8.0.11.
 - Error number: [MY-012596](#); Symbol: [ER_IB_MSG_771](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_771](#) was added in 8.0.11.

-
- Error number: [MY-012597](#); Symbol: [ER_IB_MSG_772](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_772](#) was added in 8.0.11.
 - Error number: [MY-012598](#); Symbol: [ER_IB_MSG_773](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_773](#) was added in 8.0.11.
 - Error number: [MY-012599](#); Symbol: [ER_IB_MSG_774](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_774](#) was added in 8.0.11.
 - Error number: [MY-012600](#); Symbol: [ER_IB_MSG_775](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_775](#) was added in 8.0.11.
 - Error number: [MY-012601](#); Symbol: [ER_IB_MSG_776](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_776](#) was added in 8.0.11.
 - Error number: [MY-012602](#); Symbol: [ER_IB_MSG_777](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_777](#) was added in 8.0.11.
 - Error number: [MY-012603](#); Symbol: [ER_IB_MSG_778](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_778](#) was added in 8.0.11.
 - Error number: [MY-012604](#); Symbol: [ER_IB_MSG_779](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_779](#) was added in 8.0.11.
 - Error number: [MY-012605](#); Symbol: [ER_IB_MSG_780](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_780](#) was added in 8.0.11.
 - Error number: [MY-012606](#); Symbol: [ER_IB_MSG_781](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_781](#) was added in 8.0.11.
 - Error number: [MY-012607](#); Symbol: [ER_IB_MSG_782](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_782](#) was added in 8.0.11.

-
- Error number: [MY-012608](#); Symbol: [ER_IB_MSG_783](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_783](#) was added in 8.0.11.
 - Error number: [MY-012609](#); Symbol: [ER_IB_MSG_784](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_784](#) was added in 8.0.11.
 - Error number: [MY-012610](#); Symbol: [ER_IB_MSG_785](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_785](#) was added in 8.0.11.
 - Error number: [MY-012611](#); Symbol: [ER_IB_MSG_786](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_786](#) was added in 8.0.11.
 - Error number: [MY-012612](#); Symbol: [ER_IB_MSG_787](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_787](#) was added in 8.0.11.
 - Error number: [MY-012613](#); Symbol: [ER_IB_MSG_788](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_788](#) was added in 8.0.11.
 - Error number: [MY-012614](#); Symbol: [ER_IB_MSG_789](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_789](#) was added in 8.0.11.
 - Error number: [MY-012615](#); Symbol: [ER_IB_MSG_790](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_790](#) was added in 8.0.11.
 - Error number: [MY-012616](#); Symbol: [ER_IB_MSG_791](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_791](#) was added in 8.0.11.
 - Error number: [MY-012617](#); Symbol: [ER_IB_MSG_792](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_792](#) was added in 8.0.11.
 - Error number: [MY-012618](#); Symbol: [ER_IB_MSG_793](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_793](#) was added in 8.0.11.

-
- Error number: [MY-012619](#); Symbol: [ER_IB_MSG_794](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_794](#) was added in 8.0.11.
 - Error number: [MY-012620](#); Symbol: [ER_IB_MSG_795](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_795](#) was added in 8.0.11.
 - Error number: [MY-012621](#); Symbol: [ER_IB_MSG_796](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_796](#) was added in 8.0.11.
 - Error number: [MY-012622](#); Symbol: [ER_IB_MSG_797](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_797](#) was added in 8.0.11.
 - Error number: [MY-012623](#); Symbol: [ER_IB_MSG_798](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_798](#) was added in 8.0.11.
 - Error number: [MY-012624](#); Symbol: [ER_IB_MSG_799](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_799](#) was added in 8.0.11.
 - Error number: [MY-012625](#); Symbol: [ER_IB_MSG_800](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_800](#) was added in 8.0.11, removed after 8.0.39.
 - Error number: [MY-012626](#); Symbol: [ER_IB_MSG_801](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_801](#) was added in 8.0.11.
 - Error number: [MY-012627](#); Symbol: [ER_IB_MSG_802](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_802](#) was added in 8.0.11.
 - Error number: [MY-012628](#); Symbol: [ER_IB_MSG_803](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_803](#) was added in 8.0.11.
 - Error number: [MY-012629](#); Symbol: [ER_IB_MSG_804](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_804](#) was added in 8.0.11.

-
- Error number: [MY-012630](#); Symbol: [ER_IB_MSG_805](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_805](#) was added in 8.0.11.
 - Error number: [MY-012631](#); Symbol: [ER_IB_MSG_806](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_806](#) was added in 8.0.11.
 - Error number: [MY-012632](#); Symbol: [ER_IB_MSG_807](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_807](#) was added in 8.0.11.
 - Error number: [MY-012633](#); Symbol: [ER_IB_MSG_808](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_808](#) was added in 8.0.11.
 - Error number: [MY-012634](#); Symbol: [ER_IB_MSG_809](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_809](#) was added in 8.0.11.
 - Error number: [MY-012635](#); Symbol: [ER_IB_MSG_810](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_810](#) was added in 8.0.11.
 - Error number: [MY-012636](#); Symbol: [ER_IB_MSG_811](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_811](#) was added in 8.0.11.
 - Error number: [MY-012637](#); Symbol: [ER_IB_MSG_812](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_812](#) was added in 8.0.11.
 - Error number: [MY-012638](#); Symbol: [ER_IB_MSG_813](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_813](#) was added in 8.0.11.
 - Error number: [MY-012639](#); Symbol: [ER_IB_MSG_814](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_814](#) was added in 8.0.11.
 - Error number: [MY-012640](#); Symbol: [ER_IB_MSG_815](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_815](#) was added in 8.0.11.

-
- Error number: [MY-012641](#); Symbol: [ER_IB_MSG_816](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_816](#) was added in 8.0.11.
 - Error number: [MY-012642](#); Symbol: [ER_IB_MSG_817](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_817](#) was added in 8.0.11.
 - Error number: [MY-012643](#); Symbol: [ER_IB_MSG_818](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_818](#) was added in 8.0.11.
 - Error number: [MY-012644](#); Symbol: [ER_IB_MSG_819](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_819](#) was added in 8.0.11.
 - Error number: [MY-012645](#); Symbol: [ER_IB_MSG_820](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_820](#) was added in 8.0.11.
 - Error number: [MY-012646](#); Symbol: [ER_IB_MSG_821](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_821](#) was added in 8.0.11.
 - Error number: [MY-012647](#); Symbol: [ER_IB_MSG_822](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_822](#) was added in 8.0.11.
 - Error number: [MY-012648](#); Symbol: [ER_IB_MSG_823](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_823](#) was added in 8.0.11.
 - Error number: [MY-012649](#); Symbol: [ER_IB_MSG_824](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_824](#) was added in 8.0.11.
 - Error number: [MY-012650](#); Symbol: [ER_IB_MSG_825](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_825](#) was added in 8.0.11.
 - Error number: [MY-012651](#); Symbol: [ER_IB_MSG_826](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_826](#) was added in 8.0.11.

-
- Error number: [MY-012652](#); Symbol: [ER_IB_MSG_827](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_827](#) was added in 8.0.11.
 - Error number: [MY-012653](#); Symbol: [ER_IB_MSG_828](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_828](#) was added in 8.0.11.
 - Error number: [MY-012654](#); Symbol: [ER_IB_MSG_829](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_829](#) was added in 8.0.11.
 - Error number: [MY-012655](#); Symbol: [ER_IB_MSG_830](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_830](#) was added in 8.0.11.
 - Error number: [MY-012656](#); Symbol: [ER_IB_MSG_831](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_831](#) was added in 8.0.11.
 - Error number: [MY-012657](#); Symbol: [ER_IB_MSG_832](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_832](#) was added in 8.0.11.
 - Error number: [MY-012658](#); Symbol: [ER_IB_MSG_833](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_833](#) was added in 8.0.11.
 - Error number: [MY-012659](#); Symbol: [ER_IB_MSG_834](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_834](#) was added in 8.0.11.
 - Error number: [MY-012660](#); Symbol: [ER_IB_MSG_835](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_835](#) was added in 8.0.11.
 - Error number: [MY-012661](#); Symbol: [ER_IB_MSG_836](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_836](#) was added in 8.0.11.
 - Error number: [MY-012662](#); Symbol: [ER_IB_MSG_837](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_837](#) was added in 8.0.11.

-
- Error number: [MY-012663](#); Symbol: [ER_IB_MSG_838](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_838](#) was added in 8.0.11.
 - Error number: [MY-012664](#); Symbol: [ER_IB_MSG_839](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_839](#) was added in 8.0.11.
 - Error number: [MY-012665](#); Symbol: [ER_IB_MSG_840](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_840](#) was added in 8.0.11.
 - Error number: [MY-012666](#); Symbol: [ER_IB_MSG_841](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_841](#) was added in 8.0.11.
 - Error number: [MY-012667](#); Symbol: [ER_IB_MSG_842](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_842](#) was added in 8.0.11.
 - Error number: [MY-012668](#); Symbol: [ER_IB_MSG_843](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_843](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-012668](#); Symbol: [ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA](#); SQLSTATE: [HY000](#)
Message: Can't encrypt data of redo log
[ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA](#) was added in 8.0.33.
 - Error number: [MY-012669](#); Symbol: [ER_IB_MSG_844](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_844](#) was added in 8.0.11.
 - Error number: [MY-012670](#); Symbol: [ER_IB_MSG_845](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_845](#) was added in 8.0.11.
 - Error number: [MY-012671](#); Symbol: [ER_IB_MSG_846](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_846](#) was added in 8.0.11, removed after 8.0.36.

-
- Error number: [MY-012671](#); Symbol: [ER_IB_MSG_CANT_DECRYPT_REDO_LOG](#); SQLSTATE: [HY000](#)
Message: Decryption of redo log block at offset %llu in file %s failed because there's no keyring configured
[ER_IB_MSG_CANT_DECRYPT_REDO_LOG](#) was added in 8.0.37.
 - Error number: [MY-012672](#); Symbol: [ER_IB_MSG_847](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_847](#) was added in 8.0.11.
 - Error number: [MY-012673](#); Symbol: [ER_IB_MSG_848](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_848](#) was added in 8.0.11.
 - Error number: [MY-012674](#); Symbol: [ER_IB_MSG_849](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_849](#) was added in 8.0.11.
 - Error number: [MY-012675](#); Symbol: [ER_IB_MSG_850](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_850](#) was added in 8.0.11.
 - Error number: [MY-012676](#); Symbol: [ER_IB_MSG_851](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_851](#) was added in 8.0.11.
 - Error number: [MY-012677](#); Symbol: [ER_IB_MSG_852](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_852](#) was added in 8.0.11.
 - Error number: [MY-012678](#); Symbol: [ER_IB_MSG_853](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_853](#) was added in 8.0.11.
 - Error number: [MY-012679](#); Symbol: [ER_IB_MSG_854](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_854](#) was added in 8.0.11.
 - Error number: [MY-012680](#); Symbol: [ER_IB_MSG_855](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_855](#) was added in 8.0.11.
 - Error number: [MY-012681](#); Symbol: [ER_IB_MSG_856](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_856](#) was added in 8.0.11.

- Error number: [MY-012682](#); Symbol: [ER_IB_MSG_857](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_857](#) was added in 8.0.11.

- Error number: [MY-012683](#); Symbol: [ER_IB_MSG_858](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_858](#) was added in 8.0.11.

- Error number: [MY-012684](#); Symbol: [ER_IB_MSG_859](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_859](#) was added in 8.0.11.

- Error number: [MY-012685](#); Symbol: [ER_IB_MSG_860](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_860](#) was added in 8.0.11.

- Error number: [MY-012686](#); Symbol: [ER_IB_MSG_861](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_861](#) was added in 8.0.11.

- Error number: [MY-012687](#); Symbol: [ER_IB_MSG_862](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_862](#) was added in 8.0.11.

- Error number: [MY-012688](#); Symbol: [ER_IB_MSG_863](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_863](#) was added in 8.0.11.

- Error number: [MY-012689](#); Symbol: [ER_IB_MSG_864](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_864](#) was added in 8.0.11.

- Error number: [MY-012690](#); Symbol: [ER_IB_MSG_865](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_865](#) was added in 8.0.11.

- Error number: [MY-012691](#); Symbol: [ER_IB_MSG_866](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_866](#) was added in 8.0.11.

- Error number: [MY-012692](#); Symbol: [ER_IB_MSG_867](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_867](#) was added in 8.0.11.

- Error number: [MY-012693](#); Symbol: [ER_IB_MSG_868](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_868](#) was added in 8.0.11.

- Error number: [MY-012694](#); Symbol: [ER_IB_MSG_869](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_869](#) was added in 8.0.11.

- Error number: [MY-012695](#); Symbol: [ER_IB_MSG_870](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_870](#) was added in 8.0.11.

- Error number: [MY-012696](#); Symbol: [ER_IB_MSG_871](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_871](#) was added in 8.0.11.

- Error number: [MY-012697](#); Symbol: [ER_IB_MSG_872](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_872](#) was added in 8.0.11.

- Error number: [MY-012698](#); Symbol: [ER_IB_MSG_873](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_873](#) was added in 8.0.11.

- Error number: [MY-012699](#); Symbol: [ER_IB_MSG_874](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_874](#) was added in 8.0.11.

- Error number: [MY-012700](#); Symbol: [ER_IB_MSG_875](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_875](#) was added in 8.0.11.

- Error number: [MY-012701](#); Symbol: [ER_IB_MSG_876](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_876](#) was added in 8.0.11.

- Error number: [MY-012702](#); Symbol: [ER_IB_MSG_877](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_877](#) was added in 8.0.11.

-
- Error number: [MY-012703](#); Symbol: [ER_IB_MSG_878](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_878](#) was added in 8.0.11.
 - Error number: [MY-012704](#); Symbol: [ER_IB_MSG_879](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_879](#) was added in 8.0.11.
 - Error number: [MY-012705](#); Symbol: [ER_IB_MSG_880](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_880](#) was added in 8.0.11.
 - Error number: [MY-012706](#); Symbol: [ER_IB_MSG_881](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_881](#) was added in 8.0.11.
 - Error number: [MY-012707](#); Symbol: [ER_IB_MSG_882](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_882](#) was added in 8.0.11.
 - Error number: [MY-012708](#); Symbol: [ER_IB_MSG_883](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_883](#) was added in 8.0.11.
 - Error number: [MY-012709](#); Symbol: [ER_IB_MSG_884](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_884](#) was added in 8.0.11.
 - Error number: [MY-012710](#); Symbol: [ER_IB_MSG_885](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_885](#) was added in 8.0.11.
 - Error number: [MY-012711](#); Symbol: [ER_IB_MSG_886](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_886](#) was added in 8.0.11.
 - Error number: [MY-012712](#); Symbol: [ER_IB_MSG_887](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_887](#) was added in 8.0.11.
 - Error number: [MY-012713](#); Symbol: [ER_IB_MSG_888](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_888](#) was added in 8.0.11.

-
- Error number: [MY-012714](#); Symbol: [ER_IB_MSG_889](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_889](#) was added in 8.0.11.
 - Error number: [MY-012715](#); Symbol: [ER_IB_MSG_890](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_890](#) was added in 8.0.11.
 - Error number: [MY-012716](#); Symbol: [ER_IB_MSG_891](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_891](#) was added in 8.0.11.
 - Error number: [MY-012717](#); Symbol: [ER_IB_MSG_892](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_892](#) was added in 8.0.11.
 - Error number: [MY-012718](#); Symbol: [ER_IB_MSG_893](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_893](#) was added in 8.0.11.
 - Error number: [MY-012719](#); Symbol: [ER_IB_MSG_894](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_894](#) was added in 8.0.11.
 - Error number: [MY-012720](#); Symbol: [ER_IB_MSG_895](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_895](#) was added in 8.0.11.
 - Error number: [MY-012721](#); Symbol: [ER_IB_MSG_896](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_896](#) was added in 8.0.11.
 - Error number: [MY-012722](#); Symbol: [ER_IB_MSG_897](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_897](#) was added in 8.0.11.
 - Error number: [MY-012723](#); Symbol: [ER_IB_MSG_898](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_898](#) was added in 8.0.11.
 - Error number: [MY-012724](#); Symbol: [ER_IB_MSG_899](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_899](#) was added in 8.0.11.

-
- Error number: [MY-012725](#); Symbol: [ER_IB_MSG_900](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_900](#) was added in 8.0.11.
 - Error number: [MY-012726](#); Symbol: [ER_IB_MSG_901](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_901](#) was added in 8.0.11.
 - Error number: [MY-012727](#); Symbol: [ER_IB_MSG_902](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_902](#) was added in 8.0.11.
 - Error number: [MY-012728](#); Symbol: [ER_IB_MSG_903](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_903](#) was added in 8.0.11.
 - Error number: [MY-012729](#); Symbol: [ER_IB_MSG_904](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_904](#) was added in 8.0.11.
 - Error number: [MY-012730](#); Symbol: [ER_IB_MSG_905](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_905](#) was added in 8.0.11.
 - Error number: [MY-012731](#); Symbol: [ER_IB_MSG_906](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_906](#) was added in 8.0.11.
 - Error number: [MY-012732](#); Symbol: [ER_IB_MSG_907](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_907](#) was added in 8.0.11.
 - Error number: [MY-012733](#); Symbol: [ER_IB_MSG_908](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_908](#) was added in 8.0.11.
 - Error number: [MY-012734](#); Symbol: [ER_IB_MSG_909](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_909](#) was added in 8.0.11.
 - Error number: [MY-012735](#); Symbol: [ER_IB_MSG_910](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_910](#) was added in 8.0.11.

-
- Error number: [MY-012736](#); Symbol: [ER_IB_MSG_911](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_911](#) was added in 8.0.11.
 - Error number: [MY-012737](#); Symbol: [ER_IB_MSG_912](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_912](#) was added in 8.0.11.
 - Error number: [MY-012738](#); Symbol: [ER_IB_MSG_913](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_913](#) was added in 8.0.11.
 - Error number: [MY-012739](#); Symbol: [ER_IB_MSG_914](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_914](#) was added in 8.0.11.
 - Error number: [MY-012740](#); Symbol: [ER_IB_MSG_915](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_915](#) was added in 8.0.11.
 - Error number: [MY-012741](#); Symbol: [ER_IB_MSG_916](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_916](#) was added in 8.0.11.
 - Error number: [MY-012742](#); Symbol: [ER_IB_MSG_917](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_917](#) was added in 8.0.11.
 - Error number: [MY-012743](#); Symbol: [ER_IB_MSG_918](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_918](#) was added in 8.0.11.
 - Error number: [MY-012744](#); Symbol: [ER_IB_MSG_919](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_919](#) was added in 8.0.11.
 - Error number: [MY-012745](#); Symbol: [ER_IB_MSG_920](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_920](#) was added in 8.0.11.
 - Error number: [MY-012746](#); Symbol: [ER_IB_MSG_921](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_921](#) was added in 8.0.11.

-
- Error number: [MY-012747](#); Symbol: [ER_IB_MSG_922](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_922](#) was added in 8.0.11.
 - Error number: [MY-012748](#); Symbol: [ER_IB_MSG_923](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_923](#) was added in 8.0.11.
 - Error number: [MY-012749](#); Symbol: [ER_IB_MSG_924](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_924](#) was added in 8.0.11.
 - Error number: [MY-012750](#); Symbol: [ER_IB_MSG_925](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_925](#) was added in 8.0.11.
 - Error number: [MY-012751](#); Symbol: [ER_IB_MSG_926](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_926](#) was added in 8.0.11.
 - Error number: [MY-012752](#); Symbol: [ER_IB_MSG_927](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_927](#) was added in 8.0.11.
 - Error number: [MY-012753](#); Symbol: [ER_IB_MSG_928](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_928](#) was added in 8.0.11.
 - Error number: [MY-012754](#); Symbol: [ER_IB_MSG_929](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_929](#) was added in 8.0.11.
 - Error number: [MY-012755](#); Symbol: [ER_IB_MSG_930](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_930](#) was added in 8.0.11.
 - Error number: [MY-012756](#); Symbol: [ER_IB_MSG_931](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_931](#) was added in 8.0.11.
 - Error number: [MY-012757](#); Symbol: [ER_IB_MSG_932](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_932](#) was added in 8.0.11.

-
- Error number: [MY-012758](#); Symbol: [ER_IB_MSG_933](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_933](#) was added in 8.0.11.
 - Error number: [MY-012759](#); Symbol: [ER_IB_MSG_934](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_934](#) was added in 8.0.11.
 - Error number: [MY-012760](#); Symbol: [ER_IB_MSG_935](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_935](#) was added in 8.0.11.
 - Error number: [MY-012761](#); Symbol: [ER_IB_MSG_936](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_936](#) was added in 8.0.11.
 - Error number: [MY-012762](#); Symbol: [ER_IB_MSG_937](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_937](#) was added in 8.0.11.
 - Error number: [MY-012763](#); Symbol: [ER_IB_MSG_938](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_938](#) was added in 8.0.11.
 - Error number: [MY-012764](#); Symbol: [ER_IB_MSG_939](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_939](#) was added in 8.0.11.
 - Error number: [MY-012765](#); Symbol: [ER_IB_MSG_940](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_940](#) was added in 8.0.11.
 - Error number: [MY-012766](#); Symbol: [ER_IB_MSG_941](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_941](#) was added in 8.0.11.
 - Error number: [MY-012767](#); Symbol: [ER_IB_MSG_942](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_942](#) was added in 8.0.11.
 - Error number: [MY-012768](#); Symbol: [ER_IB_MSG_943](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_943](#) was added in 8.0.11.

-
- Error number: [MY-012769](#); Symbol: [ER_IB_MSG_944](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_944](#) was added in 8.0.11.
 - Error number: [MY-012770](#); Symbol: [ER_IB_MSG_945](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_945](#) was added in 8.0.11.
 - Error number: [MY-012771](#); Symbol: [ER_IB_MSG_946](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_946](#) was added in 8.0.11.
 - Error number: [MY-012772](#); Symbol: [ER_IB_MSG_947](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_947](#) was added in 8.0.11.
 - Error number: [MY-012773](#); Symbol: [ER_IB_MSG_948](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_948](#) was added in 8.0.11.
 - Error number: [MY-012774](#); Symbol: [ER_IB_MSG_949](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_949](#) was added in 8.0.11.
 - Error number: [MY-012775](#); Symbol: [ER_IB_MSG_950](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_950](#) was added in 8.0.11.
 - Error number: [MY-012776](#); Symbol: [ER_IB_MSG_951](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_951](#) was added in 8.0.11.
 - Error number: [MY-012777](#); Symbol: [ER_IB_MSG_952](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_952](#) was added in 8.0.11.
 - Error number: [MY-012778](#); Symbol: [ER_IB_MSG_953](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_953](#) was added in 8.0.11.
 - Error number: [MY-012779](#); Symbol: [ER_IB_MSG_954](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_954](#) was added in 8.0.11.

-
- Error number: [MY-012780](#); Symbol: [ER_IB_MSG_955](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_955](#) was added in 8.0.11.
 - Error number: [MY-012781](#); Symbol: [ER_IB_MSG_956](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_956](#) was added in 8.0.11.
 - Error number: [MY-012782](#); Symbol: [ER_IB_MSG_957](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_957](#) was added in 8.0.11.
 - Error number: [MY-012783](#); Symbol: [ER_IB_MSG_958](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_958](#) was added in 8.0.11.
 - Error number: [MY-012784](#); Symbol: [ER_IB_MSG_959](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_959](#) was added in 8.0.11.
 - Error number: [MY-012785](#); Symbol: [ER_IB_MSG_960](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_960](#) was added in 8.0.11.
 - Error number: [MY-012786](#); Symbol: [ER_IB_MSG_961](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_961](#) was added in 8.0.11.
 - Error number: [MY-012787](#); Symbol: [ER_IB_MSG_962](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_962](#) was added in 8.0.11.
 - Error number: [MY-012788](#); Symbol: [ER_IB_MSG_963](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_963](#) was added in 8.0.11.
 - Error number: [MY-012789](#); Symbol: [ER_IB_MSG_964](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_964](#) was added in 8.0.11.
 - Error number: [MY-012790](#); Symbol: [ER_IB_MSG_965](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_965](#) was added in 8.0.11.

-
- Error number: [MY-012791](#); Symbol: [ER_IB_MSG_966](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_966](#) was added in 8.0.11.
 - Error number: [MY-012792](#); Symbol: [ER_IB_MSG_967](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_967](#) was added in 8.0.11.
 - Error number: [MY-012793](#); Symbol: [ER_IB_MSG_968](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_968](#) was added in 8.0.11.
 - Error number: [MY-012794](#); Symbol: [ER_IB_MSG_969](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_969](#) was added in 8.0.11.
 - Error number: [MY-012795](#); Symbol: [ER_IB_MSG_970](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_970](#) was added in 8.0.11.
 - Error number: [MY-012796](#); Symbol: [ER_IB_MSG_971](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_971](#) was added in 8.0.11.
 - Error number: [MY-012797](#); Symbol: [ER_IB_MSG_972](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_972](#) was added in 8.0.11.
 - Error number: [MY-012798](#); Symbol: [ER_IB_MSG_973](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_973](#) was added in 8.0.11.
 - Error number: [MY-012799](#); Symbol: [ER_IB_MSG_974](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_974](#) was added in 8.0.11.
 - Error number: [MY-012800](#); Symbol: [ER_IB_MSG_975](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_975](#) was added in 8.0.11.
 - Error number: [MY-012801](#); Symbol: [ER_IB_MSG_976](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_976](#) was added in 8.0.11.

-
- Error number: [MY-012802](#); Symbol: [ER_IB_MSG_977](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_977](#) was added in 8.0.11.
 - Error number: [MY-012803](#); Symbol: [ER_IB_MSG_978](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_978](#) was added in 8.0.11.
 - Error number: [MY-012804](#); Symbol: [ER_IB_MSG_979](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_979](#) was added in 8.0.11.
 - Error number: [MY-012805](#); Symbol: [ER_IB_MSG_980](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_980](#) was added in 8.0.11.
 - Error number: [MY-012806](#); Symbol: [ER_IB_MSG_981](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_981](#) was added in 8.0.11.
 - Error number: [MY-012807](#); Symbol: [ER_IB_MSG_982](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_982](#) was added in 8.0.11.
 - Error number: [MY-012808](#); Symbol: [ER_IB_MSG_983](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_983](#) was added in 8.0.11.
 - Error number: [MY-012809](#); Symbol: [ER_IB_MSG_984](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_984](#) was added in 8.0.11.
 - Error number: [MY-012810](#); Symbol: [ER_IB_MSG_985](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_985](#) was added in 8.0.11.
 - Error number: [MY-012811](#); Symbol: [ER_IB_MSG_986](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_986](#) was added in 8.0.11.
 - Error number: [MY-012812](#); Symbol: [ER_IB_MSG_987](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_987](#) was added in 8.0.11.

-
- Error number: [MY-012813](#); Symbol: [ER_IB_MSG_988](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_988](#) was added in 8.0.11.
 - Error number: [MY-012814](#); Symbol: [ER_IB_MSG_989](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_989](#) was added in 8.0.11.
 - Error number: [MY-012815](#); Symbol: [ER_IB_MSG_990](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_990](#) was added in 8.0.11.
 - Error number: [MY-012816](#); Symbol: [ER_IB_MSG_991](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_991](#) was added in 8.0.11.
 - Error number: [MY-012817](#); Symbol: [ER_IB_MSG_992](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_992](#) was added in 8.0.11.
 - Error number: [MY-012818](#); Symbol: [ER_IB_MSG_993](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_993](#) was added in 8.0.11.
 - Error number: [MY-012819](#); Symbol: [ER_IB_MSG_994](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_994](#) was added in 8.0.11.
 - Error number: [MY-012820](#); Symbol: [ER_IB_MSG_995](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_995](#) was added in 8.0.11.
 - Error number: [MY-012821](#); Symbol: [ER_IB_MSG_996](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_996](#) was added in 8.0.11.
 - Error number: [MY-012822](#); Symbol: [ER_IB_MSG_997](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_997](#) was added in 8.0.11.
 - Error number: [MY-012823](#); Symbol: [ER_IB_MSG_998](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_998](#) was added in 8.0.11.

-
- Error number: [MY-012824](#); Symbol: [ER_IB_MSG_999](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_999](#) was added in 8.0.11.
 - Error number: [MY-012825](#); Symbol: [ER_IB_MSG_1000](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1000](#) was added in 8.0.11.
 - Error number: [MY-012826](#); Symbol: [ER_IB_MSG_1001](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1001](#) was added in 8.0.11.
 - Error number: [MY-012827](#); Symbol: [ER_IB_MSG_1002](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1002](#) was added in 8.0.11.
 - Error number: [MY-012828](#); Symbol: [ER_IB_MSG_1003](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1003](#) was added in 8.0.11.
 - Error number: [MY-012829](#); Symbol: [ER_IB_MSG_1004](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1004](#) was added in 8.0.11.
 - Error number: [MY-012830](#); Symbol: [ER_IB_MSG_1005](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1005](#) was added in 8.0.11.
 - Error number: [MY-012831](#); Symbol: [ER_IB_MSG_1006](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1006](#) was added in 8.0.11.
 - Error number: [MY-012832](#); Symbol: [ER_IB_MSG_1007](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1007](#) was added in 8.0.11.
 - Error number: [MY-012833](#); Symbol: [ER_IB_MSG_1008](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1008](#) was added in 8.0.11.
 - Error number: [MY-012834](#); Symbol: [ER_IB_MSG_1009](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1009](#) was added in 8.0.11.

-
- Error number: [MY-012835](#); Symbol: [ER_IB_MSG_1010](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1010](#) was added in 8.0.11.
 - Error number: [MY-012836](#); Symbol: [ER_IB_MSG_1011](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1011](#) was added in 8.0.11.
 - Error number: [MY-012837](#); Symbol: [ER_IB_MSG_1012](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1012](#) was added in 8.0.11.
 - Error number: [MY-012838](#); Symbol: [ER_IB_MSG_1013](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1013](#) was added in 8.0.11.
 - Error number: [MY-012839](#); Symbol: [ER_IB_MSG_1014](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1014](#) was added in 8.0.11.
 - Error number: [MY-012840](#); Symbol: [ER_IB_MSG_1015](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1015](#) was added in 8.0.11.
 - Error number: [MY-012841](#); Symbol: [ER_IB_MSG_1016](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1016](#) was added in 8.0.11.
 - Error number: [MY-012842](#); Symbol: [ER_IB_MSG_1017](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1017](#) was added in 8.0.11.
 - Error number: [MY-012843](#); Symbol: [ER_IB_MSG_1018](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1018](#) was added in 8.0.11.
 - Error number: [MY-012844](#); Symbol: [ER_IB_MSG_1019](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1019](#) was added in 8.0.11.
 - Error number: [MY-012845](#); Symbol: [ER_IB_MSG_1020](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1020](#) was added in 8.0.11.

-
- Error number: [MY-012846](#); Symbol: [ER_IB_MSG_1021](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1021](#) was added in 8.0.11.
 - Error number: [MY-012847](#); Symbol: [ER_IB_MSG_1022](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1022](#) was added in 8.0.11.
 - Error number: [MY-012848](#); Symbol: [ER_IB_MSG_1023](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1023](#) was added in 8.0.11.
 - Error number: [MY-012849](#); Symbol: [ER_IB_MSG_1024](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1024](#) was added in 8.0.11.
 - Error number: [MY-012850](#); Symbol: [ER_IB_MSG_1025](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1025](#) was added in 8.0.11.
 - Error number: [MY-012851](#); Symbol: [ER_IB_MSG_1026](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1026](#) was added in 8.0.11.
 - Error number: [MY-012852](#); Symbol: [ER_IB_MSG_1027](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1027](#) was added in 8.0.11.
 - Error number: [MY-012853](#); Symbol: [ER_IB_MSG_1028](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1028](#) was added in 8.0.11.
 - Error number: [MY-012854](#); Symbol: [ER_IB_MSG_1029](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1029](#) was added in 8.0.11.
 - Error number: [MY-012855](#); Symbol: [ER_IB_MSG_1030](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1030](#) was added in 8.0.11.
 - Error number: [MY-012856](#); Symbol: [ER_IB_MSG_1031](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1031](#) was added in 8.0.11.

-
- Error number: [MY-012857](#); Symbol: [ER_IB_MSG_1032](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1032](#) was added in 8.0.11.
 - Error number: [MY-012858](#); Symbol: [ER_IB_MSG_1033](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1033](#) was added in 8.0.11.
 - Error number: [MY-012859](#); Symbol: [ER_IB_MSG_1034](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1034](#) was added in 8.0.11.
 - Error number: [MY-012860](#); Symbol: [ER_IB_MSG_1035](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1035](#) was added in 8.0.11.
 - Error number: [MY-012861](#); Symbol: [ER_IB_MSG_1036](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1036](#) was added in 8.0.11.
 - Error number: [MY-012862](#); Symbol: [ER_IB_MSG_1037](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1037](#) was added in 8.0.11.
 - Error number: [MY-012863](#); Symbol: [ER_IB_MSG_1038](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1038](#) was added in 8.0.11.
 - Error number: [MY-012864](#); Symbol: [ER_IB_MSG_1039](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1039](#) was added in 8.0.11.
 - Error number: [MY-012865](#); Symbol: [ER_IB_MSG_1040](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1040](#) was added in 8.0.11.
 - Error number: [MY-012866](#); Symbol: [ER_IB_MSG_1041](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1041](#) was added in 8.0.11.
 - Error number: [MY-012867](#); Symbol: [ER_IB_MSG_1042](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1042](#) was added in 8.0.11.

-
- Error number: [MY-012868](#); Symbol: [ER_IB_MSG_1043](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1043](#) was added in 8.0.11.
 - Error number: [MY-012869](#); Symbol: [ER_IB_MSG_1044](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1044](#) was added in 8.0.11.
 - Error number: [MY-012870](#); Symbol: [ER_IB_MSG_1045](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1045](#) was added in 8.0.11.
 - Error number: [MY-012871](#); Symbol: [ER_IB_MSG_1046](#); SQLSTATE: [HY000](#)
Message: Old log sequence number %llu was greater than the new log sequence number %llu.
Please submit a bug report to <http://bugs.mysql.com>
[ER_IB_MSG_1046](#) was added in 8.0.11.
 - Error number: [MY-012872](#); Symbol: [ER_IB_MSG_1047](#); SQLSTATE: [HY000](#)
Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.
[ER_IB_MSG_1047](#) was added in 8.0.11.
 - Error number: [MY-012873](#); Symbol: [ER_IB_MSG_1048](#); SQLSTATE: [HY000](#)
Message: Waiting for %llu table(s) to be dropped
[ER_IB_MSG_1048](#) was added in 8.0.11.
 - Error number: [MY-012874](#); Symbol: [ER_IB_MSG_1049](#); SQLSTATE: [HY000](#)
Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu
[ER_IB_MSG_1049](#) was added in 8.0.11.
 - Error number: [MY-012875](#); Symbol: [ER_IB_MSG_1050](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace(s) to be encrypted since --innodb_undo_tablespaces=0.
[ER_IB_MSG_1050](#) was added in 8.0.11, removed after 8.0.15.
 - Error number: [MY-012876](#); Symbol: [ER_IB_MSG_1051](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.
[ER_IB_MSG_1051](#) was added in 8.0.11.
 - Error number: [MY-012877](#); Symbol: [ER_IB_MSG_1052](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace '%s' to be encrypted.
[ER_IB_MSG_1052](#) was added in 8.0.11.
 - Error number: [MY-012878](#); Symbol: [ER_IB_MSG_1053](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.

[ER_IB_MSG_1053](#) was added in 8.0.11.

- Error number: [MY-012879](#); Symbol: [ER_IB_MSG_1054](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s

[ER_IB_MSG_1054](#) was added in 8.0.11.

- Error number: [MY-012880](#); Symbol: [ER_IB_MSG_1055](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

[ER_IB_MSG_1055](#) was added in 8.0.11.

- Error number: [MY-012881](#); Symbol: [ER_IB_MSG_1056](#); SQLSTATE: [HY000](#)

Message: Can't rotate encryption on undo tablespace '%s'.

[ER_IB_MSG_1056](#) was added in 8.0.11.

- Error number: [MY-012882](#); Symbol: [ER_IB_MSG_1057](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

[ER_IB_MSG_1057](#) was added in 8.0.11.

- Error number: [MY-012883](#); Symbol: [ER_IB_MSG_1058](#); SQLSTATE: [HY000](#)

Message: `os_file_get_status()` failed on '%s'. Can't determine file permissions.

[ER_IB_MSG_1058](#) was added in 8.0.11.

- Error number: [MY-012884](#); Symbol: [ER_IB_MSG_1059](#); SQLSTATE: [HY000](#)

Message: %s can't be opened in %s mode.

[ER_IB_MSG_1059](#) was added in 8.0.11.

- Error number: [MY-012885](#); Symbol: [ER_IB_MSG_1060](#); SQLSTATE: [HY000](#)

Message: '%s' not a regular file.

[ER_IB_MSG_1060](#) was added in 8.0.11.

- Error number: [MY-012886](#); Symbol: [ER_IB_MSG_1061](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

[ER_IB_MSG_1061](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012886](#); Symbol: [ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

[ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED](#) was added in 8.0.30.

- Error number: [MY-012887](#); Symbol: [ER_IB_MSG_1062](#); SQLSTATE: [HY000](#)

Message: Setting log file %s size to %llu MB. Progress : %u%%

[ER_IB_MSG_1062](#) was added in 8.0.11, removed after 8.0.29.

-
- Error number: [MY-012887](#); Symbol: [ER_IB_MSG_FILE_RESIZE](#); SQLSTATE: [HY000](#)
Message: Setting file %s size to %llu MB. Progress : %u%%
[ER_IB_MSG_FILE_RESIZE](#) was added in 8.0.30.
 - Error number: [MY-012888](#); Symbol: [ER_IB_MSG_1063](#); SQLSTATE: [HY000](#)
Message: Cannot set log file %s to size %llu MB
[ER_IB_MSG_1063](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012888](#); Symbol: [ER_IB_MSG_LOG_FILE_RESIZE_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot resize redo log file %s to %llu MB (%s)
[ER_IB_MSG_LOG_FILE_RESIZE_FAILED](#) was added in 8.0.30.
 - Error number: [MY-012889](#); Symbol: [ER_IB_MSG_1064](#); SQLSTATE: [HY000](#)
Message: Cannot create log files in read-only mode
[ER_IB_MSG_1064](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012889](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot create redo log files in read-only mode (--innodb-read-only).
[ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE](#) was added in 8.0.30.
 - Error number: [MY-012890](#); Symbol: [ER_IB_MSG_1065](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled, but the keyring is not loaded.
[ER_IB_MSG_1065](#) was added in 8.0.11.
 - Error number: [MY-012891](#); Symbol: [ER_IB_MSG_1066](#); SQLSTATE: [HY000](#)
Message: Cannot create file for log file %s.
[ER_IB_MSG_1066](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012891](#); Symbol: [ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create redo log file %s (error: %d) for start LSN %llu
[ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED](#) was added in 8.0.30.
 - Error number: [MY-012892](#); Symbol: [ER_IB_MSG_1067](#); SQLSTATE: [HY000](#)
Message: Renaming log file %s to %s
[ER_IB_MSG_1067](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012893](#); Symbol: [ER_IB_MSG_1068](#); SQLSTATE: [HY000](#)
Message: New log files created, LSN=%llu
[ER_IB_MSG_1068](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012893](#); Symbol: [ER_IB_MSG_LOG_FILES_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: New redo log files created, LSN=%llu

[ER_IB_MSG_LOG_FILES_INITIALIZED](#) was added in 8.0.30.

- Error number: [MY-012894](#); Symbol: [ER_IB_MSG_1069](#); SQLSTATE: [HY000](#)

Message: Unable to open '%s'.

[ER_IB_MSG_1069](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-012894](#); Symbol: [ER_IB_MSG_LOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to open '%s' (error: %d).

[ER_IB_MSG_LOG_FILE_OPEN_FAILED](#) was added in 8.0.30.

- Error number: [MY-012895](#); Symbol: [ER_IB_MSG_1070](#); SQLSTATE: [HY000](#)

Message: Cannot create construction log file '%s' for undo tablespace '%s'.

[ER_IB_MSG_1070](#) was added in 8.0.11.

- Error number: [MY-012896](#); Symbol: [ER_IB_MSG_1071](#); SQLSTATE: [HY000](#)

Message: Creating UNDO Tablespace %s

[ER_IB_MSG_1071](#) was added in 8.0.11.

- Error number: [MY-012897](#); Symbol: [ER_IB_MSG_1072](#); SQLSTATE: [HY000](#)

Message: Setting file %s size to %llu MB

[ER_IB_MSG_1072](#) was added in 8.0.11.

- Error number: [MY-012898](#); Symbol: [ER_IB_MSG_1073](#); SQLSTATE: [HY000](#)

Message: Physically writing the file full

[ER_IB_MSG_1073](#) was added in 8.0.11.

- Error number: [MY-012899](#); Symbol: [ER_IB_MSG_1074](#); SQLSTATE: [HY000](#)

Message: Error in creating %s: probably out of disk space

[ER_IB_MSG_1074](#) was added in 8.0.11.

- Error number: [MY-012900](#); Symbol: [ER_IB_MSG_1075](#); SQLSTATE: [HY000](#)

Message: Can't set encryption metadata for space %s

[ER_IB_MSG_1075](#) was added in 8.0.11.

- Error number: [MY-012901](#); Symbol: [ER_IB_MSG_1076](#); SQLSTATE: [HY000](#)

Message: Cannot read first page of '%s' - %s

[ER_IB_MSG_1076](#) was added in 8.0.11.

- Error number: [MY-012902](#); Symbol: [ER_IB_MSG_1077](#); SQLSTATE: [HY000](#)

Message: Undo tablespace number %lu was being truncated when mysqld quit.

[ER_IB_MSG_1077](#) was added in 8.0.11.

-
- Error number: [MY-012903](#); Symbol: [ER_IB_MSG_1078](#); SQLSTATE: [HY000](#)
Message: Cannot recover a truncated undo tablespace in read-only mode
[ER_IB_MSG_1078](#) was added in 8.0.11.
 - Error number: [MY-012904](#); Symbol: [ER_IB_MSG_1079](#); SQLSTATE: [HY000](#)
Message: Reconstructing undo tablespace number %lu.
[ER_IB_MSG_1079](#) was added in 8.0.11.
 - Error number: [MY-012905](#); Symbol: [ER_IB_MSG_1080](#); SQLSTATE: [HY000](#)
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb_undo_directory?
[ER_IB_MSG_1080](#) was added in 8.0.11.
 - Error number: [MY-012906](#); Symbol: [ER_IB_MSG_1081](#); SQLSTATE: [HY000](#)
Message: UNDO tablespace %s must be %s
[ER_IB_MSG_1081](#) was added in 8.0.11.
 - Error number: [MY-012907](#); Symbol: [ER_IB_MSG_1082](#); SQLSTATE: [HY000](#)
Message: Error creating file for %s
[ER_IB_MSG_1082](#) was added in 8.0.11.
 - Error number: [MY-012908](#); Symbol: [ER_IB_MSG_1083](#); SQLSTATE: [HY000](#)
Message: Error reading encryption for %s
[ER_IB_MSG_1083](#) was added in 8.0.11.
 - Error number: [MY-012909](#); Symbol: [ER_IB_MSG_1084](#); SQLSTATE: [HY000](#)
Message: Unable to open undo tablespace number %lu
[ER_IB_MSG_1084](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-012909](#); Symbol: [ER_IB_MSG_CANNOT_OPEN_57_UNDO](#); SQLSTATE: [HY000](#)
Message: Unable to open undo tablespace number %lu
[ER_IB_MSG_CANNOT_OPEN_57_UNDO](#) was added in 8.0.21.
 - Error number: [MY-012910](#); Symbol: [ER_IB_MSG_1085](#); SQLSTATE: [HY000](#)
Message: Opened %llu existing undo tablespaces.
[ER_IB_MSG_1085](#) was added in 8.0.11.
 - Error number: [MY-012911](#); Symbol: [ER_IB_MSG_1086](#); SQLSTATE: [HY000](#)
Message: Cannot create undo tablespaces since innodb_%s has been set. Using %llu existing undo tablespaces.
[ER_IB_MSG_1086](#) was added in 8.0.11.

-
- Error number: [MY-012912](#); Symbol: [ER_IB_MSG_1087](#); SQLSTATE: [HY000](#)
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.
[ER_IB_MSG_1087](#) was added in 8.0.11.
 - Error number: [MY-012913](#); Symbol: [ER_IB_MSG_1088](#); SQLSTATE: [HY000](#)
Message: Could not create undo tablespace '%s'.
[ER_IB_MSG_1088](#) was added in 8.0.11.
 - Error number: [MY-012914](#); Symbol: [ER_IB_MSG_1089](#); SQLSTATE: [HY000](#)
Message: Error %d - %s - opening newly created undo tablespace '%s'.
[ER_IB_MSG_1089](#) was added in 8.0.11.
 - Error number: [MY-012915](#); Symbol: [ER_IB_MSG_1090](#); SQLSTATE: [HY000](#)
Message: Created %llu undo tablespaces.
[ER_IB_MSG_1090](#) was added in 8.0.11.
 - Error number: [MY-012916](#); Symbol: [ER_IB_MSG_1091](#); SQLSTATE: [HY000](#)
Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly
[ER_IB_MSG_1091](#) was added in 8.0.11.
 - Error number: [MY-012917](#); Symbol: [ER_IB_MSG_1092](#); SQLSTATE: [HY000](#)
Message: Encryption is enabled for undo tablespace number %lu.
[ER_IB_MSG_1092](#) was added in 8.0.11.
 - Error number: [MY-012918](#); Symbol: [ER_IB_MSG_1093](#); SQLSTATE: [HY000](#)
Message: Unable to initialize the header page in undo tablespace number %lu.
[ER_IB_MSG_1093](#) was added in 8.0.11.
 - Error number: [MY-012919](#); Symbol: [ER_IB_MSG_1094](#); SQLSTATE: [HY000](#)
Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.
[ER_IB_MSG_1094](#) was added in 8.0.11.
 - Error number: [MY-012920](#); Symbol: [ER_IB_MSG_1095](#); SQLSTATE: [HY000](#)
Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.
[ER_IB_MSG_1095](#) was added in 8.0.11.
 - Error number: [MY-012921](#); Symbol: [ER_IB_MSG_1096](#); SQLSTATE: [HY000](#)
Message: Deleting %llu new independent undo tablespaces that we just created.
[ER_IB_MSG_1096](#) was added in 8.0.11.

-
- Error number: [MY-012922](#); Symbol: [ER_IB_MSG_1097](#); SQLSTATE: [HY000](#)
Message: Waiting for purge to start
[ER_IB_MSG_1097](#) was added in 8.0.11.
 - Error number: [MY-012923](#); Symbol: [ER_IB_MSG_1098](#); SQLSTATE: [HY000](#)
Message: Creating shared tablespace for temporary tables
[ER_IB_MSG_1098](#) was added in 8.0.11.
 - Error number: [MY-012924](#); Symbol: [ER_IB_MSG_1099](#); SQLSTATE: [HY000](#)
Message: The %s data file must be writable!
[ER_IB_MSG_1099](#) was added in 8.0.11.
 - Error number: [MY-012925](#); Symbol: [ER_IB_MSG_1100](#); SQLSTATE: [HY000](#)
Message: Could not create the shared %s.
[ER_IB_MSG_1100](#) was added in 8.0.11.
 - Error number: [MY-012926](#); Symbol: [ER_IB_MSG_1101](#); SQLSTATE: [HY000](#)
Message: Unable to create the shared %s.
[ER_IB_MSG_1101](#) was added in 8.0.11.
 - Error number: [MY-012927](#); Symbol: [ER_IB_MSG_1102](#); SQLSTATE: [HY000](#)
Message: The %s data file cannot be re-opened after check_file_spec() succeeded!
[ER_IB_MSG_1102](#) was added in 8.0.11.
 - Error number: [MY-012928](#); Symbol: [ER_IB_MSG_1103](#); SQLSTATE: [HY000](#)
Message: %d threads created by InnoDB had not exited at shutdown!
[ER_IB_MSG_1103](#) was added in 8.0.11.
 - Error number: [MY-012929](#); Symbol: [ER_IB_MSG_1104](#); SQLSTATE: [HY000](#)
Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.
[ER_IB_MSG_1104](#) was added in 8.0.11.
 - Error number: [MY-012930](#); Symbol: [ER_IB_MSG_1105](#); SQLSTATE: [HY000](#)
Message: Plugin initialization aborted %swith error %s.
[ER_IB_MSG_1105](#) was added in 8.0.11.
 - Error number: [MY-012931](#); Symbol: [ER_IB_MSG_1106](#); SQLSTATE: [HY000](#)
Message: Waiting for %llu buffer page I/Os to complete
[ER_IB_MSG_1106](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012931](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO](#); SQLSTATE: [HY000](#)
Message: Waiting for %zu buffer page I/Os to complete.

[ER_IB_MSG_BUF_PENDING_IO](#) was added in 8.0.30.

- Error number: [MY-012932](#); Symbol: [ER_IB_MSG_1107](#); SQLSTATE: [HY000](#)

Message: PUNCH HOLE support available

[ER_IB_MSG_1107](#) was added in 8.0.11.

- Error number: [MY-012933](#); Symbol: [ER_IB_MSG_1108](#); SQLSTATE: [HY000](#)

Message: PUNCH HOLE support not available

[ER_IB_MSG_1108](#) was added in 8.0.11.

- Error number: [MY-012934](#); Symbol: [ER_IB_MSG_1109](#); SQLSTATE: [HY000](#)

Message: Size of InnoDB's ulint is %zu but size of void* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.

[ER_IB_MSG_1109](#) was added in 8.0.11.

- Error number: [MY-012935](#); Symbol: [ER_IB_MSG_1110](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished in read-only mode.

[ER_IB_MSG_1110](#) was added in 8.0.11.

- Error number: [MY-012936](#); Symbol: [ER_IB_MSG_1111](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished with innodb_force_recovery > 0

[ER_IB_MSG_1111](#) was added in 8.0.11.

- Error number: [MY-012937](#); Symbol: [ER_IB_MSG_1112](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1112](#) was added in 8.0.11.

- Error number: [MY-012938](#); Symbol: [ER_IB_MSG_1113](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1113](#) was added in 8.0.11.

- Error number: [MY-012939](#); Symbol: [ER_IB_MSG_1114](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1114](#) was added in 8.0.11.

- Error number: [MY-012940](#); Symbol: [ER_IB_MSG_1115](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1115](#) was added in 8.0.11.

- Error number: [MY-012941](#); Symbol: [ER_IB_MSG_1116](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1116](#) was added in 8.0.11.

- Error number: [MY-012942](#); Symbol: [ER_IB_MSG_1117](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1117](#) was added in 8.0.11.

- Error number: [MY-012943](#); Symbol: [ER_IB_MSG_1118](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1118](#) was added in 8.0.11, removed after 8.0.22.

- Error number: [MY-012944](#); Symbol: [ER_IB_MSG_1119](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1119](#) was added in 8.0.11.

- Error number: [MY-012945](#); Symbol: [ER_IB_MSG_1120](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1120](#) was added in 8.0.11.

- Error number: [MY-012946](#); Symbol: [ER_IB_MSG_1121](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1121](#) was added in 8.0.11.

- Error number: [MY-012947](#); Symbol: [ER_IB_MSG_1122](#); SQLSTATE: [HY000](#)

Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw_lock violation under high thread concurrency. This may cause a hang.

[ER_IB_MSG_1122](#) was added in 8.0.11.

- Error number: [MY-012948](#); Symbol: [ER_IB_MSG_1123](#); SQLSTATE: [HY000](#)

Message: Compressed tables use zlib %s

[ER_IB_MSG_1123](#) was added in 8.0.11.

- Error number: [MY-012949](#); Symbol: [ER_IB_MSG_1124](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1124](#) was added in 8.0.11.

- Error number: [MY-012950](#); Symbol: [ER_IB_MSG_1125](#); SQLSTATE: [HY000](#)

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call `server_init()` more than once during the process lifetime.

[ER_IB_MSG_1125](#) was added in 8.0.11.

- Error number: [MY-012951](#); Symbol: [ER_IB_MSG_1126](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1126](#) was added in 8.0.11.

- Error number: [MY-012952](#); Symbol: [ER_IB_MSG_1127](#); SQLSTATE: [HY000](#)

Message: Unable to create monitor file %s: %s

`ER_IB_MSG_1127` was added in 8.0.11.

- Error number: `MY-012953`; Symbol: `ER_IB_MSG_1128`; SQLSTATE: `HY000`

Message: Disabling background ibuf IO read threads.

`ER_IB_MSG_1128` was added in 8.0.11.

- Error number: `MY-012954`; Symbol: `ER_IB_MSG_1129`; SQLSTATE: `HY000`

Message: Cannot initialize AIO sub-system

`ER_IB_MSG_1129` was added in 8.0.11.

- Error number: `MY-012955`; Symbol: `ER_IB_MSG_1130`; SQLSTATE: `HY000`

Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c

`ER_IB_MSG_1130` was added in 8.0.11.

- Error number: `MY-012956`; Symbol: `ER_IB_MSG_1131`; SQLSTATE: `HY000`

Message: Cannot allocate memory for the buffer pool

`ER_IB_MSG_1131` was added in 8.0.11.

- Error number: `MY-012957`; Symbol: `ER_IB_MSG_1132`; SQLSTATE: `HY000`

Message: Completed initialization of buffer pool

`ER_IB_MSG_1132` was added in 8.0.11.

- Error number: `MY-012958`; Symbol: `ER_IB_MSG_1133`; SQLSTATE: `HY000`

Message: Small buffer pool size (%lluM), the `flst_validate()` debug function can cause a deadlock if the buffer pool fills up.

`ER_IB_MSG_1133` was added in 8.0.11.

- Error number: `MY-012959`; Symbol: `ER_IB_MSG_1134`; SQLSTATE: `HY000`

Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit `innodb_data_file_path` in `my.cnf` back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!

`ER_IB_MSG_1134` was added in 8.0.11.

- Error number: `MY-012960`; Symbol: `ER_IB_MSG_1135`; SQLSTATE: `HY000`

Message: Cannot create log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_1135` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012960`; Symbol:

`ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED`; SQLSTATE: `HY000`

Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

`ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED` was added in 8.0.30.

-
- Error number: [MY-012961](#); Symbol: [ER_IB_MSG_1136](#); SQLSTATE: [HY000](#)
Message: Only one log file found
[ER_IB_MSG_1136](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012961](#); Symbol: [ER_IB_MSG_LOG_FILES_INVALID_SET](#); SQLSTATE: [HY000](#)
Message: Only one redo log file found
[ER_IB_MSG_LOG_FILES_INVALID_SET](#) was added in 8.0.30.
 - Error number: [MY-012962](#); Symbol: [ER_IB_MSG_1137](#); SQLSTATE: [HY000](#)
Message: Log file %s size %llu is not a multiple of innodb_page_size
[ER_IB_MSG_1137](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012962](#); Symbol: [ER_IB_MSG_LOG_FILE_SIZE_INVALID](#); SQLSTATE: [HY000](#)
Message: The redo log file %s size %llu is not a multiple of innodb_page_size
[ER_IB_MSG_LOG_FILE_SIZE_INVALID](#) was added in 8.0.30.
 - Error number: [MY-012963](#); Symbol: [ER_IB_MSG_1138](#); SQLSTATE: [HY000](#)
Message: Log file %s is of different size %llu bytes than other log files %llu bytes!
[ER_IB_MSG_1138](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012963](#); Symbol: [ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!
[ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES](#) was added in 8.0.30.
 - Error number: [MY-012964](#); Symbol: [ER_IB_MSG_1139](#); SQLSTATE: [HY000](#)
Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)
[ER_IB_MSG_1139](#) was added in 8.0.11.
 - Error number: [MY-012965](#); Symbol: [ER_IB_MSG_1140](#); SQLSTATE: [HY000](#)
Message: The log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!
[ER_IB_MSG_1140](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-012965](#); Symbol: [ER_IB_MSG_RECOVERY_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!
[ER_IB_MSG_RECOVERY_CORRUPT](#) was added in 8.0.30.
 - Error number: [MY-012966](#); Symbol: [ER_IB_MSG_1141](#); SQLSTATE: [HY000](#)
Message: Cannot resize log files in read-only mode.

`ER_IB_MSG_1141` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012966`; Symbol:

`ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot resize redo log files in read-only mode. Provide `--innodb_redo_log_capacity >= %lluMB` or start without `--innodb-read-only`.

`ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE` was added in 8.0.30, removed after 8.0.32.

- Error number: `MY-012967`; Symbol: `ER_IB_MSG_1142`; SQLSTATE: `HY000`

Message: Cannot open DD tablespace.

`ER_IB_MSG_1142` was added in 8.0.11.

- Error number: `MY-012968`; Symbol: `ER_IB_MSG_1143`; SQLSTATE: `HY000`

Message: Starting to delete and rewrite log files.

`ER_IB_MSG_1143` was added in 8.0.11, removed after 8.0.29.

- Error number: `MY-012968`; Symbol: `ER_IB_MSG_LOG_FILES_REWRITING`; SQLSTATE: `HY000`

Message: Starting to delete and rewrite redo log files.

`ER_IB_MSG_LOG_FILES_REWRITING` was added in 8.0.30.

- Error number: `MY-012969`; Symbol: `ER_IB_MSG_1144`; SQLSTATE: `HY000`

Message: Undo from 5.7 found. It will be purged

`ER_IB_MSG_1144` was added in 8.0.11.

- Error number: `MY-012970`; Symbol: `ER_IB_MSG_1145`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1145` was added in 8.0.11.

- Error number: `MY-012971`; Symbol: `ER_IB_MSG_1146`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1146` was added in 8.0.11.

- Error number: `MY-012972`; Symbol: `ER_IB_MSG_1147`; SQLSTATE: `HY000`

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages

`ER_IB_MSG_1147` was added in 8.0.11.

- Error number: `MY-012973`; Symbol: `ER_IB_MSG_1148`; SQLSTATE: `HY000`

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited `innodb_data_file_path` in `my.cnf` in an inappropriate way, removing `ibdata` files from there? You can set `innodb_force_recovery=1` in `my.cnf` to force a startup if you are trying to recover a badly corrupt database.

`ER_IB_MSG_1148` was added in 8.0.11.

- Error number: `MY-012974`; Symbol: `ER_IB_MSG_1149`; SQLSTATE: `HY000`

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages

[ER_IB_MSG_1149](#) was added in 8.0.11.

- Error number: [MY-012975](#); Symbol: [ER_IB_MSG_1150](#); SQLSTATE: [HY000](#)

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.

[ER_IB_MSG_1150](#) was added in 8.0.11.

- Error number: [MY-012976](#); Symbol: [ER_IB_MSG_1151](#); SQLSTATE: [HY000](#)

Message: %s started; log sequence number %llu

[ER_IB_MSG_1151](#) was added in 8.0.11.

- Error number: [MY-012977](#); Symbol: [ER_IB_MSG_1152](#); SQLSTATE: [HY000](#)

Message: Waiting for purge to complete

[ER_IB_MSG_1152](#) was added in 8.0.11.

- Error number: [MY-012978](#); Symbol: [ER_IB_MSG_1153](#); SQLSTATE: [HY000](#)

Message: Waiting for dict_stats_thread to exit

[ER_IB_MSG_1153](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012979](#); Symbol: [ER_IB_MSG_1154](#); SQLSTATE: [HY000](#)

Message: Query counter shows %lld queries still inside InnoDB at shutdown

[ER_IB_MSG_1154](#) was added in 8.0.11.

- Error number: [MY-012980](#); Symbol: [ER_IB_MSG_1155](#); SQLSTATE: [HY000](#)

Message: Shutdown completed; log sequence number %llu

[ER_IB_MSG_1155](#) was added in 8.0.11.

- Error number: [MY-012981](#); Symbol: [ER_IB_MSG_1156](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation.

[ER_IB_MSG_1156](#) was added in 8.0.11.

- Error number: [MY-012982](#); Symbol: [ER_IB_MSG_1157](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1157](#) was added in 8.0.11.

- Error number: [MY-012983](#); Symbol: [ER_IB_MSG_1158](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1158](#) was added in 8.0.11.

- Error number: [MY-012984](#); Symbol: [ER_IB_MSG_1159](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1159](#) was added in 8.0.11.

- Error number: [MY-012985](#); Symbol: [ER_IB_MSG_1160](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1160](#) was added in 8.0.11.

- Error number: [MY-012986](#); Symbol: [ER_IB_MSG_1161](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1161](#) was added in 8.0.11.

- Error number: [MY-012987](#); Symbol: [ER_IB_MSG_1162](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1162](#) was added in 8.0.11.

- Error number: [MY-012988](#); Symbol: [ER_IB_MSG_1163](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1163](#) was added in 8.0.11.

- Error number: [MY-012989](#); Symbol: [ER_IB_MSG_1164](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1164](#) was added in 8.0.11.

- Error number: [MY-012990](#); Symbol: [ER_IB_MSG_1165](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1165](#) was added in 8.0.11.

- Error number: [MY-012991](#); Symbol: [ER_IB_MSG_1166](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1166](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012991](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to read the existing undo truncate log file '%s'. The error is %s

[ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#) was added in 8.0.21.

- Error number: [MY-012992](#); Symbol: [ER_IB_MSG_1167](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1167](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-012992](#); Symbol: [ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: Undo tablespace %s is marked for truncate

`ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE` was added in 8.0.21.

- Error number: `MY-012993`; Symbol: `ER_IB_MSG_1168`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1168` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012994`; Symbol: `ER_IB_MSG_1169`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1169` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012994`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_START`; SQLSTATE: `HY000`

Message: Truncating UNDO tablespace %s

`ER_IB_MSG_UNDO_TRUNCATE_START` was added in 8.0.21.

- Error number: `MY-012995`; Symbol: `ER_IB_MSG_1170`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1170` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012996`; Symbol: `ER_IB_MSG_1171`; SQLSTATE: `HY000`

Message: Cannot create truncate log for undo tablespace '%s'.

`ER_IB_MSG_1171` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012996`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE`; SQLSTATE: `HY000`

Message: Cannot create truncate log for undo tablespace '%s'.

`ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE` was added in 8.0.21.

- Error number: `MY-012997`; Symbol: `ER_IB_MSG_1172`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1172` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012998`; Symbol: `ER_IB_MSG_1173`; SQLSTATE: `HY000`

Message: Failed to truncate undo tablespace '%s'.

`ER_IB_MSG_1173` was added in 8.0.11, removed after 8.0.20.

- Error number: `MY-012998`; Symbol: `ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE`; SQLSTATE: `HY000`

Message: Failed to truncate undo tablespace '%s'.

`ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE` was added in 8.0.21.

- Error number: `MY-012999`; Symbol: `ER_IB_MSG_1174`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1174` was added in 8.0.11, removed after 8.0.20.

-
- Error number: [MY-013000](#); Symbol: [ER_IB_MSG_1175](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1175](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-013000](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#); SQLSTATE: [HY000](#)
Message: Completed truncate of undo tablespace %s.
[ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#) was added in 8.0.21.
 - Error number: [MY-013001](#); Symbol: [ER_IB_MSG_1176](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1176](#) was added in 8.0.11, removed after 8.0.20.
 - Error number: [MY-013002](#); Symbol: [ER_IB_MSG_1177](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1177](#) was added in 8.0.11.
 - Error number: [MY-013003](#); Symbol: [ER_IB_MSG_1178](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1178](#) was added in 8.0.11.
 - Error number: [MY-013004](#); Symbol: [ER_IB_MSG_1179](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1179](#) was added in 8.0.11.
 - Error number: [MY-013005](#); Symbol: [ER_IB_MSG_1180](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1180](#) was added in 8.0.11.
 - Error number: [MY-013006](#); Symbol: [ER_IB_MSG_1181](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1181](#) was added in 8.0.11.
 - Error number: [MY-013007](#); Symbol: [ER_IB_MSG_1182](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1182](#) was added in 8.0.11.
 - Error number: [MY-013008](#); Symbol: [ER_IB_MSG_1183](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1183](#) was added in 8.0.11.
 - Error number: [MY-013009](#); Symbol: [ER_IB_MSG_1184](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1184](#) was added in 8.0.11.

- Error number: [MY-013010](#); Symbol: [ER_IB_MSG_1185](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1185](#) was added in 8.0.11.

- Error number: [MY-013011](#); Symbol: [ER_IB_MSG_1186](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1186](#) was added in 8.0.11.

- Error number: [MY-013012](#); Symbol: [ER_IB_MSG_1187](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1187](#) was added in 8.0.11.

- Error number: [MY-013013](#); Symbol: [ER_IB_MSG_1188](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1188](#) was added in 8.0.11.

- Error number: [MY-013014](#); Symbol: [ER_IB_MSG_1189](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1189](#) was added in 8.0.11.

- Error number: [MY-013015](#); Symbol: [ER_IB_MSG_1190](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1190](#) was added in 8.0.11, removed after 8.0.20.

- Error number: [MY-013015](#); Symbol: [ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED](#); SQLSTATE: [HY000](#)

Message: Rollback of non-prepared transactions completed

[ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED](#) was added in 8.0.21.

- Error number: [MY-013016](#); Symbol: [ER_IB_MSG_1191](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1191](#) was added in 8.0.11.

- Error number: [MY-013017](#); Symbol: [ER_IB_MSG_1192](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1192](#) was added in 8.0.11.

- Error number: [MY-013018](#); Symbol: [ER_IB_MSG_1193](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1193](#) was added in 8.0.11.

- Error number: [MY-013019](#); Symbol: [ER_IB_MSG_1194](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1194](#) was added in 8.0.11.

- Error number: [MY-013020](#); Symbol: [ER_IB_MSG_1195](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1195](#) was added in 8.0.11.

- Error number: [MY-013021](#); Symbol: [ER_IB_MSG_1196](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1196](#) was added in 8.0.11.

- Error number: [MY-013022](#); Symbol: [ER_IB_MSG_1197](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1197](#) was added in 8.0.11.

- Error number: [MY-013023](#); Symbol: [ER_IB_MSG_1198](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1198](#) was added in 8.0.11.

- Error number: [MY-013024](#); Symbol: [ER_IB_MSG_1199](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1199](#) was added in 8.0.11.

- Error number: [MY-013025](#); Symbol: [ER_IB_MSG_1200](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1200](#) was added in 8.0.11.

- Error number: [MY-013026](#); Symbol: [ER_IB_MSG_1201](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1201](#) was added in 8.0.11.

- Error number: [MY-013027](#); Symbol: [ER_IB_MSG_1202](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1202](#) was added in 8.0.11.

- Error number: [MY-013028](#); Symbol: [ER_IB_MSG_1203](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1203](#) was added in 8.0.11.

- Error number: [MY-013029](#); Symbol: [ER_IB_MSG_1204](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1204](#) was added in 8.0.11.

-
- Error number: [MY-013030](#); Symbol: [ER_IB_MSG_1205](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1205](#) was added in 8.0.11.
 - Error number: [MY-013031](#); Symbol: [ER_IB_MSG_1206](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1206](#) was added in 8.0.11.
 - Error number: [MY-013032](#); Symbol: [ER_IB_MSG_1207](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1207](#) was added in 8.0.11.
 - Error number: [MY-013033](#); Symbol: [ER_IB_MSG_1208](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1208](#) was added in 8.0.11.
 - Error number: [MY-013034](#); Symbol: [ER_IB_MSG_1209](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1209](#) was added in 8.0.11.
 - Error number: [MY-013035](#); Symbol: [ER_IB_MSG_1210](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1210](#) was added in 8.0.11.
 - Error number: [MY-013036](#); Symbol: [ER_IB_MSG_1211](#); SQLSTATE: [HY000](#)
Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.
[ER_IB_MSG_1211](#) was added in 8.0.11.
 - Error number: [MY-013037](#); Symbol: [ER_IB_MSG_1212](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1212](#) was added in 8.0.11.
 - Error number: [MY-013038](#); Symbol: [ER_IB_MSG_1213](#); SQLSTATE: [HY000](#)
Message: gettimeofday() failed: %s
[ER_IB_MSG_1213](#) was added in 8.0.11.
 - Error number: [MY-013039](#); Symbol: [ER_IB_MSG_1214](#); SQLSTATE: [HY000](#)
Message: Can't create UNDO tablespace %s %s
[ER_IB_MSG_1214](#) was added in 8.0.11.
 - Error number: [MY-013040](#); Symbol: [ER_IB_MSG_1215](#); SQLSTATE: [HY000](#)
Message: %s

[ER_IB_MSG_1215](#) was added in 8.0.11.

- Error number: [MY-013041](#); Symbol: [ER_IB_MSG_1216](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1216](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013041](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_ON_START](#); SQLSTATE: [HY000](#)

Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large `--innodb_redo_log_capacity`, and resizing the redo log online using SET.

[ER_IB_MSG_LOG_FILES_RESIZE_ON_START](#) was added in 8.0.30.

- Error number: [MY-013042](#); Symbol: [ER_IB_MSG_1217](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1217](#) was added in 8.0.11.

- Error number: [MY-013043](#); Symbol: [ER_IB_MSG_1218](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1218](#) was added in 8.0.11.

- Error number: [MY-013044](#); Symbol: [ER_IB_MSG_1219](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1219](#) was added in 8.0.11.

- Error number: [MY-013045](#); Symbol: [ER_IB_MSG_1220](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1220](#) was added in 8.0.11.

- Error number: [MY-013046](#); Symbol: [ER_IB_MSG_1221](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1221](#) was added in 8.0.11.

- Error number: [MY-013047](#); Symbol: [ER_IB_MSG_1222](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1222](#) was added in 8.0.11.

- Error number: [MY-013048](#); Symbol: [ER_IB_MSG_1223](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1223](#) was added in 8.0.11.

-
- Error number: [MY-013049](#); Symbol: [ER_IB_MSG_1224](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1224](#) was added in 8.0.11.
 - Error number: [MY-013050](#); Symbol: [ER_IB_MSG_1225](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1225](#) was added in 8.0.11.
 - Error number: [MY-013051](#); Symbol: [ER_IB_MSG_1226](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1226](#) was added in 8.0.11.
 - Error number: [MY-013052](#); Symbol: [ER_IB_MSG_1227](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1227](#) was added in 8.0.11.
 - Error number: [MY-013053](#); Symbol: [ER_IB_MSG_1228](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1228](#) was added in 8.0.11.
 - Error number: [MY-013054](#); Symbol: [ER_IB_MSG_1229](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1229](#) was added in 8.0.11.
 - Error number: [MY-013055](#); Symbol: [ER_IB_MSG_1230](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1230](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-013056](#); Symbol: [ER_IB_MSG_1231](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1231](#) was added in 8.0.11.
 - Error number: [MY-013057](#); Symbol: [ER_IB_MSG_1232](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1232](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013058](#); Symbol: [ER_IB_MSG_1233](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1233](#) was added in 8.0.11.
 - Error number: [MY-013059](#); Symbol: [ER_IB_MSG_1234](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1234](#) was added in 8.0.11, removed after 8.0.29.

-
- Error number: [MY-013059](#); Symbol: [ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing innodb_redo_log_capacity.

[ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE](#) was added in 8.0.30.
 - Error number: [MY-013060](#); Symbol: [ER_IB_MSG_1235](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1235](#) was added in 8.0.11.
 - Error number: [MY-013061](#); Symbol: [ER_IB_MSG_1236](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1236](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013061](#); Symbol: [ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb_redo_log_capacity.

[ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER](#) was added in 8.0.30.
 - Error number: [MY-013062](#); Symbol: [ER_IB_MSG_1237](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1237](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013062](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing innodb_redo_log_capacity.

[ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER](#) was added in 8.0.30.
 - Error number: [MY-013063](#); Symbol: [ER_IB_MSG_1238](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1238](#) was added in 8.0.11.
 - Error number: [MY-013064](#); Symbol: [ER_IB_MSG_1239](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1239](#) was added in 8.0.11.
 - Error number: [MY-013065](#); Symbol: [ER_IB_MSG_1240](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1240](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013066](#); Symbol: [ER_IB_MSG_1241](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1241](#) was added in 8.0.11.

- Error number: [MY-013067](#); Symbol: [ER_IB_MSG_1242](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted in read-only mode.

[ER_IB_MSG_1242](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013067](#); Symbol: [ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: Can't set redo log files to be encrypted in read-only mode.

[ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY](#) was added in 8.0.30.

- Error number: [MY-013068](#); Symbol: [ER_IB_MSG_1243](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER_IB_MSG_1243](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013068](#); Symbol: [ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Can't set redo log files to be encrypted.

[ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED](#) was added in 8.0.30.

- Error number: [MY-013069](#); Symbol: [ER_IB_MSG_1244](#); SQLSTATE: [HY000](#)

Message: Can't set redo log tablespace to be encrypted.

[ER_IB_MSG_1244](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013070](#); Symbol: [ER_IB_MSG_1245](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled.

[ER_IB_MSG_1245](#) was added in 8.0.11.

- Error number: [MY-013071](#); Symbol: [ER_IB_MSG_1246](#); SQLSTATE: [HY000](#)

Message: Waiting for archiver to finish archiving page and log

[ER_IB_MSG_1246](#) was added in 8.0.11.

- Error number: [MY-013072](#); Symbol: [ER_IB_MSG_1247](#); SQLSTATE: [HY000](#)

Message: Starting shutdown...

[ER_IB_MSG_1247](#) was added in 8.0.11.

- Error number: [MY-013073](#); Symbol: [ER_IB_MSG_1248](#); SQLSTATE: [HY000](#)

Message: Waiting for %s to exit.

[ER_IB_MSG_1248](#) was added in 8.0.11.

- Error number: [MY-013074](#); Symbol: [ER_IB_MSG_1249](#); SQLSTATE: [HY000](#)

Message: Waiting for rollback of %zu recovered transactions, before shutdown.

[ER_IB_MSG_1249](#) was added in 8.0.11.

-
- Error number: [MY-013075](#); Symbol: [ER_IB_MSG_1250](#); SQLSTATE: [HY000](#)
Message: Waiting for master thread to be suspended.
[ER_IB_MSG_1250](#) was added in 8.0.11.
 - Error number: [MY-013076](#); Symbol: [ER_IB_MSG_1251](#); SQLSTATE: [HY000](#)
Message: Waiting for page_cleaner to finish flushing of buffer pool.
[ER_IB_MSG_1251](#) was added in 8.0.11.
 - Error number: [MY-013077](#); Symbol: [ER_IB_MSG_1252](#); SQLSTATE: [HY000](#)
Message: Waiting for %lu buffer page I/Os to complete.
[ER_IB_MSG_1252](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013077](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Shutdown is waiting for %zu buffer page I/Os to complete.
[ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN](#) was added in 8.0.30.
 - Error number: [MY-013078](#); Symbol: [ER_IB_MSG_1253](#); SQLSTATE: [HY000](#)
Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!
[ER_IB_MSG_1253](#) was added in 8.0.11.
 - Error number: [MY-013079](#); Symbol: [ER_IB_MSG_1254](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1254](#) was added in 8.0.11, removed after 8.0.13.
 - Error number: [MY-013080](#); Symbol: [ER_IB_MSG_1255](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1255](#) was added in 8.0.11.
 - Error number: [MY-013081](#); Symbol: [ER_IB_MSG_1256](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1256](#) was added in 8.0.11.
 - Error number: [MY-013082](#); Symbol: [ER_IB_MSG_1257](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1257](#) was added in 8.0.11.
 - Error number: [MY-013083](#); Symbol: [ER_IB_MSG_1258](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1258](#) was added in 8.0.11.
-

-
- Error number: [MY-013084](#); Symbol: [ER_IB_MSG_1259](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1259](#) was added in 8.0.11.
 - Error number: [MY-013085](#); Symbol: [ER_IB_MSG_1260](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1260](#) was added in 8.0.11.
 - Error number: [MY-013086](#); Symbol: [ER_IB_MSG_1261](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1261](#) was added in 8.0.11.
 - Error number: [MY-013087](#); Symbol: [ER_IB_MSG_1262](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1262](#) was added in 8.0.11.
 - Error number: [MY-013088](#); Symbol: [ER_IB_MSG_1263](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1263](#) was added in 8.0.11.
 - Error number: [MY-013089](#); Symbol: [ER_IB_MSG_1264](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1264](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013089](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM](#); SQLSTATE: [HY000](#)
Message: Invalid redo log header checksum.
[ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM](#) was added in 8.0.30.
 - Error number: [MY-013090](#); Symbol: [ER_IB_MSG_1265](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1265](#) was added in 8.0.11, removed after 8.0.29.
 - Error number: [MY-013090](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9](#); SQLSTATE: [HY000](#)
Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9
[ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9](#) was added in 8.0.30.
 - Error number: [MY-013091](#); Symbol: [ER_IB_MSG_1266](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1266](#) was added in 8.0.11.

-
- Error number: [MY-013092](#); Symbol: [ER_IB_MSG_1267](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1267](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013092](#); Symbol: [ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. The innodb_redo_log_capacity=%lluM is too small for the innodb_thread_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb_thread_concurrency to a smaller value or increase innodb_redo_log_capacity. %s

[ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE](#) was added in 8.0.30.

- Error number: [MY-013093](#); Symbol: [ER_IB_MSG_1268](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1268](#) was added in 8.0.11.

- Error number: [MY-013094](#); Symbol: [ER_IB_MSG_1269](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1269](#) was added in 8.0.11.

- Error number: [MY-013095](#); Symbol: [ER_IB_MSG_1270](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1270](#) was added in 8.0.11, removed after 8.0.29.

- Error number: [MY-013095](#); Symbol: [ER_IB_MSG_THREAD_CONCURRENCY_CHANGED](#); SQLSTATE: [HY000](#)

Message: User has set innodb_thread_concurrency to %lu.

[ER_IB_MSG_THREAD_CONCURRENCY_CHANGED](#) was added in 8.0.30.

- Error number: [MY-013096](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013096](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

[ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.33.

-
- Error number: [MY-013097](#); Symbol: [ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013097](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

[ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#) was added in 8.0.33.

- Error number: [MY-013098](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

[ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE](#) was added in 8.0.11.

- Error number: [MY-013099](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

[ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT](#) was added in 8.0.11.

- Error number: [MY-013100](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

[ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE](#) was added in 8.0.11, removed after 8.0.12.

- Error number: [MY-013101](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_IGNORED](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

[ER_BINLOG_ROW_VALUE_OPTION_IGNORED](#) was added in 8.0.11.

- Error number: [MY-013102](#); Symbol: [ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED](#); SQLSTATE: [HY000](#)

Message: When %s, the option log_bin_use_v1_row_events=1 will be ignored and row events will be written in new format to binary log.

[ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED](#) was added in 8.0.11.

-
- Error number: [MY-013103](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.

[ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES](#) was added in 8.0.11.
 - Error number: [MY-013104](#); Symbol: [ER_CONNECTION_ABORTED](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

[ER_CONNECTION_ABORTED](#) was added in 8.0.11.
 - Error number: [MY-013105](#); Symbol: [ER_NORMAL_SERVER_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: %s: Normal shutdown.

[ER_NORMAL_SERVER_SHUTDOWN](#) was added in 8.0.11.
 - Error number: [MY-013106](#); Symbol: [ER_KEYRING_MIGRATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Can not perform keyring migration : %s.

[ER_KEYRING_MIGRATE_FAILED](#) was added in 8.0.11.
 - Error number: [MY-013107](#); Symbol: [ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a lower_case_table_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower_case_table_names value different from the group.

[ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#) was added in 8.0.11.
 - Error number: [MY-013108](#); Symbol: [ER_OOM_SAVE_GTIDS](#); SQLSTATE: [HY000](#)

Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid_executed table

[ER_OOM_SAVE_GTIDS](#) was added in 8.0.11.
 - Error number: [MY-013109](#); Symbol: [ER_LCTN_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: The lower_case_table_names setting for the data dictionary was not found. Starting the server using lower_case_table_names = '%u'.

[ER_LCTN_NOT_FOUND](#) was added in 8.0.11.
 - Error number: [MY-013111](#); Symbol: [ER_COMPONENT_FILTER_WRONG_VALUE](#); SQLSTATE: [HY000](#)

Message: Variable '%s' can't be set to the value of '%s'

[ER_COMPONENT_FILTER_WRONG_VALUE](#) was added in 8.0.11.
 - Error number: [MY-013112](#); Symbol: [ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

[ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#) was added in 8.0.11.

-
- Error number: [MY-013113](#); Symbol: [ER_INCONSISTENT_ERROR](#); SQLSTATE: [HY000](#)
Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'
 - Error number: [MY-013114](#); Symbol: [ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from master when reading data from binary log: '%s'
[ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-013114](#); Symbol: [ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from source when reading data from binary log: '%s'
[ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG](#) was added in 8.0.33.
 - Error number: [MY-013115](#); Symbol: [ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)
Message: Replication event checksum verification failed while reading from network.
 - Error number: [MY-013116](#); Symbol: [ER_SLAVE_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failed to create %s
[ER_SLAVE_CREATE_EVENT_FAILURE](#) was removed after 8.0.32.
 - Error number: [MY-013116](#); Symbol: [ER_REPLICA_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failed to create %s
[ER_REPLICA_CREATE_EVENT_FAILURE](#) was added in 8.0.33.
 - Error number: [MY-013117](#); Symbol: [ER_SLAVE_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error: %s
[ER_SLAVE_FATAL_ERROR](#) was removed after 8.0.32.
 - Error number: [MY-013117](#); Symbol: [ER_REPLICA_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error: %s
[ER_REPLICA_FATAL_ERROR](#) was added in 8.0.33.
 - Error number: [MY-013118](#); Symbol: [ER_SLAVE_HEARTBEAT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Unexpected master's heartbeat data: %s
[ER_SLAVE_HEARTBEAT_FAILURE](#) was removed after 8.0.32.
 - Error number: [MY-013118](#); Symbol: [ER_REPLICA_HEARTBEAT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Unexpected source's heartbeat data: %s
[ER_REPLICA_HEARTBEAT_FAILURE](#) was added in 8.0.33.
 - Error number: [MY-013119](#); Symbol: [ER_SLAVE_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the master. Message: %s

[ER_SLAVE_INCIDENT](#) was removed after 8.0.32.

- Error number: [MY-013119](#); Symbol: [ER_REPLICA_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the source. Message: %s

[ER_REPLICA_INCIDENT](#) was added in 8.0.33.

- Error number: [MY-013120](#); Symbol: [ER_SLAVE_MASTER_COM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Master command %s failed: %s

[ER_SLAVE_MASTER_COM_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013120](#); Symbol: [ER_REPLICA_SOURCE_COM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Source command %s failed: %s

[ER_REPLICA_SOURCE_COM_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013121](#); Symbol: [ER_SLAVE_RELAY_LOG_READ_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER_SLAVE_RELAY_LOG_READ_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013121](#); Symbol: [ER_REPLICA_RELAY_LOG_READ_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

[ER_REPLICA_RELAY_LOG_READ_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013122](#); Symbol: [ER_SLAVE_RELAY_LOG_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER_SLAVE_RELAY_LOG_WRITE_FAILURE](#) was removed after 8.0.32.

- Error number: [MY-013122](#); Symbol: [ER_REPLICA_RELAY_LOG_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

[ER_REPLICA_RELAY_LOG_WRITE_FAILURE](#) was added in 8.0.33.

- Error number: [MY-013123](#); Symbol: [ER_SERVER_SLAVE_MI_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Slave failed to initialize master info structure from the repository

[ER_SERVER_SLAVE_MI_INIT_REPOSITORY](#) was added in 8.0.11, removed after 8.0.32.

- Error number: [MY-013123](#); Symbol: [ER_SERVER_REPLICA_CM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Replica failed to initialize connection metadata structure from the repository

[ER_SERVER_REPLICA_CM_INIT_REPOSITORY](#) was added in 8.0.33.

-
- Error number: `MY-013124`; Symbol: `ER_SERVER_SLAVE_RLI_INIT_REPOSITORY`; SQLSTATE: `HY000`
Message: Slave failed to initialize relay log info structure from the repository
`ER_SERVER_SLAVE_RLI_INIT_REPOSITORY` was added in 8.0.11, removed after 8.0.32.
 - Error number: `MY-013124`; Symbol: `ER_SERVER_REPLICA_AM_INIT_REPOSITORY`; SQLSTATE: `HY000`
Message: Replica failed to initialize applier metadata structure from the repository
`ER_SERVER_REPLICA_AM_INIT_REPOSITORY` was added in 8.0.33.
 - Error number: `MY-013125`; Symbol: `ER_SERVER_NET_PACKET_TOO_LARGE`; SQLSTATE: `HY000`
Message: Got a packet bigger than 'max_allowed_packet' bytes
`ER_SERVER_NET_PACKET_TOO_LARGE` was added in 8.0.11.
 - Error number: `MY-013126`; Symbol: `ER_SERVER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: `HY000`
Message: Access to %s '%s.%s' is rejected.
`ER_SERVER_NO_SYSTEM_TABLE_ACCESS` was added in 8.0.11.
 - Error number: `MY-013127`; Symbol: `ER_SERVER_UNKNOWN_ERROR`; SQLSTATE: `HY000`
Message: Unknown error
`ER_SERVER_UNKNOWN_ERROR` was added in 8.0.11, removed after 8.0.32.
 - Error number: `MY-013128`; Symbol: `ER_SERVER_UNKNOWN_SYSTEM_VARIABLE`; SQLSTATE: `HY000`
Message: Unknown system variable '%s'
`ER_SERVER_UNKNOWN_SYSTEM_VARIABLE` was added in 8.0.11.
 - Error number: `MY-013129`; Symbol: `ER_SERVER_NO_SESSION_TO_SEND_TO`; SQLSTATE: `HY000`
Message: A message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s
`ER_SERVER_NO_SESSION_TO_SEND_TO` was added in 8.0.11.
 - Error number: `MY-013130`; Symbol: `ER_SERVER_NEW_ABORTING_CONNECTION`; SQLSTATE: `08S01`
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)
`ER_SERVER_NEW_ABORTING_CONNECTION` was added in 8.0.11.
 - Error number: `MY-013131`; Symbol: `ER_SERVER_OUT_OF_SORTMEMORY`; SQLSTATE: `HY000`
Message: Out of sort memory, consider increasing server sort buffer size!
`ER_SERVER_OUT_OF_SORTMEMORY` was added in 8.0.11.
 - Error number: `MY-013132`; Symbol: `ER_SERVER_RECORD_FILE_FULL`; SQLSTATE: `HY000`
Message: The table '%s' is full!

[ER_SERVER_RECORD_FILE_FULL](#) was added in 8.0.11.

- Error number: [MY-013133](#); Symbol: [ER_SERVER_DISK_FULL_NOWAIT](#); SQLSTATE: [HY000](#)

Message: Create table/tablespace '%s' failed, as disk is full.

[ER_SERVER_DISK_FULL_NOWAIT](#) was added in 8.0.11.

- Error number: [MY-013134](#); Symbol: [ER_SERVER_HANDLER_ERROR](#); SQLSTATE: [HY000](#)

Message: Handler reported error %d - %s

[ER_SERVER_HANDLER_ERROR](#) was added in 8.0.11.

- Error number: [MY-013135](#); Symbol: [ER_SERVER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file: '%s'

[ER_SERVER_NOT_FORM_FILE](#) was added in 8.0.11.

- Error number: [MY-013136](#); Symbol: [ER_SERVER_CANT_OPEN_FILE](#); SQLSTATE: [HY000](#)

Message: Can't open file: '%s' (OS errno: %d - %s)

[ER_SERVER_CANT_OPEN_FILE](#) was added in 8.0.11.

- Error number: [MY-013137](#); Symbol: [ER_SERVER_FILE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find file: '%s' (OS errno: %d - %s)

[ER_SERVER_FILE_NOT_FOUND](#) was added in 8.0.11.

- Error number: [MY-013138](#); Symbol: [ER_SERVER_FILE_USED](#); SQLSTATE: [HY000](#)

Message: '%s' is locked against change (OS errno: %d - %s)

[ER_SERVER_FILE_USED](#) was added in 8.0.11.

- Error number: [MY-013139](#); Symbol: [ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)

Message: Cannot load from %s.%s. The table is probably corrupted!

[ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#) was added in 8.0.11.

- Error number: [MY-013140](#); Symbol: [ER_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)

Message: Error in diagnostics area: MY-%06d - %s

[ER_ERROR_INFO_FROM_DA](#) was added in 8.0.11.

- Error number: [MY-013141](#); Symbol: [ER_SERVER_TABLE_CHECK_FAILED](#); SQLSTATE: [HY000](#)

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.

[ER_SERVER_TABLE_CHECK_FAILED](#) was added in 8.0.11.

-
- Error number: [MY-013142](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2](#); SQLSTATE: [HY000](#)
Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
[ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2](#) was added in 8.0.11.
 - Error number: [MY-013143](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
[ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#) was added in 8.0.11.
 - Error number: [MY-013144](#); Symbol: [ER_SERVER_ACL_TABLE_ERROR](#); SQLSTATE: [HY000](#)
Message:
[ER_SERVER_ACL_TABLE_ERROR](#) was added in 8.0.11.
 - Error number: [MY-013145](#); Symbol: [ER_SERVER_SLAVE_INIT_QUERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Slave SQL thread aborted. Can't execute init_replica query, MY-%06d - '%s'
[ER_SERVER_SLAVE_INIT_QUERY_FAILED](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-013145](#); Symbol: [ER_SERVER_REPLICA_INIT_QUERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread aborted. Can't execute init_replica query, MY-%06d - '%s'
[ER_SERVER_REPLICA_INIT_QUERY_FAILED](#) was added in 8.0.33.
 - Error number: [MY-013146](#); Symbol: [ER_SERVER_SLAVE_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)
Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
[ER_SERVER_SLAVE_CONVERSION_FAILED](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-013146](#); Symbol: [ER_SERVER_REPLICA_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)
Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
[ER_SERVER_REPLICA_CONVERSION_FAILED](#) was added in 8.0.33.
 - Error number: [MY-013147](#); Symbol: [ER_SERVER_SLAVE_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Slave SQL thread ignored the query because of replicate-*-table rules
[ER_SERVER_SLAVE_IGNORED_TABLE](#) was added in 8.0.11, removed after 8.0.32.
 - Error number: [MY-013147](#); Symbol: [ER_SERVER_REPLICA_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread ignored the query because of replicate-*-table rules
[ER_SERVER_REPLICA_IGNORED_TABLE](#) was added in 8.0.33.
 - Error number: [MY-013148](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.

- Error number: [MY-013149](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

- Error number: [MY-013150](#); Symbol: [ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

- Error number: [MY-013151](#); Symbol: [ER_SERVER_TEST_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Simulated error

[ER_SERVER_TEST_MESSAGE](#) was added in 8.0.11.

- Error number: [MY-013152](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR](#) was added in 8.0.11.

- Error number: [MY-013153](#); Symbol: [ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log filtering has not been installed.

[ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#) was added in 8.0.11.

- Error number: [MY-013154](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

[ER_PLUGIN_FAILED_TO_OPEN_TABLES](#) was added in 8.0.11.

- Error number: [MY-013155](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table.

[ER_PLUGIN_FAILED_TO_OPEN_TABLE](#) was added in 8.0.11.

- Error number: [MY-013156](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)

Message: Filter name cannot be empty.

[ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#) was added in 8.0.11.

- Error number: [MY-013157](#); Symbol: [ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the user name.

[ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#) was added in 8.0.11.

- Error number: [MY-013158](#); Symbol: [ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Request ignored for '%s'@'%s'. SUPER or AUDIT_ADMIN needed to perform operation

`ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE` was added in 8.0.11.

- Error number: `MY-013159`; Symbol: `ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED`; SQLSTATE: `HY000`

Message: No keyring installed.

`ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED` was added in 8.0.11.

- Error number: `MY-013160`; Symbol: `ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`

Message: Invalid character in the host name.

`ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER` was added in 8.0.11.

- Error number: `MY-013161`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET`; SQLSTATE: `HY000`

Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET` was added in 8.0.11.

- Error number: `MY-013162`; Symbol: `ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY`; SQLSTATE: `HY000`

Message: Could not create AES key. OpenSSL's `EVP_BytesToKey` function failed.

`ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY` was added in 8.0.11.

- Error number: `MY-013163`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED`; SQLSTATE: `HY000`

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED` was added in 8.0.11.

- Error number: `MY-013164`; Symbol: `ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS`; SQLSTATE: `HY000`

Message: Could not reinitialize audit log filters.

`ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS` was added in 8.0.11.

- Error number: `MY-013165`; Symbol: `ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: User cannot be empty.

`ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY` was added in 8.0.11.

- Error number: `MY-013166`; Symbol: `ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC`; SQLSTATE: `HY000`

Message: First character of the user name must be alphanumeric.

`ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC` was added in 8.0.11.

-
- Error number: [MY-013167](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Specified filter has not been found.
[ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST](#) was added in 8.0.11.
 - Error number: [MY-013168](#); Symbol: [ER_IB_MSG_1271](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade server earlier than 5.7 to 8.0
[ER_IB_MSG_1271](#) was added in 8.0.11.
 - Error number: [MY-013169](#); Symbol: [ER_STARTING_INIT](#); SQLSTATE: [HY000](#)
Message: %s (mysqld %s) initializing of server in progress as process %lu
[ER_STARTING_INIT](#) was added in 8.0.11.
 - Error number: [MY-013170](#); Symbol: [ER_ENDING_INIT](#); SQLSTATE: [HY000](#)
Message: %s (mysqld %s) initializing of server has completed
[ER_ENDING_INIT](#) was added in 8.0.11.
 - Error number: [MY-013171](#); Symbol: [ER_IB_MSG_1272](#); SQLSTATE: [HY000](#)
Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported
[ER_IB_MSG_1272](#) was added in 8.0.11.
 - Error number: [MY-013172](#); Symbol: [ER_SERVER_SHUTDOWN_INFO](#); SQLSTATE: [HY000](#)
Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).
[ER_SERVER_SHUTDOWN_INFO](#) was added in 8.0.12.
 - Error number: [MY-013173](#); Symbol: [ER_GRP_RPL_PLUGIN_ABORT](#); SQLSTATE: [HY000](#)
Message: The plugin encountered a critical error and will abort: %s
[ER_GRP_RPL_PLUGIN_ABORT](#) was added in 8.0.12.
 - Error number: [MY-013177](#); Symbol: [ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED](#); SQLSTATE: [HY000](#)
Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.
[ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED](#) was added in 8.0.12.
 - Error number: [MY-013178](#); Symbol: [ER_DD_INITIALIZE_SQL_ERROR](#); SQLSTATE: [HY000](#)
Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.
[ER_DD_INITIALIZE_SQL_ERROR](#) was added in 8.0.12.
 - Error number: [MY-013179](#); Symbol: [ER_NO_PATH_FOR_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)
Message: No paths allowed for shared library.
[ER_NO_PATH_FOR_SHARED_LIBRARY](#) was added in 8.0.13.

-
- Error number: [MY-013180](#); Symbol: [ER_UDF_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)
Message: Function '%s' already exists.
[ER_UDF_ALREADY_EXISTS](#) was added in 8.0.13.
 - Error number: [MY-013181](#); Symbol: [ER_SET_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Got Error: %ld from SetEvent.
[ER_SET_EVENT_FAILED](#) was added in 8.0.13.
 - Error number: [MY-013182](#); Symbol: [ER_FAILED_TO_ALLOCATE_SSL_BIO](#); SQLSTATE: [HY000](#)
Message: Error allocating SSL BIO.
[ER_FAILED_TO_ALLOCATE_SSL_BIO](#) was added in 8.0.13.
 - Error number: [MY-013183](#); Symbol: [ER_IB_MSG_1273](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_1273](#) was added in 8.0.13.
 - Error number: [MY-013184](#); Symbol: [ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#); SQLSTATE: [HY000](#)
Message: One or several locations were inaccessible while checking PID filepath.
[ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#) was added in 8.0.13.
 - Error number: [MY-013185](#); Symbol: [ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#); SQLSTATE: [HY000](#)
Message: Currently unknown variable '%s' was read from the persisted config file.
[ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#) was added in 8.0.13.
 - Error number: [MY-013186](#); Symbol: [ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#); SQLSTATE: [HY000](#)
Message: Fatal error in defaults handling. Program aborted!
[ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#) was added in 8.0.13.
 - Error number: [MY-013187](#); Symbol: [ER_DUPLICATE_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Duplicate variable name '%s'.
[ER_DUPLICATE_SYS_VAR](#) was added in 8.0.13.
 - Error number: [MY-013188](#); Symbol: [ER_FAILED_TO_INIT_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Failed to initialize system variables.
[ER_FAILED_TO_INIT_SYS_VAR](#) was added in 8.0.13.
 - Error number: [MY-013189](#); Symbol: [ER_SYS_VAR_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Variable name '%s' not found.
[ER_SYS_VAR_NOT_FOUND](#) was added in 8.0.13.
 - Error number: [MY-013190](#); Symbol: [ER_IB_MSG_1274](#); SQLSTATE: [HY000](#)

Message: Some (%d) threads are still active

[ER_IB_MSG_1274](#) was added in 8.0.13.

- Error number: [MY-013191](#); Symbol: [ER_IB_MSG_1275](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1275](#) was added in 8.0.13.

- Error number: [MY-013192](#); Symbol: [ER_TARGET_TS_UNENCRYPTED](#); SQLSTATE: [HY000](#)

Message: Source tablespace is encrypted but target tablespace is not.

[ER_TARGET_TS_UNENCRYPTED](#) was added in 8.0.13, removed after 8.0.15.

- Error number: [MY-013193](#); Symbol: [ER_IB_MSG_1276](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1276](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013193](#); Symbol: [ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD](#); SQLSTATE: [HY000](#)

Message: Waiting for tablespace_alter_encrypt_thread to exit

[ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD](#) was added in 8.0.14.

- Error number: [MY-013194](#); Symbol: [ER_IB_MSG_1277](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1277](#) was added in 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER_IB_MSG_1278](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1278](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013195](#); Symbol: [ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND](#) was added in 8.0.14.

- Error number: [MY-013196](#); Symbol: [ER_IB_MSG_1279](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1279](#) was added in 8.0.13, removed after 8.0.13.

- Error number: [MY-013196](#); Symbol: [ER_IB_MSG_RESUME_OP_FOR_SPACE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_RESUME_OP_FOR_SPACE](#) was added in 8.0.14.

- Error number: [MY-013197](#); Symbol: [ER_IB_MSG_1280](#); SQLSTATE: [HY000](#)

Message: %s

`ER_IB_MSG_1280` was added in 8.0.13.

- Error number: `MY-013198`; Symbol: `ER_IB_MSG_1281`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1281` was added in 8.0.13.

- Error number: `MY-013199`; Symbol: `ER_IB_MSG_1282`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1282` was added in 8.0.13.

- Error number: `MY-013200`; Symbol: `ER_IB_MSG_1283`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1283` was added in 8.0.13.

- Error number: `MY-013201`; Symbol: `ER_IB_MSG_1284`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1284` was added in 8.0.13.

- Error number: `MY-013202`; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE`; SQLSTATE: `HY000`

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

`ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE` was added in 8.0.13.

- Error number: `MY-013203`; Symbol: `ER_INVALID_VALUE_OF_BIND_ADDRESSES`; SQLSTATE: `HY000`

Message: Invalid value for command line option bind-addresses: '%s'

`ER_INVALID_VALUE_OF_BIND_ADDRESSES` was added in 8.0.13.

- Error number: `MY-013204`; Symbol: `ER_RELAY_LOG_SPACE_LIMIT_DISABLED`; SQLSTATE: `HY000`

Message: Ignoring the @@global.relay_log_space_limit option because @@global.relay_log_purge is disabled.

`ER_RELAY_LOG_SPACE_LIMIT_DISABLED` was added in 8.0.13.

- Error number: `MY-013205`; Symbol: `ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION`; SQLSTATE: `HY000`

Message: Error when extracting GTID execution information: %s

`ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION` was added in 8.0.13.

- Error number: `MY-013206`; Symbol: `ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR`; SQLSTATE: `HY000`

Message: Message received without a proper group coordinator module.

`ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR` was added in 8.0.13.

-
- Error number: MY-013207; Symbol: ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING; SQLSTATE: HY000

Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.

ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING was added in 8.0.13.

- Error number: MY-013208; Symbol: ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING; SQLSTATE: HY000

Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.

ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING was added in 8.0.13.

- Error number: MY-013209; Symbol: ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING; SQLSTATE: HY000

Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.

ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING was added in 8.0.13.

- Error number: MY-013210; Symbol: ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT; SQLSTATE: HY000

Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.

ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT was added in 8.0.13.

- Error number: MY-013211; Symbol: ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING; SQLSTATE: HY000

Message: Error while sending message. Context: %s

ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING was added in 8.0.13.

- Error number: MY-013212; Symbol: ER_GRP_RPL_CONFIGURATION_ACTION_ERROR; SQLSTATE: HY000

Message: Error while executing a group configuration operation: %s

ER_GRP_RPL_CONFIGURATION_ACTION_ERROR was added in 8.0.13.

- Error number: MY-013213; Symbol: ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION; SQLSTATE: HY000

Message: Configuration operation '%s' terminated. %s

ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION was added in 8.0.13.

- Error number: MY-013214; Symbol: ER_GRP_RPL_CONFIGURATION_ACTION_START; SQLSTATE: HY000

Message: Starting group operation local execution: %s

ER_GRP_RPL_CONFIGURATION_ACTION_START was added in 8.0.13.

-
- Error number: [MY-013215](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_END](#); SQLSTATE: [HY000](#)

Message: Termination of group operation local execution: %s

[ER_GRP_RPL_CONFIGURATION_ACTION_END](#) was added in 8.0.13.

- Error number: [MY-013216](#); Symbol: [ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR](#); SQLSTATE: [HY000](#)

Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.

[ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR](#) was added in 8.0.13.

- Error number: [MY-013217](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue on the primary election process: %s The member will now leave the group.

[ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#) was added in 8.0.13.

- Error number: [MY-013218](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when stopping a previous election process: %s

[ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#) was added in 8.0.13.

- Error number: [MY-013219](#); Symbol: [ER_GRP_RPL_NO_STAGE_SERVICE](#); SQLSTATE: [HY000](#)

Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.

[ER_GRP_RPL_NO_STAGE_SERVICE](#) was added in 8.0.13.

- Error number: [MY-013220](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it

[ER_GRP_RPL_UDF_REGISTER_ERROR](#) was added in 8.0.13.

- Error number: [MY-013221](#); Symbol: [ER_GRP_RPL_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.

[ER_GRP_RPL_UDF_UNREGISTER_ERROR](#) was added in 8.0.13.

- Error number: [MY-013222](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin

[ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#) was added in 8.0.13.

-
- Error number: [MY-013223](#); Symbol: [ER_GRP_RPL_SERVER_UDF_ERROR](#); SQLSTATE: [HY000](#)
Message: The function '%s' failed. %s
[ER_GRP_RPL_SERVER_UDF_ERROR](#) was added in 8.0.17.
 - Error number: [MY-013227](#); Symbol: [ER_SERVER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can't be set to the value of '%s'
[ER_SERVER_WRONG_VALUE_FOR_VAR](#) was added in 8.0.13.
 - Error number: [MY-013228](#); Symbol: [ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#); SQLSTATE: [HY000](#)
Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.
[ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#) was added in 8.0.13.
 - Error number: [MY-013229](#); Symbol: [ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: [HY000](#)
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.
[ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#) was added in 8.0.13.
 - Error number: [MY-013233](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Unable to switch security context to user: %s
[ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#) was added in 8.0.13.
 - Error number: [MY-013234](#); Symbol: [ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: [HY000](#)
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
[ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#) was added in 8.0.13.
 - Error number: [MY-013235](#); Symbol: [ER_UPGRADE_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Error in parsing %s '%s'. '%s' during upgrade. %s
[ER_UPGRADE_PARSE_ERROR](#) was added in 8.0.13.
 - Error number: [MY-013236](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE](#); SQLSTATE: [HY000](#)
Message: The designated data directory %s is unusable. You can remove all files that the server added to it.
[ER_DATA_DIRECTORY_UNUSABLE](#) was added in 8.0.13.
 - Error number: [MY-013237](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#); SQLSTATE: [HY000](#)
Message: Group search rebinding via root DN: %s
[ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#) was added in 8.0.13.
-

-
- Error number: [MY-013238](#); Symbol: [ER_PLUGIN_INSTALL_ERROR](#); SQLSTATE: [HY000](#)
Message: Error installing plugin '%s': %s
[ER_PLUGIN_INSTALL_ERROR](#) was added in 8.0.13.
 - Error number: [MY-013239](#); Symbol: [ER_PLUGIN_UNINSTALL_ERROR](#); SQLSTATE: [HY000](#)
Message: Error uninstalling plugin '%s': %s
[ER_PLUGIN_UNINSTALL_ERROR](#) was added in 8.0.13.
 - Error number: [MY-013240](#); Symbol: [ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#); SQLSTATE: [HY000](#)
Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.
[ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#) was added in 8.0.13.
 - Error number: [MY-013241](#); Symbol: [ER_UNKNOWN_TABLESPACE_TYPE](#); SQLSTATE: [HY000](#)
Message: Cannot determine the type of the tablespace named '%s'.
[ER_UNKNOWN_TABLESPACE_TYPE](#) was added in 8.0.13.
 - Error number: [MY-013242](#); Symbol: [ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#); SQLSTATE: [HY000](#)
Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.
[ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#) was added in 8.0.13.
 - Error number: [MY-013243](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#); SQLSTATE: [HY000](#)
Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.
[ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#) was added in 8.0.13.
 - Error number: [MY-013244](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#); SQLSTATE: [HY000](#)
Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
[ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#) was added in 8.0.13.
 - Error number: [MY-013245](#); Symbol: [ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.
[ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#) was added in 8.0.13.
 - Error number: [MY-013246](#); Symbol: [ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet MADV_DONTDUMP is not supported on this platform

`ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED` was added in 8.0.14.

- Error number: `MY-013247`; Symbol: `ER_IB_MSG_MADVISE_FAILED`; SQLSTATE: `HY000`

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet `madvise(%p,%zu,%s)` failed with %s

`ER_IB_MSG_MADVISE_FAILED` was added in 8.0.14.

- Error number: `MY-013249`; Symbol: `ER_WARN_REMOVED_SQL_MODE`; SQLSTATE: `HY000`

Message: `sql_mode=0x%08x` has been removed and will be ignored

`ER_WARN_REMOVED_SQL_MODE` was added in 8.0.14.

- Error number: `MY-013250`; Symbol: `ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT`; SQLSTATE: `HY000`

Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.

`ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT` was added in 8.0.14.

- Error number: `MY-013251`; Symbol: `ER_IB_MSG_NUM_POOLS`; SQLSTATE: `HY000`

Message: Number of pools: %zu

`ER_IB_MSG_NUM_POOLS` was added in 8.0.14, removed after 8.0.30.

- Error number: `MY-013252`; Symbol: `ER_IB_MSG_USING_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Using undo tablespace '%s'.

`ER_IB_MSG_USING_UNDO_SPACE` was added in 8.0.14.

- Error number: `MY-013253`; Symbol: `ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE`; SQLSTATE: `HY000`

Message: %s Unable to save the current state of tablespace '%s' to the data dictionary

`ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE` was added in 8.0.14.

- Error number: `MY-013254`; Symbol: `ER_IB_MSG_MAX_UNDO_SPACES_REACHED`; SQLSTATE: `HY000`

Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.

`ER_IB_MSG_MAX_UNDO_SPACES_REACHED` was added in 8.0.14.

- Error number: `MY-013255`; Symbol: `ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Error %d opening newly created undo tablespace %s.

`ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE` was added in 8.0.14.

- Error number: `MY-013256`; Symbol: `ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR`; SQLSTATE: `HY000`

Message: SDI Compression failed, `Z_BUF_ERROR`

`ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR` was added in 8.0.14.

-
- Error number: MY-013257; Symbol: ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR; SQLSTATE: HY000
Message: SDI Compression failed, Z_MEM_ERROR
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR was added in 8.0.14.
 - Error number: MY-013258; Symbol: ER_IB_MSG_SDI_Z_STREAM_ERROR; SQLSTATE: HY000
Message: SDI Compression failed, Z_STREAM_ERROR
ER_IB_MSG_SDI_Z_STREAM_ERROR was added in 8.0.14.
 - Error number: MY-013259; Symbol: ER_IB_MSG_SDI_Z_UNKNOWN_ERROR; SQLSTATE: HY000
Message: %s
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR was added in 8.0.14.
 - Error number: MY-013260; Symbol: ER_IB_MSG_FOUND_WRONG_UNDO_SPACE; SQLSTATE: HY000
Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb_undo_directory?
ER_IB_MSG_FOUND_WRONG_UNDO_SPACE was added in 8.0.14.
 - Error number: MY-013261; Symbol: ER_IB_MSG_NOT_END_WITH_IBU; SQLSTATE: HY000
Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.
ER_IB_MSG_NOT_END_WITH_IBU was added in 8.0.14.
 - Error number: MY-013262; Symbol: ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE; SQLSTATE: HY000
Message: ib_undo_trunc_empty_file
ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE was added in 8.0.14, removed after 8.0.20.
 - Error number: MY-013263; Symbol: ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE; SQLSTATE: HY000
Message: ib_undo_trunc_before_dd_update
ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE was added in 8.0.14, removed after 8.0.20.
 - Error number: MY-013264; Symbol: ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING; SQLSTATE: HY000
Message: ib_undo_trunc_before_done_logging
ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING was added in 8.0.14, removed after 8.0.20.
 - Error number: MY-013265; Symbol: ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG; SQLSTATE: HY000
Message: ib_undo_trunc_before_rsegs
ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG was added in 8.0.14, removed after 8.0.20.
 - Error number: MY-013266; Symbol: ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE; SQLSTATE: HY000
Message: %s Failed to finish truncating Undo Tablespace '%s'

`ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE` was added in 8.0.14.

- Error number: `MY-013267`; Symbol: `ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES`; SQLSTATE: `HY000`

Message: The setting `INNODB_UNDO_TABLESPACES` is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use `CREATE UNDO TABLESPACE`.

`ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES` was added in 8.0.14.

- Error number: `MY-013268`; Symbol: `ER_IB_MSG_DIR_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: The directory '%s' does not exist.

`ER_IB_MSG_DIR_DOES_NOT_EXIST` was added in 8.0.14, removed after 8.0.20.

- Error number: `MY-013268`; Symbol: `ER_IB_MSG_WRONG_TABLESPACE_DIR`; SQLSTATE: `HY000`

Message: The directory for tablespace %s does not exist or is incorrect.

`ER_IB_MSG_WRONG_TABLESPACE_DIR` was added in 8.0.21.

- Error number: `MY-013269`; Symbol: `ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS` was added in 8.0.14.

- Error number: `MY-013270`; Symbol: `ER_CLONE_REMOTE_ERROR`; SQLSTATE: `HY000`

Message: Clone Remote Error: %s.

`ER_CLONE_REMOTE_ERROR` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013270`; Symbol: `ER_CLONE_DONOR_TRACE`; SQLSTATE: `HY000`

Message: Clone donor reported : %s.

`ER_CLONE_DONOR_TRACE` was added in 8.0.17.

- Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_ERROR`; SQLSTATE: `HY000`

Message: Clone Protocol Error: %s.

`ER_CLONE_PROTOCOL_ERROR` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013271`; Symbol: `ER_CLONE_PROTOCOL_TRACE`; SQLSTATE: `HY000`

Message: Clone received unexpected response from donor : %s.

`ER_CLONE_PROTOCOL_TRACE` was added in 8.0.17.

- Error number: `MY-013272`; Symbol: `ER_CLONE_INFO_CLIENT`; SQLSTATE: `HY000`

Message: Client: %s.

`ER_CLONE_INFO_CLIENT` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013272`; Symbol: `ER_CLONE_CLIENT_TRACE`; SQLSTATE: `HY000`

Message: Client: %s.

`ER_CLONE_CLIENT_TRACE` was added in 8.0.17.

- Error number: `MY-013273`; Symbol: `ER_CLONE_INFO_SERVER`; SQLSTATE: `HY000`

Message: Server: %s.

`ER_CLONE_INFO_SERVER` was added in 8.0.14, removed after 8.0.16.

- Error number: `MY-013273`; Symbol: `ER_CLONE_SERVER_TRACE`; SQLSTATE: `HY000`

Message: Server: %s.

`ER_CLONE_SERVER_TRACE` was added in 8.0.17.

- Error number: `MY-013274`; Symbol: `ER_THREAD_POOL_PFS_TABLES_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize the performance schema tables service.

`ER_THREAD_POOL_PFS_TABLES_INIT_FAILED` was added in 8.0.14.

- Error number: `MY-013275`; Symbol: `ER_THREAD_POOL_PFS_TABLES_ADD_FAILED`; SQLSTATE: `HY000`

Message: Failed to add thread pool performance schema tables.

`ER_THREAD_POOL_PFS_TABLES_ADD_FAILED` was added in 8.0.14.

- Error number: `MY-013276`; Symbol: `ER_CANT_SET_DATA_DIR`; SQLSTATE: `HY000`

Message: Failed to set datadir to '%s' (OS errno: %d - %s)

`ER_CANT_SET_DATA_DIR` was added in 8.0.14.

- Error number: `MY-013277`; Symbol: `ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION`; SQLSTATE: `HY000`

Message: The innodb_undo_directory is not allowed to be an ancestor of the datadir.

`ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION` was added in 8.0.14.

- Error number: `MY-013278`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY`; SQLSTATE: `HY000`

Message: Failed to fetch key from keyring, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY` was added in 8.0.14.

- Error number: `MY-013279`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

`ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND` was added in 8.0.14.

- Error number: `MY-013280`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: `HY000`

Message: Fetched an invalid key from keyring.

`ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY` was added in 8.0.14.

-
- Error number: `MY-013281`; Symbol: `ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR`; SQLSTATE: `HY000`

Message: Error reading a replication log encryption header: %s.

`ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR` was added in 8.0.14.

- Error number: `MY-013282`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: `HY000`

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS` was added in 8.0.14.

- Error number: `MY-013283`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: `HY000`

Message: Key %s exists unexpected.

`ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED` was added in 8.0.14.

- Error number: `MY-013284`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`

Message: Failed to generate key, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY` was added in 8.0.14.

- Error number: `MY-013285`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`

Message: Failed to store key, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY` was added in 8.0.14.

- Error number: `MY-013286`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`

Message: Failed to remove key, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY` was added in 8.0.14.

- Error number: `MY-013287`; Symbol: `ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: `HY000`

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED` was added in 8.0.14.

- Error number: `MY-013288`; Symbol: `ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE`; SQLSTATE: `HY000`

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

`ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE` was added in 8.0.14.

-
- Error number: MY-013289; Symbol: ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP; SQLSTATE: HY000

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP was added in 8.0.14.
 - Error number: MY-013290; Symbol: ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP; SQLSTATE: HY000

Message: Ignoring binlog_rotate_encryption_master_key_at_startup because binlog_encryption option is disabled.

ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP was added in 8.0.14.
 - Error number: MY-013291; Symbol: ER_INVALID_ADMIN_ADDRESS; SQLSTATE: HY000

Message: Invalid value for command line option admin-address: '%s'

ER_INVALID_ADMIN_ADDRESS was added in 8.0.14.
 - Error number: MY-013292; Symbol: ER_SERVER_STARTUP_ADMIN_INTERFACE; SQLSTATE: HY000

Message: Admin interface ready for connections, address: '%s' port: %d

ER_SERVER_STARTUP_ADMIN_INTERFACE was added in 8.0.14.
 - Error number: MY-013293; Symbol: ER_CANT_CREATE_ADMIN_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle admin connections (errno= %d)

ER_CANT_CREATE_ADMIN_THREAD was added in 8.0.14.
 - Error number: MY-013294; Symbol: ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID; SQLSTATE: HY000

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID was added in 8.0.14.
 - Error number: MY-013295; Symbol: ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID; SQLSTATE: HY000

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID was added in 8.0.14.
 - Error number: MY-013299; Symbol: ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES; SQLSTATE: HY000

Message: Can not read and process value of User_attributes column from mysql.user table for user: '%s'@'%s'; Ignoring user.

ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES was added in 8.0.14.

-
- Error number: [MY-013300](#); Symbol: [ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)
Message: Second password was used for login by user: '%s'@'%s'.
[ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
 - Error number: [MY-013301](#); Symbol: [ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)
Message: Second password was used for login by user: '%s'@'%s'.
[ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
 - Error number: [MY-013302](#); Symbol: [ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#); SQLSTATE: [HY000](#)
Message: Second password was used for login by user: '%s'@'%s'.
[ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION](#) was added in 8.0.14.
 - Error number: [MY-013303](#); Symbol: [ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED](#); SQLSTATE: [HY000](#)
Message: Error sending transaction '%d:%ld' prepared message from session '%u'.
[ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED](#) was added in 8.0.14.
 - Error number: [MY-013304](#); Symbol: [ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)
Message: Error releasing transaction '%d:%ld' for commit on session '%u' after being prepared on all group members.
[ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED](#) was added in 8.0.14.
 - Error number: [MY-013305](#); Symbol: [ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)
Message: Transaction '%d:%ld' already exists on Group Replication consistency manager while being registered after conflict detection.
[ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION](#) was added in 8.0.14.
 - Error number: [MY-013306](#); Symbol: [ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION](#); SQLSTATE: [HY000](#)
Message: Error registering transaction '%d:%ld' on Group Replication consistency manager after conflict detection.
[ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION](#) was added in 8.0.14.
 - Error number: [MY-013307](#); Symbol: [ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED](#); SQLSTATE: [HY000](#)
Message: Error registering transaction '%d:%ld' from session '%u' to wait for being prepared on all group members.
[ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED](#) was added in 8.0.14.

-
- Error number: MY-013308; Symbol: ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED; SQLSTATE: HY000

Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.

ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED was added in 8.0.14.

- Error number: MY-013309; Symbol: ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE; SQLSTATE: HY000

Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE was added in 8.0.14.

- Error number: MY-013310; Symbol: ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED; SQLSTATE: HY000

Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.

ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED was added in 8.0.14.

- Error number: MY-013311; Symbol: ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED was added in 8.0.14.

- Error number: MY-013312; Symbol: ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE: HY000

Message: Error on session '%u' while waiting for its dependencies to complete commit.

ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED was added in 8.0.14.

- Error number: MY-013313; Symbol: ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED; SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for sync before execution.

ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED was added in 8.0.14.

- Error number: MY-013314; Symbol: ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED; SQLSTATE: HY000

Message: Error sending sync before execution message from session '%u'.

ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED was added in 8.0.14.

-
- Error number: [MY-013315](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Error on transaction from session '%u' while waiting for sync before execution.
[ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED](#) was added in 8.0.14.
 - Error number: [MY-013316](#); Symbol: [ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC](#); SQLSTATE: [HY000](#)
Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.
[ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC](#) was added in 8.0.14.
 - Error number: [MY-013317](#); Symbol: [ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED](#); SQLSTATE: [HY000](#)
Message: Error waiting for group executed transactions commit on session '%u'.
[ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED](#) was added in 8.0.14.
 - Error number: [MY-013320](#); Symbol: [ER_WARN_PROPERTY_STRING_PARSE_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not parse key-value pairs in property string '%s'
[ER_WARN_PROPERTY_STRING_PARSE_FAILED](#) was added in 8.0.14.
 - Error number: [MY-013321](#); Symbol: [ER_INVALID_PROPERTY_KEY](#); SQLSTATE: [HY000](#)
Message: Property key '%s' is invalid.
[ER_INVALID_PROPERTY_KEY](#) was added in 8.0.14.
 - Error number: [MY-013322](#); Symbol: [ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY](#); SQLSTATE: [HY000](#)
Message: Error when extracting the group_replication_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.
[ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY](#) was added in 8.0.14.
 - Error number: [MY-013323](#); Symbol: [ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT](#); SQLSTATE: [HY000](#)
Message: Failed to encrypt content to write into binlog file: %s.
[ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT](#) was added in 8.0.14.
 - Error number: [MY-013324](#); Symbol: [ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)
Message: Cannot get the server version number from the dictionary tablespace header.
[ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER](#) was added in 8.0.14.
 - Error number: [MY-013325](#); Symbol: [ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER](#); SQLSTATE: [HY000](#)
Message: Cannot set the server version number in the dictionary tablespace header.

`ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER` was added in 8.0.14.

- Error number: `MY-013326`; Symbol: `ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Upgrading the server from server version '%u' is not supported.

`ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED` was added in 8.0.14.

- Error number: `MY-013327`; Symbol: `ER_SERVER_UPGRADE_FROM_VERSION`; SQLSTATE: `HY000`

Message: MySQL server upgrading from version '%u' to '%u'.

`ER_SERVER_UPGRADE_FROM_VERSION` was added in 8.0.14.

- Error number: `MY-013328`; Symbol: `ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL`; SQLSTATE: `HY000`

Message: The certification information could not be set in this server: '%s'

`ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL` was added in 8.0.14.

- Error number: `MY-013329`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING`; SQLSTATE: `HY000`

Message: A request to force a new group membership was issued when the member is leaving the group.

`ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING` was added in 8.0.14.

- Error number: `MY-013330`; Symbol: `ER_TRG_WRONG_ORDER`; SQLSTATE: `HY000`

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.

`ER_TRG_WRONG_ORDER` was added in 8.0.14.

- Error number: `MY-013332`; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL`; SQLSTATE: `HY000`

Message: Special handling for group search, {GA} not found

`ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL` was added in 8.0.14.

- Error number: `MY-013333`; Symbol: `ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: User object has group information

`ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO` was added in 8.0.14.

- Error number: `MY-013334`; Symbol: `ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS`; SQLSTATE: `HY000`

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

`ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS` was added in 8.0.14.

- Error number: `MY-013335`; Symbol: `ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE`; SQLSTATE: `HY000`

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

`ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE` was added in 8.0.14.

- Error number: `MY-013336`; Symbol: `ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE`; SQLSTATE: `HY000`

Message: User group retrieval: Group attribute values is NULL.

`ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE` was added in 8.0.14.

- Error number: `MY-013337`; Symbol: `ER_LDAP_AUTH_GRP_DN_PARSING_FAILED`; SQLSTATE: `HY000`

Message: User group retrieval: parsing DN failed.

`ER_LDAP_AUTH_GRP_DN_PARSING_FAILED` was added in 8.0.14.

- Error number: `MY-013338`; Symbol: `ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: Group object has user information

`ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO` was added in 8.0.14.

- Error number: `MY-013339`; Symbol: `ER_LDAP_AUTH_LDAPS`; SQLSTATE: `HY000`

Message: Reserved port for ldaps using ldaps

`ER_LDAP_AUTH_LDAPS` was added in 8.0.14.

- Error number: `MY-013340`; Symbol: `ER_LDAP_MAPPING_GET_USER_PROXY`; SQLSTATE: `HY000`

Message: Get user proxy

`ER_LDAP_MAPPING_GET_USER_PROXY` was added in 8.0.14.

- Error number: `MY-013341`; Symbol: `ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP`; SQLSTATE: `HY000`

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.

`ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP` was added in 8.0.14.

- Error number: `MY-013342`; Symbol: `ER_LDAP_MAPPING_INFO`; SQLSTATE: `HY000`

Message: Get user proxy: configured mapping info: %s

`ER_LDAP_MAPPING_INFO` was added in 8.0.14.

- Error number: `MY-013343`; Symbol: `ER_LDAP_MAPPING_EMPTY_MAPPING`; SQLSTATE: `HY000`

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.

`ER_LDAP_MAPPING_EMPTY_MAPPING` was added in 8.0.14.

- Error number: `MY-013344`; Symbol: `ER_LDAP_MAPPING_PROCESS_MAPPING`; SQLSTATE: `HY000`

Message: Process group proxy mapping

`ER_LDAP_MAPPING_PROCESS_MAPPING` was added in 8.0.14.

-
- Error number: [MY-013345](#); Symbol: [ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE](#); SQLSTATE: [HY000](#)
Message: Check delimiter after quote
[ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE](#) was added in 8.0.14.
 - Error number: [MY-013346](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER](#); SQLSTATE: [HY000](#)
Message: Processing delimiter
[ER_LDAP_MAPPING_PROCESS_DELIMITER](#) was added in 8.0.14.
 - Error number: [MY-013347](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator = not found, resetting position
[ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND](#) was added in 8.0.14.
 - Error number: [MY-013348](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA](#); SQLSTATE: [HY000](#)
Message: "Processing delimiter, failed to get data for = separator try for separator ,."
[ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA](#) was added in 8.0.14.
 - Error number: [MY-013349](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator , not found, resetting position
[ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND](#) was added in 8.0.14.
 - Error number: [MY-013350](#); Symbol: [ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP](#); SQLSTATE: [HY000](#)
Message: Processing delimiter: No mapping separator is found, end of group information
[ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP](#) was added in 8.0.14.
 - Error number: [MY-013351](#); Symbol: [ER_LDAP_MAPPING_GETTING_NEXT_MAPPING](#); SQLSTATE: [HY000](#)
Message: Getting next mapping information
[ER_LDAP_MAPPING_GETTING_NEXT_MAPPING](#) was added in 8.0.14.
 - Error number: [MY-013352](#); Symbol: [ER_LDAP_MAPPING_PARSING_CURRENT_STATE](#); SQLSTATE: [HY000](#)
Message: Parsing mapping, current state: %d delimiter char: %c
[ER_LDAP_MAPPING_PARSING_CURRENT_STATE](#) was added in 8.0.14.
 - Error number: [MY-013353](#); Symbol: [ER_LDAP_MAPPING_PARSING_MAPPING_INFO](#); SQLSTATE: [HY000](#)
Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s
[ER_LDAP_MAPPING_PARSING_MAPPING_INFO](#) was added in 8.0.14.
 - Error number: [MY-013354](#); Symbol: [ER_LDAP_MAPPING_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: Mapping parsing error

[ER_LDAP_MAPPING_PARSING_ERROR](#) was added in 8.0.14.

- Error number: [MY-013355](#); Symbol: [ER_LDAP_MAPPING_TRIMMING_SPACES](#); SQLSTATE: [HY000](#)

Message: Trimming left spaces

[ER_LDAP_MAPPING_TRIMMING_SPACES](#) was added in 8.0.14.

- Error number: [MY-013356](#); Symbol: [ER_LDAP_MAPPING_IS_QUOTE](#); SQLSTATE: [HY000](#)

Message: Checking if current characters is quote

[ER_LDAP_MAPPING_IS_QUOTE](#) was added in 8.0.14.

- Error number: [MY-013357](#); Symbol: [ER_LDAP_MAPPING_NON_DESIRED_STATE](#); SQLSTATE: [HY000](#)

Message: Not desired state or un-defined states.

[ER_LDAP_MAPPING_NON_DESIRED_STATE](#) was added in 8.0.14.

- Error number: [MY-013358](#); Symbol: [ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP](#); SQLSTATE: [HY000](#)

Message: Invalid value for named_pipe_full_access_group.

[ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP](#) was added in 8.0.14.

- Error number: [MY-013359](#); Symbol: [ER_PREPARE_FOR_SECONDARY_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using a secondary storage engine.

[ER_PREPARE_FOR_SECONDARY_ENGINE](#) was added in 8.0.16.

- Error number: [MY-013360](#); Symbol: [ER_SERVER_WARN_DEPRECATED](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

[ER_SERVER_WARN_DEPRECATED](#) was added in 8.0.16.

- Error number: [MY-013361](#); Symbol: [ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory_roles: AuthId '%s'@'%s' has '%s' privilege.

[ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#) was added in 8.0.16.

- Error number: [MY-013362](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION](#); SQLSTATE: [HY000](#)

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

[ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION](#) was added in 8.0.16.

- Error number: [MY-013363](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected

and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

[ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#) was added in 8.0.16.

- Error number: [MY-013368](#); Symbol: [ER_TURNING_ON_PARTIAL_REVOKES](#); SQLSTATE: [HY000](#)

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial_revokes'.

[ER_TURNING_ON_PARTIAL_REVOKES](#) was added in 8.0.16.

- Error number: [MY-013369](#); Symbol: [ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT](#); SQLSTATE: [HY000](#)

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

[ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT](#) was added in 8.0.16.

- Error number: [MY-013370](#); Symbol: [ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

[ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS](#) was added in 8.0.16.

- Error number: [MY-013371](#); Symbol: [ER_WARN_INVALID_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

[ER_WARN_INVALID_DB_RESTRICTIONS](#) was added in 8.0.16.

- Error number: [MY-013372](#); Symbol: [ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL](#); SQLSTATE: [HY000](#)

Message: '%s' is an invalid value for group_replication_communication_protocol_join, please use a MySQL version between 5.7.14 and this server's version

[ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL](#) was added in 8.0.16.

- Error number: [MY-013373](#); Symbol: [ER_GRP_RPL_STARTED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Started auto-rejoin procedure attempt %lu of %lu

[ER_GRP_RPL_STARTED_AUTO_REJOIN](#) was added in 8.0.16.

- Error number: [MY-013374](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the auto-rejoin procedure

[ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN](#) was added in 8.0.16.

- Error number: [MY-013375](#); Symbol: [ER_GRP_RPL_FINISHED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.

[ER_GRP_RPL_FINISHED_AUTO_REJOIN](#) was added in 8.0.16.

-
- Error number: `MY-013376`; Symbol: `ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP`; SQLSTATE: `HY000`
Message: The member is configured with a default_table_encryption option value '%d' different from the group '%d'. The member will now exit the group.
`ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP` was added in 8.0.16.
 - Error number: `MY-013377`; Symbol: `ER_SERVER_UPGRADE_OFF`; SQLSTATE: `HY000`
Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.
`ER_SERVER_UPGRADE_OFF` was added in 8.0.16.
 - Error number: `MY-013378`; Symbol: `ER_SERVER_UPGRADE_SKIP`; SQLSTATE: `HY000`
Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.
`ER_SERVER_UPGRADE_SKIP` was added in 8.0.16.
 - Error number: `MY-013379`; Symbol: `ER_SERVER_UPGRADE_PENDING`; SQLSTATE: `HY000`
Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.
`ER_SERVER_UPGRADE_PENDING` was added in 8.0.16.
 - Error number: `MY-013380`; Symbol: `ER_SERVER_UPGRADE_FAILED`; SQLSTATE: `HY000`
Message: Failed to upgrade server.
`ER_SERVER_UPGRADE_FAILED` was added in 8.0.16.
 - Error number: `MY-013381`; Symbol: `ER_SERVER_UPGRADE_STATUS`; SQLSTATE: `HY000`
Message: Server upgrade from '%d' to '%d' %s.
`ER_SERVER_UPGRADE_STATUS` was added in 8.0.16.
 - Error number: `MY-013382`; Symbol: `ER_SERVER_UPGRADE_REPAIR_REQUIRED`; SQLSTATE: `HY000`
Message: Table '%s' requires repair.
`ER_SERVER_UPGRADE_REPAIR_REQUIRED` was added in 8.0.16.
 - Error number: `MY-013383`; Symbol: `ER_SERVER_UPGRADE_REPAIR_STATUS`; SQLSTATE: `HY000`
Message: Table '%s' repair %s.
`ER_SERVER_UPGRADE_REPAIR_STATUS` was added in 8.0.16.
 - Error number: `MY-013384`; Symbol: `ER_SERVER_UPGRADE_INFO_FILE`; SQLSTATE: `HY000`
Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.
`ER_SERVER_UPGRADE_INFO_FILE` was added in 8.0.16.
 - Error number: `MY-013385`; Symbol: `ER_SERVER_UPGRADE_SYS_SCHEMA`; SQLSTATE: `HY000`
Message: Upgrading the sys schema.
`ER_SERVER_UPGRADE_SYS_SCHEMA` was added in 8.0.16.

-
- Error number: [MY-013386](#); Symbol: [ER_SERVER_UPGRADE_MYSQL_TABLES](#); SQLSTATE: [HY000](#)
Message: Running queries to upgrade MySQL server.
[ER_SERVER_UPGRADE_MYSQL_TABLES](#) was added in 8.0.16.
 - Error number: [MY-013387](#); Symbol: [ER_SERVER_UPGRADE_SYSTEM_TABLES](#); SQLSTATE: [HY000](#)
Message: Upgrading system table data.
[ER_SERVER_UPGRADE_SYSTEM_TABLES](#) was added in 8.0.16.
 - Error number: [MY-013388](#); Symbol: [ER_SERVER_UPGRADE_EMPTY_SYS](#); SQLSTATE: [HY000](#)
Message: Found empty sys database. Installing the sys schema.
[ER_SERVER_UPGRADE_EMPTY_SYS](#) was added in 8.0.16.
 - Error number: [MY-013389](#); Symbol: [ER_SERVER_UPGRADE_NO_SYS_VERSION](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.
[ER_SERVER_UPGRADE_NO_SYS_VERSION](#) was added in 8.0.16.
 - Error number: [MY-013390](#); Symbol: [ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with a sys.version view, but it returns no results.
[ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#) was added in 8.0.16.
 - Error number: [MY-013391](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#); SQLSTATE: [HY000](#)
Message: Found outdated sys schema version %s.
[ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#) was added in 8.0.16.
 - Error number: [MY-013392](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#); SQLSTATE: [HY000](#)
Message: The sys schema is already up to date (version %s).
[ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#) was added in 8.0.16.
 - Error number: [MY-013393](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#); SQLSTATE: [HY000](#)
Message: Found %d sys %s, but expected %d. Re-installing the sys schema.
[ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#) was added in 8.0.16.
 - Error number: [MY-013394](#); Symbol: [ER_SERVER_UPGRADE_CHECKING_DB](#); SQLSTATE: [HY000](#)
Message: Checking '%s' schema.
[ER_SERVER_UPGRADE_CHECKING_DB](#) was added in 8.0.16.

-
- Error number: [MY-013395](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#); SQLSTATE: [HY000](#)

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

[ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#) was added in 8.0.16.
 - Error number: [MY-013396](#); Symbol: [ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#); SQLSTATE: [HY000](#)

Message: Error in DDL Log recovery during Post-Recovery processing.

[ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#) was added in 8.0.16.
 - Error number: [MY-013397](#); Symbol: [ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

[ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#) was added in 8.0.16.
 - Error number: [MY-013398](#); Symbol: [ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#); SQLSTATE: [HY000](#)

Message: Error in DLL Log cleanup during Post-DDL processing.

[ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#) was added in 8.0.16.
 - Error number: [MY-013399](#); Symbol: [ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.

[ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#) was added in 8.0.16.
 - Error number: [MY-013400](#); Symbol: [ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#); SQLSTATE: [HY000](#)

Message: Upgrade of help tables %s.

[ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#) was added in 8.0.16.
 - Error number: [MY-013401](#); Symbol: [ER_GRP_RPL_SRV_GTID_WAIT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when waiting for the server to execute local transactions in order assure the group change proper logging

[ER_GRP_RPL_SRV_GTID_WAIT_ERROR](#) was added in 8.0.16, removed after 8.0.31.
 - Error number: [MY-013402](#); Symbol: [ER_GRP_DELAYED_VCLE_LOGGING](#); SQLSTATE: [HY000](#)

Message: Unable to log the group change View log event in its exaction position in the log. This will not however affect the group replication recovery process or the overall plugin process.

[ER_GRP_DELAYED_VCLE_LOGGING](#) was added in 8.0.16, removed after 8.0.31.
 - Error number: [MY-013404](#); Symbol: [ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#); SQLSTATE: [HY000](#)

Message: Unable to create a new binlog file: Table `mysql.gtid_executed` couldn't be opened. %s

[ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#) was added in 8.0.16.

-
- Error number: MY-013405; Symbol: ER_NETWORK_NAMESPACES_NOT_SUPPORTED; SQLSTATE: HY000
Message: Network Namespaces is not supported on this platform
ER_NETWORK_NAMESPACES_NOT_SUPPORTED was added in 8.0.16.
 - Error number: MY-013406; Symbol: ER_UNKNOWN_NETWORK_NAMESPACE; SQLSTATE: HY000
Message: Unknown network namespace '%s'
ER_UNKNOWN_NETWORK_NAMESPACE was added in 8.0.16.
 - Error number: MY-013407; Symbol: ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS; SQLSTATE: HY000
Message: Network namespace not allowed for wildcard interface address
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS was added in 8.0.16.
 - Error number: MY-013408; Symbol: ER_SETNS_FAILED; SQLSTATE: HY000
Message: setns() failed with error '%s'
ER_SETNS_FAILED was added in 8.0.16.
 - Error number: MY-013409; Symbol: ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND; SQLSTATE: HY000
Message: Wildcard address value not allowed for multivalued bind address
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND was added in 8.0.16.
 - Error number: MY-013410; Symbol: ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG; SQLSTATE: HY000
Message: The path to a special network namespace file is too long. (got %u > max %u)
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG was added in 8.0.16.
 - Error number: MY-013411; Symbol: ER_IB_MSG_TOO_LONG_PATH; SQLSTATE: HY000
Message: Cannot create tablespace '%s'. The filepath is too long for this OS.
ER_IB_MSG_TOO_LONG_PATH was added in 8.0.16.
 - Error number: MY-013412; Symbol: ER_IB_RECV_FIRST_REC_GROUP_INVALID; SQLSTATE: HY000
Message: The last block of redo had corrupted first_rec_group and became fixed (%u -> %u).
ER_IB_RECV_FIRST_REC_GROUP_INVALID was added in 8.0.16.
 - Error number: MY-013413; Symbol: ER_DD_UPGRADE_COMPLETED; SQLSTATE: HY000
Message: Data dictionary upgrade from version '%u' to '%u' completed.
ER_DD_UPGRADE_COMPLETED was added in 8.0.16.
 - Error number: MY-013414; Symbol: ER_SSL_SERVER_CERT_VERIFY_FAILED; SQLSTATE: HY000
Message: Server SSL certificate doesn't verify: %s

`ER_SSL_SERVER_CERT_VERIFY_FAILED` was added in 8.0.16.

- Error number: `MY-013415`; Symbol: `ER_PERSIST_OPTION_USER_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a user name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_USER_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013416`; Symbol: `ER_PERSIST_OPTION_HOST_TRUNCATED`; SQLSTATE: `HY000`

Message: Truncated a host name for %s that was too long while reading the persisted variables file

`ER_PERSIST_OPTION_HOST_TRUNCATED` was added in 8.0.16.

- Error number: `MY-013417`; Symbol: `ER_NET_WAIT_ERROR`; SQLSTATE: `HY000`

Message: The wait_timeout period was exceeded, the idle time since last command was too long.

`ER_NET_WAIT_ERROR` was added in 8.0.16.

- Error number: `MY-013418`; Symbol: `ER_IB_MSG_1285`; SQLSTATE: `HY000`

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.

`ER_IB_MSG_1285` was added in 8.0.16.

- Error number: `MY-013419`; Symbol: `ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED`; SQLSTATE: `HY000`

Message: CLOCK_MONOTONIC is unsupported, so do not change the system time when MySQL is running !

`ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED` was added in 8.0.16.

- Error number: `MY-013420`; Symbol: `ER_IB_MSG_CLOCK_GETTIME_FAILED`; SQLSTATE: `HY000`

Message: clock_gettime() failed: %s

`ER_IB_MSG_CLOCK_GETTIME_FAILED` was added in 8.0.16.

- Error number: `MY-013421`; Symbol: `ER_PLUGIN_NOT_EARLY_DUP`; SQLSTATE: `HY000`

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

`ER_PLUGIN_NOT_EARLY_DUP` was added in 8.0.16.

- Error number: `MY-013422`; Symbol: `ER_PLUGIN_NO_INSTALL_DUP`; SQLSTATE: `HY000`

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

`ER_PLUGIN_NO_INSTALL_DUP` was added in 8.0.16.

- Error number: `MY-013425`; Symbol: `ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT`; SQLSTATE: `HY000`

Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.

`ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT` was added in 8.0.16.

-
- Error number: MY-013426; Symbol: ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE; SQLSTATE: HY000
Message: Member version is read compatible with the group.
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE was added in 8.0.16.
 - Error number: MY-013427; Symbol: ER_LOCK_ORDER_INIT_FAILED; SQLSTATE: HY000
Message: Lock order disabled (reason: init failed).
ER_LOCK_ORDER_INIT_FAILED was added in 8.0.16.
 - Error number: MY-013428; Symbol: ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID; SQLSTATE: HY000
Message: Keyring ID timestamp value is invalid: '%s'
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID was added in 8.0.16.
 - Error number: MY-013429; Symbol: ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID; SQLSTATE: HY000
Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID was added in 8.0.16.
 - Error number: MY-013430; Symbol: ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT; SQLSTATE: HY000
Message: Cannot process audit log file. File name does not have required format: '%s'
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT was added in 8.0.16.
 - Error number: MY-013431; Symbol: ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING; SQLSTATE: HY000
Message: Cannot process audit log file. File name keyring ID value is missing: '%s'
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING was added in 8.0.16.
 - Error number: MY-013432; Symbol: ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED; SQLSTATE: HY000
Message: Audit log file has been successfully processed: '%s'
ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED was added in 8.0.16.
 - Error number: MY-013433; Symbol: ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING; SQLSTATE: HY000
Message: Could not open audit log file for reading: '%s'
ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING was added in 8.0.16.
 - Error number: MY-013434; Symbol: ER_AUDIT_LOG_INVALID_FILE_CONTENT; SQLSTATE: HY000
Message: Invalid audit log file content: '%s'
ER_AUDIT_LOG_INVALID_FILE_CONTENT was added in 8.0.16.

-
- Error number: [MY-013435](#); Symbol: [ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot read password: '%s'.

[ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013436](#); Symbol: [ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot store password: '%s'.

[ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013437](#); Symbol: [ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot remove password: '%s'.

[ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013438](#); Symbol: [ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#); SQLSTATE: [HY000](#)

Message: 'audit_log' password has been copied into '%s' and will be removed with first purged password.

[ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#) was added in 8.0.16.
 - Error number: [MY-013447](#); Symbol: [ER_LDAP_EMPTY_USERDN_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Empty user dn or password is not allowed, not attempting LDAP bind.

[ER_LDAP_EMPTY_USERDN_PASSWORD](#) was added in 8.0.16.
 - Error number: [MY-013449](#); Symbol: [ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG](#); SQLSTATE: [HY000](#)

Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.

[ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG](#) was added in 8.0.17.
 - Error number: [MY-013450](#); Symbol: [ER_LOCK_ORDER_FAILED_WRITE_FILE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER: Failed to write to file <%s>.

[ER_LOCK_ORDER_FAILED_WRITE_FILE](#) was added in 8.0.17.
 - Error number: [MY-013451](#); Symbol: [ER_LOCK_ORDER_FAILED_READ_FILE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER: Failed to read from file <%s>.

[ER_LOCK_ORDER_FAILED_READ_FILE](#) was added in 8.0.17.
 - Error number: [MY-013452](#); Symbol: [ER_LOCK_ORDER_MESSAGE](#); SQLSTATE: [HY000](#)

Message: LOCK_ORDER message: %s

[ER_LOCK_ORDER_MESSAGE](#) was added in 8.0.17.
 - Error number: [MY-013453](#); Symbol: [ER_LOCK_ORDER_DEPENDENCIES_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s

[ER_LOCK_ORDER_DEPENDENCIES_SYNTAX](#) was added in 8.0.17.

- Error number: [MY-013454](#); Symbol: [ER_LOCK_ORDER_SCANNER_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Lock order scanner: (%d:%d) - (%d:%d) : %s

[ER_LOCK_ORDER_SCANNER_SYNTAX](#) was added in 8.0.17.

- Error number: [MY-013455](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE_DELETABLE](#); SQLSTATE: [HY000](#)

Message: The newly created data directory %s by --initialize is unusable. You can remove it.

[ER_DATA_DIRECTORY_UNUSABLE_DELETABLE](#) was added in 8.0.17.

- Error number: [MY-013456](#); Symbol: [ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED](#); SQLSTATE: [HY000](#)

Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option innodb_limit_optimistic_insert_debug is being used try tweaking it to include more records in a page.

[ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED](#) was added in 8.0.17.

- Error number: [MY-013457](#); Symbol: [ER_IB_CLONE_START_STOP](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_CLONE_START_STOP](#) was added in 8.0.17.

- Error number: [MY-013458](#); Symbol: [ER_IB_CLONE_OPERATION](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_CLONE_OPERATION](#) was added in 8.0.17.

- Error number: [MY-013459](#); Symbol: [ER_IB_CLONE_RESTART](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_CLONE_RESTART](#) was added in 8.0.17.

- Error number: [MY-013460](#); Symbol: [ER_IB_CLONE_USER_DATA](#); SQLSTATE: [HY000](#)

Message: Clone removing all user data for provisioning: %s

[ER_IB_CLONE_USER_DATA](#) was added in 8.0.17.

- Error number: [MY-013461](#); Symbol: [ER_IB_CLONE_NON_INNODB_TABLE](#); SQLSTATE: [HY000](#)

Message: Non innodb table: %s.%s is not cloned and is empty.

[ER_IB_CLONE_NON_INNODB_TABLE](#) was added in 8.0.17.

- Error number: [MY-013462](#); Symbol: [ER_CLONE_SHUTDOWN_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.

[ER_CLONE_SHUTDOWN_TRACE](#) was added in 8.0.17.

-
- Error number: [MY-013463](#); Symbol: [ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.

[ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#) was added in 8.0.17.

- Error number: [MY-013464](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when configuring the remote cloning process: %s

[ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#) was added in 8.0.17.

- Error number: [MY-013465](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when cloning from another server: %s

[ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#) was added in 8.0.17.

- Error number: [MY-013466](#); Symbol: [ER_GRP_RPL_RECOVERY_EVAL_ERROR](#); SQLSTATE: [HY000](#)

Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s

[ER_GRP_RPL_RECOVERY_EVAL_ERROR](#) was added in 8.0.17.

- Error number: [MY-013467](#); Symbol: [ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#); SQLSTATE: [HY000](#)

Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.

[ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#) was added in 8.0.17.

- Error number: [MY-013468](#); Symbol: [ER_GRP_RPL_CANT_KILL_THREAD](#); SQLSTATE: [HY000](#)

Message: The group replication plugin could not kill the plugin routine for %s. %s

[ER_GRP_RPL_CANT_KILL_THREAD](#) was added in 8.0.17.

- Error number: [MY-013469](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.

[ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#) was added in 8.0.17.

- Error number: [MY-013470](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#); SQLSTATE: [HY000](#)

Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.

[ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#) was added in 8.0.17.

- Error number: [MY-013471](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CHOICE](#); SQLSTATE: [HY000](#)

Message: Distributed recovery will transfer data using: %s

`ER_GRP_RPL_RECOVERY_STRAT_CHOICE` was added in 8.0.17.

- Error number: `MY-013472`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_FALLBACK`; SQLSTATE: `HY000`

Message: Due to some issue on the previous step distributed recovery is now executing: %s

`ER_GRP_RPL_RECOVERY_STRAT_FALLBACK` was added in 8.0.17.

- Error number: `MY-013473`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK`; SQLSTATE: `HY000`

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

`ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK` was added in 8.0.17.

- Error number: `MY-013474`; Symbol: `ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE`; SQLSTATE: `HY000`

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

`ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE` was added in 8.0.17, removed after 8.0.32.

- Error number: `MY-013474`; Symbol: `ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE`; SQLSTATE: `HY000`

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

`ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE` was added in 8.0.33.

- Error number: `MY-013475`; Symbol: `ER_UNKNOWN_TABLE_IN_UPGRADE`; SQLSTATE: `HY000`

Message: Unknown table '%s'

`ER_UNKNOWN_TABLE_IN_UPGRADE` was added in 8.0.17.

- Error number: `MY-013476`; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE`; SQLSTATE: `HY000`

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

`ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE` was added in 8.0.17.

- Error number: `MY-013477`; Symbol: `ER_XA_CANT_CREATE_MDL_BACKUP`; SQLSTATE: `HY000`

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.

`ER_XA_CANT_CREATE_MDL_BACKUP` was added in 8.0.13.

- Error number: `MY-013478`; Symbol: `ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED`; SQLSTATE: `HY000`

Message: SUPER privilege or AUDIT_ADMIN role required for '%s'@'%s' user.

`ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED` was added in 8.0.11.

-
- Error number: [MY-013479](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid argument type

[ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE](#) was added in 8.0.11.
 - Error number: [MY-013480](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT](#); SQLSTATE: [HY000](#)

Message: Invalid argument count

[ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT](#) was added in 8.0.11.
 - Error number: [MY-013481](#); Symbol: [ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED](#); SQLSTATE: [HY000](#)

Message: audit_log plugin has not been installed using INSTALL PLUGIN syntax.

[ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED](#) was added in 8.0.11.
 - Error number: [MY-013482](#); Symbol: [ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid "max_array_length" argument type.

[ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE](#) was added in 8.0.11.
 - Error number: [MY-013483](#); Symbol: [ER_LOG_CANNOT_WRITE_EXTENDED](#); SQLSTATE: [HY000](#)

Message: Failed to write to %s: %s (%s)

[ER_LOG_CANNOT_WRITE_EXTENDED](#) was added in 8.0.17.
 - Error number: [MY-013484](#); Symbol: [ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED](#); SQLSTATE: [HY000](#)

Message: Upgrading from server version %d with partitioned tables and lower_case_table_names == 1 on a case sensitive file system may cause issues, and is therefore prohibited. To upgrade anyway, restart the new server version with the command line option 'upgrade=FORCE'. When upgrade is completed, please execute 'RENAME TABLE <part_table_name> TO <new_table_name>; RENAME TABLE <new_table_name> TO <part_table_name>;' for each of the partitioned tables. Please see the documentation for further information.

[ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED](#) was added in 8.0.17, removed after 8.0.18.
 - Error number: [MY-013485](#); Symbol: [ER_KEYRING_AWS_INCORRECT_PROXY](#); SQLSTATE: [HY000](#)

Message: Incorrect environment variable %s, invalid port: %s

[ER_KEYRING_AWS_INCORRECT_PROXY](#) was added in 8.0.18.
 - Error number: [MY-013486](#); Symbol: [ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS](#); SQLSTATE: [HY000](#)

Message: The server was automatically set into offline mode after an error was detected.

[ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS](#) was added in 8.0.18.

-
- Error number: [MY-013487](#); Symbol: [ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.

[ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR](#) was added in 8.0.18.

- Error number: [MY-013488](#); Symbol: [ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid SOURCE_COMPRESSION_ALGORITHMS '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).

[ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG](#) was added in 8.0.18.

- Error number: [MY-013489](#); Symbol: [ER_WARN_WRONG_COMPRESSION_LEVEL_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid SOURCE_ZSTD_COMPRESSION_LEVEL found in repository for channel '%s'. Resetting to %u.

[ER_WARN_WRONG_COMPRESSION_LEVEL_LOG](#) was added in 8.0.18.

- Error number: [MY-013490](#); Symbol: [ER_PROTOCOL_COMPRESSION_RESET_LOG](#); SQLSTATE: [HY000](#)

Message: Option --protocol-compression-algorithms is reset to default value.

[ER_PROTOCOL_COMPRESSION_RESET_LOG](#) was added in 8.0.18.

- Error number: [MY-013491](#); Symbol: [ER_XPLUGIN_COMPRESSION_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error while compressing outgoing data - %s

[ER_XPLUGIN_COMPRESSION_ERROR](#) was added in 8.0.18.

- Error number: [MY-013492](#); Symbol: [ER_MYSQLBACKUP_MSG](#); SQLSTATE: [HY000](#)

Message: %s

[ER_MYSQLBACKUP_MSG](#) was added in 8.0.18.

- Error number: [MY-013493](#); Symbol: [ER_WARN_UNKNOWN_KEYRING_AWS_REGION](#); SQLSTATE: [HY000](#)

Message: Unknown keyring_aws_region '%s'. Connection to AWS KMS may fail.

[ER_WARN_UNKNOWN_KEYRING_AWS_REGION](#) was added in 8.0.18.

- Error number: [MY-013494](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to '%s'@'%s', but this is not an existing user. Correct this before starting replication threads.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#) was added in 8.0.18.

-
- Error number: [MY-013495](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER to correct the configuration.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT](#) was added in 8.0.18.

- Error number: [MY-013496](#); Symbol: [ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to '%s'@'%s', but this user does not have REPLICATION_APPLIER privilege. Correct this before starting the replication threads.

[ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#) was added in 8.0.18.

- Error number: [MY-013497](#); Symbol: [ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on master. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

[ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#) was added in 8.0.18, removed after 8.0.30.

- Error number: [MY-013497](#); Symbol: [ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

[ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#) was added in 8.0.31.

- Error number: [MY-013498](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#); SQLSTATE: [HY000](#)

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s

[ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#) was added in 8.0.18, removed after 8.0.32.

- Error number: [MY-013498](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s

[ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#) was added in 8.0.33.

- Error number: [MY-013499](#); Symbol: [ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot generate password: '%s'

[ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#) was added in 8.0.18.

-
- Error number: MY-013500; Symbol: ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD; SQLSTATE: HY000

Message: Failed to generate a random password for root. Probabably not enough entrophy.

ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD was added in 8.0.18.

- Error number: MY-013501; Symbol: ER_PLUGIN_LOAD_OPTIONS_IGNORED; SQLSTATE: HY000

Message: Ignoring --plugin-load[_add] list as the server is running with --initialize(-insecure).

ER_PLUGIN_LOAD_OPTIONS_IGNORED was added in 8.0.18.

- Error number: MY-013502; Symbol: ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES; SQLSTATE: HY000

Message: Cannot set mandatory_roles: AuthId '%s'@'%s' has '%s' privilege. AuthId(s) set in the mandatory_roles are ignored.

ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES was added in 8.0.18.

- Error number: MY-013503; Symbol: ER_IB_MSG_SKIP_HIDDEN_DIR; SQLSTATE: HY000

Message: Directory '%s' will not be scanned because it is a hidden directory.

ER_IB_MSG_SKIP_HIDDEN_DIR was added in 8.0.18.

- Error number: MY-013504; Symbol: ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER_EOF; SQLSTATE: HY000

Message: Server was not able to find a rotate event from master server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER_EOF was added in 8.0.19, removed after 8.0.32.

- Error number: MY-013504; Symbol: ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE_EOF; SQLSTATE: HY000

Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE_EOF was added in 8.0.33.

- Error number: MY-013505; Symbol: ER_IB_LOB_ROLLBACK_INDEX_LEN; SQLSTATE: HY000

Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu. (iteration %llu)

ER_IB_LOB_ROLLBACK_INDEX_LEN was added in 8.0.19.

- Error number: MY-013506; Symbol: ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD; SQLSTATE: HY000

Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s

ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD was added in 8.0.19.

-
- Error number: [MY-013507](#); Symbol: [ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as an invalid event according to [REQUIRE_ROW_FORMAT](#) was found.

[ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#) was added in 8.0.19, removed after 8.0.32.
 - Error number: [MY-013507](#); Symbol: [ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)

Message: The queue event failed for channel '%s' as an invalid event according to [REQUIRE_ROW_FORMAT](#) was found.

[ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#) was added in 8.0.33.
 - Error number: [MY-013508](#); Symbol: [ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)

Message: The application of relay events failed for channel '%s' as an invalid event according to [REQUIRE_ROW_FORMAT](#) was found.

[ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#) was added in 8.0.19, removed after 8.0.30.
 - Error number: [MY-013508](#); Symbol: [ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION](#); SQLSTATE: [HY000](#)

Message: The application of relay events failed for channel '%s' as an invalid event according to [REQUIRE_ROW_FORMAT](#) was found.

[ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION](#) was added in 8.0.31.
 - Error number: [MY-013509](#); Symbol: [ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET](#); SQLSTATE: [HY000](#)

Message: [PRIVILEGE_CHECKS_USER](#) for replication channel '%s' can't be set to '%s'@'%s' unless [REQUIRE_ROW_FORMAT](#) is also set to %d.

[ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET](#) was added in 8.0.19.
 - Error number: [MY-013510](#); Symbol: [ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the SQL thread while applying an event.

[ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#) was added in 8.0.19, removed after 8.0.32.
 - Error number: [MY-013510](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the SQL thread while applying an event.

[ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#) was added in 8.0.33.

-
- Error number: MY-013511; Symbol: ER_IB_MSG_UPGRADE_PARTITION_FILE; SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade

ER_IB_MSG_UPGRADE_PARTITION_FILE was added in 8.0.19.

- Error number: MY-013512; Symbol: ER_IB_MSG_DOWNGRADE_PARTITION_FILE; SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade

ER_IB_MSG_DOWNGRADE_PARTITION_FILE was added in 8.0.19.

- Error number: MY-013513; Symbol: ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT; SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' for import

ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT was added in 8.0.19.

- Error number: MY-013514; Symbol: ER_IB_WARN_OPEN_PARTITION_FILE; SQLSTATE: HY000

Message: Unable to open partition file with new name '%s'. Please check if innodb_directories is set to include all external file paths

ER_IB_WARN_OPEN_PARTITION_FILE was added in 8.0.19.

- Error number: MY-013515; Symbol: ER_IB_MSG_FIL_STATE_MOVED_CORRECTED; SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

ER_IB_MSG_FIL_STATE_MOVED_CORRECTED was added in 8.0.19.

- Error number: MY-013516; Symbol: ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH; SQLSTATE: HY000

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH was added in 8.0.19.

- Error number: MY-013517; Symbol: ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME; SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME was added in 8.0.19.

- Error number: MY-013518; Symbol: ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY; SQLSTATE: HY000

Message: %s Too many files have been moved, disabling logging of detailed messages

ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY was added in 8.0.19.

- Error number: MY-013519; Symbol: ER_GR_ELECTED_PRIMARY_GTID_INFORMATION; SQLSTATE: HY000

Message: Elected primary member %s: %s

ER_GR_ELECTED_PRIMARY_GTID_INFORMATION was added in 8.0.19.

-
- Error number: [MY-013520](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters is not allowed with lower_case_table_names = 1.

[ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED](#) was added in 8.0.19.
 - Error number: [MY-013521](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters is not allowed with lower_case_table_names = 1.

[ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#) was added in 8.0.19.
 - Error number: [MY-013522](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

[ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#) was added in 8.0.19.
 - Error number: [MY-013523](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.

[ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#) was added in 8.0.19.
 - Error number: [MY-013524](#); Symbol: [ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Table Partition: %s is not found in InnoDB dictionary

[ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#) was added in 8.0.19.
 - Error number: [MY-013525](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

[ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#) was added in 8.0.19.
 - Error number: [MY-013526](#); Symbol: [ER_INNOODB_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: %s

[ER_INNOODB_OUT_OF_RESOURCES](#) was added in 8.0.19.
 - Error number: [MY-013527](#); Symbol: [ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Upgrade cannot proceed due to an existing prepared XA transaction.

[ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION](#) was added in 8.0.19.
 - Error number: [MY-013528](#); Symbol: [ER_MIGRATE_TABLE_TO_DD_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for key_info when migrating table %s.%s

[ER_MIGRATE_TABLE_TO_DD_OOM](#) was added in 8.0.19.

- Error number: [MY-013529](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#); SQLSTATE: [HY000](#)

Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'

[ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#) was added in 8.0.19.

- Error number: [MY-013530](#); Symbol: [ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to delete 5.7 undo tablespace: %s during upgrade

[ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL](#) was added in 8.0.19.

- Error number: [MY-013531](#); Symbol: [ER_IB_MSG_DBLWR_1285](#); SQLSTATE: [HY000](#)

Message: Empty doublewrite file: %s

[ER_IB_MSG_DBLWR_1285](#) was added in 8.0.20.

- Error number: [MY-013532](#); Symbol: [ER_IB_MSG_DBLWR_1286](#); SQLSTATE: [HY000](#)

Message: Using '%s' for doublewrite

[ER_IB_MSG_DBLWR_1286](#) was added in 8.0.20.

- Error number: [MY-013533](#); Symbol: [ER_IB_MSG_DBLWR_1287](#); SQLSTATE: [HY000](#)

Message: Error reading doublewrite buffer from the system tablespace

[ER_IB_MSG_DBLWR_1287](#) was added in 8.0.20.

- Error number: [MY-013534](#); Symbol: [ER_IB_MSG_DBLWR_1288](#); SQLSTATE: [HY000](#)

Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

[ER_IB_MSG_DBLWR_1288](#) was added in 8.0.20.

- Error number: [MY-013535](#); Symbol: [ER_IB_MSG_DBLWR_1290](#); SQLSTATE: [HY000](#)

Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb_force_recovery=6

[ER_IB_MSG_DBLWR_1290](#) was added in 8.0.20.

- Error number: [MY-013536](#); Symbol: [ER_IB_MSG_DBLWR_1291](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1291](#) was added in 8.0.20, removed after 8.0.20.

- Error number: [MY-013536](#); Symbol: [ER_IB_MSG_BAD_DBLWR_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: The doublewrite filename '%s' is incorrect.

[ER_IB_MSG_BAD_DBLWR_FILE_NAME](#) was added in 8.0.21.

- Error number: [MY-013537](#); Symbol: [ER_IB_MSG_DBLWR_1292](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1292](#) was added in 8.0.20, removed after 8.0.20.

- Error number: [MY-013538](#); Symbol: [ER_IB_MSG_DBLWR_1293](#); SQLSTATE: [HY000](#)

Message: Doublewrite file create failed: %s

[ER_IB_MSG_DBLWR_1293](#) was added in 8.0.20.

- Error number: [MY-013539](#); Symbol: [ER_IB_MSG_DBLWR_1294](#); SQLSTATE: [HY000](#)

Message: DBLWRThread: pthread_setaffinity() failed!

[ER_IB_MSG_DBLWR_1294](#) was added in 8.0.20.

- Error number: [MY-013540](#); Symbol: [ER_IB_MSG_DBLWR_1295](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1295](#) was added in 8.0.20.

- Error number: [MY-013541](#); Symbol: [ER_IB_MSG_DBLWR_1296](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1296](#) was added in 8.0.20.

- Error number: [MY-013542](#); Symbol: [ER_IB_MSG_DBLWR_1297](#); SQLSTATE: [HY000](#)

Message: Doublewrite file read failed: %s

[ER_IB_MSG_DBLWR_1297](#) was added in 8.0.20.

- Error number: [MY-013543](#); Symbol: [ER_IB_MSG_DBLWR_1298](#); SQLSTATE: [HY000](#)

Message: Dump of the data file page:

[ER_IB_MSG_DBLWR_1298](#) was added in 8.0.20.

- Error number: [MY-013544](#); Symbol: [ER_IB_MSG_DBLWR_1300](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1300](#) was added in 8.0.20.

- Error number: [MY-013545](#); Symbol: [ER_IB_MSG_DBLWR_1301](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1301](#) was added in 8.0.20.

- Error number: [MY-013546](#); Symbol: [ER_IB_MSG_DBLWR_1304](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1304](#) was added in 8.0.20.

- Error number: [MY-013547](#); Symbol: [ER_IB_MSG_DBLWR_1305](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_DBLWR_1305](#) was added in 8.0.20.

-
- Error number: [MY-013548](#); Symbol: [ER_IB_MSG_DBLWR_1306](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1306](#) was added in 8.0.20.
 - Error number: [MY-013549](#); Symbol: [ER_IB_MSG_DBLWR_1307](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1307](#) was added in 8.0.20.
 - Error number: [MY-013550](#); Symbol: [ER_IB_MSG_DBLWR_1308](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1308](#) was added in 8.0.20.
 - Error number: [MY-013551](#); Symbol: [ER_IB_MSG_DBLWR_1309](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1309](#) was added in 8.0.20.
 - Error number: [MY-013552](#); Symbol: [ER_IB_MSG_DBLWR_1310](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1310](#) was added in 8.0.20.
 - Error number: [MY-013553](#); Symbol: [ER_IB_MSG_DBLWR_1311](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1311](#) was added in 8.0.20.
 - Error number: [MY-013554](#); Symbol: [ER_IB_MSG_DBLWR_1312](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1312](#) was added in 8.0.20.
 - Error number: [MY-013555](#); Symbol: [ER_IB_MSG_DBLWR_1313](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1313](#) was added in 8.0.20.
 - Error number: [MY-013556](#); Symbol: [ER_IB_MSG_DBLWR_1314](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1314](#) was added in 8.0.20.
 - Error number: [MY-013557](#); Symbol: [ER_IB_MSG_DBLWR_1315](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1315](#) was added in 8.0.20.
 - Error number: [MY-013558](#); Symbol: [ER_IB_MSG_DBLWR_1316](#); SQLSTATE: HY000
Message: %s
[ER_IB_MSG_DBLWR_1316](#) was added in 8.0.20.

-
- Error number: [MY-013559](#); Symbol: [ER_IB_MSG_DBLWR_1317](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1317](#) was added in 8.0.20.
 - Error number: [MY-013560](#); Symbol: [ER_IB_MSG_DBLWR_1318](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1318](#) was added in 8.0.20.
 - Error number: [MY-013561](#); Symbol: [ER_IB_MSG_DBLWR_1319](#); SQLSTATE: [HY000](#)
Message: Doublewrite load file %s size %lu is not a multiple of the configured page size %lu"
[ER_IB_MSG_DBLWR_1319](#) was added in 8.0.20.
 - Error number: [MY-013562](#); Symbol: [ER_IB_MSG_DBLWR_1320](#); SQLSTATE: [HY000](#)
Message: Doublewrite file %s truncate failed
[ER_IB_MSG_DBLWR_1320](#) was added in 8.0.20.
 - Error number: [MY-013563](#); Symbol: [ER_IB_MSG_DBLWR_1321](#); SQLSTATE: [HY000](#)
Message: Doublewrite file %s failed to writ zeros
[ER_IB_MSG_DBLWR_1321](#) was added in 8.0.20.
 - Error number: [MY-013564](#); Symbol: [ER_IB_MSG_DBLWR_1322](#); SQLSTATE: [HY000](#)
Message: Doublewrite create file %s size %lu is not a multiple of the configured page size %lu"
[ER_IB_MSG_DBLWR_1322](#) was added in 8.0.20.
 - Error number: [MY-013565](#); Symbol: [ER_IB_MSG_DBLWR_1323](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1323](#) was added in 8.0.20.
 - Error number: [MY-013566](#); Symbol: [ER_IB_MSG_DBLWR_1324](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1324](#) was added in 8.0.20.
 - Error number: [MY-013567](#); Symbol: [ER_IB_MSG_DBLWR_1325](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1325](#) was added in 8.0.20.
 - Error number: [MY-013568](#); Symbol: [ER_IB_MSG_DBLWR_1326](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1326](#) was added in 8.0.20.
 - Error number: [MY-013569](#); Symbol: [ER_IB_MSG_DBLWR_1327](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_DBLWR_1327](#) was added in 8.0.20.

-
- Error number: [MY-013570](#); Symbol: [ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.
[ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#) was added in 8.0.20.
 - Error number: [MY-013571](#); Symbol: [ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to delete 5.7 stat tablespace: %s during upgrade
[ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#) was added in 8.0.20.
 - Error number: [MY-013572](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Installing ndbinfo schema version %s
[ER_NDBINFO_UPGRADING_SCHEMA](#) was added in 8.0.20.
 - Error number: [MY-013573](#); Symbol: [ER_NDBINFO_NOT_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Installed ndbinfo schema is current. Not upgrading.
[ER_NDBINFO_NOT_UPGRADING_SCHEMA](#) was added in 8.0.20.
 - Error number: [MY-013574](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to upgrade ndbinfo schema.
[ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#) was added in 8.0.20.
 - Error number: [MY-013575](#); Symbol: [ER_IB_MSG_CREATE_LOG_FILE](#); SQLSTATE: [HY000](#)
Message: Creating log file %s
[ER_IB_MSG_CREATE_LOG_FILE](#) was added in 8.0.20, removed after 8.0.29.
 - Error number: [MY-013576](#); Symbol: [ER_IB_MSG_INNOODB_START_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB initialization has started.
[ER_IB_MSG_INNOODB_START_INITIALIZE](#) was added in 8.0.20.
 - Error number: [MY-013577](#); Symbol: [ER_IB_MSG_INNOODB_END_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: InnoDB initialization has ended.
[ER_IB_MSG_INNOODB_END_INITIALIZE](#) was added in 8.0.20.
 - Error number: [MY-013578](#); Symbol: [ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#); SQLSTATE: [HY000](#)
Message: Could not find appropriate reset points.
[ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#) was added in 8.0.20.
 - Error number: [MY-013579](#); Symbol: [ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#); SQLSTATE: [HY000](#)
Message: Unable to flush. Page archiving data may be corrupt in case of a crash.
[ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#) was added in 8.0.20.

-
- Error number: [MY-013580](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#); SQLSTATE: [HY000](#)

Message: Page archiver's doublewrite buffer for %ld is not valid.

[ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#) was added in 8.0.20.
 - Error number: [MY-013581](#); Symbol: [ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: Page archiver system's recovery failed.

[ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#) was added in 8.0.20.
 - Error number: [MY-013582](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]*.

[ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#) was added in 8.0.20.
 - Error number: [MY-013583](#); Symbol: [ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#); SQLSTATE: [HY000](#)

Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket

[ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#) was added in 8.0.20.
 - Error number: [MY-013584](#); Symbol: [ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#); SQLSTATE: [HY000](#)

Message: %s

[ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#) was added in 8.0.20.
 - Error number: [MY-013585](#); Symbol: [ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY](#); SQLSTATE: [HY000](#)

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

[ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY](#) was added in 8.0.21.
 - Error number: [MY-013586](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#); SQLSTATE: [HY000](#)

Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.

[ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#) was added in 8.0.21.
 - Error number: [MY-013587](#); Symbol: [ER_GRP_RPL_IS_STARTING](#); SQLSTATE: [HY000](#)

Message: Plugin 'group_replication' is starting.

[ER_GRP_RPL_IS_STARTING](#) was added in 8.0.21.
 - Error number: [MY-013588](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace %s because the directory is not a valid location. %s

`ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE` was added in 8.0.21.

- Error number: `MY-013589`; Symbol: `ER_IB_MSG_INVALID_LOCATION_WRONG_DB`; SQLSTATE: `HY000`

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.

`ER_IB_MSG_INVALID_LOCATION_WRONG_DB` was added in 8.0.21.

- Error number: `MY-013590`; Symbol: `ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.

`ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE` was added in 8.0.21.

- Error number: `MY-013591`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT`; SQLSTATE: `HY000`

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

`ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT` was added in 8.0.21.

- Error number: `MY-013592`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID`; SQLSTATE: `HY000`

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID` was added in 8.0.21.

- Error number: `MY-013593`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT`; SQLSTATE: `HY000`

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT` was added in 8.0.21.

- Error number: `MY-013594`; Symbol: `ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS`; SQLSTATE: `HY000`

Message: Failed to retrieve IP addresses from enabled host network interfaces.

`ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS` was added in 8.0.21.

- Error number: `MY-013595`; Symbol: `ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR`; SQLSTATE: `HY000`

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.

`ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR` was added in 8.0.21.

- Error number: `MY-013596`; Symbol: `ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS`; SQLSTATE: `HY000`

Message: Validation of value '%s' set to `Mysqlx_bind_address` failed: %s. Skipping this value.

`ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS` was added in 8.0.21.

-
- Error number: [MY-013597](#); Symbol: [ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Value '%s' set to `Mysqlx_bind_address`, X Plugin can't bind to it. Skipping this value.

[ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#) was added in 8.0.21.
 - Error number: [MY-013598](#); Symbol: [ER_IB_ERR_RECOVERY_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with `innodb_force_recovery=6`

[ER_IB_ERR_RECOVERY_REDO_DISABLED](#) was added in 8.0.21.
 - Error number: [MY-013599](#); Symbol: [ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB cannot do cold shutdown '`innodb_fast_shutdown = 2`' and is forcing '`innodb_fast_shutdown = 1`' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.

[ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#) was added in 8.0.21.
 - Error number: [MY-013600](#); Symbol: [ER_IB_WRN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.

[ER_IB_WRN_REDO_DISABLED](#) was added in 8.0.21.
 - Error number: [MY-013601](#); Symbol: [ER_IB_WRN_REDO_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.

[ER_IB_WRN_REDO_ENABLED](#) was added in 8.0.21.
 - Error number: [MY-013602](#); Symbol: [ER_TLS_CONFIGURED_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.

[ER_TLS_CONFIGURED_FOR_CHANNEL](#) was added in 8.0.21.
 - Error number: [MY-013603](#); Symbol: [ER_TLS_CONFIGURATION_REUSED](#); SQLSTATE: [HY000](#)

Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.

[ER_TLS_CONFIGURATION_REUSED](#) was added in 8.0.21.
 - Error number: [MY-013604](#); Symbol: [ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED](#); SQLSTATE: [HY000](#)

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

[ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED](#) was added in 8.0.21.
 - Error number: [MY-013605](#); Symbol: [ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: Upgrade failed because database contains discarded tablespaces.

`ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES` was added in 8.0.21.

- Error number: `MY-013606`; Symbol: `ER_USERNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_USERNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013607`; Symbol: `ER_HOSTNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.

`ER_HOSTNAME_TRUNCATED` was added in 8.0.21.

- Error number: `MY-013608`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

`ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED` was added in 8.0.21.

- Error number: `MY-013609`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with empty authorization ID; Skipped

`ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013610`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013611`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with empty authorization ID; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME` was added in 8.0.21.

- Error number: `MY-013612`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with unknown authorization ID '%s'; Skipped

`ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID` was added in 8.0.21.

- Error number: `MY-013613`; Symbol: `ER_IB_ERR_DDL_LOG_INSERT_FAILURE`; SQLSTATE: `HY000`

Message: Couldn't insert entry in ddl log for ddl.

`ER_IB_ERR_DDL_LOG_INSERT_FAILURE` was added in 8.0.21.

- Error number: `MY-013614`; Symbol: `ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013615`; Symbol: `ER_IB_RELOCK_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

`ER_IB_RELOCK_LATCH_ORDER_VIOLATION` was added in 8.0.21.

- Error number: `MY-013621`; Symbol: `ER_IB_MSG_1357`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1357` was added in 8.0.21.

- Error number: `MY-013622`; Symbol: `ER_IB_MSG_1358`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1358` was added in 8.0.21.

- Error number: `MY-013623`; Symbol: `ER_IB_MSG_1359`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_1359` was added in 8.0.21.

- Error number: `MY-013624`; Symbol: `ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE`; SQLSTATE: `HY000`

Message: %s

`ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE` was added in 8.0.21.

- Error number: `MY-013625`; Symbol: `ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL`; SQLSTATE: `HY000`

Message: %s

`ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL` was added in 8.0.21.

- Error number: `MY-013626`; Symbol: `ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY`; SQLSTATE: `HY000`

Message: %s

`ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY` was added in 8.0.21.

- Error number: `MY-013627`; Symbol: `ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR` was added in 8.0.21.

- Error number: `MY-013628`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST`; SQLSTATE: `HY000`

Message: %s

`ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST` was added in 8.0.21.

-
- Error number: MY-013629; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY; SQLSTATE: HY000
Message: %s
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY was added in 8.0.21.
 - Error number: MY-013630; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON; SQLSTATE: HY000
Message: %s
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON was added in 8.0.21.
 - Error number: MY-013631; Symbol: ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR; SQLSTATE: HY000
Message: %s
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR was added in 8.0.21.
 - Error number: MY-013632; Symbol: ER_IB_ERR_SCHED_SETAFFINITY_FAILED; SQLSTATE: HY000
Message: %s
ER_IB_ERR_SCHED_SETAFFINITY_FAILED was added in 8.0.21.
 - Error number: MY-013633; Symbol: ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE; SQLSTATE: HY000
Message: %s
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE was added in 8.0.21.
 - Error number: MY-013634; Symbol: ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW; SQLSTATE: HY000
Message: %s
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW was added in 8.0.21.
 - Error number: MY-013635; Symbol: ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER; SQLSTATE: HY000
Message: %s
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER was added in 8.0.21.
 - Error number: MY-013636; Symbol: ER_IB_MSG_1372; SQLSTATE: HY000
Message: %s
ER_IB_MSG_1372 was added in 8.0.21.
 - Error number: MY-013637; Symbol: ER_IB_MSG_1373; SQLSTATE: HY000
Message: %s
ER_IB_MSG_1373 was added in 8.0.21.
 - Error number: MY-013638; Symbol: ER_IB_MSG_1374; SQLSTATE: HY000
Message: %s

[ER_IB_MSG_1374](#) was added in 8.0.21.

- Error number: [MY-013639](#); Symbol: [ER_IB_MSG_1375](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1375](#) was added in 8.0.21.

- Error number: [MY-013640](#); Symbol: [ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED](#) was added in 8.0.21.

- Error number: [MY-013641](#); Symbol: [ER_IB_ERR_ZLIB_BUF_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_BUF_ERROR](#) was added in 8.0.21.

- Error number: [MY-013642](#); Symbol: [ER_IB_ERR_ZLIB_MEM_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_MEM_ERROR](#) was added in 8.0.21.

- Error number: [MY-013643](#); Symbol: [ER_IB_ERR_ZLIB_DATA_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_DATA_ERROR](#) was added in 8.0.21.

- Error number: [MY-013644](#); Symbol: [ER_IB_ERR_ZLIB_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_ZLIB_UNKNOWN_ERROR](#) was added in 8.0.21.

- Error number: [MY-013645](#); Symbol: [ER_IB_MSG_1381](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_1381](#) was added in 8.0.21.

- Error number: [MY-013646](#); Symbol: [ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER](#) was added in 8.0.21.

- Error number: [MY-013647](#); Symbol: [ER_IB_ERR_INDEX_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_INDEX_DUPLICATE_KEY](#) was added in 8.0.21.

-
- Error number: [MY-013648](#); Symbol: [ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#) was added in 8.0.21.
 - Error number: [MY-013649](#); Symbol: [ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#) was added in 8.0.21.
 - Error number: [MY-013650](#); Symbol: [ER_IB_ERR_PARALLEL_READ_OOM](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_ERR_PARALLEL_READ_OOM](#) was added in 8.0.21.
 - Error number: [MY-013651](#); Symbol: [ER_IB_MSG_UNDO_MARKED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to active implicitly.

[ER_IB_MSG_UNDO_MARKED_ACTIVE](#) was added in 8.0.21.
 - Error number: [MY-013652](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.

[ER_IB_MSG_UNDO_ALTERED_ACTIVE](#) was added in 8.0.21.
 - Error number: [MY-013653](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_INACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.

[ER_IB_MSG_UNDO_ALTERED_INACTIVE](#) was added in 8.0.21.
 - Error number: [MY-013654](#); Symbol: [ER_IB_MSG_UNDO_MARKED_EMPTY](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'empty'.

[ER_IB_MSG_UNDO_MARKED_EMPTY](#) was added in 8.0.21.
 - Error number: [MY-013655](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to clone activity.

[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#) was added in 8.0.21.
 - Error number: [MY-013656](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to a metadata lock.

[ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#) was added in 8.0.21.
 - Error number: [MY-013657](#); Symbol: [ER_IB_MSG_UNDO_INJECT_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s

[ER_IB_MSG_UNDO_INJECT_CRASH](#) was added in 8.0.21, removed after 8.0.21.

-
- Error number: [MY-013657](#); Symbol: [ER_IB_MSG_INJECT_CRASH](#); SQLSTATE: [HY000](#)
Message: Injected debug crash point: %s
[ER_IB_MSG_INJECT_CRASH](#) was added in 8.0.22.
 - Error number: [MY-013658](#); Symbol: [ER_IB_MSG_UNDO_INJECT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Injected debug failure point: %s
[ER_IB_MSG_UNDO_INJECT_FAILURE](#) was added in 8.0.21, removed after 8.0.21.
 - Error number: [MY-013658](#); Symbol: [ER_IB_MSG_INJECT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Injected debug failure point: %s
[ER_IB_MSG_INJECT_FAILURE](#) was added in 8.0.22.
 - Error number: [MY-013659](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#); SQLSTATE: [HY000](#)
Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.
[ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#) was added in 8.0.22.
 - Error number: [MY-013660](#); Symbol: [ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE](#); SQLSTATE: [HY000](#)
Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.
[ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE](#) was added in 8.0.22.
 - Error number: [MY-013661](#); Symbol: [ER_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of UDF functions. Check for other errors in the log
[ER_UDF_REGISTER_SERVICE_ERROR](#) was added in 8.0.22.
 - Error number: [MY-013662](#); Symbol: [ER_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.
[ER_UDF_REGISTER_ERROR](#) was added in 8.0.22.
 - Error number: [MY-013663](#); Symbol: [ER_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not uninstall UDF functions. Try to remove them manually if present.
[ER_UDF_UNREGISTER_ERROR](#) was added in 8.0.22.
 - Error number: [MY-013664](#); Symbol: [ER_EMPTY_PRIVILEGE_NAME_IGNORED](#); SQLSTATE: [HY000](#)
Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.
[ER_EMPTY_PRIVILEGE_NAME_IGNORED](#) was added in 8.0.22.
 - Error number: [MY-013665](#); Symbol: [ER_IB_MSG_INCORRECT_SIZE](#); SQLSTATE: [HY000](#)
Message: %s

`ER_IB_MSG_INCORRECT_SIZE` was added in 8.0.22.

- Error number: `MY-013666`; Symbol: `ER_TMPDIR_PATH_TOO_LONG`; SQLSTATE: `HY000`

Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.

`ER_TMPDIR_PATH_TOO_LONG` was added in 8.0.22.

- Error number: `MY-013667`; Symbol: `ER_ERROR_LOG_DESTINATION_NOT_A_FILE`; SQLSTATE: `HY000`

Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.

`ER_ERROR_LOG_DESTINATION_NOT_A_FILE` was added in 8.0.22.

- Error number: `MY-013668`; Symbol: `ER_NO_ERROR_LOG_PARSER_CONFIGURED`; SQLSTATE: `HY000`

Message: None of the log-sinks selected with `--log-error-services=...` provides a log-parser. The server will not be able to make the previous runs' error-logs available in `performance_schema.error_log`.

`ER_NO_ERROR_LOG_PARSER_CONFIGURED` was added in 8.0.22.

- Error number: `MY-013669`; Symbol: `ER_UPGRADE_NONEXISTENT_SCHEMA`; SQLSTATE: `HY000`

Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.

`ER_UPGRADE_NONEXISTENT_SCHEMA` was added in 8.0.22.

- Error number: `MY-013670`; Symbol: `ER_IB_MSG_CREATED_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Created undo tablespace '%s'.

`ER_IB_MSG_CREATED_UNDO_SPACE` was added in 8.0.22.

- Error number: `MY-013671`; Symbol: `ER_IB_MSG_DROPPED_UNDO_SPACE`; SQLSTATE: `HY000`

Message: Dropped undo tablespace '%s'.

`ER_IB_MSG_DROPPED_UNDO_SPACE` was added in 8.0.22.

- Error number: `MY-013672`; Symbol: `ER_IB_MSG_MASTER_KEY_ROTATED`; SQLSTATE: `HY000`

Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.

`ER_IB_MSG_MASTER_KEY_ROTATED` was added in 8.0.22.

- Error number: `MY-013673`; Symbol: `ER_IB_DBLWR_DECOMPRESS_FAILED`; SQLSTATE: `HY000`

Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.

`ER_IB_DBLWR_DECOMPRESS_FAILED` was added in 8.0.23.

- Error number: `MY-013674`; Symbol: `ER_IB_DBLWR_DECRYPT_FAILED`; SQLSTATE: `HY000`

Message: Decrypting a page in doublewrite file failed: %s.

`ER_IB_DBLWR_DECRYPT_FAILED` was added in 8.0.23.

-
- Error number: `MY-013675`; Symbol: `ER_IB_DBLWR_KEY_MISSING`; SQLSTATE: `HY000`
Message: Encryption key missing: %s.
`ER_IB_DBLWR_KEY_MISSING` was added in 8.0.23.
 - Error number: `MY-013676`; Symbol: `ER_INNODB_IO_WRITE_ERROR_RETRYING`; SQLSTATE: `HY000`
Message: I/O error while writing to file: %s. Retrying ...
`ER_INNODB_IO_WRITE_ERROR_RETRYING` was added in 8.0.23.
 - Error number: `MY-013677`; Symbol: `ER_INNODB_IO_WRITE_FAILED`; SQLSTATE: `HY000`
Message: Failed to write data to file: %s
`ER_INNODB_IO_WRITE_FAILED` was added in 8.0.23.
 - Error number: `MY-013678`; Symbol: `ER_LOG_COMPONENT_CANNOT_INIT`; SQLSTATE: `HY000`
Message: Log component %s failed to initialize.
`ER_LOG_COMPONENT_CANNOT_INIT` was added in 8.0.23.
 - Error number: `MY-013679`; Symbol: `ER_RPL_ASYNC_CHANNEL_CANT_CONNECT`; SQLSTATE: `HY000`
Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network_namespace:%s) for channel '%s', thence it will try to connect to another source.
`ER_RPL_ASYNC_CHANNEL_CANT_CONNECT` was added in 8.0.23.
 - Error number: `MY-013680`; Symbol: `ER_RPL_ASYNC_SENDER_ADDED`; SQLSTATE: `HY000`
Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has joined the group (group_name: %s), and so added its entry into replication_asynchronous_connection_failover table.
`ER_RPL_ASYNC_SENDER_ADDED` was added in 8.0.23.
 - Error number: `MY-013681`; Symbol: `ER_RPL_ASYNC_SENDER_REMOVED`; SQLSTATE: `HY000`
Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has left the group (group_name: %s), and so removed its entry from replication_asynchronous_connection_failover table.
`ER_RPL_ASYNC_SENDER_REMOVED` was added in 8.0.23.
 - Error number: `MY-013682`; Symbol: `ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST`; SQLSTATE: `HY000`
Message: The Monitor IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.
`ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST` was added in 8.0.23.
 - Error number: `MY-013683`; Symbol: `ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM`; SQLSTATE: `HY000`
Message: The IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

`ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM` was added in 8.0.23.

- Error number: `MY-013684`; Symbol: `ER_RPL_ASYNC_EXECUTING_QUERY`; SQLSTATE: `HY000`

Message: %s on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

`ER_RPL_ASYNC_EXECUTING_QUERY` was added in 8.0.23.

- Error number: `MY-013685`; Symbol: `ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING`; SQLSTATE: `HY000`

Message: Replica Monitor IO thread exiting.

`ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING` was added in 8.0.23.

- Error number: `MY-013686`; Symbol: `ER_RPL_ASYNC_MANAGED_NAME_REMOVED`; SQLSTATE: `HY000`

Message: The group (group_name: %s) for the channel '%s' has been removed, and so removed its entry from replication_asynchronous_connection_failover_managed and all the group members from replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_MANAGED_NAME_REMOVED` was added in 8.0.23.

- Error number: `MY-013687`; Symbol: `ER_RPL_ASYNC_MANAGED_NAME_ADDED`; SQLSTATE: `HY000`

Message: The group (group_name: %s) for the channel '%s' has been added, and so added its entry in replication_asynchronous_connection_failover_managed and source to replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_MANAGED_NAME_ADDED` was added in 8.0.23.

- Error number: `MY-013688`; Symbol: `ER_RPL_ASYNC_READ_FAILOVER_TABLE`; SQLSTATE: `HY000`

Message: Error reading failover sources for channel '%s' from replication_asynchronous_connection_failover table.

`ER_RPL_ASYNC_READ_FAILOVER_TABLE` was added in 8.0.23.

- Error number: `MY-013689`; Symbol: `ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL`; SQLSTATE: `HY000`

Message: Error %s the channel '%s', the operation will be automatically retried.

`ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL` was added in 8.0.23.

- Error number: `MY-013690`; Symbol: `ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL`

<UUID>. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

`ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON` was added in 8.0.23, removed after 8.0.32.

- Error number: `MY-013690`; Symbol:

`ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

`ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON` was added in 8.0.33.

- Error number: `MY-013691`; Symbol:

`ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_group_name`. To fix this issue, either change the `group_replication_group_name` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

`ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME` was added in 8.0.23.

- Error number: `MY-013692`; Symbol:

`ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID`; SQLSTATE: `HY000`

Message: The `group_replication_group_name` '%s' is the same as the UUID value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` in a server channel

`ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID` was added in 8.0.23.

- Error number: `MY-013693`; Symbol: `ER_WARN_GTID_THRESHOLD_BREACH`; SQLSTATE: `HY000`

Message: The integer component of the GTID number is high. Suggest restarting the server with a new `server_uuid` to prevent it from reaching the maximum number $2^{63}-1$, which will make it impossible to write the binary log and invoke the behavior specified by `binlog_error_action`.

`ER_WARN_GTID_THRESHOLD_BREACH` was added in 8.0.23.

- Error number: `MY-013694`; Symbol: `ER_HEALTH_INFO`; SQLSTATE: `HY000`

Message: %s

`ER_HEALTH_INFO` was added in 8.0.23.

- Error number: `MY-013695`; Symbol: `ER_HEALTH_WARNING`; SQLSTATE: `HY000`

Message: %s

`ER_HEALTH_WARNING` was added in 8.0.23.

- Error number: `MY-013696`; Symbol: `ER_HEALTH_ERROR`; SQLSTATE: `HY000`

Message: %s

[ER_HEALTH_ERROR](#) was added in 8.0.23.

- Error number: [MY-013697](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

[ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1](#) was added in 8.0.23.

- Error number: [MY-013698](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

[ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2](#) was added in 8.0.23.

- Error number: [MY-013699](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

[ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#) was added in 8.0.23.

- Error number: [MY-013700](#); Symbol: [ER_IB_INNODB_TBSP_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.

[ER_IB_INNODB_TBSP_OUT_OF_SPACE](#) was added in 8.0.23.

- Error number: [MY-013701](#); Symbol: [ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group_replication_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

[ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#) was added in 8.0.23.

- Error number: [MY-013702](#); Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with SOURCE_CONNECTION_AUTO_FAILOVER = 1, but the server was started with a value other than --gtid-mode = ON. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '%s', or change GTID_MODE to value ON, before starting the replica receiver thread.

[ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#) was added in 8.0.23.

- Error number: [MY-013703](#); Symbol: [ER_FIREWALL_SERVICES_NOT_ACQUIRED](#); SQLSTATE: [HY000](#)

Message: Could not acquire required component services.

[ER_FIREWALL_SERVICES_NOT_ACQUIRED](#) was added in 8.0.23.

- Error number: [MY-013704](#); Symbol: [ER_FIREWALL_UDF_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of function(s) failed.

`ER_FIREWALL_UDF_REGISTER_FAILED` was added in 8.0.23.

- Error number: `MY-013705`; Symbol: `ER_FIREWALL_PFS_TABLE_REGISTER_FAILED`; SQLSTATE: `HY000`

Message: Automatic registration of Performance schema table(s) failed.

`ER_FIREWALL_PFS_TABLE_REGISTER_FAILED` was added in 8.0.23.

- Error number: `MY-013706`; Symbol: `ER_IB_MSG_STATS_SAMPLING_TOO_LARGE`; SQLSTATE: `HY000`

Message: %s

`ER_IB_MSG_STATS_SAMPLING_TOO_LARGE` was added in 8.0.23.

- Error number: `MY-013707`; Symbol: `ER_AUDIT_LOG_FILE_PRUNE_FAILED`; SQLSTATE: `HY000`

Message: Failed to auto-prune file '%s', Error (%d): %s

`ER_AUDIT_LOG_FILE_PRUNE_FAILED` was added in 8.0.24.

- Error number: `MY-013708`; Symbol: `ER_AUDIT_LOG_FILE_AUTO_PRUNED`; SQLSTATE: `HY000`

Message: File '%s' auto-pruned

`ER_AUDIT_LOG_FILE_AUTO_PRUNED` was added in 8.0.24.

- Error number: `MY-013709`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT`; SQLSTATE: `HY000`

Message: Received an error while processing components from manifest file: %s

`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT` was added in 8.0.24.

- Error number: `MY-013710`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT`; SQLSTATE: `HY000`

Message: Received an error while unloading components read from manifest file: %s

`ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT` was added in 8.0.24.

- Error number: `MY-013711`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO`; SQLSTATE: `HY000`

Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.

`ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO` was added in 8.0.24.

- Error number: `MY-013712`; Symbol: `ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND`; SQLSTATE: `HY000`

Message: No suitable '%s' service implementation found to fulfill the request.

`ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND` was added in 8.0.24.

- Error number: `MY-013713`; Symbol: `ER_NOTE_KEYRING_COMPONENT_INITIALIZED`; SQLSTATE: `HY000`

Message: Keyring component initialized successfully.

`ER_NOTE_KEYRING_COMPONENT_INITIALIZED` was added in 8.0.24.

- Error number: `MY-013714`; Symbol: `ER_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: The component is not initialized properly. Make sure that configuration is proper and use `ALTER INSTANCE RELOAD KEYRING` to reinitialize the component.

`ER_KEYRING_COMPONENT_NOT_INITIALIZED` was added in 8.0.24.

- Error number: `MY-013715`; Symbol: `ER_KEYRING_COMPONENT_EXCEPTION`; SQLSTATE: `HY000`

Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'

`ER_KEYRING_COMPONENT_EXCEPTION` was added in 8.0.24.

- Error number: `MY-013716`; Symbol: `ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR`; SQLSTATE: `HY000`

Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'

`ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR` was added in 8.0.24.

- Error number: `MY-013717`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE`; SQLSTATE: `HY000`

Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.

`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE` was added in 8.0.24.

- Error number: `MY-013718`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY`; SQLSTATE: `HY000`

Message: A valid data identifier is required in order to fetch the key required for the AES operation.

`ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY` was added in 8.0.24.

- Error number: `MY-013719`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY`; SQLSTATE: `HY000`

Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.

`ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY` was added in 8.0.24.

- Error number: `MY-013720`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR`; SQLSTATE: `HY000`

Message: Encountered error: '%s' while executing '%s' API of keyring_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.

`ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR` was added in 8.0.24.

- Error number: `MY-013721`; Symbol: `ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND`; SQLSTATE: `HY000`

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

`ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND` was added in 8.0.24.

- Error number: `MY-013722`; Symbol: `ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH`; SQLSTATE: `HY000`

Message: Maximum permissible size of data is '%zu' bits

`ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH` was added in 8.0.24.

- Error number: `MY-013723`; Symbol: `ER_NOTE_KEYRING_COMPONENT_STORE_FAILED`; SQLSTATE: `HY000`

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

`ER_NOTE_KEYRING_COMPONENT_STORE_FAILED` was added in 8.0.24.

- Error number: `MY-013724`; Symbol: `ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED`; SQLSTATE: `HY000`

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exists with same identifier or keyring backend encountered an error.

`ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED` was added in 8.0.24.

- Error number: `MY-013725`; Symbol: `ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED`; SQLSTATE: `HY000`

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

`ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED` was added in 8.0.24.

- Error number: `MY-013726`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED`; SQLSTATE: `HY000`

Message: Failed to get metadata from current keys metadata iterator position.

`ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED` was added in 8.0.24.

- Error number: `MY-013727`; Symbol: `ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM`; SQLSTATE: `HY000`

Message: Key and value length parameters must not be null.

`ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM` was added in 8.0.24.

- Error number: `MY-013728`; Symbol: `ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE`; SQLSTATE: `HY000`

Message: Innodb could not acquire service : %s

`ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE` was added in 8.0.24.

- Error number: `MY-013729`; Symbol: `ER_IB_WRN_OLD_GEOMETRY_TYPE`; SQLSTATE: `HY000`

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

`ER_IB_WRN_OLD_GEOMETRY_TYPE` was added in 8.0.24.

- Error number: `MY-013730`; Symbol: `ER_NET_WAIT_ERROR2`; SQLSTATE: `HY000`

Message: 'wait_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

`ER_NET_WAIT_ERROR2` was added in 8.0.26.

- Error number: `MY-013731`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_TRIGGERED`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" will be run.

`ER_GRP_RPL_MEMBER_ACTION_TRIGGERED` was added in 8.0.26.

- Error number: `MY-013732`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

`ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE` was added in 8.0.26.

- Error number: `MY-013733`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_FAILURE`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

`ER_GRP_RPL_MEMBER_ACTION_FAILURE` was added in 8.0.26.

- Error number: `MY-013734`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE`; SQLSTATE: `HY000`

Message: Unable to parse the member actions configuration sent by the primary.

`ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE` was added in 8.0.26.

- Error number: `MY-013735`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS`; SQLSTATE: `HY000`

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

`ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS` was added in 8.0.26.

- Error number: `MY-013736`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA`; SQLSTATE: `HY000`

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

`ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA` was added in 8.0.26.

- Error number: `MY-013737`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

`ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION` was added in 8.0.26.

- Error number: `MY-013738`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#) was added in 8.0.26.

- Error number: [MY-013739](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the group on member join.

[ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013740](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013741](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version' on all members.

[ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#) was added in 8.0.26.

- Error number: [MY-013742](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

[ER_GRP_RPL_MEMBER_ACTION_ENABLED](#) was added in 8.0.26.

- Error number: [MY-013743](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

[ER_GRP_RPL_MEMBER_ACTION_DISABLED](#) was added in 8.0.26.

- Error number: [MY-013744](#); Symbol: [ER_GRP_RPL_MEMBER_ACTIONS_RESET](#); SQLSTATE: [HY000](#)

Message: Member actions configuration was reset.

[ER_GRP_RPL_MEMBER_ACTIONS_RESET](#) was added in 8.0.26.

- Error number: [MY-013745](#); Symbol: [ER_DEPRECATED_TLS_VERSION_SESSION](#); SQLSTATE: [HY000](#)

Message: Accepted a connection with deprecated protocol '%s' for account '%s'@'%s' from host '%s'. Client supplied username '%s'

[ER_DEPRECATED_TLS_VERSION_SESSION](#) was added in 8.0.26, removed after 8.0.27.

-
- Error number: [MY-013746](#); Symbol: [ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: A deprecated TLS version %s is enabled for channel %s

[ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL](#) was added in 8.0.26, removed after 8.0.27.

- Error number: [MY-013747](#); Symbol: [ER_FIREWALL_DEPRECATED_USER_PROFILE](#); SQLSTATE: [HY000](#)

Message: User profile '%s' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.

[ER_FIREWALL_DEPRECATED_USER_PROFILE](#) was added in 8.0.26.

- Error number: [MY-013748](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid input value for group_replication_view_change_uuid '%s'. Please, provide a valid UUID.

[ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#) was added in 8.0.26.

- Error number: [MY-013749](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Variable 'group_replication_view_change_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group_replication_group_name' for the UUID of View_change_log_events, please set 'group_replication_view_change_uuid' to AUTOMATIC.

[ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#) was added in 8.0.26.

- Error number: [MY-013750](#); Symbol: [ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: group_replication_group_name '%s', which is the same as group_replication_view_change_uuid. Please change group_replication_view_change_uuid to AUTOMATIC

[ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: [MY-013751](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_view_change_uuid '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel

[ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#) was added in 8.0.26.

- Error number: [MY-013752](#); Symbol: [ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID](#); SQLSTATE: [HY000](#)

Message: group_replication_view_change_uuid is incompatible with group.
group_replication_view_change_uuid %s matches server_uuid %s.

[ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID](#) was added in 8.0.26.

-
- Error number: [MY-013753](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_view_change_uuid option value '%s' different from the group '%s'. The member will now exit the group.

[ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP](#) was added in 8.0.26.

- Error number: [MY-013754](#); Symbol: [ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_view_change_uuid`. To fix this issue, either change the `group_replication_view_change_uuid` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

[ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: [MY-013755](#); Symbol: [ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: Unable to parse the `group_replication_view_change_uuid`.

[ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: [MY-013756](#); Symbol: [ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: Unable to generate sidno for `group_replication_view_change_uuid`.

[ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID](#) was added in 8.0.26.

- Error number: [MY-013757](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to parse the `group_replication_view_change_uuid` during the Certification module initialization.

[ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR](#) was added in 8.0.26.

- Error number: [MY-013758](#); Symbol: [ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating `group_gtid_executed` GTID set with view change uuid during the Certification module initialization.

[ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTED_ERROR](#) was added in 8.0.26.

- Error number: [MY-013759](#); Symbol: [ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to add the `group_replication_view_change_uuid` sidno in the `group_gtid_sid_map` during the Certification module initialization.

[ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR](#) was added in 8.0.26.

-
- Error number: `MY-013760`; Symbol: `ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR`; SQLSTATE: `HY000`

Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.

`ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR` was added in 8.0.26.
 - Error number: `MY-013761`; Symbol: `ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE`; SQLSTATE: `HY000`

Message: Unable to retrieve group_replication_view_change_uuid during server checks on replication operations.

`ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE` was added in 8.0.26.
 - Error number: `MY-013762`; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG`; SQLSTATE: `HY000`

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

`ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG` was added in 8.0.26.
 - Error number: `MY-013763`; Symbol: `ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG`; SQLSTATE: `HY000`

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

`ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG` was added in 8.0.26.
 - Error number: `MY-013764`; Symbol: `ER_PLUGIN_INVALID_TABLE_DEFINITION`; SQLSTATE: `HY000`

Message: Invalid table definition for '%s.%s'.

`ER_PLUGIN_INVALID_TABLE_DEFINITION` was added in 8.0.26.
 - Error number: `MY-013765`; Symbol: `ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG`; SQLSTATE: `HY000`

Message: %s

`ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG` was added in 8.0.26.
 - Error number: `MY-013766`; Symbol: `ER_INSTALL_PLUGIN_CONFLICT_LOG`; SQLSTATE: `HY000`

Message: Cannot install the %s plugin when the %s plugin is installed.

`ER_INSTALL_PLUGIN_CONFLICT_LOG` was added in 8.0.26.
 - Error number: `MY-013767`; Symbol: `ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS`; SQLSTATE: `HY000`

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.

`ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS` was added in 8.0.26.
 - Error number: `MY-013768`; Symbol: `ER_LOG_COMPONENT_FLUSH_FAILED`; SQLSTATE: `HY000`

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

`ER_LOG_COMPONENT_FLUSH_FAILED` was added in 8.0.26.

- Error number: `MY-013769`; Symbol: `ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY`; SQLSTATE: `HY000`

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.

`ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY` was added in 8.0.26.

- Error number: `MY-013770`; Symbol: `ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY`; SQLSTATE: `HY000`

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.

`ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY` was added in 8.0.26.

- Error number: `MY-013771`; Symbol: `ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED`; SQLSTATE: `HY000`

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.

`ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED` was added in 8.0.26.

- Error number: `MY-013772`; Symbol: `ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBUF_MERGES`; SQLSTATE: `HY000`

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with `--innodb-force-recovery=4`.

`ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBUF_MERGES` was added in 8.0.26.

- Error number: `MY-013773`; Symbol: `ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED`; SQLSTATE: `HY000`

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with `--innodb-force-recovery=6`).

`ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED` was added in 8.0.26.

- Error number: `MY-013774`; Symbol: `ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG`; SQLSTATE: `HY000`

Message: `audit_log_format_unix_timestamp` is applicable only when `audit_log_format = JSON`.

`ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG` was added in 8.0.26.

- Error number: `MY-013775`; Symbol: `ER_PREPARE_FOR_PRIMARY_ENGINE`; SQLSTATE: `HY000`

Message: Retry the statement using the primary storage engine.

`ER_PREPARE_FOR_PRIMARY_ENGINE` was added in 8.0.26.

-
- Error number: [MY-013776](#); Symbol: [ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG](#); SQLSTATE: [HY000](#)

Message: Parallel initialization of rseg complete

[ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG](#) was added in 8.0.27.
 - Error number: [MY-013777](#); Symbol: [ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG](#); SQLSTATE: [HY000](#)

Message: Time taken to initialize rseg using %u thread: %u ms.

[ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG](#) was added in 8.0.27.
 - Error number: [MY-013778](#); Symbol: [ER_DDL_MSG_1](#); SQLSTATE: [HY000](#)

Message: DDL failed to create a thread to load an index, fall back to single thread

[ER_DDL_MSG_1](#) was added in 8.0.27.
 - Error number: [MY-013779](#); Symbol: [ER_MTR_MSG_1](#); SQLSTATE: [HY000](#)

Message: Debug_check_no_latching failed, slot->type=%d

[ER_MTR_MSG_1](#) was added in 8.0.27.
 - Error number: [MY-013780](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONN_ERR](#); SQLSTATE: [HY000](#)

Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

[ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONN_ERR](#) was added in 8.0.27.
 - Error number: [MY-013781](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND_ERR](#); SQLSTATE: [HY000](#)

Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

[ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND_ERR](#) was added in 8.0.27.
 - Error number: [MY-013782](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA](#) was added in 8.0.27.
 - Error number: [MY-013783](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

[ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION](#) was added in 8.0.27.

-
- Error number: [MY-013784](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.

[ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION](#) was added in 8.0.27.
 - Error number: [MY-013785](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the replication failover channels configuration sent by the group on member join.

[ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN](#) was added in 8.0.27.
 - Error number: [MY-013786](#); Symbol: [ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Unable to set SOURCE_CONNECTION_AUTO_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

[ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST](#) was added in 8.0.27.
 - Error number: [MY-013787](#); Symbol: [ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_SERVICE](#); SQLSTATE: [HY000](#)

Message: Unable to register the listener 'replication_asynchronous_connection_failover_configuration' to the service 'group_replication_message_service_rcv'.

[ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_SERVICE](#) was added in 8.0.27.
 - Error number: [MY-013788](#); Symbol: [ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

[ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY](#) was added in 8.0.27.
 - Error number: [MY-013789](#); Symbol: [ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is back to the group majority. Replication failover channels handling is resumed.

[ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY](#) was added in 8.0.27.
 - Error number: [MY-013790](#); Symbol: [ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION](#); SQLSTATE: [HY000](#)

Message: Error incrementing member action configuration version for %s.%s table.

[ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION](#) was added in 8.0.27.
 - Error number: [MY-013791](#); Symbol: [ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

[ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER](#) was added in 8.0.27, removed after 8.0.32.

- Error number: [MY-013791](#); Symbol:

[ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

[ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER](#) was added in 8.0.33.

- Error number: [MY-013792](#); Symbol: [ER_IB_MSG_CLONE_DDL_NTFN](#); SQLSTATE: [HY000](#)

Message: Clone DDL Notification: %s

[ER_IB_MSG_CLONE_DDL_NTFN](#) was added in 8.0.27.

- Error number: [MY-013793](#); Symbol: [ER_IB_MSG_CLONE_DDL_APPLY](#); SQLSTATE: [HY000](#)

Message: Clone DDL APPLY: %s

[ER_IB_MSG_CLONE_DDL_APPLY](#) was added in 8.0.27.

- Error number: [MY-013794](#); Symbol: [ER_IB_MSG_CLONE_DDL_INVALIDATE](#); SQLSTATE: [HY000](#)

Message: Clone DDL Invalidate : %s

[ER_IB_MSG_CLONE_DDL_INVALIDATE](#) was added in 8.0.27.

- Error number: [MY-013795](#); Symbol: [ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED](#); SQLSTATE: [HY000](#)

Message: Encryption key is loaded for undo tablespace '%s'.

[ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED](#) was added in 8.0.27.

- Error number: [MY-013796](#); Symbol: [ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu

[ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH](#) was added in 8.0.27.

- Error number: [MY-013797](#); Symbol: [ER_INVALID_AUTHENTICATION_POLICY](#); SQLSTATE: [HY000](#)

Message: Option --authentication-policy is set to an invalid value. Please check if the specified authentication plugins are valid.

[ER_INVALID_AUTHENTICATION_POLICY](#) was added in 8.0.27.

- Error number: [MY-013798](#); Symbol: [ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)

Message: Signature verification failed during registration.

[ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED](#) was added in 8.0.27.

- Error number: [MY-013799](#); Symbol:

[ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER](#); SQLSTATE: [HY000](#)

Message: Buffer too small to hold registration challenge response.

`ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER` was added in 8.0.27.

- Error number: `MY-013800`; Symbol: `ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT`; SQLSTATE: `HY000`

Message: FIDO device authenticator data corrupt.

`ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT` was added in 8.0.27.

- Error number: `MY-013801`; Symbol: `ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT`; SQLSTATE: `HY000`

Message: FIDO device signature corrupt.

`ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT` was added in 8.0.27.

- Error number: `MY-013802`; Symbol: `ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED`; SQLSTATE: `HY000`

Message: Signature verification failed during authentication.

`ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED` was added in 8.0.27.

- Error number: `MY-013803`; Symbol: `ER_AUTHENTICATION_PLUGIN_OOM`; SQLSTATE: `HY000`

Message: Out of memory.

`ER_AUTHENTICATION_PLUGIN_OOM` was added in 8.0.27.

- Error number: `MY-013804`; Symbol: `ER_AUTHENTICATION_PLUGIN_LOG`; SQLSTATE: `HY000`

Message: Can't initialize logging service

`ER_AUTHENTICATION_PLUGIN_LOG` was added in 8.0.27.

- Error number: `MY-013805`; Symbol: `ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `GTID_ONLY=1`, which is invalid when `GTID_MODE <> ON`. If you intend to disable GTIDs in the replication topology, change `GTID_ONLY` to 0.

`ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON` was added in 8.0.27.

- Error number: `MY-013806`; Symbol: `ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS`; SQLSTATE: `HY000`

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of `GTID_ONLY=1`. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

`ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS` was added in 8.0.27.

- Error number: `MY-013807`; Symbol: `ER_RPL_CANNOT_OPEN_RELAY_LOG`; SQLSTATE: `HY000`

Message: Could not open relay log: %s

`ER_RPL_CANNOT_OPEN_RELAY_LOG` was added in 8.0.27.

-
- Error number: MY-013808; Symbol: ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED; SQLSTATE: HY000

Message: Authentication plugin not initialized.

ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED was added in 8.0.27.

- Error number: MY-013809; Symbol: ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR; SQLSTATE: HY000

Message: Cannot use the generated private key file.

ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR was added in 8.0.27.

- Error number: MY-013810; Symbol: ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY; SQLSTATE: HY000

Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .

ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY was added in 8.0.27.

- Error number: MY-013811; Symbol: ER_AUTHENTICATION_OCI_IMDS; SQLSTATE: HY000

Message: Cannot obtain the OCI configuration from the IMDS service.

ER_AUTHENTICATION_OCI_IMDS was added in 8.0.27.

- Error number: MY-013812; Symbol: ER_AUTHENTICATION_OCI_IAM; SQLSTATE: HY000

Message: Cannot initialize the IAM service.

ER_AUTHENTICATION_OCI_IAM was added in 8.0.27.

- Error number: MY-013813; Symbol: ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING; SQLSTATE: HY000

Message: Invalid authentication string details for user: '%s'@'%s'.

ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING was added in 8.0.27.

- Error number: MY-013814; Symbol: ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS; SQLSTATE: HY000

Message: None of the groups returned by IAM matches any of the entries from authentication string.

ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS was added in 8.0.27.

- Error number: MY-013815; Symbol: ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND; SQLSTATE: HY000

Message: User is not part of any groups. However, account is configured to use group mapping.

ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND was added in 8.0.27.

- Error number: MY-013816; Symbol: ER_AUTHENTICATION_OCI_NONCE; SQLSTATE: HY000

Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s .

ER_AUTHENTICATION_OCI_NONCE was added in 8.0.27.

- Error number: MY-013817; Symbol: ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1; SQLSTATE: HY000

Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

[ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1](#) was added in 8.0.27.

- Error number: [MY-013818](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

[ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2](#) was added in 8.0.27.

- Error number: [MY-013819](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

[ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3](#) was added in 8.0.27.

- Error number: [MY-013820](#); Symbol: [ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)

Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.

[ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER](#) was added in 8.0.27.

- Error number: [MY-013821](#); Symbol: [ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER](#) was added in 8.0.27.

- Error number: [MY-013822](#); Symbol: [ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)

Message: All members were set as consensus leaders.

[ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER](#) was added in 8.0.27.

- Error number: [MY-013823](#); Symbol: [ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)

Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.

[ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER](#) was added in 8.0.27.

- Error number: [MY-013824](#); Symbol: [ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

`ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP` was added in 8.0.27.

- Error number: `MY-013825`; Symbol: `ER_MFA_USER_ATTRIBUTES_CORRUPT`; SQLSTATE: `HY000`

Message: Invalid and/or corrupted multi factor authentication methods in `User_attributes` column in `mysql.user` table. "%s".

`ER_MFA_USER_ATTRIBUTES_CORRUPT` was added in 8.0.27.

- Error number: `MY-013826`; Symbol: `ER_MFA_PLUGIN_NOT_LOADED`; SQLSTATE: `HY000`

Message: Plugin '%s' is not loaded; Ignoring user

`ER_MFA_PLUGIN_NOT_LOADED` was added in 8.0.27.

- Error number: `MY-013827`; Symbol: `ER_WARN_DEPRECATED_CHARSET_OPTION`; SQLSTATE: `HY000`

Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.

`ER_WARN_DEPRECATED_CHARSET_OPTION` was added in 8.0.28.

- Error number: `MY-013828`; Symbol: `ER_WARN_DEPRECATED_COLLATION_OPTION`; SQLSTATE: `HY000`

Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

`ER_WARN_DEPRECATED_COLLATION_OPTION` was added in 8.0.28.

- Error number: `MY-013829`; Symbol: `ER_REGEXP_MISSING_ICU_DATADIR`; SQLSTATE: `HY000`

Message: Missing data directory for ICU regular expressions: %s.

`ER_REGEXP_MISSING_ICU_DATADIR` was added in 8.0.28.

- Error number: `MY-013830`; Symbol: `ER_IB_WARN_MANY_NON_LRU_FILES_OPENED`; SQLSTATE: `HY000`

Message: More than 90%% of files opened out of the `innodb_open_files` limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the `innodb_open_files` system variable. There are %zu such files opened out of the total limit for all files opened of %zu.

`ER_IB_WARN_MANY_NON_LRU_FILES_OPENED` was added in 8.0.28.

- Error number: `MY-013831`; Symbol: `ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME`; SQLSTATE: `HY000`

Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting `innobase_open_files` higher.

`ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME` was added in 8.0.28.

- Error number: `MY-013832`; Symbol: `ER_GLOBAL_CONN_LIMIT`; SQLSTATE: `HY000`

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

`ER_GLOBAL_CONN_LIMIT` was added in 8.0.28.

- Error number: `MY-013833`; Symbol: `ER_CONN_LIMIT`; SQLSTATE: `HY000`

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

`ER_CONN_LIMIT` was added in 8.0.28.

- Error number: `MY-013834`; Symbol: `ER_WARN_AUDIT_LOG_DISABLED`; SQLSTATE: `HY000`

Message: Audit Log is disabled. Enable it with `audit_log_disable = false`.

`ER_WARN_AUDIT_LOG_DISABLED` was added in 8.0.28.

- Error number: `MY-013835`; Symbol: `ER_INVALID_TLS_VERSION`; SQLSTATE: `HY000`

Message: Option `--tls-version` or `--admin-tls-version` is set to an invalid value %s.

`ER_INVALID_TLS_VERSION` was added in 8.0.28.

- Error number: `MY-013836`; Symbol: `ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY`; SQLSTATE: `HY000`

Message: Relay log recovery on channel with `GTID_ONLY=1`. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.

`ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY` was added in 8.0.28.

- Error number: `MY-013837`; Symbol: `ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED`; SQLSTATE: `HY000`

Message: Number of `STANDBY_SERVER` values exceeded maximum limit of 64.

`ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED` was added in 8.0.29.

- Error number: `MY-013838`; Symbol: `ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING`; SQLSTATE: `HY000`

Message: Source keyring does not have any keys to migrate.

`ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING` was added in 8.0.29.

- Error number: `MY-013839`; Symbol: `ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot persist SENSITIVE system variables because keyring component support is unavailable and `persist_sensitive_variables_in_plaintext` is set to OFF. Please make sure that keyring services are active and required keys are available.

`ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES` was added in 8.0.29.

- Error number: `MY-013840`; Symbol: `ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot interpret persisted SENSITIVE system variables. Please make sure that keyring services are active and required keys are available.

`ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES` was added in 8.0.29.

-
- Error number: MY-013841; Symbol: ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED; SQLSTATE: HY000
Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables
ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED was added in 8.0.29.
 - Error number: MY-013842; Symbol: ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND; SQLSTATE: HY000
Message: Could not find master key %s in keyring
ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND was added in 8.0.29.
 - Error number: MY-013843; Symbol: ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED; SQLSTATE: HY000
Message: A new master key %s could not be generated
ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED was added in 8.0.29.
 - Error number: MY-013844; Symbol: ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED; SQLSTATE: HY000
Message: Failed to encrypt %s using %s
ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED was added in 8.0.29.
 - Error number: MY-013845; Symbol: ER_PERSISTED_VARIABLES_DECRYPTION_FAILED; SQLSTATE: HY000
Message: Failed to decrypt %s using %s
ER_PERSISTED_VARIABLES_DECRYPTION_FAILED was added in 8.0.29.
 - Error number: MY-013846; Symbol: ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT; SQLSTATE: HY000
Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.
ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT was added in 8.0.29.
 - Error number: MY-013847; Symbol: ER_MY_MALLOC_USING_JEMALLOC; SQLSTATE: HY000
Message: Using jemalloc.dll for my_malloc and ut::malloc etc.
ER_MY_MALLOC_USING_JEMALLOC was added in 8.0.29.
 - Error number: MY-013848; Symbol: ER_MY_MALLOC_USING_STD_MALLOC; SQLSTATE: HY000
Message: %s.
ER_MY_MALLOC_USING_STD_MALLOC was added in 8.0.29.
 - Error number: MY-013849; Symbol: ER_MY_MALLOC_LOADLIBRARY_FAILED; SQLSTATE: HY000
Message: %s.
ER_MY_MALLOC_LOADLIBRARY_FAILED was added in 8.0.29.
 - Error number: MY-013850; Symbol: ER_MY_MALLOC_GETPROCADDRESS_FAILED; SQLSTATE: HY000

Message: %s.

[ER_MY_MALLOC_GETPROCADDRESS_FAILED](#) was added in 8.0.29.

- Error number: [MY-013851](#); Symbol: [ER_ACCOUNT_WITH_EXPIRED_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.

[ER_ACCOUNT_WITH_EXPIRED_PASSWORD](#) was added in 8.0.29.

- Error number: [MY-013852](#); Symbol: [ER_THREAD_POOL_PLUGIN_STARTED](#); SQLSTATE: [HY000](#)

Message: Thread pool plugin started successfully with parameters: %s

[ER_THREAD_POOL_PLUGIN_STARTED](#) was added in 8.0.4.

- Error number: [MY-013853](#); Symbol: [ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID](#); SQLSTATE: [HY000](#)

Message: thread_pool_dedicated_listeners cannot be set unless thread_pool_max_transactions_limit > 0

[ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID](#) was added in 8.0.29.

- Error number: [MY-013854](#); Symbol: [ER_IB_DBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_DBLWR_BYTES_INFO](#) was added in 8.0.30.

- Error number: [MY-013855](#); Symbol: [ER_IB_RDBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_RDBLWR_BYTES_INFO](#) was added in 8.0.30.

- Error number: [MY-013856](#); Symbol: [ER_IB_MSG_LOG_FILE_IS_EMPTY](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.

[ER_IB_MSG_LOG_FILE_IS_EMPTY](#) was added in 8.0.30.

- Error number: [MY-013857](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_SMALL](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER_IB_MSG_LOG_FILE_TOO_SMALL](#) was added in 8.0.30.

- Error number: [MY-013858](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

[ER_IB_MSG_LOG_FILE_TOO_BIG](#) was added in 8.0.30.

- Error number: [MY-013859](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read header of the redo log file %s

`ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED` was added in 8.0.30.

- Error number: `MY-013860`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE`; SQLSTATE: `HY000`

Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.

`ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE` was added in 8.0.30.

- Error number: `MY-013861`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED`; SQLSTATE: `HY000`

Message: Failed to list redo log files in the redo log directory %s

`ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED` was added in 8.0.30.

- Error number: `MY-013862`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR`; SQLSTATE: `HY000`

Message: Neither found %s subdirectory, nor %s* files in %s

`ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR` was added in 8.0.30.

- Error number: `MY-013863`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot restore cloned data directory, InnoDB running in read-only mode!

`ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE` was added in 8.0.30.

- Error number: `MY-013864`; Symbol: `ER_IB_MSG_LOG_WRITER_WRITE_FAILED`; SQLSTATE: `HY000`

Message: Error %d encountered when writing to the redo log file: %s.

`ER_IB_MSG_LOG_WRITER_WRITE_FAILED` was added in 8.0.30.

- Error number: `MY-013865`; Symbol: `ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE`; SQLSTATE: `HY000`

Message: Redo log writer is waiting for a new redo log file. Consider increasing `innodb_redo_log_capacity`.

`ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE` was added in 8.0.30.

- Error number: `MY-013866`; Symbol: `ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE`; SQLSTATE: `HY000`

Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.

`ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE` was added in 8.0.30.

- Error number: `MY-013867`; Symbol: `ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN`; SQLSTATE: `HY000`

Message: Redo log is running out of free space, pausing user threads... Consider increasing `innodb_redo_log_capacity`.

`ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN` was added in 8.0.30.

-
- Error number: `MY-013868`; Symbol: `ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN`; SQLSTATE: `HY000`

Message: Redo log reclaimed some free space, resuming user threads.

`ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN` was added in 8.0.30.
 - Error number: `MY-013869`; Symbol: `ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_file_size`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED` was added in 8.0.30.
 - Error number: `MY-013870`; Symbol: `ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED`; SQLSTATE: `HY000`

Message: Ignored deprecated configuration parameter `innodb_log_files_in_group`. Used `innodb_redo_log_capacity` instead.

`ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED` was added in 8.0.30.
 - Error number: `MY-013871`; Symbol: `ER_IB_MSG_LOG_UPGRADE_FORCED_RECV`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files when `innodb-force-recovery > 0`.

`ER_IB_MSG_LOG_UPGRADE_FORCED_RECV` was added in 8.0.30.
 - Error number: `MY-013872`; Symbol: `ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (`--innodb-read-only`).

`ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE` was added in 8.0.30.
 - Error number: `MY-013873`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CLONED_DB`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CLONED_DB` was added in 8.0.30.
 - Error number: `MY-013874`; Symbol: `ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES` was added in 8.0.30.
 - Error number: `MY-013875`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).

`ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED` was added in 8.0.30.
 - Error number: `MY-013876`; Symbol: `ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA__UNEXPECTED`; SQLSTATE: `HY000`

Message: Cannot upgrade format (v%lu) of redo log files when there is non-persisted DD metadata in redo. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA__UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013877](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Cannot upgrade format (v%lu) of redo log files, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013878](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED__UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Failed to resize the redo log synchronously, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

[ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED__UNEXPECTED](#) was added in 8.0.30, removed after 8.0.32.

- Error number: [MY-013879](#); Symbol: [ER_IB_MSG_LOG_FILE_FOREIGN_UUID](#); SQLSTATE: [HY000](#)

Message: The redo log file %s comes from other data directory than redo log file %s.

[ER_IB_MSG_LOG_FILE_FOREIGN_UUID](#) was added in 8.0.30.

- Error number: [MY-013880](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_START_LSN](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has invalid start_lsn %llu.

[ER_IB_MSG_LOG_FILE_INVALID_START_LSN](#) was added in 8.0.30.

- Error number: [MY-013881](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES](#); SQLSTATE: [HY000](#)

Message: The redo log file %s has start_lsn %llu but expected %llu (end_lsn of the previous redo log file).

[ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES](#) was added in 8.0.30.

- Error number: [MY-013882](#); Symbol: [ER_IB_MSG_LOG_FILE_MISSING_FOR_ID](#); SQLSTATE: [HY000](#)

Message: Missing redo log file %s (with start_lsn = %llu).

[ER_IB_MSG_LOG_FILE_MISSING_FOR_ID](#) was added in 8.0.30.

- Error number: [MY-013883](#); Symbol: [ER_IB_MSG_LOG_CHECKPOINT_FOUND](#); SQLSTATE: [HY000](#)

Message: The latest found checkpoint is at lsn = %llu in redo log file %s.

[ER_IB_MSG_LOG_CHECKPOINT_FOUND](#) was added in 8.0.30.

-
- Error number: MY-013884; Symbol: ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED; SQLSTATE: HY000
Message: User has set innodb_redo_log_capacity to %lluM.
ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED was added in 8.0.30.
 - Error number: MY-013885; Symbol: ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED; SQLSTATE: HY000
Message: Redo log has been requested to resize from %lluM to %lluM.
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED was added in 8.0.30.
 - Error number: MY-013886; Symbol: ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED; SQLSTATE: HY000
Message: Redo log resize has been cancelled.
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED was added in 8.0.30.
 - Error number: MY-013887; Symbol: ER_IB_MSG_LOG_FILES_RESIZE_FINISHED; SQLSTATE: HY000
Message: Redo log has been resized to %lluM.
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED was added in 8.0.30.
 - Error number: MY-013888; Symbol: ER_IB_MSG_LOG_FILES_UPGRADE; SQLSTATE: HY000
Message: Upgrading redo log: %lluM, LSN=%llu.
ER_IB_MSG_LOG_FILES_UPGRADE was added in 8.0.30.
 - Error number: MY-013889; Symbol: ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE; SQLSTATE: HY000
Message: Marked the current redo log file %s as incomplete.
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE was added in 8.0.30.
 - Error number: MY-013890; Symbol: ER_IB_MSG_LOG_FILE_REMOVE_FAILED; SQLSTATE: HY000
Message: Failed to remove redo log file %s.
ER_IB_MSG_LOG_FILE_REMOVE_FAILED was added in 8.0.30.
 - Error number: MY-013891; Symbol: ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED; SQLSTATE: HY000
Message: Failed to rename %s when creating redo log file %s (error: %d)
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED was added in 8.0.30.
 - Error number: MY-013892; Symbol: ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR; SQLSTATE: HY000
Message: Redo log files created by unknown creator %s.
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR was added in 8.0.30.
 - Error number: MY-013893; Symbol: ER_IB_MSG_LOG_FILES_FOUND_MISSING; SQLSTATE: HY000

Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing --innodb-force-recovery > 0.

`ER_IB_MSG_LOG_FILES_FOUND_MISSING` was added in 8.0.30.

- Error number: `MY-013894`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW`; SQLSTATE: `HY000`

Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb_redo.

`ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW` was added in 8.0.30.

- Error number: `MY-013895`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD`; SQLSTATE: `HY000`

Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb_redo.

`ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD` was added in 8.0.30.

- Error number: `MY-013896`; Symbol: `ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS`; SQLSTATE: `HY000`

Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.

`ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS` was added in 8.0.30.

- Error number: `MY-013897`; Symbol: `ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0`; SQLSTATE: `HY000`

Message: Missing ib_logfile0 in the directory %s.

`ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0` was added in 8.0.30.

- Error number: `MY-013898`; Symbol: `ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize services required to handle redo log PFS tables.

`ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED` was added in 8.0.30.

- Error number: `MY-013899`; Symbol: `ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED`; SQLSTATE: `HY000`

Message: Failed to create redo log PFS tables.

`ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED` was added in 8.0.30.

- Error number: `MY-013900`; Symbol: `ER_IB_MSG_LOG_FILE_TRUNCATE`; SQLSTATE: `HY000`

Message: Truncating redo log file %s...

`ER_IB_MSG_LOG_FILE_TRUNCATE` was added in 8.0.30.

- Error number: `MY-013901`; Symbol: `ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED`; SQLSTATE: `HY000`

Message: Failed to resize unused redo log file %s to %llu MB (%s).

`ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED` was added in 8.0.30.

- Error number: `MY-013902`; Symbol: `ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED`; SQLSTATE: `HY000`

Message: Failed to remove unused redo log file %s.

[ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED](#) was added in 8.0.30.

- Error number: [MY-013903](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rename unused redo log file %s to %s.

[ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED](#) was added in 8.0.30.

- Error number: [MY-013904](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark unused redo log file %s as in use (by renaming to %s).

[ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED](#) was added in 8.0.30.

- Error number: [MY-013905](#); Symbol: [ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark redo log file %s as unused (by renaming to %s).

[ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED](#) was added in 8.0.30.

- Error number: [MY-013906](#); Symbol: [ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED](#); SQLSTATE: [HY000](#)

Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.

[ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED](#) was added in 8.0.30.

- Error number: [MY-013907](#); Symbol: [ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE](#); SQLSTATE: [HY000](#)

Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.

[ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE](#) was added in 8.0.30.

- Error number: [MY-013908](#); Symbol: [ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE](#); SQLSTATE: [HY000](#)

Message: This member was unable to log the `View_change_log_event` into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

[ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE](#) was added in 8.0.29.

- Error number: [MY-013909](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG](#); SQLSTATE: [HY000](#)

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already

acknowledged as successful to client connections and may have been replicated to other servers in the topology.

[ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG](#) was added in 8.0.30.

- Error number: [MY-013910](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE](#); SQLSTATE: [HY000](#)

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

[ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE](#) was added in 8.0.30.

- Error number: [MY-013911](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS](#); SQLSTATE: [HY000](#)

Message: Crash recovery finished in %s engine. %s

[ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS](#) was added in 8.0.30.

- Error number: [MY-013912](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to commit %s in %s, with failure code %s.

[ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED](#) was added in 8.0.30.

- Error number: [MY-013913](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

[ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED](#) was added in 8.0.30.

- Error number: [MY-013914](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to prepare %s in %s, with failure code %s.

[ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED](#) was added in 8.0.30.

- Error number: [MY-013915](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013916](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013917](#); Symbol: [ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

[ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013918](#); Symbol: [ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013919](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

[ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS](#) was added in 8.0.30.

- Error number: [MY-013920](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

[ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM](#) was added in 8.0.30.

- Error number: [MY-013921](#); Symbol: [ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

[ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE](#) was added in 8.0.30.

- Error number: [MY-013922](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.

[ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013923](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.

[ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE](#) was added in 8.0.30.

- Error number: [MY-013924](#); Symbol: [ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).

[ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE](#) was added in 8.0.30.

- Error number: [MY-013925](#); Symbol: [ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

`ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR` was added in 8.0.30.

- Error number: `MY-013926`; Symbol: `ER_COMPONENT_EE_DATA_DECRYPTION_ERROR`; SQLSTATE: `HY000`

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

`ER_COMPONENT_EE_DATA_DECRYPTION_ERROR` was added in 8.0.30.

- Error number: `MY-013927`; Symbol: `ER_COMPONENT_EE_DATA_SIGN_ERROR`; SQLSTATE: `HY000`

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have been logged before this message.

`ER_COMPONENT_EE_DATA_SIGN_ERROR` was added in 8.0.30.

- Error number: `MY-013928`; Symbol: `ER_COMPONENT_EE_OPENSSL_ERROR`; SQLSTATE: `HY000`

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

`ER_COMPONENT_EE_OPENSSL_ERROR` was added in 8.0.30.

- Error number: `MY-013929`; Symbol: `ER_COMPONENT_EE_INSUFFICIENT_LENGTH`; SQLSTATE: `HY000`

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

`ER_COMPONENT_EE_INSUFFICIENT_LENGTH` was added in 8.0.30.

- Error number: `MY-013930`; Symbol: `ER_SYSTEMD_NOTIFY_DEBUG`; SQLSTATE: `HY000`

Message: %s%s

`ER_SYSTEMD_NOTIFY_DEBUG` was added in 8.0.30.

- Error number: `MY-013931`; Symbol: `ER_TMP_SESSION_FOR_VAR`; SQLSTATE: `HY000`

Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').

`ER_TMP_SESSION_FOR_VAR` was added in 8.0.30.

- Error number: `MY-013932`; Symbol: `ER_BUILD_ID`; SQLSTATE: `HY000`

Message: BuildID[sha1]=%s

`ER_BUILD_ID` was added in 8.0.30.

- Error number: `MY-013933`; Symbol: `ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGE`; SQLSTATE: `HY000`

Message: Failed to register dynamic privilege %s.

`ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGE` was added in 8.0.30.

- Error number: `MY-013934`; Symbol: `ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER`; SQLSTATE: `HY000`

Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb_redo_log_capacity.

`ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER` was added in 8.0.30.

- Error number: `MY-013935`; Symbol: `ER_CONDITIONAL_DEBUG`; SQLSTATE: `HY000`

Message: %s

`ER_CONDITIONAL_DEBUG` was added in 8.0.30.

- Error number: `MY-013936`; Symbol: `ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION`; SQLSTATE: `HY000`

Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format

`ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION` was added in 8.0.30.

- Error number: `MY-013937`; Symbol: `ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Failed to switch resource group. %s

`ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013938`; Symbol: `ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_GLOBAL_LOCK`; SQLSTATE: `HY000`

Message: Failed to switch resource group. Could not acquire resource groups global lock.

`ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_GLOBAL_LOCK` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013939`; Symbol: `ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK`; SQLSTATE: `HY000`

Message: Failed to switch resource group. Could not acquire lock on resource group %s.

`ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013940`; Symbol: `ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RES_GRP`; SQLSTATE: `HY000`

Message: Failed to switch resource group. Unable to apply resource group controller %s.

`ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RES_GRP` was added in 8.0.30, removed after 8.0.31.

- Error number: `MY-013941`; Symbol: `ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA`; SQLSTATE: `HY000`

Message: Failed to clear instant drop column metadata for table %s

`ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA` was added in 8.0.30.

- Error number: `MY-013942`; Symbol: `ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE`; SQLSTATE: `HY000`

Message: Cannot open signing key file %s.

`ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE` was added in 8.0.31.

- Error number: `MY-013943`; Symbol: `ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY`; SQLSTATE: `HY000`

Message: Out of memory! Cannot create private key.

[ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY](#) was added in 8.0.31.

- Error number: [MY-013944](#); Symbol: [ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE](#); SQLSTATE: [HY000](#)

Message: Cannot read signing key file %s.

[ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE](#) was added in 8.0.31.

- Error number: [MY-013945](#); Symbol: [ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE](#); SQLSTATE: [HY000](#)

Message: Incomplete key: missing Name/Type for the Key: %s.

[ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE](#) was added in 8.0.31.

- Error number: [MY-013946](#); Symbol: [ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: Duplicate key found in keyring with Name: %s and Owner: %s.

[ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY](#) was added in 8.0.31.

- Error number: [MY-013947](#); Symbol: [ER_KEYRING_OCI_PARSE_JSON](#); SQLSTATE: [HY000](#)

Message: Error parsing JSON response %s.

[ER_KEYRING_OCI_PARSE_JSON](#) was added in 8.0.31.

- Error number: [MY-013948](#); Symbol: [ER_KEYRING_OCI_INVALID_JSON](#); SQLSTATE: [HY000](#)

Message: Invalid JSON response!

[ER_KEYRING_OCI_INVALID_JSON](#) was added in 8.0.31.

- Error number: [MY-013949](#); Symbol: [ER_KEYRING_OCI_HTTP_REQUEST](#); SQLSTATE: [HY000](#)

Message: HTTP request failed with error: '%s'

[ER_KEYRING_OCI_HTTP_REQUEST](#) was added in 8.0.31.

- Error number: [MY-013950](#); Symbol: [ER_THREAD_POOL_SYSVAR_CHANGE](#); SQLSTATE: [HY000](#)

Message: Variable thread_pool.%s was updated: %s

[ER_THREAD_POOL_SYSVAR_CHANGE](#) was added in 8.0.31.

- Error number: [MY-013951](#); Symbol: [ER_STACK_BACKTRACE](#); SQLSTATE: [HY000](#)

Message: %s

[ER_STACK_BACKTRACE](#) was added in 8.0.31.

- Error number: [MY-013952](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE](#); SQLSTATE: [HY000](#)

Message: Status code %u: Completed

[ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE](#) was added in 8.0.31.

-
- Error number: MY-013953; Symbol: ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE; SQLSTATE: HY000

Message: Status code %u: %u%% complete

ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE was added in 8.0.31.

- Error number: MY-013954; Symbol: ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS; SQLSTATE: HY000

Message: Status code %u: %s

ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS was added in 8.0.31.

- Error number: MY-013955; Symbol: ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID; SQLSTATE: HY000

Message: Invalid value set to thread_pool_query_threads_per_group. Valid value range is %u - %u.

ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID was added in 8.0.31.

- Error number: MY-013956; Symbol: ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT; SQLSTATE: HY000

Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group

ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT was added in 8.0.31.

- Error number: MY-013957; Symbol: ER_IB_MSG_INVALID_PAGE_TYPE; SQLSTATE: HY000

Message: Found page type mismatch. Expected %u, found %u, in page: space_id=%lu page_no=%lu

ER_IB_MSG_INVALID_PAGE_TYPE was added in 8.0.32.

- Error number: MY-013958; Symbol: ER_IB_PARALLEL_READER_WORKER_INFO; SQLSTATE: HY000

Message: preader: space_id=%zu, table=%s, index=%s, scan_ctx=%zu, ctx=%zu, thread_id=%zu, n_threads=%zu

ER_IB_PARALLEL_READER_WORKER_INFO was added in 8.0.32.

- Error number: MY-013959; Symbol: ER_IB_BULK_LOAD_SUBTREE_INFO; SQLSTATE: HY000

Message: bulkload: space_id=%zu, table=%s, index=%s, height=%zu, n_extents=%zu, n_pages=%zu

ER_IB_BULK_LOAD_SUBTREE_INFO was added in 8.0.32.

- Error number: MY-013960; Symbol: ER_IB_BULK_FLUSHER_INFO; SQLSTATE: HY000

Message: bulkflusher: sleep_count=%zu, sleep_duration=%zu milliseconds, total_sleep=%zu milliseconds, pages_flushed=%zu

ER_IB_BULK_FLUSHER_INFO was added in 8.0.32.

- Error number: MY-013961; Symbol: ER_IB_BUFFER_POOL_OVERUSE; SQLSTATE: HY000

Message: %s: Over 67 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set

too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.

[ER_IB_BUFFER_POOL_OVERUSE](#) was added in 8.0.32.

- Error number: [MY-013962](#); Symbol: [ER_IB_BUFFER_POOL_FULL](#); SQLSTATE: [HY000](#)

Message: %s: Over 95 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!

[ER_IB_BUFFER_POOL_FULL](#) was added in 8.0.32.

- Error number: [MY-013963](#); Symbol: [ER_IB_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)

Message: %s: table=%s, index=%s, n_uniq=%zu, n_fields=%zu, lhs=(%s), rhs=(%s)

[ER_IB_DUPLICATE_KEY](#) was added in 8.0.32.

- Error number: [MY-013964](#); Symbol: [ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK](#); SQLSTATE: [HY000](#)

Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.

[ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK](#) was added in 8.0.32.

- Error number: [MY-013965](#); Symbol: [ER_BULK_EXECUTOR_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk executor: %s

[ER_BULK_EXECUTOR_INFO](#) was added in 8.0.32.

- Error number: [MY-013966](#); Symbol: [ER_BULK_LOADER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk loader: %s

[ER_BULK_LOADER_INFO](#) was added in 8.0.32.

- Error number: [MY-013967](#); Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE_LOG](#); SQLSTATE: [HY000](#)

Message: The first file being loaded contained less lines than the ignore clause

[ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE_LOG](#) was added in 8.0.32.

- Error number: [MY-013968](#); Symbol: [ER_BULK_READER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk reader: %s

[ER_BULK_READER_INFO](#) was added in 8.0.32.

-
- Error number: [MY-013969](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader failed to initialize libcurl

[ER_BULK_READER_LIBCURL_INIT_FAILED_LOG](#) was added in 8.0.32.

- Error number: [MY-013970](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader got libcurl error: %s

[ER_BULK_READER_LIBCURL_ERROR_LOG](#) was added in 8.0.32.

- Error number: [MY-013971](#); Symbol: [ER_BULK_READER_SERVER_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error response from server: %ld

[ER_BULK_READER_SERVER_ERROR_LOG](#) was added in 8.0.32.

- Error number: [MY-013972](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk reader got error in communication with source server, check the error log for additional details

[ER_BULK_READER_COMMUNICATION_ERROR_LOG](#) was added in 8.0.32.

- Error number: [MY-013973](#); Symbol: [ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)

Message: Missing ENCLOSED BY character at row %ld in file %s. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

[ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG](#) was added in 8.0.32.

- Error number: [MY-013974](#); Symbol: [ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

[ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG](#) was added in 8.0.32.

- Error number: [MY-013975](#); Symbol: [ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.

[ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG](#) was added in 8.0.32.

- Error number: [MY-013976](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

[ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG](#) was added in 8.0.32.

-
- Error number: [MY-013977](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

[ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG](#) was added in 8.0.32.

- Error number: [MY-013978](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.

[ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY_LOG](#) was added in 8.0.32.

- Error number: [MY-013979](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.

[ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG](#) was added in 8.0.32.

- Error number: [MY-013980](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected characters after column terminator found at row %ld in file '%s'.

[ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG](#) was added in 8.0.32.

- Error number: [MY-013981](#); Symbol: [ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.

[ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG](#) was added in 8.0.32.

- Error number: [MY-013982](#); Symbol: [ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG](#); SQLSTATE: [HY000](#)

Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

[ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG](#) was added in 8.0.32.

- Error number: [MY-013983](#); Symbol: [ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG](#); SQLSTATE: [HY000](#)

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

[ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG](#) was added in 8.0.32.

- Error number: [MY-013984](#); Symbol: [ER_IB_BULK_LOAD_THREAD_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s

[ER_IB_BULK_LOAD_THREAD_FAIL](#) was added in 8.0.32.

- Error number: [MY-013985](#); Symbol: [ER_IB_BULK_LOAD_MERGE_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s

`ER_IB_BULK_LOAD_MERGE_FAIL` was added in 8.0.32.

- Error number: `MY-013986`; Symbol: `ER_IB_LOAD_BULK_CONCURRENCY_REDUCED`; SQLSTATE: `HY000`

Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.

`ER_IB_LOAD_BULK_CONCURRENCY_REDUCED` was added in 8.0.32.

- Error number: `MY-013987`; Symbol: `ER_PLUGIN_EXCEPTION_OPERATION_FAILED`; SQLSTATE: `HY000`

Message: C++ Exception caught while %s the %s plugin: [%s]

`ER_PLUGIN_EXCEPTION_OPERATION_FAILED` was added in 8.0.32.

- Error number: `MY-013988`; Symbol: `ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR_IN_REPO`; SQLSTATE: `HY000`

Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting `REQUIRE_TABLE_PRIMARY_KEY_CHECK` to 'GENERATE' is not allowed. Run `RESET REPLICA ALL` to reset it.

`ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR_IN_REPO` was added in 8.0.32.

- Error number: `MY-013989`; Symbol: `ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET`; SQLSTATE: `HY000`

Message: Record has both instant and version bit set.

`ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET` was added in 8.0.32.

- Error number: `MY-013990`; Symbol: `ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP`; SQLSTATE: `HY000`

Message: This member is configured with a `group_replication_paxos_single_leader` option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, `group_replication_paxos_single_leader` value must be configured to the value 0. This member will now exit the group.

`ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP` was added in 8.0.32.

- Error number: `MY-013991`; Symbol: `ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY`; SQLSTATE: `HY000`

Message: Ignored the `innodb-redo-log-capacity` option in the Innodb read-only mode. Server is using active redo log files.

`ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY` was added in 8.0.32.

- Error number: `MY-013992`; Symbol: `ER_IB_PRIMARY_KEY_IS_INSTANT`; SQLSTATE: `HY000`

Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging

`ER_IB_PRIMARY_KEY_IS_INSTANT` was added in 8.0.32.

- Error number: `MY-013993`; Symbol: `ER_THREAD_POOL_IDLE_CONNECTION_CLOSED`; SQLSTATE: `HY000`

Message: %s

[ER_THREAD_POOL_IDLE_CONNECTION_CLOSED](#) was added in 8.0.32.

- Error number: [MY-013994](#); Symbol: [ER_IB_HIDDEN_NAME_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.

[ER_IB_HIDDEN_NAME_CONFLICT](#) was added in 8.0.32.

- Error number: [MY-013995](#); Symbol: [ER_IB_DICT_INVALID_COLUMN_POSITION](#); SQLSTATE: [HY000](#)

Message: Field number: %llu too large, Total fields in Record: %zu.

[ER_IB_DICT_INVALID_COLUMN_POSITION](#) was added in 8.0.32.

- Error number: [MY-013996](#); Symbol: [ER_IB_DICT_LOG_TABLE_INFO](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_DICT_LOG_TABLE_INFO](#) was added in 8.0.32.

- Error number: [MY-013997](#); Symbol: [ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED](#); SQLSTATE: [HY000](#)

Message: The connection has timed out after %lu retries connecting to '%s@%s:%d%s', and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'

[ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED](#) was added in 8.0.33.

- Error number: [MY-013998](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED](#); SQLSTATE: [HY000](#)

Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server_uuid %s.

[ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED](#) was added in 8.0.33.

- Error number: [MY-013999](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: The server_uuid for source server '%s:%d' has changed from %s to %s. This should not happen unless you have changed it manually.

[ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT_UNCHANGED](#) was added in 8.0.33.

- Error number: [MY-014000](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED](#); SQLSTATE: [HY000](#)

Message: The source server has changed from '%s:%d' with server_uuid %s, to '%s:%d' with server_uuid %s.

[ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED](#) was added in 8.0.33.

- Error number: [MY-014001](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FILE_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server_uuid=%s, server_id=%d. Starting replication from file '%s', position '%s'.

`ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FILE_BASED` was added in 8.0.33.

- Error number: `MY-014002`; Symbol: `ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_GTID_BASED`; SQLSTATE: `HY000`

Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server_uuid=%s, server_id=%d. Starting GTID-based replication.

`ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_GTID_BASED` was added in 8.0.33.

- Error number: `MY-014003`; Symbol: `ER_IB_INDEX_LOADER_DONE`; SQLSTATE: `HY000`

Message: Loader::build_all(): Completed building %zu indexes for old_table=%s, new_table=%s, err=%zu.

`ER_IB_INDEX_LOADER_DONE` was added in 8.0.32.

- Error number: `MY-014004`; Symbol: `ER_IB_INDEX_BUILDER_DONE`; SQLSTATE: `HY000`

Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.

`ER_IB_INDEX_BUILDER_DONE` was added in 8.0.32.

- Error number: `MY-014005`; Symbol: `ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION`; SQLSTATE: `HY000`

Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

`ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION` was added in 8.0.33.

- Error number: `MY-014006`; Symbol: `ER_IB_INDEX_BUILDER_INIT`; SQLSTATE: `HY000`

Message: Builder::init(): Initialize for building index=%s of table=%s, n_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.

`ER_IB_INDEX_BUILDER_INIT` was added in 8.0.33.

- Error number: `MY-014007`; Symbol: `ER_IB_SELECT_COUNT_STAR`; SQLSTATE: `HY000`

Message: SELECT COUNT(*) FROM table=%s, n_threads=%zu, n_partitions=%zu.

`ER_IB_SELECT_COUNT_STAR` was added in 8.0.33.

- Error number: `MY-014008`; Symbol: `ER_IB_INDEX_LOG_VERSION_MISMATCH`; SQLSTATE: `HY000`

Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.

`ER_IB_INDEX_LOG_VERSION_MISMATCH` was added in 8.0.33.

- Error number: `MY-014009`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING`; SQLSTATE: `HY000`

Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.

`ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING` was added in 8.0.33.

-
- Error number: [MY-014010](#); Symbol: [ER_GRP_RPL_HAS_STARTED](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' has been started.
[ER_GRP_RPL_HAS_STARTED](#) was added in 8.0.33.
 - Error number: [MY-014011](#); Symbol: [ER_CHECK_TABLE_MIN_REC_FLAG_SET](#); SQLSTATE: [HY000](#)
Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.
[ER_CHECK_TABLE_MIN_REC_FLAG_SET](#) was added in 8.0.33.
 - Error number: [MY-014012](#); Symbol: [ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET](#); SQLSTATE: [HY000](#)
Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.
[ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET](#) was added in 8.0.33.
 - Error number: [MY-014013](#); Symbol: [ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS](#); SQLSTATE: [HY000](#)
Message: Successfully registered slot '%d' for component '%s'.
[ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS](#) was added in 8.0.33.
 - Error number: [MY-014014](#); Symbol: [ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS](#); SQLSTATE: [HY000](#)
Message: Successfully de-registered slot '%d' from component '%s'.
[ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS](#) was added in 8.0.33.
 - Error number: [MY-014015](#); Symbol: [ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.
[ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION_FAILED](#) was added in 8.0.33.
 - Error number: [MY-014016](#); Symbol: [ER_IB_RESURRECT_TRX_INSERT](#); SQLSTATE: [HY000](#)
Message: Transaction ID: %lu found for resurrecting inserts
[ER_IB_RESURRECT_TRX_INSERT](#) was added in 8.0.33.
 - Error number: [MY-014017](#); Symbol: [ER_IB_RESURRECT_TRX_UPDATE](#); SQLSTATE: [HY000](#)
Message: Transaction ID: %lu found for resurrecting updates
[ER_IB_RESURRECT_TRX_UPDATE](#) was added in 8.0.33.
 - Error number: [MY-014018](#); Symbol: [ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK](#); SQLSTATE: [HY000](#)
Message: Identified table ID: %lu to acquire lock
[ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK](#) was added in 8.0.33.
 - Error number: [MY-014019](#); Symbol: [ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK](#); SQLSTATE: [HY000](#)

Message: Acquired lock on table ID: %lu, name: %s

[ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK](#) was added in 8.0.33.

- Error number: [MY-014020](#); Symbol: [ER_IB_RESURRECT_RECORD_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Records read: %lu - Pages read: %lu

[ER_IB_RESURRECT_RECORD_PROGRESS](#) was added in 8.0.33.

- Error number: [MY-014021](#); Symbol: [ER_IB_RESURRECT_RECORD_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu

[ER_IB_RESURRECT_RECORD_COMPLETE](#) was added in 8.0.33.

- Error number: [MY-014022](#); Symbol: [ER_IB_RESURRECT_TRX_INSERT_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Resurrected %lu transactions doing inserts.

[ER_IB_RESURRECT_TRX_INSERT_COMPLETE](#) was added in 8.0.33.

- Error number: [MY-014023](#); Symbol: [ER_IB_RESURRECT_TRX_UPDATE_COMPLETE](#); SQLSTATE: [HY000](#)

Message: Resurrected %lu transactions doing updates.

[ER_IB_RESURRECT_TRX_UPDATE_COMPLETE](#) was added in 8.0.33.

- Error number: [MY-014024](#); Symbol: [ER_AUTHENTICATION_OCI_INVALID_TOKEN](#); SQLSTATE: [HY000](#)

Message: Invalid security token provided by '%s' for '%s'@'%s': %s.

[ER_AUTHENTICATION_OCI_INVALID_TOKEN](#) was added in 8.0.33.

- Error number: [MY-014025](#); Symbol: [ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.

[ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH](#) was added in 8.0.33.

- Error number: [MY-014026](#); Symbol: [ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED](#); SQLSTATE: [HY000](#)

Message: Verification failed for security token provided by '%s' for '%s'@'%s': %s.

[ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED](#) was added in 8.0.33.

- Error number: [MY-014027](#); Symbol: [ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY](#); SQLSTATE: [HY000](#)

Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.

[ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY](#) was added in 8.0.33.

- Error number: [MY-014028](#); Symbol: [ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN_TOKEN](#); SQLSTATE: [HY000](#)

Message: None of the groups extracted from security token matches any of the entries from authentication string.

[ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN_TOKEN](#) was added in 8.0.33, removed after 8.0.33.

- Error number: [MY-014029](#); Symbol: [ER_SYS_VAR_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

[ER_SYS_VAR_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014030](#); Symbol: [ER_SYS_VAR_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

[ER_SYS_VAR_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014031](#); Symbol: [ER_UDF_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

[ER_UDF_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014032](#); Symbol: [ER_UDF_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

[ER_UDF_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014033](#); Symbol: [ER_PRIVILEGE_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

[ER_PRIVILEGE_REGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014034](#); Symbol: [ER_PRIVILEGE_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

[ER_PRIVILEGE_DEREGISTRATION](#) was added in 8.0.33.

- Error number: [MY-014035](#); Symbol: [ER_UDF_EXEC_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

[ER_UDF_EXEC_FAILURE](#) was added in 8.0.33.

- Error number: [MY-014036](#); Symbol: [ER_UDF_EXEC_FAILURE_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

[ER_UDF_EXEC_FAILURE_REASON](#) was added in 8.0.33.

- Error number: [MY-014037](#); Symbol: [ER_COMPONENT_SERVICE_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

[ER_COMPONENT_SERVICE_CALL](#) was added in 8.0.33.

-
- Error number: `MY-014038`; Symbol: `ER_COMPONENT_SERVICE_CALL_RESULT`; SQLSTATE: `HY000`

Message: %s failed with %u.

`ER_COMPONENT_SERVICE_CALL_RESULT` was added in 8.0.33.
 - Error number: `MY-014039`; Symbol: `ER_COMPONENT_LOCK`; SQLSTATE: `HY000`

Message: Lock failed at %s : %u.

`ER_COMPONENT_LOCK` was added in 8.0.33.
 - Error number: `MY-014040`; Symbol: `ER_COMPONENT_UNLOCK`; SQLSTATE: `HY000`

Message: Lock from %s : %u failed to unlock.

`ER_COMPONENT_UNLOCK` was added in 8.0.33.
 - Error number: `MY-014041`; Symbol: `ER_COMPONENT_MASKING_OTHER_ERROR`; SQLSTATE: `HY000`

Message: Masking component error: '%s'.

`ER_COMPONENT_MASKING_OTHER_ERROR` was added in 8.0.33.
 - Error number: `MY-014042`; Symbol: `ER_COMPONENT_MASKING_ABI`; SQLSTATE: `HY000`

Message: %s failed.

`ER_COMPONENT_MASKING_ABI` was added in 8.0.33.
 - Error number: `MY-014043`; Symbol: `ER_COMPONENT_MASKING_ABI_REASON`; SQLSTATE: `HY000`

Message: %s failed because %s.

`ER_COMPONENT_MASKING_ABI_REASON` was added in 8.0.33.
 - Error number: `MY-014044`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE`; SQLSTATE: `HY000`

Message: Creation of random context failed.

`ER_COMPONENT_MASKING_RANDOM_CREATE` was added in 8.0.33.
 - Error number: `MY-014045`; Symbol: `ER_COMPONENT_MASKING_RANDOM_CREATE_REASON`; SQLSTATE: `HY000`

Message: Creation of random context failed because %s.

`ER_COMPONENT_MASKING_RANDOM_CREATE_REASON` was added in 8.0.33.
 - Error number: `MY-014046`; Symbol: `ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE`; SQLSTATE: `HY000`

Message: Cannot access %s.%s table.

`ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE` was added in 8.0.33.
 - Error number: `MY-014047`; Symbol: `ER_REDUCED_DBLWR_FILE_CORRUPTED`; SQLSTATE: `HY000`

Message: Cannot recover from detect_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

`ER_REDUCED_DBLWR_FILE_CORRUPTED` was added in 8.0.30.

- Error number: `MY-014048`; Symbol: `ER_REDUCED_DBLWR_PAGE_FOUND`; SQLSTATE: `HY000`

Message: Database page corruption of tablespace %s space_id: %u page_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect_only-doublewrite mode.

`ER_REDUCED_DBLWR_PAGE_FOUND` was added in 8.0.30.

- Error number: `MY-014049`; Symbol: `ER_CONN_INIT_CONNECT_IGNORED_MFA`; SQLSTATE: `HY000`

Message: init_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing

`ER_CONN_INIT_CONNECT_IGNORED_MFA` was added in 8.0.33.

- Error number: `MY-014050`; Symbol: `ER_SECONDARY_ENGINE_DDL_FAILED`; SQLSTATE: `HY000`

Message: Execution of alter table %s %s failed because %s.

`ER_SECONDARY_ENGINE_DDL_FAILED` was added in 8.0.33.

- Error number: `MY-014051`; Symbol: `ER_THREAD_POOL_CONNECTION_REPORT`; SQLSTATE: `HY000`

Message: TP conn (port: managed(delta), active, opened, closed, added, dropped): %s

`ER_THREAD_POOL_CONNECTION_REPORT` was added in 8.0.33.

- Error number: `MY-014052`; Symbol: `ER_WARN_SCHEDULED_TASK_RUN_FAILED`; SQLSTATE: `HY000`

Message: Scheduled run of task %s failed

`ER_WARN_SCHEDULED_TASK_RUN_FAILED` was added in 8.0.34.

- Error number: `MY-014053`; Symbol: `ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE`; SQLSTATE: `HY000`

Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d

`ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE` was added in 8.0.34.

- Error number: `MY-014054`; Symbol: `ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK`; SQLSTATE: `HY000`

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

`ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK` was added in 8.0.34.

- Error number: `MY-014055`; Symbol: `ER_CONVERT_MULTI_VALUE`; SQLSTATE: `HY000`

Message: Multi-values cannot be converted to MySQL format: %s

`ER_CONVERT_MULTI_VALUE` was added in 8.0.35.

- Error number: `MY-014056`; Symbol: `ER_IB_DDL_CONVERT_HEAP_NOT_FOUND`; SQLSTATE: `HY000`

Message: Heap required to convert columns is not present.

`ER_IB_DDL_CONVERT_HEAP_NOT_FOUND` was added in 8.0.35.

- Error number: `MY-014057`; Symbol: `ER_SERVER_DOWNGRADE_FROM_VERSION`; SQLSTATE: `HY000`

Message: MySQL server downgrading from version '%u' to '%u'.

`ER_SERVER_DOWNGRADE_FROM_VERSION` was added in 8.0.35.

- Error number: `MY-014058`; Symbol: `ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD`; SQLSTATE: `HY000`

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.

`ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD` was added in 8.0.35.

- Error number: `MY-014059`; Symbol: `ER_BEYOND_SERVER_UPGRADE_THRESHOLD`; SQLSTATE: `HY000`

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.

`ER_BEYOND_SERVER_UPGRADE_THRESHOLD` was added in 8.0.35.

- Error number: `MY-014060`; Symbol: `ER_INVALID_SERVER_UPGRADE_NOT_LTS`; SQLSTATE: `HY000`

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.

`ER_INVALID_SERVER_UPGRADE_NOT_LTS` was added in 8.0.35.

- Error number: `MY-014061`; Symbol: `ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH`; SQLSTATE: `HY000`

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.

`ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH` was added in 8.0.35.

- Error number: `MY-014062`; Symbol: `ER_FAILED_GET_DD_PROPERTY`; SQLSTATE: `HY000`

Message: Failed to get the data dictionary property %s.

`ER_FAILED_GET_DD_PROPERTY` was added in 8.0.35.

- Error number: `MY-014063`; Symbol: `ER_FAILED_SET_DD_PROPERTY`; SQLSTATE: `HY000`

Message: Failed to set the data dictionary property %s.

`ER_FAILED_SET_DD_PROPERTY` was added in 8.0.35.

- Error number: `MY-014064`; Symbol: `ER_SERVER_DOWNGRADE_STATUS`; SQLSTATE: `HY000`

Message: Server downgrade from '%d' to '%d' %s.

`ER_SERVER_DOWNGRADE_STATUS` was added in 8.0.35.

- Error number: `MY-014065`; Symbol: `ER_INFORMATION_SCHEMA_VERSION_CHANGE`; SQLSTATE: `HY000`

Message: %s information schema from version %u to %u.

[ER_INFORMATION_SCHEMA_VERSION_CHANGE](#) was added in 8.0.35.

- Error number: [MY-014066](#); Symbol: [ER_PERFORMANCE_SCHEMA_VERSION_CHANGE](#); SQLSTATE: [HY000](#)

Message: %s performance schema from version %u to %u.

[ER_PERFORMANCE_SCHEMA_VERSION_CHANGE](#) was added in 8.0.35.

- Error number: [MY-014067](#); Symbol: [ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER](#); SQLSTATE: [HY000](#)

Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.

[ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER](#) was added in 8.0.35.

- Error number: [MY-014068](#); Symbol: [ER_IB_MSG_DDL_FAIL_NO_BUILDER](#); SQLSTATE: [HY000](#)

Message: DDL failed as Builder is already freed. Builder: state=%u, error_state=%u. Index: id=%zu, name='%s', space_id=%u, page=%u. Table: old_name='%s', new_name='%s'.

[ER_IB_MSG_DDL_FAIL_NO_BUILDER](#) was added in 8.0.36.

- Error number: [MY-014069](#); Symbol: [ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.

[ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST](#) was added in 8.0.36.

- Error number: [MY-014070](#); Symbol: [ER_USAGE_DEPRECATED_COUNTER](#); SQLSTATE: [HY000](#)

Message: Deprecated '%s' used %s times, last time used '%s'.

[ER_USAGE_DEPRECATED_COUNTER](#) was added in 8.0.36.

- Error number: [MY-014071](#); Symbol: [ER_WAITING_FOR_NO_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Waiting for %u connections to be closed.

[ER_WAITING_FOR_NO_CONNECTIONS](#) was added in 8.0.38.

- Error number: [MY-014072](#); Symbol: [ER_WAITING_FOR_NO_THDS](#); SQLSTATE: [HY000](#)

Message: Waiting for THDs in partition %u to be closed, %u still left. %u THDs left in total for all partitions.

[ER_WAITING_FOR_NO_THDS](#) was added in 8.0.38.

- Error number: [MY-014073](#); Symbol: [ER_IB_INDEX_PART_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index %s of %s.%s exceeds limit of %lu bytes per column.

[ER_IB_INDEX_PART_TOO_LONG](#) was added in 8.0.38.

- Error number: [MY-014074](#); Symbol: [ER_DD_UPDATE_DATADIR_FLAG_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to update data directory flag for dd table with tablespace id '%llu' when ibd file for '%s' is moved to new location '%s' during server shutdown

[ER_DD_UPDATE_DATADIR_FLAG_FAIL](#) was added in 8.0.38.

-
- Error number: [MY-014075](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_PREV](#); SQLSTATE: [HY000](#)
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory, but DD misses info about DATA DIRECTORY
[ER_IB_MSG_FIL_STATE_MOVED_PREV](#) was added in 8.0.38.
 - Error number: [MY-014075](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR](#); SQLSTATE: [HY000](#)
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory. It is either moved or is created with 'DATA DIRECTORY'
[ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR](#) was added in 8.0.39, removed after 8.0.40.
 - Error number: [MY-014076](#); Symbol: [ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED](#); SQLSTATE: [HY000](#)
Message: Upon reconnection with the replica, while initializing the dump thread for %s <%s>, an existing dump thread with the same %s was detected. The source is terminating the previous dump thread (%u), which is normal and expected.
[ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED](#) was added in 8.0.41.
 - Error number: [MY-014077](#); Symbol: [ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)
Message: The transaction '%s' will commit out of order with respect to its source to follow the group global order.
[ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER](#) was added in 8.0.41.
 - Error number: [MY-014078](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS](#); SQLSTATE: [HY000](#)
Message: Can not open table `%s`.`%s`; functions in constraints, partitions, or virtual columns may have failed.
[ER_CHECK_TABLE_FUNCTIONS](#) was added in 8.0.42.
 - Error number: [MY-014079](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS_DETAIL](#); SQLSTATE: [HY000](#)
Message: %s
[ER_CHECK_TABLE_FUNCTIONS_DETAIL](#) was added in 8.0.42.
 - Error number: [MY-014080](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create the Group Replication certifier broadcast thread (THD_certifier_broadcast).
[ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED](#) was added in 8.0.42.
 - Error number: [MY-014081](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED](#); SQLSTATE: [HY000](#)
Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) started.
[ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED](#) was added in 8.0.42.
 - Error number: [MY-014082](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED](#); SQLSTATE: [HY000](#)

Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) stopped.

[ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED](#) was added in 8.0.42.

- Error number: [MY-014083](#); Symbol: [ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL](#); SQLSTATE: [HY000](#)

Message: The group replication applier thread has received KILL request.

[ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL](#) was added in 8.0.43.

Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: 2000; Symbol: `CR_UNKNOWN_ERROR`;
Message: Unknown MySQL error
- Error number: 2001; Symbol: `CR_SOCKET_CREATE_ERROR`;
Message: Can't create UNIX socket (%d)
- Error number: 2002; Symbol: `CR_CONNECTION_ERROR`;
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: 2003; Symbol: `CR_CONN_HOST_ERROR`;
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: 2004; Symbol: `CR_IPSOCK_ERROR`;
Message: Can't create TCP/IP socket (%d)
- Error number: 2005; Symbol: `CR_UNKNOWN_HOST`;
Message: Unknown MySQL server host '%s' (%d)
- Error number: 2006; Symbol: `CR_SERVER_GONE_ERROR`;
Message: MySQL server has gone away
- Error number: 2007; Symbol: `CR_VERSION_ERROR`;
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: 2008; Symbol: `CR_OUT_OF_MEMORY`;
Message: MySQL client ran out of memory
- Error number: 2009; Symbol: `CR_WRONG_HOST_INFO`;
Message: Wrong host info
- Error number: 2010; Symbol: `CR_LOCALHOST_CONNECTION`;
Message: Localhost via UNIX socket

-
- Error number: [2011](#); Symbol: [CR_TCP_CONNECTION](#);
Message: %s via TCP/IP
 - Error number: [2012](#); Symbol: [CR_SERVER_HANDSHAKE_ERR](#);
Message: Error in server handshake
 - Error number: [2013](#); Symbol: [CR_SERVER_LOST](#);
Message: Lost connection to MySQL server during query
 - Error number: [2014](#); Symbol: [CR_COMMANDS_OUT_OF_SYNC](#);
Message: Commands out of sync; you can't run this command now

Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
 - Error number: [2015](#); Symbol: [CR_NAMEDPIPE_CONNECTION](#);
Message: Named pipe: %s
 - Error number: [2016](#); Symbol: [CR_NAMEDPIPEWAIT_ERROR](#);
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
 - Error number: [2017](#); Symbol: [CR_NAMEDPIPEOPEN_ERROR](#);
Message: Can't open named pipe to host: %s pipe: %s (%lu)
 - Error number: [2018](#); Symbol: [CR_NAMEDPIPESETSTATE_ERROR](#);
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
 - Error number: [2019](#); Symbol: [CR_CANT_READ_CHARSET](#);
Message: Can't initialize character set %s (path: %s)
 - Error number: [2020](#); Symbol: [CR_NET_PACKET_TOO_LARGE](#);
Message: Got packet bigger than 'max_allowed_packet' bytes
 - Error number: [2021](#); Symbol: [CR_EMBEDDED_CONNECTION](#);
Message: Embedded server
 - Error number: [2022](#); Symbol: [CR_PROBE_SLAVE_STATUS](#);
Message: Error on SHOW SLAVE STATUS:

[CR_PROBE_SLAVE_STATUS](#) was removed after 8.0.32.
 - Error number: [2022](#); Symbol: [CR_PROBE_REPLICA_STATUS](#);
Message: Error on SHOW REPLICA STATUS:

[CR_PROBE_REPLICA_STATUS](#) was added in 8.0.33.
 - Error number: [2023](#); Symbol: [CR_PROBE_SLAVE_HOSTS](#);
Message: Error on SHOW SLAVE HOSTS:

`CR_PROBE_SLAVE_HOSTS` was removed after 8.0.32.

- Error number: 2023; Symbol: `CR_PROBE_REPLICA_HOSTS`;

Message: Error on SHOW REPLICA HOSTS:

`CR_PROBE_REPLICA_HOSTS` was added in 8.0.33.

- Error number: 2024; Symbol: `CR_PROBE_SLAVE_CONNECT`;

Message: Error connecting to slave:

`CR_PROBE_SLAVE_CONNECT` was removed after 8.0.32.

- Error number: 2024; Symbol: `CR_PROBE_REPLICA_CONNECT`;

Message: Error connecting to replica:

`CR_PROBE_REPLICA_CONNECT` was added in 8.0.33.

- Error number: 2025; Symbol: `CR_PROBE_MASTER_CONNECT`;

Message: Error connecting to master:

`CR_PROBE_MASTER_CONNECT` was removed after 8.0.32.

- Error number: 2025; Symbol: `CR_PROBE_SOURCE_CONNECT`;

Message: Error connecting to source:

`CR_PROBE_SOURCE_CONNECT` was added in 8.0.33.

- Error number: 2026; Symbol: `CR_SSL_CONNECTION_ERROR`;

Message: SSL connection error: %s

- Error number: 2027; Symbol: `CR_MALFORMED_PACKET`;

Message: Malformed packet

- Error number: 2028; Symbol: `CR_WRONG_LICENSE`;

Message: This client library is licensed only for use with MySQL servers having '%s' license

- Error number: 2029; Symbol: `CR_NULL_POINTER`;

Message: Invalid use of null pointer

- Error number: 2030; Symbol: `CR_NO_PREPARE_STMT`;

Message: Statement not prepared

- Error number: 2031; Symbol: `CR_PARAMS_NOT_BOUND`;

Message: No data supplied for parameters in prepared statement

- Error number: 2032; Symbol: `CR_DATA_TRUNCATED`;

Message: Data truncated

- Error number: 2033; Symbol: `CR_NO_PARAMETERS_EXISTS`;

Message: No parameters exist in the statement

-
- Error number: 2034; Symbol: CR_INVALID_PARAMETER_NO;
Message: Invalid parameter number
The column number for `mysql_stmt_fetch_column()` was invalid.
The parameter number for `mysql_stmt_send_long_data()` was invalid.
A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
 - Error number: 2035; Symbol: CR_INVALID_BUFFER_USE;
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
 - Error number: 2036; Symbol: CR_UNSUPPORTED_PARAM_TYPE;
Message: Using unsupported buffer type: %d (parameter: %d)
 - Error number: 2037; Symbol: CR_SHARED_MEMORY_CONNECTION;
Message: Shared memory: %s
 - Error number: 2038; Symbol: CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR;
Message: Can't open shared memory; client could not create request event (%lu)
 - Error number: 2039; Symbol: CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR;
Message: Can't open shared memory; no answer event received from server (%lu)
 - Error number: 2040; Symbol: CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR;
Message: Can't open shared memory; server could not allocate file mapping (%lu)
 - Error number: 2041; Symbol: CR_SHARED_MEMORY_CONNECT_MAP_ERROR;
Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
 - Error number: 2042; Symbol: CR_SHARED_MEMORY_FILE_MAP_ERROR;
Message: Can't open shared memory; client could not allocate file mapping (%lu)
 - Error number: 2043; Symbol: CR_SHARED_MEMORY_MAP_ERROR;
Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
 - Error number: 2044; Symbol: CR_SHARED_MEMORY_EVENT_ERROR;
Message: Can't open shared memory; client could not create %s event (%lu)
 - Error number: 2045; Symbol: CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR;
Message: Can't open shared memory; no answer from server (%lu)
 - Error number: 2046; Symbol: CR_SHARED_MEMORY_CONNECT_SET_ERROR;
Message: Can't open shared memory; cannot send request event to server (%lu)
 - Error number: 2047; Symbol: CR_CONN_UNKNOW_PROTOCOL;
Message: Wrong or unknown protocol
 - Error number: 2048; Symbol: CR_INVALID_CONN_HANDLE;

Message: Invalid connection handle

- Error number: 2049; Symbol: CR_UNUSED_1;

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)

- Error number: 2050; Symbol: CR_FETCH_CANCELED;

Message: Row retrieval was canceled by mysql_stmt_close() call

- Error number: 2051; Symbol: CR_NO_DATA;

Message: Attempt to read column without prior row fetch

- Error number: 2052; Symbol: CR_NO_STMT_METADATA;

Message: Prepared statement contains no metadata

- Error number: 2053; Symbol: CR_NO_RESULT_SET;

Message: Attempt to read a row while there is no result set associated with the statement

- Error number: 2054; Symbol: CR_NOT_IMPLEMENTED;

Message: This feature is not implemented yet

- Error number: 2055; Symbol: CR_SERVER_LOST_EXTENDED;

Message: Lost connection to MySQL server at '%s', system error: %d

- Error number: 2056; Symbol: CR_STMT_CLOSED;

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: CR_NEW_STMT_METADATA;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: CR_ALREADY_CONNECTED;

Message: This handle is already connected. Use a separate handle for each connection.

- Error number: 2059; Symbol: CR_AUTH_PLUGIN_CANNOT_LOAD;

Message: Authentication plugin '%s' cannot be loaded: %s

- Error number: 2060; Symbol: CR_DUPLICATE_CONNECTION_ATTR;

Message: There is an attribute with the same name already

A duplicate connection attribute name was specified for `mysql_options4()`.

- Error number: 2061; Symbol: CR_AUTH_PLUGIN_ERR;

Message: Authentication plugin '%s' reported error: %s

- Error number: 2062; Symbol: CR_INSECURE_API_ERR;

Message: Insecure API function call: '%s' Use instead: '%s'

An insecure function call was detected. Modify the application to use the suggested alternative function instead.

-
- Error number: 2063; Symbol: `CR_FILE_NAME_TOO_LONG`;
Message: File name is too long
`CR_FILE_NAME_TOO_LONG` was added in 8.0.1.
 - Error number: 2064; Symbol: `CR_SSL_FIPS_MODE_ERR`;
Message: Set FIPS mode ON/STRICT failed
`CR_SSL_FIPS_MODE_ERR` was added in 8.0.11.
 - Error number: 2065; Symbol: `CR_COMPRESSION_NOT_SUPPORTED`;
Message: Compression protocol not supported with asynchronous protocol
`CR_COMPRESSION_NOT_SUPPORTED` was added in 8.0.16, removed after 8.0.20.
 - Error number: 2065; Symbol: `CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED`;
Message: Compression protocol not supported with asynchronous protocol
`CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED` was added in 8.0.21.
 - Error number: 2066; Symbol: `CR_COMPRESSION_WRONGLY_CONFIGURED`;
Message: Connection failed due to wrongly configured compression algorithm
`CR_COMPRESSION_WRONGLY_CONFIGURED` was added in 8.0.18.
 - Error number: 2067; Symbol: `CR_KERBEROS_USER_NOT_FOUND`;
Message: SSO user not found, Please perform SSO authentication using kerberos.
`CR_KERBEROS_USER_NOT_FOUND` was added in 8.0.20.
 - Error number: 2068; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REJECTED`;
Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.
`CR_LOAD_DATA_LOCAL_INFILE_REJECTED` was added in 8.0.21.
 - Error number: 2069; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL`;
Message: Determining the real path for '%s' failed with error (%d): %s
`CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL` was added in 8.0.21.
 - Error number: 2070; Symbol: `CR_DNS_SRV_LOOKUP_FAILED`;
Message: DNS SRV lookup failed with error : %d
`CR_DNS_SRV_LOOKUP_FAILED` was added in 8.0.22.
 - Error number: 2071; Symbol: `CR_MANDATORY_TRACKER_NOT_FOUND`;
Message: Client does not recognise tracker type %d marked as mandatory by server.
`CR_MANDATORY_TRACKER_NOT_FOUND` was added in 8.0.27.
 - Error number: 2072; Symbol: `CR_INVALID_FACTOR_NO`;
Message: Invalid first argument for MYSQL_OPT_USER_PASSWORD option. Valid value should be between 1 and 3 inclusive.

`CR_INVALID_FACTOR_NO` was added in 8.0.27.

- Error number: `2073`; Symbol: `CR_CANT_GET_SESSION_DATA`;

Message: Can't get session data: %s

`CR_CANT_GET_SESSION_DATA` was added in 8.0.29.

- Error number: `2074`; Symbol: `CR_INVALID_CLIENT_CHARSET`;

Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. utf8mb4, latin1 etc.

`CR_INVALID_CLIENT_CHARSET` was added in 8.0.33.

Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: [1](#); Symbol: `EE_CANTCREATEFILE`;
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: [2](#); Symbol: `EE_READ`;
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: [3](#); Symbol: `EE_WRITE`;
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: [4](#); Symbol: `EE_BADCLOSE`;
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: [5](#); Symbol: `EE_OUTOFMEMORY`;
Message: Out of memory (Needed %u bytes)
- Error number: [6](#); Symbol: `EE_DELETE`;
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: [7](#); Symbol: `EE_LINK`;
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: [9](#); Symbol: `EE_EOFERR`;
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: [10](#); Symbol: `EE_CANTLOCK`;
Message: Can't lock file (OS errno %d - %s)
- Error number: [11](#); Symbol: `EE_CANTUNLOCK`;
Message: Can't unlock file (OS errno %d - %s)
- Error number: [12](#); Symbol: `EE_DIR`;
Message: Can't read dir of '%s' (OS errno %d - %s)
- Error number: [13](#); Symbol: `EE_STAT`;

-
- Message: Can't get stat of '%s' (OS errno %d - %s)
 - Error number: 14; Symbol: `EE_CANT_CHSIZE`;
Message: Can't change size of file (OS errno %d - %s)
 - Error number: 15; Symbol: `EE_CANT_OPEN_STREAM`;
Message: Can't open stream from handle (OS errno %d - %s)
 - Error number: 16; Symbol: `EE_GETWD`;
Message: Can't get working directory (OS errno %d - %s)
 - Error number: 17; Symbol: `EE_SETWD`;
Message: Can't change dir to '%s' (OS errno %d - %s)
 - Error number: 18; Symbol: `EE_LINK_WARNING`;
Message: Warning: '%s' had %d links
 - Error number: 19; Symbol: `EE_OPEN_WARNING`;
Message: Warning: %d files and %d streams are left open
 - Error number: 20; Symbol: `EE_DISK_FULL`;
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
 - Error number: 21; Symbol: `EE_CANT_MKDIR`;
Message: Can't create directory '%s' (OS errno %d - %s)
 - Error number: 22; Symbol: `EE_UNKNOWN_CHARSET`;
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
 - Error number: 23; Symbol: `EE_OUT_OF_FILERESOURCES`;
Message: Out of resources when opening file '%s' (OS errno %d - %s)
 - Error number: 24; Symbol: `EE_CANT_READLINK`;
Message: Can't read value for symlink '%s' (Error %d - %s)
 - Error number: 25; Symbol: `EE_CANT_SYMLINK`;
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
 - Error number: 26; Symbol: `EE_REALPATH`;
Message: Error on realpath() on '%s' (Error %d - %s)
 - Error number: 27; Symbol: `EE_SYNC`;
Message: Can't sync file '%s' to disk (OS errno %d - %s)
 - Error number: 28; Symbol: `EE_UNKNOWN_COLLATION`;
Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file
 - Error number: 29; Symbol: `EE_FILENOTFOUND`;

Message: File '%s' not found (OS errno %d - %s)

- Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;

Message: File '%s' (fileno: %d) was not closed

- Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;

Message: Cannot change ownership of the file '%s' (OS errno %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Cannot change permissions of the file '%s' (OS errno %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Cannot seek in file '%s' (OS errno %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

- Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.

`EE_DISK_FULL_WITH_RETRY_MSG` was added in 8.0.13.

- Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;

Message: Failed to create timer (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER` was added in 8.0.13.

- Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;

Message: Failed to delete timer (OS errno %d).

`EE_FAILED_TO_DELETE_TIMER` was added in 8.0.13.

- Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;

Message: Failed to create timer queue (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_QUEUE` was added in 8.0.13.

- Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;

Message: Failed to start timer notify thread.

`EE_FAILED_TO_START_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 40; Symbol: `EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;

Message: Failed to create event to interrupt timer notifier thread (OS errno %d).

`EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT` was added in 8.0.13.

- Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;

Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.

`EE_EXITING_TIMER_NOTIFY_THREAD` was added in 8.0.13.

- Error number: 42; Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.

`EE_WIN_LIBRARY_LOAD_FAILED` was added in 8.0.13.

- Error number: 43; Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;
Message: %s.

`EE_WIN_RUN_TIME_ERROR_CHECK` was added in 8.0.13.

- Error number: 44; Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;
Message: Failed to determine large page size.

`EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE` was added in 8.0.13.

- Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;
Message: Error in my_thread_global_end(): %d thread(s) did not exit.

`EE_FAILED_TO_KILL_ALL_THREADS` was added in 8.0.13.

- Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;
Message: Failed to create IO completion port (OS errno %d).

`EE_FAILED_TO_CREATE_IO_COMPLETION_PORT` was added in 8.0.13.

- Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;
Message: Failed to open required defaults file: %s

`EE_FAILED_TO_OPEN_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;
Message: Fatal error in defaults handling. Program aborted!

`EE_FAILED_TO_HANDLE_DEFAULTS_FILE` was added in 8.0.13.

- Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;
Message: Wrong '!%s' directive in config file %s at line %d.

`EE_WRONG_DIRECTIVE_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.

`EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION` was added in 8.0.13.

- Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;
Message: Wrong group definition in config file %s at line %d.

`EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;

Message: Found option without preceding group in config file %s at line %d.

`EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE` was added in 8.0.13.

- Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;

Message: %s should be readable/writable only by current user.

`EE_CONFIG_FILE_PERMISSION_ERROR` was added in 8.0.13.

- Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;

Message: World-writable config file '%s' is ignored.

`EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE` was added in 8.0.13.

- Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;

Message: %s: Option '%s' was used, but is disabled.

`EE_USING_DISABLED_OPTION` was added in 8.0.13.

- Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;

Message: %s: Option '-%c' was used, but is disabled.

`EE_USING_DISABLED_SHORT_OPTION` was added in 8.0.13.

- Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;

Message: Using a password on the command line interface can be insecure.

`EE_USING_PASSWORD_ON_CLI_IS_INSECURE` was added in 8.0.13.

- Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;

Message: Unknown suffix '%c' used for variable '%s' (value '%s').

`EE_UNKNOWN_SUFFIX_FOR_VARIABLE` was added in 8.0.13.

- Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;

Message: SSL error: %s from '%s'.

`EE_SSL_ERROR_FROM_FILE` was added in 8.0.13.

- Error number: 60; Symbol: `EE_SSL_ERROR`;

Message: SSL error: %s.

`EE_SSL_ERROR` was added in 8.0.13.

- Error number: 61; Symbol: `EE_NET_SEND_ERROR_IN_BOOTSTRAP`;

Message: %d %s.

`EE_NET_SEND_ERROR_IN_BOOTSTRAP` was added in 8.0.13.

- Error number: 62; Symbol: `EE_PACKETS_OUT_OF_ORDER`;

Message: Packets out of order (found %u, expected %u).

`EE_PACKETS_OUT_OF_ORDER` was added in 8.0.13.

-
- Error number: 63; Symbol: `EE_UNKNOWN_PROTOCOL_OPTION`;
Message: Unknown option to protocol: %s.
`EE_UNKNOWN_PROTOCOL_OPTION` was added in 8.0.13.
 - Error number: 64; Symbol: `EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY`;
Message: Failed to locate server public key '%s'.
`EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY` was added in 8.0.13.
 - Error number: 65; Symbol: `EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT`;
Message: Public key is not in Privacy Enhanced Mail format: '%s'.
`EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT` was added in 8.0.13.
 - Error number: 66; Symbol: `EE_DEBUG_INFO`;
Message: %s.
`EE_DEBUG_INFO` was added in 8.0.13.
 - Error number: 67; Symbol: `EE_UNKNOWN_VARIABLE`;
Message: unknown variable '%s'.
`EE_UNKNOWN_VARIABLE` was added in 8.0.13.
 - Error number: 68; Symbol: `EE_UNKNOWN_OPTION`;
Message: unknown option '--%s'.
`EE_UNKNOWN_OPTION` was added in 8.0.13.
 - Error number: 69; Symbol: `EE_UNKNOWN_SHORT_OPTION`;
Message: %s: unknown option '-%c'.
`EE_UNKNOWN_SHORT_OPTION` was added in 8.0.13.
 - Error number: 70; Symbol: `EE_OPTION_WITHOUT_ARGUMENT`;
Message: %s: option '--%s' cannot take an argument.
`EE_OPTION_WITHOUT_ARGUMENT` was added in 8.0.13.
 - Error number: 71; Symbol: `EE_OPTION_REQUIRES_ARGUMENT`;
Message: %s: option '--%s' requires an argument.
`EE_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.
 - Error number: 72; Symbol: `EE_SHORT_OPTION_REQUIRES_ARGUMENT`;
Message: %s: option '-%c' requires an argument.
`EE_SHORT_OPTION_REQUIRES_ARGUMENT` was added in 8.0.13.
 - Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;
Message: %s: ignoring option '--%s' due to invalid value '%s'.
`EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE` was added in 8.0.13.

-
- Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;
Message: %s: Empty value for '%s' specified.
`EE_OPTION_WITH_EMPTY_VALUE` was added in 8.0.13.
 - Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;
Message: %s: Maximum value of '%s' cannot be set.
`EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION` was added in 8.0.13.
 - Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;
Message: option '%s': boolean value '%s' was not recognized. Set to OFF.
`EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;
Message: %s: Error while setting value '%s' to '%s'.
`EE_FAILED_TO_SET_OPTION_VALUE` was added in 8.0.13.
 - Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;
Message: Incorrect integer value: '%s'.
`EE_INCORRECT_INT_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;
Message: Incorrect unsigned integer value: '%s'.
`EE_INCORRECT_UINT_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;
Message: option '%s': signed value %s adjusted to %s.
`EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;
Message: option '%s': unsigned value %s adjusted to %s.
`EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;
Message: option '%s': value %s adjusted to %s.
`EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;
Message: option '%s': value %g adjusted to %g.
`EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION` was added in 8.0.13.
 - Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;
Message: Invalid decimal value for option '%s'.
`EE_INVALID_DECIMAL_VALUE_FOR_OPTION` was added in 8.0.13.

-
- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;
Message: %s.
`EE_COLLATION_PARSER_ERROR` was added in 8.0.13.
 - Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a primary ignorable character %s.
`EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR` was added in 8.0.13.
 - Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a tertiary ignorable character %s.
`EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR` was added in 8.0.13.
 - Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;
Message: Shift character out of range: %s.
`EE_SHIFT_CHAR_OUT_OF_RANGE` was added in 8.0.13.
 - Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;
Message: Reset character out of range: %s.
`EE_RESET_CHAR_OUT_OF_RANGE` was added in 8.0.13.
 - Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;
Message: Unknown LDML tag: '%.*s'.
`EE_UNKNOWN_LDML_TAG` was added in 8.0.13.
 - Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a secondary ignorable character %s.
`EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR` was added in 8.0.16.
 - Error number: 92; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;
Message: Stopped processing the '%s' directive in file %s at line %d.
`EE_FAILED_PROCESSING_DIRECTIVE` was added in 8.0.27.
 - Error number: 93; Symbol: `EE_PTHREAD_KILL_FAILED`;
Message: pthread_kill(thread_id:%lu, signal:%s) returned '%s'.
`EE_PTHREAD_KILL_FAILED` was added in 8.0.31.

Index

C

CR_ALREADY_CONNECTED error code, 615
CR_AUTH_PLUGIN_CANNOT_LOAD error code, 615
CR_AUTH_PLUGIN_ERR error code, 615
CR_CANT_GET_SESSION_DATA error code, 617
CR_CANT_READ_CHARSET error code, 612
CR_COMMANDS_OUT_OF_SYNC error code, 612
CR_COMPRESSION_NOT_SUPPORTED error code, 616
CR_COMPRESSION_WRONGLY_CONFIGURED error code, 616
CR_CONNECTION_ERROR error code, 611
CR_CONN_HOST_ERROR error code, 611
CR_CONN_UNKNOW_PROTOCOL error code, 614
CR_DATA_TRUNCATED error code, 613
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED error code, 616
CR_DNS_SRV_LOOKUP_FAILED error code, 616
CR_DUPLICATE_CONNECTION_ATTR error code, 615
CR_EMBEDDED_CONNECTION error code, 612
CR_FETCH_CANCELED error code, 615
CR_FILE_NAME_TOO_LONG error code, 616
CR_INSECURE_API_ERR error code, 615
CR_INVALID_BUFFER_USE error code, 614
CR_INVALID_CLIENT_CHARSET error code, 617
CR_INVALID_CONN_HANDLE error code, 615
CR_INVALID_FACTOR_NO error code, 617
CR_INVALID_PARAMETER_NO error code, 614
CR_IPSOCK_ERROR error code, 611
CR_KERBEROS_USER_NOT_FOUND error code, 616
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL error code, 616
CR_LOAD_DATA_LOCAL_INFILE_REJECTED error code, 616
CR_LOCALHOST_CONNECTION error code, 611
CR_MALFORMED_PACKET error code, 613
CR_MANDATORY_TRACKER_NOT_FOUND error code, 616
CR_NAMEDPIPEOPEN_ERROR error code, 612
CR_NAMEDPIPESETSTATE_ERROR error code, 612
CR_NAMEDPIPEWAIT_ERROR error code, 612
CR_NAMEDPIPE_CONNECTION error code, 612
CR_NET_PACKET_TOO_LARGE error code, 612
CR_NEW_STMT_METADATA error code, 615
CR_NOT_IMPLEMENTED error code, 615
CR_NO_DATA error code, 615
CR_NO_PARAMETERS_EXISTS error code, 613
CR_NO_PREPARE_STMT error code, 613
CR_NO_RESULT_SET error code, 615
CR_NO_STMT_METADATA error code, 615
CR_NULL_POINTER error code, 613
CR_OUT_OF_MEMORY error code, 611
CR_PARAMS_NOT_BOUND error code, 613
CR_PROBE_MASTER_CONNECT error code, 613
CR_PROBE_REPLICA_CONNECT error code, 613
CR_PROBE_REPLICA_HOSTS error code, 613
CR_PROBE_REPLICA_STATUS error code, 612
CR_PROBE_SLAVE_CONNECT error code, 613
CR_PROBE_SLAVE_HOSTS error code, 613
CR_PROBE_SLAVE_STATUS error code, 612
CR_PROBE_SOURCE_CONNECT error code, 613
CR_SERVER_GONE_ERROR error code, 611
CR_SERVER_HANDSHAKE_ERR error code, 612
CR_SERVER_LOST error code, 612
CR_SERVER_LOST_EXTENDED error code, 615
CR_SHARED_MEMORY_CONNECTION error code, 614
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR error code, 614
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR error code, 614
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR error code, 614
CR_SHARED_MEMORY_CONNECT_MAP_ERROR error code, 614
CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR error code, 614
CR_SHARED_MEMORY_CONNECT_SET_ERROR error code, 614
CR_SHARED_MEMORY_EVENT_ERROR error code, 614
CR_SHARED_MEMORY_FILE_MAP_ERROR error code, 614
CR_SHARED_MEMORY_MAP_ERROR error code, 614
CR_SOCKET_CREATE_ERROR error code, 611
CR_SSL_CONNECTION_ERROR error code, 613
CR_SSL_FIPS_MODE_ERR error code, 616
CR_STMT_CLOSED error code, 615
CR_TCP_CONNECTION error code, 612
CR_UNKNOWN_ERROR error code, 611
CR_UNKNOWN_HOST error code, 611
CR_UNSUPPORTED_PARAM_TYPE error code, 614
CR_UNUSED_1 error code, 615
CR_VERSION_ERROR error code, 611
CR_WRONG_HOST_INFO error code, 611
CR_WRONG_LICENSE error code, 613

E

EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION error code, 625
EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION error code, 625
EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION error code, 625
EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION error code, 625
EE_BADCLOSE error code, 619
EE_CANTCREATEFILE error code, 619
EE_CANTLOCK error code, 619
EE_CANTUNLOCK error code, 619

EE_CANT_CHSIZE error code, 620	EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION error code, 625
EE_CANT_MKDIR error code, 620	EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE error code, 622
EE_CANT_OPEN_STREAM error code, 620	EE_INCORRECT_INT_VALUE_FOR_OPTION error code, 625
EE_CANT_READLINK error code, 620	EE_INCORRECT_UINT_VALUE_FOR_OPTION error code, 625
EE_CANT_SEEK error code, 621	EE_INVALID_DECIMAL_VALUE_FOR_OPTION error code, 625
EE_CANT_SYMLINK error code, 620	EE_LINK error code, 619
EE_CAPACITY_EXCEEDED error code, 621	EE_LINK_WARNING error code, 620
EE_CHANGE_OWNERSHIP error code, 621	EE_NET_SEND_ERROR_IN_BOOTSTRAP error code, 623
EE_CHANGE_PERMISSIONS error code, 621	EE_OPEN_WARNING error code, 620
EE_COLLATION_PARSER_ERROR error code, 626	EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE error code, 624
EE_CONFIG_FILE_PERMISSION_ERROR error code, 623	EE_OPTION_REQUIRES_ARGUMENT error code, 624
EE_DEBUG_INFO error code, 624	EE_OPTION_WITHOUT_ARGUMENT error code, 624
EE_DELETE error code, 619	EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE error code, 623
EE_DIR error code, 619	EE_OPTION_WITH_EMPTY_VALUE error code, 625
EE_DISK_FULL error code, 620	EE_OUTOFMEMORY error code, 619
EE_DISK_FULL_WITH_RETRY_MSG error code, 621	EE_OUT_OF_FILERESOURCES error code, 620
EE_EOFERR error code, 619	EE_PACKETS_OUT_OF_ORDER error code, 623
EE_EXITING_TIMER_NOTIFY_THREAD error code, 622	EE_PTHREAD_KILL_FAILED error code, 626
EE_FAILED_PROCESSING_DIRECTIVE error code, 626	EE_INTERRUPTED_NOT_IN_PEM_FORMAT error code, 624
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION error code, 625	EE_READ error code, 619
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT error code, 622	EE_REALPATH error code, 620
EE_FAILED_TO_CREATE_TIMER error code, 621	EE_RESET_CHAR_OUT_OF_RANGE error code, 626
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD error code, 621	EE_SETWD error code, 620
EE_FAILED_TO_CREATE_TIMER_QUEUE error code, 621	EE_SHIFT_CHAR_OUT_OF_RANGE error code, 626
EE_FAILED_TO_DELETE_TIMER error code, 621	EE_SHORT_OPTION_REQUIRES_ARGUMENT error code, 624
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE error code, 622	EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION error code, 622
EE_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 622	EE_SSL_ERROR error code, 623
EE_FAILED_TO_KILL_ALL_THREADS error code, 622	EE_SSL_ERROR_FROM_FILE error code, 623
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY error code, 624	EE_STAT error code, 620
EE_FAILED_TO_OPEN_DEFAULTS_FILE error code, 622	EE_SYNC error code, 620
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNORE error code, 626	EE_UNKNOWN_CHARSET error code, 620
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNORE error code, 626	EE_UNKNOWN_COLLATION error code, 620
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNORE error code, 626	EE_UNKNOWN_LDML_TAG error code, 626
EE_FAILED_TO_SET_OPTION_VALUE error code, 625	EE_UNKNOWN_OPTION error code, 624
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD error code, 621	EE_UNKNOWN_PROTOCOL_OPTION error code, 624
EE_FILENOTFOUND error code, 621	EE_UNKNOWN_SHORT_OPTION error code, 624
EE_FILE_NOT_CLOSED error code, 621	EE_UNKNOWN_SUFFIX_FOR_VARIABLE error code, 623
EE_GETWD error code, 620	EE_UNKNOWN_VARIABLE error code, 624
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE error code, 623	EE_USING_DISABLED_OPTION error code, 623
	EE_USING_DISABLED_SHORT_OPTION error code, 623
	EE_USING_PASSWORD_ON_CLI_IS_INSECURE error code, 623
	EE_WIN_LIBRARY_LOAD_FAILED error code, 622

EE_WIN_RUN_TIME_ERROR_CHECK error code, 622	CR_PROBE_REPLICA_HOSTS, 613
EE_WRITE error code, 619	CR_PROBE_REPLICA_STATUS, 612
EE_WRONG_DIRECTIVE_IN_CONFIG_FILE error code, 622	CR_PROBE_SLAVE_CONNECT, 613
error code	CR_PROBE_SLAVE_HOSTS, 613
CR_ALREADY_CONNECTED, 615	CR_PROBE_SLAVE_STATUS, 612
CR_AUTH_PLUGIN_CANNOT_LOAD, 615	CR_PROBE_SOURCE_CONNECT, 613
CR_AUTH_PLUGIN_ERR, 615	CR_SERVER_GONE_ERROR, 611
CR_CANT_GET_SESSION_DATA, 617	CR_SERVER_HANDSHAKE_ERR, 612
CR_CANT_READ_CHARSET, 612	CR_SERVER_LOST, 612
CR_COMMANDS_OUT_OF_SYNC, 612	CR_SERVER_LOST_EXTENDED, 615
CR_COMPRESSION_NOT_SUPPORTED, 616	CR_SHARED_MEMORY_CONNECTION, 614
CR_COMPRESSION_WRONGLY_CONFIGURED, 616	CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 614
CR_CONNECTION_ERROR, 611	CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR, 614
CR_CONN_HOST_ERROR, 611	CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR, 614
CR_CONN_UNKNOW_PROTOCOL, 614	CR_SHARED_MEMORY_CONNECT_MAP_ERROR, 614
CR_DATA_TRUNCATED, 613	CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR, 614
CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED, 616	CR_SHARED_MEMORY_CONNECT_SET_ERROR, 614
CR_DNS_SRV_LOOKUP_FAILED, 616	CR_SHARED_MEMORY_EVENT_ERROR, 614
CR_DUPLICATE_CONNECTION_ATTR, 615	CR_SHARED_MEMORY_FILE_MAP_ERROR, 614
CR_EMBEDDED_CONNECTION, 612	CR_SHARED_MEMORY_MAP_ERROR, 614
CR_FETCH_CANCELED, 615	CR_SOCKET_CREATE_ERROR, 611
CR_FILE_NAME_TOO_LONG, 616	CR_SSL_CONNECTION_ERROR, 613
CR_INSECURE_API_ERR, 615	CR_SSL_FIPS_MODE_ERR, 616
CR_INVALID_BUFFER_USE, 614	CR_STMT_CLOSED, 615
CR_INVALID_CLIENT_CHARSET, 617	CR_TCP_CONNECTION, 612
CR_INVALID_CONN_HANDLE, 615	CR_UNKNOWN_ERROR, 611
CR_INVALID_FACTOR_NO, 617	CR_UNKNOWN_HOST, 611
CR_INVALID_PARAMETER_NO, 614	CR_UNSUPPORTED_PARAM_TYPE, 614
CR_IPSOCK_ERROR, 611	CR_UNUSED_1, 615
CR_KERBEROS_USER_NOT_FOUND, 616	CR_VERSION_ERROR, 611
CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL, 616	CR_WRONG_HOST_INFO, 611
CR_LOAD_DATA_LOCAL_INFILE_REJECTED, 616	CR_WRONG_LICENSE, 613
CR_LOCALHOST_CONNECTION, 611	EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION, 625
CR_MALFORMED_PACKET, 613	EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION, 625
CR_MANDATORY_TRACKER_NOT_FOUND, 616	EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION, 625
CR_NAMEDPIPEOPEN_ERROR, 612	EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION, 625
CR_NAMEDPIPESETSTATE_ERROR, 612	EE_BADCLOSE, 619
CR_NAMEDPIPEWAIT_ERROR, 612	EE_CANTCREATEFILE, 619
CR_NAMEDPIPE_CONNECTION, 612	EE_CANTLOCK, 619
CR_NET_PACKET_TOO_LARGE, 612	EE_CANTUNLOCK, 619
CR_NEW_STMT_METADATA, 615	EE_CANT_CHSIZE, 620
CR_NOT_IMPLEMENTED, 615	EE_CANT_MKDIR, 620
CR_NO_DATA, 615	EE_CANT_OPEN_STREAM, 620
CR_NO_PARAMETERS_EXISTS, 613	EE_CANT_READLINK, 620
CR_NO_PREPARE_STMT, 613	EE_CANT_SEEK, 621
CR_NO_RESULT_SET, 615	EE_CANT_SYMLINK, 620
CR_NO_STMT_METADATA, 615	EE_CAPACITY_EXCEEDED, 621
CR_NULL_POINTER, 613	EE_CHANGE_OWNERSHIP, 621
CR_OUT_OF_MEMORY, 611	
CR_PARAMS_NOT_BOUND, 613	
CR_PROBE_MASTER_CONNECT, 613	
CR_PROBE_REPLICA_CONNECT, 613	

EE_CHANGE_PERMISSIONS, 621	EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE, 623
EE_COLLATION_PARSER_ERROR, 626	EE_OPTION_WITH_EMPTY_VALUE, 625
EE_CONFIG_FILE_PERMISSION_ERROR, 623	EE_OUTOFMEMORY, 619
EE_DEBUG_INFO, 624	EE_OUT_OF_FILERESOURCES, 620
EE_DELETE, 619	EE_PACKETS_OUT_OF_ORDER, 623
EE_DIR, 619	EE_PTHREAD_KILL_FAILED, 626
EE_DISK_FULL, 620	EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT, 624
EE_DISK_FULL_WITH_RETRY_MSG, 621	EE_READ, 619
EE_EOFERR, 619	EE_REALPATH, 620
EE_EXITING_TIMER_NOTIFY_THREAD, 622	EE_RESET_CHAR_OUT_OF_RANGE, 626
EE_FAILED_PROCESSING_DIRECTIVE, 626	EE_SETWD, 620
EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION, 625	EE_SHIFT_CHAR_OUT_OF_RANGE, 626
EE_FAILED_TO_CREATE_IO_COMPLETION_PORT, 622	EE_SHORT_OPTION_REQUIRES_ARGUMENT, 624
EE_FAILED_TO_CREATE_TIMER, 621	EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION, 622
EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD, 621	EE_INTERRUPT_EVENT, 622
EE_FAILED_TO_CREATE_TIMER_QUEUE, 621	EE_SSL_ERROR, 623
EE_FAILED_TO_DELETE_TIMER, 621	EE_SSL_ERROR_FROM_FILE, 623
EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE, 622	EE_STAT, 620
EE_FAILED_TO_HANDLE_DEFAULTS_FILE, 622	EE_SYNC, 620
EE_FAILED_TO_KILL_ALL_THREADS, 622	EE_UNKNOWN_CHARSET, 620
EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY, 624	EE_UNKNOWN_COLLATION, 620
EE_FAILED_TO_OPEN_DEFAULTS_FILE, 622	EE_UNKNOWN_LDML_TAG, 626
EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR, 626	EE_UNKNOWN_OPTION, 624
EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR, 626	EE_UNKNOWN_PROTOCOL_OPTION, 624
EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR, 626	EE_UNKNOWN_SHORT_OPTION, 624
EE_FAILED_TO_SET_OPTION_VALUE, 625	EE_UNKNOWN_SUFFIX_FOR_VARIABLE, 623
EE_FAILED_TO_START_TIMER_NOTIFY_THREAD, 621	EE_UNKNOWN_VARIABLE, 624
EE_FILENOTFOUND, 621	EE_USING_DISABLED_OPTION, 623
EE_FILE_NOT_CLOSED, 621	EE_USING_DISABLED_SHORT_OPTION, 623
EE_GETWD, 620	EE_USING_PASSWORD_ON_CLI_IS_INSECURE, 623
EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE, 623	EE_WIN_LIBRARY_LOAD_FAILED, 622
EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION, 625	EE_WIN_RUN_TIME_ERROR_CHECK, 622
EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE, 622	EE_WRITE, 619
EE_INCORRECT_INT_VALUE_FOR_OPTION, 625	EE_WRONG_DIRECTIVE_IN_CONFIG_FILE, 622
EE_INCORRECT_UINT_VALUE_FOR_OPTION, 625	ER_ABORTING, 166
EE_INVALID_DECIMAL_VALUE_FOR_OPTION, 625	ER_ABORTING_CONNECTION, 13
EE_LINK, 619	ER_ABORTING_USER_CONNECTION, 265
EE_LINK_WARNING, 620	ER_ACCESS_DENIED_CHANGE_USER_ERROR, 63
EE_NET_SEND_ERROR_IN_BOOTSTRAP, 623	ER_ACCESS_DENIED_ERROR, 6
EE_OPEN_WARNING, 620	ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD, 266
EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE, 624	ER_ACCESS_DENIED_ERROR_WITH_PASSWORD, 266
EE_OPTION_REQUIRES_ARGUMENT, 624	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD, 545
EE_OPTION_WITHOUT_ARGUMENT, 624	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED, 266
	ER_ACCESS_DENIED_NO_PASSWORD_ERROR, 47
	ER_ACCOUNT_HAS_BEEN_LOCKED, 76
	ER_ACCOUNT_WITH_EXPIRED_PASSWORD, 583
	ER_ACL_OPERATION_FAILED, 83

[illegible]

ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT,	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE,
301	539
ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
301	539
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED,	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,
299	82
ER_AUDIT_LOG_FILTER_RESULT_MSG,	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA,
301	505
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY,	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER,
302	505
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED,	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS,
539	300
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER,	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE,
506	300
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIRECTORY,	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED,
299	300
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED,
125	300
ER_AUDIT_LOG_INVALID_FILE_CONTENT,	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE,
534	300
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE,	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTHENTICATION,
606	190
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED,	ER_AUDIT_PLUGIN_HAS_INVALID_DATA,
505	191
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST,	ER_AUDIT_WARNING,
507	263
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY,	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM,
505	188
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR,	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLE,
505	187
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL,	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL,
301	187
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE,	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME,
301	187
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE,	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE,
301	187
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR,	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME,
301	187
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY,	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION,
506	187
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID,	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED,
534	187
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED,	ER_AUTHCACHE_PLUGIN_CONFIG,
506	186
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED,	ER_AUTHCACHE_PLUGIN_MISSING,
299	186
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED,	ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROLE,
535	188
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH,	ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE,
300	188
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED,	ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE,
538	186
ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST,	ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME,
299	554
ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED,	ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION,
507	554
ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE,	ER_AUTHCACHE_ROLE_TABLES_DODGY,
506	186
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT,	ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE,
539	188
	ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING,
	187

ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD, 186	ER_AUTH_KEY_GENERATION_DISABLED, 186
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD, 187	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT, 185
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN, 186	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG, 305
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE, 186	ER_AUTH_RSA_CANT_FIND, 183
ER_AUTHCACHE_USER_TABLE_DODGY, 186	ER_AUTH_RSA_CANT_PARSE, 183
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY, 603	ER_AUTH_RSA_CANT_READ, 183
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY, 578	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION, 185
ER_AUTHENTICATION_OCI_IAM, 578	ER_AUTH_RSA_FILES_NOT_FOUND, 183
ER_AUTHENTICATION_OCI_IMDS, 578	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION, 185
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_TOKEN, 578	ER_AUTH_USING_EXISTING_CERTS, 185
ER_AUTHENTICATION_OCI_INVALID_TOKEN, 603	ER_AUTHENTIC_READ_FAILED, 33
ER_AUTHENTICATION_OCI_NONCE, 578	ER_AUTO_CONVERT, 20
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND, 578	ER_AUTO_INCREMENT_CONFLICT, 62
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS, 578	ER_AUTO_OPTIONS_FAILED, 173
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS, 604	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF, 54
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED, 578	ER_BACK_IN_TIME, 166
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR, 578	ER_BAD_DB_ERROR, 6
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH, 603	ER_BAD_FIELD_ERROR, 7
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED, 603	ER_BAD_INDEX_COLUMN, 22
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPTED, 577	ER_BAD_HOST_ERROR, 5
ER_AUTHENTICATION_PLUGIN_LOG, 577	ER_BAD_LOG_STATEMENT, 39
ER_AUTHENTICATION_PLUGIN_OOM, 577	ER_BAD_NULL_ERROR, 6
ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED, 576	ER_BAD_NULL_ERROR_NOT_IGNORED, 99
ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER, 576	ER_BAD_REPLICA, 16
ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPTED, 577	ER_BAD_REPLICA_AUTO_POSITION, 54
ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED, 577	ER_BAD_REPLICA_UNTIL_COND, 22
ER_AUTHENTICATION_POLICY_MISMATCH, 142	ER_BAD_SLAVE, 16
ER_AUTH_CANT_ACTIVATE_ROLE, 184	ER_BAD_SLAVE_AUTO_POSITION, 54
ER_AUTH_CANT_CREATE_RSA_PAIR, 185	ER_BAD_SLAVE_UNTIL_COND, 22
ER_AUTH_CANT_SET_DEFAULT_PLUGIN, 172	ER_BAD_TABLE_ERROR, 6
ER_AUTH_CANT_WRITE_PRIVKEY, 185	ER_BAD_TIMESTAMP_FORMAT, 149
ER_AUTH_CANT_WRITE_PUBKEY, 185	ER_BASE64_DECODE_ERROR, 39
ER_AUTH_CERTS_SAVED_TO_DATADIR, 185	ER_BASEDIR_SET_TO, 269
ER_AUTH_CERT_GENERATION_DISABLED, 185	ER_BEFORE_DML_VALIDATION_ERROR, 74
ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROWS, 527	ER_BEFORE_DML_VALIDATION_ERROR, 168
ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG, 572	ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD, 607
	ER_BEYOND_SERVER_UPGRADE_THRESHOLD, 607
	ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALLY_FREED, 253
	ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 51
	ER_BINLOG_CACHE_SIZE_TOO_LARGE, 264
	ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 256
	ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASH, 259
	ER_BINLOG_CANT_CLOSE_TMP_INDEX, 256
	ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 256
	ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG, 253

ER_BINLOG_CANT_DELETE_FILE, 256	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REB
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG, 258	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE,
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX, 258	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBU
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 258	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE,
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 255	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE,
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY, 256	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE,
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 257	ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE,
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 259	ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REE
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 254	ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK,
ER_BINLOG_CANT_OPEN_LOG, 253	ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK,
ER_BINLOG_CANT_OPEN_TMP_INDEX, 256	ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME,
ER_BINLOG_CANT_RESIZE_CACHE, 253	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE,
ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 256	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN,
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 259	ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES,
ER_BINLOG_CANT_USE_FOR_LOGGING, 255	ER_BINLOG_FATAL_ERROR, 40
ER_BINLOG_CRASHED_BINLOG_TRIMMED, 259	ER_BINLOG_FILE_BEING_READ_NOT_PURGED,
ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED, 590	ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED,
ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS, 590	ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW,
ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED, 590	ER_BINLOG_FILE_NAME_TOO_LONG, 254
ER_BINLOG_CRASH_RECOVERY_FAILED, 259	ER_BINLOG_FILE_OPEN_FAILED, 270
ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG, 590	ER_BINLOG_IO_ERROR_READING_HEADER,
ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED, 590	ER_BINLOG_LOGGING_IMPOSSIBLE, 40
ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED, 590	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS,
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 30	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES,
ER_BINLOG_END, 167	ER_BINLOG_LOGGING_NOT_POSSIBLE, 284
ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX, 256	ER_BINLOG_LOGICAL_CORRUPTION, 62
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY, 255	ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG,
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY, 254	ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINA
ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA, 254	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP,
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 255	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP,
ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO, 254	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE,
ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED, 270	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRY
ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED, 284	
ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED, 100	
ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE, 255	

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_BINLOGS, 114	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBQUERY, 533
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_FAILURE, 45	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 65
ER_BINLOG_NEEDS_SERVERID, 171	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 49
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_BINLOG_FILE, 243	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 49
ER_BINLOG_PURGE_EMFILE, 40	ER_BINLOG_UNSAFE_INSERT_TWO_KEYS, 50
ER_BINLOG_PURGE_FATAL_ERR, 28	ER_BINLOG_UNSAFE_LIMIT, 45
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_FOUND, 257	ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT, 265
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE, 257	ER_BINLOG_UNSAFE_MIXED_STATEMENT, 47
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTERED_FILE, 257	ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_FAILURE, 45
ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 257	ER_BINLOG_UNSAFE_NOWAIT, 88
ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 257	ER_BINLOG_UNSAFE_REPLACE_SELECT, 49
ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 257	ER_BINLOG_UNSAFE_ROUTINE, 30
ER_BINLOG_PURGE_PROHIBITED, 28	ER_BINLOG_UNSAFE_SKIP_LOCKED, 88
ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 259	ER_BINLOG_UNSAFE_STATEMENT, 40
ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 45	ER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 46
ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 45	ER_BINLOG_UNSAFE_SYSTEM_TABLE, 45
ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 45	ER_BINLOG_UNSAFE_SYSTEM_VARIABLE, 46
ER_BINLOG_ROW_LOGGING_FAILED, 37	ER_BINLOG_UNSAFE_UDF, 45
ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 45	ER_BINLOG_UNSAFE_UPDATE_IGNORE, 49
ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 498	ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT, 50
ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_PARTIAL_IMAGES, 499	ER_BINLOG_UNSAFE_XA, 82
ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX, 51	ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED, 498
ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE, 264	ER_BINLOG_WARNING_SUPPRESSED, 260
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 60	ER_BLOBS_AND_NO_TERMINATED, 8
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 45	ER_BLOB_CANT_HAVE_DEFAULT, 10
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READ, 531	ER_BLOB_FIELD_IN_PART_FUNC_ERROR, 35
ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_EXECUTION, 136	ER_BLOB_IMAGES_WITHOUT_LENGTH, 14
ER_BINLOG_UNSAFE_AND_STMT_ENGINE, 45	ER_BLOB_USED_AS_KEY, 8
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS, 45	ER_BOOST_GEOMETRY_CENTROID_EXCEPTION, 68
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST, 50	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION, 68
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 49	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION, 76
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 49	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION, 68
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 50	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION, 68
	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION, 68
	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION, 69
	ER_BOOTSTRAP_CANT_THREAD, 155
	ER_BUFPOOL_RESIZE_INPROGRESS, 80
	ER_BUILD_ID, 592
	ER_BULK_EXECUTOR_ERROR, 151
	ER_BULK_EXECUTOR_INFO, 596
	ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVERS, 151

ER_BULK_LOADER_COMPONENT_ERROR, 151	ER_CANNOT_ADD_FOREIGN, 18
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_CAUSE, 151	ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 81
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_CAUSE, 596	ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 80
ER_BULK_LOADER_INFO, 596	ER_CANNOT ALTER SRID DUE TO INDEX, 96
ER_BULK_LOAD_DATA_FAILED, 151	ER_CANNOT_CHANGE_TO_ROOT_DIR, 269
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED, 152	ER_CANNOT_CONVERT_STRING, 119
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED, 597	ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 80
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE, 153	ER_CANNOT_DISCARD_TEMPORARY_TABLE, 65
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE, 598	ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX, 88
ER_BULK_PARSER_MISSING_ENCLOSED_BY, 152	ER_CANNOT_FIND_KEY_IN_KEYRING, 81
ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG, 597	ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE, 523
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLUMNS_EXCEEDED, 152	ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 121
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLUMNS_EXCEEDED, 597	ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE, 123
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR, 152	ER_CANNOT_LOAD_INTO_PERSISTED_SENSITIVE_VARIABLE, 581
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR, 598	ER_CANNOT_LOAD_INTO_TEMPORARY_TABLE_V2, 50
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY, 152	ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 86
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY, 598	ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID, 20
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE, 152	ER_CANNOT_PERSIST_SENSITIVE_VARIABLES, 115
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE, 598	ER_CANNOT_PERSIST_SENSITIVE_VARIABLES_LOG, 116
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT, 152	ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 115
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT, 597	ER_CANNOT_SET_DATABASE_ENCRYPTION, 116
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR, 152	ER_CANNOT_SET_LOG_ERROR_SERVICES, 269
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR, 598	ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER, 524
ER_BULK_READER_COMMUNICATION_ERROR, 151	ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 116
ER_BULK_READER_COMMUNICATION_ERROR_LOG, 597	ER_CANNOT_SET_TABLE_ENCRYPTION, 116
ER_BULK_READER_INFO, 596	ER_CANNOT_USER, 29
ER_BULK_READER_LIBCURL_ERROR, 151	ER_CANNOT_USER_REFERENCED_AS_DEFINER, 136
ER_BULK_READER_LIBCURL_ERROR_LOG, 597	ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 138
ER_BULK_READER_LIBCURL_INIT_FAILED, 151	ER_CANNOT_USE_ENCRYPTION_CLAUSE, 117
ER_BULK_READER_LIBCURL_INIT_FAILED_LOG, 597	ER_CANT_ACCESS_CAPATH, 173
ER_BULK_READER_SERVER_ERROR, 151	ER_CANT_AGGREGATE_2COLLATIONS, 21
ER_BULK_READER_SERVER_ERROR_LOG, 597	ER_CANT_AGGREGATE_3COLLATIONS, 21
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION, 521	ER_CANT_AGGREGATE_NCOLLATIONS, 21
ER_CALL_ME_LOCALHOST, 167	ER_CANT_ALLOC_TABLE_OBJECT, 247
	ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE, 153
	ER_CANT_CHANGE_TX_CHARACTERISTICS, 39
	ER_CANT_CHECK_PID_PATH, 370
	ER_CANT_CREATE_TEMPORARY_TABLE, 172
	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPURGE, 137

ER_CANT_CREATE_ADMIN_THREAD, 520	ER_CANT_LOCK_TABLE, 247
ER_CANT_CREATE_CACHE_FOR_DB_OPT, 248	ER_CANT_LOCK_TABLESPACE, 248
ER_CANT_CREATE_DB, 3	ER_CANT_MODIFY_SRID_0, 103
ER_CANT_CREATE_FILE, 3	ER_CANT_MODIFY_SRS_USED_BY_COLUMN, 104
ER_CANT_CREATE_GEOMETRY_OBJECT, 30	ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES, 190
ER_CANT_CREATE_HANDLER_FILE, 35	ER_CANT_OPEN_CA, 173
ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 247	ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE, 250
ER_CANT_CREATE_HANDLE_MGR_THREAD, 158	ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET, 248
ER_CANT_CREATE_INTERRUPT_THREAD, 165	ER_CANT_OPEN_DIR, 250
ER_CANT_CREATE_NAMED_PIPES_THREAD, 165	ER_CANT_OPEN_ERROR_LOG, 173
ER_CANT_CREATE_PID_FILE, 164	ER_CANT_OPEN_FILE, 4
ER_CANT_CREATE_SCHEDULER_THREAD, 159	ER_CANT_OPEN_FRM_FILE, 190
ER_CANT_CREATE_SHM_THREAD, 165	ER_CANT_OPEN_LIBRARY, 11
ER_CANT_CREATE_SHUTDOWN_THREAD, 164	ER_CANT_OPEN_TABLE_MYSQL_PROC, 250
ER_CANT_CREATE_TABLE, 3	ER_CANT_PARSE_STORED_ROUTINE_BODY, 249
ER_CANT_CREATE_TABLE_SHARE_FROM_FRM, 247	ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED, 542
ER_CANT_CREATE_TCPIP_THREAD, 165	ER_CANT_READ_DIR, 4
ER_CANT_CREATE_TEST_FILE, 163	ER_CANT_READ_ERRMSG, 169
ER_CANT_CREATE_THREAD, 12	ER_CANT_READ_FRM_FILE, 190
ER_CANT_CREATE_USER_WITH_GRANT, 30	ER_CANT_READ_TABLE_MYSQL_PROC, 250
ER_CANT_CREATE_UUID, 162	ER_CANT_REMOVE_ALL_FIELDS, 9
ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 206	ER_CANT_REMOVE_PID_FILE, 164
ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_IS_ENABLED, 54	ER_CANT_RENAME_LOG_TABLE, 39
ER_CANT_DO_THIS_DURING_AN_TRANSACTION, 15	ER_CANT_REOPEN_TABLE, 12
ER_CANT_DROP_FIELD_OR_KEY, 9	ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POS, 505
ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONLINE_REPLICATION, 75	ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_OFF, 505
ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_NEXT, 146	ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF, 505
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION, 56	ER_CANT_RESET_MASTER, 81
ER_CANT_FIND_DL_ENTRY, 11	ER_CANT_RESET_SOURCE, 81
ER_CANT_FIND_SYSTEM_REC, 4	ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY, 154
ER_CANT_FIND_UDF, 11	ER_CANT_SAVE_GTIDS, 172
ER_CANT_GET_STAT, 4	ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL, 137
ER_CANT_HASH_DO_AND_IGNORE_RULES, 172	ER_CANT_SET_DATADIR, 172
ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT, 248	ER_CANT_SET_DATA_DIR, 518
ER_CANT_INCREASE_MAX_OPEN_FILES, 168	ER_CANT_SET_ERROR_LOG_SERVICE, 102
ER_CANT_INITIALIZE_BUILTIN_PLUGINS, 171	ER_CANT_SET_ERROR_SUPPRESSION_LIST, 106
ER_CANT_INITIALIZE_DYNAMIC_PLUGINS, 171	ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_CONFIG, 510
ER_CANT_INITIALIZE_EARLY_PLUGINS, 171	ER_CANT_SET_GTID_MODE, 75
ER_CANT_INITIALIZE_GTID, 171	ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_DISABLED, 55
ER_CANT_INITIALIZE_UDF, 11	ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_DISABLED, 55
ER_CANT_INIT_DBS, 169	ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_DISABLED, 55
ER_CANT_INIT_SCHEDULER_THREAD, 159	
ER_CANT_INIT_TC_LOG, 159	
ER_CANT_INIT_TIMER, 173	
ER_CANT_JOIN_SHUTDOWN_THREAD, 172	
ER_CANT_LOCK, 4	
ER_CANT_LOCK_LOG_TABLE, 38	

[illegible]

ER_CLIENT_INTERACTION_TIMEOUT, 139	ER_COLUMN_CHANGE_SIZE, 122
ER_CLIENT_KEYRING_UDF_KEY_INVALID, 127	ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_TABLES, 115
ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 127	ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 57
ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID, 127	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 38
ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG, 127	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 65
ER_CLIENT_LOCAL_FILES_DISABLED, 129	ER_COMPONENTS_BACKEND_FAILED_TO_FETCH_SECURITY_DEFINITIONS, 149
ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS, 126	ER_COMMAND_SERVICE_BACKEND_FAILED, 149
ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT, 127	ER_COMMENT_CONTAINS_INVALID_STRING, 146
ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 127	ER_COMPONENT_NOT_ALLOWED_IN_SF_OR_TRG, 30
ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_ROLE, 127	ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION, 85
ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT, 129	ER_COMPONENTS_CANT_LOAD, 85
ER_CLONE_CHARSET, 120	ER_COMPONENTS_CANT_RELEASE_SERVICE, 85
ER_CLONE_CLIENT_TRACE, 518	ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 85
ER_CLONE_CONFIG, 120	ER_COMPONENTS_CANT_UNLOAD, 86
ER_CLONE_CREATE_HANDLER_FAIL_TRACE, 280	ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 284
ER_CLONE_DDL_IN_PROGRESS, 95	ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP, 161
ER_CLONE_DISALLOWED, 121	ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINITIALIZE, 565
ER_CLONE_DISK_SPACE, 121	ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT, 565
ER_CLONE_DONOR, 120	ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, 161
ER_CLONE_DONOR_TRACE, 517	ER_COMPONENTS_LOAD_CANT_INITIALIZE, 85
ER_CLONE_DONOR_VERSION, 120	ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPL, 85
ER_CLONE_ENCRYPTION, 121	ER_COMPONENTS_NO_SCHEME, 85
ER_CLONE_HANDLER_EXISTS, 279	ER_COMPONENTS_NO_SCHEME_SERVICE, 85
ER_CLONE_HANDLER_EXIST_TRACE, 279	ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP, 161
ER_CLONE_INFO_CLIENT, 517	ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE, 85
ER_CLONE_INFO_SERVER, 518	ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE_IMPL, 86
ER_CLONE_IN_PROGRESS, 121	ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP, 86
ER_CLONE_LOOPBACK, 121	ER_COMPONENTS_UNLOAD_NOT_LOADED, 85
ER_CLONE_NETWORK_PACKET, 130	ER_COMPONENT_EE_DATA_DECRYPTION_ERROR, 592
ER_CLONE_OS, 120	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR, 592
ER_CLONE_PLATFORM, 120	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE, 591
ER_CLONE_PLUGIN_MATCH, 120	ER_COMPONENT_EE_DATA_SIGN_ERROR, 592
ER_CLONE_PLUGIN_NOT_LOADED, 279	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE, 591
ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 279	
ER_CLONE_PROTOCOL, 120	
ER_CLONE_PROTOCOL_ERROR, 517	
ER_CLONE_PROTOCOL_TRACE, 517	
ER_CLONE_REMOTE_ERROR, 517	
ER_CLONE_SERVER_TRACE, 518	
ER_CLONE_SHUTDOWN_TRACE, 536	
ER_CLONE_SYS_CONFIG, 120	
ER_CLONE_TOO_MANY_CONCURRENT_CLONES, 95	
ER_CMD_NEED_SUPER, 94	
ER_COALESCE_ONLY_ON_HASH_PARTITION, 36	
ER_COALESCE_PARTITION_NO_PARTITION, 36	
ER_COLLATION_CHARSET_MISMATCH, 20	
ER_COLUMNACCESS_DENIED_ERROR, 12	

ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM,	591	ER_CONNECT_TO_MASTER, 18
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENT,	591	ER_CONNECT_TO_SOURCE, 18
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE,	591	ER_CONN_ATTR_TRUNCATED, 183
ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILED,	591	ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED,
ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILED,	591	307
ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILED,	591	ER_CONN_CONTROL_ERROR_MSG, 305
ER_COMPONENT_EE_INSUFFICIENT_LENGTH,	592	ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED,
ER_COMPONENT_EE_OPENSSL_ERROR,	592	307
ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILED,	590	ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY,
ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILED,	590	308
ER_COMPONENT_FILTER_CONFUSED,	306	ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY,
ER_COMPONENT_FILTER_DIAGNOSTICS,	102	308
ER_COMPONENT_FILTER_FLABBERGASTED,	94	ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE,
ER_COMPONENT_FILTER_WRONG_VALUE,	499	307
ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY_FAILURE,	594	ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RE,
ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE,	593	307
ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE,	594	ER_CONN_INIT_CONNECT_IGNORED, 307
ER_COMPONENT_LOCK,	605	ER_CONN_INIT_CONNECT_IGNORED_MFA, 606
ER_COMPONENT_MANIPULATE_ROW_FAILED,	86	ER_CONN_LIMIT, 581
ER_COMPONENT_MASKING_ABI,	605	ER_CONN_PER_THREAD_NO_THREAD, 179
ER_COMPONENT_MASKING_ABI_REASON,	605	ER_CONN_PIP_CANT_CREATE_EVENT, 179
ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE,	605	ER_CONN_PIP_CANT_CREATE_PIPE, 179
ER_COMPONENT_MASKING_OTHER_ERROR,	605	ER_CONN_SHM_CANT_CREATE_CONNECTION,
ER_COMPONENT_MASKING_RANDOM_CREATE,	605	179
ER_COMPONENT_MASKING_RANDOM_CREATE_REASON,	605	ER_CONN_SHM_CANT_CREATE_SERVICE, 179
ER_COMPONENT_SERVICE_CALL,	604	ER_CONN_SHM_LISTENER, 179
ER_COMPONENT_SERVICE_CALL_RESULT,	605	ER_CONN_SOCKET_ACCEPT_FAILED, 183
ER_COMPONENT_TABLE_INCORRECT,	86	ER_CONN_SOCKET_SELECT_FAILED, 183
ER_COMPONENT_UNLOCK,	605	ER_CONN_TCP_ADDRESS, 180
ER_CONCURRENT_PROCEDURE_USAGE,	145	ER_CONN_TCP_BIND_FAIL, 181
ER_CONDITIONAL_DEBUG,	593	ER_CONN_TCP_BIND_RETRY, 181
ER_COND_ITEM_TOO_LONG,	44	ER_CONN_TCP_CANT_RESET_V6ONLY, 181
ER_CONFIG_OPTION_WITHOUT_GROUP,	176	ER_CONN_TCP_CANT_RESOLVE_HOSTNAME,
ER_CONFIRMING_THE_FUTURE,	166	180
ER_CONFLICTING_DECLARATIONS,	24	ER_CONN_TCP_CREATED, 180
ER_CONFLICT_FN_PARSE_ERROR,	42	ER_CONN_TCP_ERROR_WITH_STRERROR, 180
ER_CONNECTION_ABORTED,	499	ER_CONN_TCP_IPV6_AVAILABLE, 180
ER_CONNECTION_HANDLING_OOM,	163	ER_CONN_TCP_IPV6_UNAVAILABLE, 180
ER_CONNECTION_METADATA,	16	ER_CONN_TCP_IP_NOT_LOGGED, 181
ER_CONNECT_TO_FOREIGN_DATA_SOURCE,	31	ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT,
		180
		ER_CONN_TCP_LISTEN_FAIL, 181
		ER_CONN_TCP_NO_SOCKET, 179
		ER_CONN_TCP_RESOLVE_INFO, 181
		ER_CONN_TCP_START_FAIL, 181
		ER_CONN_TPC_BIND_FAIL, 181
		ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET,
		180
		ER_CONN_UNIX_LISTEN_FAILED, 182
		ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE, 183
		ER_CONN_UNIX_LOCK_FILE_CANT_CREATE,
		182
		ER_CONN_UNIX_LOCK_FILE_CANT_DELETE,
		183
		ER_CONN_UNIX_LOCK_FILE_CANT_OPEN, 182
		ER_CONN_UNIX_LOCK_FILE_CANT_READ, 182

ER_CONN_UNIX_LOCK_FILE_CANT_SYNC, 183	ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MAND, 121
ER_CONN_UNIX_LOCK_FILE_CANT_WRITE, 182	ER_DA_CANT_OPEN_ERROR_LOG, 135
ER_CONN_UNIX_LOCK_FILE_EMPTY, 182	ER_DA_CONN_LIMIT, 145
ER_CONN_UNIX_LOCK_FILE_FAIL, 181	ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED, 141
ER_CONN_UNIX_LOCK_FILE_GIVING_UP, 182	ER_DA_ERROR_LOG_MULTIPLE_FILTERS, 135
ER_CONN_UNIX_LOCK_FILE_PIDLESS, 182	ER_DA_ERROR_LOG_TABLE_DISABLED, 135
ER_CONN_UNIX_NO_BIND_NO_START, 182	ER_DA_EXPIRE_LOGS_DAYS_IGNORED, 148
ER_CONN_UNIX_NO_FD, 182	ER_DA_GLOBAL_CONN_LIMIT, 145
ER_CONN_UNIX_PATH_TOO_LONG, 181	ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 132
ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE, 180	ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 132
ER_CONSECUTIVE_REORG_PARTITIONS, 36	ER_DA_GRP_RPL_STARTED_AUTO_REJOIN, 125
ER_CONSTRAINT_NOT_FOUND, 128	ER_DA_INVALID_CONDITION_NUMBER, 53
ER_CONVERT_MULTI_VALUE, 606	ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED, 135
ER_CON_COUNT_ERROR, 5	ER_DA_OOM, 129
ER_CORE_VALUES, 165	ER_DA_PLUGIN_INSTALL_ERROR, 122
ER_CORRUPTED_JSON_DIFF, 97	ER_DA_RPL_GTID_TABLE_CANNOT_OPEN, 122
ER_CORRUPT_HELP_DB, 20	ER_DA_SSL_FIPS_MODE_ERROR, 144
ER_COULD_NOT_APPLY_JSON_DIFF, 97	ER_DA_SSL_LIBRARY_ERROR, 122
ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY, 513	ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET, 129
ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 506	ER_DA_UDF_INVALID_CHARSET, 128
ER_CRASHED_ON_REPAIR, 16	ER_DA_UDF_INVALID_CHARSET_SPECIFIED, 127
ER_CRASHED_ON_USAGE, 16	ER_DA_UDF_INVALID_COLLATION, 128
ER_CREATED_SYSTEM_WITH_VERSION, 277	ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE, 128
ER_CREATE_FILEGROUP_FAILED, 37	ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET, 129
ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SCHEMA, 148	ER_DA_UNKNOWN_ERROR_NUMBER, 122
ER_CREATING_NEW_UUID, 162	ER_DBACCESS_DENIED_ERROR, 6
ER_CREATING_NEW_UUID_FIRST_START, 268	ER_DEBUG_CHECK_SHARES_DROPPED, 212
ER_CREDENTIALLESS_AUTO_USER_BAD, 163	ER_DEBUG_CHECK_SHARES_INFO, 212
ER_CREDENTIALS_CONTRADICT_TO_HISTORY, 95	ER_DEBUG_CHECK_SHARES_OPEN, 212
ER_CTE_MAX_RECURSION_DEPTH, 95	ER_DB_ACCESS_DENIED, 121
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER, 89	ER_DB_CREATE_EXISTS, 4
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION, 89	ER_DB_DROP_EXISTS, 4
ER_CTE_RECURSIVE_NOT_UNION, 149	ER_DB_DROP_RMDIR, 4
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST, 89	ER_DB_DROP_RMDIR2, 92
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE, 89	ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET, 248
ER_CTE_RECURSIVE_REQUIRES_UNION, 89	ER_DDL_IN_PROGRESS, 95
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED, 123	ER_DDL_LOG_ERROR, 39
ER_CURRENT_PASSWORD_NOT_REQUIRED, 123	ER_DDL_MSG_1, 574
ER_CUT_VALUE_GROUP_CONCAT, 21	ER_DD_ABORTING_PARTIAL_UPGRADE, 188
ER_CYCLE_TIMER_IS_NOT_AVAILABLE, 280	ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN, 157
ER_DATABASE_NAME, 43	ER_DD_CANT_CREATE_OBJECT_KEY, 157
ER_DATA_DIRECTORY_UNUSABLE, 513	ER_DD_CANT_CREATE_SP, 248
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE, 536	ER_DD_CANT_FETCH_TABLE_DATA, 248
ER_DATA_OUT_OF_RANGE, 47	ER_DD_CANT_FIX_SE_DATA, 248
ER_DATA_TOO_LONG, 29	ER_DD_CANT_GET_OBJECT_KEY, 157
ER_DATETIME_FUNCTION_OVERFLOW, 32	ER_DD_CANT_RESOLVE_VIEW, 175

642

ER_DEPRECATED_NATIONAL, 104	ER_DUP_LIST_ENTRY, 67
ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 572	ER_DUP_SIGNAL_SET, 43
ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 283	ER_DUP_UNIQUE, 14
ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 283	ER_DUP_UNKNOWN_IN_INDEX, 61
ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 163	ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE, 102
ER_DEPRECATED_TLS_VERSION_SESSION, 569	ER_EMPTY_PRIVILEGE_NAME_IGNORED, 559
ER_DEPRECATED_UTF8_ALIAS, 104	ER_EMPTY_QUERY, 7
ER_DEPRECATE_MSG_NO_REPLACEMENT, 283	ER_ENDING_INIT, 507
ER_DEPRECATE_MSG_WITH_REPLACEMENT, 266	ER_END_INITFILE, 168
ER_DERIVED_MUST_HAVE_ALIAS, 20	ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONG, 75
ER_DES_FILE_WRONG_KEY, 176	ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED, 133
ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 206	ER_ENGINE_CANT_DROP_MISSING_TABLE, 92
ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 206	ER_ENGINE_CANT_DROP_TABLE, 92
ER_DIMENSION_UNSUPPORTED, 71	ER_ENGINE_COST_FAILED_TO_READ, 203
ER_DISABLED_STORAGE_ENGINE, 79	ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_S, 203
ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 158	ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 202
ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECOVER, 134	ER_ENGINE_COST_UNKNOWN_COST_CONSTANT, 202
ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECOVER, 134	ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE, 202
ER_DISALLOWED_OPERATION, 97	ER_ENGINE_OUT_OF_MEMORY, 66
ER_DISCARD_FK_CHECKS_RUNNING, 58	ER_ERRMSG_CANT_FIND_FILE, 189
ER_DISCONNECTING_REMAINING_CLIENTS, 166	ER_ERRMSG_CANT_READ, 189
ER_DISK_FULL_NOWAIT, 99	ER_ERRMSG_LOADING_55_STYLE, 189
ER_DIVISION_BY_ZERO, 27	ER_ERRMSG_MISSING_IN_FILE, 189
ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER, 68	ER_ERRMSG_OOM, 189
ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER, 67	ER_ERRMSG_REPLACEMENTS_FAILED, 262
ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY, 284	ER_ERRMSG_REPLACEMENT_DODGY, 262
ER_DROP_FILEGROUP_FAILED, 37	ER_ERROR_DURING_COMMIT, 15
ER_DROP_INDEX_FK, 38	ER_ERROR_DURING_FLUSH_LOGS, 15
ER_DROP_LAST_PARTITION, 36	ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE, 15
ER_DROP_PARTITION_NON_EXISTENT, 36	ER_ERROR_DURING_OPTIMIZE_TABLE, 247
ER_DROP_PK_COLUMN_TO_DROP_GIPK, 148	ER_ERROR_DURING_ROLLBACK, 15
ER_DUPLICATED_VALUE_IN_TYPE, 23	ER_ERROR_ENABLING_KEYS, 247
ER_DUPLICATE_OPTION_KEY, 87	ER_ERROR_INFO_FROM_DA, 503
ER_DUPLICATE_SYS_VAR, 508	ER_ERROR_IN_TRIGGER_BODY, 49
ER_DUPLICATE_TABLE_LOCK, 88	ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 49
ER_DUP_ARGUMENT, 18	ER_ERROR_LOG_DESTINATION_NOT_A_FILE, 560
ER_DUP_ENTRY, 7	ER_ERROR_ON_MASTER, 65
ER_DUP_ENTRY_AUTOINCREMENT_CASE, 39	ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE, 80
ER_DUP_ENTRY_WITH_KEY_NAME, 40	ER_ERROR_ON_READ, 4
ER_DUP_FD_OPEN_FAILED, 268	ER_ERROR_ON_RENAME, 4
ER_DUP_FIELDNAME, 7	ER_ERROR_ON_SOURCE, 65
ER_DUP_INDEX, 59	ER_ERROR_ON_WRITE, 4
ER_DUP_KEY, 4	ER_ERROR_WHEN_EXECUTING_COMMAND, 18
ER_DUP_KEYNAME, 7	ER_EVENT_ALREADY_EXISTS, 37
	ER_EVENT_CANNOT ALTER IN THE PAST, 40
	ER_EVENT_CANNOT_CREATE IN THE PAST, 40
	ER_EVENT_CANT_FIND_TIMEZONE, 249

ER_EVENT_CANT_GET_CHARSET, 249	ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GRP
ER_EVENT_CANT_GET_COLLATION, 249	272
ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT, 253	ER_FAILED_TO_ALLOCATE_SSL_BIO, 508
ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD, 249	ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER, 273
ER_EVENT_CANT_INIT_QUEUE, 159	ER_FAILED_TO_BINLOG_DROP_EVENT, 278
ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT, 249	ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES, 279
ER_EVENT_DOES_NOT_EXIST, 37	ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE, 195
ER_EVENT_DROPPING, 204	ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM, 195
ER_EVENT_ENDS_BEFORE_STARTS, 38	ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY, 277
ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG, 252	ER_FAILED_TO_CREATE_CLONE_HANDLER, 280
ER_EVENT_ERROR_DURING_COMPILATION, 204	ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD_USER, 195
ER_EVENT_EXECUTION_FAILED, 159	ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE, 275
ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER, 204	ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS, 207
ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT, 204	ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE, 194
ER_EVENT_EXEC_TIME_IN_THE_PAST, 38	ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP, 272
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 37	ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY, 129
ER_EVENT_INVALID_CREATION_CTX, 41	ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST, 129
ER_EVENT_LAST_EXECUTION, 159	ER_FAILED_TO_FIND_COLLATION_NAME, 267
ER_EVENT_MESSAGE_STACK, 159	ER_FAILED_TO_FIND_DL_ENTRY, 264
ER_EVENT_PURGING_QUEUE, 159	ER_FAILED_TO_FIND_LOCALE_NAME, 267
ER_EVENT_RECURSION_FORBIDDEN, 39	ER_FAILED_TO_FIND_MYSQLD_STATUS, 283
ER_EVENT_SAME_NAME, 38	ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE, 264
ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT, 252	ER_FAILED_TO_GET_ABSOLUTE_PATH, 268
ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB, 252	ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 508
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE, 253	ER_FAILED_TO_INIT_SYS_VAR, 508
ER_EVENT_SET_VAR_ERROR, 39	ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_CONTROLLER, 195
ER_EVENT_UNABLE_TO_DROP_EVENT, 253	ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREADS, 195
ER_EXCEEDED_MV_KEYS_NUM, 124	ER_FAILED_TO_LOCK_MEM, 168
ER_EXCEEDED_MV_KEYS_SPACE, 124	ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES, 203
ER_EXCEPTIONS_WRITE_ERROR, 42	ER_FAILED_TO_OPEN_SHARED_LIBRARY, 264
ER_EXCESS_ARGUMENTS, 169	ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA, 272
ER_EXPIRE_LOGS_DAYS_IGNORED, 284	ER_FAILED_TO_READ_FILE, 264
ER_EXPLAIN_NOT_SUPPORTED, 65	ER_FAILED_TO_REMOVE_TEMP_TABLE, 243
ER_FAILED_DEFAULT_ROLES, 85	ER_FAILED_TO_REPAIR_TABLE, 243
ER_FAILED_GET_DD_PROPERTY, 607	ER_FAILED_TO_SET_PERSISTED_OPTIONS, 284
ER_FAILED_READ_FROM_PAR_FILE, 47	ER_FAILED_TO_START_REPLICA_THREAD, 278
ER_FAILED_REVOKE_ROLE, 85	ER_FAILED_TO_START_SLAVE_THREAD, 278
ER_FAILED_ROLE_GRANT, 84	ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE, 275
ER_FAILED_SET_DD_PROPERTY, 607	ER_FAILED_TO_STORE_RESOURCE_GROUP, 275
ER_FAILED_START_MYSQLD_DAEMON, 268	
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP, 273	
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP, 273	
ER_FAILED_TO_ADD_RPL_FILTER, 279	
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP, 272	

ER_FAILED_TO_UPDATE_RESOURCE_GROUP, 272	ER_FK_COLUMN_CANNOT_DROP, 59
ER_FAILED_TO_WRITE_TO_FILE, 265	ER_FK_COLUMN_CANNOT_DROP_CHILD, 59
ER_FAIL_CHROOT, 168	ER_FK_COLUMN_NOT_NULL, 59
ER_FAIL_SETGID, 167	ER_FK_DEPTH_EXCEEDED, 65
ER_FAIL_SETREGID, 167	ER_FK_DUP_NAME, 59
ER_FAIL_SETREUID, 167	ER_FK_FAIL_ADD_SYSTEM, 59
ER_FAIL_SETUID, 167	ER_FK_INCOMPATIBLE_COLUMNS, 111
ER_FEATURE_DISABLED, 23	ER_FK_INCORRECT_OPTION, 59
ER_FEATURE_DISABLED_SEE_DOC, 80	ER_FK_NO_COLUMN_PARENT, 106
ER_FEATURE_NOT_AVAILABLE, 75	ER_FK_NO_INDEX_CHILD, 58
ER_FEATURE_UNSUPPORTED, 98	ER_FK_NO_INDEX_PARENT, 59
ER_FIELD_IN_GROUPING_NOT_GROUP_BY, 92	ER_FORBID_SCHEMA_CHANGE, 32
ER_FIELD_IN_ORDER_NOT_SELECT, 70	ER_FORCE_CLOSE_THREAD, 265
ER_FIELD_NOT_FOUND_PART_ERROR, 34	ER_FORCING_CLOSE, 8
ER_FIELD_SPECIFIED_TWICE, 10	ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST, 31
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD, 44	ER_FOREIGN_DATA_STRING_INVALID, 31
ER_FILEGROUP_OPTION_ONLY_ONCE, 37	ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE, 31
ER_FILESORT_TERMINATED, 267	ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED, 38
ER_FILE_CORRUPT, 64	ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO, 53
ER_FILE_EXISTS_DURING_UPGRADE, 250	ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO, 53
ER_FILE_EXISTS_ERROR, 8	ER_FOREIGN_KEY_ON_PARTITIONED, 36
ER_FILE_HAS_OLD_FORMAT, 266	ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT, 133
ER_FILE_NOT_FOUND, 4	ER_FOREIGN_SERVER_DOESNT_EXIST, 34
ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 541	ER_FOREIGN_SERVER_EXISTS, 34
ER_FILE_TYPE_UNKNOWN, 190	ER_FOUND_MISSING_GTIDS, 370
ER_FILE_USED, 5	ER_FOUND_ROWS_WHILE_REPAIRING, 247
ER_FILSORT_ABORT, 5	ER_FPARSER_BAD_HEADER, 26
ER_FIREWALL_ACCESS_DENIED, 298	ER_FPARSER_EOF_IN_COMMENT, 26
ER_FIREWALL_DEPRECATED_USER_PROFILE, 570	ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER, 26
ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES, 298	ER_FPARSER_ERROR_IN_PARAMETER, 26
ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES, 298	ER_FPARSER_TOO_BIG_FILE, 26
ER_FIREWALL_PFS_TABLE_REGISTER_FAILED, 565	ER_FSEEK_FAIL, 28
ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED, 298	ER_FT_BOOL_SYNTAX_INVALID, 163
ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT, 298	ER_FT_MATCHING_KEY_NOT_FOUND, 15
ER_FIREWALL_RELOADING_CACHE, 299	ER_FULLTEXT_FUNCTIONAL_INDEX, 108
ER_FIREWALL_RESET_FOR_USER, 299	ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING, 53
ER_FIREWALL_SERVICES_NOT_ACQUIRED, 564	ER_FULLTEXT_WITH_ROLLUP, 144
ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE, 298	ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG, 124
ER_FIREWALL_STATUS_FLUSHED, 299	ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED, 108
ER_FIREWALL_SUSPICIOUS_STMT, 298	ER_FUNCTIONAL_INDEX_ON_FIELD, 109
ER_FIREWALL_UDF_REGISTER_FAILED, 565	ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTIONS, 108
ER_FIXING_CLIENT_CHARSET, 168	ER_FUNCTIONAL_INDEX_ON_LOB, 108
ER_FK_CANNOT_CHANGE_ENGINE, 110	ER_FUNCTIONAL_INDEX_PRIMARY_KEY, 108
ER_FK_CANNOT_DROP_PARENT, 105	ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT, 108
ER_FK_CANNOT_OPEN_PARENT, 59	ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED, 113
ER_FK_CANNOT_USE_VIRTUAL_COLUMN, 105	
ER_FK_COLUMN_CANNOT_CHANGE, 59	
ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 59	

ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET, 134	ER_GROUP_REPLICATION_MAX_GROUP_SIZE, 81
ER_FUNCTION_NOT_DEFINED, 11	ER_GROUP_REPLICATION_PASSWORD_LENGTH, 132
ER_FUNC_INEXISTENT_NAME_COLLISION, 42	ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED, 132
ER_FUTURE_DATE, 166	ER_GROUP_REPLICATION_RUNNING, 74
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED, 74	ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT, 74
ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED, 109	ER_GROUP_REPLICATION_USER_EMPTY_MSG, 131
ER_GENERATED_COLUMN_NON_PRIOR, 75	ER_GROUP_REPLICATION_USER_MANDATORY_MSG, 132
ER_GENERATED_COLUMN_REF_AUTO_INC, 75	ER_GRP_DELAYED_VCLE_LOGGING, 531
ER_GENERATED_COLUMN_ROW_VALUE, 109	ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP, 130
ER_GENERATED_COLUMN_VARIABLES, 109	ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MY_ENGINE, 53
ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT, 122	ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR, 328
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE, 105	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED, 339
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE, 105	ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED, 340
ER_GET_ERRMSG, 23	ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED, 339
ER_GET_ERRNO, 5	ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED, 339
ER_GET_ERRNO_FROM_STORAGE_ENGINE, 266	ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR, 328
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER, 65	ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR, 329
ER_GET_TEMPORARY_ERRMSG, 23	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR, 571
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 148	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY, 341
ER_GIPK_COLUMN_EXISTS, 148	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED, 352
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS, 148	ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE_FAILED, 346
ER_GIS_DATA_WRONG_ENDIANESS, 69	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING, 564
ER_GIS_DIFFERENT_SRIDS, 68	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR, 327
ER_GIS_DIFFERENT_SRIDS_AGGREGATION, 139	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE, 357
ER_GIS_INVALID_DATA, 68	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED, 357
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED, 77	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE, 357
ER_GIS_UNKNOWN_ERROR, 68	ER_GRP_RPL_APPLIER_INITIALIZED, 353
ER_GIS_UNKNOWN_EXCEPTION, 68	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE, 353
ER_GIS_UNSUPPORTED_ARGUMENT, 68	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_SESSION_ERROR, 353
ER_GLOBAL_CONN_LIMIT, 580	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED, 327
ER_GLOBAL_VARIABLE, 19	
ER_GLOBSTAT_CHANGE_DURING_QUERY, 125	
ER_GNO_EXHAUSTED, 54	
ER_GRANT_WRONG_HOST_OR_USER, 13	
ER_GROUPING_ON_TIMESTAMP_IN_DST, 125	
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR, 74	
ER_GROUP_REPLICATION_COMMAND_FAILURE, 98	
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR, 74	
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ERROR, 74	
ER_GROUP_REPLICATION_CONFIGURATION, 74	
ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE, 149	

ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT, 351	ON_GRP_VIEW_CHANGE_GRP_MEM_NOT_PROCESSED, 332
ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED, 327	ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACT, 511
ER_GRP_RPL_APPLIER_THD_KILLED, 326	ER_GRP_RPL_CHECK_STATUS_TABLE, 342
ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL, 610	ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 537
ER_GRP_RPL_APPLIER_THD_SETUP_ERROR, 336	ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 537
ER_GRP_RPL_APPLIER_THD_START_ERROR, 336	ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 353
ER_GRP_RPL_APPLIER_THD_STOP_ERROR, 336	ER_GRP_RPL_CONFIGURATION_ACTION_END, 512
ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT, 511	ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 511
ER_GRP_RPL_AUTO_INC_OFFSET_RESET, 338	ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR, 512
ER_GRP_RPL_AUTO_INC_OFFSET_SET, 338	ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERM, 511
ER_GRP_RPL_AUTO_INC_RESET, 338	ER_GRP_RPL_CONFIGURATION_ACTION_START, 511
ER_GRP_RPL_AUTO_INC_SET, 338	ER_GRP_RPL_CONFIG_RECOVERY, 342
ER_GRP_RPL_BINLOG_CHECKSUM_SET, 344	ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 511
ER_GRP_RPL_BINLOG_DISABLED, 353	ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST, 354
ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP, 335	ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 540
ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED, 346	ER_GRP_RPL_CONTACT_WITH_SRV_FAILED, 340
ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG, 360	ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 340
ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED, 327	ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 520
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR, 344	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 330
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE, 345	ER_GRP_RPL_CREATE_SESSION_UNABLE, 341
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING, 344	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 334
ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING, 344	ER_GRP_RPL_DEBUG_OPTIONS, 359
ER_GRP_RPL_CANT_GENERATE_GTID, 329	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FR, 529
ER_GRP_RPL_CANT_KILL_THREAD, 537	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 333
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED, 330	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTE, 331
ER_GRP_RPL_CANT_READ_GTID, 330	ER_GRP_RPL_DONOR_CONN_TERMINATION, 342
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM, 330	ER_GRP_RPL_DONOR_SERVER_CONN, 342
ER_GRP_RPL_CERTIFICATE_SIZE_ERROR, 326	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 328
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE, 329	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_IN, 572
ER_GRP_RPL_CERTIFICATION_REC_PROCESS, 347	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 333
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR, 331	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SE, 328
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATED_FAILED, 609	
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED, 609	
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED, 610	

ER_GRP_RPL_ERROR_FETCHING_GTID_SET,	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER,
328	357
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO,	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE,
326	353
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION,	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE,
510	349
ER_GRP_RPL_ERROR_MSG, 305	ER_GRP_RPL_FAILED_TO_INIT_HANDLER, 351
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL,	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFT
524	521
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING,	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE,
511	589
ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSGR,	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EV
327	343
ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER,	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME,
579	352
ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER,	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_U
579	571
ER_GRP_RPL_ERROR_STOPPING_CHANNELS,	ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBS
327	351
ER_GRP_RPL_ERROR_VERIFYING_SIDNO, 329	ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OB
ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFL	IST DETECTION,
346	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_M
ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR,	408,
342	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBS
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR,	342
342	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_R
ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR,	345
341	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODUL
ER_GRP_RPL_EVENT_HANDLING_ERROR, 326	351
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE,	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGI
334	349
ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 359	ER_GRP_RPL_FAILED_TO_START_ON_BOOT,
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HAN	DLING INFRASTRUCTURE,
357	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION,	343
343	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION,	343
343	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL,
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE,	349
349	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_C
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LE	352GRP,
350	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_C
ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE	352
346	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_O
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT	352
345	ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATIO
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE	ON SHUTDOWN,
351	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EX
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE,	351
349	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE SET,	574,
345	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DA
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE SET,	574,
345	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP,	352
352	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID,	571
571	

ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY, 575	ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT, 356
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY, 575	ER_GRP_RPL_GRP_MEMBER_OFFLINE, 359
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER, 575	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID, 563
ER_GRP_RPL_FATAL_REC_PROCESS, 347	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS, 563
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED, 338	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 355
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED, 339	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY, 355
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 340	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE, 570
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED, 339	ER_GRP_RPL_GTID_ALREADY_USED, 326
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED, 338	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR, 334
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED, 339	ER_GRP_RPL_GTID_MODE_OFF, 353
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED, 337	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR, 537
ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR, 329	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR, 334
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED, 340	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_REPLICATION, 523
ER_GRP_RPL_FINISHED_AUTO_REJOIN, 528	ER_GRP_RPL_HAS_STARTED, 602
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED, 338	ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_REPLICATION, 354
ER_GRP_RPL_FLOW_CONTROL_STATS, 360	ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE, 331
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTA, 356	ER_GRP_RPL_INTERNAL_QUERY, 341
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA, 355	ER_GRP_RPL_INVALID_BINLOG_FORMAT, 344
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA, 356	ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL, 528
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY, 348	ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 359
ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED, 356	ER_GRP_RPL_INVALID_MAX_QUOTA_SET, 329
ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING, 524	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING, 356
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET, 360	ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION, 354
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR, 360	ER_GRP_RPL_IS_STARTING, 551
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT, 360	ER_GRP_RPL_IS_STOPPED, 350
ER_GRP_RPL_GCS_GR_ERROR_MSG, 361	ER_GRP_RPL_IS_STOPPING, 350
ER_GRP_RPL_GCS_INTERFACE_ERROR, 359	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING, 511
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION, 359	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING, 511
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR, 328	ER_GRP_RPL_KILLED_FAILED_ID, 341
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_INFO, 570	ER_GRP_RPL_KILLED_SESSION_ID, 340
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR, 334	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR, 335
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED, 359	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET, 354
	ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET, 354
	ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_MASTER, 499
	ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE, 354
	ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED, 341

ER_GRP_RPL_MEMBER_ACTIONS_RESET, 569	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR, 440
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION, 568	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE, 125
ER_GRP_RPL_MEMBER_ACTION_DISABLED, 569	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR, 510
ER_GRP_RPL_MEMBER_ACTION_ENABLED, 569	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER, 331
ER_GRP_RPL_MEMBER_ACTION_FAILURE, 568	ER_GRP_RPL_MODULE_TERMINATE_ERROR, 331
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE, 568	ER_GRP_RPL_MODULE_TERMINATE_ERROR, 331
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA, 568	ER_GRP_RPL_MSG_DISCARDED, 331
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN, 569	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_F, 346
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN, 569	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED, 345
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE, 568	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR, 574
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED, 568	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR, 574
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION, 569	ER_GRP_RPL_NEW_PRIMARY_ELECTED, 333
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS, 568	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED, 339
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN, 569	ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 537
ER_GRP_RPL_MEMBER_ADDED, 332	ER_GRP_RPL_NO_STAGE_SERVICE, 512
ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 334	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM, 334
ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP, 336	ER_GRP_RPL_NO_VALID_DONOR, 342
ER_GRP_RPL_MEMBER_CHANGE, 333	ER_GRP_RPL_NULL_PACKET, 330
ER_GRP_RPL_MEMBER_CONF_INFO, 350	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 347
ER_GRP_RPL_MEMBER_CONTACT_RESTORED, 332	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION, 343
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR, 333	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP, 580
ER_GRP_RPL_MEMBER_EXPELLED, 333	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD, 599
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST, 608	ER_GRP_RPL_PIPELINE_CREATE_FAILED, 360
ER_GRP_RPL_MEMBER_LEFT_GRP, 333	ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 361
ER_GRP_RPL_MEMBER_NOT_FOUND, 341	ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ, 361
ER_GRP_RPL_MEMBER_REMOVED, 332	ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE, 361
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP, 349	ER_GRP_RPL_PLUGIN_ABORT, 507
ER_GRP_RPL_MEMBER_STATS_INFO, 360	ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON, 349
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR, 336	ER_GRP_RPL_PREV_REC_SESSION_RUNNING, 347
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP, 335	ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR, 312
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP, 335	ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR, 512
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE, 335	ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED, 338
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE, 534	ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP, 332
ER_GRP_RPL_MEM_ONLINE, 331	ER_GRP_RPL_PROCESS_GTID_SET_ERROR, 330
ER_GRP_RPL_MEM_REACHABLE, 332	
ER_GRP_RPL_MEM_UNREACHABLE, 332	

ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR, 330	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN, 337
ER_GRP_RPL_PURGE_APPLIER_LOGS, 336	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT, 361
ER_GRP_RPL_PURGE_REC, 343	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED, 361
ER_GRP_RPL_QUERY_FAIL, 341	ER_READ_ONLY, 361
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SLAVE, 348	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_M, 361
ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY, 348	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_M, 337
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS, 330	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN, 337
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING, 138	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE, 538
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 552	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECOND, 538
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES, 552	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_T, 350
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 552	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR, 337
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR, 552	ER_GRP_RPL_RECOVERY_ENDPOINT, 337
ER_GRP_RPL_RECOVERY_EVAL_ERROR, 537	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMB, 360
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION, 351	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED, 521
ER_GRP_RPL_RECOVERY_STRAT_CHOICE, 537	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION, 522
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED, 537	ER_GRP_RPL_SERVER_ALREADY_LEFT, 350
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD, 537	ER_GRP_RPL_SERVER_CONN_ERROR, 328
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK, 538	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING, 350
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK, 538	ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE, 539
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES, 522	ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO, 359
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_COMMIT, 521	ER_GRP_RPL_SERVER_UDF_ERROR, 513
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC, 522	ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY, 333
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE, 347	ER_GRP_RPL_SESSION_OPEN_FAILED, 333
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_READ, 345	ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGG, 359
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE, 346	ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER, 579
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE, 354	ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER, 579
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES, 522	ER_GRP_RPL_SET_STABLE_TRANS_ERROR, 330
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR, 523	ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_W, 330
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE, 521	ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTE, 330
ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT, 362	ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT, 362
ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED, 362	ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED, 362
	ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN, 337

ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT,	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN
361	559
ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED,	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN,
361	528
ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET,	ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_S
355	350
ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER,	ER_GRP_RPL_TRANS_GREATER_THAN_GRP,
337	335
ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN,	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP,
337	335
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE,	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT,
538	345
ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER,	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET
576	344
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIATED,	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM
357	336
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY,	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER
358	521
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_ON_PRIMARY,	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HAND
357	522
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY,	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED,
358	523
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER,	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED,
358	522
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE,	ER_GRP_RPL_WAIT_FOR_SYNC_BEFORE_EXECUTION
358	523
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER,	ER_GRP_RPL_UDF_ERROR, 125
358	ER_GRP_RPL_UDF_REGISTER_ERROR, 512
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN,	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR,
358	512
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE,	ER_GRP_RPL_UDF_UNREGISTER_ERROR, 512
358	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS,
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED,	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET
357	361
ER_GRP_RPL_SRV_BLOCKED, 332	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 332	360
ER_GRP_RPL_SRV_GTID_WAIT_ERROR, 531	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC,
ER_GRP_RPL_SRV_NOT_ONLINE, 331	347
ER_GRP_RPL_SRV_ONLINE, 331	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS,
ER_GRP_RPL_SRV_PRIMARY_MEM, 333	347
ER_GRP_RPL_SRV_SECONDARY_MEM, 333	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE
ER_GRP_RPL_SRV_WAIT_TIME_OUT, 340	353
ER_GRP_RPL_SSL_DISABLED, 353	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPL
ER_GRP_RPL_STARTED_AUTO_REJOIN, 528	343
ER_GRP_RPL_STARTING_GRP_REC, 342	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAIL
ER_GRP_RPL_START_FAILED, 335	343
ER_GRP_RPL_START_GRP_RPL_FAILED, 340	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE,
ER_GRP_RPL_STOPPING_GRP_REC, 342	348
ER_GRP_RPL_STOP_REP_CHANNEL, 361	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS,
ER_GRP_RPL_SUPER_READ_OFF, 340	348
ER_GRP_RPL_SUPER_READ_ON, 340	ER_GRP_RPL_UNBLOCK_WAITING_THD, 327
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR,	ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_R
334	355
ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS_SET,	ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_M
356	357
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP,	ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION,
349	344

ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR,	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_
328	54
ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_ERROR,	ER_GTID_NEXT_ERROR, UNDEFINED_GROUP, 60
571	ER_GTID_NEXT_TYPE_UNDEFINED_GTID, 60
ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 329	ER_GTID_PURGED_WAS_CHANGED, 60
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION_ERROR,	ER_GTID_PURGED_WAS_UPDATED, 265
329	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_E
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED,	110
339	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT,
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR,	329
329	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT,
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VERSION_ERROR,	327
327	ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE,
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRPGTID,	55
571	ER_GTID_UNSAFE_CREATE_SELECT, 55
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE,	140
140	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE,
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID,	55
570	ER_HANDLERTON_OOM, 179
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER,	570
570	ER_HANDSHAKE_ERROR, 5
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR,	570
571	ER_HEALTH_INFO, 563
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUPGTID,	571
570	ER_HEALTH_WARNING, 563
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE,	350
350	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1,
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED,	522
522	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2,
ER_GRP_RPL_WHILE_SENDING_MSG_REC, 348	347
347	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3,
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED,	344
344	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1,
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED,	346
346	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2,
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_BUFFER_FAILED,	346
346	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3,
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN,	113
113	ER_HOSTNAME, 33
ER_GRP_TRX_CONSISTENCY_BEFORE, 113	ER_HOSTNAME_DOESNT_RESOLVE_TO, 160
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED,	113
113	ER_HOSTNAME_RESEMBLES_IPV4, 160
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED,	112
112	ER_HOSTNAME_TOO_LONG, 131
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION,	544
544	ER_HOSTNAME_TRUNCATED, 554
ER_GR_HOLD_KILLED, 111	ER_HOST_IS_BLOCKED, 12
ER_GR_HOLD_MEMBER_STATUS_ERROR, 111	ER_HOST_NOT_PRIVILEGED, 12
ER_GR_HOLD_WAIT_TIMEOUT, 111	ER_HYPERGRAPH_NOT_SUPPORTED_YET, 135
ER_GTID_ALREADY_ADDED_BY_USER, 194	ER_IB_BUFFER_POOL_FULL, 596
ER_GTID_EXECUTED_WAS_CHANGED, 60	ER_IB_BUFFER_POOL_OVERUSE, 596
ER_GTID_EXECUTED_WAS_UPDATED, 266	ER_IB_BULK_FLUSHER_INFO, 595
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_ATIME,	55
55	ER_IB_BULK_LOAD_MERGE_FAIL, 599
ER_GTID_MODE_OFF, 70	ER_IB_BULK_LOAD_SUBTREE_INFO, 595
ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY,	55
55	ER_IB_BULK_LOAD_THREAD_FAIL, 598
	ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLES,
	554
	ER_IB_CLONE_GTID_PERSIST, 386
	ER_IB_CLONE_INTERNAL, 385
	ER_IB_CLONE_NON_INNODB_TABLE, 536
	ER_IB_CLONE_ONE_OPERATION, 536
	ER_IB_CLONE_PUNCH_HOLE, 386
	ER_IB_CLONE_RESTART, 536
	ER_IB_CLONE_SQL, 386
	ER_IB_CLONE_START_STOP, 536

ER_IB_CLONE_STATUS_FILE, 386	ER_IB_INDEX_PART_TOO_LONG, 608
ER_IB_CLONE_TIMEOUT, 385	ER_IB_INNODB_TBSP_OUT_OF_SPACE, 564
ER_IB_CLONE_USER_DATA, 536	ER_IB_LOAD_BULK_CONCURRENCY_REDUCED, 599
ER_IB_CLONE_VALIDATE, 386	ER_IB_LOB_ROLLBACK_INDEX_LEN, 542
ER_IB_DBLWR_BYTES_INFO, 583	ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, 554
ER_IB_DBLWR_DECOMPRESS_FAILED, 560	ER_IB_LONG_AHI_DISABLE_WAIT, 389
ER_IB_DBLWR_DECRYPT_FAILED, 560	ER_IB_MSG_0, 371
ER_IB_DBLWR_KEY_MISSING, 561	ER_IB_MSG_1, 371
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND, 607	ER_IB_MSG_10, 372
ER_IB_DICT_INVALID_COLUMN_POSITION, 600	ER_IB_MSG_100, 381
ER_IB_DICT_LOG_TABLE_INFO, 600	ER_IB_MSG_1000, 468
ER_IB_DUPLICATE_KEY, 596	ER_IB_MSG_1001, 468
ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 554	ER_IB_MSG_1002, 468
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 558	ER_IB_MSG_1003, 468
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER, 558	ER_IB_MSG_1004, 468
ER_IB_ERR_INDEX_DUPLICATE_KEY, 557	ER_IB_MSG_1005, 468
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER, 557	ER_IB_MSG_1006, 468
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW, 556	ER_IB_MSG_1007, 468
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER, 556	ER_IB_MSG_1008, 468
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED, 573	ER_IB_MSG_1009, 468
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE, 551	ER_IB_MSG_101, 381
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, 551	ER_IB_MSG_1010, 469
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, 551	ER_IB_MSG_1011, 469
ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN, 379	ER_IB_MSG_1012, 469
ER_IB_ERR_PARALLEL_READ_OOM, 558	ER_IB_MSG_1013, 469
ER_IB_ERR_RECOVERY_REDO_DISABLED, 553	ER_IB_MSG_1014, 469
ER_IB_ERR_SCHED_SETAFFINITY_FAILED, 556	ER_IB_MSG_1015, 469
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SYMBOLS, 556	ER_IB_MSG_1016, 469
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST, 555	ER_IB_MSG_1017, 469
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, 556	ER_IB_MSG_1018, 469
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATA_DIR, 556	ER_IB_MSG_1019, 469
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, 556	ER_IB_MSG_102, 381
ER_IB_ERR_ZLIB_BUF_ERROR, 557	ER_IB_MSG_1020, 469
ER_IB_ERR_ZLIB_DATA_ERROR, 557	ER_IB_MSG_1021, 470
ER_IB_ERR_ZLIB_MEM_ERROR, 557	ER_IB_MSG_1022, 470
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 557	ER_IB_MSG_1023, 470
ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 557	ER_IB_MSG_1024, 470
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, 555	ER_IB_MSG_1025, 470
ER_IB_HIDDEN_NAME_CONFLICT, 600	ER_IB_MSG_1026, 470
ER_IB_INDEX_BUILDER_DONE, 601	ER_IB_MSG_1027, 470
ER_IB_INDEX_BUILDER_INIT, 601	ER_IB_MSG_1028, 470
ER_IB_INDEX_LOADER_DONE, 601	ER_IB_MSG_1029, 470
ER_IB_INDEX_LOG_VERSION_MISMATCH, 601	ER_IB_MSG_103, 381
	ER_IB_MSG_1030, 470
	ER_IB_MSG_1031, 470
	ER_IB_MSG_1032, 471
	ER_IB_MSG_1033, 471
	ER_IB_MSG_1034, 471
	ER_IB_MSG_1035, 471
	ER_IB_MSG_1036, 471
	ER_IB_MSG_1037, 471
	ER_IB_MSG_1038, 471
	ER_IB_MSG_1039, 471
	ER_IB_MSG_104, 381
	ER_IB_MSG_1040, 471
	ER_IB_MSG_1041, 471

ER_IB_MSG_1042, 471	ER_IB_MSG_1095, 477
ER_IB_MSG_1043, 472	ER_IB_MSG_1096, 477
ER_IB_MSG_1044, 472	ER_IB_MSG_1097, 478
ER_IB_MSG_1045, 472	ER_IB_MSG_1098, 478
ER_IB_MSG_1046, 472	ER_IB_MSG_1099, 478
ER_IB_MSG_1047, 472	ER_IB_MSG_11, 372
ER_IB_MSG_1048, 472	ER_IB_MSG_110, 382
ER_IB_MSG_1049, 472	ER_IB_MSG_1100, 478
ER_IB_MSG_105, 381	ER_IB_MSG_1101, 478
ER_IB_MSG_1050, 472	ER_IB_MSG_1102, 478
ER_IB_MSG_1051, 472	ER_IB_MSG_1103, 478
ER_IB_MSG_1052, 472	ER_IB_MSG_1104, 478
ER_IB_MSG_1053, 473	ER_IB_MSG_1105, 478
ER_IB_MSG_1054, 473	ER_IB_MSG_1106, 478
ER_IB_MSG_1055, 473	ER_IB_MSG_1107, 479
ER_IB_MSG_1056, 473	ER_IB_MSG_1108, 479
ER_IB_MSG_1057, 473	ER_IB_MSG_1109, 479
ER_IB_MSG_1058, 473	ER_IB_MSG_111, 382
ER_IB_MSG_1059, 473	ER_IB_MSG_1110, 479
ER_IB_MSG_106, 381	ER_IB_MSG_1111, 479
ER_IB_MSG_1060, 473	ER_IB_MSG_1112, 479
ER_IB_MSG_1061, 473	ER_IB_MSG_1113, 479
ER_IB_MSG_1062, 473	ER_IB_MSG_1114, 479
ER_IB_MSG_1063, 474	ER_IB_MSG_1115, 479
ER_IB_MSG_1064, 474	ER_IB_MSG_1116, 479
ER_IB_MSG_1065, 474	ER_IB_MSG_1117, 480
ER_IB_MSG_1066, 474	ER_IB_MSG_1118, 480
ER_IB_MSG_1067, 474	ER_IB_MSG_1119, 480
ER_IB_MSG_1068, 474	ER_IB_MSG_112, 382
ER_IB_MSG_1069, 475	ER_IB_MSG_1120, 480
ER_IB_MSG_107, 381	ER_IB_MSG_1121, 480
ER_IB_MSG_1070, 475	ER_IB_MSG_1122, 480
ER_IB_MSG_1071, 475	ER_IB_MSG_1123, 480
ER_IB_MSG_1072, 475	ER_IB_MSG_1124, 480
ER_IB_MSG_1073, 475	ER_IB_MSG_1125, 480
ER_IB_MSG_1074, 475	ER_IB_MSG_1126, 480
ER_IB_MSG_1075, 475	ER_IB_MSG_1127, 481
ER_IB_MSG_1076, 475	ER_IB_MSG_1128, 481
ER_IB_MSG_1077, 475	ER_IB_MSG_1129, 481
ER_IB_MSG_1078, 476	ER_IB_MSG_113, 382
ER_IB_MSG_1079, 476	ER_IB_MSG_1130, 481
ER_IB_MSG_108, 381	ER_IB_MSG_1131, 481
ER_IB_MSG_1080, 476	ER_IB_MSG_1132, 481
ER_IB_MSG_1081, 476	ER_IB_MSG_1133, 481
ER_IB_MSG_1082, 476	ER_IB_MSG_1134, 481
ER_IB_MSG_1083, 476	ER_IB_MSG_1135, 481
ER_IB_MSG_1084, 476	ER_IB_MSG_1136, 482
ER_IB_MSG_1085, 476	ER_IB_MSG_1137, 482
ER_IB_MSG_1086, 476	ER_IB_MSG_1138, 482
ER_IB_MSG_1087, 477	ER_IB_MSG_1139, 482
ER_IB_MSG_1088, 477	ER_IB_MSG_114, 382
ER_IB_MSG_1089, 477	ER_IB_MSG_1140, 482
ER_IB_MSG_109, 382	ER_IB_MSG_1141, 483
ER_IB_MSG_1090, 477	ER_IB_MSG_1142, 483
ER_IB_MSG_1091, 477	ER_IB_MSG_1143, 483
ER_IB_MSG_1092, 477	ER_IB_MSG_1144, 483
ER_IB_MSG_1093, 477	ER_IB_MSG_1145, 483
ER_IB_MSG_1094, 477	ER_IB_MSG_1146, 483

ER_IB_MSG_1147, 483
ER_IB_MSG_1148, 483
ER_IB_MSG_1149, 484
ER_IB_MSG_115, 382
ER_IB_MSG_1150, 484
ER_IB_MSG_1151, 484
ER_IB_MSG_1152, 484
ER_IB_MSG_1153, 484
ER_IB_MSG_1154, 484
ER_IB_MSG_1155, 484
ER_IB_MSG_1156, 484
ER_IB_MSG_1157, 484
ER_IB_MSG_1158, 484
ER_IB_MSG_1159, 485
ER_IB_MSG_116, 382
ER_IB_MSG_1160, 485
ER_IB_MSG_1161, 485
ER_IB_MSG_1162, 485
ER_IB_MSG_1163, 485
ER_IB_MSG_1164, 485
ER_IB_MSG_1165, 485
ER_IB_MSG_1166, 485
ER_IB_MSG_1167, 485
ER_IB_MSG_1168, 486
ER_IB_MSG_1169, 486
ER_IB_MSG_117, 382
ER_IB_MSG_1170, 486
ER_IB_MSG_1171, 486
ER_IB_MSG_1172, 486
ER_IB_MSG_1173, 486
ER_IB_MSG_1174, 486
ER_IB_MSG_1175, 487
ER_IB_MSG_1176, 487
ER_IB_MSG_1177, 487
ER_IB_MSG_1178, 487
ER_IB_MSG_1179, 487
ER_IB_MSG_118, 382
ER_IB_MSG_1180, 487
ER_IB_MSG_1181, 487
ER_IB_MSG_1182, 487
ER_IB_MSG_1183, 487
ER_IB_MSG_1184, 488
ER_IB_MSG_1185, 488
ER_IB_MSG_1186, 488
ER_IB_MSG_1187, 488
ER_IB_MSG_1188, 488
ER_IB_MSG_1189, 488
ER_IB_MSG_119, 382
ER_IB_MSG_1190, 488
ER_IB_MSG_1191, 488
ER_IB_MSG_1192, 488
ER_IB_MSG_1193, 488
ER_IB_MSG_1194, 489
ER_IB_MSG_1195, 489
ER_IB_MSG_1196, 489
ER_IB_MSG_1197, 489
ER_IB_MSG_1198, 489
ER_IB_MSG_1199, 489

ER_IB_MSG_12, 372
ER_IB_MSG_120, 383
ER_IB_MSG_1200, 489
ER_IB_MSG_1201, 489
ER_IB_MSG_1202, 489
ER_IB_MSG_1203, 489
ER_IB_MSG_1204, 489
ER_IB_MSG_1205, 490
ER_IB_MSG_1206, 490
ER_IB_MSG_1207, 490
ER_IB_MSG_1208, 490
ER_IB_MSG_1209, 490
ER_IB_MSG_121, 383
ER_IB_MSG_1210, 490
ER_IB_MSG_1211, 490
ER_IB_MSG_1212, 490
ER_IB_MSG_1213, 490
ER_IB_MSG_1214, 490
ER_IB_MSG_1215, 490
ER_IB_MSG_1216, 491
ER_IB_MSG_1217, 491
ER_IB_MSG_1218, 491
ER_IB_MSG_1219, 491
ER_IB_MSG_122, 383
ER_IB_MSG_1220, 491
ER_IB_MSG_1221, 491
ER_IB_MSG_1222, 491
ER_IB_MSG_1223, 491
ER_IB_MSG_1224, 492
ER_IB_MSG_1225, 492
ER_IB_MSG_1226, 492
ER_IB_MSG_1227, 492
ER_IB_MSG_1228, 492
ER_IB_MSG_1229, 492
ER_IB_MSG_123, 383
ER_IB_MSG_1230, 492
ER_IB_MSG_1231, 492
ER_IB_MSG_1232, 492
ER_IB_MSG_1233, 492
ER_IB_MSG_1234, 492
ER_IB_MSG_1235, 493
ER_IB_MSG_1236, 493
ER_IB_MSG_1237, 493
ER_IB_MSG_1238, 493
ER_IB_MSG_1239, 493
ER_IB_MSG_124, 383
ER_IB_MSG_1240, 493
ER_IB_MSG_1241, 494
ER_IB_MSG_1242, 494
ER_IB_MSG_1243, 494
ER_IB_MSG_1244, 494
ER_IB_MSG_1245, 494
ER_IB_MSG_1246, 494
ER_IB_MSG_1247, 494
ER_IB_MSG_1248, 494
ER_IB_MSG_1249, 494
ER_IB_MSG_125, 383
ER_IB_MSG_1250, 495

ER_IB_MSG_1251, 495
ER_IB_MSG_1252, 495
ER_IB_MSG_1253, 495
ER_IB_MSG_1254, 495
ER_IB_MSG_1255, 495
ER_IB_MSG_1256, 495
ER_IB_MSG_1257, 495
ER_IB_MSG_1258, 495
ER_IB_MSG_1259, 496
ER_IB_MSG_126, 383
ER_IB_MSG_1260, 496
ER_IB_MSG_1261, 496
ER_IB_MSG_1262, 496
ER_IB_MSG_1263, 496
ER_IB_MSG_1264, 496
ER_IB_MSG_1265, 496
ER_IB_MSG_1266, 496
ER_IB_MSG_1267, 497
ER_IB_MSG_1268, 497
ER_IB_MSG_1269, 497
ER_IB_MSG_127, 383
ER_IB_MSG_1270, 497
ER_IB_MSG_1271, 507
ER_IB_MSG_1272, 507
ER_IB_MSG_1273, 508
ER_IB_MSG_1274, 509
ER_IB_MSG_1275, 509
ER_IB_MSG_1276, 509
ER_IB_MSG_1277, 509
ER_IB_MSG_1278, 509
ER_IB_MSG_1279, 509
ER_IB_MSG_128, 383
ER_IB_MSG_1280, 510
ER_IB_MSG_1281, 510
ER_IB_MSG_1282, 510
ER_IB_MSG_1283, 510
ER_IB_MSG_1284, 510
ER_IB_MSG_1285, 533
ER_IB_MSG_129, 383
ER_IB_MSG_13, 373
ER_IB_MSG_130, 383
ER_IB_MSG_131, 384
ER_IB_MSG_132, 384
ER_IB_MSG_133, 384
ER_IB_MSG_134, 384
ER_IB_MSG_135, 384
ER_IB_MSG_1357, 555
ER_IB_MSG_1358, 555
ER_IB_MSG_1359, 555
ER_IB_MSG_136, 384
ER_IB_MSG_137, 384
ER_IB_MSG_1372, 556
ER_IB_MSG_1373, 556
ER_IB_MSG_1374, 556
ER_IB_MSG_1375, 557
ER_IB_MSG_138, 384
ER_IB_MSG_1381, 557
ER_IB_MSG_139, 384

ER_IB_MSG_14, 373
ER_IB_MSG_140, 384
ER_IB_MSG_141, 384
ER_IB_MSG_142, 385
ER_IB_MSG_143, 385
ER_IB_MSG_144, 385
ER_IB_MSG_145, 385
ER_IB_MSG_146, 385
ER_IB_MSG_147, 385
ER_IB_MSG_148, 385
ER_IB_MSG_149, 385
ER_IB_MSG_15, 373
ER_IB_MSG_150, 385
ER_IB_MSG_151, 386
ER_IB_MSG_152, 386
ER_IB_MSG_153, 386
ER_IB_MSG_154, 386
ER_IB_MSG_155, 386
ER_IB_MSG_156, 386
ER_IB_MSG_157, 387
ER_IB_MSG_158, 387
ER_IB_MSG_159, 387
ER_IB_MSG_16, 373
ER_IB_MSG_160, 387
ER_IB_MSG_161, 387
ER_IB_MSG_162, 387
ER_IB_MSG_163, 387
ER_IB_MSG_164, 387
ER_IB_MSG_165, 387
ER_IB_MSG_166, 387
ER_IB_MSG_167, 387
ER_IB_MSG_168, 388
ER_IB_MSG_169, 388
ER_IB_MSG_17, 373
ER_IB_MSG_170, 388
ER_IB_MSG_171, 388
ER_IB_MSG_172, 388
ER_IB_MSG_173, 388
ER_IB_MSG_174, 388
ER_IB_MSG_175, 388
ER_IB_MSG_176, 388
ER_IB_MSG_177, 388
ER_IB_MSG_178, 388
ER_IB_MSG_179, 389
ER_IB_MSG_18, 373
ER_IB_MSG_180, 389
ER_IB_MSG_181, 389
ER_IB_MSG_182, 389
ER_IB_MSG_183, 389
ER_IB_MSG_184, 389
ER_IB_MSG_185, 389
ER_IB_MSG_186, 389
ER_IB_MSG_187, 389
ER_IB_MSG_188, 389
ER_IB_MSG_189, 390
ER_IB_MSG_19, 373
ER_IB_MSG_190, 390
ER_IB_MSG_191, 390

ER_IB_MSG_192, 390
ER_IB_MSG_193, 390
ER_IB_MSG_194, 390
ER_IB_MSG_195, 390
ER_IB_MSG_196, 390
ER_IB_MSG_197, 390
ER_IB_MSG_198, 390
ER_IB_MSG_199, 390
ER_IB_MSG_2, 372
ER_IB_MSG_20, 373
ER_IB_MSG_200, 391
ER_IB_MSG_201, 391
ER_IB_MSG_202, 391
ER_IB_MSG_203, 391
ER_IB_MSG_204, 391
ER_IB_MSG_205, 391
ER_IB_MSG_206, 391
ER_IB_MSG_207, 391
ER_IB_MSG_208, 391
ER_IB_MSG_209, 391
ER_IB_MSG_21, 373
ER_IB_MSG_210, 391
ER_IB_MSG_211, 392
ER_IB_MSG_212, 392
ER_IB_MSG_213, 392
ER_IB_MSG_214, 392
ER_IB_MSG_215, 392
ER_IB_MSG_216, 392
ER_IB_MSG_217, 392
ER_IB_MSG_218, 392
ER_IB_MSG_219, 392
ER_IB_MSG_22, 373
ER_IB_MSG_220, 392
ER_IB_MSG_221, 392
ER_IB_MSG_222, 393
ER_IB_MSG_223, 393
ER_IB_MSG_224, 393
ER_IB_MSG_225, 393
ER_IB_MSG_226, 393
ER_IB_MSG_227, 393
ER_IB_MSG_228, 393
ER_IB_MSG_229, 393
ER_IB_MSG_23, 373
ER_IB_MSG_230, 393
ER_IB_MSG_231, 393
ER_IB_MSG_232, 393
ER_IB_MSG_233, 394
ER_IB_MSG_234, 394
ER_IB_MSG_235, 394
ER_IB_MSG_236, 394
ER_IB_MSG_237, 394
ER_IB_MSG_238, 394
ER_IB_MSG_239, 394
ER_IB_MSG_24, 374
ER_IB_MSG_240, 394
ER_IB_MSG_241, 394
ER_IB_MSG_242, 394
ER_IB_MSG_243, 394

ER_IB_MSG_244, 395
ER_IB_MSG_245, 395
ER_IB_MSG_246, 395
ER_IB_MSG_247, 395
ER_IB_MSG_248, 395
ER_IB_MSG_249, 395
ER_IB_MSG_25, 374
ER_IB_MSG_250, 395
ER_IB_MSG_251, 395
ER_IB_MSG_252, 395
ER_IB_MSG_253, 395
ER_IB_MSG_254, 395
ER_IB_MSG_255, 396
ER_IB_MSG_256, 396
ER_IB_MSG_257, 396
ER_IB_MSG_258, 396
ER_IB_MSG_259, 396
ER_IB_MSG_26, 374
ER_IB_MSG_260, 396
ER_IB_MSG_261, 396
ER_IB_MSG_262, 396
ER_IB_MSG_263, 396
ER_IB_MSG_264, 396
ER_IB_MSG_265, 396
ER_IB_MSG_266, 397
ER_IB_MSG_267, 397
ER_IB_MSG_268, 397
ER_IB_MSG_269, 397
ER_IB_MSG_27, 374
ER_IB_MSG_270, 397
ER_IB_MSG_271, 397
ER_IB_MSG_272, 397
ER_IB_MSG_273, 397
ER_IB_MSG_274, 397
ER_IB_MSG_275, 397
ER_IB_MSG_276, 397
ER_IB_MSG_277, 398
ER_IB_MSG_278, 398
ER_IB_MSG_279, 398
ER_IB_MSG_28, 374
ER_IB_MSG_280, 398
ER_IB_MSG_281, 398
ER_IB_MSG_282, 398
ER_IB_MSG_283, 398
ER_IB_MSG_284, 398
ER_IB_MSG_285, 398
ER_IB_MSG_286, 398
ER_IB_MSG_287, 399
ER_IB_MSG_288, 399
ER_IB_MSG_289, 399
ER_IB_MSG_29, 374
ER_IB_MSG_290, 399
ER_IB_MSG_291, 399
ER_IB_MSG_292, 399
ER_IB_MSG_293, 399
ER_IB_MSG_294, 399
ER_IB_MSG_295, 399
ER_IB_MSG_296, 400

ER_IB_MSG_297, 400
ER_IB_MSG_298, 400
ER_IB_MSG_299, 400
ER_IB_MSG_3, 372
ER_IB_MSG_30, 374
ER_IB_MSG_300, 400
ER_IB_MSG_301, 400
ER_IB_MSG_302, 400
ER_IB_MSG_303, 401
ER_IB_MSG_304, 401
ER_IB_MSG_305, 401
ER_IB_MSG_306, 401
ER_IB_MSG_307, 401
ER_IB_MSG_308, 401
ER_IB_MSG_309, 401
ER_IB_MSG_31, 374
ER_IB_MSG_310, 401
ER_IB_MSG_311, 401
ER_IB_MSG_312, 401
ER_IB_MSG_313, 402
ER_IB_MSG_314, 402
ER_IB_MSG_315, 402
ER_IB_MSG_316, 402
ER_IB_MSG_317, 402
ER_IB_MSG_318, 402
ER_IB_MSG_319, 402
ER_IB_MSG_32, 374
ER_IB_MSG_320, 402
ER_IB_MSG_321, 402
ER_IB_MSG_322, 402
ER_IB_MSG_323, 402
ER_IB_MSG_324, 403
ER_IB_MSG_325, 403
ER_IB_MSG_326, 403
ER_IB_MSG_327, 403
ER_IB_MSG_328, 403
ER_IB_MSG_329, 403
ER_IB_MSG_33, 374
ER_IB_MSG_330, 403
ER_IB_MSG_331, 403
ER_IB_MSG_332, 403
ER_IB_MSG_333, 403
ER_IB_MSG_334, 403
ER_IB_MSG_335, 404
ER_IB_MSG_336, 404
ER_IB_MSG_337, 404
ER_IB_MSG_338, 404
ER_IB_MSG_339, 404
ER_IB_MSG_34, 374
ER_IB_MSG_340, 404
ER_IB_MSG_341, 404
ER_IB_MSG_342, 404
ER_IB_MSG_343, 404
ER_IB_MSG_344, 404
ER_IB_MSG_345, 404
ER_IB_MSG_346, 405
ER_IB_MSG_347, 405
ER_IB_MSG_348, 405

ER_IB_MSG_349, 405
ER_IB_MSG_35, 375
ER_IB_MSG_350, 405
ER_IB_MSG_351, 405
ER_IB_MSG_352, 405
ER_IB_MSG_353, 405
ER_IB_MSG_354, 405
ER_IB_MSG_355, 406
ER_IB_MSG_356, 406
ER_IB_MSG_357, 406
ER_IB_MSG_358, 406
ER_IB_MSG_359, 406
ER_IB_MSG_36, 375
ER_IB_MSG_360, 406
ER_IB_MSG_361, 406
ER_IB_MSG_362, 406
ER_IB_MSG_363, 406
ER_IB_MSG_364, 406
ER_IB_MSG_365, 406
ER_IB_MSG_366, 407
ER_IB_MSG_367, 407
ER_IB_MSG_368, 407
ER_IB_MSG_369, 407
ER_IB_MSG_37, 375
ER_IB_MSG_370, 407
ER_IB_MSG_371, 407
ER_IB_MSG_372, 407
ER_IB_MSG_373, 407
ER_IB_MSG_374, 407
ER_IB_MSG_375, 407
ER_IB_MSG_376, 408
ER_IB_MSG_377, 408
ER_IB_MSG_378, 408
ER_IB_MSG_379, 408
ER_IB_MSG_38, 375
ER_IB_MSG_380, 408
ER_IB_MSG_381, 408
ER_IB_MSG_382, 408
ER_IB_MSG_383, 408
ER_IB_MSG_384, 408
ER_IB_MSG_385, 408
ER_IB_MSG_386, 408
ER_IB_MSG_387, 409
ER_IB_MSG_388, 409
ER_IB_MSG_389, 409
ER_IB_MSG_39, 375
ER_IB_MSG_390, 409
ER_IB_MSG_391, 409
ER_IB_MSG_392, 409
ER_IB_MSG_393, 409
ER_IB_MSG_394, 409
ER_IB_MSG_395, 410
ER_IB_MSG_396, 410
ER_IB_MSG_397, 410
ER_IB_MSG_398, 410
ER_IB_MSG_399, 410
ER_IB_MSG_4, 372
ER_IB_MSG_40, 375

ER_IB_MSG_400, 410
ER_IB_MSG_401, 410
ER_IB_MSG_402, 410
ER_IB_MSG_403, 410
ER_IB_MSG_404, 410
ER_IB_MSG_405, 410
ER_IB_MSG_406, 411
ER_IB_MSG_407, 411
ER_IB_MSG_408, 411
ER_IB_MSG_409, 411
ER_IB_MSG_41, 375
ER_IB_MSG_410, 411
ER_IB_MSG_411, 411
ER_IB_MSG_412, 411
ER_IB_MSG_413, 411
ER_IB_MSG_414, 411
ER_IB_MSG_415, 411
ER_IB_MSG_416, 411
ER_IB_MSG_417, 412
ER_IB_MSG_418, 412
ER_IB_MSG_419, 412
ER_IB_MSG_42, 375
ER_IB_MSG_420, 412
ER_IB_MSG_421, 412
ER_IB_MSG_422, 412
ER_IB_MSG_423, 412
ER_IB_MSG_424, 412
ER_IB_MSG_425, 412
ER_IB_MSG_426, 412
ER_IB_MSG_427, 412
ER_IB_MSG_428, 413
ER_IB_MSG_429, 413
ER_IB_MSG_43, 375
ER_IB_MSG_430, 413
ER_IB_MSG_431, 413
ER_IB_MSG_432, 413
ER_IB_MSG_433, 413
ER_IB_MSG_434, 413
ER_IB_MSG_435, 413
ER_IB_MSG_436, 413
ER_IB_MSG_437, 413
ER_IB_MSG_438, 413
ER_IB_MSG_439, 414
ER_IB_MSG_44, 375
ER_IB_MSG_440, 414
ER_IB_MSG_441, 414
ER_IB_MSG_442, 414
ER_IB_MSG_443, 414
ER_IB_MSG_444, 414
ER_IB_MSG_445, 414
ER_IB_MSG_446, 414
ER_IB_MSG_447, 414
ER_IB_MSG_448, 414
ER_IB_MSG_449, 414
ER_IB_MSG_45, 375
ER_IB_MSG_450, 415
ER_IB_MSG_451, 415
ER_IB_MSG_452, 415

ER_IB_MSG_453, 415
ER_IB_MSG_454, 415
ER_IB_MSG_455, 415
ER_IB_MSG_456, 415
ER_IB_MSG_457, 415
ER_IB_MSG_458, 415
ER_IB_MSG_459, 415
ER_IB_MSG_46, 376
ER_IB_MSG_460, 415
ER_IB_MSG_461, 416
ER_IB_MSG_462, 416
ER_IB_MSG_463, 416
ER_IB_MSG_464, 416
ER_IB_MSG_465, 416
ER_IB_MSG_466, 416
ER_IB_MSG_467, 416
ER_IB_MSG_468, 416
ER_IB_MSG_469, 416
ER_IB_MSG_47, 376
ER_IB_MSG_470, 416
ER_IB_MSG_471, 416
ER_IB_MSG_472, 417
ER_IB_MSG_473, 417
ER_IB_MSG_474, 417
ER_IB_MSG_475, 417
ER_IB_MSG_476, 417
ER_IB_MSG_477, 417
ER_IB_MSG_478, 417
ER_IB_MSG_479, 417
ER_IB_MSG_48, 376
ER_IB_MSG_480, 417
ER_IB_MSG_481, 417
ER_IB_MSG_482, 417
ER_IB_MSG_483, 418
ER_IB_MSG_484, 418
ER_IB_MSG_485, 418
ER_IB_MSG_486, 418
ER_IB_MSG_487, 418
ER_IB_MSG_488, 418
ER_IB_MSG_489, 418
ER_IB_MSG_49, 376
ER_IB_MSG_490, 418
ER_IB_MSG_491, 418
ER_IB_MSG_492, 418
ER_IB_MSG_493, 418
ER_IB_MSG_494, 419
ER_IB_MSG_495, 419
ER_IB_MSG_496, 419
ER_IB_MSG_497, 419
ER_IB_MSG_498, 419
ER_IB_MSG_499, 419
ER_IB_MSG_5, 372
ER_IB_MSG_50, 376
ER_IB_MSG_500, 419
ER_IB_MSG_501, 419
ER_IB_MSG_502, 419
ER_IB_MSG_503, 419
ER_IB_MSG_504, 419

ER_IB_MSG_505, 420	ER_IB_MSG_558, 424
ER_IB_MSG_506, 420	ER_IB_MSG_559, 424
ER_IB_MSG_507, 420	ER_IB_MSG_56, 377
ER_IB_MSG_508, 420	ER_IB_MSG_560, 425
ER_IB_MSG_509, 420	ER_IB_MSG_561, 425
ER_IB_MSG_51, 376	ER_IB_MSG_562, 425
ER_IB_MSG_510, 420	ER_IB_MSG_563, 425
ER_IB_MSG_511, 420	ER_IB_MSG_564, 425
ER_IB_MSG_512, 420	ER_IB_MSG_565, 425
ER_IB_MSG_513, 420	ER_IB_MSG_566, 425
ER_IB_MSG_514, 420	ER_IB_MSG_567, 425
ER_IB_MSG_515, 420	ER_IB_MSG_568, 425
ER_IB_MSG_516, 421	ER_IB_MSG_569, 426
ER_IB_MSG_517, 421	ER_IB_MSG_57, 377
ER_IB_MSG_518, 421	ER_IB_MSG_570, 426
ER_IB_MSG_519, 421	ER_IB_MSG_571, 426
ER_IB_MSG_52, 376	ER_IB_MSG_572, 426
ER_IB_MSG_520, 421	ER_IB_MSG_573, 426
ER_IB_MSG_521, 421	ER_IB_MSG_574, 426
ER_IB_MSG_522, 421	ER_IB_MSG_575, 426
ER_IB_MSG_523, 421	ER_IB_MSG_576, 426
ER_IB_MSG_524, 421	ER_IB_MSG_577, 426
ER_IB_MSG_525, 421	ER_IB_MSG_578, 426
ER_IB_MSG_526, 421	ER_IB_MSG_579, 426
ER_IB_MSG_527, 422	ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL,
ER_IB_MSG_528, 422	550
ER_IB_MSG_529, 422	ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL,
ER_IB_MSG_53, 376	546
ER_IB_MSG_530, 422	ER_IB_MSG_58, 377
ER_IB_MSG_531, 422	ER_IB_MSG_580, 427
ER_IB_MSG_532, 422	ER_IB_MSG_581, 427
ER_IB_MSG_533, 422	ER_IB_MSG_582, 427
ER_IB_MSG_534, 422	ER_IB_MSG_583, 427
ER_IB_MSG_535, 422	ER_IB_MSG_584, 427
ER_IB_MSG_536, 422	ER_IB_MSG_585, 427
ER_IB_MSG_537, 422	ER_IB_MSG_586, 427
ER_IB_MSG_538, 423	ER_IB_MSG_587, 427
ER_IB_MSG_539, 423	ER_IB_MSG_588, 427
ER_IB_MSG_54, 376	ER_IB_MSG_589, 427
ER_IB_MSG_540, 423	ER_IB_MSG_59, 377
ER_IB_MSG_541, 423	ER_IB_MSG_590, 427
ER_IB_MSG_542, 423	ER_IB_MSG_591, 428
ER_IB_MSG_543, 423	ER_IB_MSG_592, 428
ER_IB_MSG_544, 423	ER_IB_MSG_593, 428
ER_IB_MSG_545, 423	ER_IB_MSG_594, 428
ER_IB_MSG_546, 423	ER_IB_MSG_595, 428
ER_IB_MSG_547, 423	ER_IB_MSG_596, 428
ER_IB_MSG_548, 423	ER_IB_MSG_597, 428
ER_IB_MSG_549, 424	ER_IB_MSG_598, 428
ER_IB_MSG_55, 376	ER_IB_MSG_599, 428
ER_IB_MSG_550, 424	ER_IB_MSG_6, 372
ER_IB_MSG_551, 424	ER_IB_MSG_60, 377
ER_IB_MSG_552, 424	ER_IB_MSG_600, 428
ER_IB_MSG_553, 424	ER_IB_MSG_601, 428
ER_IB_MSG_554, 424	ER_IB_MSG_602, 429
ER_IB_MSG_555, 424	ER_IB_MSG_603, 429
ER_IB_MSG_556, 424	ER_IB_MSG_604, 429
ER_IB_MSG_557, 424	ER_IB_MSG_605, 429

ER_IB_MSG_606, 429
ER_IB_MSG_607, 429
ER_IB_MSG_608, 429
ER_IB_MSG_609, 429
ER_IB_MSG_61, 377
ER_IB_MSG_610, 429
ER_IB_MSG_611, 429
ER_IB_MSG_612, 429
ER_IB_MSG_613, 430
ER_IB_MSG_614, 430
ER_IB_MSG_615, 430
ER_IB_MSG_616, 430
ER_IB_MSG_617, 430
ER_IB_MSG_618, 430
ER_IB_MSG_619, 430
ER_IB_MSG_62, 377
ER_IB_MSG_620, 430
ER_IB_MSG_621, 430
ER_IB_MSG_622, 430
ER_IB_MSG_623, 430
ER_IB_MSG_624, 431
ER_IB_MSG_625, 431
ER_IB_MSG_626, 431
ER_IB_MSG_627, 431
ER_IB_MSG_628, 431
ER_IB_MSG_629, 431
ER_IB_MSG_63, 377
ER_IB_MSG_630, 431
ER_IB_MSG_631, 431
ER_IB_MSG_632, 431
ER_IB_MSG_633, 431
ER_IB_MSG_634, 431
ER_IB_MSG_635, 432
ER_IB_MSG_636, 432
ER_IB_MSG_637, 432
ER_IB_MSG_638, 432
ER_IB_MSG_639, 432
ER_IB_MSG_64, 377
ER_IB_MSG_640, 432
ER_IB_MSG_641, 432
ER_IB_MSG_642, 432
ER_IB_MSG_643, 432
ER_IB_MSG_644, 432
ER_IB_MSG_645, 433
ER_IB_MSG_646, 433
ER_IB_MSG_647, 433
ER_IB_MSG_648, 433
ER_IB_MSG_649, 433
ER_IB_MSG_65, 377
ER_IB_MSG_650, 433
ER_IB_MSG_651, 433
ER_IB_MSG_652, 433
ER_IB_MSG_653, 433
ER_IB_MSG_654, 434
ER_IB_MSG_655, 434
ER_IB_MSG_656, 434
ER_IB_MSG_657, 434
ER_IB_MSG_658, 434

ER_IB_MSG_659, 434
ER_IB_MSG_66, 377
ER_IB_MSG_660, 434
ER_IB_MSG_661, 434
ER_IB_MSG_662, 434
ER_IB_MSG_663, 434
ER_IB_MSG_664, 434
ER_IB_MSG_665, 435
ER_IB_MSG_666, 435
ER_IB_MSG_667, 435
ER_IB_MSG_668, 435
ER_IB_MSG_669, 435
ER_IB_MSG_67, 378
ER_IB_MSG_670, 435
ER_IB_MSG_671, 435
ER_IB_MSG_672, 435
ER_IB_MSG_673, 435
ER_IB_MSG_674, 435
ER_IB_MSG_675, 436
ER_IB_MSG_676, 436
ER_IB_MSG_677, 436
ER_IB_MSG_678, 436
ER_IB_MSG_679, 436
ER_IB_MSG_68, 378
ER_IB_MSG_680, 436
ER_IB_MSG_681, 436
ER_IB_MSG_682, 436
ER_IB_MSG_683, 436
ER_IB_MSG_684, 436
ER_IB_MSG_685, 436
ER_IB_MSG_686, 437
ER_IB_MSG_687, 437
ER_IB_MSG_688, 437
ER_IB_MSG_689, 437
ER_IB_MSG_69, 378
ER_IB_MSG_690, 437
ER_IB_MSG_691, 437
ER_IB_MSG_692, 437
ER_IB_MSG_693, 437
ER_IB_MSG_694, 437
ER_IB_MSG_695, 437
ER_IB_MSG_696, 438
ER_IB_MSG_697, 438
ER_IB_MSG_698, 438
ER_IB_MSG_699, 438
ER_IB_MSG_7, 372
ER_IB_MSG_70, 378
ER_IB_MSG_700, 438
ER_IB_MSG_701, 438
ER_IB_MSG_702, 439
ER_IB_MSG_703, 439
ER_IB_MSG_704, 439
ER_IB_MSG_705, 439
ER_IB_MSG_706, 439
ER_IB_MSG_707, 439
ER_IB_MSG_708, 439
ER_IB_MSG_709, 440
ER_IB_MSG_71, 378

ER_IB_MSG_710, 440
ER_IB_MSG_711, 440
ER_IB_MSG_712, 440
ER_IB_MSG_713, 440
ER_IB_MSG_714, 440
ER_IB_MSG_715, 440
ER_IB_MSG_716, 440
ER_IB_MSG_717, 440
ER_IB_MSG_718, 440
ER_IB_MSG_719, 441
ER_IB_MSG_72, 378
ER_IB_MSG_720, 441
ER_IB_MSG_721, 441
ER_IB_MSG_722, 441
ER_IB_MSG_723, 441
ER_IB_MSG_724, 441
ER_IB_MSG_725, 441
ER_IB_MSG_726, 441
ER_IB_MSG_727, 441
ER_IB_MSG_728, 442
ER_IB_MSG_729, 442
ER_IB_MSG_73, 378
ER_IB_MSG_730, 442
ER_IB_MSG_731, 442
ER_IB_MSG_732, 442
ER_IB_MSG_733, 442
ER_IB_MSG_734, 443
ER_IB_MSG_735, 443
ER_IB_MSG_736, 443
ER_IB_MSG_737, 443
ER_IB_MSG_738, 443
ER_IB_MSG_739, 444
ER_IB_MSG_74, 378
ER_IB_MSG_740, 444
ER_IB_MSG_741, 444
ER_IB_MSG_742, 444
ER_IB_MSG_743, 444
ER_IB_MSG_744, 444
ER_IB_MSG_745, 444
ER_IB_MSG_746, 444
ER_IB_MSG_747, 444
ER_IB_MSG_748, 444
ER_IB_MSG_749, 444
ER_IB_MSG_75, 378
ER_IB_MSG_750, 445
ER_IB_MSG_751, 445
ER_IB_MSG_752, 445
ER_IB_MSG_753, 445
ER_IB_MSG_754, 445
ER_IB_MSG_755, 445
ER_IB_MSG_756, 445
ER_IB_MSG_757, 445
ER_IB_MSG_758, 445
ER_IB_MSG_759, 445
ER_IB_MSG_76, 378
ER_IB_MSG_760, 445
ER_IB_MSG_761, 446
ER_IB_MSG_762, 446

ER_IB_MSG_763, 446
ER_IB_MSG_764, 446
ER_IB_MSG_765, 446
ER_IB_MSG_766, 446
ER_IB_MSG_767, 446
ER_IB_MSG_768, 446
ER_IB_MSG_769, 446
ER_IB_MSG_77, 378
ER_IB_MSG_770, 446
ER_IB_MSG_771, 446
ER_IB_MSG_772, 447
ER_IB_MSG_773, 447
ER_IB_MSG_774, 447
ER_IB_MSG_775, 447
ER_IB_MSG_776, 447
ER_IB_MSG_777, 447
ER_IB_MSG_778, 447
ER_IB_MSG_779, 447
ER_IB_MSG_78, 379
ER_IB_MSG_780, 447
ER_IB_MSG_781, 447
ER_IB_MSG_782, 447
ER_IB_MSG_783, 448
ER_IB_MSG_784, 448
ER_IB_MSG_785, 448
ER_IB_MSG_786, 448
ER_IB_MSG_787, 448
ER_IB_MSG_788, 448
ER_IB_MSG_789, 448
ER_IB_MSG_79, 379
ER_IB_MSG_790, 448
ER_IB_MSG_791, 448
ER_IB_MSG_792, 448
ER_IB_MSG_793, 448
ER_IB_MSG_794, 449
ER_IB_MSG_795, 449
ER_IB_MSG_796, 449
ER_IB_MSG_797, 449
ER_IB_MSG_798, 449
ER_IB_MSG_799, 449
ER_IB_MSG_8, 372
ER_IB_MSG_80, 379
ER_IB_MSG_800, 449
ER_IB_MSG_801, 449
ER_IB_MSG_802, 449
ER_IB_MSG_803, 449
ER_IB_MSG_804, 449
ER_IB_MSG_805, 450
ER_IB_MSG_806, 450
ER_IB_MSG_807, 450
ER_IB_MSG_808, 450
ER_IB_MSG_809, 450
ER_IB_MSG_81, 379
ER_IB_MSG_810, 450
ER_IB_MSG_811, 450
ER_IB_MSG_812, 450
ER_IB_MSG_813, 450
ER_IB_MSG_814, 450

ER_IB_MSG_815, 450
ER_IB_MSG_816, 451
ER_IB_MSG_817, 451
ER_IB_MSG_818, 451
ER_IB_MSG_819, 451
ER_IB_MSG_82, 379
ER_IB_MSG_820, 451
ER_IB_MSG_821, 451
ER_IB_MSG_822, 451
ER_IB_MSG_823, 451
ER_IB_MSG_824, 451
ER_IB_MSG_825, 451
ER_IB_MSG_826, 451
ER_IB_MSG_827, 452
ER_IB_MSG_828, 452
ER_IB_MSG_829, 452
ER_IB_MSG_83, 379
ER_IB_MSG_830, 452
ER_IB_MSG_831, 452
ER_IB_MSG_832, 452
ER_IB_MSG_833, 452
ER_IB_MSG_834, 452
ER_IB_MSG_835, 452
ER_IB_MSG_836, 452
ER_IB_MSG_837, 452
ER_IB_MSG_838, 453
ER_IB_MSG_839, 453
ER_IB_MSG_84, 379
ER_IB_MSG_840, 453
ER_IB_MSG_841, 453
ER_IB_MSG_842, 453
ER_IB_MSG_843, 453
ER_IB_MSG_844, 453
ER_IB_MSG_845, 453
ER_IB_MSG_846, 453
ER_IB_MSG_847, 454
ER_IB_MSG_848, 454
ER_IB_MSG_849, 454
ER_IB_MSG_85, 379
ER_IB_MSG_850, 454
ER_IB_MSG_851, 454
ER_IB_MSG_852, 454
ER_IB_MSG_853, 454
ER_IB_MSG_854, 454
ER_IB_MSG_855, 454
ER_IB_MSG_856, 455
ER_IB_MSG_857, 455
ER_IB_MSG_858, 455
ER_IB_MSG_859, 455
ER_IB_MSG_86, 379
ER_IB_MSG_860, 455
ER_IB_MSG_861, 455
ER_IB_MSG_862, 455
ER_IB_MSG_863, 455
ER_IB_MSG_864, 455
ER_IB_MSG_865, 455
ER_IB_MSG_866, 455
ER_IB_MSG_867, 456

ER_IB_MSG_868, 456
ER_IB_MSG_869, 456
ER_IB_MSG_87, 380
ER_IB_MSG_870, 456
ER_IB_MSG_871, 456
ER_IB_MSG_872, 456
ER_IB_MSG_873, 456
ER_IB_MSG_874, 456
ER_IB_MSG_875, 456
ER_IB_MSG_876, 456
ER_IB_MSG_877, 456
ER_IB_MSG_878, 457
ER_IB_MSG_879, 457
ER_IB_MSG_88, 380
ER_IB_MSG_880, 457
ER_IB_MSG_881, 457
ER_IB_MSG_882, 457
ER_IB_MSG_883, 457
ER_IB_MSG_884, 457
ER_IB_MSG_885, 457
ER_IB_MSG_886, 457
ER_IB_MSG_887, 457
ER_IB_MSG_888, 457
ER_IB_MSG_889, 458
ER_IB_MSG_89, 380
ER_IB_MSG_890, 458
ER_IB_MSG_891, 458
ER_IB_MSG_892, 458
ER_IB_MSG_893, 458
ER_IB_MSG_894, 458
ER_IB_MSG_895, 458
ER_IB_MSG_896, 458
ER_IB_MSG_897, 458
ER_IB_MSG_898, 458
ER_IB_MSG_899, 458
ER_IB_MSG_9, 372
ER_IB_MSG_90, 380
ER_IB_MSG_900, 459
ER_IB_MSG_901, 459
ER_IB_MSG_902, 459
ER_IB_MSG_903, 459
ER_IB_MSG_904, 459
ER_IB_MSG_905, 459
ER_IB_MSG_906, 459
ER_IB_MSG_907, 459
ER_IB_MSG_908, 459
ER_IB_MSG_909, 459
ER_IB_MSG_91, 380
ER_IB_MSG_910, 459
ER_IB_MSG_911, 460
ER_IB_MSG_912, 460
ER_IB_MSG_913, 460
ER_IB_MSG_914, 460
ER_IB_MSG_915, 460
ER_IB_MSG_916, 460
ER_IB_MSG_917, 460
ER_IB_MSG_918, 460
ER_IB_MSG_919, 460

ER_IB_MSG_92, 380
ER_IB_MSG_920, 460
ER_IB_MSG_921, 460
ER_IB_MSG_922, 461
ER_IB_MSG_923, 461
ER_IB_MSG_924, 461
ER_IB_MSG_925, 461
ER_IB_MSG_926, 461
ER_IB_MSG_927, 461
ER_IB_MSG_928, 461
ER_IB_MSG_929, 461
ER_IB_MSG_93, 380
ER_IB_MSG_930, 461
ER_IB_MSG_931, 461
ER_IB_MSG_932, 461
ER_IB_MSG_933, 462
ER_IB_MSG_934, 462
ER_IB_MSG_935, 462
ER_IB_MSG_936, 462
ER_IB_MSG_937, 462
ER_IB_MSG_938, 462
ER_IB_MSG_939, 462
ER_IB_MSG_94, 380
ER_IB_MSG_940, 462
ER_IB_MSG_941, 462
ER_IB_MSG_942, 462
ER_IB_MSG_943, 462
ER_IB_MSG_944, 463
ER_IB_MSG_945, 463
ER_IB_MSG_946, 463
ER_IB_MSG_947, 463
ER_IB_MSG_948, 463
ER_IB_MSG_949, 463
ER_IB_MSG_95, 380
ER_IB_MSG_950, 463
ER_IB_MSG_951, 463
ER_IB_MSG_952, 463
ER_IB_MSG_953, 463
ER_IB_MSG_954, 463
ER_IB_MSG_955, 464
ER_IB_MSG_956, 464
ER_IB_MSG_957, 464
ER_IB_MSG_958, 464
ER_IB_MSG_959, 464
ER_IB_MSG_96, 380
ER_IB_MSG_960, 464
ER_IB_MSG_961, 464
ER_IB_MSG_962, 464
ER_IB_MSG_963, 464
ER_IB_MSG_964, 464
ER_IB_MSG_965, 464
ER_IB_MSG_966, 465
ER_IB_MSG_967, 465
ER_IB_MSG_968, 465
ER_IB_MSG_969, 465
ER_IB_MSG_97, 380
ER_IB_MSG_970, 465
ER_IB_MSG_971, 465

ER_IB_MSG_972, 465
ER_IB_MSG_973, 465
ER_IB_MSG_974, 465
ER_IB_MSG_975, 465
ER_IB_MSG_976, 465
ER_IB_MSG_977, 466
ER_IB_MSG_978, 466
ER_IB_MSG_979, 466
ER_IB_MSG_98, 381
ER_IB_MSG_980, 466
ER_IB_MSG_981, 466
ER_IB_MSG_982, 466
ER_IB_MSG_983, 466
ER_IB_MSG_984, 466
ER_IB_MSG_985, 466
ER_IB_MSG_986, 466
ER_IB_MSG_987, 466
ER_IB_MSG_988, 467
ER_IB_MSG_989, 467
ER_IB_MSG_99, 381
ER_IB_MSG_990, 467
ER_IB_MSG_991, 467
ER_IB_MSG_992, 467
ER_IB_MSG_993, 467
ER_IB_MSG_994, 467
ER_IB_MSG_995, 467
ER_IB_MSG_996, 467
ER_IB_MSG_997, 467
ER_IB_MSG_998, 467
ER_IB_MSG_999, 468
ER_IB_MSG_BAD_DBLWR_FILE_NAME, 546
ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED,
536
ER_IB_MSG_BUF_PENDING_IO, 479
ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN,
495
ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS,
595
ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_COD
594
ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE,
595
ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE,
552
ER_IB_MSG_CANNOT_OPEN_57_UNDO, 476
ER_IB_MSG_CANT_DECRYPT_REDO_LOG, 454
ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA,
453
ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA,
593
ER_IB_MSG_CLOCK_GETTIME_FAILED, 533
ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED,
533
ER_IB_MSG_CLONE_DDL_APPLY, 576
ER_IB_MSG_CLONE_DDL_INVALIDATE, 576
ER_IB_MSG_CLONE_DDL_NTFN, 576
ER_IB_MSG_CREATED_UNDO_SPACE, 560
ER_IB_MSG_CREATE_LOG_FILE, 550

ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED, 481	ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 515
ER_IB_MSG_DBLWR_1285, 546	ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE, 517
ER_IB_MSG_DBLWR_1286, 546	ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE, 515
ER_IB_MSG_DBLWR_1287, 546	ER_IB_MSG_FILE_RESIZE, 474
ER_IB_MSG_DBLWR_1288, 546	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME, 544
ER_IB_MSG_DBLWR_1290, 546	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH, 544
ER_IB_MSG_DBLWR_1291, 546	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED, 544
ER_IB_MSG_DBLWR_1292, 547	ER_IB_MSG_FIL_STATE_MOVED_PREV, 609
ER_IB_MSG_DBLWR_1293, 547	ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR, 609
ER_IB_MSG_DBLWR_1294, 547	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY, 544
ER_IB_MSG_DBLWR_1295, 547	ER_IB_MSG_FOUND_WRONG_UNDO_SPACE, 516
ER_IB_MSG_DBLWR_1296, 547	ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR, 409
ER_IB_MSG_DBLWR_1297, 547	ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 550
ER_IB_MSG_DBLWR_1298, 547	ER_IB_MSG_IGNORE_SCAN_PATH, 407
ER_IB_MSG_DBLWR_1300, 547	ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR, 409
ER_IB_MSG_DBLWR_1301, 547	ER_IB_MSG_INCORRECT_SIZE, 560
ER_IB_MSG_DBLWR_1304, 547	ER_IB_MSG_INJECT_CRASH, 559
ER_IB_MSG_DBLWR_1305, 547	ER_IB_MSG_INJECT_FAILURE, 559
ER_IB_MSG_DBLWR_1306, 548	ER_IB_MSG_INNODB_END_INITIALIZE, 550
ER_IB_MSG_DBLWR_1307, 548	ER_IB_MSG_INNODB_START_INITIALIZE, 550
ER_IB_MSG_DBLWR_1308, 548	ER_IB_MSG_INVALID_LOCATION_FOR_TABLE, 425
ER_IB_MSG_DBLWR_1309, 548	ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE, 552
ER_IB_MSG_DBLWR_1310, 548	ER_IB_MSG_INVALID_LOCATION_WRONG_DB, 552
ER_IB_MSG_DBLWR_1311, 548	ER_IB_MSG_INVALID_PAGE_TYPE, 595
ER_IB_MSG_DBLWR_1312, 548	ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS, 517
ER_IB_MSG_DBLWR_1313, 548	ER_IB_MSG_LOG_CHECKPOINT_FOUND, 586
ER_IB_MSG_DBLWR_1314, 548	ER_IB_MSG_LOG_CORRUPT, 438
ER_IB_MSG_DBLWR_1315, 548	ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY, 494
ER_IB_MSG_DBLWR_1316, 548	ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED, 587
ER_IB_MSG_DBLWR_1317, 549	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE, 402
ER_IB_MSG_DBLWR_1318, 549	ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY, 584
ER_IB_MSG_DBLWR_1319, 549	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB, 442
ER_IB_MSG_DBLWR_1320, 549	ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY, 442
ER_IB_MSG_DBLWR_1321, 549	ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATE, 587
ER_IB_MSG_DBLWR_1322, 549	ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE, 474
ER_IB_MSG_DBLWR_1323, 549	
ER_IB_MSG_DBLWR_1324, 549	
ER_IB_MSG_DBLWR_1325, 549	
ER_IB_MSG_DBLWR_1326, 549	
ER_IB_MSG_DBLWR_1327, 549	
ER_IB_MSG_DDL_FAIL_NO_BUILDER, 608	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 433	
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT, 531	
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 531	
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES, 517	
ER_IB_MSG_DICT_PARTITION_NOT_FOUND, 545	
ER_IB_MSG_DIR_DOES_NOT_EXIST, 517	
ER_IB_MSG_DOWNGRADE_PARTITION_FILE, 544	
ER_IB_MSG_DROPPED_UNDO_SPACE, 560	
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE, 515	
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 515	
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 516	

ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES, 482	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED, 589
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED, 494	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED, 589
ER_IB_MSG_LOG_FILES_FOUND_MISSING, 588	ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED, 588
ER_IB_MSG_LOG_FILES_INITIALIZED, 475	ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9, 496
ER_IB_MSG_LOG_FILES_INVALID_SET, 482	ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 439
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED, 587	ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED, 443
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED, 587	ER_IB_MSG_LOG_FORMAT_OLD, 442
ER_IB_MSG_LOG_FILES_RESIZE_ON_START, 491	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED, 438
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED, 586	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 438
ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ_ONLY_MODE, 483	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 584
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED, 587	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 584
ER_IB_MSG_LOG_FILES_REWRITING, 483	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE, 584
ER_IB_MSG_LOG_FILES_UPGRADE, 587	ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNUSABLE, 497
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS, 588	ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED, 589
ER_IB_MSG_LOG_FILE_FOREIGN_UUID, 586	ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED, 585
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW, 588	ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 589
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD, 588	ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 585
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN, 439	ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 588
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM, 496	ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 588
ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED, 584	ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 588
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES, 586	ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 585
ER_IB_MSG_LOG_FILE_INVALID_START_LSN, 586	ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED, 585
ER_IB_MSG_LOG_FILE_IS_EMPTY, 583	ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED, 586
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED, 589	ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 585
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE, 587	ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 585
ER_IB_MSG_LOG_FILE_MISSING_FOR_ID, 586	ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA, 586
ER_IB_MSG_LOG_FILE_OPEN_FAILED, 475	ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 585
ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED, 473	ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 493
ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED, 474	ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 584
ER_IB_MSG_LOG_FILE_REMOVE_FAILED, 587	ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN, 585
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED, 587	ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 493
ER_IB_MSG_LOG_FILE_RESIZE_FAILED, 474	
ER_IB_MSG_LOG_FILE_SIZE_INVALID, 482	
ER_IB_MSG_LOG_FILE_TOO_BIG, 583	
ER_IB_MSG_LOG_FILE_TOO_SMALL, 583	
ER_IB_MSG_LOG_FILE_TRUNCATE, 588	
ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED, 589	

ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER,	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED,
493	488
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER,	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED,
593	554
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE,	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME,
584	580
ER_IB_MSG_LOG_WRITER_WRITE_FAILED,	ER_IB_MSG_UNDO_ALTERED_ACTIVE,
584	558
ER_IB_MSG_MADVISE_FAILED,	ER_IB_MSG_UNDO_ALTERED_INACTIVE,
515	558
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED,	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED,
515	576
ER_IB_MSG_MASTER_KEY_ROTATED,	ER_IB_MSG_UNDO_INJECT_CRASH,
560	558
ER_IB_MSG_MAX_UNDO_SPACES_REACHED,	ER_IB_MSG_UNDO_INJECT_FAILURE,
515	559
ER_IB_MSG_NOT_END_WITH_IBU,	ER_IB_MSG_UNDO_MARKED_ACTIVE,
516	558
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND,	ER_IB_MSG_UNDO_MARKED_EMPTY,
509	558
ER_IB_MSG_NUM_POOLS,	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE,
515	486
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS,	ER_IB_MSG_UNDO_TRUNCATE_COMPLETE,
550	487
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE,
593	558
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE,
574	486
ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE,
574	486
ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER,	ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL,
531	558
ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT,	ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE,
531	485
ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_UNDO_TRUNCATE,	ER_IB_MSG_UNDO_TRUNCATE_START,
443	486
ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND,	ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN,
439	551
ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE,	ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING,
584	516
ER_IB_MSG_RECOVERY_CORRUPT,	ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE,
482	516
ER_IB_MSG_RECOVERY_IN_READ_ONLY,	ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE,
443	516
ER_IB_MSG_RECOVERY_IS_NEEDED,	ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG,
443	516
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG,	ER_IB_MSG_UNDO_TRUNC_SKIP_IBUF_MERGES,
573	516
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG_UNEXPECTED,	ER_IB_MSG_UNEXPECTED_FILE_EXISTS,
573	400
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE,	ER_IB_MSG_UNEXPECTED_PROTECTED_LOCATION_ALLOWED,
441	405
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY,	ER_IB_MSG_UPGRADE_PARTITION_FILE,
573	544
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY,	ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT,
573	544
ER_IB_MSG_RESUME_OP_FOR_SPACE,	ER_IB_MSG_USING_UNDO_SPACE,
509	515
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR,	ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD,
555	509
ER_IB_MSG_SDI_Z_STREAM_ERROR,	ER_IB_MSG_WRONG_TABLESPACE_DIR,
516	517
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR,	ER_IB_PARALLEL_READER_WORKER_INFO,
516	595
ER_IB_MSG_SKIP_HIDDEN_DIR,	ER_IB_PRIMARY_KEY_IS_INSTANT,
542	599
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE,	ER_IB_RDBLWR_BYTES_INFO,
565	583
ER_IB_MSG_THREAD_CONCURRENCY_CHANGED,	ER_IB_RECV_FIRST_REC_GROUP_INVALID,
497	532
ER_IB_MSG_TOO_LONG_PATH,	ER_IB_RELOCK_LATCH_ORDER_VIOLATION,
532	555
	ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK,
	603
	ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK,
	602

ER_IB_RESURRECT_RECORD_COMPLETE, 603	ER_INCONSISTENT_PARTITION_INFO_ERROR,
ER_IB_RESURRECT_RECORD_PROGRESS, 603	35
ER_IB_RESURRECT_TRX_INSERT, 602	ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR,
ER_IB_RESURRECT_TRX_INSERT_COMPLETE,	35
603	ER_INCORRECT_CURRENT_PASSWORD, 123
ER_IB_RESURRECT_TRX_UPDATE, 602	ER_INCORRECT_GLOBAL_LOCAL_VAR, 19
ER_IB_RESURRECT_TRX_UPDATE_COMPLETE,	ER_INCORRECT_TYPE, 70
603	ER_INDEX_COLUMN_TOO_LONG, 49
ER_IB_SELECT_COUNT_STAR, 601	ER_INDEX_CORRUPT, 49
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED,	ER_INDEX_OTHER_THAN_PK, 150
553	ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDE
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY,	553
555	ER_INFORMATION_SCHEMA_VERSION_CHANGE,
ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE,	555
555	ER_INIT_BOOTSTRAP_COMPLETE, 205
ER_IB_WARN_ACCESSING_NONEXISTING_SPACE,	ER_INIT_CANT_OPEN_BOOTSTRAP_FILE, 205
399	ER_INIT_CREATING_DD, 205
ER_IB_WARN_MANY_NON_LRU_FILES_OPENED,	ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT,
580	205
ER_IB_WARN_OPEN_PARTITION_FILE, 544	ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WO
ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH,	205
576	ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE,
ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE,	205
567	ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE,
ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED,	205
553	ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD,
ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY,	542
599	ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT,
ER_IB_WRN_OLD_GEOMETRY_TYPE, 567	204
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA, 550	ER_INIT_ROOT_WITHOUT_PASSWORD, 204
ER_IB_WRN_REDO_DISABLED, 553	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED,
ER_IB_WRN_REDO_ENABLED, 553	281
ER_IDENTIFIED_BY_UNSUPPORTED, 142	ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE,
ER_IDENT_CAUSES_TOO_LONG_PATH, 61	138
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE,	ER_INNODB_CANNOT_BE_IGNORED, 102
538	ER_INNODB_CANNOT_CREATE_TABLE, 281
ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_OR_IDENTIFIER_TABLE,	262
147	ER_INNODB_CANNOT_CREATE_INDEX, 261
ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FUNC_IN_TABLE,	261
147	ER_INNODB_CANT_OPEN_TABLE, 261
ER_ILLEGAL_GRANT_FOR_TABLE, 13	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK,
ER_ILLEGAL_HA, 5	261
ER_ILLEGAL_HA_CREATE_OPTION, 34	ER_INNODB_CLUSTERED_INDEX_PRIVATE, 262
ER_ILLEGAL_PRIVILEGE_LEVEL, 93	ER_INNODB_COMPRESSION_FAILURE, 139
ER_ILLEGAL_REFERENCE, 20	ER_INNODB_DIFF_IN_REF_LEN, 281
ER_ILLEGAL_USER_VAR, 70	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW,
ER_ILLEGAL_VALUE_FOR_TYPE, 28	261
ER_IMPLICIT_COMPARISON_FOR_JSON, 133	ER_INNODB_ERROR_LOGGER_FATAL_MSG,
ER_IMPOSSIBLE_STRING_CONVERSION, 134	283
ER_IMP_INCOMPATIBLE_CFG_VERSION, 129	ER_INNODB_ERROR_LOGGER_MSG, 283
ER_IMP_INCOMPATIBLE_DD_VERSION, 93	ER_INNODB_FAILED_TO_FIND_IDX, 280
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION, 93	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE,
ER_IMP_INCOMPATIBLE_SDI_VERSION, 93	281
ER_IMP_NO_FILES_MATCHED, 92	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO,
ER_IMP_SCHEMA_DOES_NOT_EXIST, 92	280
ER_IMP_TABLE_ALREADY_EXISTS, 93	ER_INNODB_FILES_SAME, 261
ER_INCONSISTENT_ERROR, 500	ER_INNODB_FORCED_RECOVERY, 63

ER_INNODB_FT_AUX_NOT_HEX_ID, 63	ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 118
ER_INNODB_FT_LIMIT, 56	ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 118
ER_INNODB_FT_WRONG_DOCID_COLUMN, 56	ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 118
ER_INNODB_FT_WRONG_DOCID_INDEX, 56	ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 118
ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL, 281	ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 118
ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL, 281	ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 118
ER_INNODB_IDX_COLUMN_CNT_DIFF, 281	ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR, 118
ER_INNODB_ILLEGAL_COLON_IN_POOL, 260	ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 118
ER_INNODB_IMPORT_ERROR, 58	ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH_MAX_SIZE, 118
ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE, 138	ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT, 118
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQL, 261	ER_INNODB_REDO_LOG_ARCHIVE_START_FIELDS, 118
ER_INNODB_INDEX_CORRUPT, 58	ER_INNODB_TRX_XLATION_TABLE_OOM, 261
ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED, 153	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT, 551
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE, 153	ER_INNODB_UNDO_LOG_FULL, 66
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE, 146	ER_INNODB_UNKNOWN_COLLATION, 260
ER_INNODB_INTERNAL_INDEX, 281	ER_INNODB_UNREGISTERED_TRX_ACTIVE, 261
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE, 138	ER_INNODB_USE_MONITOR_GROUP_NAME, 282
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY, 260	ER_INSECURE_CHANGE_MASTER, 53
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOG, 518	ER_INSECURE_CHANGE_SOURCE, 53
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR, 260	ER_INSECURE_PLAIN_TEXT, 53
ER_INNODB_INVALID_MONITOR_COUNTER_NAME, 282	ER_INSERT_INFO, 9
ER_INNODB_INVALID_PAGE_SIZE, 260	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT, 47
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 261	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT, 46
ER_INNODB_IO_WRITE_ERROR_RETRYING, 561	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOGOFF, 47
ER_INNODB_IO_WRITE_FAILED, 561	ER_INSTALL_COMPONENT_SET_NULL_VALUE, 154
ER_INNODB_MANDATORY, 163	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE, 154
ER_INNODB_MAX_ROW_VERSION, 146	ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 141
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 282	ER_INSTALL_PLUGIN_CONFLICT_LOG, 572
ER_INNODB_MONITOR_IS_ENABLED, 282	ER_INTERNAL_ERROR, 58
ER_INNODB_NO_FT_TEMP_TABLE, 56	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED, 149
ER_INNODB_ONLINE_LOG_TOO_BIG, 56	ER_INVALID_ADMIN_ADDRESS, 520
ER_INNODB_OUT_OF_RESOURCES, 545	ER_INVALID_ARGUMENT_FOR_LOGARITHM, 66
ER_INNODB_PARTITION_TABLE_LOWERCASED, 262	ER_INVALID_ASSIGNMENT_TARGET, 141
ER_INNODB_PK_NOT_IN_MYSQL, 262	ER_INVALID_AUTHENTICATION_POLICY, 576
ER_INNODB_PK_ONLY_IN_MYSQL, 262	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE, 84
ER_INNODB_READ_ONLY, 63	ER_INVALID_BITWISE_OPERANDS_SIZE, 84
ER_INNODB_REDO_ARCHIVING_ENABLED, 133	ER_INVALID_CAST, 135
ER_INNODB_REDO_DISABLED, 133	ER_INVALID_CAST_POLYGON_RING_DIRECTION, 139
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 118	ER_INVALID_CAST_TO_GEOMETRY, 139
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 117	ER_INVALID_CAST_TO_JSON, 78
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 118	

ER_INVALID_CHARACTER_STRING, 23	ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN, 70
ER_INVALID_CHARSET_AND_DEFAULT_IS_MB, 190	ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH, 607
ER_INVALID_COLLATION_FOR_CHARSET, 267	ER_INVALID_SERVER_UPGRADE_NOT_LTS, 607
ER_INVALID_DD_OBJECT, 83	ER_INVALID_THREAD_ID, 98
ER_INVALID_DD_OBJECT_ID, 83	ER_INVALID_THREAD_PRIORITY, 97
ER_INVALID_DD_OBJECT_NAME, 83	ER_INVALID_TIME_ZONE_INTERVAL, 135
ER_INVALID_DEFAULT, 7	ER_INVALID_TLS_VERSION, 581
ER_INVALID_DEFAULT_UTF8MB4_COLLATION, 104	ER_INVALID_TYPE_FOR_JSON, 78
ER_INVALID_ENCRYPTION_OPTION, 81	ER_INVALID_USER_ATTRIBUTE_JSON, 133
ER_INVALID_ENCRYPTION_REQUEST, 116	ER_INVALID_USER_FOR_REGISTRATION, 142
ER_INVALID_ERROR_LOG_NAME, 173	ER_INVALID_USE_OF_FORCE_OPTION, 98
ER_INVALID_FIELD_SIZE, 66	ER_INVALID_USE_OF_NULL, 12
ER_INVALID_GEOJSON CRS NOT TOP LEVEL, 99	ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENT, 158
ER_INVALID_GEOJSON_MISSING_MEMBER, 70	ER_INVALID_VALUE_OF_BIND_ADDRESSES, 510
ER_INVALID_GEOJSON_UNSPECIFIED, 71	ER_INVALID_VCPU_ID, 97
ER_INVALID_GEOJSON_WRONG_TYPE, 71	ER_INVALID_VCPU_RANGE, 97
ER_INVALID_GROUP_FUNC_USE, 10	ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER, 551
ER_INVALID_INFO_IN_FRM, 190	ER_INVALID_YEAR_COLUMN_LENGTH, 58
ER_INVALID_INSTRUMENT, 162	ER_IO_ERR_LOG_INDEX_READ, 28
ER_INVALID_JSON_ATTRIBUTE, 133	ER_IO_READ_ERROR, 58
ER_INVALID_JSON_BINARY_DATA, 78	ER_IO_WRITE_ERROR, 58
ER_INVALID_JSON_CHARSET, 78	ER_IPSOCK_ERROR, 8
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 78	ER_IS_QUERY_INVALID_CLAUSE, 86
ER_INVALID_JSON_DATA, 70	ER_I_S_SKIPPED_TABLESPACE, 96
ER_INVALID_JSON_PATH, 78	ER_JSON_BAD_ONE_OR_ALL_ARG, 79
ER_INVALID_JSON_PATH_ARRAY_CELL, 79	ER_JSON_DOCUMENT_NULL_KEY, 79
ER_INVALID_JSON_PATH_CHARSET, 78	ER_JSON_DOCUMENT_TOO_DEEP, 79
ER_INVALID_JSON_PATH_WILDCARD, 78	ER_JSON_KEY_TOO_BIG, 78
ER_INVALID_JSON_TEXT, 78	ER_JSON_PARSE_ERROR, 176
ER_INVALID_JSON_TEXT_IN_PARAM, 78	ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILS, 127
ER_INVALID_JSON_TYPE, 119	ER_JSON_USED_AS_KEY, 78
ER_INVALID_JSON_VALUE_FOR_CAST, 79	ER_JSON_VACUOUS_PATH, 78
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX, 124	ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX, 124
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER, 143	ER_JSON_VALUE_TOO_BIG, 78
ER_INVALID_MFA_PLUGIN_SPECIFIED, 142	ER_JT_MAX_NESTED_PATH, 99
ER_INVALID_MULTIPLE_CLAUSES, 117	ER_JT_VALUE_OUT_OF_RANGE, 99
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP, 527	ER_KERBEROS_CREATE_USER, 141
ER_INVALID_NO_OF_ARGS, 92	ER_KEYCACHE_OOM, 166
ER_INVALID_ON_UPDATE, 23	ER_KEYRING_ACCESS_DENIED_ERROR, 82
ER_INVALID_OPTION_CHARACTERS, 87	ER_KEYRING_AWS_CMK_ID_NOT_SET, 324
ER_INVALID_OPTION_END_CHARACTER, 87	ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE, 324
ER_INVALID_OPTION_KEY, 87	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_C, 323
ER_INVALID_OPTION_KEY_VALUE_PAIR, 87	ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM, 323
ER_INVALID_OPTION_START_CHARACTER, 87	ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE, 324
ER_INVALID_OPTION_VALUE, 87	ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE, 323
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME, 212	
ER_INVALID_PARAMETER_USE, 134	
ER_INVALID_PLUGIN_FOR_REGISTRATION, 142	
ER_INVALID_PROPERTY_KEY, 523	
ER_INVALID_REPLICATION_TIMESTAMPS, 270	

ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS,	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING,
325	321
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY,	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING,
326	321
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY,	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE,
325	321
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE,	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR,
325	322
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR,	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE,
325	321
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEYRING,	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR,
325	322
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS,	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE,
324	322
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR,	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR,
324	322
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR,	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID,
324	322
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE,	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG,
323	322
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR,
325	315
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY,	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE,
326	316
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK,	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING,
326	317
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID,	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP,
322	317
ER_KEYRING_AWS_FAILED_TO_SET_REGION,	ER_KEYRING_FAILED_TO_GENERATE_KEY,
323	316
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE,	ER_KEYRING_FAILED_TO_GET_FILE_STAT,
325	317
ER_KEYRING_AWS_INCORRECT_FILE,	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT,
325	317
ER_KEYRING_AWS_INCORRECT_PROXY,	ER_KEYRING_FAILED_TO_REMOVE_FILE,
539	317
ER_KEYRING_AWS_INCORRECT_REGION,	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING,
325	318
ER_KEYRING_AWS_INIT_FAILURE,	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE,
324	316
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH,	ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA,
323	317
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH,	ER_KEYRING_FAILED_TO_TRUNCATE_FILE,
323	317
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER,	ER_KEYRING_FILE_INIT_FAILED,
324	315
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR,	ER_KEYRING_FILE_IO_ERROR,
82	317
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID,	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE,
316	317
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY,	ER_KEYRING_INCORRECT_FILE,
316	316
ER_KEYRING_COMPONENT_EXCEPTION,	ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT,
566	316
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR,	ER_KEYRING_INVALID_KEY_LENGTH,
566	315
ER_KEYRING_COMPONENT_NOT_INITIALIZED,	ER_KEYRING_INVALID_KEY_TYPE,
566	315
ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED,	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING,
321	318
ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED,	ER_KEYRING_LOGGER_ERROR_MSG,
321	299
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR,	ER_KEYRING_MIGRATE_FAILED,
322	499
	ER_KEYRING_MIGRATION_EXTRA_OPTIONS,
	301
	ER_KEYRING_MIGRATION_FAILED,
	285
	ER_KEYRING_MIGRATION_FAILURE,
	82
	ER_KEYRING_MIGRATION_STATUS,
	82

ER_KEYRING_MIGRATION_SUCCESSFUL, 285	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR, 81
ER_KEYRING_OCI_HTTP_REQUEST, 594	ER_KEYRING_UNKNOWN_ERROR, 317
ER_KEYRING_OCI_INVALID_JSON, 594	ER_KEY_COLUMN_DOES_NOT_EXISTS, 8
ER_KEYRING_OCI_PARSE_JSON, 594	ER_KEY_DOES_NOT_EXISTS, 14
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED, 319	ER_KEY_NOT_FOUND, 5
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS, 320	ER_KEY_PART_0, 29
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE, 319	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF, 19
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY, 320	ER_KILLED_THREADS_OF_PLUGIN, 207
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY, 319	ER_KILLING_THREAD, 206
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY, 319	ER_KILL_DENIED_ERROR, 9
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY, 320	ER_LATITUDE_OUT_OF_RANGE, 93
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUPLICATE, 318	ER_LCTN_CHANGED, 285
ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT, 319	ER_LCTN_NOT_FOUND, 499
ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER, 319	ER_LDAP_AUTH_CERTIFICATE_NAME, 365
ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID, 319	ER_LDAP_AUTH_COMMUNICATION_HOST_INFO, 368
ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE, 320	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER, 367
ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE, 319	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL, 367
ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY, 319	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED, 366
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY, 320	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER, 369
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE, 320	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL, 369
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE, 320	ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING, 363
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE, 321	ER_LDAP_AUTH_CONN_POOL_INITIALIZING, 363
ER_KEYRING_OKV_FAILED_TO_STORE_KEY, 320	ER_LDAP_AUTH_CONN_POOL_NOT_CREATED, 363
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY, 320	ER_LDAP_AUTH_CREATE_CONNECTION_KEY, 363
ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURATION, 318	ER_LDAP_AUTH_CREATING_LDAP_CONNECTION, 363
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG, 318	ER_LDAP_AUTH_DEINIT_FAILED, 362
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR, 318	ER_LDAP_AUTH_DELETING_CONNECTION_KEY, 367
ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER, 318	ER_LDAP_AUTH_DISTINGUISHED_NAME, 368
ER_KEYRING_OKV_INVALID_KEY_TYPE, 318	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION_KEY, 369
ER_KEYRING_OKV_KEY_MISMATCH, 321	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT, 369
ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED, 581	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CONFIGURATION, 363
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR, 316	ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION, 362
	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY, 365
	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_REALTIME, 365
	ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION, 369
	ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLAINTEXT, 366

ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEFAULT_STATE, 365	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 368
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INITIAL_STATE, 365	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 364
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING, 365	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND, 367
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 365	ER_LDAP_AUTH_SETTING_USERNAME, 364
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 369	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, 362
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET, 363	ER_LDAP_AUTH_STARTED_FOR_USER, 368
ER_LDAP_AUTH_FREEING_CONNECTION, 367	ER_LDAP_AUTH_STARTING_TLS, 367
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL, 366	ER_LDAP_AUTH_TLS_CONF, 363
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED, 525	ER_LDAP_AUTH_TLS_CONNECTION, 363
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE, 524	ER_LDAP_AUTH_USER_AUTH_DATA, 364
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS, 524	ER_LDAP_AUTH_USER_BIND_FAILED, 369
ER_LDAP_AUTH_GRP_IS_FULL_DN, 364	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS, 364
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 525	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED, 369
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 525	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO, 364
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 524	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND, 513
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 364	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES, 364
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO, 524	ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP, 364
ER_LDAP_AUTH_INFO_FOR_USER, 364	ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED, 526
ER_LDAP_AUTH_INIT_FAILED, 368	ER_LDAP_EMPTY_USERDN_PASSWORD, 535
ER_LDAP_AUTH_LDAPS, 525	ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE, 526
ER_LDAP_AUTH_LDAP_INFO_NULL, 367	ER_LDAP_MAPPING_EMPTY_MAPPING, 525
ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT, 366	ER_LDAP_MAPPING_GETTING_NEXT_MAPPING, 526
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 366	ER_LDAP_MAPPING_GET_USER_PROXY, 525
ER_LDAP_AUTH_METHOD_TO_CLIENT, 368	ER_LDAP_MAPPING_INFO, 525
ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 365	ER_LDAP_MAPPING_IS_QUOTE, 527
ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 368	ER_LDAP_MAPPING_NON_DESIRED_STATE, 527
ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 366	ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP, 526
ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 367	ER_LDAP_MAPPING_PARSING_CURRENT_STATE, 526
ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 362	ER_LDAP_MAPPING_PARSING_ERROR, 527
ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 369	ER_LDAP_MAPPING_PARSING_MAPPING_INFO, 526
ER_LDAP_AUTH_POOL_REINITIALIZING, 363	ER_LDAP_MAPPING_PROCESS_DELIMITER, 526
ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL, 366	ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND, 526
ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 368	ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND, 526
ER_LDAP_AUTH_SASL_PROCESS_SASL, 368	ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA, 526
	ER_LDAP_MAPPING_PROCESS_MAPPING, 525
	ER_LDAP_MAPPING_TRIMMING_SPACES, 527
	ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP, 525

ER_LIMITED_PART_RANGE, 37	ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_U
ER_LOAD_BULK_DATA_FAILED, 153	170
ER_LOAD_BULK_DATA_UNSORTED, 151	ER_LOWER_CASE_TABLE_NAMES_USING_0,
ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL,	170
153	ER_LOWER_CASE_TABLE_NAMES_USING_2,
ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_L	170,
598	ER_MALFORMED_GTID_SET_ENCODING, 54
ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD,	ER_MALFORMED_GTID_SET_SPECIFICATION,
153	54
ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD,	ER_MALFORMED_GTID_SPECIFICATION, 54
598	ER_MALFORMED_PACKET, 59
ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_W	ER_MANDATORY_ROLE, 94
176	ER_MASTER, 15
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR,	ER_MASTER_DELAY_VALUE_OUT_OF_RANGE,
30	50
ER_LOAD_INFO, 9	ER_MASTER_FATAL_ERROR_READING_BINLOG,
ER_LOCAL_VARIABLE, 18	19
ER_LOCKING_SERVICE_DEADLOCK, 77	ER_MASTER_HAS_PURGED_REQUIRED_GTIDS,
ER_LOCKING_SERVICE_TIMEOUT, 77	55
ER_LOCKING_SERVICE_WRONG_NAME, 77	ER_MASTER_INFO, 16
ER_LOCK_ABORTED, 47	ER_MASTER_KEY_ROTATION_BINLOG_FAILED,
ER_LOCK_DEADLOCK, 17	80
ER_LOCK_NOWAIT, 88	ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_S
ER_LOCK_ORDER_DEPENDENCIES_SYNTAX,	80
536	ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE,
ER_LOCK_ORDER_FAILED_READ_FILE, 535	81
ER_LOCK_ORDER_FAILED_WRITE_FILE, 535	ER_MASTER_NET_READ, 15
ER_LOCK_ORDER_INIT_FAILED, 534	ER_MASTER_NET_WRITE, 15
ER_LOCK_ORDER_MESSAGE, 535	ER_MAXVALUE_IN_VALUES_IN, 44
ER_LOCK_ORDER_SCANNER_SYNTAX, 536	ER_MAX_PREPARED_STMT_COUNT_REACHED,
ER_LOCK_OR_ACTIVE_TRANSACTION, 15	33
ER_LOCK_REFUSED_BY_ENGINE, 80	ER_MDL_OUT_OF_RESOURCES, 133
ER_LOCK_TABLE_FULL, 17	ER_MECAB_CHARSET_LOADED, 289
ER_LOCK_WAIT_TIMEOUT, 17	ER_MECAB_CREATE_LATTICE_FAILED, 289
ER_LOG_BIN_BETTER_WITH_NAME, 171	ER_MECAB_CREATING_MODEL, 288
ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP	ER_MECAB_FAILED_TO_CREATE_MODEL, 289
606	ER_MECAB_FAILED_TO_CREATE_TRIGGER, 289
ER_LOG_CANNOT_WRITE, 156	ER_MECAB_NOT_SUPPORTED, 288
ER_LOG_CANNOT_WRITE_EXTENDED, 539	ER_MECAB_NOT_VERIFIED, 288
ER_LOG_COMPONENT_CANNOT_INIT, 561	ER_MECAB_OOM_WHILE_PARSING_TEXT, 289
ER_LOG_COMPONENT_FLUSH_FAILED, 573	ER_MECAB_PARSE_FAILED, 289
ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE,	ER_MECAB_UNSUPPORTED_CHARSET, 289
170	ER_MESSAGE_AND_STATEMENT, 46
ER_LOG_FILE_CANNOT_OPEN, 306	ER_MFA_METHODS_IDENTICAL, 143
ER_LOG_FILE_INVALID, 170	ER_MFA_METHODS_INVALID_ORDER, 143
ER_LOG_GENERAL_CANNOT_OPEN, 156	ER_MFA_METHOD_EXISTS, 142
ER_LOG_IN_USE, 28	ER_MFA_METHOD_NOT_EXISTS, 142
ER_LOG_OUTPUT_CONTRADICTION, 169	ER_MFA_PLUGIN_NOT_LOADED, 580
ER_LOG_PRINTF_MSG, 283	ER_MFA_USER_ATTRIBUTES_CORRUPT, 580
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_N	ER_MILLISECOND_TIMER_IS_NOT_AVAILABLE,
543	280
ER_LOG_PURGE_NO_FILE, 41	ER_MIGRATE_TABLE_TO_DD_OOM, 546
ER_LOG_PURGE_UNKNOWN_ERR, 28	ER_MISPLACED_INTO, 130
ER_LOG_SLOW_CANNOT_OPEN, 156	ER_MISSING_ACL_SYSTEM_TABLE, 271
ER_LOG_SYSLOG_CANNOT_OPEN, 155	ER_MISSING_CURRENT_PASSWORD, 123
ER_LOG_SYSLOG_FACILITY_FAIL, 155	ER_MISSING_GRANT_SYSTEM_TABLE, 271
ER_LONGITUDE_OUT_OF_RANGE, 93	ER_MISSING_HA_CREATE_OPTION, 66
	ER_MISSING_JSON_TABLE_VALUE, 98

ER_MISSING_JSON_VALUE, 131	ER_M_BIGGER_THAN_D, 31
ER_MISSING_KEY, 64	ER_NAME_BECOMES_EMPTY, 34
ER_MISSING_SKIP_REPLICA, 22	ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE, 280
ER_MISSING_SKIP_SLAVE, 22	ER_NATIVE_FCT_NAME_COLLISION, 40
ER_MISSING_TABLESPACE_FILE, 94	ER_NDBINFO_NOT_UPGRADING_SCHEMA, 550
ER_MIXING_NOT_ALLOWED, 18	ER_NDBINFO_UPGRADING_SCHEMA, 550
ER_MIX_HANDLER_ERROR, 35	ER_NDBINFO_UPGRADING_SCHEMA_FAIL, 550
ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 12	ER_NDB_BINLOG_BLOB_REQUIRES_PK, 237
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 73	ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX, 235
ER_MTA_CANT_PARALLEL, 52	ER_NDB_BINLOG_CANT_CREATE_BLOB, 238
ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS, 57	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB, 237
ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 62	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_CANT_CREATE_EVENT_IN_DB, 237
ER_MTA_FEATURE_IS_NOT_SUPPORTED, 52	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED, 238
ER_MTA_INCONSISTENT_DATA, 53	ER_NDB_BINLOG_CANT_CREATE_PURGE_THD, 260
ER_MTA_RECOVERY_FAILURE, 57	ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA, 232
ER_MTA_RESET_WORKERS, 57	ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB, 238
ER_MTA_UPDATED_DBS_GREATER_MAX, 52	ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_R, 240
ER_MTR_MSG_1, 574	ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX, 235
ER_MTS_CANT_PARALLEL, 52	ER_NDB_BINLOG_CANT_RELEASE_SLOCK, 233
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS, 57	ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE, 234
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 62	ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX, 235
ER_MTS_FEATURE_IS_NOT_SUPPORTED, 52	ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS, 231
ER_MTS_INCONSISTENT_DATA, 52	ER_NDB_BINLOG_CLUSTER_FAILURE, 239
ER_MTS_RECOVERY_FAILURE, 57	ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED, 240
ER_MTS_RESET_WORKERS, 57	ER_NDB_BINLOG_CLUSTER_RESTARTED_RESET_MASTER, 239
ER_MTS_UPDATED_DBS_GREATER_MAX, 52	ER_NDB_BINLOG_CREATE_TABLE_EVENT, 209
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME, 128	ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED, 237
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR, 35	ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO, 237
ER_MULTIPLE_INTO_CLAUSES, 129	ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED, 238
ER_MULTIPLE_JSON_VALUES, 131	ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS, 238
ER_MULTIPLE_PRI_KEY, 7	ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO, 237
ER_MULTI_UPDATE_KEY_CONFLICT, 48	ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT, 241
ER_MUST_CHANGE_EXPIRED_PASSWORD, 267	ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK, 241
ER_MUST_CHANGE_PASSWORD, 58	ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT, 241
ER_MUST_CHANGE_PASSWORD_LOGIN, 61	ER_NDB_BINLOG_ERROR_INFO_FROM_DA, 209
ER_MYINIT_FAILED, 168	
ER_MYISAM_CHECK_METHOD_ERROR, 283	
ER_MYISAM_CRASHED_ERROR, 283	
ER_MYISAM_CRASHED_ERROR_IN, 178	
ER_MYISAM_CRASHED_ERROR_IN_THREAD, 178	
ER_MYSQLBACKUP_CLIENT_MSG, 146	
ER_MYSQLBACKUP_MSG, 540	
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD, 521	
ER_MY_MALLOC_GETPROCADDRESS_FAILED, 583	
ER_MY_MALLOC_LOADLIBRARY_FAILED, 582	
ER_MY_MALLOC_USING_JEMALLOC, 582	
ER_MY_MALLOC_USING_STD_MALLOC, 582	
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR, 246	

ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATION, 209	ER_NDB_BINLOG_RESTARTING_LOG_AT_EPOCH, 240
ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATION, 209	ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE, 239
ER_NDB_BINLOG_FAILED_TO_GET_TABLE, 237	ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT, 239
ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT, 210	ER_NDB_BINLOG_MIXED, 239
ER_NDB_BINLOG_GENERIC_MESSAGE, 236	ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_FAIL, 236
ER_NDB_BINLOG_GOT_DIST_PRIV_EVENT_FLUSHING, 234	ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED, 236
ER_NDB_BINLOG_GOT_SCHEMA_EVENT, 234	ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX, 236
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILURE, 235	ER_NDB_CANT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION_METADATA, 251
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENT, 239	ER_NDB_CANT_ALLOC_GLOBAL_NDB_OBJECT, 251
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG, 241	ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION, 251
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONNECTION, 240	ER_NDB_CANT_ALLOC_NDB_CLUSTER_CONNECTION, 251
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING, 240	ER_NDB_CANT_FIND_TABLE, 233
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED, 238	ER_NDB_CANT_PARSE_NDB_CLUSTER_CONNECTION_INFO, 250
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING, 236	ER_NDB_CANT_START_CONNECT_THREAD, 252
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRED, 236	ER_NDB_CLEAR_SHARE_INFO, 230
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY, 211	ER_NDB_CLEAR_SLOCK_INFO, 233
ER_NDB_BINLOG_NDB_TABLES_WRITABLE, 240	ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL, 231
ER_NDB_BINLOG_NOT_LOGGING, 237	ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY, 231
ER_NDB_BINLOG_ONLINE_ALTER_RENAME, 233	ER_NDB_CLUSTER_FREE_SHARE_INFO, 211
ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETED, 234	ER_NDB_CLUSTER_GENERIC_MESSAGE, 197
ER_NDB_BINLOG_OPENING_INDEX, 235	ER_NDB_CLUSTER_GET_SHARE_INFO, 210
ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCE, 241	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYED, 211
ER_NDB_BINLOG_REMAINING_OPEN_TABLES, 241	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO, 211
ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO, 241	ER_NDB_CLUSTER_OOM_THD_NDB, 211
ER_NDB_BINLOG_RENAME_EVENT, 209	ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED, 211
ER_NDB_BINLOG_REPLY_TO, 233	ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO, 211
ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START, 239	ER_NDB_CLUSTER_SCHEMA_INFO, 197
ER_NDB_BINLOG_SHUTDOWN_DETECTED, 240	ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGS, 197
ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE, 233	ER_NDB_COLUMN_DEFAULTS_DIFFER, 207
ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINED_IN_BINLOG, 234	ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT, 207
ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE, 234	ER_NDB_CONFLICT_FN_PARSE_ERROR, 237
ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE, 233	ER_NDB_CONFLICT_FN_SETUP_ERROR, 237
ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION, 234	ER_NDB_CONFLICT_FN_SETUP_ERROR, 237
ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE, 234	ER_NDB_GENERIC_MESSAGE, 236
	ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE, 239
	ER_NDB_CPU_MASK_TOO_SHORT, 252
	ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO, 238
	ER_NDB_CREATING_SHARE_IN_OPEN, 210
	ER_NDB_CREATING_TABLE, 230

ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH, 233	ER_NDB_SCHEMA_DISTRIBUTION_FAILED, 232
ER_NDB_DISCARDING_EVENT_NO_OBJ, 233	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE, 232
ER_NDB_DISCONNECT_INFO, 207	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE, 232
ER_NDB_DISCOVERED_MISSING_DB, 230	ER_NDB_SCHEMA_GENERIC_MESSAGE, 204
ER_NDB_DISCOVERED_REMAINING_DB, 231	ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE, 236
ER_NDB_DISTRIBUTED_INFO, 232	ER_NDB_SHARE_ALREADY_EXISTS, 210
ER_NDB_DISTRIBUTING_ERR, 263	ER_NDB_SKIP_POOLED_SLAVE, 231
ER_NDB_DISTRIBUTION_COMPLETE, 232	ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_RESOLUTION_POOL_NODEIDS, 209
ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS, 251	ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE, 209
ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS, 250	ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSACTION_MASK, 208
ER_NDB_ERROR_IN_GET_AUTO_INCREMENT, 210	ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE, 208
ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE, 208	ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO, 209
ER_NDB_FAILED_TO_SET_UP_TABLE, 231	ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO, 196
ER_NDB_FIELD_INFO, 207	ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION, 196
ER_NDB_FLUSHING_TABLE_INFO, 230	ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE, 209
ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT, 208	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO, 207
ER_NDB_GENERIC_ERROR, 252	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN, 207
ER_NDB_HANDLE_TRAILING_SHARE_INFO, 210	ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN, 196
ER_NDB_IGNOREING_UNKNOWN_EVENT, 235	ER_NDB_SLAVE_PARALLEL_WORKERS, 263
ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD_CPU_MASK, 211	ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED, 196
ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO, 197	ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH, 196
ER_NDB_INFO_FAILED_TO_INIT_NDBINFO, 197	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS, 196
ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE, 197	ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS_CONNECTION_POOL_NODEIDS, 196
ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISABLED, 210	ER_NDB_SLAVE_TOO_MANY_RETRIES, 209
ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS, 251	ER_NDB_STARTING_CONNECT_THREAD, 252
ER_NDB_LOG_ENTRY, 260	ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT, 235
ER_NDB_LOG_ENTRY_WITH_PREFIX, 260	ER_NDB_TABLES_NOT_READY, 174
ER_NDB_MISMATCH_IN_FRM_DISCOVERING, 231	ER_NDB_TABLE_IS_NOT_DISTRIBUTED, 230
ER_NDB_MISSING_FRM_DISCOVERING, 231	ER_NDB_TABLE_OPENED_READ_ONLY, 210
ER_NDB_MISSING_FRM_DISCOVERING, 231	ER_NDB_THREAD_TIMED_OUT, 230
ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONNECTION_POOL_NODEIDS, 251	ER_NDB_TIMED_OUT_IN_DROP_TABLE, 238
ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO, 207	ER_NDB_TIMEOUT_WHILE_DISTRIBUTING, 232
ER_NDB_NODE_INFO, 252	ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD_CONNECTION_POOL_NODEIDS, 210
ER_NDB_NOT_WAITING_FOR_DISTRIBUTING, 232	ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHE, 210
ER_NDB_NUMBER_OF_CHANNELS, 263	ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR, 236
ER_NDB_OOM_GET_NDB_BLOBS_VALUE, 230	ER_NDB_UNEXPECTED_RENAME_TYPE, 209
ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER, 208	
ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNECTION_POOL_SIZE, 251	
ER_NDB_QUERY_FAILED, 206	
ER_NDB_REMAINING_OPEN_TABLES, 239	
ER_NDB_REMAINING_OPEN_TABLE_INFO, 239	
ER_NDB_REPLICATION_SCHEMA_ERROR, 42	

ER_NDB_USING_NODEID, 251	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE, 566
ER_NDB_USING_NODEID_LIST, 251	ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR, 566
ER_NDB_UTIL_THREAD_OOM, 211	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED, 567
ER_NDB_WAITING_INFO, 231	ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 566
ER_NDB_WAITING_INFO_WITH_MAP, 231	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR, 567
ER_NEED_FILE_INSTEAD_OF_DIR, 171	ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND, 566
ER_NEED_LOG_BIN, 171	ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED, 567
ER_NEED_REPREPARE, 41	ER_NOTE_KEYRING_COMPONENT_STORE_FAILED, 567
ER_NETWORK_NAMESPACES_NOT_SUPPORTED, 532	ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_SIZE, 567
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG, 532	ER_NOT_ALLOWED_COMMAND, 13
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_VIRTUAL_IP_ADDRESS, 566	ER_NOT_ALLOWED_WITH_START_TRANSACTION, 133
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE, 500	ER_NOT_FORM_FILE, 5
ER_NET_ERROR_ON_WRITE, 13	ER_NOT_HINT_UPDATABLE_VARIABLE, 95
ER_NET_FCNTL_ERROR, 13	ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS, 102
ER_NET_OK_PACKET_TOO_LARGE, 70	ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS, 93
ER_NET_PACKETS_OUT_OF_ORDER, 13	ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS, 102
ER_NET_PACKET_TOO_LARGE, 13	ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS, 306
ER_NET_READ_ERROR, 13	ER_NOT_KEYFILE, 5
ER_NET_READ_ERROR_FROM_PIPE, 13	ER_NOT_RIGHT_NOW, 168
ER_NET_READ_INTERRUPTED, 13	ER_NOT_SUPPORTED_AUTH_MODE, 20
ER_NET_UNCOMPRESS_ERROR, 13	ER_NOT_SUPPORTED_YET, 19
ER_NET_WAIT_ERROR, 533	ER_NOT_VALID_PASSWORD, 58
ER_NET_WAIT_ERROR2, 568	ER_NO_ACCESS_TO_NATIVE_FCT, 88
ER_NET_WRITE_INTERRUPTED, 13	ER_NO_BINARY_LOGGING, 28
ER_NEW_ABORTING_CONNECTION, 15	ER_NO_BINLOG_ERROR, 36
ER_NO, 3	ER_NO_CSV_NO_LOG_TABLES, 170
ER_NONEXISTING_GRANT, 12	ER_NO_DB_ERROR, 6
ER_NONEXISTING_PROC_GRANT, 29	ER_NO_DEFAULT, 19
ER_NONEXISTING_TABLE_GRANT, 13	ER_NO_DEFAULT_FOR_FIELD, 27
ER_NONPOSITIVE_RADIUS, 103	ER_NO_DEFAULT_FOR_VIEW_FIELD, 30
ER_NONUNIQ_TABLE, 7	ER_NO_ERROR_LOG_PARSER_CONFIGURED, 566
ER_NONUPDATEABLE_COLUMN, 26	ER_NO_OR_TYPE, 566
ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT, 114	ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_START, 566
ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN, 75	ER_NO_FT_MATERIALIZED_SUBQUERY, 66
ER_NON_GROUPING_FIELD_USED, 33	ER_NO_PARTITION_FOR_GIVEN_VALUE, 37
ER_NON_INSERTABLE_TABLE, 34	ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 40
ER_NON_RO_SELECT_DISABLE_TIMER, 67	ER_NO_PARTS_ERROR, 35
ER_NON_UNIQ_ERROR, 6	ER_NO_PATH_FOR_SHARED_LIBRARY, 507
ER_NON_UPDATABLE_TABLE, 23	ER_NO_PERMISSION_TO_CREATE_USER, 17
ER_NORMAL_SERVER_SHUTDOWN, 499	ER_NO_REFERENCED_ROW, 18
ER_NORMAL_SHUTDOWN, 8	
ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME, 594	
ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS, 602	
ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS, 602	
ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER, 566	
ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY, 566	

ER_NO_REFERENCED_ROW_2, 32	ER_OPTION_PREVENTS_STATEMENT, 23
ER_NO_SECURE_TRANSPORTS_CONFIGURED, 79	ER_OPT_WRONG_TREE, 155
ER_NO_SESSION_TEMP, 122	ER_OUTOFMEMORY, 5
ER_NO_SUCH_DB, 83	ER_OUT_OF_RESOURCES, 5
ER_NO_SUCH_INDEX, 8	ER_OUT_OF_SORTMEMORY, 5
ER_NO_SUCH_TABLE, 13	ER_PAGE_TRACKING_CANNOT_PURGE, 113
ER_NO_SUCH_THREAD, 9	ER_PAGE_TRACKING_NOT_STARTED, 113
ER_NO_SUCH_USER, 32	ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 113
ER_NO_SUPER_WITHOUT_USER_PLUGIN, 187	ER_PARSER_TRACE, 155
ER_NO_SYSTEM_SCHEMA_ACCESS, 86	ER_PARSE_ERROR, 7
ER_NO_SYSTEM_TABLESPACE_ACCESS, 86	ER_PARSE_ERROR_IN_DIGEST_FN, 99
ER_NO_SYSTEM_TABLE_ACCESS, 87	ER_PARSING_VIEW, 161
ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE, 87	ER_PARTITION_REVOKE_EXISTS, 123
ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE, 87	ER_PARTITION_REVOKE_AND_DB_GRANT_BOTH_EXISTS, 124
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE, 87	ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 35
ER_NO_SYSTEM_VIEW_ACCESS, 93	ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 51
ER_NO_TABLES_USED, 9	ER_PARTITION_COLUMN_LIST_ERROR, 44
ER_NO_THD_NO_UUID, 161	ER_PARTITION_CONST_DOMAIN_ERROR, 39
ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA, 33	ER_PARTITION_ENTRY_ERROR, 35
ER_NO_UNIQUE_LOGFILE, 9	ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 50
ER_NPIPE_CANT_CREATE, 262	ER_PARTITION_EXCHANGE_FOREIGN_KEY, 51
ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR, 195	ER_PARTITION_EXCHANGE_PART_TABLE, 51
ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR, 195	ER_PARTITION_EXCHANGE_TEMP_TABLE, 51
ER_NPIPE_PIPE_ALREADY_IN_USE, 195	ER_PARTITION_FIELDS_TOO_LONG, 45
ER_NULL_COLUMN_IN_INDEX, 11	ER_PARTITION_FUNCTION_FAILURE, 37
ER_NULL_IN_VALUES_LESS_THAN, 39	ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 39
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 79	ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 35
ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION, 541	ER_PARTITION_HANDLER_ADMIN_MSG, 282
ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION, 543	ER_PARTITION_INSTEAD_OF_SUBPARTITION, 51
ER_OLD_FILE_FORMAT, 33	ER_PARTITION_MAXVALUE_ERROR, 34
ER_OLD_KEYFILE, 5	ER_PARTITION_MERGE_ERROR, 39
ER_OLD_PASSWORDS_NO_MIDDLE_GROUND, 163	ER_PARTITION_MGMT_ON_NONPARTITIONED, 36
ER_OLD_TEMPORALS_UPGRADED, 63	ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_DROP_STATEMENT, 262
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT, 50	ER_PARTITION_NAME, 43
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326, 100	ER_PARTITION_NOT_DEFINED_ERROR, 35
ER_ONLY INTEGERS ALLOWED, 39	ER_PARTITION_NO_TEMPORARY, 38
ER_ONLY_ON_RANGE_LIST_PARTITION, 36	ER_PARTITION_REQUIRES_VALUES_ERROR, 34
ER_OOM, 168	ER_PARTITION_WRONG_NO_PART_ERROR, 34
ER_OOM_SAVE_GTIDS, 499	ER_PARTITION_WRONG_NO_SUBPART_ERROR, 34
ER_OPEN_AS_READONLY, 5	ER_PARTITION_WRONG_VALUES_ERROR, 34
ER_OPEN_ROLE_TABLES, 85	ER_PART_EXPR_TOO_LONG, 94
ER_OPERAND_COLUMNS, 20	ER_PASSWORD_ANONYMOUS_USER, 12
ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY, 141	ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE, 123
ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING, 146	ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_PLUGIN, 99

ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 66	ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 207
ER_PASSWORD_FORMAT, 59	ER_PLUGIN_DISABLED, 246
ER_PASSWORD_NOT_ALLOWED, 12	ER_PLUGIN_EXCEPTION_OPERATION_FAILED, 599
ER_PASSWORD_NO_MATCH, 12	ER_PLUGIN_FAILED_DEINITIALIZATION, 244
ER_PATH_IN_DATADIR, 95	ER_PLUGIN_FAILED_TO_OPEN_TABLE, 505
ER_PATH_LENGTH, 46	ER_PLUGIN_FAILED_TO_OPEN_TABLES, 505
ER_PERFORMANCE_SCHEMA_VERSION_CHANGE, 608	ER_PLUGIN_FORCING_SHUTDOWN, 245
ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP_FAILED, 268	ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES, 246
ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, 268	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION, 244
ER_PERFSCHEMA_INIT_FAILED, 172	ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN, 245
ER_PERFSCHEMA_TABLES_INIT_FAILED, 269	ER_PLUGIN_INIT_FAILED, 175
ER_PERSISTED_VARIABLES_DECRYPTION_FAILED, 582	ER_PLUGIN_INSTALL_ERROR, 514
ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED, 582	ER_PLUGIN_INVALID_TABLE_DEFINITION, 572
ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED, 582	ER_PLUGIN_IS_NOT_LOADED, 37
ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT, 582	ER_PLUGIN_IS_PERMANENT, 48
ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED, 582	ER_PLUGIN_LOAD_OPTIONS_IGNORED, 542
ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND, 582	ER_PLUGIN_LOAD_PARAMETER_TOO_LONG, 245
ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 269	ER_PLUGIN_LOADED_TOO_EARLY, 117
ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 94	ER_PLUGIN_NOT_EARLY_DUP, 533
ER_PERSIST_OPTION_HOST_TRUNCATED, 533	ER_PLUGIN_NO_INSTALL, 50
ER_PERSIST_OPTION_STATUS, 306	ER_PLUGIN_NO_INSTALL_DUP, 533
ER_PERSIST_OPTION_USER_TRUNCATED, 533	ER_PLUGIN_NO_UNINSTALL, 49
ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_REQUIRED, 279	ER_PLUGIN_OOM, 246
ER_PFS_MALLOC_ARRAY_OOM, 280	ER_PLUGIN_PARSING_OPTIONS_FAILED, 246
ER_PFS_MALLOC_ARRAY_OVERFLOW, 280	ER_PLUGIN_REGISTRATION_DONE, 142
ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED, 273	ER_PLUGIN_REGISTRATION_FAILED, 245
ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE, 508	ER_PLUGIN_REQUIRES_REGISTRATION, 142
ER_PID_FILE_PRIV_DIRECTORY_INSECURE, 370	ER_PLUGIN_SHUTTING_DOWN_PLUGIN, 244
ER_PK_INDEX_CANT_BE_INVISIBLE, 84	ER_PLUGIN_UNINSTALL_ERROR, 514
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED, 77	ER_PLUGIN_UNKNOWN_VARIABLE_TYPE, 245
ER_PLUGIN_BAD_OPTIONS, 246	ER_PLUGIN_VARIABLE_MISSING_NAME, 245
ER_PLUGIN_CANNOT_BE_UNINSTALLED, 64	ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL, 246
ER_PLUGIN_CANT_LOAD, 245	ER_PLUGIN_VARIABLE_SET_READ_ONLY, 245
ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 245	ER_POINTLESS_WITHOUT_SLOWLOG, 163
ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 246	ER_POLYGON_TOO_LARGE, 105
ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES, 305	ER_PREPARE_FOR_PRIMARY_ENGINE, 573
ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE, 305	ER_PREPARE_FOR_SECONDARY_ENGINE, 527
ER_PLUGIN_DELETE_BUILTIN, 42	ER_PREVENTS_VARIABLE_WITHOUT_RBR, 74
	ER_PRIMARY_CANT_HAVE_NULL, 14
	ER_PRIVILEGE_DEREGISTRATION, 604
	ER_PRIVILEGE_REGISTRATION, 604
	ER_PRIVILEGE_SYSTEM_INIT_FAILED, 269
	ER_PROCAccess_DENIED_Error, 28
	ER_PROC_AUTO_GRANT_FAIL, 29
	ER_PROC_AUTO_REVOKE_FAIL, 29
	ER_PROTOCOL_COMPRESSION_RESET_LOG, 245
	ER_PS_MANY_PARAM, 28
	ER_PS_NO_RECURSION, 32
	ER_QUERY_CACHE_DISABLED, 44
	ER_QUERY_INTERRUPTED, 25

ER_QUERY_ON_FOREIGN_DATA_SOURCE, 31
 ER_QUERY_TIMEOUT, 67
 ER_RANGE_NOT_INCREASING_ERROR, 35
 ER_READING_TABLE_FAILED, 176
 ER_READY, 8
 ER_READ_LOG_EVENT_FAILED, 277
 ER_READ_ONLY_MODE, 59
 ER_READ_ONLY_TRANSACTION, 17
 ER REALLY_RUN_AS_ROOT, 167
 ER_RECORD_FILE_FULL, 10
 ER_RECOVERING_TABLE, 247
 ER_REDUCED_DBLWR_FILE_CORRUPTED, 606
 ER_REDUCED_DBLWR_PAGE_FOUND, 606
 ER_REFERENCED_TRG_DOES_NOT_EXIST, 65
 ER_REGEX_BAD_ESCAPE_SEQUENCE, 101
 ER_REGEX_BAD_INTERVAL, 101
 ER_REGEX_BUFFER_OVERFLOW, 100
 ER_REGEX_ERROR, 12
 ER_REGEX_ILLEGAL_ARGUMENT, 100
 ER_REGEX_INDEX_OUTOFBOUNDS_ERROR, 101
 ER_REGEX_INTERNAL_ERROR, 101
 ER_REGEX_INVALID_BACK_REF, 101
 ER_REGEX_INVALID_CAPTURE_GROUP_NAME, 122
 ER_REGEX_INVALID_FLAG, 123
 ER_REGEX_INVALID_RANGE, 102
 ER_REGEX_LOOK_BEHIND_LIMIT, 101
 ER_REGEX_MAX_LT_MIN, 101
 ER_REGEX_MISMATCHED_PAREN, 101
 ER_REGEX_MISSING_CLOSE_BRACKET, 101
 ER_REGEX_MISSING_FILE, 145
 ER_REGEX_MISSING_ICU_DATADIR, 580
 ER_REGEX_MISSING_RESOURCE, 144
 ER_REGEX_PATTERN_TOO_BIG, 102
 ER_REGEX_RULE_SYNTAX, 101
 ER_REGEX_STACK_OVERFLOW, 102
 ER_REGEX_STRING_NOT_TERMINATED, 100
 ER_REGEX_TIME_OUT, 102
 ER_REGEX_UNIMPLEMENTED, 101
 ER_REGEX_NUMBER_TOO_BIG, 136
 ER_RELAY_LOG_FAIL, 28
 ER_RELAY_LOG_INIT, 28
 ER_RELAY_LOG_SPACE_LIMIT_DISABLED, 510
 ER_RELOAD_KEYRING_FAILURE, 139
 ER_REMOVED_SPACES, 33
 ER_RENAMED_NAME, 43
 ER_RENAME_ROLE, 85
 ER_REORG_HASH_ONLY_ON_SAME_NO, 36
 ER_REORG_NO_PARAM_ERROR, 36
 ER_REORG_OUTSIDE_RANGE, 36
 ER_REORG_PARTITION_NOT_EXIST, 36
 ER_REPLACE_INACCESSIBLE_ROWS, 70
 ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GID, 596
 ER_REPLICA_AM_INIT_REPOSITORY, 62
 ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME, 563

ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_G, 563
 ER_REPLICA_CANT_CREATE_CONVERSION, 46
 ER_REPLICA_CANT_USE_TEMPDIR, 229
 ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 228
 ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 71
 ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 66
 ER_REPLICA_CHANNEL_MUST_STOP, 72
 ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 71
 ER_REPLICA_CHANNEL_NOT_RUNNING, 72
 ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 78
 ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 73
 ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 73
 ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 72
 ER_REPLICA_CHANNEL_WAS_RUNNING, 72
 ER_REPLICA_CM_INIT_REPOSITORY, 62
 ER_REPLICA_CONFIGURATION, 56
 ER_REPLICA_CORRUPT_EVENT, 41
 ER_REPLICA_CREATE_EVENT_FAILURE, 500
 ER_REPLICA_FATAL_ERROR, 500
 ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 64
 ER_REPLICA_HEARTBEAT_FAILURE, 500
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 42
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 48
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 48
 ER_REPLICA_IGNORED_SSL_PARAMS, 22
 ER_REPLICA_IGNORED_TABLE, 19
 ER_REPLICA_IGNORE_SERVER_IDS, 44
 ER_REPLICA_INCIDENT, 501
 ER_REPLICA_KILLED_AFTER_RECONNECT, 278
 ER_REPLICA_MAX_CHANNELS_EXCEEDED, 72
 ER_REPLICA_MULTIPLE_CHANNELS_CMD, 71
 ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 71
 ER_REPLICA_NOT_RUNNING, 16
 ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 279
 ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 105
 ER_REPLICA_RECONNECT_FAILED, 278
 ER_REPLICA_RELAY_LOG_PURGE_FAILED, 270
 ER_REPLICA_RELAY_LOG_READ_FAILURE, 501
 ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 270
 ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 501

ER_REPLICA_SILENT_RETRY_TRANSACTION, 58	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED, 274
ER_REPLICA_SOURCE_COM_FAILURE, 501	ER_RES_GRP_INVALID_THREAD_PRIORITY, 274
ER_REPLICA_SQL_THREAD_MUST_STOP, 66	ER_RES_GRP_INVALID_VCPU_ID, 284
ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTID, 194	ER_RES_GRP_INVALID_VCPU_RANGE, 284
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTID, 193	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED, 273
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTID, 194	ER_RES_GRP_SET_THR_AFFINITY_FAILED, 273
ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED, 194	ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED, 273
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION, 193	ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED, 274
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION, 193	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID, 274
ER_REPLICA_THREAD, 17	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD, 274
ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR, 67	ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE, 593
ER_REQUIRES_PRIMARY_KEY, 14	ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE, 593
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE, 129	ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_R, 593
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED, 153	ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED, 273
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED, 599	ER_RETRYING_REPAIR_WITHOUT_QUICK, 246
ER_RESERVED_SYNTAX, 28	ER_RETRYING_REPAIR_WITH_KEYCACHE, 246
ER_RESERVED_TABLESPACE_NAME, 104	ER_REVOKE_GRANTS, 21
ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE, 88	ER_REWRITER_LOAD_FAILED, 307
ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE, 88	ER_REWRITER_OOM, 307
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 43	ER_REWRITER_QUERY_ERROR_MSG, 303
ER_RESOURCE_GROUP_BIND_FAILED, 98	ER_REWRITER_QUERY_FAILED, 303
ER_RESOURCE_GROUP_BUSY, 97	ER_REWRITER_READ_FAILED, 307
ER_RESOURCE_GROUP_DISABLED, 98	ER_REWRITER_TABLE_MALFORMED_ERROR, 307
ER_RESOURCE_GROUP_EXISTS, 97	ER_ROLE_GRANTED_TO_ITSELF, 139
ER_RESOURCE_GROUP_IS_DISABLED, 273	ER_ROLE_NOT_GRANTED, 85
ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED, 272	ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG, 277
ER_RESOURCE_GROUP_NOT_EXISTS, 97	ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET, 51
ER_RESOURCE_GROUP_POST_INIT_FAILED, 268	ER_ROW_DOES_NOT_MATCH_PARTITION, 51
ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED, 268	ER_ROW_IN_WRONG_PARTITION, 62
ER_RESOURCE_GROUP_VALIDATION_FAILED, 272	ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR, 178
ER_RESTART_RECEIVED_INFO, 285	ER_ROW_IS_REFERENCED, 18
ER_RESTART_SERVER_FAILED, 103	ER_ROW_IS_REFERENCED_2, 32
ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT, 274	ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 44
ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY, 274	ER_RPL_AM_INIT_INFO_MSG, 282
ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE, 274	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 561
ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP, 593	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM, 561
ER_RES_GRP_FEATURE_NOT_AVAILABLE, 274	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST, 561
	ER_RPL_ASYNC_EXECUTING_QUERY, 562
	ER_RPL_ASYNC_MANAGED_NAME_ADDED, 562

ER_RPL_ASYNC_MANAGED_NAME_REMOVED, 562	ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED, 199
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTOR, 600	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID, 198
ER_RPL_ASYNC_READ_FAILOVER_TABLE, 562	ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORY, 198
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF, 134	ER_RPL_CORRUPTED_INFO_TABLE, 197
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE, 559	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE, 197
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF, 134	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY, 113
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL, 564	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 113
ER_RPL_ASYNC_SENDER_ADDED, 561	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 111
ER_RPL_ASYNC_SENDER_REMOVED, 561	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 112
ER_RPL_BINLOG_FILTERS_OOM, 165	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 112
ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT, 205	ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 112
ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_CANT, 206	ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 112
ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED, 175	ER_RPL_ENCRYPTION_HEADER_ERROR, 111
ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT, 206	ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 111
ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT, 206	ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 112
ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_SLAVE_CANT, 206	ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 111
ER_RPL_BINLOG_STARTING_DUMP, 205	ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 112
ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED, 175	ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION, 112
ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED, 175	ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE, 199
ER_RPL_CANNOT_OPEN_RELAY_LOG, 577	ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REPO_TYPE, 199
ER_RPL_CANT_ADD_DO_TABLE, 169	ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE, 198
ER_RPL_CANT_ADD_IGNORE_TABLE, 169	ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE, 199
ER_RPL_CANT_CREATE_REPLICA_THREAD, 217	ER_RPL_ERROR_CHECKING_REPOSITORY, 200
ER_RPL_CANT_CREATE_SLAVE_THREAD, 216	ER_RPL_ERROR_CREATING_APPLIER_METADATA, 199
ER_RPL_CANT_FIND_FOLLOWUP_FILE, 223	ER_RPL_ERROR_CREATING_CONNECTION_METADATA, 198
ER_RPL_CANT_HAVE_SAME_BASENAME, 265	ER_RPL_ERROR_CREATING_MASTER_INFO, 198
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO, 229	ER_RPL_ERROR_CREATING_RELAY_LOG_INFO, 199
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO, 229	ER_RPL_ERROR_LOOKING_FOR_LOG, 222
ER_RPL_CANT_MAKE_PATHS, 171	ER_RPL_ERROR_READING_MASTER_CONFIGURATION, 242
ER_RPL_CANT_OPEN_INFO_TABLE, 197	ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION, 242
ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO, 230	ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION_FAILED_DUE_TO_GAPS, 242
ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO, 230	
ER_RPL_CANT_SCAN_INFO_TABLE, 197	
ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP, 119	
ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP, 119	
ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE, 199	

ER_RPL_ERROR_READING_SOURCE_CONFIGURATION,	244	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOW	221
ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION,	244	ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWE	221
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION,	230	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY	229
ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION,	242	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER,	609
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION,	244	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED,	216
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE,	202	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_	223
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE,	202	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA	223
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER	200	ER_RPL_MTA_REPOSITORY_RECOVERY_APPLIER_METADATA	222
ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKER	200	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG,	216
ER_RPL_FAILED_TO_OPEN_INFO_FILE,	202	ER_RPL_MTA_RECOVERY_COMPLETE,	220
ER_RPL_FAILED_TO_OPEN_RELAY_LOG,	242	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDI	206
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO	200	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR,	216
ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFO	200	ER_RPL_MTA_RECOVERY_SUCCESSFUL,	216
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX,	228	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED,	243
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL,	279	ER_RPL_MTA_STATISTICS,	219
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED,	269	ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED,	216
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED	269	ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_	223
ER_RPL_GTID_LOG_EVENT_IN_STREAM,	203	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO,	223
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE,	202	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_	215
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CON	265	ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG,	216
ER_RPL_GTID_TABLE_CANNOT_OPEN,	156	ER_RPL_MTS_RECOVERY_COMPLETE,	220
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFA	513	ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDI	215
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT,	498	ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR,	215
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TAB	498	ER_RPL_MTS_RECOVERY_SUCCESSFUL,	216
ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TAB	498	ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED,	243
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR,	204	ER_RPL_MTS_STATISTICS,	219
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX,	198	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REP	201
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX,	198	ER_RPL_OPEN_INDEX_FILE_FAILED,	229
ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION	575	ER_RPL_PLEASE_USE_OPTION_RELAY_LOG,	214
ER_RPL_INFINITY_DENIED,	173	ER_RPL_PLUGIN_FUNCTION_FAILED,	175
ER_RPL_INFINITY_IGNORED,	174	ER_RPL_RECOVERY_ERROR,	215
ER_RPL_INFO_DATA_TOO_LONG,	51	ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE,	214
ER_RPL_IO_THREAD_KILLED,	278	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG,	214
ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED,	609		

ER_RPL_RECOVERY_FILE_MASTER_POS_INFO,	ER_RPL_REPLICA_ERROR_RUNNING_QUERY,
215	225
ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO,	ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_C
215	201
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX,	ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INF
215	213
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER,	ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_META
214	201
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE,	ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA
214	201
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRED,	ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH,
215	224
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL,	ER_RPL_REPLICA_FILTER_CREATE_FAILED,
214	271
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY,	ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD
229	221
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY,	ER_RPL_REPLICA_GENERIC_MESSAGE,
229	200
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY,	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED,
581	271
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLOSE,	ER_RPL_REPLICA_INCORRECT_CHANNEL,
546	264
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_MASTER,	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE,
225	263
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF,	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_F
214	222
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA,	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOU
218	220
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER,	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_
222	226
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION,	ER_RPL_REPLICA_IO_THREAD_EXITING,
220	222
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL,	ER_RPL_REPLICA_IO_THREAD_KILLED,
214	220
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL,	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOU
214	498
ER_RPL_REPLICA_CANT_USE_CHARSET,	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED,
227	217
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION,	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING,
227	562
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE,	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CH
600	602
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE,	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CH
601	602
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_FOR,	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER
200	228
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE,	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE,
219	227
ER_RPL_REPLICA_ERROR_INFO_FROM_DAEMON,	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE,
225	227
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_FILTER,	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFI
225	226
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER,	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_F
219	543
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS,	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE,
228	226
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP,	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG,
221	218
ER_RPL_REPLICA_ERROR_RETRYING,	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG,
219	218
	ER_RPL_REPLICA_REPORT_USER_TOO_LONG,
	218
	ER_RPL_REPLICA_RESET_FILTER_OPTIONS,
	271

ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS,	217	ER_RPL_SLAVE_COULD_NOT_CREATE_CHANNEL_LIST	200
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED,	224	ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER,	219
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED,	600	ER_RPL_SLAVE_HOST_PORT_CHANGED,	225
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED,	600	ER_RPL_SLAVE_ERROR_LOADING_USER_DEFINED_LIB	225
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED,	600	ER_RPL_SLAVE_ERROR_READING_FROM_SERVER,	225
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE,	543	ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENT	228
ER_RPL_REPLICA_SQL_THREAD_EXITING,	226	ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP,	221
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT,	228	ER_RPL_SLAVE_ERROR_RETRYING,	219
ER_RPL_REPLICA_SQL_THREAD_STARTING,	224	ER_RPL_SLAVE_ERROR_RUNNING_QUERY,	225
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PROTOCOL_CHECKS,	541	ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM	201
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIME_OUT,	497	ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_IN	213
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM,	221	ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_ST	201
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_IP,	217	ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO_STRU	201
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED,	223	ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH,	224
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO,	224	ER_RPL_SLAVE_FILTER_CREATE_FAILED,	270
ER_RPL_REPO_HAS_GAPS,	158	ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED,	268
ER_RPL_REPO_SHOULD_BE_TABLE,	198	ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREA	221
ER_RPL_REWRITEDB_EMPTY_FROM,	170	ER_RPL_SLAVE_GENERIC_MESSAGE,	200
ER_RPL_REWRITEDB_EMPTY_TO,	170	ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED,	271
ER_RPL_REWRITEDB_MISSING_ARROW,	170	ER_RPL_SLAVE_INCORRECT_CHANNEL,	264
ER_RPL_RLI_INIT_INFO_MSG,	282	ER_RPL_SLAVE_INSECURE_CHANGE_MASTER,	263
ER_RPL_SERVER_ID_MISSING,	216	ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR	222
ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_MASTER,	224	ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MA	220
ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_FORMAT,	543	ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED	226
ER_RPL_SLAVE_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF,	213	ER_RPL_SLAVE_IO_THREAD_EXITING,	222
ER_RPL_SLAVE_CANT_FLUSH_MASTER_INFO_FILE,	218	ER_RPL_SLAVE_IO_THREAD_KILLED,	220
ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER,	222	ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEO	498
ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION,	220	ER_RPL_SLAVE_IO_THREAD_WAS_KILLED,	217
ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL,	214	ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED,	217
ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL,	214	ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE,	224
ER_RPL_SLAVE_CANT_USE_CHARSET,	226	ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOS	228
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION,	227	ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE,	227
ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION,	220	ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE,	227
		ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CON	226

ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT, 543	ER_ROW_FORMAT_KILLING, 160
ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER, 226	ER_SCHEDULER_STARTED, 160
ER_RPL_SLAVE_REPORT_HOST_TOO_LONG, 218	ER_SCHEDULER_STOPPED, 159
ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG, 218	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER, 160
ER_RPL_SLAVE_REPORT_USER_TOO_LONG, 218	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT, 160
ER_RPL_SLAVE_RESET_FILTER_OPTIONS, 271	ER_SCHEDULER_WAITING, 159
ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS, 217	ER_SCHEMA_DIR_CREATE_FAILED, 100
ER_RPL_SLAVE_SKIP_COUNTER_EXECUTED, 224	ER_SCHEMA_DIR_EXISTS, 100
ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE, 543	ER_SCHEMA_DIR_MISSING, 100
ER_RPL_SLAVE_SQL_THREAD_EXITING, 225	ER_SCHEMA_DIR_UNKNOWN, 100
ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING, 227	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED, 545
ER_RPL_SLAVE_SQL_THREAD_STARTING, 224	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_SECONDARY_ENGINE, 122
ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIORITY, 541	ER_SCHEMA_READ_ONLY, 134
ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT, 497	ER_SDI_GET_KEYS_INVALID_TABLESPACE, 139
ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM, 221	ER_SDI_OPERATION_FAILED, 98
ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRIOR, 217	ER_SDI_OPERATION_FAILED_MISSING_RECORD, 130
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED, 223	ER_SECONDARY_ENGINE, 122
ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO, 223	ER_SECONDARY_ENGINE_DDL, 122
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED, 244	ER_SECONDARY_ENGINE_DDL_FAILED, 606
ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED, 244	ER_SECONDARY_ENGINE_PLUGIN, 121
ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL, 270	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY, 121
ER_RPL_TRX_DELEGATES_INIT_FAILED, 175	ER_SECURE_AUTH_VALUE_UNSUPPORTED, 162
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM, 203	ER_SECURE_TRANSPORT_REQUIRED, 79
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ERROR, 203	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG, 164
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM, 204	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 164
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM, 203	ER_SEC_FILE_PRIV_CANT_STAT, 164
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG, 243	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE, 164
ER_RPL_WORKER_CANT_READ_RELAY_LOG, 243	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS, 165
ER_RPL_WORKER_ID_IS, 198	ER_SEC_FILE_PRIV_EMPTY, 164
ER_RPL_ZOMBIE_ENCOUNTED, 156	ER_SEC_FILE_PRIV_IGNORED, 164
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL, 107	ER_SEC_FILE_PRIV_NULL, 164
ER_RUN_HOOK_ERROR, 74	ER_SEMI_SYNC_ADD_ACK_TO_SLOT, 294
ER_SAME_NAME_PARTITION, 36	ER_SEMI_SYNC_BINLOG_REPLY_IS_AHEAD, 292
ER_SAME_NAME_PARTITION_FIELD, 44	ER_SEMI_SYNC_BINLOG_WRITE_OUT_OF_ORDER, 290
	ER_SEMI_SYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POSITION, 290
	ER_SEMI_SYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NOT, 290
	ER_SEMI_SYNC_DISABLED_ON_MASTER, 291
	ER_SEMI_SYNC_DISABLED_ON_SOURCE, 292
	ER_SEMI_SYNC_EXECUTION_FAILED_ON_MASTER, 291
	ER_SEMI_SYNC_EXECUTION_FAILED_ON_SOURCE, 297
	ER_SEMI_SYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER, 295

ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER,	295	ER_SEMISYNC_SERVER_REPLY,	291
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE,	290	ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED,	297
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE,	293	ER_SEMISYNC_SLAVE_REPLY,	296
ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD,	294	ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO,	296
ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD,	298	ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED,	297
ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET,	295	ER_SEMISYNC_SLAVE_SET_FAILED,	298
ER_SEMISYNC_FORCED_SHUTDOWN,	292	ER_SEMISYNC_SLAVE_START,	296
ER_SEMISYNC_FUNCTION_CALLED_TWICE,	291	ER_SEMISYNC_SOCKET_FD_TOO_LARGE,	296
ER_SEMISYNC_INIT_WAIT_POS,	293	ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH,	294
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY,	290	ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS,	292
ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH,	294	ER_SEMISYNC_SOURCE_OOM,	291
ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS,	292	ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS,	292
ER_SEMISYNC_MASTER_OOM,	291	ER_SEMISYNC_SOURCE_TRX_WAIT_POS,	292
ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS,	292	ER_SEMISYNC_STARTING_ACK_RECEIVER_THD,	294
ER_SEMISYNC_MASTER_TRX_WAIT_POS,	292	ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA,	295
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT,	296	ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE,	295
ER_SEMISYNC_MOVE_BACK_WAIT_POS,	293	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD,	295
ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER,	297	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA,	295
ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE,	297	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE,	295
ER_SEMISYNC_NO_SPACE_IN_THE_PKT,	293	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO,	293
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY,	290	ER_SEMISYNC_TRACE_ENTER_FUNC,	289
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER,	294	ER_SEMISYNC_TRACE_EXIT,	290
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED,	297	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE,	290
ER_SEMISYNC_REPLICA_REPLY,	296	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE,	289
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO,	297	ER_SEMISYNC_TRX_SKIPPED_AT_POS,	294
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED,	297	ER_SEMISYNC_UNREGISTERED_REPLICATOR,	296
ER_SEMISYNC_REPLICA_SET_FAILED,	298	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER,	296
ER_SEMISYNC_REPLICA_START,	296	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER,	296
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE,	291	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED,	295
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR,	291	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK,	294
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL,	291	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK,	294
ER_SEMISYNC_RPL_ENABLED_ON_MASTER,	291	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT,	293
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE,	291	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMITS,	293
ER_SEMISYNC_RPL_INIT_FOR_TRX,	290	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT,	293
ER_SEMISYNC_RPL_SWITCHED_OFF,	293		
ER_SEMISYNC_RPL_SWITCHED_ON,	293		

ER_SERVERID_TOO_LARGE, 173	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 518
ER_SERVER_ACL_TABLE_ERROR, 504	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 519
ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SEQUENCE, 527	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 519
ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAILED, 528	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOG, 519
ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 531	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 519
ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2, 503	ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR, 520
ER_SERVER_CANT_OPEN_FILE, 503	ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER, 520
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 504	ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 518
ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 504	ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 519
ER_SERVER_COST_FAILED_TO_READ, 203	ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND, 518
ER_SERVER_COST_INVALID_COST_CONSTANT, 202	ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY, 519
ER_SERVER_COST_UNKNOWN_COST_CONSTANT, 202	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE, 519
ER_SERVER_DISK_FULL_NOWAIT, 503	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER, 520
ER_SERVER_DOWNGRADE_FROM_VERSION, 607	ER_SERVER_SHUTDOWN, 6
ER_SERVER_DOWNGRADE_STATUS, 607	ER_SERVER_SHUTDOWN_COMPLETE, 265
ER_SERVER_FILE_NOT_FOUND, 503	ER_SERVER_SHUTDOWN_INFO, 507
ER_SERVER_FILE_USED, 503	ER_SERVER_SLAVE_CONVERSION_FAILED, 504
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TEMP_TABLE, 513	ER_SERVER_SLAVE_IGNORED_TABLE, 504
ER_SERVER_HANDLER_ERROR, 503	ER_SERVER_SLAVE_INIT_QUERY_FAILED, 504
ER_SERVER_INIT_COMPILED_IN_COMMANDS, 282	ER_SERVER_SLAVE_MI_INIT_REPOSITORY, 501
ER_SERVER_ISNT_AVAILABLE, 80	ER_SERVER_SLAVE_RLI_INIT_REPOSITORY, 502
ER_SERVER_IS_IN_SECURE_AUTH_MODE, 22	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG, 500
ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG, 500	ER_SERVER_STARTUP_ADMIN_INTERFACE, 520
ER_SERVER_NET_PACKET_TOO_LARGE, 502	ER_SERVER_STARTUP_MSG, 267
ER_SERVER_NEW_ABORTING_CONNECTION, 502	ER_SERVER_TABLE_CHECK_FAILED, 503
ER_SERVER_NOT_FORM_FILE, 503	ER_SERVER_TEST_MESSAGE, 505
ER_SERVER_NO_SESSION_TO_SEND_TO, 502	ER_SERVER_UNKNOWN_ERROR, 502
ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 502	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 502
ER_SERVER_OFFLINE_MODE, 68	ER_SERVER_UPGRADE_CHECKING_DB, 530
ER_SERVER_OUTOFMEMORY, 267	ER_SERVER_UPGRADE_EMPTY_SYS, 530
ER_SERVER_OUT_OF_RESOURCES, 267	ER_SERVER_UPGRADE_FAILED, 529
ER_SERVER_OUT_OF_SORTMEMORY, 502	ER_SERVER_UPGRADE_FROM_VERSION, 524
ER_SERVER_RECORD_FILE_FULL, 502	ER_SERVER_UPGRADE_HELP_TABLE_STATUS, 531
ER_SERVER_REPLICA_AM_INIT_REPOSITORY, 502	ER_SERVER_UPGRADE_INFO_FILE, 529
ER_SERVER_REPLICA_CM_INIT_REPOSITORY, 501	ER_SERVER_UPGRADE_MYSQL_TABLES, 530
ER_SERVER_REPLICA_CONVERSION_FAILED, 504	ER_SERVER_UPGRADE_NO_SYS_VERSION, 530
ER_SERVER_REPLICA_IGNORED_TABLE, 504	ER_SERVER_UPGRADE_OFF, 529
ER_SERVER_REPLICA_INIT_QUERY_FAILED, 504	ER_SERVER_UPGRADE_PENDING, 529
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 523	ER_SERVER_UPGRADE_REPAIR_REQUIRED, 529

ER_SERVER_UPGRADE_REPAIR_STATUS, 529	ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP, 66
ER_SERVER_UPGRADE_SKIP, 529	ER_SLAVE_CHANNEL_MUST_STOP, 72
ER_SERVER_UPGRADE_STATUS, 529	ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG, 71
ER_SERVER_UPGRADE_SYSTEM_TABLES, 530	ER_SLAVE_CHANNEL_NOT_RUNNING, 72
ER_SERVER_UPGRADE_SYS_SCHEMA, 529	ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED, 77
ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT, 530	ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER, 73
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 530	ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP, 73
ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 530	ER_SLAVE_CHANNEL_WAS_NOT_RUNNING, 72
ER_SERVER_UPGRADE_SYS_VERSION_EMPTY, 530	ER_SLAVE_CHANNEL_WAS_RUNNING, 72
ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED, 524	ER_SLAVE_CONFIGURATION, 56
ER_SERVER_WARN_DEPRECATED, 527	ER_SLAVE_CONVERSION_FAILED, 46
ER_SERVER_WRONG_VALUE_FOR_VAR, 513	ER_SLAVE_CORRUPT_EVENT, 41
ER_SESSION_WAS_KILLED, 80	ER_SLAVE_CREATE_EVENT_FAILURE, 500
ER_SETNS_FAILED, 532	ER_SLAVE_FATAL_ERROR, 500
ER_SET_CONSTANTS_ONLY, 17	ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER, 64
ER_SET_EVENT_FAILED, 508	ER_SLAVE_HEARTBEAT_FAILURE, 500
ER_SET_PASSWORD_AUTH_PLUGIN, 48	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE, 42
ER_SET_PASSWORD_AUTH_PLUGIN_ERROR, 147	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 48
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 54	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 48
ER_SE_TYPECODE_CONFLICT, 179	ER_SLAVE_IGNORED_SSL_PARAMS, 21
ER_SHA256_PASSWORD_SECOND_PASSWORD_USED, 521	ER_SLAVE_IGNORED_TABLE, 19
ER_SHAPE_PREDICTION_UDF, 150	ER_SLAVE_IGNORE_SERVER_IDS, 44
ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE, 514	ER_SLAVE_INCIDENT, 501
ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL, 304	ER_SLAVE_KILLED_AFTER_RECONNECT, 278
ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH, 304	ER_SLAVE_MASTER_COM_FAILURE, 501
ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING, 304	ER_SLAVE_MAX_CHANNELS_EXCEEDED, 72
ER_SHA_PWD_RSA_KEY_TOO_LONG, 305	ER_SLAVE_MI_INIT_REPOSITORY, 62
ER_SHA_PWD_SALT_FOR_USER_CORRUPT, 305	ER_SLAVE_MULTIPLE_CHANNELS_CMD, 71
ER_SHUTDOWN_COMPLETE, 8	ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY, 71
ER_SHUTTING_DOWN_REPLICA_THREADS, 166	ER_SLAVE_NOT_RUNNING, 16
ER_SHUTTING_DOWN_SLAVE_THREADS, 166	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS, 278
ER_SIGNAL_BAD_CONDITION_TYPE, 43	ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL, 104
ER_SIGNAL_EXCEPTION, 43	ER_SLAVE_RECONNECT_FAILED, 278
ER_SIGNAL_NOT_FOUND, 43	ER_SLAVE_RELAY_LOG_PURGE_FAILED, 270
ER_SIGNAL_WARN, 43	ER_SLAVE_RELAY_LOG_READ_FAILURE, 501
ER_SIZE_OVERFLOW_ERROR, 37	ER_SLAVE_RELAY_LOG_TRUNCATE_INFO, 270
ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE, 277	ER_SLAVE_RELAY_LOG_WRITE_FAILURE, 501
ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UNKNOWN, 563	ER_SLAVE_RLI_INIT_REPOSITORY, 62
ER_SLAVE_CANT_CREATE_CONVERSION, 46	ER_SLAVE_SILENT_RETRY_TRANSACTION, 57
ER_SLAVE_CANT_USE_TEMPDIR, 229	ER_SLAVE_SQL_THREAD_MUST_STOP, 66
ER_SLAVE_CHANGE_MASTER_TO_EXECUTED, 228	ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REPLICATION, 194
ER_SLAVE_CHANNEL_DOES_NOT_EXIST, 71	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_AVAILABLE, 193
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_RUNNING, 194

ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED,	ER_SP_NO_DROP_SP, 27
194	ER_SP_NO_RECURSION, 31
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD,	ER_SP_NO_RECURSIVE_CREATE, 24
193	ER_SP_NO_RESET, 30
ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_ERROR,	ER_SP_NO_RECURSION_LIMIT, 33
193	ER_SP_STORE_FAILED, 24
ER_SLAVE_THREAD, 16	ER_SP_SUBSELECT_NYI, 26
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR,	ER_SP_UNDECLARED_VAR, 25
67	ER_SP_UNINIT_VAR, 24
ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING,	ER_SPS_OVERRIDE_COND_AFTER_CURSHNDLR, 26
112	ER_SP_WRONG_NAME, 33
ER_SOURCE, 15	ER_SP_WRONG_NO_OF_ARGS, 25
ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE,	ER_SP_WRONG_NO_OF_FETCH_ARGS, 25
50	ER_SQLTHREAD_WITH_SECURE_REPLICA, 53
ER_SOURCE_FATAL_ERROR_READING_BINLOG,	ER_SQLTHREAD_WITH_SECURE_SLAVE, 53
19	ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL, 178
ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS,	ER_SQL_HA_READ_FAILED, 175
56	ER_SQL_MODE_MERGED, 77
ER_SOURCE_NET_READ, 15	ER_SQL_MODE_MERGED_WITH_STRICT_MODE,
ER_SOURCE_NET_WRITE, 15	265
ER_SPATIAL_CANT_HAVE_NULL, 20	ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE,
ER_SPATIAL_FUNCTIONAL_INDEX, 108	137
ER_SPATIAL_MUST_HAVE_GEOM_COL, 47	ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID,
ER_SPATIAL_UNIQUE_INDEX, 105	61
ER_SPECIFIC_ACCESS_DENIED_ERROR, 18	ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE,
ER_SPVAR_NONINTEGER_TYPE, 136	137
ER_SP_ALREADY_EXISTS, 24	ER_SQL_USER_TABLE ALTER WARNING, 178
ER_SP_BADRETURN, 24	ER_SQL_USER_TABLE_CREATE WARNING, 178
ER_SP_BADSELECT, 24	ER_SRS_ATTRIBUTE_STRING_TOO_LONG, 104
ER_SP_BADSTATEMENT, 24	ER_SRS_GEOGCS_INVALID_AXES, 106
ER_SP_BAD_CURSOR_QUERY, 25	ER_SRS_ID_ALREADY_EXISTS, 103
ER_SP_BAD_CURSOR_SELECT, 25	ER_SRS_INVALID_ANGULAR_UNIT, 106
ER_SP_BAD_SQLSTATE, 30	ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE,
ER_SP_BAD_VAR_SHADOW, 32	104
ER_SP_CANT ALTER, 26	ER_SRS_INVALID_HEIGHT, 150
ER_SP_CANT_SET_AUTOCOMMIT, 32	ER_SRS_INVALID_INVERSE_FLATTENING, 106
ER_SP_CASE_NOT_FOUND, 26	ER_SRS_INVALID_LATITUDE_OF_ORIGIN, 148
ER_SP_COND_MISMATCH, 25	ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A,
ER_SP_CURSOR_AFTER_HANDLER, 26	150
ER_SP_CURSOR_ALREADY_OPEN, 25	ER_SRS_INVALID_LONGITUDE_OF_ORIGIN, 148
ER_SP_CURSOR_MISMATCH, 25	ER_SRS_INVALID_PRIME_MERIDIAN, 106
ER_SP_CURSOR_NOT_OPEN, 25	ER_SRS_INVALID_SCALING, 150
ER_SP_DOES_NOT_EXIST, 24	ER_SRS_INVALID_SEMI_MAJOR_AXIS, 106
ER_SP_DROP_FAILED, 24	ER_SRS_INVALID_ZONE_WIDTH, 150
ER_SP_DUP_COND, 25	ER_SRS_MISSING_MANDATORY_ATTRIBUTE,
ER_SP_DUP_CURS, 26	103
ER_SP_DUP_HANDLER, 30	ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS,
ER_SP_DUP_PARAM, 25	103
ER_SP_DUP_VAR, 25	ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE,
ER_SP_FETCH_NO_DATA, 25	103
ER_SP_LABEL_MISMATCH, 24	ER_SRS_NOT_CARTESIAN, 84
ER_SP_LABEL_REDEFINE, 24	ER_SRS_NOT_CARTESIAN_UNDEFINED, 84
ER_SP_LILABEL_MISMATCH, 24	ER_SRS_NOT_FOUND, 86
ER_SP_LOAD_FAILED, 84	ER_SRS_NOT_GEOGRAPHIC, 105
ER_SP_NORETURN, 25	ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPA
ER_SP_NORETURNEND, 25	103
ER_SP_NOT_VAR_ARG, 30	ER_SRS_PARSE_ERROR, 84
ER_SP_NO_AGGREGATE, 33	ER_SRS_PROJ_PARAMETER_MISSING, 84

ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT, 148	ER_SYNTAX_ERROR, 13
ER_SR_BOGUS_VALUE, 175	ER_SYSTEMD_NOTIFY_CONNECT_FAILED, 369
ER_SR_INVALID_CONTEXT, 176	ER_SYSTEMD_NOTIFY_DEBUG, 592
ER_SSL_FIPS_MODE_ERROR, 307	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG, 369
ER_SSL_LIBRARY_ERROR, 161	ER_SYSTEMD_NOTIFY_WRITE_FAILED, 370
ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED, 514	ER_SYSTEM_SCHEMA_NOT_FOUND, 156
ER_SSL_SERVER_CERT_VERIFY_FAILED, 533	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE, 267
ER_SSL_TRYING_DATADIR_DEFAULTS, 173	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL, 243
ER_STACKSIZE_UNEXPECTED, 172	ER_SYSTEM_VIEW_INIT_FAILED, 268
ER_STACK_BACKTRACE, 594	ER_SYSVAR_CHANGE_DURING_QUERY, 125
ER_STACK_OVERRUN, 11	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE, 306
ER_STACK_OVERRUN_NEED_MORE, 31	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE, 306
ER_STARTING_AS, 166	ER_SYS_VAR_COMPONENT_OOM, 305
ER_STARTING_INIT, 507	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE, 306
ER_STARTING_REPLICA_MONITOR_IO_THREAD, 136	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY, 305
ER_STARTUP, 30	ER_SYS_VAR_DEREGISTRATION, 604
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION, 132	ER_SYS_VAR_NOT_FOUND, 508
ER_STD_BAD_ALLOC_ERROR, 69	ER_SYS_VAR_REGISTRATION, 604
ER_STD_DOMAIN_ERROR, 69	ER_TABLEACCESS_DENIED_ERROR, 12
ER_STD_INVALID_ARGUMENT, 69	ER_TABLENAME_NOT_ALLOWED_HERE, 20
ER_STD_LENGTH_ERROR, 69	ER_TABLESPACE_AUTO_EXTEND_ERROR, 37
ER_STD_LOGIC_ERROR, 69	ER_TABLESPACE_CANNOT_BE_DECRYPTED, 116
ER_STD_OUT_OF_RANGE_ERROR, 69	ER_TABLESPACE_CANNOT_BE_ENCRYPTED, 116
ER_STD_OVERFLOW_ERROR, 69	ER_TABLESPACE_CANNOT_ENCRYPT, 81
ER_STD_RANGE_ERROR, 69	ER_TABLESPACE_DISCARDED, 58
ER_STD_REGEX_ERROR, 119	ER_TABLESPACE_DUP_FILENAME, 92
ER_STD_RUNTIME_ERROR, 69	ER_TABLESPACE_ENGINE_MISMATCH, 96
ER_STD_UNDERFLOW_ERROR, 69	ER_TABLESPACE_EXISTS, 58
ER_STD_UNKNOWN_EXCEPTION, 69	ER_TABLESPACE_IS_NOT_EMPTY, 76
ER_STMT_CACHE_FULL, 48	ER_TABLESPACE_MISSING, 58
ER_STMT_HAS_NO_OPEN_CURSOR, 30	ER_TABLESPACE_MISSING_WITH_NAME, 84
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 26	ER_TABLESPACE_TYPE_UNKNOWN, 116
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE, 306	ER_TABLES_DIFFERENT_METADATA, 51
ER_STOP_REPLICA_IO_THREAD_TIMEOUT, 63	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT, 14
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT, 136	ER_TABLE_CANT_HANDLE_BLOB, 14
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT, 63	ER_TABLE_CANT_HANDLE_FT, 17
ER_STOP_SLAVE_IO_THREAD_DISK_SPACE, 306	ER_TABLE_CANT_HANDLE_SPKEYS, 33
ER_STOP_SLAVE_IO_THREAD_TIMEOUT, 63	ER_TABLE_CHECK_INTEGRITY, 174
ER_STOP_SLAVE_SQL_THREAD_TIMEOUT, 63	ER_TABLE_CORRUPT, 63
ER_STORAGE_ENGINE_NOT_LOADED, 65	ER_TABLE_CREATED_WITH_DIFFERENT_VERSION, 60
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT, 47	ER_TABLE_DEF_CHANGED, 30
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT, 38	ER_TABLE_EXISTS_ERROR, 6
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN, 47	ER_TABLE_HAS_NO_FT, 53
ER_SUBPARTITION_ERROR, 35	ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD, 189
ER_SUBPARTITION_NAME, 43	ER_TABLE_INCOMPATIBLE_YEAR_FIELD, 189
ER_SUBQUERY_NO_1_ROW, 20	ER_TABLE_IN_FK_CHECK, 50
ER_SUBQUERY_TRANSFORM_REJECTED, 132	ER_TABLE_IN_SHARED_TABLESPACE, 150
ER_SWITCH_TMP_ENGINE, 89	

ER_TABLE_IN_SYSTEM_TABLESPACE, 58	ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGES, 592
ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN, 139	ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA, 287
ER_TABLE_MUST_HAVE_COLUMNS, 10	ER_THREAD_POOL_CONNECTION_REPORT, 606
ER_TABLE_NAME, 43	ER_THREAD_POOL_CON_HANDLER_INIT_FAILED, 287
ER_TABLE_NAME_CAUSES_TOO_LONG_PATH, 125	ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID, 545
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED, 545	ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT, 288
ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK, 545	ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER, 287
ER_TABLE_NEEDS_DUMP_UPGRADE, 285	ER_THREAD_POOL_FAILED_TO_CREATE_POOL, 288
ER_TABLE_NEEDS_REBUILD, 48	ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_PLUGIN, 288
ER_TABLE_NEEDS_UPGRADE, 33	ER_THREAD_POOL_IDLE_CONNECTION_CLOSED, 600
ER_TABLE_NOT_EMPTY, 150	ER_THREAD_POOL_INIT_FAILED, 287
ER_TABLE_NOT_LOCKED, 9	ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER, 287
ER_TABLE_NOT_LOCKED_FOR_WRITE, 9	ER_THREAD_POOL_INVALID_STALL_LIMIT, 287
ER_TABLE_NO_PRIMARY_KEY, 150	ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED, 288
ER_TABLE_REFERENCED, 81	ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID, 287
ER_TABLE_SCHEMA_MISMATCH, 58	ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM, 286
ER_TABLE_UPGRADE_REQUIRED, 266	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED, 518
ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT, 128	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED, 518
ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMN, 128	ER_THREAD_POOL_PLUGIN_STARTED, 583
ER_TABLE_WITHOUT_PK, 107	ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID, 595
ER_TABLE_WRONG_KEY_DEFINITION, 190	ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_THREADS, 595
ER_TARGET_TABLESPACE_UNENCRYPTED, 117	ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS, 288
ER_TARGET_TS_UNENCRYPTED, 509	ER_THREAD_POOL_SIZE_TOO_HIGH, 286
ER_TC_BAD_MAGIC_IN_TC_LOG, 212	ER_THREAD_POOL_SIZE_TOO_LOW, 286
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC, 212	ER_THREAD_POOL_SYSVAR_CHANGE, 594
ER_TC_HEURISTIC_RECOVERY_FAILED, 213	ER_THREAD_PRIORITY_IGNORED, 264
ER_TC_HEURISTIC_RECOVERY_MODE, 213	ER_THREAD_RESOURCE_CONFIGURATION_REUSED, 553
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY, 212	ER_TLS_CONFIGURED_FOR_CHANNEL, 553
ER_TC_RECOVERING_AFTER_CRASH_USING, 212	ER_TMPDIR_PATH_TOO_LONG, 560
ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS, 213	ER_TMP_SESSION_FOR_VAR, 592
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY, 213	ER_TOO_BIG_DISPLAYWIDTH, 31
ER_TEMPORARY_NAME, 43	ER_TOO_BIG_ENUM, 83
ER_TEMP_FILE_WRITE_FAILURE, 63	ER_TOO_BIG_FIELDLENGTH, 8
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT, 107	ER_TOO_BIG_FOR_UNCOMPRESS, 20
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR, 38	ER_TOO_BIG_PRECISION, 31
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT, 107	ER_TOO_BIG_ROWSIZE, 11
ER_TEXTFILE_NOT_READABLE, 8	ER_TOO_BIG_SCALE, 31
ER_TF_FORBIDDEN_JOIN_TYPE, 99	ER_TOO_BIG_SELECT, 10
ER_TF_MUST_HAVE_ALIAS, 98	ER_TOO_BIG_SET, 9
ER_THE_USER_ABIDES, 169	
ER_THREAD_HANDLING_OOM, 163	
ER_THREAD_POOL_ALGORITHM_INVALID, 287	
ER_THREAD_POOL_BUFFER_TOO_SMALL, 288	

ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT, 34	ER_TRG_DOES_NOT_EXIST, 27
ER_TOO_LONG_BODY, 31	ER_TRG_INVALID_CREATION_CTX, 41
ER_TOO_LONG_FIELD_COMMENT, 42	ER_TRG_IN_WRONG_SCHEMA, 31
ER_TOO_LONG_IDENT, 7	ER_TRG_NO_CLIENT_CHARSET, 161
ER_TOO_LONG_INDEX_COMMENT, 47	ER_TRG_NO_CREATION_CTX, 41
ER_TOO_LONG_KEY, 8	ER_TRG_NO_DEFINER, 33
ER_TOO_LONG_ROUTINE_COMMENT, 84	ER_TRG_NO_SUCH_ROW_IN_TRG, 27
ER_TOO_LONG_SET_ENUM_VALUE, 83	ER_TRG_ON_VIEW_OR_TEMP_TABLE, 27
ER_TOO_LONG_STRING, 14	ER_TRG_WITHOUT_DEFINER, 161
ER_TOO_LONG_TABLESPACE_COMMENT, 92	ER_TRG_WRONG_ORDER, 524
ER_TOO_LONG_TABLE_COMMENT, 42	ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED, 288
ER_TOO_LONG_TABLE_PARTITION_COMMENT, 56	ER_TRIGGER_INVALID_VALUE, 155
ER_TOO_MANY_CONCURRENT_CLONES, 95	ER_TRUNCATED_WRONG_VALUE, 23
ER_TOO_MANY_CONCURRENT_TRXS, 43	ER_TRUNCATED_WRONG_VALUE_FOR_FIELD, 27
ER_TOO_MANY_FIELDS, 11	ER_TRUNCATE_ILLEGAL_FK, 48
ER_TOO_MANY_KEYS, 7	ER_TRX_GTID_COLLECT_REJECT, 178
ER_TOO_MANY_KEY_PARTS, 8	ER_TRX_WRITE_SET_OOM, 179
ER_TOO_MANY_PARTITIONS_ERROR, 35	ER_TURNING_LOGGING_OFF_FOR_THE_DURATION, 259
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR, 44	ER_TURNING_ON_PARTIAL_REVOKES, 528
ER_TOO_MANY_ROWS, 14	ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX_DENIED, 269
ER_TOO_MANY_STORAGE_ENGINES, 179	ER_TZ_CANT_BUILD_MKTIME_MAP, 192
ER_TOO_MANY_TABLES, 11	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 191
ER_TOO_MANY_USER_CONNECTIONS, 17	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_IDENTITY, 191
ER_TOO_MANY_VALUES_ERROR, 44	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE, 191
ER_TOO_MANY_WINDOWS, 146	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE, 191
ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THRESHOLD, 149	ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE, 192
ER_TRACK_VARIABLES_BOGUS, 169	ER_TZ_OOM_INITIALIZING_TIME_ZONES, 191
ER_TRANSACTION_ROLLBACK_DURING_COMMIT, 74	ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE, 191
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84, 107	ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION, 192
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED, 106	ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 193
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84, 107	ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 193
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED, 106	ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE, 191
ER_TRANSPORTS_WHAT_TRANSPORTS, 167	ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE, 192
ER_TRANS_CACHE_FULL, 16	ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 192
ER_TREE_CORRUPT_2_CONSECUTIVE_REDS, 241	ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS, 192
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT, 242	ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXIST, 192
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT, 241	ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR, 192
ER_TREE_CORRUPT_RIGHT_IS_LEFT, 242	ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE, 192
ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK, 241	ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE, 191
ER_TRG_ALREADY_EXISTS, 27	ER_UDF_ALREADY_EXISTS, 508
ER_TRG_CANT_CHANGE_ROW, 27	
ER_TRG_CANT_OPEN_TABLE, 41	
ER_TRG_CANT_PARSE, 174	
ER_TRG_CORRUPTED_FILE, 41	
ER_TRG_CREATION_CTX_NOT_SET, 266	

ER_UDF_CANT_ALLOC_FOR_FUNCTION, 177
 ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 176
 ER_UDF_CANT_OPEN_FUNCTION_TABLE, 177
 ER_UDF_DEREGISTRATION, 604
 ER_UDF_DROP_DYNAMICALLY_REGISTERED, 94
 ER_UDF_ERROR, 82
 ER_UDF_EXEC_FAILURE, 604
 ER_UDF_EXEC_FAILURE_REASON, 604
 ER_UDF_EXISTS, 11
 ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE, 177
 ER_UDF_NO_PATHS, 11
 ER_UDF_REGISTER_ERROR, 559
 ER_UDF_REGISTER_SERVICE_ERROR, 559
 ER_UDF_REGISTRATION, 604
 ER_UDF_UNREGISTER_ERROR, 559
 ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANTS, 117
 ER_UNABLE_TO_BUILD_HISTOGRAM, 94
 ER_UNABLE_TO_COLLECT_LOG_STATUS, 104
 ER_UNABLE_TO_DROP_COLUMN_STATISTICS, 94
 ER_UNABLE_TO_RESOLVE_HOSTNAME, 160
 ER_UNABLE_TO_RESOLVE_IP, 160
 ER_UNABLE_TO_SET_OPTION, 104
 ER_UNABLE_TO_STORE_COLUMN_STATISTICS, 94
 ER_UNABLE_TO_STORE_STATISTICS, 86
 ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS, 94
 ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN, 99
 ER_UNDO_RECORD_TOO_BIG, 49
 ER_UNEXPECTED_GEOMETRY_TYPE, 84
 ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 35
 ER_UNIT_NOT_FOUND, 124
 ER_UNKNOWN_ALTER_ALGORITHM, 56
 ER_UNKNOWN_ALTER_LOCK, 57
 ER_UNKNOWN_AUTHID, 84
 ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE, 272
 ER_UNKNOWN_CHARACTER_SET, 10
 ER_UNKNOWN_COLLATION, 21
 ER_UNKNOWN_COM_ERROR, 6
 ER_UNKNOWN_ERROR, 10
 ER_UNKNOWN_ERROR_DETECTED_IN_SE, 277
 ER_UNKNOWN_ERROR_NUMBER, 176
 ER_UNKNOWN_EXPLAIN_FORMAT, 56
 ER_UNKNOWN_KEY_CACHE, 23
 ER_UNKNOWN_LOCALE, 44
 ER_UNKNOWN_NETWORK_NAMESPACE, 532
 ER_UNKNOWN_PARTITION, 51
 ER_UNKNOWN_PROCEDURE, 10
 ER_UNKNOWN_STMT_HANDLER, 20
 ER_UNKNOWN_STORAGE_ENGINE, 23
 ER_UNKNOWN_SYSTEM_VARIABLE, 16
 ER_UNKNOWN_TABLE, 10
 ER_UNKNOWN_TABLESPACE_TYPE, 514
 ER_UNKNOWN_TABLE_IN_UPGRADE, 538
 ER_UNKNOWN_TARGET_BINLOG, 28
 ER_UNKNOWN_TIME_ZONE, 23
 ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE, 162
 ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE, 508
 ER_UNRESOLVED_HINT_NAME, 76
 ER_UNRESOLVED_TABLE_LOCK, 88
 ER_UNSUPPORTED_LOG_ENGINE, 39
 ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATION, 110
 ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN, 75
 ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, 81
 ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMNS, 74
 ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMNS, 80
 ER_UNSUPPORTED_DATE, 166
 ER_UNSUPPORTED_ENGINE, 50
 ER_UNSUPPORTED_EXTENSION, 10
 ER_UNSUPPORTED_INDEX_ALGORITHM, 83
 ER_UNSUPPORTED_PS, 23
 ER_UNSUPPORTED_SQL_MODE, 123
 ER_UNSUPPORTED_USE_OF_GRANT_AS, 117
 ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE, 83
 ER_UNTIL_COND_IGNORED, 22
 ER_UPDATE_GTID_PURGED_WITH_GR, 125
 ER_UPDATE_INFO, 12
 ER_UPDATE_LOG_DEPRECATED_IGNORED, 24
 ER_UPDATE_LOG_DEPRECATED_TRANSLATED, 24
 ER_UPDATE_TABLE_USED, 9
 ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 14
 ER_UPDATING_DD_TABLE, 83
 ER_UPGRADE_NONEXISTENT_SCHEMA, 560
 ER_UPGRADE_PARSE_ERROR, 513
 ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED, 539
 ER_USAGE_DEPRECATION_COUNTER, 608
 ER_USERNAME, 33
 ER_USERNAME_TRUNCATED, 554
 ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCK, 130
 ER_USER_ALREADY_EXISTS, 79
 ER_USER_COLUMN_OLD_LENGTH, 81
 ER_USER_DOES_NOT_EXIST, 79
 ER_USER_LIMIT_REACHED, 18
 ER_USER_LOCK_DEADLOCK, 70
 ER_USER_LOCK_OVERLONG_NAME, 154
 ER_USER_LOCK_WRONG_NAME, 70
 ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCORRECT, 188

ER_USER_REFERENCED_AS_DEFINER, 136	ER_VAR_DOES_NOT_EXIST, 93
ER_USER_REGISTRATION_FAILED, 142	ER_VERBOSE_HINT, 169
ER_USER_REQUIRES_ROOT, 167	ER_VERBOSE_REQUIRES_HELP, 163
ER_USER_WHAT_USER, 167	ER_VIEW_CHECKSUM, 29
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION, 137	ER_VIEW_CREATE_CTX_NOT_SET, 266
ER_UUID_INVALID, 162	ER_VIEW_DELETE_MERGE_VIEW, 29
ER_UUID_IS, 162	ER_VIEW_FRM_NO_USER, 32
ER_UUID_SALT, 162	ER_VIEW_INVALID, 27
ER_UUID_SCRUB, 162	ER_VIEW_INVALID_CREATION_CTX, 40
ER_VALGRIND_COUNT_LEAKS, 176	ER_VIEW_MULTIUPDATE, 29
ER_VALGRIND_DO_QUICK_LEAK_CHECK, 176	ER_VIEW_NONUPD_CHECK, 28
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGES, 154	ER_VIEW_NO_EXPLAIN, 26
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED, 371	ER_VIEW_NO_INSERT_FIELD_LIST, 29
ER_VALIDATE_PWD_COULD_BE_NULL, 370	ER_VIEW_OTHER_USER, 32
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED, 302	ER_VIEW_PREVENT_UPDATE, 32
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED, 302	ER_VIEW_RECURSIVE, 33
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED, 370	ER_VIEW_SELECT_CLAUSE, 27
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 303	ER_VIEW_SELECT_TMPTABLE, 27
ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX, 303	ER_VIEW_SELECT_VARIABLE, 27
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX, 303	ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, 156
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE, 303	ER_VIEW_UNPARSABLE, 190
ER_VALIDATE_PWD_LENGTH_CHANGED, 303	ER_VIEW_WRONG_LIST, 27
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED, 370	ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 77
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED, 370	ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 77
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED, 371	ER_WAITING_FOR_NO_CONNECTIONS, 608
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED, 370	ER_WAITING_FOR_NO_THDS, 608
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED, 371	ER_WAITPID_FAILED, 283
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED, 371	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 520
ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED, 371	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID, 520
ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED, 371	ER_WARNING_NOT_COMPLETE_ROLLBACK, 16
ER_VALUES_IS_NOT_INT_TYPE_ERROR, 47	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE, 52
ER_VALUE_OUT_OF_RANGE, 144	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP, 52
ER_VARIABLE_IS_NOT_STRUCT, 21	ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDARY, 140
ER_VARIABLE_IS_READONLY, 42	ER_WARN_AUDIT_LOG_MAX_SIZE_AND_PRUNE_SECONDARY, 572
ER_VARIABLE_NOT_PERSISTED, 86	ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 140
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER, 54	ER_WARN_AUDIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 572
ER_VARIABLE_NOT_SETTABLE_IN_SP, 60	ER_WARN_ALLOWED_PACKET_OVERFLOWED, 24
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, 54	ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME, 139
ER_VAR_CANT_BE_READ, 19	ER_WARN_AUDIT_LOG_DISABLED, 581
	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_OPTION, 141

ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_DEPRECATED, 573	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 111
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROWS, 542	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 608
ER_WARN_BAD_MAX_EXECUTION_TIME, 76	ER_WARN_DEPRECATED_SQLMODE, 73
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 96	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 131
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_INDEXES, 97	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 147
ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED, 96	ER_WARN_DEPRECATED_SYNTAX, 23
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOC_FAILED, 602	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 147
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 581	ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 38
ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES, 147	ER_WARN_DEPRECATED_SYSVAR_UPDATE, 73
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 31	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL, 570
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY, 131	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL_C, 140
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_WARNING_DEPRECATED, 601	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS, 154
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_WARNING_DEPRECATED, 565	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_O, 601
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY, 594	ER_WARN_DEPRECATED_USER_SET_EXPR, 110
ER_WARN_CONFLICTING_HINT, 76	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 514
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS, 144	ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 514
ER_WARN_DATA_OUT_OF_RANGE, 21	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 514
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX, 108	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 514
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 108	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_N, 131
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 127	ER_WARN_DEPRECATED_WITH_NOTE, 154
ER_WARN_DEPRECATED_CHARSET_OPTION, 580	ER_WARN_DEPRECATED_YEAR_UNSIGNED, 130
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 150	ER_WARN_DEPRECATED_ZEROFILL, 120
ER_WARN_DEPRECATED_COLLATION, 145	ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 42
ER_WARN_DEPRECATED_COLLATION_OPTION, 580	ER_WARN_FIELD_RESOLVED, 22
ER_WARN_DEPRECATED_DATETIME_DELIMITER, 147	ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 124
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 119	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VAR, 572
ER_WARN_DEPRECATED_FLOAT_DIGITS, 119	ER_WARN_GTID_THRESHOLD_BREACH, 563
ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 119	ER_WARN_HOSTNAME_WONT_WORK, 23
ER_WARN_DEPRECATED_FOUND_ROWS, 131	ER_WARN_HYPERGRAPH_EXPERIMENTAL, 135
ER_WARN_DEPRECATED_IDENT, 149	ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTION, 528
ER_WARN_DEPRECATED_INNER_INTO, 131	ER_WARN_INDEX_NOT_APPLICABLE, 51
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 120	ER_WARN_INVALID_DB_RESTRICTIONS, 528
ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_WARN, 130	ER_WARN_INVALID_HINT, 93
	ER_WARN_INVALID_TIMESTAMP, 23
	ER_WARN_I_S_SKIPPED_TABLE, 46
	ER_WARN_LEGACY_SYNTAX_CONVERTED, 65

ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_551	ER_WARN_TRG_ALREADY_EXISTS, 147
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT_541	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 85
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST_540	ER_WARN_UNKNOWN_KEYRING_AWS_REGION, 76
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_REPLICATION_541	ER_WARN_UNKNOWN_QB_NAME, 76
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_577	ER_WARN_UNAPPLIED_LOAD, THE_NOT_PERSISTED, 86
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING_581	ER_WARN_UNSUPPORTED_HINT, 84
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND_565	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 76
ER_WARN_NO_SERVERID_SPECIFIED, 265	ER_WARN_USING_OTHER_HANDLER, 21
ER_WARN_NO_SPACE_VERSION_COMMENT, 154	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED, 135
ER_WARN_NULL_TO_NOTNULL, 21	ER_WARN_VIEW_MERGE, 27
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS, 67	ER_WARN_VIEW_WITHOUT_KEY, 27
ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 67	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG, 540
ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE_76	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG, 540
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 66	ER_WASTEFUL_NET_BUFFER_SIZE, 163
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 76	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_532
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 528	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH, 89
ER_WARN_PROPERTY_STRING_PARSE_FAILED, 523	ER_WINDOW_DUPLICATE_NAME, 90
ER_WARN_PURGE_LOG_IN_USE, 62	ER_WINDOW_EXPLAIN_JSON, 91
ER_WARN_PURGE_LOG_IS_ACTIVE, 62	ER_WINDOW_FRAME_END_ILLEGAL, 90
ER_WARN_QC_RESIZE, 22	ER_WINDOW_FRAME_ILLEGAL, 90
ER_WARN_REGEX_USING_DEFAULT, 145	ER_WINDOW_FRAME_START_ILLEGAL, 90
ER_WARN_REMOVED_SQL_MODE, 515	ER_WINDOW_FUNCTION_IGNORES_FRAME, 91
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_571	ER_WINDOW_ILLEGAL_ORDER_BY, 91
ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_577	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE, 91
ER_WARN_RESERVED_SRID_RANGE, 103	ER_WINDOW_INVALID_WINDOW_FUNC_USE, 91
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_542	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_91
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_542	ER_WINDOW_NO_CHILD_PARTITIONING, 89
ER_WARN_SCHEDULED_TASK_RUN_FAILED, 606	ER_WINDOW_NO_GROUP_ORDER, 91
ER_WARN_SF_UDF_NAME_COLLISION, 145	ER_WINDOW_NO_GROUP_ORDER_UNUSED, 91
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED_141	ER_WINDOW_NO_INHERIT_FRAME, 90
ER_WARN_SRS_ID_ALREADY_EXISTS, 103	ER_WINDOW_NO_REDEFINE_ORDER_BY, 90
ER_WARN_SRS_NOT_FOUND, 84	ER_WINDOW_NO_SUCH_WINDOW, 89
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 88	ER_WINDOW_RANGE_FRAME_BOUND_NOT_CONSTANT, 90
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR, 552	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE, 90
ER_WARN_TOO_FEW_RECORDS, 21	ER_WINDOW_RANGE_FRAME_ORDER_TYPE, 90
ER_WARN_TOO_MANY_RECORDS, 21	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE, 90
	ER_WINDOW_ROWS_INTERVAL_USE, 91
	ER_WINDOW_SE_NOT_ACCEPTABLE, 91
	ER_WIN_LISTEN_BUT_HOW, 168
	ER_WIN_LOAD_LIBRARY_FAILED, 282
	ER_WL9236_NOW_UNUSED, 92
	ER_WRITABLE_CONFIG_REMOVED, 165
	ER_WRITE_ROW_TO_PARTITION_FAILED, 272
	ER_WRITE_SET_EXCEEDS_LIMIT, 82

ER_WRONG_ARGUMENTS, 17	ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 44
ER_WRONG_AUTO_KEY, 8	ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD, 281
ER_WRONG_COLUMN_NAME, 14	ER_WRONG_TYPE_FOR_VAR, 19
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT, 126	ER_WRONG_USAGE, 18
ER_WRONG_COMPRESSION_LEVEL_CLIENT, 126	ER_WRONG_VALUE, 37
ER_WRONG_COUNT_FOR_KEY, 242	ER_WRONG_VALUE_COUNT, 7
ER_WRONG_COUNT_FOR_ORIGIN, 242	ER_WRONG_VALUE_COUNT_ON_ROW, 12
ER_WRONG_COUNT_OF_ELEMENTS, 242	ER_WRONG_VALUE_FOR_TYPE, 30
ER_WRONG_DATETIME_SPEC, 165	ER_WRONG_VALUE_FOR_VAR, 19
ER_WRONG_DB_NAME, 10	ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART, 132
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 34	ER_X509_CANT_CHMOD_KEY, 184
ER_WRONG_FIELD_SPEC, 7	ER_X509_CANT_CREATE_CERT, 184
ER_WRONG_FIELD_TERMINATORS, 8	ER_X509_CANT_READ_CA_CERT, 184
ER_WRONG_FIELD_WITH_GROUP, 7	ER_X509_CANT_READ_CA_KEY, 184
ER_WRONG_FIELD_WITH_GROUP_V2, 73	ER_X509_CANT_WRITE_CERT, 184
ER_WRONG_FILE_NAME, 76	ER_X509_CANT_WRITE_KEY, 184
ER_WRONG_FK_DEF, 19	ER_X509_CIPHERS_MISMATCH, 184
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 75	ER_X509_ISSUER_MISMATCH, 184
ER_WRONG_GROUP_FIELD, 7	ER_X509_NEEDS_RSA_PRIVKEY, 184
ER_WRONG_JSON_TABLE_VALUE, 98	ER_X509_SUBJECT_MISMATCH, 184
ER_WRONG_KEY_COLUMN, 14	ER_XAER_DUPID, 32
ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 109	ER_XAER_INVALID, 29
ER_WRONG_LOCK_OF_SYSTEM_TABLE, 31	ER_XAER_NOTA, 29
ER_WRONG_MRG_TABLE, 14	ER_XAER_OUTSIDE, 29
ER_WRONG_MVI_VALUE, 124	ER_XAER_RMERR, 29
ER_WRONG_NAME_FOR_CATALOG, 22	ER_XAER_RMFAIL, 29
ER_WRONG_NAME_FOR_INDEX, 22	ER_XA_CANT_CREATE_MDL_BACKUP, 538
ER_WRONG_NATIVE_TABLE_STRUCTURE, 46	ER_XA_COMMITTING_XID, 177
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 18	ER_XA_IGNOREING_XID, 177
ER_WRONG_OBJECT, 26	ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER, 177
ER_WRONG_OUTER_JOIN, 11	ER_XA_RBDEADLOCK, 41
ER_WRONG_OUTER_JOIN_UNUSED, 11	ER_XA_RBROLLBACK, 29
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 40	ER_XA_RBTIMEOUT, 41
ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 10	ER_XA_RECOVERY_DONE, 178
ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 40	ER_XA_RECOVER_EXPLANATION, 178
ER_WRONG_PARAMETERS_TO_PROCEDURE, 10	ER_XA_RECOVER_FOUND_TRX_IN_SE, 177
ER_WRONG_PARAMETERS_TO_STORED_FCT, 40	ER_XA_RECOVER_FOUND_XA_TRX, 177
ER_WRONG_PARTITION_NAME, 39	ER_XA_REPLICATION_FILTERS, 123
ER_WRONG_PERFSCHEMA_USAGE, 46	ER_XA_RETRY, 82
ER_WRONG_SIZE_NUMBER, 37	ER_XA_ROLLING_BACK_XID, 177
ER_WRONG_SPVAR_TYPE_IN_LIMIT, 47	ER_XA_STARTING_RECOVERY, 177
ER_WRONG_SRID_FOR_COLUMN, 96	ER_XA_TEMP_TABLE, 146
ER_WRONG_STRING_LENGTH, 33	ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED, 311
ER_WRONG_SUB_KEY, 9	ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED, 308
ER_WRONG_SUM_SELECT, 7	ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED, 315
ER_WRONG_TABLESPACE_NAME, 76	ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD, 314
ER_WRONG_TABLE_NAME, 10	ER_XPLUGIN_CLIENT_KILL_MSG, 313
	ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED, 313

ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED, 310	ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF, 315
ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN, 311	ER_XPLUGIN_FAILED_TO_USE_SSL_CONF, 304
ER_XPLUGIN_COMPRESSION_ERROR, 540	ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS, 552
ER_XPLUGIN_DETECTED_HANGING_CLIENTS, 308	ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA, 314
ER_XPLUGIN_EMPTY_ADMIN_CMD, 314	ER_XPLUGIN_FORCE_STOP_CLIENT, 308
ER_XPLUGIN_ERROR_MSG, 304	ER_XPLUGIN_GET_PEER_ADDRESS_FAILED, 315
ER_XPLUGIN_ERROR_READING_SOCKET, 311	ER_XPLUGIN_INVALID_AUTH_METHOD, 311
ER_XPLUGIN_ERROR_WRITING_TO_CLIENT, 311	ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT, 311
ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP, 309	ER_XPLUGIN_IPv6_AVAILABLE, 313
ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER, 309	ER_XPLUGIN_LISTENER_SETUP_FAILED, 309
ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCORRECT 312	ER_XPLUGIN_LISTENER_STATUS_MSG, 312
ER_XPLUGIN_FAILED_AT_SSL_CONF, 310	ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR, 312
ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT, 308	ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED, 308
ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS, 553	ER_XPLUGIN_MESSAGE_TOO_LONG, 310
ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION, 313	ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING, 311
ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN, 310	ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION, 311
ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD, 314	ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_ 304
ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT, 314	ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC, 309
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO, 314	ER_XPLUGIN_RETRYING_BIND_ON_PORT, 312
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX, 313	ER_XPLUGIN_SCHEDULER_STARTED, 312
ER_XPLUGIN_FAILED_TO_GET_SYS_VAR, 314	ER_XPLUGIN_SCHEDULER_STOPPED, 312
ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION, 310	ER_XPLUGIN_SERVER_EXITED, 303
ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION, 313	ER_XPLUGIN_SERVER_EXITING, 303
ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION, 314	ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTION, 312
ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES, 309	ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTION, 313
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG, 315	ER_XPLUGIN_SHUTDOWN_TRIGGERED, 312
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT, 308	ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED, 309
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS, 310	ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED, 310
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG, 314	ER_XPLUGIN_STARTUP_FAILED, 303
ER_XPLUGIN_FAILED_TO_STOP_SERVICES, 499	ER_XPLUGIN_TASK_SCHEDULING_FAILED, 309
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT, 314	ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION, 310
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX, 513	ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT, 309
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX, 313	ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING, 309
	ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION, 311
	ER_XPLUGIN_UNINITIALIZED_MESSAGE, 310
	ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED, 313
	ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS, 312

ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX, 304	ER_ADD_PARTITION_NO_NEW_PARTITION error code, 36
ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER, 304	ER_ADD_PARTITION_SUBPART_ERROR error code, 36
ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION, 304	ER_ADMIN_WRONG_MRG_TABLE error code, 34
ER_XPLUING_NET_STARTUP_FAILED, 310	ER_AES_INVALID_IV error code, 63
ER_YES, 3	ER_AES_INVALID_KDF_ITERATIONS error code, 83
ER_ZLIB_Z_BUF_ERROR, 20	ER_AES_INVALID_KDF_NAME error code, 82
ER_ZLIB_Z_DATA_ERROR, 20	ER_AES_INVALID_KDF_OPTION_SIZE error code, 83
ER_ZLIB_Z_MEM_ERROR, 20	ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 70
WARN_AES_KEY_SIZE, 83	ER_AGGREGATE_ORDER_FOR_UNION error code, 67
WARN_COND_ITEM_TRUNCATED, 44	ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 67
WARN_DATA_TRUNCATED, 21	ER ALTER CONSTRAINT ENFORCEMENT NOT SUPPORTED error code, 128
WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 107	ER ALTER FILEGROUP FAILED error code, 37
WARN_NAMED_PIPE_ACCESS_EVERYONE, 64	ER ALTER_INFO error code, 9
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED, 43	ER ALTER_OPERATION_NOT_SUPPORTED error code, 60
WARN_NO_CONNECTION_METADATA, 41	ER ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 60
WARN_NO_MASTER_INFO, 41	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOIN error code, 61
WARN_ON_BLOCKHOLE_IN_RBR, 62	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE error code, 61
WARN_OPTION_BELOW_LIMIT, 48	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN error code, 61
WARN_OPTION_IGNORED, 42	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN error code, 145
WARN_PLUGIN_BUSY, 42	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY error code, 60
WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB, 116	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK error code, 61
WARN_UNSUPPORTED_ACL_TABLES_READ, 136	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_REM error code, 60
WARN_USELESS_SPATIAL_INDEX, 99	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS error code, 61
ER_ABORTING error code, 166	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS error code, 70
ER_ABORTING_CONNECTION error code, 13	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN error code, 61
ER_ABORTING_USER_CONNECTION error code, 265	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK error code, 61
ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 63	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL error code, 61
ER_ACCESS_DENIED_ERROR error code, 6	ER ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION error code, 60
ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD error code, 266	ER AMBIGUOUS_FIELD_TERM error code, 34
ER_ACCESS_DENIED_ERROR_WITH_PASSWORD error code, 266	ER ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY error code, 271
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD, 545	ER ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME error code, 138
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED_BY_PASSWORD, 266	ER ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE error code, 140
ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 47	ER APPLIER_LOG_EVENT_VALIDATION_ERROR error code, 95
ER_ACCOUNT_HAS_BEEN_LOCKED error code, 76	
ER_ACCOUNT_WITH_EXPIRED_PASSWORD error code, 583	
ER_ACL_OPERATION_FAILED error code, 83	
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG error code, 535	
ER_ADDRESSES_FOR_HOSTNAME_HEADER error code, 160	
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM error code, 160	

ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS error code, 137	ER_AUDIT_LOG_FILTER_INVALID_COLUMN_COUNT error code, 301
ER_ATTRIBUTE_IGNORED error code, 98	ER_AUDIT_LOG_FILTER_INVALID_COLUMN_DEFINITION error code, 301
ER_AUDIT_API_ABORT error code, 79	ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED error code, 299
ER_AUDIT_CANT_ABORT_COMMAND error code, 263	ER_AUDIT_LOG_FILTER_RESULT_MSG error code, 301
ER_AUDIT_CANT_ABORT_EVENT error code, 263	ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE error code, 302
ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD error code, 541	ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error code, 539
ER_AUDIT_LOG_CANNOT_READ_PASSWORD error code, 535	OTHER POLICIES
ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD error code, 535	ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER error code, 506
ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH error code, 299	ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR error code, 299
ER_AUDIT_LOG_CANNOT_STORE_PASSWORD error code, 535	ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error code, 125
ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY error code, 506	ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 534
ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING error code, 534	ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE error code, 606
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE error code, 300	ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 505
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION error code, 300	ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 507
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION error code, 300	ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY error code, 505
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_EMPTY error code, 506	ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR error code, 505
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NO ENCRYPTION error code, 506	ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL error code, 301
ER_AUDIT_LOG_FILE_AUTO_PRUNED error code, 565	ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE error code, 301
ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY PROCESSED error code, 534	ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE error code, 301
ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE REQUIRED FORMAT error code, 534	ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR error code, 301
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS MISSING error code, 534	ER_AUDIT_LOG_JSON_READER_INVALID error code, 301
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS MISSING error code, 534	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY error code, 506
ER_AUDIT_LOG_FILE_PRUNE_FAILED error code, 565	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID error code, 534
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE AFTER READING error code, 302	ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED error code, 506
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM TABLE error code, 302	ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED error code, 299
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE FOR READ error code, 302	ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED error code, 535
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT INTO TABLE error code, 302	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH error code, 300
ER_AUDIT_LOG_FILTER_FAILED_TO_READ TABLE error code, 302	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED error code, 538
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE TABLE error code, 301	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST error code, 299
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE TABLE error code, 301	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED error code, 507

ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE error code, 506	ER_AUTHCACHE_ROLE_TABLES_DODGY error code, 186
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT error code, 539	ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 188
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE error code, 539	ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING error code, 187
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 539	ER_AUTHCACHE_TABLE_USER_IGNORED_DEPRECATED_PASSWORD error code, 186
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 82	ER_AUTHCACHE_TABLE_USER_IGNORED_INVALID_PASSWORD error code, 187
ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC error code, 506	ER_AUTHCACHE_TABLE_USER_IGNORED_NEEDS_PLUGIN error code, 186
ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER error code, 505	ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE error code, 186
ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS error code, 300	ER_AUTHCACHE_USER_TABLE_DODGY error code, 186
ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE error code, 300	ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY error code, 603
ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAME error code, 300	ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY error code, 578
ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED error code, 300	ER_AUTHENTICATION_OCI_IAM error code, 578
ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_RENAME error code, 300	ER_AUTHENTICATION_OCI_IMDS error code, 578
ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AURACLE_EVENTS error code, 190	ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING error code, 578
ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 191	ER_AUTHENTICATION_OCI_INVALID_TOKEN error code, 603
ER_AUDIT_WARNING error code, 263	ER_AUTHENTICATION_OCI_NONCE error code, 578
ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM error code, 188	ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND error code, 578
ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 187	ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS error code, 578
ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKED error code, 187	ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS_IN_TOKEN error code, 604
ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME error code, 187	ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED error code, 578
ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE error code, 187	ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR error code, 578
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME error code, 554	ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH error code, 603
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHENTICATION error code, 554	ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED error code, 603
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED error code, 187	ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT error code, 577
ER_AUTHCACHE_PLUGIN_CONFIG error code, 186	ER_AUTHENTICATION_PLUGIN_LOG error code, 577
ER_AUTHCACHE_PLUGIN_MISSING error code, 186	ER_AUTHENTICATION_PLUGIN_OOM error code, 577
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BARE error code, 188	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED error code, 576
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE error code, 188	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT error code, 576
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE error code, 186	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT error code, 577
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME error code, 554	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED error code, 577
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHENTICATION error code, 554	ER_AUTHENTICATION_POLICY_MISMATCH error code, 142
	ER_AUTH_CANT_ACTIVATE_ROLE error code, 184

ER_AUTH_CANT_CREATE_RSA_PAIR error code, 185	ER_BEG_INITFILE error code, 168
ER_AUTH_CANT_SET_DEFAULT_PLUGIN error code, 172	ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD error code, 607
ER_AUTH_CANT_WRITE_PRIVKEY error code, 185	ER_BEYOND_SERVER_UPGRADE_THRESHOLD error code, 607
ER_AUTH_CANT_WRITE_PUBKEY error code, 185	ER_BINLOG_ATTACHING_THREAD_MEMORY_FINALY_AV error code, 253
ER_AUTH_CERTS_SAVED_TO_DATADIR error code, 185	ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 51
ER_AUTH_CERT_GENERATION_DISABLED error code, 185	ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 256
ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY error code, 527	ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 256
ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG error code, 572	ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED error code, 259
ER_AUTH_KEYS_SAVED_TO_DATADIR error code, 185	ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 256
ER_AUTH_KEY_GENERATION_DISABLED error code, 186	ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 256
ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT error code, 185	ER_BINLOG_CANT_CREATE_CACHE_FOR_LOG error code, 253
ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG error code, 305	ER_BINLOG_CANT_DELETE_FILE error code, 256
ER_AUTH_RSA_CANT_FIND error code, 183	ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_IN error code, 258
ER_AUTH_RSA_CANT_PARSE error code, 183	ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MAT error code, 258
ER_AUTH_RSA_CANT_READ error code, 183	ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 258
ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION error code, 185	ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 255
ER_AUTH_RSA_FILES_NOT_FOUND error code, 183	ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LO error code, 256
ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION error code, 185	ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 257
ER_AUTH_USING_EXISTING_CERTS error code, 185	ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 259
ER_AUTOINC_READ_FAILED error code, 33	ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 254
ER_AUTO_CONVERT error code, 20	ER_BINLOG_CANT_OPEN_LOG error code, 253
ER_AUTO_INCREMENT_CONFLICT error code, 62	ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 256
ER_AUTO_OPTIONS_FAILED error code, 173	ER_BINLOG_CANT_RESIZE_CACHE error code, 253
ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_ON error code, 54	ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 256
ER_BACK_IN_TIME error code, 166	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 259
ER_BAD_DB_ERROR error code, 6	ER_BINLOG_CANT_USE_FOR_LOGGING error code, 255
ER_BAD_FIELD_ERROR error code, 7	ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 259
ER_BAD_FT_COLUMN error code, 22	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED error code, 590
ER_BAD_HOST_ERROR error code, 5	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS error code, 590
ER_BAD_LOG_STATEMENT error code, 39	ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE error code, 590
ER_BAD_NULL_ERROR error code, 6	ER_BINLOG_CRASH_RECOVERY_FAILED error code, 259
ER_BAD_NULL_ERROR_NOT_IGNORED error code, 99	
ER_BAD_REPLICA error code, 16	
ER_BAD_REPLICA_AUTO_POSITION error code, 54	
ER_BAD_REPLICA_UNTIL_COND error code, 22	
ER_BAD_SLAVE error code, 16	
ER_BAD_SLAVE_AUTO_POSITION error code, 54	
ER_BAD_SLAVE_UNTIL_COND error code, 22	
ER_BAD_TABLE_ERROR error code, 6	
ER_BAD_TIMESTAMP_FORMAT error code, 149	
ER_BASE64_DECODE_ERROR error code, 39	
ER_BASEDIR_SET_TO error code, 269	
ER_BEFORE_DML_VALIDATION_ERROR error code, 74	

ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG error code, 590	ER_BINLOG_FILE_BEING_READ_NOT_PURGED error code, 253
ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED error code, 590	ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 254
ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED error code, 590	ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 254
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 30	ER_BINLOG_FILE_NAME_TOO_LONG error code, 254
ER_BINLOG_END error code, 167	ER_BINLOG_FILE_OPEN_FAILED error code, 270
ER_BINLOG_ERROR_GETTING_NEXT_LOG_FROM_INDEX error code, 256	ER_BINLOG_IO_ERROR_READING_HEADER error code, 253
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG error code, 255	ER_BINLOG_LOGGING_IMPOSSIBLE error code, 40
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG error code, 254	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS error code, 258
ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA error code, 254	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_SLAVES error code, 258
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 255	ER_BINLOG_LOGGING_NOT_POSSIBLE error code, 284
ER_BINLOG_EVENTS_READ_FROM_RELAY_LOG_INFO error code, 254	ER_BINLOG_LOGICAL_CORRUPTION error code, 62
ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 270	ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 285
ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 284	ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION error code, 114
ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER error code, 100	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AFTER error code, 114
ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING error code, 255	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UP error code, 114
ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING error code, 255	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY error code, 114
ER_BINLOG_FAILED_TO_DELETE_LOG_FILE error code, 258	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT error code, 114
ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING error code, 255	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOG error code, 114
ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 257	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE error code, 45
ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 256	ER_BINLOG_NEEDS_SERVERID error code, 171
ER_BINLOG_FAILED_TO_READ_REGISTER_FILE error code, 258	ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP error code, 243
ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 258	ER_BINLOG_PURGE_EMFILE error code, 40
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING error code, 255	ER_BINLOG_PURGE_FATAL_ERR error code, 28
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 259	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX error code, 257
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 259	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE error code, 257
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 257	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE error code, 257
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 254	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE error code, 257
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN_TABLE error code, 255	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE error code, 257
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE error code, 243	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG error code, 257
ER_BINLOG_FATAL_ERROR error code, 40	ER_BINLOG_PURGE_PROHIBITED error code, 28
	ER_BINLOG_RECOVERING_AFTER_CRASH_USING error code, 259
	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE error code, 45

ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE error code, 45	ER_BINLOG_UNSAFE_SKIP_LOCKED error code, 88
ER_BINLOG_ROW_INJECTION_AND_STMT_MODE error code, 45	ER_BINLOG_UNSAFE_STATEMENT error code, 40
ER_BINLOG_ROW_LOGGING_FAILED error code, 37	ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 46
ER_BINLOG_ROW_MODE_AND_STMT_ENGINE error code, 45	ER_BINLOG_UNSAFE_SYSTEM_TABLE error code, 45
ER_BINLOG_ROW_VALUE_OPTION_IGNORED error code, 498	ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error code, 46
ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_ERROR_IGNORES error code, 499	ER_BINLOG_UNSAFE_UDF error code, 45
ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX error code, 51	ER_BINLOG_UNSAFE_UPDATE_IGNORE error code, 49
ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE error code, 264	ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT error code, 50
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES error code, 60	ER_BINLOG_UNSAFE_XA error code, 82
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE error code, 45	ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED error code, 498
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READ error code, 531	ER_BINLOG_WARNING_SUPPRESSED error code, 260
ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL error code, 136	ER_BLOBS_AND_NO_TERMINATED error code, 8
ER_BINLOG_UNSAFE_AND_STMT_ENGINE error code, 45	ER_BLOB_CANT_HAVE_DEFAULT error code, 10
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 45	ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 35
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 50	ER_BLOB_KEY_WITHOUT_LENGTH error code, 14
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT error code, 49	ER_BLOB_USED_AS_KEY error code, 8
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT error code, 49	ER_BOOST_GEOMETRY_CENTROID_EXCEPTION error code, 68
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC error code, 50	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION error code, 68
ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT error code, 533	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION error code, 76
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 65	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION error code, 68
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT error code, 49	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION error code, 68
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE error code, 49	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION error code, 68
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error code, 50	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION error code, 69
ER_BINLOG_UNSAFE_LIMIT error code, 45	ER_BOOTSTRAP_CANT_THREAD error code, 155
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT error code, 265	ER_BUFPOOL_RESIZE_INPROGRESS error code, 80
ER_BINLOG_UNSAFE_MIXED_STATEMENT error code, 47	ER_BUILD_ID error code, 592
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELECT error code, 47	ER_BULK_EXECUTOR_ERROR error code, 151
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS error code, 46	ER_BULK_EXECUTOR_INFO error code, 596
ER_BINLOG_UNSAFE_NOWAIT error code, 88	ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER error code, 151
ER_BINLOG_UNSAFE_REPLACE_SELECT error code, 49	ER_BULK_LOADER_COMPONENT_ERROR error code, 151
ER_BINLOG_UNSAFE_ROUTINE error code, 30	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_I error code, 151
	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_I error code, 151
	ER_BULK_LOADER_INFO error code, 596
	ER_BULK_LOAD_DATA_FAILED error code, 151
	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 152
	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOCAL error code, 597

ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 153	ER_CANNOT ALTER SRID DUE TO INDEX error code, 96
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 598	ER_CANNOT CHANGE TO ROOT DIR error code, 269
ER_BULK_PARSER_MISSING_ENCLOSED_BY error code, 152	ER_CANNOT CONVERT STRING error code, 119
ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG error code, 597	ER_CANNOT CREATE VIRTUAL INDEX CONSTRAINT error code, 80
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 152	ER_CANNOT DISCARD TEMPORARY TABLE error code, 65
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 597	ER_CANNOT DROP COLUMN FUNCTIONAL INDEX error code, 113
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR error code, 152	ER_CANNOT FIND KEY IN KEYRING error code, 110
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG error code, 598	ER_CANNOT GET SERVER VERSION FROM TABLESPACE HEAD error code, 524
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING BY error code, 152	ER_CANNOT GRANT ROLES TO ANONYMOUS USER error code, 126
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING BY error code, 598	ER_CANNOT GRANT SYSTEM PRIV TO MANDATORY ROLE error code, 125
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 152	ER_CANNOT INTERPRET PERSISTED SENSITIVE VARIABLES error code, 581
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 598	ER_CANNOT LOAD FROM TABLE_V2 error code, 50
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG error code, 598	ER_CANNOT LOCK USER MANAGEMENT CACHES error code, 86
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 152	ER_CANNOT LOG PARTIAL DROP DATABASE WITH GTID error code, 73
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG error code, 597	ER_CANNOT PERSIST SENSITIVE VARIABLES error code, 147
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 152	ER_CANNOT PURGE BINLOG WITH BACKUP LOCK error code, 145
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 598	ER_CANNOT SET DATABASE ENCRYPTION error code, 116
ER_BULK_READER_COMMUNICATION_ERROR error code, 151	ER_CANNOT SET LOG ERROR SERVICES error code, 269
ER_BULK_READER_COMMUNICATION_ERROR_LOG error code, 597	ER_CANNOT SET SERVER VERSION IN TABLESPACE HEAD error code, 524
ER_BULK_READER_INFO error code, 596	ER_CANNOT SET TABLESPACE ENCRYPTION error code, 116
ER_BULK_READER_LIBCURL_ERROR error code, 151	ER_CANNOT SET TABLE ENCRYPTION error code, 116
ER_BULK_READER_LIBCURL_ERROR_LOG error code, 597	ER_CANNOT USER error code, 29
ER_BULK_READER_LIBCURL_INIT_FAILED error code, 151	ER_CANNOT USER REFERENCED AS DEFINER error code, 136
ER_BULK_READER_LIBCURL_INIT_FAILED_LOG error code, 597	ER_CANNOT USE AUTOEXTEND_SIZE_CLAUSE error code, 138
ER_BULK_READER_SERVER_ERROR error code, 151	ER_CANNOT USE ENCRYPTION_CLAUSE error code, 117
ER_BULK_READER_SERVER_ERROR_LOG error code, 597	ER_CANT ACCESS CAPATH error code, 173
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_ERROR error code, 521	ER_CANT ALTER INFORMATION SCHEMA COLLATIONS error code, 21
ER_CALL_ME_LOCALHOST error code, 167	ER_CANT AGGREGATE 3COLLATIONS error code, 21
ER_CANNOT_ADD_FOREIGN error code, 18	ER_CANT AGGREGATE NCOLLATIONS error code, 21
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 81	ER_CANT ALLOC TABLE OBJECT error code, 247
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 80	ER_CANT CHANGE SYS_VAR IN READ_ONLY_MODE error code, 153

ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 39	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT error code, 248
ER_CANT_CHECK_PID_PATH error code, 370	ER_CANT_INCREASE_MAX_OPEN_FILES error code, 168
ER_CANT_CHOWN_DATADIR error code, 172	ER_CANT_INITIALIZE_BUILTIN_PLUGINS error code, 171
ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTO_POSITION error code, 137	ER_CANT_INITIALIZE_DYNAMIC_PLUGINS error code, 171
ER_CANT_CREATE_ADMIN_THREAD error code, 520	ER_CANT_INITIALIZE_EARLY_PLUGINS error code, 171
ER_CANT_CREATE_CACHE_FOR_DB_OPT error code, 248	ER_CANT_INITIALIZE_GTID error code, 171
ER_CANT_CREATE_DB error code, 3	ER_CANT_INITIALIZE_UDF error code, 11
ER_CANT_CREATE_FILE error code, 3	ER_CANT_INIT_DBS error code, 169
ER_CANT_CREATE_GEOMETRY_OBJECT error code, 30	ER_CANT_INIT_SCHEDULER_THREAD error code, 159
ER_CANT_CREATE_HANDLER_FILE error code, 35	ER_CANT_INIT_TC_LOG error code, 159
ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE error code, 247	ER_CANT_INIT_TIMER error code, 173
ER_CANT_CREATE_HANDLE_MGR_THREAD error code, 158	ER_CANT_JOIN_SHUTDOWN_THREAD error code, 172
ER_CANT_CREATE_INTERRUPT_THREAD error code, 165	ER_CANT_LOCK error code, 4
ER_CANT_CREATE_NAMED_PIPES_THREAD error code, 165	ER_CANT_LOCK_LOG_TABLE error code, 38
ER_CANT_CREATE_PID_FILE error code, 164	ER_CANT_LOCK_TABLE error code, 247
ER_CANT_CREATE_SCHEDULER_THREAD error code, 159	ER_CANT_LOCK_TABLESPACE error code, 248
ER_CANT_CREATE_SHM_THREAD error code, 165	ER_CANT_MODIFY_SRID_0 error code, 103
ER_CANT_CREATE_SHUTDOWN_THREAD error code, 164	ER_CANT_MODIFY_SRS_USED_BY_COLUMN error code, 104
ER_CANT_CREATE_TABLE error code, 3	ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 190
ER_CANT_CREATE_TABLE_SHARE_FROM_FRM error code, 247	ER_CANT_OPEN_CA error code, 173
ER_CANT_CREATE_TCPIP_THREAD error code, 165	ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE error code, 250
ER_CANT_CREATE_TEST_FILE error code, 163	ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET error code, 248
ER_CANT_CREATE_THREAD error code, 12	ER_CANT_OPEN_DIR error code, 250
ER_CANT_CREATE_USER_WITH_GRANT error code, 30	ER_CANT_OPEN_ERROR_LOG error code, 173
ER_CANT_CREATE_UUID error code, 162	ER_CANT_OPEN_FILE error code, 4
ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN error code, 206	ER_CANT_OPEN_FRM_FILE error code, 190
ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_MODE_IS OFF error code, 54	ER_CANT_OPEN_LIBRARY error code, 11
ER_CANT_DO_THIS_DURING_AN_TRANSACTION error code, 15	ER_CANT_OPEN_TABLE_MYSQL_PROC error code, 250
ER_CANT_DROP_FIELD_OR_KEY error code, 9	ER_CANT_PARSE_STORED_ROUTINE_BODY error code, 249
ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONLINE_BINLOG error code, 75	ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN error code, 542
ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_ONLY error code, 146	ER_CANT_READ_DIR error code, 4
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION error code, 56	ER_CANT_READ_TABLESPACE error code, 169
ER_CANT_FIND_DL_ENTRY error code, 11	ER_CANT_READ_FRM_FILE error code, 190
ER_CANT_FIND_SYSTEM_REC error code, 4	ER_CANT_READ_TABLE_MYSQL_PROC error code, 250
ER_CANT_FIND_UDF error code, 11	ER_CANT_REMOVE_ALL_FIELDS error code, 9
ER_CANT_GET_STAT error code, 4	ER_CANT_REMOVE_PID_FILE error code, 164
ER_CANT_HASH_DO_AND_IGNORE_RULES error code, 172	ER_CANT_RENAME_LOG_TABLE error code, 39
	ER_CANT_REOPEN_TABLE error code, 12
	ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION error code, 505
	ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE error code, 505

ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFFER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON	error code, 505	error code, 144
ER_CANT_RESET_MASTER error code, 81		ER_CANT_USE_OPTION_HERE error code, 19
ER_CANT_RESET_SOURCE error code, 81		ER_CANT_USE_SAME_UUID_AS_GROUP_NAME
ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY error code, 154		error code, 138
ER_CANT_SAVE_GTIDS error code, 172		ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID
ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_WAS_APPLIED error code, 137		error code, 140
ER_CANT_SET_DATADIR error code, 172		ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID
ER_CANT_SET_DATA_DIR error code, 518		error code, 140
ER_CANT_SET_ERROR_LOG_SERVICE error code, 102		ER_CAPACITY_EXCEEDED error code, 80
ER_CANT_SET_ERROR_SUPPRESSION_LIST error code, 106		ER_CAPACITY_EXCEEDED_IN_PARSER error code, 81
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMANDLINE error code, 510		ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 80
ER_CANT_SET_GTID_MODE error code, 75		ER_CA_SELF_SIGNED error code, 161
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_ON error code, 55		ER_CANNOT_ENFORCE_GTID_CONSISTENCY error code, 158
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON error code, 55		ER_CHANGED_GTID_MODE error code, 158
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF error code, 55		ER_CHANGED_GTID_MODE error code, 158
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID error code, 56		ER_CHANGED_MAX_CONNECTIONS error code, 169
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS error code, 86		ER_CANNOT_OPEN_OPEN_FILES error code, 168
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY error code, 60		ER_CHANGED_TABLE_OPEN_CACHE error code, 140
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS ARE NOT EMPTY error code, 60		ER_CHANGE_MASTER_PASSWORD_LENGTH error code, 69
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE error code, 247		ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM error code, 125
ER_CANT_SET_PATH_FOR error code, 250		ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM error code, 125
ER_CANT_SET_PERSISTED error code, 154		ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 126
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS error code, 138		ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 126
ER_CANT_SET_UP_PERSISTED_VALUES error code, 172		ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID error code, 143
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID error code, 77		ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION error code, 143
ER_CANT_START_ERROR_LOG_SERVICE error code, 268		ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITH_ANONYMOUS error code, 140
ER_CANT_STAT_DATADIR error code, 172		ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITH_ANONYMOUS error code, 143
ER_CANT_STAT_FILE error code, 258		ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FOR_GTID error code, 143
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT error code, 51		ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE error code, 144
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG error code, 32		ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE error code, 52
ER_CANT_UPDATE_WITH_READLOCK error code, 18		ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM error code, 140
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DONOT_READ error code, 248		ER_CHANGE_SOURCE_PASSWORD_LENGTH error code, 69
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_ON error code, 136		ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 126
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_ON error code, 75		ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 126
		ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT error code, 126
		ER_CHARACTER_SET_MISMATCH error code, 134
		ER_CHECKING_TABLE error code, 247
		ER_CHECKREAD error code, 4

ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCES error code, 116	ER_CLONE_CHARSET error code, 120
ER_CHECK_CONSTRAINT_DUP_NAME error code, 115	ER_CLONE_CLIENT_TRACE error code, 518
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED error code, 115	ER_CLONE_CONFIG error code, 120
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 115	ER_CLONE_CREATE_HANDLER_FAIL_TRACE error code, 280
ER_CHECK_CONSTRAINT_NOT_FOUND error code, 115	ER_CLONE_DDL_IN_PROGRESS error code, 95
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN error code, 115	ER_CLONE_DISABLED error code, 121
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN error code, 115	ER_CLONE_DISK_SPACE error code, 121
ER_CHECK_CONSTRAINT_ROW_VALUE error code, 115	ER_CLONE_DONOR error code, 120
ER_CHECK_CONSTRAINT_VARIABLES error code, 115	ER_CLONE_DONOR_TRACE error code, 517
ER_CHECK_CONSTRAINT_VIOLATED error code, 115	ER_CLONE_DONOR_VERSION error code, 120
ER_CHECK_NOT_IMPLEMENTED error code, 14	ER_CLONE_ENCRYPTION error code, 121
ER_CHECK_NO_SUCH_TABLE error code, 14	ER_CLONE_HANDLER_EXISTS error code, 279
ER_CHECK_TABLE_FUNCTIONS error code, 609	ER_CLONE_HANDLER_EXIST_TRACE error code, 279
ER_CHECK_TABLE_FUNCTIONS_DETAIL error code, 609	ER_CLONE_INFO_CLIENT error code, 517
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET error code, 599	ER_CLONE_INFO_SERVER error code, 518
ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET error code, 602	ER_CLONE_IN_PROGRESS error code, 121
ER_CHECK_TABLE_MIN_REC_FLAG_SET error code, 602	ER_CLONE_LOOPBACK error code, 121
ER_CLIENT_DOES_NOT_SUPPORT error code, 96	ER_CLONE_NETWORK_PACKET error code, 130
ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK error code, 149	ER_CLONE_OS error code, 120
ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE error code, 107	ER_CLONE_PLATFORM error code, 120
ER_CLIENT_INTERACTION_TIMEOUT error code, 139	ER_CLONE_PLUGIN_MATCH error code, 120
ER_CLIENT_KEYRING_UDF_KEY_INVALID error code, 127	ER_CLONE_PLUGIN_NOT_LOADED error code, 279
ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG error code, 127	ER_CLONE_PLUGIN_NOT_LOADED_TRACE error code, 279
ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID error code, 127	ER_CLONE_PROTOCOL error code, 120
ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG error code, 127	ER_CLONE_PROTOCOL_ERROR error code, 517
ER_CLIENT_LOCAL_FILES_DISABLED error code, 129	ER_CLONE_PROTOCOL_TRACE error code, 517
ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS error code, 126	ER_CLONE_REMOTE_ERROR error code, 517
ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT error code, 127	ER_CLONE_SERVER_TRACE error code, 518
ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 127	ER_CLONE_SHUTDOWN_TRACE error code, 536
ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_PRIVILEGE error code, 127	ER_CLONE_SYS_CONFIG error code, 120
ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT error code, 129	ER_CLONE_TOO_MANY_CONCURRENT_CLONES error code, 94
	ER_CMD_NEED_SUPER error code, 94
	ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 36
	ER_COALESCE_PARTITION_NO_PARTITION error code, 36
	ER_COLLATION_CHARSET_MISMATCH error code, 20
	ER_COLUMNACCESS_DENIED_ERROR error code, 12
	ER_COLUMN_CHANGE_SIZE error code, 122
	ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_TABLE error code, 115
	ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 65
	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 38
	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2 error code, 65
	ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CONTEXT error code, 131
	ER_COMMAND_SERVICE_BACKEND_FAILED error code, 149

ER_COMMENT_CONTAINS_INVALID_STRING error code, 146	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION error code, 591
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 30	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 591
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 85	ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 592
ER_COMPONENTS_CANT_LOAD error code, 85	ER_COMPONENT_EE_OPENSSL_ERROR error code, 592
ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 85	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 590
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 85	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 590
ER_COMPONENTS_CANT_UNLOAD error code, 86	ER_COMPONENT_FILTER_FILTER_CONFUSED error code, 306
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION error code, 284	ER_COMPONENT_FILTER_DIAGNOSTICS error code, 102
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 161	ER_COMPONENT_FILTER_FLABBERGASTED error code, 94
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DENIED error code, 565	ER_COMPONENT_FILTER_WRONG_VALUE error code, 499
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INVALID error code, 565	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY error code, 594
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 161	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE error code, 593
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 85	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE error code, 594
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION error code, 85	ER_COMPONENT_LOCK error code, 605
ER_COMPONENTS_NO_SCHEME error code, 85	ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 86
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 85	ER_COMPONENT_MASKING_ABI error code, 605
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 161	ER_COMPONENT_MASKING_ABI_REASON error code, 605
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 85	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 605
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 86	ER_COMPONENT_MASKING_OTHER_ERROR error code, 605
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 86	ER_COMPONENT_MASKING_RANDOM_CREATE error code, 605
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 85	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON error code, 605
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 592	ER_COMPONENT_SERVICE_CALL error code, 604
ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 592	ER_COMPONENT_SERVICE_CALL_RESULT error code, 605
ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 591	ER_COMPONENT_TABLE_INCORRECT error code, 86
ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 592	ER_COMPONENT_UNLOCK error code, 605
ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE error code, 591	ER_CONCURRENT_PROCEDURE_USAGE error code, 445
ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 591	ER_CONDITIONAL_DEBUG error code, 593
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENT error code, 591	ER_COND_ITEM_TOO_LONG error code, 44
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE error code, 591	ER_CONFIG_OPTION_WITHOUT_GROUP error code, 176
ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE error code, 591	ER_CONFIRMING_THE_FUTURE error code, 166
	ER_CONNECTING_DECLARATIONS error code, 24
	ER_CONFLICT_FN_PARSE_ERROR error code, 42
	ER_CONNECTION_ABORTED error code, 499
	ER_CONNECTION_HANDLING_OOM error code, 163
	ER_CONNECTION_METADATA error code, 16

ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 31	ER_CONN_TCP_START_FAIL error code, 181
ER_CONNECT_TO_MASTER error code, 18	ER_CONN_TPC_BIND_FAIL error code, 181
ER_CONNECT_TO_SOURCE error code, 18	ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET error code, 180
ER_CONN_ATTR_TRUNCATED error code, 183	ER_CONN_UNIX_LISTEN_FAILED error code, 182
ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 308	ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE error code, 183
ER_CONN_CONTROL_ERROR_MSG error code, 305	ER_CONN_UNIX_LOCK_FILE_CANT_CREATE error code, 182
ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 307	ER_CONN_UNIX_LOCK_FILE_CANT_DELETE error code, 183
ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY error code, 308	ER_CONN_UNIX_LOCK_FILE_CANT_OPEN error code, 182
ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY error code, 308	ER_CONN_UNIX_LOCK_FILE_CANT_READ error code, 182
ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE error code, 307	ER_CONN_UNIX_LOCK_FILE_CANT_SYNC error code, 182
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 307	ER_CONN_UNIX_LOCK_FILE_CANT_WRITE error code, 182
ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 307	ER_CONN_UNIX_LOCK_FILE_EMPTY error code, 182
ER_CONN_INIT_CONNECT_IGNORED error code, 307	ER_CONN_UNIX_LOCK_FILE_FAIL error code, 181
ER_CONN_INIT_CONNECT_IGNORED_MFA error code, 606	ER_CONN_UNIX_LOCK_FILE_GIVING_UP error code, 182
ER_CONN_LIMIT error code, 581	ER_CONN_UNIX_LOCK_FILE_PIDLESS error code, 182
ER_CONN_PER_THREAD_NO_THREAD error code, 179	ER_CONN_UNIX_NO_BIND_NO_START error code, 182
ER_CONN_PIP_CANT_CREATE_EVENT error code, 179	ER_CONN_UNIX_NO_FD error code, 182
ER_CONN_PIP_CANT_CREATE_PIPE error code, 179	ER_CONN_UNIX_PATH_TOO_LONG error code, 181
ER_CONN_SHM_CANT_CREATE_CONNECTION error code, 179	ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE error code, 180
ER_CONN_SHM_CANT_CREATE_SERVICE error code, 179	ER_CONSECUTIVE_REORG_PARTITIONS error code, 36
ER_CONN_SHM_LISTENER error code, 179	ER_CONSTRAINT_NOT_FOUND error code, 128
ER_CONN_SOCKET_ACCEPT_FAILED error code, 183	ER_CONVERT_MULTI_VALUE error code, 606
ER_CONN_SOCKET_SELECT_FAILED error code, 183	ER_CON_COUNT_ERROR error code, 5
ER_CONN_TCP_ADDRESS error code, 180	ER_CORE_VALUES error code, 165
ER_CONN_TCP_BIND_FAIL error code, 181	ER_CORRUPTED_JSON_DIFF error code, 97
ER_CONN_TCP_BIND_RETRY error code, 181	ER_CORRUPT_HELP_DB error code, 20
ER_CONN_TCP_CANT_RESET_V6ONLY error code, 181	ER_COULD_NOT_APPLY_JSON_DIFF error code, 97
ER_CONN_TCP_CANT_RESOLVE_HOSTNAME error code, 180	ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY error code, 513
ER_CONN_TCP_CREATED error code, 180	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS error code, 506
ER_CONN_TCP_ERROR_WITH_STRERROR error code, 180	ER_CRASHED_ON_REPAIR error code, 16
ER_CONN_TCP_IPV6_AVAILABLE error code, 180	ER_CRASHED_ON_USAGE error code, 16
ER_CONN_TCP_IPV6_UNAVAILABLE error code, 180	ER_CREATED_SYSTEM_WITH_VERSION error code, 277
ER_CONN_TCP_IP_NOT_LOGGED error code, 181	ER_CREATE_FILEGROUP_FAILED error code, 37
ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT error code, 180	ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR error code, 148
ER_CONN_TCP_LISTEN_FAIL error code, 181	ER_CREATING_NEW_UUID error code, 162
ER_CONN_TCP_NO_SOCKET error code, 179	ER_CREATING_NEW_UUID_FIRST_START error code, 268
ER_CONN_TCP_RESOLVE_INFO error code, 181	ER_CREDENTIALLESS_AUTO_USER_BAD error code, 163

ER_CREDENTIALS_CONTRADICT_TO_HISTORY error code, 95	ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET error code, 129
ER_CTE_MAX_RECURSION_DEPTH error code, 95	ER_DA_UDF_INVALID_CHARSET error code, 128
ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER error code, 89	ER_DA_UDF_INVALID_CHARSET_SPECIFIED error code, 127
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION error code, 89	ER_DA_UDF_INVALID_COLLATION error code, 128
ER_CTE_RECURSIVE_NOT_UNION error code, 149	ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE error code, 128
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FILTER error code, 89	ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET error code, 129
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE error code, 89	ER_DA_UNKNOWN_ERROR_NUMBER error code, 122
ER_CTE_RECURSIVE_REQUIRES_UNION error code, 89	ER_DBACCESS_DENIED_ERROR error code, 6
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED error code, 123	ER_DEBUG_CHECK_SHARES_DROPPED error code, 212
ER_CURRENT_PASSWORD_NOT_REQUIRED error code, 123	ER_DEBUG_CHECK_SHARES_INFO error code, 212
ER_CUT_VALUE_GROUP_CONCAT error code, 21	ER_DEBUG_CHECK_SHARES_OPEN error code, 212
ER_CYCLE_TIMER_IS_NOT_AVAILABLE error code, 280	ER_DB_ACCESS_DENIED error code, 121
ER_DATABASE_NAME error code, 43	ER_DB_CREATE_EXISTS error code, 4
ER_DATA_DIRECTORY_UNUSABLE error code, 513	ER_DB_DROP_EXISTS error code, 4
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE error code, 536	ER_DB_DROP_RMDIR error code, 4
ER_DATA_OUT_OF_RANGE error code, 47	ER_DB_DROP_RMDIR2 error code, 92
ER_DATA_TOO_LONG error code, 29	ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET error code, 248
ER_DATETIME_FUNCTION_OVERFLOW error code, 32	ER_DDL_IN_PROGRESS error code, 95
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_COLUMNS error code, 121	ER_DDL_LOG_ERROR error code, 39
ER_DA_CANT_OPEN_ERROR_LOG error code, 135	ER_DDL_MSG_1 error code, 574
ER_DA_CONN_LIMIT error code, 145	ER_DD_ABORTING_PARTIAL_UPGRADE error code, 188
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED error code, 141	ER_DD_CANNOT_EMPTY_AT_SHUTDOWN error code, 157
ER_DA_ERROR_LOG_MULTIPLE_FILTERS error code, 135	ER_DD_CANT_CREATE_OBJECT_KEY error code, 157
ER_DA_ERROR_LOG_TABLE_DISABLED error code, 135	ER_DD_CANT_CREATE_SP error code, 248
ER_DA_EXPIRE_LOGS_DAYS_IGNORED error code, 148	ER_DD_CANT_FETCH_TABLE_DATA error code, 248
ER_DA_GLOBAL_CONN_LIMIT error code, 145	ER_DD_CANT_FIX_SE_DATA error code, 248
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 132	ER_DD_CANT_GET_OBJECT_KEY error code, 157
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 132	ER_DD_CANT_RESOLVE_VIEW error code, 175
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN error code, 125	ER_DD_CREATED_FOR_UPGRADE error code, 189
ER_DA_INVALID_CONDITION_NUMBER error code, 53	ER_DD_ERROR_CREATING_ENTRY error code, 248
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED error code, 135	ER_DD_FAILSAFE error code, 155
ER_DA_OOM error code, 129	ER_DD_FRM_EXISTS_FOR_TABLE error code, 189
ER_DA_PLUGIN_INSTALL_ERROR error code, 122	ER_DD_INITIALIZE error code, 285
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN error code, 122	ER_DD_INITIALIZE_SQL_ERROR error code, 507
ER_DA_SSL_FIPS_MODE_ERROR error code, 144	ER_DD_INIT_FAILED error code, 156
ER_DA_SSL_LIBRARY_ERROR error code, 122	ER_DD_INIT_UPGRADE_FAILED error code, 156
	ER_DD_METADATA_NOT_FOUND error code, 157
	ER_DD_MINOR_DOWNGRADE error code, 286
	ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED error code, 286
	ER_DD_NO_VERSION_FOUND error code, 286
	ER_DD_NO_WRITES_NO_REPOPULATION error code, 155
	ER_DD_OBJECT_RELEASER_REMAINS error code, 157
	ER_DD_OBJECT_REMAINS error code, 157
	ER_DD_OBJECT_REMAINS_IN_RELEASER error code, 157

ER_DD_POPULATING_TABLES_FAILED error code, 157	ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED error code, 277
ER_DD_RESTART error code, 285	ER_DD_UPGRADE_SE_LOGS_FAILED error code, 277
ER_DD_SCHEMA_NOT_FOUND error code, 188	ER_DD_UPGRADE_START error code, 276
ER_DD_SE_INIT_FAILED error code, 188	ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED error code, 276
ER_DD_TABLESPACE_NOT_FOUND error code, 174	ER_DD_UPGRADE_TABLE_INTACT_ERROR error code, 282
ER_DD_TRG_CANT_ADD error code, 174	ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED error code, 276
ER_DD_TRG_CONNECTION_COLLATION_MISSING error code, 174	ER_DD_UPGRADE_VERSION_NOT_SUPPORTED error code, 286
ER_DD_TRG_DB_COLLATION_MISSING error code, 174	ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG error code, 285
ER_DD_TRG_DEFINDER_OOM error code, 174	ER_DD_VERSION_FOUND error code, 155
ER_DD_TRG_FILE_UNREADABLE error code, 174	ER_DD_VERSION_INSTALLED error code, 155
ER_DD_UPDATE_DATADIR_FLAG_FAIL error code, 608	ER_DD_VERSION_UNSUPPORTED error code, 155
ER_DD_UPDATING_PLUGIN_MD_FAILED error code, 157	ER_DD_VIEW_CANT_ALLOC_CHARSET error code, 156
ER_DD_UPGRADE error code, 286	ER_DD_VIEW_CANT_CREATE error code, 157
ER_DD_UPGRADE_COMPLETED error code, 532	ER_DD_VIEW_WITHOUT_DEFINER error code, 175
ER_DD_UPGRADE_DD_OPEN_FAILED error code, 275	ER_DEBUG_SYNC_EXECUTED error code, 158
ER_DD_UPGRADE_DD_POPULATED error code, 275	ER_DEBUG_SYNC_HIT error code, 158
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR error code, 276	ER_DEBUG_SYNC_HIT_LIMIT error code, 43
ER_DD_UPGRADE_FAILED_INIT_DD_SE error code, 276	ER_DEBUG_SYNC_OOM error code, 158
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE error code, 275	ER_DEBUG_SYNC_THREAD_MAX error code, 158
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS error code, 276	ER_DEBUG_SYNC_TIMEOUT error code, 43
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS error code, 276	ER_DEFAULT_AS_VAL_GENERATED error code, 130
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES error code, 275	ER_DEFAULT_SE_UNAVAILABLE error code, 173
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACE error code, 275	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED error code, 109
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE error code, 275	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 110
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN error code, 285	ER_DEFAULT_VAL_GENERATED_NON_PRIOR error code, 109
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED error code, 277	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC error code, 109
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED error code, 277	ER_DEFAULT_VAL_GENERATED_ROW_VALUE error code, 110
ER_DD_UPGRADE_FOUND_PREPARED_XA_TRANSACTION error code, 545	ER_DEFAULT_VAL_GENERATED_VARIABLES error code, 110
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED error code, 276	ER_DEFINITION_CONTAINS_INVALID_STRING error code, 146
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED error code, 276	ER_DROP_PARTITION_WITH_GRACE error code, 161
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED error code, 275	ER_DEPENDENT_BY_CHECK_CONSTRAINT error code, 130
ER_DD_UPGRADE_OFF error code, 286	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE error code, 109
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED error code, 275	ER_DEPENDENT_BY_FUNCTIONAL_INDEX error code, 117
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE error code, 286	ER_DEPENDENT_BY_GENERATED_COLUMN error code, 75
	ER_DEPENDENT_BY_PARTITION_FUNC error code, 119
	ER_DEPRECATED_NATIONAL error code, 104

ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS error code, 572	ER_DUP_FD_OPEN_FAILED error code, 268
ER_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 283	ER_DUP_FIELDNAME error code, 7
ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT error code, 283	ER_DUP_INDEX error code, 59
ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS error code, 163	ER_DUP_KEY error code, 4
ER_DEPRECATED_TLS_VERSION_SESSION error code, 569	ER_DUP_KEYNAME error code, 7
ER_DEPRECATED_UTF8_ALIAS error code, 104	ER_DUP_LIST_ENTRY error code, 67
ER_DEPRECATE_MSG_NO_REPLACEMENT error code, 283	ER_DUP_SIGNAL_SET error code, 43
ER_DEPRECATE_MSG_WITH_REPLACEMENT error code, 266	ER_DUP_UNIQUE error code, 14
ER_DERIVED_MUST_HAVE_ALIAS error code, 20	ER_DUP_UNKNOWN_IN_INDEX error code, 61
ER_DES_FILE_WRONG_KEY error code, 176	ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE error code, 102
ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN error code, 206	ER_EMPTY_PRIVILEGE_NAME_IGNORED error code, 559
ER_DETACHING_SESSION_LEFT_BY_PLUGIN error code, 206	ER_EMPTY_QUERY error code, 7
ER_DIMENSION_UNSUPPORTED error code, 71	ER_ENDING_INIT error code, 507
ER_DISABLED_STORAGE_ENGINE error code, 79	ER_END_INITFILE error code, 168
ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT error code, 158	ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING error code, 75
ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECOVER error code, 134	ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED error code, 133
ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECOVER error code, 134	ER_ENGINE_CANT_DROP_MISSING_TABLE error code, 92
ER_DISALLOWED_OPERATION error code, 97	ER_ENGINE_CANT_DROP_TABLE error code, 92
ER_DISCARD_FK_CHECKS_RUNNING error code, 58	ER_ENGINE_COST_FAILED_TO_READ error code, 203
ER_DISCONNECTING_REMAINING_CLIENTS error code, 166	ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AN error code, 203
ER_DISK_FULL_NOWAIT error code, 99	ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE error code, 202
ER_DIVISION_BY_ZERO error code, 27	ER_ENGINE_COST_UNKNOWN_COST_CONSTANT error code, 202
ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER error code, 68	ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE error code, 202
ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER error code, 67	ER_ENGINE_OUT_OF_MEMORY error code, 66
ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY error code, 284	ER_ERRMSG_CANT_FIND_FILE error code, 189
ER_DROP_FILEGROUP_FAILED error code, 37	ER_ERRMSG_CANT_READ error code, 189
ER_DROP_INDEX_FK error code, 38	ER_ERRMSG_LOADING_55_STYLE error code, 189
ER_DROP_LAST_PARTITION error code, 36	ER_ERRMSG_MISSING_IN_FILE error code, 189
ER_DROP_PARTITION_NON_EXISTENT error code, 36	ER_ERRMSG_OOM error code, 189
ER_DROP_PK_COLUMN_TO_DROP_GIPK error code, 148	ER_ERRMSG_REPLACEMENTS_FAILED error code, 262
ER_DUPLICATED_VALUE_IN_TYPE error code, 23	ER_ERRMSG_REPLACEMENT_DODGY error code, 262
ER_DUPLICATE_OPTION_KEY error code, 87	ER_ERROR_DURING_COMMIT error code, 15
ER_DUPLICATE_SYS_VAR error code, 508	ER_ERROR_DURING_FLUSH_LOGS error code, 15
ER_DUPLICATE_TABLE_LOCK error code, 88	ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE error code, 284
ER_DUP_ARGUMENT error code, 18	ER_ERROR_DURING_OPTIMIZE_TABLE error code, 247
ER_DUP_ENTRY error code, 7	ER_ERROR_DURING_ROLLBACK error code, 15
ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 39	ER_ERROR_ENABLING_KEYS error code, 247
ER_DUP_ENTRY_WITH_KEY_NAME error code, 40	ER_ERROR_INFO_FROM_DA error code, 503
	ER_ERROR_IN_TRIGGER_BODY error code, 49
	ER_ERROR_IN_UNKNOWN_TRIGGER_BODY error code, 49
	ER_ERROR_LOG_DESTINATION_NOT_A_FILE error code, 560
	ER_ERROR_ON_MASTER error code, 65

ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 80
 ER_ERROR_ON_READ error code, 4
 ER_ERROR_ON_RENAME error code, 4
 ER_ERROR_ON_SOURCE error code, 65
 ER_ERROR_ON_WRITE error code, 4
 ER_ERROR_WHEN_EXECUTING_COMMAND error code, 18
 ER_EVENT_ALREADY_EXISTS error code, 37
 ER_EVENT_CANNOT_ALTER_IN_THE_PAST error code, 40
 ER_EVENT_CANNOT_CREATE_IN_THE_PAST error code, 40
 ER_EVENT_CANT_FIND_TIMEZONE error code, 249
 ER_EVENT_CANT_GET_CHARSET error code, 249
 ER_EVENT_CANT_GET_COLLATION error code, 249
 ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT error code, 253
 ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD error code, 249
 ER_EVENT_CANT_INIT_QUEUE error code, 159
 ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT error code, 249
 ER_EVENT_DOES_NOT_EXIST error code, 37
 ER_EVENT_DROPPING error code, 204
 ER_EVENT_ENDS_BEFORE_STARTS error code, 38
 ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_IN_BINLOG error code, 252
 ER_EVENT_ERROR_DURING_COMPILATION error code, 204
 ER_EVENT_EXECUTION_FAILED error code, 159
 ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE error code, 204
 ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT error code, 204
 ER_EVENT_EXEC_TIME_IN_THE_PAST error code, 38
 ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG error code, 37
 ER_EVENT_INVALID_CREATION_CTX error code, 41
 ER_EVENT_LAST_EXECUTION error code, 159
 ER_EVENT_MESSAGE_STACK error code, 159
 ER_EVENT_PURGING_QUEUE error code, 159
 ER_EVENT_RECURSION_FORBIDDEN error code, 39
 ER_EVENT_SAME_NAME error code, 38
 ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT error code, 252
 ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB error code, 252
 ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE error code, 253
 ER_EVENT_SET_VAR_ERROR error code, 39
 ER_EVENT_UNABLE_TO_DROP_EVENT error code, 253
 ER_EXCEEDED_MV_KEYS_NUM error code, 124
 ER_EXCEEDED_MV_KEYS_SPACE error code, 124
 ER_EXCEPTIONS_WRITE_ERROR error code, 42
 ER_EXCESS_ARGUMENTS error code, 169
 ER_EXPIRE_LOGS_DAYS_IGNORED error code, 284
 ER_EXPLAIN_NOT_SUPPORTED error code, 65
 ER_FAILED_DEFAULT_ROLES error code, 85
 ER_FAILED_GET_DD_PROPERTY error code, 607
 ER_FAILED_READ_FROM_PAR_FILE error code, 47
 ER_FAILED_REVOKE_ROLE error code, 85
 ER_FAILED_ROLE_GRANT error code, 84
 ER_FAILED_SET_DD_PROPERTY error code, 607
 ER_FAILED_START_MYSQLD_DAEMON error code, 268
 ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP error code, 273
 ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP error code, 273
 ER_FAILED_TO_ADD_RPL_FILTER error code, 279
 ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 272
 ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 272
 ER_FAILED_TO_ALLOCATE_SSL_BIO error code, 508
 ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER error code, 273
 ER_FAILED_TO_BINLOG_DROP_EVENT error code, 278
 ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES error code, 279
 ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 195
 ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OCCUPANCY error code, 195
 ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY error code, 277
 ER_FAILED_TO_CREATE_CLONE_HANDLER error code, 280
 ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THRESHOLD error code, 195
 ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE error code, 275
 ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS error code, 207
 ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE error code, 194
 ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP error code, 272
 ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY error code, 129
 ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST error code, 129
 ER_FAILED_TO_FIND_COLLATION_NAME error code, 267
 ER_FAILED_TO_FIND_DL_ENTRY error code, 264
 ER_FAILED_TO_FIND_LOCALE_NAME error code, 267
 ER_FAILED_TO_FIND_MYSQLD_STATUS error code, 283

ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE error code, 264	ER_FILE_NOT_FOUND error code, 4
ER_FAILED_TO_GET_ABSOLUTE_PATH error code, 268	ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS error code, 541
ER_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 508	ER_FILE_TYPE_UNKNOWN error code, 190
ER_FAILED_TO_INIT_SYS_VAR error code, 508	ER_FILE_USED error code, 5
ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE error code, 195	ER_FILSORT_ABORT error code, 5
ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION error code, 195	ER_FIREWALL_ACCESS_DENIED error code, 298
ER_FAILED_TO_LOCK_MEM error code, 168	ER_FIREWALL_DEPRECATED_USER_PROFILE error code, 570
ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES error code, 203	ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES error code, 298
ER_FAILED_TO_OPEN_SHARED_LIBRARY error code, 264	ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES error code, 298
ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA error code, 272	ER_FIREWALL_PFS_TABLE_REGISTER_FAILED error code, 565
ER_FAILED_TO_READ_FILE error code, 264	ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED error code, 298
ER_FAILED_TO_REMOVE_TEMP_TABLE error code, 243	ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT error code, 298
ER_FAILED_TO_REPAIR_TABLE error code, 243	ER_FIREWALL_RELOADING_CACHE error code, 299
ER_FAILED_TO_SET_PERSISTED_OPTIONS error code, 284	ER_FIREWALL_RESET_FOR_USER error code, 299
ER_FAILED_TO_START_REPLICA_THREAD error code, 278	ER_FIREWALL_SERVICES_NOT_ACQUIRED error code, 564
ER_FAILED_TO_START_SLAVE_THREAD error code, 278	ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE error code, 298
ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE error code, 275	ER_FIREWALL_STATUS_FLUSHED error code, 299
ER_FAILED_TO_UPDATE_RESOURCE_GROUP error code, 272	ER_FIREWALL_SUSPICIOUS_STMT error code, 298
ER_FAILED_TO_WRITE_TO_FILE error code, 265	ER_FIREWALL_UDF_REGISTER_FAILED error code, 565
ER_FAIL_CHROOT error code, 168	ER_FIXING_CLIENT_CHARSET error code, 168
ER_FAIL_SETGID error code, 167	ER_FK_CANNOT_CHANGE_ENGINE error code, 110
ER_FAIL_SETREGID error code, 167	ER_FK_CANNOT_DROP_PARENT error code, 105
ER_FAIL_SETREUID error code, 167	ER_FK_CANNOT_OPEN_PARENT error code, 59
ER_FAIL_SETTUID error code, 167	ER_FK_CANNOT_USE_VIRTUAL_COLUMN error code, 105
ER_FEATURE_DISABLED error code, 23	ER_FK_COLUMN_CANNOT_CHANGE error code, 59
ER_FEATURE_DISABLED_SEE_DOC error code, 80	ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 59
ER_FEATURE_NOT_AVAILABLE error code, 75	ER_FK_COLUMN_CANNOT_DROP error code, 59
ER_FEATURE_UNSUPPORTED error code, 98	ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 59
ER_FIELD_IN_GROUPING_NOT_GROUP_BY error code, 92	ER_FK_COLUMN_NOT_NULL error code, 59
ER_FIELD_IN_ORDER_NOT_SELECT error code, 70	ER_FK_DEPTH_EXCEEDED error code, 65
ER_FIELD_NOT_FOUND_PART_ERROR error code, 34	ER_FK_DUP_NAME error code, 59
ER_FIELD_SPECIFIED_TWICE error code, 10	ER_FK_FAIL_ADD_SYSTEM error code, 59
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 44	ER_FK_INCOMPATIBLE_COLUMNS error code, 111
ER_FILEGROUP_OPTION_ONLY_ONCE error code, 37	ER_FK_INCORRECT_OPTION error code, 59
ER_FILESORT_TERMINATED error code, 267	ER_FK_NO_COLUMN_PARENT error code, 106
ER_FILE_CORRUPT error code, 64	ER_FK_NO_INDEX_CHILD error code, 58
ER_FILE_EXISTS_DURING_UPGRADE error code, 250	ER_FK_NO_INDEX_PARENT error code, 59
ER_FILE_EXISTS_ERROR error code, 8	ER_FORBID_SCHEMA_CHANGE error code, 32
ER_FILE_HAS_OLD_FORMAT error code, 266	ER_FORCE_CLOSE_THREAD error code, 265
	ER_FORCING_CLOSE error code, 8
	ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 31
	ER_FOREIGN_DATA_STRING_INVALID error code, 31

ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE error code, 31	ER_GENERATED_COLUMN_NON_PRIOR error code, 75
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 38	ER_GENERATED_COLUMN_REF_AUTO_INC error code, 75
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 53	ER_GENERATED_COLUMN_ROW_VALUE error code, 109
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 53	ER_GENERATED_COLUMN_VARIABLES error code, 109
ER_FOREIGN_KEY_ON_PARTITIONED error code, 36	ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT error code, 122
ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT error code, 133	ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE error code, 105
ER_FOREIGN_SERVER_DOESNT_EXIST error code, 34	ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE error code, 105
ER_FOREIGN_SERVER_EXISTS error code, 34	ER_GET_ERRMSG error code, 23
ER_FOUND_MISSING_GTIDS error code, 370	ER_GET_ERRNO error code, 5
ER_FOUND_ROWS_WHILE_REPAIRING error code, 247	ER_GET_ERRNO_FROM_STORAGE_ENGINE error code, 266
ER_FPARSER_BAD_HEADER error code, 26	ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 65
ER_FPARSER_EOF_IN_COMMENT error code, 26	ER_GET_TEMPORARY_ERRMSG error code, 23
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 26	ER_GIPK_COLUMN_ALTER_NOT_ALLOWED error code, 148
ER_FPARSER_ERROR_IN_PARAMETER error code, 26	ER_GIPK_COLUMN_EXISTS error code, 148
ER_FPARSER_TOO_BIG_FILE error code, 26	ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS error code, 148
ER_FSEEK_FAIL error code, 28	ER_GIS_DATA_WRONG_ENDIANESS error code, 69
ER_FT_BOOL_SYNTAX_INVALID error code, 163	ER_GIS_DIFFERENT_SRIDS error code, 68
ER_FT_MATCHING_KEY_NOT_FOUND error code, 15	ER_GIS_DIFFERENT_SRIDS_AGGREGATION error code, 139
ER_FULLTEXT_FUNCTIONAL_INDEX error code, 108	ER_GIS_INVALID_DATA error code, 68
ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 53	ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 77
ER_FULLTEXT_WITH_ROLLUP error code, 144	ER_GIS_UNKNOWN_ERROR error code, 68
ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG error code, 124	ER_GIS_UNKNOWN_EXCEPTION error code, 68
ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED error code, 108	ER_GIS_UNSUPPORTED_ARGUMENT error code, 68
ER_FUNCTIONAL_INDEX_ON_FIELD error code, 109	ER_GLOBAL_CONN_LIMIT error code, 580
ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION error code, 108	ER_GLOBAL_VARIABLE error code, 19
ER_FUNCTIONAL_INDEX_ON_LOB error code, 108	ER_GLOBSTAT_CHANGE_DURING_QUERY error code, 125
ER_FUNCTIONAL_INDEX_PRIMARY_KEY error code, 108	ER_GNO_EXHAUSTED error code, 54
ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT error code, 108	ER_GRANT_WRONG_HOST_OR_USER error code, 13
ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED error code, 113	ER_GROUPING_ON_TIMESTAMP_IN_DST error code, 125
ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET error code, 134	ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 74
ER_FUNCTION_NOT_DEFINED error code, 11	ER_GROUP_REPLICATION_COMMAND_FAILURE error code, 98
ER_FUNC_INEXISTENT_NAME_COLLISION error code, 42	ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN error code, 74
ER_FUTURE_DATE error code, 166	ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION error code, 74
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED error code, 74	ER_GROUP_REPLICATION_CONFIGURATION error code, 145
ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 109	ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND error code, 149

ER_GROUP_REPLICATION_MAX_GROUP_SIZE error code, 81	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 327
ER_GROUP_REPLICATION_PASSWORD_LENGTH error code, 132	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN error code, 351
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED error code, 194	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED error code, 327
ER_GROUP_REPLICATION_RUNNING error code, 74	ER_GRP_RPL_APPLIER_THD_KILLED error code, 327
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD error code, 74	ER_GRP_RPL_APPLIER_THD_KILLED_BY_SQL_KILL error code, 610
ER_GROUP_REPLICATION_USER_EMPTY_MSG error code, 131	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 336
ER_GROUP_REPLICATION_USER_MANDATORY_MSG error code, 132	ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 336
ER_GRP_DELAYED_VCLE_LOGGING error code, 531	ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 336
ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP error code, 130	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT error code, 511
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED error code, 353	ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 338
ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTID_SID_MAP error code, 328	ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 338
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID error code, 339	ER_GRP_RPL_AUTO_INC_RESET error code, 338
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID error code, 340	ER_GRP_RPL_AUTO_INC_SET error code, 338
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID error code, 339	ER_GRP_RPL_BINLOG_CHECKSUM_SET error code, 344
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID error code, 339	ER_GRP_RPL_BINLOG_DISABLED error code, 353
ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED error code, 328	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 335
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID error code, 329	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED error code, 346
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP error code, 571	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 360
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY error code, 341	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 327
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED error code, 352	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE error code, 344
ER_GRP_RPL_APPENDING_DATA_TO_INTERNAL_CACHE error code, 346	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE error code, 345
ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING error code, 564	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING error code, 344
ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR error code, 327	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING error code, 344
ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE error code, 357	ER_GRP_RPL_CANT_GENERATE_GTID error code, 329
ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED error code, 357	ER_GRP_RPL_CANT_KILL_THREAD error code, 537
ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE error code, 357	ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 330
ER_GRP_RPL_APPLIER_INITIALIZED error code, 353	ER_GRP_RPL_CANT_READ_GTID error code, 330
ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_AVAILABLE error code, 354	ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 330
ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING error code, 353	ER_GRP_RPL_CERTIFICATE_SIZE_ERROR error code, 326
	ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 329
	ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 347

ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 331	ER_GRP_RPL_DONOR_SERVER_CONN error code, 342
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED error code, 609	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 328
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED error code, 609	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO error code, 572
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED error code, 610	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 333
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 332	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET error code, 328
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING error code, 511	ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 328
ER_GRP_RPL_CHECK_STATUS_TABLE error code, 342	ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 326
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR error code, 537	ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION error code, 510
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR error code, 537	ER_GRP_RPL_ERROR_MSG error code, 305
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 353	ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL error code, 524
ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 512	ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING error code, 511
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 511	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG error code, 327
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 512	ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER error code, 579
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 511	ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER error code, 579
ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 511	ER_GRP_RPL_ERROR_STOPPING_CHANNELS error code, 327
ER_GRP_RPL_CONFIG_RECOVERY error code, 342	ER_GRP_RPL_ERROR_VERIFYING_SIDNO error code, 329
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 331	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_RESOLVED error code, 346
ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_STABLE error code, 354	ER_GRP_RPL_ERROR_ESTABLISHING_CONN_GRP_REC_DONOR error code, 342
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 340	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_D error code, 342
ER_GRP_RPL_CONTACT_WITH_SRV_FAILED error code, 340	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 341
ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 341	ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 326
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 326	ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 334
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 342	ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 359
ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 341	ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING error code, 357
ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM error code, 334	ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP error code, 343
ER_GRP_RPL_DEBUG_OPTIONS error code, 359	ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS error code, 343
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFFERENT error code, 529	ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION error code, 349
ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 333	ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GROUP error code, 350
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 331	ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE error code, 346
ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 342	

ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 345	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER error code, 352
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE error code, 351	ER_GRP_RPL_FAILED_TO_UPDATE_OVER_CHANNEL_STATUS_PROPAGATION error code, 141
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE error code, 349	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 575
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 345	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION error code, 574
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 345	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA error code, 574
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 352	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN error code, 575
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW error code, 571	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT error code, 575
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 357	ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 575
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 353	ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 575
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 349	ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER error code, 575
ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 351	ER_GRP_RPL_FATAL_REC_PROCESS error code, 347
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION error code, 521	ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 338
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 589	ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 339
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_ERROR error code, 343	ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 340
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 352	ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 339
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE error code, 571	ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 338
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER error code, 351	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 339
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER error code, 351	ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 337
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOMES_ERROR error code, 346	ER_GRP_RPL_FETCH_TRANS_SIDNO_ERROR error code, 329
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER error code, 351	ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 340
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_GRP error code, 345	ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 528
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE error code, 351	ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 338
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE error code, 349	ER_GRP_RPL_FLOW_CONTROL_STATS error code, 360
ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 352	ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIB error code, 356
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY error code, 349	ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MIB error code, 355
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER error code, 348	ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MIB error code, 356
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 352	ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 348
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER error code, 352	ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED error code, 356
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER error code, 352	ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 524

ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 360	ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING error code, 356
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 360	ER_GRP_RPL_INVALID_TRANS_WRITE_SET_EXTRACTION error code, 354
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 360	ER_GRP_RPL_IS_STARTING error code, 551
ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 361	ER_GRP_RPL_IS_STOPPED error code, 350
ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 359	ER_GRP_RPL_IS_STOPPING error code, 350
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 359	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING error code, 511
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 328	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING error code, 511
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID error code, 570	ER_GRP_RPL_KILLED_FAILED_ID error code, 341
ER_GRP_RPL_GRP_CHANGE_INFO_EXTRACT_ERROR error code, 334	ER_GRP_RPL_KILLED_SESSION_ID error code, 340
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED error code, 359	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR error code, 335
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT error code, 356	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET error code, 354
ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 359	ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET error code, 354
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 355	ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_MASTER error code, 499
ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_UUID error code, 563	ER_GRP_RPL_MASTER_INFO_REPO_MUST_BE_TABLE error code, 354
ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 355	ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED error code, 341
ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 355	ER_GRP_RPL_MEMBER_ACTIONS_RESET error code, 569
ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE error code, 570	ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION error code, 568
ER_GRP_RPL_GTID_ALREADY_USED error code, 326	ER_GRP_RPL_MEMBER_ACTION_DISABLED error code, 569
ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 334	ER_GRP_RPL_MEMBER_ACTION_ENABLED error code, 569
ER_GRP_RPL_GTID_MODE_OFF error code, 353	ER_GRP_RPL_MEMBER_ACTION_ENABLED_WITH_SERVER_UUID error code, 569
ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR error code, 537	ER_GRP_RPL_MEMBER_ACTION_FAILURE error code, 568
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR error code, 334	ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE error code, 568
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY error code, 523	ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA error code, 568
ER_GRP_RPL_HAS_STARTED error code, 602	ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER error code, 569
ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_EXECUTION error code, 354	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN error code, 569
ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE error code, 331	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE error code, 568
ER_GRP_RPL_INTERNAL_QUERY error code, 341	ER_GRP_RPL_MEMBER_ACTION_TRIGGERED error code, 568
ER_GRP_RPL_INVALID_BINLOG_FORMAT error code, 344	ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT error code, 569
ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL error code, 528	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 568
ER_GRP_RPL_INVALID_DEBUG_OPTIONS error code, 359	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_JOIN error code, 569
ER_GRP_RPL_INVALID_GTID_SET error code, 329	ER_GRP_RPL_MEMBER_ADDED error code, 332
	ER_GRP_RPL_MEMBER_ALREADY_EXISTS error code, 334
	ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP error code, 336

ER_GRP_RPL_MEMBER_CHANGE error code, 333	ER_GRP_RPL_NO_STAGE_SERVICE error code, 512
ER_GRP_RPL_MEMBER_CONF_INFO error code, 350	ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM error code, 334
ER_GRP_RPL_MEMBER_CONTACT_RESTORED error code, 332	ER_GRP_RPL_NO_VALID_DONOR error code, 342
ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR error code, 333	ER_GRP_RPL_NULL_PACKET error code, 330
ER_GRP_RPL_MEMBER_EXPELLED error code, 333	ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE error code, 347
ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST error code, 608	ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION error code, 343
ER_GRP_RPL_MEMBER_LEFT_GRP error code, 333	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP error code, 580
ER_GRP_RPL_MEMBER_NOT_FOUND error code, 341	ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP error code, 599
ER_GRP_RPL_MEMBER_REMOVED error code, 332	ER_GRP_RPL_PIPELINE_CREATE_FAILED error code, 361
ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE WITH_GRP error code, 349	ER_GRP_RPL_PIPELINE_FLUSH_FAIL error code, 361
ER_GRP_RPL_MEMBER_STATS_INFO error code, 360	ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 361
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR error code, 336	ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 361
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP error code, 335	ER_GRP_RPL_PLUGIN_ABORT error code, 507
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP error code, 335	ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SESSION error code, 349
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE error code, 335	ER_GRP_RPL_PREV_REC_SESSION_RUNNING error code, 347
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE error code, 534	ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 512
ER_GRP_RPL_MEM_ONLINE error code, 331	ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 512
ER_GRP_RPL_MEM_REACHABLE error code, 332	ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 338
ER_GRP_RPL_MEM_UNREACHABLE error code, 332	ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 332
ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR error code, 540	ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 330
ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE error code, 125	ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 330
ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR error code, 510	ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 336
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER error code, 331	ER_GRP_RPL_PURGE_REC error code, 343
ER_GRP_RPL_MODULE_TERMINATE_ERROR error code, 355	ER_GRP_RPL_QUERY_FAIL error code, 341
ER_GRP_RPL_MSG_DISCARDED error code, 331	ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_SESSION error code, 348
ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANSACTION error code, 346	ER_GRP_RPL_READ_UNABLE_FOR_SUPER_READ_ONLY_SESSION error code, 348
ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED error code, 345	ER_GRP_RPL_RECOVERED error code, 330
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR error code, 574	ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING error code, 138
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR error code, 574	ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 552
ER_GRP_RPL_NEEDS_INNODB_TABLE error code, 338	ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS error code, 552
ER_GRP_RPL_NEW_PRIMARY_ELECTED error code, 333	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 552
ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED error code, 339	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_END error code, 552
ER_GRP_RPL_NO_POSSIBLE_RECOVERY error code, 537	

ER_GRP_RPL_RECOVERY_EVAL_ERROR error code, 537	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER error code, 337
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION error code, 351	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 521
ER_GRP_RPL_RECOVERY_STRAT_CHOICE error code, 537	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED error code, 522
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED error code, 537	ER_GRP_RPL_SERVER_ALREADY_LEFT error code, 350
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD error code, 537	ER_GRP_RPL_SERVER_CONN_ERROR error code, 328
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK error code, 538	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING error code, 350
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK error code, 538	ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERROR error code, 539
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCY error code, 522	ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERROR error code, 539
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_SYNC error code, 521	ER_GRP_RPL_SERVER_FAILURE error code, 513
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC error code, 522	ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY error code, 348
ER_GRP_RPL_REINIT_OF_COMMIT_CACHE_FOR_WRITE error code, 347	ER_GRP_RPL_SESSION_OPEN_FAILED error code, 333
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_READ error code, 345	ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER error code, 359
ER_GRP_RPL_REINIT_OF_INTERNAL_CACHE_FOR_WRITE error code, 346	ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER error code, 579
ER_GRP_RPL_RELAY_LOG_INFO_REPO_MUST_BE_TABLE error code, 354	ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER error code, 579
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCY error code, 522	ER_GRP_RPL_SET_SYNC_BEFORE_EXECUTION error code, 330
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT error code, 523	ER_GRP_RPL_SLAVE_FETCH_ERROR error code, 327
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_SYNC error code, 521	ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITHOUT error code, 355
ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR error code, 362	ER_GRP_RPL_SKIP_COMPUTATION_TRANS_COMMITTED error code, 330
ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED error code, 362	ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT error code, 362
ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN error code, 337	ER_GRP_RPL_SLAVE_APPLIER_THREAD_UNBLOCKED error code, 362
ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT error code, 361	ER_GRP_RPL_SLAVE_IO_THD_PRIMARY_UNKNOWN error code, 337
ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED error code, 361	ER_GRP_RPL_SLAVE_IO_THREAD_ERROR_OUT error code, 361
ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER error code, 355	ER_GRP_RPL_SLAVE_IO_THREAD_UNBLOCKED error code, 361
ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER error code, 337	ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_ALLOWED error code, 355
ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN error code, 337	ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER error code, 337
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE error code, 538	ER_GRP_RPL_SLAVE_SQL_THD_PRIMARY_UNKNOWN error code, 337
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 576	ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE error code, 538
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER error code, 350	ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 576
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 336	

ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 357	ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 335
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY_GRP error code, 358	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 335
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_ON_GRP error code, 357	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT error code, 345
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 358	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET error code, 344
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER error code, 358	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP error code, 336
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION error code, 358	ER_GRP_RPL_TRANS_ALREADY_EXISTS_ON_TCM_ON_AFTER_C error code, 521
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER error code, 358	ER_GRP_RPL_TRANS_DOES_NOT_EXIST_ON_TCM_ON_HANDLE error code, 522
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN error code, 358	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 523
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 358	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 522
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 357	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 523
ER_GRP_RPL_SRV_BLOCKED error code, 332	ER_GRP_RPL_UDF_ERROR error code, 125
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 332	ER_GRP_RPL_UDF_REGISTER_ERROR error code, 512
ER_GRP_RPL_SRV_GTID_WAIT_ERROR error code, 531	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 512
ER_GRP_RPL_SRV_NOT_ONLINE error code, 331	ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 512
ER_GRP_RPL_SRV_ONLINE error code, 331	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS error code, 348
ER_GRP_RPL_SRV_PRIMARY_MEM error code, 333	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 361
ER_GRP_RPL_SRV_SECONDARY_MEM error code, 333	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 360
ER_GRP_RPL_SRV_WAIT_TIME_OUT error code, 340	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC error code, 347
ER_GRP_RPL_SSL_DISABLED error code, 353	ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 347
ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 528	ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 353
ER_GRP_RPL_STARTING_GRP_REC error code, 342	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER error code, 343
ER_GRP_RPL_START_FAILED error code, 335	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOV error code, 343
ER_GRP_RPL_START_GRP_RPL_FAILED error code, 340	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 348
ER_GRP_RPL_STOPPING_GRP_REC error code, 342	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS error code, 348
ER_GRP_RPL_STOP_REP_CHANNEL error code, 361	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 348
ER_GRP_RPL_SUPER_READ_OFF error code, 340	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 348
ER_GRP_RPL_SUPER_READ_ON error code, 340	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 348
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 334	ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 348
ER_GRP_RPL_SUPPORTS_ONLY_ONE_FORCE_MEMBERS error code, 356	ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REC error code, 356
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP error code, 349	ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_ME error code, 358
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN error code, 559	ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION error code, 344
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 528	ER_GRP_RPL_UPDATE_GRP_GTID_EXECUTED_ERROR error code, 344
ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_SLAVE error code, 350	ER_GRP_RPL_UPDATE_GRP_GTID_EXECUTED_ERROR error code, 344

ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_ALREADY_EXISTS error code, 571	ER_GTID_MODE_ERROR error code, 55
ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 329	ER_GTID_MODE_OFF error code, 70
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION error code, 329	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 55
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 339	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LI error code, 54
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR error code, 329	ER_GTID_NEXT_TYPE_UNDEFINED_GROUP error code, 60
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VERSION_ERROR error code, 327	ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 60
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP error code, 571	ER_GTID_PURGED_WAS_CHANGED error code, 60
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 140	ER_GTID_PURGED_WAS_UPDATED error code, 265
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 570	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 110
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER error code, 570	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND error code, 64
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 571	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND error code, 64
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME error code, 570	ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE error code, 55
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 350	ER_GTID_UNSAFE_CREATE_SELECT error code, 55
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 522	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 55
ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 348	ER_HANDLERTON_OOM error code, 179
ER_GRP_RPL_WHILE_STOPPING_REP_CHANNEL error code, 347	ER_HANDSHAKE_ERROR error code, 5
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED error code, 344	ER_HEALTH_ERROR error code, 564
ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED error code, 346	ER_HEALTH_INFO error code, 563
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED error code, 346	ER_HEALTH_WARNING error code, 563
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 113	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1 error code, 564
ER_GRP_TRX_CONSISTENCY_BEFORE error code, 113	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2 error code, 564
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 113	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3 error code, 564
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 112	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1 error code, 579
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION error code, 544	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2 error code, 579
ER_GR_HOLD_KILLED error code, 111	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3 error code, 579
ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 111	ER_HOSTNAME error code, 33
ER_GR_HOLD_WAIT_TIMEOUT error code, 111	ER_HOSTNAME_DOESNT_RESOLVE_TO error code, 160
ER_GTID_ALREADY_ADDED_BY_USER error code, 194	ER_HOSTNAME_RESEMBLES_IPV4 error code, 160
ER_GTID_EXECUTED_WAS_CHANGED error code, 60	ER_HOSTNAME_TOO_LONG error code, 131
ER_GTID_EXECUTED_WAS_UPDATED error code, 266	ER_HOSTNAME_TRUNCATED error code, 554
	ER_HOST_IS_BLOCKED error code, 12
	ER_HOST_NOT_PRIVILEGED error code, 12
	ER_HYPERGRAPH_NOT_SUPPORTED_YET error code, 135
	ER_IB_BUFFER_POOL_FULL error code, 596
	ER_IB_BUFFER_POOL_OVERUSE error code, 596
	ER_IB_BULK_FLUSHER_INFO error code, 595
	ER_IB_BULK_LOAD_MERGE_FAIL error code, 599
	ER_IB_BULK_LOAD_SUBTREE_INFO error code, 595
	ER_IB_BULK_LOAD_THREAD_FAIL error code, 598

ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES error code, 554	ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 555
ER_IB_CLONE_GTID_PERSIST error code, 386	ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 556
ER_IB_CLONE_INTERNAL error code, 385	ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR error code, 556
ER_IB_CLONE_NON_INNODB_TABLE error code, 536	ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 556
ER_IB_CLONE_OPERATION error code, 536	ER_IB_ERR_ZLIB_BUF_ERROR error code, 557
ER_IB_CLONE_PUNCH_HOLE error code, 386	ER_IB_ERR_ZLIB_DATA_ERROR error code, 557
ER_IB_CLONE_RESTART error code, 536	ER_IB_ERR_ZLIB_MEM_ERROR error code, 557
ER_IB_CLONE_SQL error code, 386	ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 557
ER_IB_CLONE_START_STOP error code, 536	ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 557
ER_IB_CLONE_STATUS_FILE error code, 386	ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 555
ER_IB_CLONE_TIMEOUT error code, 385	ER_IB_HIDDEN_NAME_CONFLICT error code, 600
ER_IB_CLONE_USER_DATA error code, 536	ER_IB_INDEX_BUILDER_DONE error code, 601
ER_IB_CLONE_VALIDATE error code, 386	ER_IB_INDEX_BUILDER_INIT error code, 601
ER_IB_DBLWR_BYTES_INFO error code, 583	ER_IB_INDEX_LOADER_DONE error code, 601
ER_IB_DBLWR_DECOMPRESS_FAILED error code, 560	ER_IB_INDEX_LOG_VERSION_MISMATCH error code, 601
ER_IB_DBLWR_DECRYPT_FAILED error code, 560	ER_IB_INDEX_PART_TOO_LONG error code, 608
ER_IB_DBLWR_KEY_MISSING error code, 561	ER_IB_INNODB_TBSP_OUT_OF_SPACE error code, 564
ER_IB_DDL_CONVERT_HEAP_NOT_FOUND error code, 607	ER_IB_LOAD_BULK_CONCURRENCY_REDUCED error code, 599
ER_IB_DICT_INVALID_COLUMN_POSITION error code, 600	ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 542
ER_IB_DICT_LOG_TABLE_INFO error code, 600	ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 554
ER_IB_DUPLICATE_KEY error code, 596	ER_IB_LONG_AHI_DISABLE_WAIT error code, 389
ER_IB_ERR_DDL_LOG_INSERT_FAILURE error code, 554	ER_IB_MSG_0 error code, 371
ER_IB_ERR_FOUND_N_DUPLICATE_KEYS error code, 558	ER_IB_MSG_1 error code, 371
ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER error code, 558	ER_IB_MSG_10 error code, 372
ER_IB_ERR_INDEX_DUPLICATE_KEY error code, 557	ER_IB_MSG_100 error code, 381
ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER error code, 557	ER_IB_MSG_1000 error code, 468
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW error code, 556	ER_IB_MSG_1001 error code, 468
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER error code, 556	ER_IB_MSG_1002 error code, 468
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED error code, 573	ER_IB_MSG_1003 error code, 468
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE error code, 551	ER_IB_MSG_1004 error code, 468
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT error code, 551	ER_IB_MSG_1005 error code, 468
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED error code, 551	ER_IB_MSG_1006 error code, 468
ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN error code, 379	ER_IB_MSG_1007 error code, 468
ER_IB_ERR_PARALLEL_READ_OOM error code, 558	ER_IB_MSG_1008 error code, 468
ER_IB_ERR_RECOVERY_REDO_DISABLED error code, 553	ER_IB_MSG_1009 error code, 468
ER_IB_ERR_SCHED_SETAFFINITY_FAILED error code, 556	ER_IB_MSG_101 error code, 381
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMIOCOLS error code, 556	ER_IB_MSG_1010 error code, 469
	ER_IB_MSG_1011 error code, 469
	ER_IB_MSG_1012 error code, 469
	ER_IB_MSG_1013 error code, 469
	ER_IB_MSG_1014 error code, 469
	ER_IB_MSG_1015 error code, 469
	ER_IB_MSG_1016 error code, 469
	ER_IB_MSG_1017 error code, 469
	ER_IB_MSG_1018 error code, 469
	ER_IB_MSG_1019 error code, 469
	ER_IB_MSG_102 error code, 381

ER_IB_MSG_899 error code, 458	ER_IB_MSG_950 error code, 463
ER_IB_MSG_9 error code, 372	ER_IB_MSG_951 error code, 463
ER_IB_MSG_90 error code, 380	ER_IB_MSG_952 error code, 463
ER_IB_MSG_900 error code, 459	ER_IB_MSG_953 error code, 463
ER_IB_MSG_901 error code, 459	ER_IB_MSG_954 error code, 463
ER_IB_MSG_902 error code, 459	ER_IB_MSG_955 error code, 464
ER_IB_MSG_903 error code, 459	ER_IB_MSG_956 error code, 464
ER_IB_MSG_904 error code, 459	ER_IB_MSG_957 error code, 464
ER_IB_MSG_905 error code, 459	ER_IB_MSG_958 error code, 464
ER_IB_MSG_906 error code, 459	ER_IB_MSG_959 error code, 464
ER_IB_MSG_907 error code, 459	ER_IB_MSG_96 error code, 380
ER_IB_MSG_908 error code, 459	ER_IB_MSG_960 error code, 464
ER_IB_MSG_909 error code, 459	ER_IB_MSG_961 error code, 464
ER_IB_MSG_91 error code, 380	ER_IB_MSG_962 error code, 464
ER_IB_MSG_910 error code, 459	ER_IB_MSG_963 error code, 464
ER_IB_MSG_911 error code, 460	ER_IB_MSG_964 error code, 464
ER_IB_MSG_912 error code, 460	ER_IB_MSG_965 error code, 464
ER_IB_MSG_913 error code, 460	ER_IB_MSG_966 error code, 465
ER_IB_MSG_914 error code, 460	ER_IB_MSG_967 error code, 465
ER_IB_MSG_915 error code, 460	ER_IB_MSG_968 error code, 465
ER_IB_MSG_916 error code, 460	ER_IB_MSG_969 error code, 465
ER_IB_MSG_917 error code, 460	ER_IB_MSG_97 error code, 380
ER_IB_MSG_918 error code, 460	ER_IB_MSG_970 error code, 465
ER_IB_MSG_919 error code, 460	ER_IB_MSG_971 error code, 465
ER_IB_MSG_92 error code, 380	ER_IB_MSG_972 error code, 465
ER_IB_MSG_920 error code, 460	ER_IB_MSG_973 error code, 465
ER_IB_MSG_921 error code, 460	ER_IB_MSG_974 error code, 465
ER_IB_MSG_922 error code, 461	ER_IB_MSG_975 error code, 465
ER_IB_MSG_923 error code, 461	ER_IB_MSG_976 error code, 465
ER_IB_MSG_924 error code, 461	ER_IB_MSG_977 error code, 466
ER_IB_MSG_925 error code, 461	ER_IB_MSG_978 error code, 466
ER_IB_MSG_926 error code, 461	ER_IB_MSG_979 error code, 466
ER_IB_MSG_927 error code, 461	ER_IB_MSG_98 error code, 381
ER_IB_MSG_928 error code, 461	ER_IB_MSG_980 error code, 466
ER_IB_MSG_929 error code, 461	ER_IB_MSG_981 error code, 466
ER_IB_MSG_93 error code, 380	ER_IB_MSG_982 error code, 466
ER_IB_MSG_930 error code, 461	ER_IB_MSG_983 error code, 466
ER_IB_MSG_931 error code, 461	ER_IB_MSG_984 error code, 466
ER_IB_MSG_932 error code, 461	ER_IB_MSG_985 error code, 466
ER_IB_MSG_933 error code, 462	ER_IB_MSG_986 error code, 466
ER_IB_MSG_934 error code, 462	ER_IB_MSG_987 error code, 466
ER_IB_MSG_935 error code, 462	ER_IB_MSG_988 error code, 467
ER_IB_MSG_936 error code, 462	ER_IB_MSG_989 error code, 467
ER_IB_MSG_937 error code, 462	ER_IB_MSG_99 error code, 381
ER_IB_MSG_938 error code, 462	ER_IB_MSG_990 error code, 467
ER_IB_MSG_939 error code, 462	ER_IB_MSG_991 error code, 467
ER_IB_MSG_94 error code, 380	ER_IB_MSG_992 error code, 467
ER_IB_MSG_940 error code, 462	ER_IB_MSG_993 error code, 467
ER_IB_MSG_941 error code, 462	ER_IB_MSG_994 error code, 467
ER_IB_MSG_942 error code, 462	ER_IB_MSG_995 error code, 467
ER_IB_MSG_943 error code, 462	ER_IB_MSG_996 error code, 467
ER_IB_MSG_944 error code, 463	ER_IB_MSG_997 error code, 467
ER_IB_MSG_945 error code, 463	ER_IB_MSG_998 error code, 467
ER_IB_MSG_946 error code, 463	ER_IB_MSG_999 error code, 468
ER_IB_MSG_947 error code, 463	ER_IB_MSG_BAD_DBLWR_FILE_NAME error code, 546
ER_IB_MSG_948 error code, 463	ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED error code, 536
ER_IB_MSG_949 error code, 463	
ER_IB_MSG_95 error code, 380	

ER_IB_MSG_BUF_PENDING_IO error code, 479	ER_IB_MSG_DBLWR_1315 error code, 548
ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN error code, 495	ER_IB_MSG_DBLWR_1316 error code, 548
ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS error code, 595	ER_IB_MSG_DBLWR_1317 error code, 549
ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE error code, 594	ER_IB_MSG_DBLWR_1318 error code, 549
ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE error code, 595	ER_IB_MSG_DBLWR_1319 error code, 549
ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE error code, 552	ER_IB_MSG_DBLWR_1320 error code, 549
ER_IB_MSG_CANNOT_OPEN_57_UNDO error code, 476	ER_IB_MSG_DBLWR_1321 error code, 549
ER_IB_MSG_CANT_DECRYPT_REDO_LOG error code, 454	ER_IB_MSG_DBLWR_1322 error code, 549
ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA error code, 453	ER_IB_MSG_DBLWR_1323 error code, 549
ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA error code, 593	ER_IB_MSG_DBLWR_1324 error code, 549
ER_IB_MSG_CLOCK_GETTIME_FAILED error code, 533	ER_IB_MSG_DBLWR_1325 error code, 549
ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED error code, 533	ER_IB_MSG_DBLWR_1326 error code, 549
ER_IB_MSG_CLONE_DDL_APPLY error code, 576	ER_IB_MSG_DBLWR_1327 error code, 549
ER_IB_MSG_CLONE_DDL_INVALIDATE error code, 576	ER_IB_MSG_DDL_FAIL_NO_BUILDER error code, 608
ER_IB_MSG_CLONE_DDL_NTFN error code, 576	ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK error code, 433
ER_IB_MSG_CREATED_UNDO_SPACE error code, 560	ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT error code, 531
ER_IB_MSG_CREATE_LOG_FILE error code, 550	ER_IB_MSG_DDL_LOG_FAIL_POST_DDL error code, 531
ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED error code, 481	ER_IB_MSG_DEPRECATED_INNO_DB_UNDO_TABLESPACES error code, 517
ER_IB_MSG_DBLWR_1285 error code, 546	ER_IB_MSG_DICT_PARTITION_NOT_FOUND error code, 545
ER_IB_MSG_DBLWR_1286 error code, 546	ER_IB_MSG_DIR_DOES_NOT_EXIST error code, 517
ER_IB_MSG_DBLWR_1287 error code, 546	ER_IB_MSG_DOWNGRADE_PARTITION_FILE error code, 544
ER_IB_MSG_DBLWR_1288 error code, 546	ER_IB_MSG_DROPPED_UNDO_SPACE error code, 560
ER_IB_MSG_DBLWR_1290 error code, 546	ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE error code, 515
ER_IB_MSG_DBLWR_1291 error code, 546	ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR error code, 515
ER_IB_MSG_DBLWR_1292 error code, 547	ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR error code, 516
ER_IB_MSG_DBLWR_1293 error code, 547	ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT error code, 515
ER_IB_MSG_DBLWR_1294 error code, 547	ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE error code, 517
ER_IB_MSG_DBLWR_1295 error code, 547	ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE error code, 515
ER_IB_MSG_DBLWR_1296 error code, 547	ER_IB_MSG_FILE_RESIZE error code, 474
ER_IB_MSG_DBLWR_1297 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME error code, 544
ER_IB_MSG_DBLWR_1298 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH error code, 544
ER_IB_MSG_DBLWR_1300 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_CORRECTED error code, 544
ER_IB_MSG_DBLWR_1301 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_PREV error code, 609
ER_IB_MSG_DBLWR_1304 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATA error code, 609
ER_IB_MSG_DBLWR_1305 error code, 547	ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY error code, 544
ER_IB_MSG_DBLWR_1306 error code, 548	ER_IB_MSG_FOUND_WRONG_UNDO_SPACE error code, 516
ER_IB_MSG_DBLWR_1307 error code, 548	
ER_IB_MSG_DBLWR_1308 error code, 548	
ER_IB_MSG_DBLWR_1309 error code, 548	
ER_IB_MSG_DBLWR_1310 error code, 548	
ER_IB_MSG_DBLWR_1311 error code, 548	
ER_IB_MSG_DBLWR_1312 error code, 548	
ER_IB_MSG_DBLWR_1313 error code, 548	
ER_IB_MSG_DBLWR_1314 error code, 548	

ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATA error code, 409	ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED error code, 586
ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN error code, 550	ER_IB_MSG_LOG_FILES_RESIZE_ON_START_IN_READ error code, 483
ER_IB_MSG_IGNORE_SCAN_PATH error code, 407	ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED error code, 587
ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR error code, 409	ER_IB_MSG_LOG_FILES_REWRITING error code, 483
ER_IB_MSG_INCORRECT_SIZE error code, 560	ER_IB_MSG_LOG_FILES_UPGRADE error code, 587
ER_IB_MSG_INJECT_CRASH error code, 559	ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS error code, 588
ER_IB_MSG_INJECT_FAILURE error code, 559	ER_IB_MSG_LOG_FILE_FOREIGN_UUID error code, 586
ER_IB_MSG_INNODB_END_INITIALIZE error code, 550	ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW error code, 588
ER_IB_MSG_INNODB_START_INITIALIZE error code, 550	ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD error code, 588
ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 425	ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN error code, 439
ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 552	ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM error code, 496
ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 552	ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED error code, 584
ER_IB_MSG_INVALID_PAGE_TYPE error code, 595	ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES error code, 586
ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS error code, 517	ER_IB_MSG_LOG_FILE_INVALID_START_LSN error code, 586
ER_IB_MSG_LOG_CHECKPOINT_FOUND error code, 586	ER_IB_MSG_LOG_FILE_IS_EMPTY error code, 583
ER_IB_MSG_LOG_CORRUPT error code, 438	ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED error code, 589
ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ error code, 494	ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE error code, 587
ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED error code, 587	ER_IB_MSG_LOG_FILE_MISSING_FOR_ID error code, 586
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE error code, 442	ER_IB_MSG_LOG_FILE_OPEN_FAILED error code, 475
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ error code, 584	ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED error code, 473
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB error code, 442	ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED error code, 474
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ error code, 442	ER_IB_MSG_LOG_FILE_REMOVE_FAILED error code, 587
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN error code, 587	ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED error code, 587
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY error code, 474	ER_IB_MSG_LOG_FILE_RESIZE_FAILED error code, 474
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES error code, 482	ER_IB_MSG_LOG_FILE_SIZE_INVALID error code, 482
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED error code, 494	ER_IB_MSG_LOG_FILE_TOO_BIG error code, 583
ER_IB_MSG_LOG_FILES_FOUND_MISSING error code, 588	ER_IB_MSG_LOG_FILE_TOO_SMALL error code, 583
ER_IB_MSG_LOG_FILES_INITIALIZED error code, 475	ER_IB_MSG_LOG_FILE_TRUNCATE error code, 588
ER_IB_MSG_LOG_FILES_INVALID_SET error code, 482	ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED error code, 589
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED error code, 587	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED error code, 589
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED error code, 587	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED error code, 589
ER_IB_MSG_LOG_FILES_RESIZE_ON_START error code, 491	

ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED error code, 588	ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER error code, 493
ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9 error code, 496	ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER error code, 593
ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30 error code, 439	ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE error code, 584
ER_IB_MSG_LOG_FORMAT_NOT_SUPPORTED error code, 443	ER_IB_MSG_LOG_WRITER_WRITE_FAILED error code, 584
ER_IB_MSG_LOG_FORMAT_OLD error code, 442	ER_IB_MSG_MADVISE_FAILED error code, 515
ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED error code, 438	ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 515
ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN error code, 438	ER_IB_MSG_MASTER_KEY_ROTATED error code, 560
ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED error code, 584	ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 515
ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR error code, 584	ER_IB_MSG_NOT_END_WITH_IBU error code, 516
ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INIT error code, 584	ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 509
ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN error code, 497	ER_IB_MSG_NUM_POOLS error code, 515
ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED error code, 589	ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 550
ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED error code, 585	ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION error code, 593
ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE error code, 589	ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG error code, 574
ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED error code, 585	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error code, 574
ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED error code, 588	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 531
ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED error code, 588	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 531
ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0 error code, 588	ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEANUP error code, 443
ER_IB_MSG_LOG_UPGRADE_CLONED_DB error code, 585	ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND error code, 439
ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED error code, 585	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE error code, 584
ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED error code, 586	ER_IB_MSG_RECOVERY_CORRUPT error code, 482
ER_IB_MSG_LOG_UPGRADE_FORCED_RECV error code, 585	ER_IB_MSG_RECOVERY_IN_READ_ONLY error code, 443
ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE error code, 585	ER_IB_MSG_RECOVERY_IS_NEEDED error code, 443
ER_IB_MSG_LOG_UPGRADE_NON_PERSISTED_DD_METADATA error code, 586	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IF_NO_SPACE error code, 573
ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES error code, 585	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED error code, 573
ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER error code, 493	ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE error code, 441
ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN error code, 584	ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY error code, 573
ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN error code, 585	ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY error code, 573
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error code, 493	ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 509
	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 555
	ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 516

ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 516	ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 544
ER_IB_MSG_SKIP_HIDDEN_DIR error code, 542	ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 544
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 565	ER_IB_MSG_USING_UNDO_SPACE error code, 515
ER_IB_MSG_THREAD_CONCURRENCY_CHANGED error code, 497	ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 509
ER_IB_MSG_TOO_LONG_PATH error code, 532	ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 517
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETE error code, 488	ER_IB_PARALLEL_READER_WORKER_INFO error code, 595
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETE error code, 554	ER_IB_PRIMARY_KEY_IS_INSTANT error code, 599
ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME error code, 580	ER_IB_RDBLWR_BYTES_INFO error code, 583
ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 558	ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 532
ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 558	ER_IB_RELOCK_LATCH_ORDER_VIOLATION error code, 555
ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED error code, 576	ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK error code, 603
ER_IB_MSG_UNDO_INJECT_CRASH error code, 558	ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK error code, 602
ER_IB_MSG_UNDO_INJECT_FAILURE error code, 559	ER_IB_RESURRECT_RECORD_COMPLETE error code, 603
ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 558	ER_IB_RESURRECT_RECORD_PROGRESS error code, 603
ER_IB_MSG_UNDO_MARKED_EMPTY error code, 558	ER_IB_RESURRECT_TRX_INSERT error code, 602
ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 486	ER_IB_RESURRECT_TRX_INSERT_COMPLETE error code, 603
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 487	ER_IB_RESURRECT_TRX_UPDATE error code, 602
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 558	ER_IB_RESURRECT_TRX_UPDATE_COMPLETE error code, 603
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 486	ER_IB_SELECT_COUNT_STAR error code, 601
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CORRUPTION error code, 486	ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 553
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 558	ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY error code, 555
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE error code, 485	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 555
ER_IB_MSG_UNDO_TRUNCATE_START error code, 486	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE error code, 399
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 551	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED error code, 580
ER_IB_MSG_UNDO_TRUNC_BEFORE_UNDO_LOGGING error code, 516	ER_IB_WARN_OPEN_PARTITION_FILE error code, 544
ER_IB_MSG_UNDO_TRUNC_BEFORE_DD_UPDATE error code, 516	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH error code, 576
ER_IB_MSG_UNDO_TRUNC_EMPTY_FILE error code, 516	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 567
ER_IB_MSG_UNDO_TRUNC_BEFORE_RSEG error code, 516	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 553
ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 400	ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY error code, 599
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 405	ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 567
	ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 550
	ER_IB_WRN_REDO_DISABLED error code, 553
	ER_IB_WRN_REDO_ENABLED error code, 553

ER_IDENTIFIED_BY_UNSUPPORTED error code, 142	ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE error code, 205
ER_IDENT_CAUSES_TOO_LONG_PATH error code, 61	ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE error code, 205
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 538	ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD error code, 542
ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS error code, 147	ER_INNODB_GENERATING_TEMP_PASSWORD_FOR_ROOT error code, 204
ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FUNC_IN_INIT error code, 147	ER_INNODB_ILLEGAL_COLUMN_WITHOUT_PASSWORD error code, 204
ER_ILLEGAL_GRANT_FOR_TABLE error code, 13	ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED error code, 281
ER_ILLEGAL_HA error code, 5	ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE error code, 138
ER_ILLEGAL_HA_CREATE_OPTION error code, 34	ER_INNODB_CANNOT_BE_IGNORED error code, 102
ER_ILLEGAL_PRIVILEGE_LEVEL error code, 93	ER_INNODB_CANNOT_CREATE_TABLE error code, 281
ER_ILLEGAL_REFERENCE error code, 20	ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR error code, 262
ER_ILLEGAL_USER_VAR error code, 70	ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD error code, 261
ER_ILLEGAL_VALUE_FOR_TYPE error code, 28	ER_INNODB_CANT_OPEN_TABLE error code, 261
ER_IMPLICIT_COMPARISON_FOR_JSON error code, 133	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK error code, 261
ER_IMPOSSIBLE_STRING_CONVERSION error code, 134	ER_INNODB_CLUSTERED_INDEX_PRIVATE error code, 262
ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 129	ER_INNODB_COMPRESSION_FAILURE error code, 139
ER_IMP_INCOMPATIBLE_DD_VERSION error code, 93	ER_INNODB_DIFF_IN_REF_LEN error code, 281
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 93	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW error code, 261
ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 93	ER_INNODB_ERROR_LOGGER_FATAL_MSG error code, 283
ER_IMP_NO_FILES_MATCHED error code, 92	ER_INNODB_ERROR_LOGGER_MSG error code, 283
ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 92	ER_INNODB_FAILED_TO_FIND_IDX error code, 280
ER_IMP_TABLE_ALREADY_EXISTS error code, 93	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE error code, 281
ER_INCONSISTENT_ERROR error code, 500	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO error code, 280
ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 35	ER_INNODB_FILES_SAME error code, 261
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 35	ER_INNODB_FORCED_RECOVERY error code, 63
ER_INCORRECT_CURRENT_PASSWORD error code, 123	ER_INNODB_FT_AUX_NOT_HEX_ID error code, 63
ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 19	ER_INNODB_FT_LIMIT error code, 56
ER_INCORRECT_TYPE error code, 70	ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 56
ER_INDEX_COLUMN_TOO_LONG error code, 49	ER_INNODB_FT_WRONG_DOCID_INDEX error code, 56
ER_INDEX_CORRUPT error code, 49	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL error code, 281
ER_INDEX_OTHER_THAN_PK error code, 150	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL error code, 281
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL error code, 105	ER_INNODB_INDEX_COLUMN_CNT_DIFF error code, 281
ER_INFORMATION_SCHEMA_VERSION_CHANGE error code, 608	ER_INNODB_ILLEGAL_COLON_IN_POOL error code, 260
ER_INIT_BOOTSTRAP_COMPLETE error code, 205	ER_INNODB_IMPORT_ERROR error code, 58
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE error code, 205	
ER_INIT_CREATING_DD error code, 205	
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE error code, 205	
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE error code, 205	

ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE error code, 138	ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE error code, 118
ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQL error code, 261	ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE error code, 118
ER_INNODB_INDEX_CORRUPT error code, 58	ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND error code, 118
ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED error code, 153	ER_INNODB_REDO_LOG_ARCHIVE_MAX_SIZE error code, 118
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE error code, 153	ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR error code, 118
ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_SIZE error code, 146	ER_INNODB_REDO_LOG_ARCHIVE_SESSION error code, 118
ER_INNODB_INTERNAL_INDEX error code, 281	ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH error code, 117
ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE error code, 138	ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT error code, 117
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY error code, 260	ER_INNODB_TRX_XLATION_TABLE_OOM error code, 261
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LENGTH error code, 518	ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT error code, 551
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR error code, 260	ER_INNODB_UNDO_LOG_FULL error code, 66
ER_INNODB_INVALID_MONITOR_COUNTER_NAME error code, 282	ER_INNODB_UNKNOWN_COLLATION error code, 260
ER_INNODB_INVALID_PAGE_SIZE error code, 260	ER_INNODB_UNREGISTERED_TRX_ACTIVE error code, 261
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX error code, 261	ER_INNODB_USE_MONITOR_GROUP_NAME error code, 282
ER_INNODB_IO_WRITE_ERROR_RETRYING error code, 561	ER_INSECURE_CHANGE_MASTER error code, 53
ER_INNODB_IO_WRITE_FAILED error code, 561	ER_INSECURE_CHANGE_SOURCE error code, 53
ER_INNODB_MANDATORY error code, 163	ER_INSECURE_PLAIN_TEXT error code, 53
ER_INNODB_MAX_ROW_VERSION error code, 146	ER_INSERT_INFO error code, 9
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED error code, 282	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 47
ER_INNODB_MONITOR_IS_ENABLED error code, 282	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 46
ER_INNODB_NO_FT_TEMP_TABLE error code, 56	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 47
ER_INNODB_ONLINE_LOG_TOO_BIG error code, 56	ER_INSTALL_COMPONENT_SET_NULL_VALUE error code, 154
ER_INNODB_OUT_OF_RESOURCES error code, 545	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE error code, 154
ER_INNODB_PARTITION_TABLE_LOWER_CASED error code, 262	ER_INSTALL_PLUGIN_CONFLICT_CLIENT error code, 141
ER_INNODB_PK_NOT_IN_MYSQL error code, 262	ER_INSTALL_PLUGIN_CONFLICT_LOG error code, 572
ER_INNODB_PK_ONLY_IN_MYSQL error code, 262	ER_INTERNAL_ERROR error code, 58
ER_INNODB_READ_ONLY error code, 63	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED error code, 149
ER_INNODB_REDO_ARCHIVING_ENABLED error code, 133	ER_INVALID_ADMIN_ADDRESS error code, 520
ER_INNODB_REDO_DISABLED error code, 133	ER_INVALID_ARGUMENT_FOR_LOGARITHM error code, 66
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE error code, 118	ER_INVALID_ASSIGNMENT_TARGET error code, 141
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID error code, 117	ER_INVALID_AUTHENTICATION_POLICY error code, 576
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH error code, 118	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE error code, 84
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY error code, 118	ER_INVALID_BITWISE_OPERANDS_SIZE error code, 84
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS error code, 118	ER_INVALID_CAST error code, 135
ER_INNODB_REDO_LOG_ARCHIVE_FAILED error code, 118	

ER_INVALID_CAST_POLYGON_RING_DIRECTION error code, 139
 ER_INVALID_CAST_TO_GEOMETRY error code, 139
 ER_INVALID_CAST_TO_JSON error code, 78
 ER_INVALID_CHARACTER_STRING error code, 23
 ER_INVALID_CHARSET_AND_DEFAULT_IS_MB error code, 190
 ER_INVALID_COLLATION_FOR_CHARSET error code, 267
 ER_INVALID_DD_OBJECT error code, 83
 ER_INVALID_DD_OBJECT_ID error code, 83
 ER_INVALID_DD_OBJECT_NAME error code, 83
 ER_INVALID_DEFAULT error code, 7
 ER_INVALID_DEFAULT_UTF8MB4_COLLATION error code, 104
 ER_INVALID_ENCRYPTION_OPTION error code, 81
 ER_INVALID_ENCRYPTION_REQUEST error code, 116
 ER_INVALID_ERROR_LOG_NAME error code, 173
 ER_INVALID_FIELD_SIZE error code, 66
 ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL error code, 99
 ER_INVALID_GEOJSON_MISSING_MEMBER error code, 70
 ER_INVALID_GEOJSON_UNSPECIFIED error code, 71
 ER_INVALID_GEOJSON_WRONG_TYPE error code, 71
 ER_INVALID_GROUP_FUNC_USE error code, 10
 ER_INVALID_INFO_IN_FRM error code, 190
 ER_INVALID_INSTRUMENT error code, 162
 ER_INVALID_JSON_ATTRIBUTE error code, 133
 ER_INVALID_JSON_BINARY_DATA error code, 78
 ER_INVALID_JSON_CHARSET error code, 78
 ER_INVALID_JSON_CHARSET_IN_FUNCTION error code, 78
 ER_INVALID_JSON_DATA error code, 70
 ER_INVALID_JSON_PATH error code, 78
 ER_INVALID_JSON_PATH_ARRAY_CELL error code, 79
 ER_INVALID_JSON_PATH_CHARSET error code, 78
 ER_INVALID_JSON_PATH_WILDCARD error code, 78
 ER_INVALID_JSON_TEXT error code, 78
 ER_INVALID_JSON_TEXT_IN_PARAM error code, 78
 ER_INVALID_JSON_TYPE error code, 119
 ER_INVALID_JSON_VALUE_FOR_CAST error code, 79
 ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX error code, 124
 ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_LOGIN error code, 143
 ER_INVALID_MFA_PLUGIN_SPECIFIED error code, 142
 ER_INVALID_MULTIPLE_CLAUSES error code, 117
 ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP error code, 527
 ER_INVALID_NO_OF_ARGS error code, 92
 ER_INVALID_ON_UPDATE error code, 23
 ER_INVALID_OPTION_CHARACTERS error code, 87
 ER_INVALID_OPTION_END_CHARACTER error code, 87
 ER_INVALID_OPTION_KEY error code, 87
 ER_INVALID_OPTION_KEY_VALUE_PAIR error code, 87
 ER_INVALID_OPTION_START_CHARACTER error code, 87
 ER_INVALID_OPTION_VALUE error code, 87
 ER_INVALID_OR_OLD_TABLE_OR_DB_NAME error code, 212
 ER_INVALID_PARAMETER_USE error code, 134
 ER_INVALID_PLUGIN_FOR_REGISTRATION error code, 142
 ER_INVALID_PROPERTY_KEY error code, 523
 ER_INVALID_REPLICATION_TIMESTAMPS error code, 270
 ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN error code, 70
 ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH error code, 607
 ER_INVALID_SERVER_UPGRADE_NOT_LTS error code, 607
 ER_INVALID_THREAD_ID error code, 98
 ER_INVALID_THREAD_PRIORITY error code, 97
 ER_INVALID_TIME_ZONE_INTERVAL error code, 135
 ER_INVALID_TLS_VERSION error code, 581
 ER_INVALID_TYPE_FOR_JSON error code, 78
 ER_INVALID_USER_ATTRIBUTE_JSON error code, 133
 ER_INVALID_USER_FOR_REGISTRATION error code, 142
 ER_INVALID_USE_OF_FORCE_OPTION error code, 98
 ER_INVALID_USE_OF_NULL error code, 12
 ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY error code, 158
 ER_INVALID_VALUE_OF_BIND_ADDRESSES error code, 510
 ER_INVALID_VCPU_ID error code, 97
 ER_INVALID_VCPU_RANGE error code, 97
 ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER error code, 551
 ER_INVALID_YEAR_COLUMN_LENGTH error code, 58
 ER_IO_ERR_LOG_INDEX_READ error code, 28
 ER_IO_READ_ERROR error code, 58
 ER_IO_WRITE_ERROR error code, 58
 ER_IPSOCK_ERROR error code, 8
 ER_INVALID_SERVER_QUERY_INVALID_CLAUSE error code, 86
 ER_I_S_SKIPPED_TABLESPACE error code, 96
 ER_JSON_BAD_ONE_OR_ALL_ARG error code, 79
 ER_JSON_DOCUMENT_NULL_KEY error code, 79
 ER_JSON_DOCUMENT_TOO_DEEP error code, 79
 ER_JSON_KEY_TOO_BIG error code, 78
 ER_JSON_PARSE_ERROR error code, 176

ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILS error code, 127	ER_KEYRING_AWS_INCORRECT_FILE error code, 325
ER_JSON_USED_AS_KEY error code, 78	ER_KEYRING_AWS_INCORRECT_PROXY error code, 539
ER_JSON_VACUOUS_PATH error code, 78	ER_KEYRING_AWS_INCORRECT_REGION error code, 325
ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX error code, 124	ER_KEYRING_AWS_INIT_FAILURE error code, 324
ER_JSON_VALUE_TOO_BIG error code, 78	ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 323
ER_JT_MAX_NESTED_PATH error code, 99	ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 323
ER_JT_VALUE_OUT_OF_RANGE error code, 99	ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 324
ER_KERBEROS_CREATE_USER error code, 141	ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 82
ER_KEYCACHE_OOM error code, 166	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY error code, 316
ER_KEYRING_ACCESS_DENIED_ERROR error code, 82	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 316
ER_KEYRING_AWS_CMK_ID_NOT_SET error code, 324	ER_KEYRING_COMPONENT_EXCEPTION error code, 566
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE error code, 324	ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 566
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_BACKUP error code, 323	ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 566
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_BACKUP error code, 323	ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED error code, 321
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEY error code, 324	ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED error code, 321
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEY error code, 323	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEY error code, 322
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS error code, 325	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEY error code, 321
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY error code, 326	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEY error code, 321
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY error code, 325	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP error code, 321
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 325	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INVALID_CONF error code, 322
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUETO_KEYRING_ERROR error code, 325	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE error code, 321
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 325	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INVALID_KEYRING error code, 322
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS error code, 324	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE error code, 322
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 324	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR error code, 322
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR error code, 324	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID error code, 322
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 323	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG error code, 322
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP error code, 325	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR error code, 315
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 326	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 316
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 326	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 317
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 322	
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 323	
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP error code, 325	

ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 317	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR error code, 318
ER_KEYRING_FAILED_TO_GENERATE_KEY error code, 316	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT error code, 319
ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 317	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER error code, 319
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 317	ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID error code, 319
ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 317	ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE error code, 320
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING error code, 318	ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE error code, 319
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP error code, 316	ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY error code, 319
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA error code, 317	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY error code, 320
ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 317	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE error code, 320
ER_KEYRING_FILE_INIT_FAILED error code, 315	ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE error code, 320
ER_KEYRING_FILE_IO_ERROR error code, 317	ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE error code, 321
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 316	ER_KEYRING_OKV_FAILED_TO_STORE_KEY error code, 320
ER_KEYRING_INCORRECT_FILE error code, 316	ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY error code, 320
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT error code, 316	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED error code, 318
ER_KEYRING_INVALID_KEY_LENGTH error code, 315	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG error code, 318
ER_KEYRING_INVALID_KEY_TYPE error code, 315	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 318
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING error code, 318	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER error code, 318
ER_KEYRING_LOGGER_ERROR_MSG error code, 299	ER_KEYRING_OKV_INVALID_KEY_TYPE error code, 318
ER_KEYRING_MIGRATE_FAILED error code, 499	ER_KEYRING_OKV_KEY_MISMATCH error code, 321
ER_KEYRING_MIGRATION_EXTRA_OPTIONS error code, 371	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED error code, 581
ER_KEYRING_MIGRATION_FAILED error code, 285	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR error code, 316
ER_KEYRING_MIGRATION_FAILURE error code, 82	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 81
ER_KEYRING_MIGRATION_STATUS error code, 82	ER_KEYRING_UNKNOWN_ERROR error code, 317
ER_KEYRING_MIGRATION_SUCCESSFUL error code, 285	ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8
ER_KEYRING_OCI_HTTP_REQUEST error code, 594	ER_KEY_DOES_NOT_EXISTS error code, 14
ER_KEYRING_OCI_INVALID_JSON error code, 594	ER_KEY_NOT_FOUND error code, 5
ER_KEYRING_OCI_PARSE_JSON error code, 594	ER_KEY_PART_0 error code, 29
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED error code, 319	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 19
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS error code, 320	ER_KILLED_THREADS_OF_PLUGIN error code, 207
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE error code, 319	ER_KILLING_THREAD error code, 206
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY error code, 320	ER_KILL_DENIED_ERROR error code, 9
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY error code, 319	ER_KEY_NOT_IN_RANGE error code, 93
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER error code, 319	ER_LCTN_CHANGED error code, 285
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY error code, 320	ER_LCTN_NOT_FOUND error code, 499
	ER_LDAP_AUTH_CERTIFICATE_NAME error code, 365

ER_LDAP_AUTH_COMMUNICATION_HOST_INFO error code, 368	ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 366
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER error code, 367	ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 525
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL error code, 367	ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 524
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED error code, 366	ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 524
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER error code, 369	ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 364
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL error code, 367	ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 525
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING error code, 363	ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 525
ER_LDAP_AUTH_CONN_POOL_INITIALIZING error code, 363	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 524
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED error code, 363	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 364
ER_LDAP_AUTH_CREATE_CONNECTION_KEY error code, 368	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 524
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 366	ER_LDAP_AUTH_INFO_FOR_USER error code, 364
ER_LDAP_AUTH_DEINIT_FAILED error code, 362	ER_LDAP_AUTH_INIT_FAILED error code, 368
ER_LDAP_AUTH_DELETING_CONNECTION_KEY error code, 367	ER_LDAP_AUTH_LDAPS error code, 525
ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 368	ER_LDAP_AUTH_LDAP_INFO_NULL error code, 367
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 369	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 366
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 363	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 366
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATE error code, 363	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 368
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 362	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 365
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 365	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 368
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_DEINIT error code, 365	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET error code, 366
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 369	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 367
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN error code, 366	ER_LDAP_AUTH_RECONSTRUCT_POOL_DISABLE_MAX_SIZE_ZERO error code, 362
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT error code, 365	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 369
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT error code, 365	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 363
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING error code, 365	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 366
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 365	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 368
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 369	ER_LDAP_AUTH_SASL_PROCESS_SASL error code, 368
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 363	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 368
ER_LDAP_AUTH_FREEING_CONNECTION error code, 367	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 364
	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 367
	ER_LDAP_AUTH_SETTING_USERNAME error code, 364

ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 362	ER_LDAP_MAPPING_TRIMMING_SPACES error code, 527
ER_LDAP_AUTH_STARTED_FOR_USER error code, 368	ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP error code, 525
ER_LDAP_AUTH_STARTING_TLS error code, 367	ER_LIMITED_PART_RANGE error code, 37
ER_LDAP_AUTH_TLS_CONF error code, 363	ER_LOAD_BULK_DATA_FAILED error code, 153
ER_LDAP_AUTH_TLS_CONNECTION error code, 363	ER_LOAD_BULK_DATA_UNSORTED error code, 151
ER_LDAP_AUTH_USER_AUTH_DATA error code, 364	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL error code, 153
ER_LDAP_AUTH_USER_BIND_FAILED error code, 369	ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG error code, 598
ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP error code, 364	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD error code, 153
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 369	ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG error code, 598
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 364	ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY error code, 176
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND error code, 513	ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 30
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 364	ER_LOAD_INFO error code, 9
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP error code, 364	ER_LOCAL_VARIABLE error code, 18
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED error code, 363	ER_LOCKING_SERVICE_DEADLOCK error code, 77
ER_LDAP_EMPTY_USERDN_PASSWORD error code, 535	ER_LOCKING_SERVICE_TIMEOUT error code, 77
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE error code, 526	ER_LOCKING_SERVICE_WRONG_NAME error code, 77
ER_LDAP_MAPPING_EMPTY_MAPPING error code, 525	ER_LOCK_ABORTED error code, 47
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING error code, 526	ER_LOCK_DEADLOCK error code, 17
ER_LDAP_MAPPING_GET_USER_PROXY error code, 525	ER_LOCK_NOWAIT error code, 88
ER_LDAP_MAPPING_INFO error code, 525	ER_LOCK_ORDER_DEPENDENCIES_SYNTAX error code, 536
ER_LDAP_MAPPING_IS_QUOTE error code, 527	ER_LOCK_ORDER_FAILED_READ_FILE error code, 535
ER_LDAP_MAPPING_NON_DESIRED_STATE error code, 527	ER_LOCK_ORDER_FAILED_WRITE_FILE error code, 535
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP error code, 526	ER_LOCK_ORDER_INIT_FAILED error code, 534
ER_LDAP_MAPPING_PARSING_CURRENT_STATE error code, 526	ER_LOCK_ORDER_MESSAGE error code, 535
ER_LDAP_MAPPING_PARSING_ERROR error code, 527	ER_LOCK_ORDER_SCANNER_SYNTAX error code, 536
ER_LDAP_MAPPING_PARSING_MAPPING_INFO error code, 526	ER_LOCK_OR_ACTIVE_TRANSACTION error code, 536
ER_LDAP_MAPPING_PROCESS_DELIMITER error code, 526	ER_LOCK_REFUSED_BY_ENGINE error code, 80
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA error code, 526	ER_LOCK_TABLE_FULL error code, 17
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL error code, 526	ER_LOCK_WAIT_TIMEOUT error code, 17
ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMPILE error code, 526	ER_LOG_BIN_BETTER_WITH_NAME error code, 171
ER_LDAP_MAPPING_PROCESS_MAPPING error code, 525	ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK error code, 606
	ER_LOG_CANNOT_WRITE error code, 156
	ER_LOG_CANNOT_WRITE_EXTENDED error code, 539
	ER_LOG_COMPONENT_CANNOT_INIT error code, 561
	ER_LOG_COMPONENT_FLUSH_FAILED error code, 573
	ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE error code, 170
	ER_LOG_FILE_CANNOT_OPEN error code, 306
	ER_LOG_FILE_INVALID error code, 170
	ER_LOG_GENERAL_CANNOT_OPEN error code, 156

ER_LOG_IN_USE error code, 28	ER_MECAB_PARSE_FAILED error code, 289
ER_LOG_OUTPUT_CONTRADICTION error code, 169	ER_MECAB_UNSUPPORTED_CHARSET error code, 289
ER_LOG_PRINTF_MSG error code, 283	ER_MESSAGE_AND_STATEMENT error code, 46
ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT error code, 543	ER_MFA_METHODS_IDENTICAL error code, 143
ER_LOG_PURGE_NO_FILE error code, 41	ER_MFA_METHODS_INVALID_ORDER error code, 143
ER_LOG_PURGE_UNKNOWN_ERR error code, 28	ER_MFA_METHOD_EXISTS error code, 142
ER_LOG_SLOW_CANNOT_OPEN error code, 156	ER_MFA_METHOD_NOT_EXISTS error code, 142
ER_LOG_SYSLOG_CANNOT_OPEN error code, 155	ER_MFA_PLUGIN_NOT_LOADED error code, 580
ER_LOG_SYSLOG_FACILITY_FAIL error code, 155	ER_MFA_USER_ATTRIBUTES_CORRUPT error code, 580
ER_LONGITUDE_OUT_OF_RANGE error code, 93	ER_MISAPPROPRIATE_TIMER_IS_NOT_AVAILABLE error code, 280
ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI error code, 170	ER_MIGRATE_TABLE_TO_DD_OOM error code, 546
ER_LOWER_CASE_TABLE_NAMES_USING_0 error code, 170	ER_MISPLACED_INTO error code, 130
ER_LOWER_CASE_TABLE_NAMES_USING_2 error code, 170	ER_MISSING_ACL_SYSTEM_TABLE error code, 271
ER_MALFORMED_GTID_SET_ENCODING error code, 54	ER_MISSING_CURRENT_PASSWORD error code, 123
ER_MALFORMED_GTID_SET_SPECIFICATION error code, 54	ER_MISSING_GRANT_SYSTEM_TABLE error code, 271
ER_MALFORMED_GTID_SPECIFICATION error code, 54	ER_MISSING_HA_CREATE_OPTION error code, 66
ER_MALFORMED_PACKET error code, 59	ER_MISSING_JSON_TABLE_VALUE error code, 98
ER_MANDATORY_ROLE error code, 94	ER_MISSING_JSON_VALUE error code, 131
ER_MASTER error code, 15	ER_MISSING_KEY error code, 64
ER_MASTER_DELAY_VALUE_OUT_OF_RANGE error code, 50	ER_MISSING_SKIP_REPLICA error code, 22
ER_MASTER_FATAL_ERROR_READING_BINLOG error code, 19	ER_MISSING_SKIP_SLAVE error code, 22
ER_MASTER_HAS_PURGED_REQUIRED_GTIDS error code, 55	ER_MISSING_TABLESPACE_FILE error code, 94
ER_MASTER_INFO error code, 16	ER_MIXING_NOT_ALLOWED error code, 18
ER_MASTER_KEY_ROTATION_BINLOG_FAILED error code, 80	ER_MIX_HANDLER_ERROR error code, 35
ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SLAVE error code, 80	ER_MIX_OF_GROUP_FUNC_AND_FIELDS error code, 12
ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE error code, 81	ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2 error code, 73
ER_MASTER_NET_READ error code, 15	ER_MTA_CANT_PARALLEL error code, 52
ER_MASTER_NET_WRITE error code, 15	ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS error code, 57
ER_MAXVALUE_IN_VALUES_IN error code, 44	ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 62
ER_MAX_PREPARED_STMT_COUNT_REACHED error code, 33	ER_MTA_FEATURE_IS_NOT_SUPPORTED error code, 52
ER_MDL_OUT_OF_RESOURCES error code, 133	ER_MTA_INCONSISTENT_DATA error code, 53
ER_MECAB_CHARSET_LOADED error code, 289	ER_MTA_RECOVERY_FAILURE error code, 57
ER_MECAB_CREATE_LATTICE_FAILED error code, 289	ER_MTA_RESET_WORKERS error code, 57
ER_MECAB_CREATING_MODEL error code, 288	ER_MTA_UPDATED_DBS_GREATER_MAX error code, 52
ER_MECAB_FAILED_TO_CREATE_MODEL error code, 289	ER_MTR_MSG_1 error code, 574
ER_MECAB_FAILED_TO_CREATE_TRIGGER error code, 289	ER_MTS_CANT_PARALLEL error code, 52
ER_MECAB_NOT_SUPPORTED error code, 288	ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS error code, 57
ER_MECAB_NOT_VERIFIED error code, 288	ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 62
ER_MECAB_OOM_WHILE_PARSING_TEXT error code, 289	ER_MTS_FEATURE_IS_NOT_SUPPORTED error code, 52
	ER_MTS_INCONSISTENT_DATA error code, 52
	ER_MTS_RECOVERY_FAILURE error code, 57
	ER_MTS_RESET_WORKERS error code, 57

ER_MTS_UPDATED_DBS_GREATER_MAX error code, 52	ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_DROPPED error code, 238
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME error code, 128	ER_NDB_BINLOG_CANT_CREATE_PURGE_THD error code, 260
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 35	ER_NDB_BINLOG_CANT_DISCOVER_TABLE_FROM_SCHEMA error code, 232
ER_MULTIPLE_INT0 CLAUSES error code, 129	ER_NDB_BINLOG_CANT_DROP_EVENT_FROM_DB error code, 238
ER_MULTIPLE_JSON_VALUES error code, 131	ER_NDB_BINLOG_CANT_INJECT_APPLY_STATUS_WRITE_ROW error code, 240
ER_MULTIPLE_PRI_KEY error code, 7	ER_NDB_BINLOG_CANT_LOCK_NDB_BINLOG_INDEX error code, 235
ER_MULTI_UPDATE_KEY_CONFLICT error code, 48	ER_NDB_BINLOG_CANT_RELEASE_SLOCK error code, 233
ER_MUST_CHANGE_EXPIRED_PASSWORD error code, 267	ER_NDB_BINLOG_CANT_REOPEN_SHADOW_TABLE error code, 234
ER_MUST_CHANGE_PASSWORD error code, 58	ER_NDB_BINLOG_CANT_WRITE_TO_NDB_BINLOG_INDEX error code, 235
ER_MUST_CHANGE_PASSWORD_LOGIN error code, 61	ER_NDB_BINLOG_CLEANING_UP_SETUP_LEFTOVERS error code, 231
ER_MYINIT_FAILED error code, 168	ER_NDB_BINLOG_CLUSTER_FAILURE error code, 239
ER_MYISAM_CHECK_METHOD_ERROR error code, 283	ER_NDB_BINLOG_CLUSTER_HAS_RECONNECTED error code, 240
ER_MYISAM_CRASHED_ERROR error code, 283	ER_NDB_BINLOG_CLUSTER_MASTER_RESTARTED_RESET_MASTER_STATUS error code, 239
ER_MYISAM_CRASHED_ERROR_IN error code, 178	ER_NDB_BINLOG_CREATE_TABLE_EVENT error code, 209
ER_MYISAM_CRASHED_ERROR_IN_THREAD error code, 178	ER_NDB_BINLOG_CREATE_TABLE_EVENT_FAILED error code, 237
ER_MYSQLBACKUP_CLIENT_MSG error code, 146	ER_NDB_BINLOG_CREATE_TABLE_EVENT_INFO error code, 237
ER_MYSQLBACKUP_MSG error code, 540	ER_NDB_BINLOG_CREATING_NDBEVENTOPERATION_FAILED error code, 238
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD error code, 521	ER_NDB_BINLOG_DISCOVER_REUSING_OLD_EVENT_OPS error code, 238
ER_MY_MALLOC_GETPROCADDRESS_FAILED error code, 583	ER_NDB_BINLOG_DISCOVER_TABLE_EVENT_INFO error code, 237
ER_MY_MALLOC_LOADLIBRARY_FAILED error code, 582	ER_NDB_BINLOG_ERROR_DURING_GCI_COMMIT error code, 241
ER_MY_MALLOC_USING_JEMALLOC error code, 582	ER_NDB_BINLOG_ERROR_DURING_GCI_ROLLBACK error code, 241
ER_MY_MALLOC_USING_STD_MALLOC error code, 582	ER_NDB_BINLOG_ERROR_HANDLING_SCHEMA_EVENT error code, 240
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STREAM error code, 246	ER_NDB_BINLOG_ERROR_INFO_FROM_DA error code, 209
ER_M_BIGGER_THAN_D error code, 31	ER_NDB_BINLOG_FAILED_CREATE_EVENT_OPERATIONS_DURING_FLUSH error code, 209
ER_NAME_BECOMES_EMPTY error code, 34	ER_NDB_BINLOG_FAILED_CREATE_TABLE_EVENT_OPERATION error code, 209
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE error code, 280	ER_NDB_BINLOG_FAILED_TO_GET_TABLE error code, 237
ER_NATIVE_FCT_NAME_COLLISION error code, 40	ER_NDB_BINLOG_FORMAT_CHANGED_FROM_STMT_TO_MIXED error code, 210
ER_NDBINFO_NOT_UPGRADING_SCHEMA error code, 550	ER_NDB_BINLOG_GENERIC_MESSAGE error code, 236
ER_NDBINFO_UPGRADING_SCHEMA error code, 550	ER_NDB_BINLOG_CANT_DROP error code, 234
ER_NDBINFO_UPGRADING_SCHEMA_FAIL error code, 550	
ER_NDB_BINLOG_BLOB_REQUIRES_PK error code, 237	
ER_NDB_BINLOG_CANT_COMMIT_TO_NDB_BINLOG_INDEX error code, 235	
ER_NDB_BINLOG_CANT_CREATE_BLOB error code, 238	
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB error code, 237	
ER_NDB_BINLOG_CANT_CREATE_EVENT_IN_DB_AND_INDEX error code, 237	

ER_NDB_BINLOG_GOT_SCHEMA_EVENT error code, 234	ER_NDB_BINLOG_USING_SERVER_ID_0_SLAVES_WILL_NOT_WRITE error code, 236
ER_NDB_BINLOG_INJECTING_RANDOM_WRITE_FAILED error code, 235	ER_NDB_BINLOG_WRITE_TO_NDB_BINLOG_INDEX_FAILED error code, 236
ER_NDB_BINLOG_INJECTOR_DISCARDING_ROW_EVENTS error code, 239	ER_NDB_BINLOG_WRITING_TO_NDB_BINLOG_INDEX error code, 235
ER_NDB_BINLOG_LATEST_TRX_IN_EPOCH_NOT_IN_BINLOG error code, 241	ER_NDB_CANNOT_ALLOC_GLOBAL_NDB_CLUSTER_CONNECTION error code, 251
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_CONNECTION error code, 240	ER_NDB_CANNOT_ALLOC_GLOBAL_NDB_OBJECT error code, 251
ER_NDB_BINLOG_LOST_SCHEMA_CONNECTION_WAITING error code, 240	ER_NDB_CANNOT_ALLOC_NDB_CLUSTER_CONNECTION error code, 252
ER_NDB_BINLOG_NDBEVENT_EXECUTE_FAILED error code, 238	ER_NDB_CANNOT_FIND_TABLE error code, 233
ER_NDB_BINLOG_NDB_LOG_APPLY_STATUS_FORCING error code, 236	ER_NDB_CANNOT_PARSE_NDB_CLUSTER_CONNECTION_PARAMETERS error code, 255
ER_NDB_BINLOG_NDB_LOG_TRANSACTION_ID_REQUIRED error code, 236	ER_NDB_CANNOT_START_CONNECT_THREAD error code, 252
ER_NDB_BINLOG_NDB_TABLES_INITIALLY_READ_ONLY error code, 211	ER_NDB_CANNOT_WRITE error code, 252
ER_NDB_BINLOG_NDB_TABLES_WRITABLE error code, 240	ER_NDB_CLEANING_STRAY_TABLES error code, 230
ER_NDB_BINLOG_NOT_LOGGING error code, 237	ER_NDB_CLEAR_SLOCK_INFO error code, 233
ER_NDB_BINLOG_ONLINE_ALTER_RENAME error code, 233	ER_NDB_CLUSTER_FAILURE error code, 234
ER_NDB_BINLOG_ONLINE_ALTER_RENAME_COMPLETED error code, 234	ER_NDB_CLUSTER_FIND_ALL_DBS_FAIL error code, 231
ER_NDB_BINLOG_OPENING_INDEX error code, 235	ER_NDB_CLUSTER_FIND_ALL_DBS_RETRY error code, 231
ER_NDB_BINLOG_RELEASING_EXTRA_SHARE_REFERENCES error code, 241	ER_NDB_CLUSTER_FREE_SHARE_INFO error code, 211
ER_NDB_BINLOG_REMAINING_OPEN_TABLES error code, 241	ER_NDB_CLUSTER_GENERIC_MESSAGE error code, 197
ER_NDB_BINLOG_REMAINING_OPEN_TABLE_INFO error code, 241	ER_NDB_CLUSTER_GET_SHARE_INFO error code, 210
ER_NDB_BINLOG_RENAME_EVENT error code, 209	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_DESTROYING error code, 211
ER_NDB_BINLOG_REPLY_TO error code, 233	ER_NDB_CLUSTER_MARK_SHARE_DROPPED_INFO error code, 211
ER_NDB_BINLOG_SERVER_SHUTDOWN_DURING_NDB_CLUSTER_START error code, 239	ER_NDB_CLUSTER_OOM_THD_NDB error code, 211
ER_NDB_BINLOG_SHUTDOWN_DETECTED error code, 240	ER_NDB_CLUSTER_REAL_FREE_SHARE_DROP_FAILED error code, 211
ER_NDB_BINLOG_SIGNALLING_UNKNOWN_VALUE error code, 233	ER_NDB_CLUSTER_REAL_FREE_SHARE_INFO error code, 211
ER_NDB_BINLOG_SKIPPING_DROP_OF_DB_CONTAINING_TABLES error code, 234	ER_NDB_CLUSTER_SCHEMA_INFO error code, 197
ER_NDB_BINLOG_SKIPPING_DROP_OF_LOCAL_TABLE error code, 234	ER_NDB_CLUSTER_WRONG_NUMBER_OF_FUNCTION_ARGUMENTS error code, 197
ER_NDB_BINLOG_SKIPPING_LOCAL_TABLE error code, 233	ER_NDB_COLUMN_DEFAULTS_DIFFER error code, 207
ER_NDB_BINLOG_SKIPPING_OLD_SCHEMA_OPERATION error code, 234	ER_NDB_COLUMN_INFO error code, 208
ER_NDB_BINLOG_SKIPPING_RENAME_OF_LOCAL_TABLE error code, 234	ER_NDB_COLUMN_SHOULD_NOT_HAVE_NATIVE_DEFAULT error code, 207
ER_NDB_BINLOG_STARTING_LOG_AT_EPOCH error code, 240	ER_NDB_CONFLICT_FN_PARSE_ERROR error code, 237
ER_NDB_BINLOG_UNHANDLED_ERROR_FOR_TABLE error code, 239	ER_NDB_CONFLICT_FN_SETUP_ERROR error code, 237
ER_NDB_BINLOG_UNKNOWN_NON_DATA_EVENT error code, 239	ER_NDB_CONFLICT_GENERIC_MESSAGE error code, 236
	ER_NDB_COULD_NOT_GET_APPLY_STATUS_SHARE error code, 239
	ER_NDB_CPU_MASK_TOO_SHORT error code, 252

ER_NDB_CREATE_EVENT_OPS_LOGGING_INFO error code, 238	ER_NDB_NODE_ID_AND_MANAGEMENT_SERVER_INFO error code, 207
ER_NDB_CREATING_SHARE_IN_OPEN error code, 210	ER_NDB_NODE_INFO error code, 252
ER_NDB_CREATING_TABLE error code, 230	ER_NDB_NOT_WAITING_FOR_DISTRIBUTING error code, 232
ER_NDB_DISCARDING_EVENT_ID_VERSION_MISMATCH error code, 233	ER_NDB_NUMBER_OF_CHANNELS error code, 263
ER_NDB_DISCARDING_EVENT_NO_OBJ error code, 233	ER_NDB_OOM_GET_NDB_BLOBS_VALUE error code, 230
ER_NDB_DISCONNECT_INFO error code, 207	ER_NDB_OOM_IN_FIX_UNIQUE_INDEX_ATTR_ORDER error code, 208
ER_NDB_DISCOVERED_MISSING_DB error code, 230	ER_NDB_POOL_SIZE_MUST_MATCH_NDB_CLUSTER_CONNEC error code, 251
ER_NDB_DISCOVERED_REMAINING_DB error code, 231	ER_NDB_QUERY_FAILED error code, 206
ER_NDB_DISTRIBUTED_INFO error code, 232	ER_NDB_REMAINING_OPEN_TABLES error code, 239
ER_NDB_DISTRIBUTING_ERR error code, 263	ER_NDB_REMAINING_OPEN_TABLE_INFO error code, 239
ER_NDB_DISTRIBUTION_COMPLETE error code, 232	ER_NDB_REPLICATION_SCHEMA_ERROR error code, 232
ER_NDB_DUPLICATE_NODEID_IN_NDB_CLUSTER_CONN error code, 251	ER_NDB_REPLICATION_POOL_NODEIDS error code, 232
ER_NDB_EMPTY_NODEID_IN_NDB_CLUSTER_CONN error code, 250	ER_NDB_SCHEMA_DISTRIBUTION_FAILED error code, 232
ER_NDB_ERROR_IN_GET_AUTO_INCREMENT error code, 210	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_SUBSCRIBE error code, 232
ER_NDB_ERROR_IN_READAUTOINCREMENTVALUE error code, 208	ER_NDB_SCHEMA_DISTRIBUTION_REPORTS_UNSUBSCRIBE error code, 232
ER_NDB_FAILED_TO_SET_UP_TABLE error code, 231	ER_NDB_SCHEMA_GENERIC_MESSAGE error code, 204
ER_NDB_FIELD_INFO error code, 207	ER_NDB_SERVER_ID_RESERVED_OR_TOO_LARGE error code, 236
ER_NDB_FLUSHING_TABLE_INFO error code, 230	ER_NDB_SHARE_ALREADY_EXISTS error code, 210
ER_NDB_FOUND_UNCOMMITTED_AUTOCOMMIT error code, 208	ER_NDB_SKIPPING_SETUP_TABLE error code, 231
ER_NDB_GENERIC_ERROR error code, 252	ER_NDB_SLAVE_BINLOG_MISSING_INFO_FOR_CONFLICT_DE error code, 208
ER_NDB_HANDLE_TRAILING_SHARE_INFO error code, 210	ER_NDB_SLAVE_CANT_ALLOCATE_TABLE_SHARE error code, 209
ER_NDB_IGNOREING_UNKNOWN_EVENT error code, 235	ER_NDB_SLAVE_CONFLICT_DETECTION_REQUIRES_TRANSA error code, 208
ER_NDB_ILLEGAL_VALUE_FOR_NDB_RECV_THREAD error code, 211	ER_NDB_SLAVE_CONFLICT_FUNCTION_REQUIRES_ROLE error code, 208
ER_NDB_INFO_FAILED_TO_CREATE_NDBINFO error code, 197	ER_NDB_SLAVE_ERROR_IN_UPDATE_CREATE_INFO error code, 209
ER_NDB_INFO_FAILED_TO_INIT_NDBINFO error code, 197	ER_NDB_SLAVE_LOGGING_EXCEPTIONS_TO error code, 196
ER_NDB_INFO_FOUND_UNEXPECTED_FIELD_TYPE error code, 197	ER_NDB_SLAVE_LOW_EPOCH_RESOLUTION error code, 196
ER_NDB_INITIALIZE_GIVEN_CLUSTER_PLUGIN_DISAB error code, 210	ER_NDB_SLAVE_MALFORMED_EVENT_RECEIVED_ON_TABLE error code, 208
ER_NDB_INVALID_NODEID_IN_NDB_CLUSTER_CONN error code, 251	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_SET_TO error code, 207
ER_NDB_LOG_ENTRY error code, 260	ER_NDB_SLAVE_MAX_REPLICATED_EPOCH_UNKNOWN error code, 207
ER_NDB_LOG_ENTRY_WITH_PREFIX error code, 260	ER_NDB_SLAVE_MISSING_DATA_FOR_TIMESTAMP_COLUMN error code, 196
ER_NDB_MISMATCH_IN_FRM_DISCOVERING error code, 231	ER_NDB_SLAVE_PARALLEL_WORKERS error code, 263
ER_NDB_MISSING_FRM_DISCOVERING error code, 231	ER_NDB_SLAVE_PREVIOUS_EPOCH_NOT_COMMITTED error code, 196
ER_NDB_NODEID_NOT_FIRST_IN_NDB_CLUSTER_CONN error code, 251	ER_NDB_SLAVE_REPLICATION_POOL_NODEIDS error code, 232

ER_NDB_SLAVE_SAW_ALREADY_COMMITTED_EPOCH error code, 196	ER_NET_WRITE_INTERRUPTED error code, 13
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS error code, 196	ER_NEW_ABORTING_CONNECTION error code, 15
ER_NDB_SLAVE_SAW_EPOCH_LOWER_THAN_PREVIOUS error code, 196	ER_NO error code, 3
ER_NDB_SLAVE_TOO_MANY_RETRIES error code, 209	ER_NONEXISTING_GRANT error code, 12
ER_NDB_STARTING_CONNECT_THREAD error code, 252	ER_NONEXISTING_PROC_GRANT error code, 29
ER_NDB_TABLES_INITIALLY_READ_ONLY_ON_RECONNECT error code, 235	ER_NONEXISTING_TABLE_GRANT error code, 13
ER_NDB_TABLES_NOT_READY error code, 174	ER_NONPOSITIVE_RADIUS error code, 103
ER_NDB_TABLE_IS_NOT_DISTRIBUTED error code, 230	ER_NONUNIQ_TABLE error code, 7
ER_NDB_TABLE_OPENED_READ_ONLY error code, 210	ER_NONUPDATEABLE_COLUMN error code, 26
ER_NDB_THREAD_TIMED_OUT error code, 230	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT error code, 114
ER_NDB_TIMED_OUT_IN_DROP_TABLE error code, 238	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN error code, 75
ER_NDB_TIMEOUT_WHILE_DISTRIBUTING error code, 232	ER_NON_GROUPING_FIELD_USED error code, 33
ER_NDB_TOO_MANY_CPUS_IN_NDB_RECV_THREAD error code, 212	ER_NON_INSERTABLE_TABLE error code, 34
ER_NDB_TRAILING_SHARE_RELEASED_BY_CLOSE_CACHE error code, 210	ER_NON_RO_SELECT_DISABLE_TIMER error code, 67
ER_NDB_TRANS_DEPENDENCY_TRACKER_ERROR error code, 236	ER_NON_UNIQ_ERROR error code, 6
ER_NDB_UNEXPECTED_RENAME_TYPE error code, 209	ER_NON_UPDATABLE_TABLE error code, 23
ER_NDB_USING_NODEID error code, 251	ER_NORMAL_SERVER_SHUTDOWN error code, 499
ER_NDB_USING_NODEID_LIST error code, 251	ER_NORMAL_SHUTDOWN error code, 8
ER_NDB_UTIL_THREAD_OOM error code, 211	ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_COMPONENT error code, 564
ER_NDB_WAITING_INFO error code, 231	ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS error code, 602
ER_NDB_WAITING_INFO_WITH_MAP error code, 231	ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS error code, 602
ER_NEED_FILE_INSTEAD_OF_DIR error code, 171	ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER error code, 566
ER_NEED_LOG_BIN error code, 171	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY error code, 566
ER_NEED_REPREPARE error code, 41	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_ERROR error code, 566
ER_NETWORK_NAMESPACES_NOT_SUPPORTED error code, 532	ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR error code, 566
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG error code, 532	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED error code, 567
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE error code, 532	ER_NOTE_KEYRING_COMPONENT_INITIALIZED error code, 566
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE error code, 500	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR error code, 567
ER_NET_ERROR_ON_WRITE error code, 13	ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR error code, 567
ER_NET_FCNTL_ERROR error code, 13	ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND error code, 566
ER_NET_OK_PACKET_TOO_LARGE error code, 70	ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED error code, 567
ER_NET_PACKETS_OUT_OF_ORDER error code, 13	ER_NOTE_KEYRING_COMPONENT_STORE_FAILED error code, 567
ER_NET_PACKET_TOO_LARGE error code, 13	ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA error code, 567
ER_NET_READ_ERROR error code, 13	ER_NOT_ALLOWED_COMMAND error code, 13
ER_NET_READ_ERROR_FROM_PIPE error code, 13	ER_NOT_ALLOWED_WITH_START_TRANSACTION error code, 133
ER_NET_READ_INTERRUPTED error code, 13	ER_NOT_FORM_FILE error code, 5
ER_NET_UNCOMPRESS_ERROR error code, 13	ER_NOT_HINT_UPDATABLE_VARIABLE error code, 95
ER_NET_WAIT_ERROR error code, 533	
ER_NET_WAIT_ERROR2 error code, 568	

ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS error code, 102	ER_NO_SYSTEM_VIEW_ACCESS error code, 93
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS error code, 93	ER_NO_TABLES_USED error code, 9
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS error code, 102	ER_NO_THD_NO_UUID error code, 161
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS error code, 306	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA error code, 33
ER_NOT_KEYFILE error code, 5	ER_NO_UNIQUE_LOGFILE error code, 9
ER_NOT_RIGHT_NOW error code, 168	ER_NPIPE_CANT_CREATE error code, 262
ER_NOT_SUPPORTED_AUTH_MODE error code, 20	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR error code, 195
ER_NOT_SUPPORTED_YET error code, 19	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR error code, 195
ER_NOT_VALID_PASSWORD error code, 58	ER_NPIPE_PIPE_ALREADY_IN_USE error code, 195
ER_NO_ACCESS_TO_NATIVE_FCT error code, 88	ER_NULL_COLUMN_IN_INDEX error code, 11
ER_NO_BINARY_LOGGING error code, 28	ER_NULL_IN_VALUES_LESS_THAN error code, 39
ER_NO_BINLOG_ERROR error code, 36	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 79
ER_NO_CSV_NO_LOG_TABLES error code, 170	ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECKSUM error code, 541
ER_NO_DB_ERROR error code, 6	ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION error code, 543
ER_NO_DEFAULT error code, 19	ER_OLD_FILE_FORMAT error code, 33
ER_NO_DEFAULT_FOR_FIELD error code, 27	ER_OLD_KEYFILE error code, 5
ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 30	ER_OLD_PASSWORDS_NO_MIDDLE_GROUND error code, 33
ER_NO_ERROR_LOG_PARSER_CONFIGURED error code, 560	ER_OLD_STATEMENT error code, 33
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT error code, 41	ER_OLD_TEMPORALS_UPGRADED error code, 63
ER_NO_FT_MATERIALIZED_SUBQUERY error code, 66	ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT error code, 50
ER_NO_PARTITION_FOR_GIVEN_VALUE error code, 37	ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326 error code, 100
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT error code, 40	ER_ONLY INTEGERS ALLOWED error code, 39
ER_NO_PARTS_ERROR error code, 35	ER_ONLY_ON_RANGE_LIST_PARTITION error code, 36
ER_NO_PATH_FOR_SHARED_LIBRARY error code, 507	ER_OOM error code, 168
ER_NO_PERMISSION_TO_CREATE_USER error code, 17	ER_OOM_SAVE_GTIDS error code, 499
ER_NO_REFERENCED_ROW error code, 18	ER_OPEN_AS_READONLY error code, 5
ER_NO_REFERENCED_ROW_2 error code, 32	ER_OPEN_ROLE_TABLES error code, 85
ER_NO_SECURE_TRANSPORTS_CONFIGURED error code, 79	ER_OPERAND_COLUMNS error code, 20
ER_NO_SESSION_TEMP error code, 122	ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY error code, 141
ER_NO_SUCH_DB error code, 83	ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE error code, 146
ER_NO_SUCH_INDEX error code, 8	ER_OPTION_PREVENTS_STATEMENT error code, 23
ER_NO_SUCH_TABLE error code, 13	ER_OPT_WRONG_TREE error code, 155
ER_NO_SUCH_THREAD error code, 9	ER_OUTOFMEMORY error code, 5
ER_NO_SUCH_USER error code, 32	ER_OUT_OF_RESOURCES error code, 5
ER_NO_SUPER_WITHOUT_USER_PLUGIN error code, 187	ER_OUT_OF_SORTMEMORY error code, 5
ER_NO_SYSTEM_SCHEMA_ACCESS error code, 86	ER_PAGE_TRACKING_CANNOT_PURGE error code, 113
ER_NO_SYSTEM_TABLESPACE_ACCESS error code, 86	ER_PAGE_TRACKING_NOT_STARTED error code, 113
ER_NO_SYSTEM_TABLE_ACCESS error code, 87	ER_PAGE_TRACKING_RANGE_NOT_TRACKED error code, 113
ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLES error code, 87	ER_PARSER_TRACE error code, 155
ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLES error code, 87	ER_PARSE_ERROR error code, 7
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLESPACE error code, 87	ER_PARSE_ERROR_IN_DIGEST_FN error code, 99
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLESPACE error code, 87	ER_PARSING_VIEW error code, 161
	ER_PARTIAL_REVOKES_EXIST error code, 123

ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXIST error code, 124	ER_PASSWORD_NO_MATCH error code, 12
ER_PARTITIONS_MUST_BE_DEFINED_ERROR error code, 35	ER_PATH_IN_DATADIR error code, 95
ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 51	ER_PATH_LENGTH error code, 46
ER_PARTITION_COLUMN_LIST_ERROR error code, 44	ER_PERFORMANCE_SCHEMA_VERSION_CHANGE error code, 608
ER_PARTITION_CONST_DOMAIN_ERROR error code, 39	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 268
ER_PARTITION_ENTRY_ERROR error code, 35	ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 268
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 50	ER_PERFSCHEMA_INIT_FAILED error code, 172
ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 51	ER_PERFSCHEMA_TABLES_INIT_FAILED error code, 269
ER_PARTITION_EXCHANGE_PART_TABLE error code, 51	ER_PERSISTED_VARIABLES_DECRYPTION_FAILED error code, 582
ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 51	ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED error code, 582
ER_PARTITION_FIELDS_TOO_LONG error code, 45	ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED error code, 582
ER_PARTITION_FUNCTION_FAILURE error code, 37	ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT error code, 582
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 39	ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_LOADED error code, 582
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 35	ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND error code, 582
ER_PARTITION_HANDLER_ADMIN_MSG error code, 282	ER_PERSISTENT_PRIVILEGES_BOOTSTRAP error code, 269
ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 51	ER_PERSIST_ONLY_ACCESS_DENIED_ERROR error code, 94
ER_PARTITION_MAXVALUE_ERROR error code, 34	ER_PERSIST_OPTION_HOST_TRUNCATED error code, 533
ER_PARTITION_MERGE_ERROR error code, 39	ER_PERSIST_OPTION_STATUS error code, 306
ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 36	ER_PERSIST_OPTION_USER_TRUNCATED error code, 533
ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW error code, 262	ER_PFS_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL error code, 279
ER_PARTITION_NAME error code, 43	ER_PFS_MALLOC_ARRAY_OOM error code, 280
ER_PARTITION_NOT_DEFINED_ERROR error code, 35	ER_PFS_MALLOC_ARRAY_OVERFLOW error code, 280
ER_PARTITION_NO_TEMPORARY error code, 38	ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED error code, 273
ER_PARTITION_REQUIRES_VALUES_ERROR error code, 34	ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE error code, 508
ER_PARTITION_WRONG_NO_PART_ERROR error code, 34	ER_PID_FILE_PRIV_DIRECTORY_INSECURE error code, 370
ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 34	ER_PK_INDEX_CANT_BE_INVISIBLE error code, 84
ER_PARTITION_WRONG_VALUES_ERROR error code, 34	ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 77
ER_PART_EXPR_TOO_LONG error code, 94	ER_PLUGIN_BAD_OPTIONS error code, 246
ER_PASSWORD_ANONYMOUS_USER error code, 12	ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 64
ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_INSTALL error code, 123	ER_PLUGIN_CANT_LOAD error code, 245
ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD error code, 99	ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE error code, 245
ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 66	ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS error code, 246
ER_PASSWORD_FORMAT error code, 59	ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES error code, 305
ER_PASSWORD_NOT_ALLOWED error code, 12	

ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE error code, 305	ER_PREPARE_FOR_PRIMARY_ENGINE error code, 573
ER_PLUGIN_DELETE_BUILTIN error code, 42	ER_PREPARE_FOR_SECONDARY_ENGINE error code, 527
ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS error code, 207	ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 74
ER_PLUGIN_DISABLED error code, 246	ER_PRIMARY_CANT_HAVE_NULL error code, 14
ER_PLUGIN_EXCEPTION_OPERATION_FAILED error code, 599	ER_PRIVILEGE_DEREGISTRATION error code, 604
ER_PLUGIN_FAILED_DEINITIALIZATION error code, 244	ER_PRIVILEGE_REGISTRATION error code, 604
ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 505	ER_PRIVILEGE_SYSTEM_INIT_FAILED error code, 269
ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 505	ER_PROCAccess_DENIED_ERROR error code, 28
ER_PLUGIN_FORCING_SHUTDOWN error code, 245	ER_PROC_AUTO_GRANT_FAIL error code, 29
ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLE error code, 246	ER_PROC_AUTO_REVOKE_FAIL error code, 29
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION error code, 244	ER_PROTOCOL_COMPRESSION_RESET_LOG error code, 540
ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN error code, 245	ER_PS_MANY_PARAM error code, 28
ER_PLUGIN_INIT_FAILED error code, 175	ER_QUERY_INTERRUPTED error code, 32
ER_PLUGIN_INSTALL_ERROR error code, 514	ER_QUERY_CACHE_DISABLED error code, 44
ER_PLUGIN_INVALID_TABLE_DEFINITION error code, 572	ER_QUERY_INTERRUPTED error code, 25
ER_PLUGIN_IS_NOT_LOADED error code, 37	ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 31
ER_PLUGIN_IS_PERMANENT error code, 48	ER_QUERY_TIMEOUT error code, 67
ER_PLUGIN_LOAD_OPTIONS_IGNORED error code, 542	ER_RANGE_NOT_INCREASING_ERROR error code, 35
ER_PLUGIN_LOAD_PARAMETER_TOO_LONG error code, 245	ER_READING_TABLE_FAILED error code, 176
ER_PLUGIN_NOT_EARLY error code, 117	ER_READY error code, 8
ER_PLUGIN_NOT_EARLY_DUP error code, 533	ER_READ_LOG_EVENT_FAILED error code, 277
ER_PLUGIN_NO_INSTALL error code, 50	ER_READ_ONLY_MODE error code, 59
ER_PLUGIN_NO_INSTALL_DUP error code, 533	ER_READ_ONLY_TRANSACTION error code, 17
ER_PLUGIN_NO_UNINSTALL error code, 49	ER REALLY_RUN_AS_ROOT error code, 167
ER_PLUGIN_OOM error code, 246	ER_RECORD_FILE_FULL error code, 10
ER_PLUGIN_PARSING_OPTIONS_FAILED error code, 246	ER_RECOVERING_TABLE error code, 247
ER_PLUGIN_REGISTRATION_DONE error code, 142	ER_REDUCED_DBLWR_FILE_CORRUPTED error code, 606
ER_PLUGIN_REGISTRATION_FAILED error code, 245	ER_REDUCED_DBLWR_PAGE_FOUND error code, 606
ER_PLUGIN_REQUIRES_REGISTRATION error code, 142	ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 65
ER_PLUGIN_SHUTTING_DOWN_PLUGIN error code, 244	ER_REGEXP_BAD_ESCAPE_SEQUENCE error code, 101
ER_PLUGIN_UNINSTALL_ERROR error code, 514	ER_REGEXP_BAD_INTERVAL error code, 101
ER_PLUGIN_UNKNOWN_VARIABLE_TYPE error code, 245	ER_REGEXP_BUFFER_OVERFLOW error code, 100
ER_PLUGIN_VARIABLE_MISSING_NAME error code, 245	ER_REGEXP_ERROR error code, 12
ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL error code, 246	ER_REGEXP_ILLEGAL_ARGUMENT error code, 100
ER_PLUGIN_VARIABLE_SET_READ_ONLY error code, 245	ER_REGEXP_INDEX_OUTOFBOUNDS_ERROR error code, 101
ER_POINTLESS_WITHOUT_SLOWLOG error code, 163	ER_REGEXP_INTERNAL_ERROR error code, 101
ER_POLYGON_TOO_LARGE error code, 105	ER_REGEXP_INVALID_BACK_REF error code, 101
	ER_REGEXP_INVALID_CAPTURE_GROUP_NAME error code, 122
	ER_REGEXP_INVALID_FLAG error code, 123
	ER_REGEXP_INVALID_RANGE error code, 102
	ER_REGEXP_LOOK_BEHIND_LIMIT error code, 101
	ER_REGEXP_MAX_LT_MIN error code, 101
	ER_REGEXP_MISMATCHED_PAREN error code, 101
	ER_REGEXP_MISSING_CLOSE_BRACKET error code, 101

ER_REGEX_MISSING_FILE error code, 145	ER_REPLICA_CM_INIT_REPOSITORY error code, 62
ER_REGEX_MISSING_ICU_DATADIR error code, 580	ER_REPLICA_CONFIGURATION error code, 56
ER_REGEX_MISSING_RESOURCE error code, 144	ER_REPLICA_CORRUPT_EVENT error code, 41
ER_REGEX_PATTERN_TOO_BIG error code, 102	ER_REPLICA_CREATE_EVENT_FAILURE error code, 500
ER_REGEX_RULE_SYNTAX error code, 101	ER_REPLICA_FATAL_ERROR error code, 500
ER_REGEX_STACK_OVERFLOW error code, 102	ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE error code, 64
ER_REGEX_STRING_NOT_TERMINATED error code, 100	ER_REPLICA_HEARTBEAT_FAILURE error code, 500
ER_REGEX_TIME_OUT error code, 102	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 42
ER_REGEX_UNIMPLEMENTED error code, 101	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX error code, 48
ER_REGEX_NUMBER_TOO_BIG error code, 136	ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN error code, 48
ER_RELAY_LOG_FAIL error code, 28	ER_REPLICA_IGNORED_SSL_PARAMS error code, 22
ER_RELAY_LOG_INIT error code, 28	ER_REPLICA_IGNORED_TABLE error code, 19
ER_RELAY_LOG_SPACE_LIMIT_DISABLED error code, 510	ER_REPLICA_IGNORE_SERVER_IDS error code, 44
ER_RELOAD_KEYRING_FAILURE error code, 139	ER_REPLICA_INCIDENT error code, 501
ER_REMOVED_SPACES error code, 33	ER_REPLICA_KILLED_AFTER_RECONNECT error code, 278
ER_RENAMED_NAME error code, 43	ER_REPLICA_MAX_CHANNELS_EXCEEDED error code, 72
ER_RENAME_ROLE error code, 85	ER_REPLICA_MULTIPLE_CHANNELS_CMD error code, 71
ER_REORG_HASH_ONLY_ON_SAME_NO error code, 36	ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY error code, 71
ER_REORG_NO_PARAM_ERROR error code, 36	ER_REPLICA_NOT_RUNNING error code, 16
ER_REORG_OUTSIDE_RANGE error code, 36	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REORG_PARTITION_NOT_EXIST error code, 36	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLACE_INACCESSIBLE_ROWS error code, 70	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GPI error code, 596	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_AM_INIT_REPOSITORY error code, 62	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_SOURCE error code, 563	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_REPLICATION_POSSIBLY_DIVERGED_AFTER_DDL error code, 563	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CANT_CREATE_CONVERSION error code, 46	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CANT_USE_TMPDIR error code, 229	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED error code, 228	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_DOES_NOT_EXIST error code, 71	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP error code, 66	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_MUST_STOP error code, 72	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 71	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_NOT_RUNNING error code, 72	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED error code, 78	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER error code, 73	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP error code, 73	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING error code, 72	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
ER_REPLICA_CHANNEL_WAS_RUNNING error code, 72	ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 279
	ER_REPLICA_SOURCE_COM_FAILURE error code, 501
	ER_REPLICA_SQL_THREAD_MUST_STOP error code, 66
	ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_RE error code, 194
	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_A error code, 193
	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_R error code, 194
	ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCE error code, 194
	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION error code, 193

ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED error code, 193	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED error code, 273
ER_REPLICA_THREAD error code, 17	ER_RES_GRP_SET_THR_AFFINITY_FAILED error code, 273
ER_REPLICA_WORKER_STOPPED_PREVIOUS_THREAD error code, 67	ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED error code, 273
ER_REQUIRES_PRIMARY_KEY error code, 14	ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED error code, 274
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE error code, 129	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_ID_FAILED error code, 274
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED error code, 153	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED error code, 274
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED error code, 599	ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_GLOB error code, 593
ER_RESERVED_SYNTAX error code, 28	ER_RES_GRP_SWITCH_FAILED_COULD_NOT_ACQUIRE_LOCK error code, 593
ER_RESERVED_TABLESPACE_NAME error code, 104	ER_RES_GRP_SWITCH_FAILED_UNABLE_TO_APPLY_RES_GRP error code, 593
ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE error code, 88	ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED error code, 273
ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE error code, 88	ER_RETRYING_REPAIR_WITHOUT_QUICK error code, 246
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER error code, 43	ER_RETRYING_REPAIR_WITH_KEYCACHE error code, 246
ER_RESOURCE_GROUP_BIND_FAILED error code, 98	ER_REVOKE_GRANTS error code, 21
ER_RESOURCE_GROUP_BUSY error code, 97	ER_REWRITER_LOAD_FAILED error code, 307
ER_RESOURCE_GROUP_DISABLED error code, 98	ER_REWRITER_OOM error code, 307
ER_RESOURCE_GROUP_EXISTS error code, 97	ER_REWRITER_QUERY_ERROR_MSG error code, 303
ER_RESOURCE_GROUP_IS_DISABLED error code, 273	ER_REWRITER_QUERY_FAILED error code, 303
ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED error code, 272	ER_REWRITER_READ_FAILED error code, 307
ER_RESOURCE_GROUP_NOT_EXISTS error code, 97	ER_REWRITER_TABLE_MALFORMED_ERROR error code, 307
ER_RESOURCE_GROUP_POST_INIT_FAILED error code, 268	ER_ROLE_GRANTED_TO_ITSELF error code, 139
ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED error code, 268	ER_ROLE_NOT_GRANTED error code, 85
ER_RESOURCE_GROUP_VALIDATION_FAILED error code, 272	ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG error code, 277
ER_RESTART_RECEIVED_INFO error code, 285	ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET error code, 51
ER_RESTART_SERVER_FAILED error code, 103	ER_ROW_DOES_NOT_MATCH_PARTITION error code, 51
ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT error code, 274	ER_ROW_IN_WRONG_PARTITION error code, 62
ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY error code, 274	ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR error code, 178
ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE error code, 274	ER_ROW_IS_REFERENCED error code, 18
ER_RES_GRP_FAILED_TO_SWITCH_RESOURCE_GROUP error code, 593	ER_ROW_IS_REFERENCED_2 error code, 32
ER_RES_GRP_FEATURE_NOT_AVAILABLE error code, 274	ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 44
ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED error code, 274	ER_RPL_AM_INIT_INFO_MSG error code, 282
ER_RES_GRP_INVALID_THREAD_PRIORITY error code, 274	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT error code, 561
ER_RES_GRP_INVALID_VCPU_ID error code, 284	ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM error code, 561
ER_RES_GRP_INVALID_VCPU_RANGE error code, 284	ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST error code, 561
	ER_RPL_ASYNC_EXECUTING_QUERY error code, 562

ER_RPL_ASYNC_MANAGED_NAME_ADDED error code, 562	ER_RPL_CANT_OPEN_LOG_IN_RLI_INIT_INFO error code, 230
ER_RPL_ASYNC_MANAGED_NAME_REMOVED error code, 562	ER_RPL_CANT_SCAN_INFO_TABLE error code, 197
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED error code, 600	ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP error code, 119
ER_RPL_ASYNC_READ_FAILOVER_TABLE error code, 562	ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP error code, 119
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF error code, 134	ER_RPL_CHANGING_APPLIER_METADATA_REPO_TYPE_FAILED error code, 199
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE error code, 559	ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED error code, 199
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF error code, 134	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 198
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL error code, 564	ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES error code, 198
ER_RPL_ASYNC_SENDER_ADDED error code, 561	ER_RPL_CORRUPTED_INFO_TABLE error code, 197
ER_RPL_ASYNC_SENDER_REMOVED error code, 561	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 197
ER_RPL_BINLOG_FILTERS_OOM error code, 165	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY error code, 113
ER_RPL_BINLOG_MASTER_SENDS_HEARTBEAT error code, 205	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 113
ER_RPL_BINLOG_MASTER_USES_CHECKSUM_AND_SLAVE_ERROR error code, 206	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 111
ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED error code, 175	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 112
ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEATS error code, 206	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 112
ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT error code, 206	ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 112
ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_SLAVE_ERROR error code, 206	ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 112
ER_RPL_BINLOG_STARTING_DUMP error code, 205	ER_RPL_ENCRYPTION_HEADER_ERROR error code, 111
ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED error code, 175	ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 111
ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED error code, 175	ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 112
ER_RPL_CANNOT_OPEN_RELAY_LOG error code, 577	ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 111
ER_RPL_CANT_ADD_DO_TABLE error code, 169	ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 112
ER_RPL_CANT_ADD_IGNORE_TABLE error code, 169	ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION error code, 112
ER_RPL_CANT_CREATE_REPLICA_THREAD error code, 217	ER_RPL_ERROR_CHANGING_APPLIER_METADATA_REPO_TYPE error code, 199
ER_RPL_CANT_CREATE_SLAVE_THREAD error code, 216	ER_RPL_ERROR_CHANGING_CONNECTION_METADATA_REPO_TYPE error code, 199
ER_RPL_CANT_FIND_FOLLOWUP_FILE error code, 223	ER_RPL_ERROR_CHANGING_MASTER_INFO_REPO_TYPE error code, 198
ER_RPL_CANT_HAVE_SAME_BASENAME error code, 265	ER_RPL_ERROR_CHANGING_RELAY_LOG_INFO_REPO_TYPE error code, 199
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO error code, 229	ER_RPL_ERROR_CHECKING_REPOSITORY error code, 200
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_RLI_INIT_INFO error code, 229	ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 199
ER_RPL_CANT_MAKE_PATHS error code, 171	ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 198
ER_RPL_CANT_OPEN_INFO_TABLE error code, 197	
ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO error code, 230	

ER_RPL_ERROR_CREATING_MASTER_INFO error code, 198	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE error code, 498
ER_RPL_ERROR_CREATING_RELAY_LOG_INFO error code, 199	ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE error code, 498
ER_RPL_ERROR_LOOKING_FOR_LOG error code, 222	ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 204
ER_RPL_ERROR_READING_MASTER_CONFIGURATION error code, 244	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 198
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION error code, 242	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 198
ER_RPL_ERROR_READING_SLAVE_WORKER_CONFIGURATION error code, 242	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION error code, 575
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION error code, 244	ER_RPL_INFINITY_DENIED error code, 173
ER_RPL_ERROR_WRITING_MASTER_CONFIGURATION error code, 244	ER_RPL_INFINITY_IGNORED error code, 174
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 230	ER_RPL_INFO_DATA_TOO_LONG error code, 51
ER_RPL_ERROR_WRITING_SLAVE_WORKER_CONFIGURATION error code, 242	ER_RPL_IO_THREAD_KILLED error code, 278
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION error code, 244	ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED error code, 609
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 202	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET error code, 221
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 202	ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET error code, 221
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_CONFIGURATION error code, 200	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_ENTRIES error code, 229
ER_RPL_FAILED_TO_DELETE_FROM_SLAVE_WORKER_CONFIGURATION error code, 200	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER error code, 609
ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 202	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED error code, 216
ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 242	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT error code, 223
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFORMATION_SCHEMA error code, 200	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA error code, 223
ER_RPL_FAILED_TO_RESET_STATE_IN_SLAVE_INFORMATION_SCHEMA error code, 200	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_GROUP error code, 222
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 228	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG error code, 216
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 279	ER_RPL_MTA_RECOVERY_COMPLETE error code, 220
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 269	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR error code, 216
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 269	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR error code, 215
ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 203	ER_RPL_MTA_RECOVERY_SUCCESSFUL error code, 216
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 202	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED error code, 243
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 265	ER_RPL_MTA_STATISTICS error code, 219
ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 156	ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED error code, 216
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 513	ER_RPL_MTS_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT error code, 223
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 498	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO error code, 223
	ER_RPL_MTS_GROUP_RECOVERY_RELAY_LOG_INFO_FOR_VERSION error code, 222
	ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG error code, 216

ER_RPL_MTS_RECOVERY_COMPLETE error code, 220	ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL error code, 214
ER_RPL_MTS_RECOVERY_FAILED_TO_START_COORDINATOR error code, 215	ER_RPL_REPLICA_CANT_USE_CHARSET error code, 227
ER_RPL_MTS_RECOVERY_STARTING_COORDINATOR error code, 215	ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION error code, 227
ER_RPL_MTS_RECOVERY_SUCCESSFUL error code, 216	ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_START error code, 600
ER_RPL_MTS_SLAVE_COORDINATOR_HAS_WAITED error code, 243	ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_START error code, 601
ER_RPL_MTS_STATISTICS error code, 219	ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST error code, 228
ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY error code, 201	ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE error code, 219
ER_RPL_OPEN_INDEX_FILE_FAILED error code, 229	ER_RPL_REPLICA_ERROR_INFO_FROM_DA error code, 225
ER_RPL_PLEASE_USE_OPTION_RELAY_LOG error code, 229	ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIB error code, 225
ER_RPL_PLUGIN_FUNCTION_FAILED error code, 175	ER_RPL_REPLICA_ERROR_READING_FROM_SERVER error code, 219
ER_RPL_RECOVERY_ERROR error code, 215	ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENT error code, 228
ER_RPL_RECOVERY_ERROR_FREEING_IO_CACHE error code, 214	ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP error code, 221
ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG error code, 214	ER_RPL_REPLICA_ERROR_RETRYING error code, 219
ER_RPL_RECOVERY_FILE_MASTER_POS_INFO error code, 215	ER_RPL_REPLICA_ERROR_RUNNING_QUERY error code, 225
ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO error code, 215	ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_LOG_INDEX error code, 201
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG error code, 215	ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INSTEAD error code, 213
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER error code, 214	ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA error code, 201
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 214	ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_REQUIRES_POSITION error code, 201
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID error code, 215	ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH error code, 224
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION error code, 214	ER_RPL_REPLICA_FILTER_CREATE_FAILED error code, 271
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY error code, 229	ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD error code, 221
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY error code, 229	ER_RPL_REPLICA_GENERIC_MESSAGE error code, 200
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY error code, 581	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED error code, 271
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLOSE error code, 546	ER_RPL_REPLICA_INCORRECT_CHANNEL error code, 264
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA error code, 225	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE error code, 263
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF error code, 214	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_DA error code, 222
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA error code, 218	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE error code, 220
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER error code, 222	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED error code, 226
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION error code, 220	ER_RPL_REPLICA_IO_THREAD_EXITING error code, 222
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL error code, 214	

ER_RPL_REPLICA_IO_THREAD_KILLED error code, 220	ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 224
ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 498	ER_RPL_REPO_HAS_GAPS error code, 158
ER_RPL_REPLICA_IO_THREAD_WAS_KILLED error code, 217	ER_RPL_REPO_SHOULD_BE_TABLE error code, 198
ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING error code, 562	ER_RPL_REWRITEDB_EMPTY_FROM error code, 170
ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECTED error code, 562	ER_RPL_REWRITEDB_EMPTY_TO error code, 170
ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_INFO error code, 228	ER_RPL_REWRITEDB_MISSING_ARROW error code, 170
ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE error code, 227	ER_RPL_SERVER_ID_MISSING error code, 216
ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE error code, 227	ER_RPL_SLAVE_ADDITIONAL_ERROR_INFO_FROM_DA error code, 224
ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIG error code, 226	ER_RPL_SLAVE_APPLY_LOG_EVENT_FAILED_INVALID_NON_PUSHAUTO_POSITION_IS_1_AND_GTID_MODE_IS_1 error code, 543
ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_FORMAT error code, 543	ER_RPL_SLAVE_CANNOT_FLUSH_MASTER_INFO_FILE error code, 218
ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 226	ER_RPL_SLAVE_CANT_INITIALIZE_SLAVE_WORKER error code, 222
ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 218	ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION error code, 220
ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 218	ER_RPL_SLAVE_CANT_START_SLAVE_FOR_CHANNEL error code, 214
ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 218	ER_RPL_SLAVE_CANT_STOP_SLAVE_FOR_CHANNEL error code, 214
ER_RPL_REPLICA_RESET_FILTER_OPTIONS error code, 271	ER_RPL_SLAVE_CANT_USE_CHARSET error code, 226
ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS error code, 217	ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_REMOTE_HOST error code, 227
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED error code, 224	ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STALE error code, 220
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED error code, 600	ER_RPL_SLAVE_CANNOT_CREATE_CHANNEL_LIST error code, 200
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 600	ER_RPL_SLAVE_DUMP_THREAD_KILLED_BY_MASTER error code, 219
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED error code, 600	ER_RPL_SLAVE_ERROR_INFO_FROM_DA error code, 225
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT error code, 543	ER_RPL_SLAVE_LOADING_USER_DEFINED_LIBRARY_FAILED error code, 225
ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 226	ER_RPL_SLAVE_ERROR_READING_FROM_SERVER error code, 219
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT error code, 228	ER_RPL_SLAVE_ERROR_READING_RELAY_LOG_EVENTS error code, 228
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 224	ER_RPL_SLAVE_ERROR_REQUESTING_BINLOG_DUMP error code, 221
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_WRONG_PAGES error code, 541	ER_RPL_SLAVE_ERROR_RETRYING error code, 219
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 497	ER_RPL_SLAVE_ERROR_RUNNING_QUERY error code, 205
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 221	ER_RPL_SLAVE_FAILED_TO_CREATE_CHANNEL_FROM_MASTER error code, 201
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_UUID error code, 217	ER_RPL_SLAVE_FAILED_TO_CREATE_OR_RECOVER_INFO_RPL error code, 213
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 223	ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE error code, 201

ER_RPL_SLAVE_FAILED_TO_INIT_MASTER_INFO error code, 201	ER_REPAIR_SLAVE_SKIP_COUNTER_EXECUTED error code, 224
ER_RPL_SLAVE_FAILED_TO_INIT_PARTITIONS_HASH error code, 224	ER_RPL_SLAVE_SQL_THREAD_DETECTED_UNEXPECTED error code, 543
ER_RPL_SLAVE_FILTER_CREATE_FAILED error code, 270	ER_RPL_SLAVE_SQL_THREAD_EXITING error code, 225
ER_RPL_SLAVE_FLUSH_RELAY_LOGS_NOT_ALLOWED error code, 263	ER_RPL_SLAVE_SQL_THREAD_IO_ERROR_READING_EVENT error code, 227
ER_RPL_SLAVE_FORCING_TO_RECONNECT_IO_THREAD error code, 221	ER_RPL_SLAVE_SQL_THREAD_STARTING error code, 224
ER_RPL_SLAVE_GENERIC_MESSAGE error code, 200	ER_RPL_SLAVE_SQL_THREAD_STARTING_WITH_PRIVILEGE error code, 541
ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED error code, 271	ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 497
ER_RPL_SLAVE_INCORRECT_CHANNEL error code, 264	ER_RPL_SLAVE_STOPPING_AS_MASTER_OOM error code, 221
ER_RPL_SLAVE_INSECURE_CHANGE_MASTER error code, 263	ER_RPL_SLAVE_USES_CHECKSUM_AND_MASTER_PRE_5 error code, 217
ER_RPL_SLAVE_IO_THREAD_ABORTED_WAITING_FOR_REPLY error code, 222	ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED error code, 223
ER_RPL_SLAVE_IO_THREAD_CANT_REGISTER_ON_MASTER error code, 220	ER_RPL_SLAVE_WORKER_THREAD_CREATION_FAILED_V error code, 223
ER_RPL_SLAVE_IO_THREAD_DETECTED_UNEXPECTED_EVENTS error code, 226	ER_RPL_SLAVE_WORKER_THREAD_DISCONNECTED_METADATA_IGNORED error code, 244
ER_RPL_SLAVE_IO_THREAD_EXITING error code, 222	ER_RPL_SSL_INFO_IN_MASTER_INFO_IGNORED error code, 244
ER_RPL_SLAVE_IO_THREAD_KILLED error code, 220	ER_RPL_TIMESTAMPS_RETURNED_TO_NORMAL error code, 270
ER_RPL_SLAVE_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 498	ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 175
ER_RPL_SLAVE_IO_THREAD_WAS_KILLED error code, 217	ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 203
ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED error code, 217	ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOCK error code, 203
ER_RPL_SLAVE_NDB_TABLES_NOT_AVAILABLE error code, 224	ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM error code, 204
ER_RPL_SLAVE_NEW_MASTER_INFO_NEEDS_REPOSITORY error code, 228	ER_RPL_UNSUPPORTED_FILE_TYPE_OR_UNSUPPORTED_BINIGNORABLE_EVENT_IN_STREAM error code, 203
ER_RPL_SLAVE_NEXT_LOG_IS_ACTIVE error code, 227	ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 243
ER_RPL_SLAVE_NEXT_LOG_IS_INACTIVE error code, 227	ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 243
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_CONNECTION error code, 226	ER_RPL_WORKER_ID_IS error code, 198
ER_RPL_SLAVE_QUEUE_EVENT_FAILED_INVALID_NON_INITIALIZED error code, 543	ER_RPL_ZOMBIE_ENCOUNTED error code, 156
ER_RPL_SLAVE_READ_INVALID_EVENT_FROM_MASTER error code, 226	ER_ROUNDROBIN_APPLIER_PREVENTS_SWITCH_GLOBAL_BIN error code, 107
ER_RPL_SLAVE_REPORT_HOST_TOO_LONG error code, 218	ERR_RUN_HOOK_ERROR error code, 74
ER_RPL_SLAVE_REPORT_PASSWORD_TOO_LONG error code, 218	ER_SAME_NAME_PARTITION error code, 36
ER_RPL_SLAVE_REPORT_USER_TOO_LONG error code, 218	ER_SAME_NAME_PARTITION_FIELD error code, 44
ER_RPL_SLAVE_RESET_FILTER_OPTIONS error code, 271	ER_SCHEDULER_KILLING error code, 160
ER_RPL_SLAVE_SECONDS_BEHIND_MASTER_DUBIOUS error code, 217	ER_SCHEDULER_STARTED error code, 160
	ER_SCHEDULER_STOPPED error code, 159
	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 160
	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 160
	ER_SCHEDULER_WAITING error code, 159
	ER_SCHEMA_DIR_CREATE_FAILED error code, 100

ER_SCHEMA_DIR_EXISTS error code, 100	ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE error code, 290
ER_SCHEMA_DIR_MISSING error code, 100	ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE error code, 293
ER_SCHEMA_DIR_UNKNOWN error code, 100	ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD error code, 294
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 545	ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD error code, 298
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 545	ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET error code, 295
ER_SCHEMA_READ_ONLY error code, 134	ER_SEMISYNC_FORCED_SHUTDOWN error code, 292
ER_SDI_GET_KEYS_INVALID_TABLESPACE error code, 139	ER_SEMISYNC_FUNCTION_CALLED_TWICE error code, 291
ER_SDI_OPERATION_FAILED error code, 98	ER_SEMISYNC_INIT_WAIT_POS error code, 293
ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 130	ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY error code, 290
ER_SECONDARY_ENGINE error code, 122	ER_SEMISYNC_MASTER_FAILED_ON_NET_FLUSH error code, 294
ER_SECONDARY_ENGINE_DDL error code, 122	ER_SEMISYNC_MASTER_GOT_REPLY_AT_POS error code, 292
ER_SECONDARY_ENGINE_DDL_FAILED error code, 606	ER_SEMISYNC_MASTER_OOM error code, 291
ER_SECONDARY_ENGINE_PLUGIN error code, 121	ER_SEMISYNC_MASTER_SIGNAL_ALL_WAITING_THREADS error code, 292
ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 121	ER_SEMISYNC_MASTER_TRX_WAIT_POS error code, 292
ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 162	ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT error code, 296
ER_SECURE_TRANSPORT_REQUIRED error code, 79	ER_SEMISYNC_MOVE_BACK_WAIT_POS error code, 293
ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG error code, 165	ER_SEMISYNC_NOT_SUPPORTED_BY_MASTER error code, 297
ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 164	ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE error code, 297
ER_SEC_FILE_PRIV_CANT_STAT error code, 164	ER_SEMISYNC_NO_SPACE_IN_THE_PKT error code, 293
ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 164	ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY error code, 290
ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 165	ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER error code, 294
ER_SEC_FILE_PRIV_EMPTY error code, 164	ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED error code, 297
ER_SEC_FILE_PRIV_IGNORED error code, 164	ER_SEMISYNC_REPLICA_REPLY error code, 296
ER_SEC_FILE_PRIV_NULL error code, 164	ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO error code, 297
ER_SELECT_REDUCED error code, 20	ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED error code, 297
ER_SEMISYNC_ADD_ACK_TO_SLOT error code, 294	ER_SEMISYNC_REPLICA_SET_FAILED error code, 298
ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 292	ER_SEMISYNC_REPLICA_START error code, 296
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER error code, 290	ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE error code, 291
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TIMEOUT error code, 290	ER_SEMISYNC_REPLY_MAGIC_NO_ERROR error code, 291
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_TIMEOUT error code, 290	ER_SEMISYNC_REPLICA_PKT_LENGTH_TOO_SMALL error code, 291
ER_SEMISYNC_DISABLED_ON_MASTER error code, 291	ER_SEMISYNC_RPL_ENABLED_ON_MASTER error code, 291
ER_SEMISYNC_DISABLED_ON_SOURCE error code, 292	
ER_SEMISYNC_EXECUTION_FAILED_ON_MASTER error code, 297	
ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE error code, 297	
ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER error code, 295	
ER_SEMISYNC_FAILED_REGISTER_SLAVE_TO_RECEIVER error code, 295	

ER_SEMISYNC_RPL_ENABLED_ON_SOURCE error code, 291	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 295
ER_SEMISYNC_RPL_INIT_FOR_TRX error code, 290	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK error code, 294
ER_SEMISYNC_RPL_SWITCHED_OFF error code, 293	ER_SEMISYNC_UPDATE_EXISTING_SLAVE_ACK error code, 294
ER_SEMISYNC_RPL_SWITCHED_ON error code, 293	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 293
ER_SEMISYNC_SERVER_REPLY error code, 291	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT error code, 293
ER_SEMISYNC_SLAVE_NET_FLUSH_REPLY_FAILED error code, 297	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 293
ER_SEMISYNC_SLAVE_REPLY error code, 296	ER_SERVERID_TOO_LARGE error code, 173
ER_SEMISYNC_SLAVE_REPLY_WITH_BINLOG_INFO error code, 296	ER_SERVER_ACL_TABLE_ERROR error code, 504
ER_SEMISYNC_SLAVE_SEND_REPLY_FAILED error code, 297	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF error code, 527
ER_SEMISYNC_SLAVE_SET_FAILED error code, 298	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO error code, 528
ER_SEMISYNC_SLAVE_START error code, 296	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 531
ER_SEMISYNC_SOCKET_FD_TOO_LARGE error code, 296	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 503
ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH error code, 294	ER_SERVER_CANT_OPEN_FILE error code, 503
ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS error code, 292	ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED error code, 504
ER_SEMISYNC_SOURCE_OOM error code, 291	ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UP error code, 504
ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS error code, 292	ER_SERVER_COST_FAILED_TO_READ error code, 203
ER_SEMISYNC_SOURCE_TRX_WAIT_POS error code, 292	ER_SERVER_COST_INVALID_COST_CONSTANT error code, 202
ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 294	ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 202
ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA error code, 295	ER_SERVER_DISK_FULL_NOWAIT error code, 503
ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE error code, 295	ER_SERVER_DOWNGRADE_FROM_VERSION error code, 607
ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 295	ER_SERVER_DOWNGRADE_STATUS error code, 607
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA error code, 295	ER_SERVER_FILE_NOT_FOUND error code, 503
ER_SEMISYNC_STOP_BINLOG_DUMP_TO_SLAVE error code, 295	ER_SERVER_FILE_USED error code, 503
ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 293	ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE error code, 513
ER_SEMISYNC_TRACE_ENTER_FUNC error code, 289	ER_SERVER_HANDLER_ERROR error code, 503
ER_SEMISYNC_TRACE_EXIT error code, 290	ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 282
ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 290	ER_SERVER_ISNT_AVAILABLE error code, 80
ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 289	ER_SERVER_IS_IN_SECURE_AUTH_MODE error code, 22
ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 294	ER_SERVER_MASTER_FATAL_ERROR_READING_BINLOG error code, 500
ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 296	ER_SERVER_MASTER_PACKET_TOO_LARGE error code, 502
ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 296	ER_SERVER_NEW_ABORTING_CONNECTION error code, 502
ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 296	ER_SERVER_NOT_FORM_FILE error code, 503
	ER_SERVER_OUT_OF_SESSION_TO_SEND_TO error code, 502

ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 502	ER_SERVER_SLAVE_RLI_INIT_REPOSITORY error code, 502
ER_SERVER_OFFLINE_MODE error code, 68	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 500
ER_SERVER_OUTOFMEMORY error code, 267	ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 520
ER_SERVER_OUT_OF_RESOURCES error code, 267	ER_SERVER_STARTUP_MSG error code, 267
ER_SERVER_OUT_OF_SORTMEMORY error code, 502	ER_SERVER_TABLE_CHECK_FAILED error code, 503
ER_SERVER_RECORD_FILE_FULL error code, 502	ER_SERVER_TEST_MESSAGE error code, 505
ER_SERVER_REPLICA_AM_INIT_REPOSITORY error code, 502	ER_SERVER_UNKNOWN_ERROR error code, 502
ER_SERVER_REPLICA_CM_INIT_REPOSITORY error code, 501	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 502
ER_SERVER_REPLICA_CONVERSION_FAILED error code, 504	ER_SERVER_UPGRADE_CHECKING_DB error code, 530
ER_SERVER_REPLICA_IGNORED_TABLE error code, 504	ER_SERVER_UPGRADE_EMPTY_SYS error code, 530
ER_SERVER_REPLICA_INIT_QUERY_FAILED error code, 504	ER_SERVER_UPGRADE_FAILED error code, 529
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 523	ER_SERVER_UPGRADE_FROM_VERSION error code, 524
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 518	ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 531
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 519	ER_SERVER_UPGRADE_INFO_FILE error code, 529
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 519	ER_SERVER_UPGRADE_MYSQL_TABLES error code, 530
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_KEY error code, 519	ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 530
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 519	ER_SERVER_UPGRADE_OFF error code, 529
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 519	ER_SERVER_UPGRADE_PENDING error code, 529
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY error code, 520	ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 529
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID error code, 518	ER_SERVER_UPGRADE_REPAIR_STATUS error code, 529
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 519	ER_SERVER_UPGRADE_REPAIR_STATUS_MASTER_KEY_AT_STARTUP error code, 529
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 518	ER_SERVER_UPGRADE_SKIP error code, 529
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECORDING_FAILED error code, 519	ER_SERVER_UPGRADE_STATUS error code, 529
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 519	ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 530
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY error code, 520	ER_SERVER_UPGRADE_SYS_SCHEMA error code, 529
ER_SERVER_SHUTDOWN error code, 6	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 530
ER_SERVER_SHUTDOWN_COMPLETE error code, 265	ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 530
ER_SERVER_SHUTDOWN_INFO error code, 507	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE error code, 530
ER_SERVER_SLAVE_CONVERSION_FAILED error code, 504	ER_SERVER_UPGRADE_SYS_SCHEMA_MASTER_KEY_AT_STARTUP error code, 530
ER_SERVER_SLAVE_IGNORED_TABLE error code, 504	ER_SERVER_UPGRADE_SYS_VERSION_EMPTY error code, 530
ER_SERVER_SLAVE_INIT_QUERY_FAILED error code, 504	ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED error code, 524
ER_SERVER_SLAVE_MI_INIT_REPOSITORY error code, 501	ER_SERVER_WARN_DEPRECATED error code, 527
	ER_SERVER_WRONG_VALUE_FOR_VAR error code, 513
	ER_SESSION_WAS_KILLED error code, 80
	ER_SETNS_FAILED error code, 532
	ER_SET_CONSTANTS_ONLY error code, 17
	ER_SET_EVENT_FAILED error code, 508
	ER_SET_PASSWORD_AUTH_PLUGIN error code, 48

ER_SET_PASSWORD_AUTH_PLUGIN_ERROR error code, 147	ER_SLAVE_CONFIGURATION error code, 56
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 54	ER_SLAVE_CONVERSION_FAILED error code, 46
ER_SE_TYPECODE_CONFLICT error code, 179	ER_SLAVE_CORRUPT_EVENT error code, 41
ER_SHA256_PASSWORD_SECOND_PASSWORD_USED error code, 521	ER_SLAVE_CREATE_EVENT_FAILURE error code, 500
ER_SHAPE_PREDICTION_UDF error code, 150	ER_SLAVE_INFORMATIONAL_ERROR error code, 500
ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE error code, 514	ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER error code, 64
ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL error code, 304	ER_SLAVE_HEARTBEAT_FAILURE error code, 500
ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH error code, 304	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 42
ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING error code, 304	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX error code, 48
ER_SHA_PWD_RSA_KEY_TOO_LONG error code, 305	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN error code, 48
ER_SHA_PWD_SALT_FOR_USER_CORRUPT error code, 305	ER_SLAVE_IGNORED_SSL_PARAMS error code, 21
ER_SHUTDOWN_COMPLETE error code, 8	ER_SLAVE_IGNORED_TABLE error code, 19
ER_SHUTTING_DOWN_REPLICA_THREADS error code, 166	ER_SLAVE_IGNORE_SERVER_IDS error code, 44
ER_SHUTTING_DOWN_SLAVE_THREADS error code, 166	ER_SLAVE_INCIDENT error code, 501
ER_SIGNAL_BAD_CONDITION_TYPE error code, 43	ER_SLAVE_KILLED_AFTER_RECONNECT error code, 278
ER_SIGNAL_EXCEPTION error code, 43	ER_SLAVE_MASTER_COM_FAILURE error code, 501
ER_SIGNAL_NOT_FOUND error code, 43	ER_SLAVE_MAX_CHANNELS_EXCEEDED error code, 72
ER_SIGNAL_WARN error code, 43	ER_SLAVE_MI_INIT_REPOSITORY error code, 62
ER_SIZE_OVERFLOW_ERROR error code, 37	ER_SLAVE_MULTIPLE_CHANNELS_CMD error code, 71
ER_SKIP_UPDATING_METADATA_IN_SE_RDONLY_MODE error code, 277	ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY error code, 71
ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UNKNOWN error code, 563	ER_SLAVE_NOT_RUNNING error code, 16
ER_SLAVE_CANT_CREATE_CONVERSION error code, 46	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CANT_USE_TMPDIR error code, 229	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANGE_MASTER_TO_EXECUTED error code, 228	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_DOES_NOT_EXIST error code, 71	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP error code, 66	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_MUST_STOP error code, 72	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 71	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_NOT_RUNNING error code, 72	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED error code, 77	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER error code, 73	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP error code, 73	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_WAS_NOT_RUNNING error code, 72	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
ER_SLAVE_CHANNEL_WAS_RUNNING error code, 72	ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS error code, 278
	ER_SLAVE_RECONNECT_FAILED error code, 278
	ER_SLAVE_RELAY_LOG_PURGE_FAILED error code, 270
	ER_SLAVE_RELAY_LOG_READ_FAILURE error code, 501
	ER_SLAVE_RELAY_LOG_TRUNCATE_INFO error code, 270
	ER_SLAVE_RELAY_LOG_WRITE_FAILURE error code, 501
	ER_SLAVE_RLI_INIT_REPOSITORY error code, 62
	ER_SLAVE_SILENT_RETRY_TRANSACTION error code, 57
	ER_SLAVE_SQL_THREAD_MUST_STOP error code, 66
	ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_READ error code, 194
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_READ error code, 193
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_READ error code, 194
	ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_READ error code, 194
	ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSING error code, 194
	ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_CONDITION_ERROR error code, 193

ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION error code, 193
 ER_SLAVE_THREAD error code, 16
 ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD error code, 67
 ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGED error code, 112
 ER_SOURCE error code, 15
 ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE error code, 50
 ER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 19
 ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS error code, 56
 ER_SOURCE_NET_READ error code, 15
 ER_SOURCE_NET_WRITE error code, 15
 ER_SPATIAL_CANT_HAVE_NULL error code, 20
 ER_SPATIAL_FUNCTIONAL_INDEX error code, 108
 ER_SPATIAL_MUST_HAVE_GEOM_COL error code, 47
 ER_SPATIAL_UNIQUE_INDEX error code, 105
 ER_SPECIFIC_ACCESS_DENIED_ERROR error code, 18
 ER_SPVAR_NONINTEGER_TYPE error code, 136
 ER_SP_ALREADY_EXISTS error code, 24
 ER_SP_BADRETURN error code, 24
 ER_SP_BADSELECT error code, 24
 ER_SP_BADSTATEMENT error code, 24
 ER_SP_BAD_CURSOR_QUERY error code, 25
 ER_SP_BAD_CURSOR_SELECT error code, 25
 ER_SP_BAD_SQLSTATE error code, 30
 ER_SP_BAD_VAR_SHADOW error code, 32
 ER_SP_CANT_ALTER error code, 26
 ER_SP_CANT_SET_AUTOCOMMIT error code, 32
 ER_SP_CASE_NOT_FOUND error code, 26
 ER_SP_COND_MISMATCH error code, 25
 ER_SP_CURSOR_AFTER_HANDLER error code, 26
 ER_SP_CURSOR_ALREADY_OPEN error code, 25
 ER_SP_CURSOR_MISMATCH error code, 25
 ER_SP_CURSOR_NOT_OPEN error code, 25
 ER_SP_DOES_NOT_EXIST error code, 24
 ER_SP_DROP_FAILED error code, 24
 ER_SP_DUP_COND error code, 25
 ER_SP_DUP_CURS error code, 26
 ER_SP_DUP_HANDLER error code, 30
 ER_SP_DUP_PARAM error code, 25
 ER_SP_DUP_VAR error code, 25
 ER_SP_FETCH_NO_DATA error code, 25
 ER_SP_LABEL_MISMATCH error code, 24
 ER_SP_LABEL_REDEFINE error code, 24
 ER_SP_LILABEL_MISMATCH error code, 24
 ER_SP_LOAD_FAILED error code, 84
 ER_SP_NORETURN error code, 25
 ER_SP_NORETURNEND error code, 25
 ER_SP_NOT_VAR_ARG error code, 30
 ER_SP_NO_AGGREGATE error code, 33
 ER_SP_NO_DROP_SP error code, 27
 ER_SP_NO_RECURSION error code, 31
 ER_SP_NO_RECURSIVE_CREATE error code, 24
 ER_SP_NO_RESET error code, 30
 ER_SP_RECURSION_LIMIT error code, 33
 ER_SP_STORE_FAILED error code, 24
 ER_SP_SUBSELECT_NYI error code, 26
 ER_SP_UNDECLARED_VAR error code, 25
 ER_SP_UNINIT_VAR error code, 24
 ER_SP_VARCOND_AFTER_CURSHNDLR error code, 26
 ER_SP_WRONG_NAME error code, 33
 ER_SP_WRONG_NO_OF_ARGS error code, 25
 ER_SP_WRONG_NO_OF_FETCH_ARGS error code, 25
 ER_SQLTHREAD_WITH_SECURE_REPLICA error code, 53
 ER_SQLTHREAD_WITH_SECURE_SLAVE error code, 53
 ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL error code, 178
 ER_SQL_HA_READ_FAILED error code, 175
 ER_SQL_MODE_MERGED error code, 77
 ER_SQL_MODE_MERGED_WITH_STRICT_MODE error code, 265
 ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 137
 ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE error code, 61
 ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 137
 ER_SQL_USER_TABLE ALTER WARNING error code, 178
 ER_SQL_USER_TABLE CREATE WARNING error code, 178
 ER_SRS_ATTRIBUTE_STRING_TOO_LONG error code, 104
 ER_SRS_GEOGCS_INVALID_AXES error code, 106
 ER_SRS_ID_ALREADY_EXISTS error code, 103
 ER_SRS_INVALID_ANGULAR_UNIT error code, 106
 ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE error code, 104
 ER_SRS_INVALID_HEIGHT error code, 150
 ER_SRS_INVALID_INVERSE_FLATTENING error code, 106
 ER_SRS_INVALID_LATITUDE_OF_ORIGIN error code, 148
 ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A error code, 150
 ER_SRS_INVALID_LONGITUDE_OF_ORIGIN error code, 148
 ER_SRS_INVALID_PRIME_MERIDIAN error code, 106
 ER_SRS_INVALID_SCALING error code, 150
 ER_SRS_INVALID_SEMI_MAJOR_AXIS error code, 106
 ER_SRS_INVALID_ZONE_WIDTH error code, 150
 ER_SRS_MISSING_MANDATORY_ATTRIBUTE error code, 103

ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS error code, 103	ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT error code, 136
ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE error code, 103	ER_STOP_REPLICA_SQL_THREAD_TIMEOUT error code, 63
ER_SRS_NOT_CARTESIAN error code, 84	ER_STOP_SLAVE_IO_THREAD_DISK_SPACE error code, 306
ER_SRS_NOT_CARTESIAN_UNDEFINED error code, 84	ER_STOP_SLAVE_IO_THREAD_TIMEOUT error code, 63
ER_SRS_NOT_FOUND error code, 86	ER_STOP_SLAVE_SQL_THREAD_TIMEOUT error code, 63
ER_SRS_NOT_GEOGRAPHIC error code, 105	ER_STOP_SLAVE_SQL_THREAD_TIMEOUT error code, 63
ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE error code, 103	ER_STORAGE_ENGINE_NOT_LOADED error code, 65
ER_SRS_PARSE_ERROR error code, 84	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DISCARD error code, 47
ER_SRS_PROJ_PARAMETER_MISSING error code, 84	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 38
ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT error code, 148	ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 47
ER_SR_BOGUS_VALUE error code, 175	ER_SUBPARTITION_ERROR error code, 35
ER_SR_INVALID_CONTEXT error code, 176	ER_SUBPARTITION_NAME error code, 43
ER_SSL_FIPS_MODE_ERROR error code, 307	ER_SUBQUERY_NO_1_ROW error code, 20
ER_SSL_LIBRARY_ERROR error code, 161	ER_SUBQUERY_TRANSFORM_REJECTED error code, 132
ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED error code, 514	ER_SWITCH_TMP_ENGINE error code, 89
ER_SSL_SERVER_CERT_VERIFY_FAILED error code, 533	ER_SYNTAX_ERROR error code, 13
ER_SSL_TRYING_DATADIR_DEFAULTS error code, 173	ER_SYSTEMD_NOTIFY_CONNECT_FAILED error code, 369
ER_STACKSIZE_UNEXPECTED error code, 172	ER_SYSTEMD_NOTIFY_DEBUG error code, 592
ER_STACK_BACKTRACE error code, 594	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG error code, 369
ER_STACK_OVERRUN error code, 11	ER_SYSTEMD_NOTIFY_WRITE_FAILED error code, 370
ER_STACK_OVERRUN_NEED_MORE error code, 31	ER_SYSTEM_SCHEMA_NOT_FOUND error code, 156
ER_STARTING_AS error code, 166	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE error code, 167
ER_STARTING_INIT error code, 507	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL error code, 243
ER_STARTING_REPLICA_MONITOR_IO_THREAD error code, 136	ER_SYSTEM_VIEW_INIT_FAILED error code, 268
ER_STARTUP error code, 30	ER_SYSVAR_CHANGE_DURING_QUERY error code, 125
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION error code, 132	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE error code, 306
ER_STD_BAD_ALLOC_ERROR error code, 69	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE error code, 306
ER_STD_DOMAIN_ERROR error code, 69	ER_SYS_VAR_COMPONENT_OOM error code, 305
ER_STD_INVALID_ARGUMENT error code, 69	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE error code, 306
ER_STD_LENGTH_ERROR error code, 69	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY error code, 305
ER_STD_LOGIC_ERROR error code, 69	ER_SYS_VAR_DEREGISTRATION error code, 604
ER_STD_OUT_OF_RANGE_ERROR error code, 69	ER_SYS_VAR_NOT_FOUND error code, 508
ER_STD_OVERFLOW_ERROR error code, 69	ER_SYS_VAR_REGISTRATION error code, 604
ER_STD_RANGE_ERROR error code, 69	ER_TABLEACCESS_DENIED_ERROR error code, 12
ER_STD_REGEX_ERROR error code, 119	ER_TABLENAME_NOT_ALLOWED_HERE error code, 20
ER_STD_RUNTIME_ERROR error code, 69	ER_TABLESPACE_AUTO_EXTEND_ERROR error code, 37
ER_STD_UNDERFLOW_ERROR error code, 69	
ER_STMT_CACHE_FULL error code, 48	
ER_STMT_HAS_NO_OPEN_CURSOR error code, 30	
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 26	
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE error code, 306	
ER_STOP_REPLICA_IO_THREAD_TIMEOUT error code, 63	

ER_TABLESPACE_CANNOT_BE_DECRYPTED error code, 116
 ER_TABLESPACE_CANNOT_BE_ENCRYPTED error code, 116
 ER_TABLESPACE_CANNOT_ENCRYPT error code, 81
 ER_TABLESPACE_DISCARDED error code, 58
 ER_TABLESPACE_DUP_FILENAME error code, 92
 ER_TABLESPACE_ENGINE_MISMATCH error code, 96
 ER_TABLESPACE_EXISTS error code, 58
 ER_TABLESPACE_IS_NOT_EMPTY error code, 76
 ER_TABLESPACE_MISSING error code, 58
 ER_TABLESPACE_MISSING_WITH_NAME error code, 84
 ER_TABLESPACE_TYPE_UNKNOWN error code, 116
 ER_TABLES_DIFFERENT_METADATA error code, 51
 ER_TABLE_CANT_HANDLE_AUTO_INCREMENT error code, 14
 ER_TABLE_CANT_HANDLE_BLOB error code, 14
 ER_TABLE_CANT_HANDLE_FT error code, 17
 ER_TABLE_CANT_HANDLE_SPKEYS error code, 33
 ER_TABLE_CHECK_INTACT error code, 174
 ER_TABLE_CORRUPT error code, 63
 ER_TABLE_CREATED_WITH_DIFFERENT_VERSION error code, 190
 ER_TABLE_DEF_CHANGED error code, 30
 ER_TABLE_EXISTS_ERROR error code, 6
 ER_TABLE_HAS_NO_FT error code, 53
 ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD error code, 189
 ER_TABLE_INCOMPATIBLE_YEAR_FIELD error code, 189
 ER_TABLE_IN_FK_CHECK error code, 50
 ER_TABLE_IN_SHARED_TABLESPACE error code, 150
 ER_TABLE_IN_SYSTEM_TABLESPACE error code, 58
 ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN error code, 139
 ER_TABLE_MUST_HAVE_COLUMNS error code, 10
 ER_TABLE_NAME error code, 43
 ER_TABLE_NAME_CAUSES_TOO_LONG_PATH error code, 125
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 545
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_TEMP error code, 545
 ER_TABLE_NEEDS_DUMP_UPGRADE error code, 285
 ER_TABLE_NEEDS_REBUILD error code, 48
 ER_TABLE_NEEDS_UPGRADE error code, 33
 ER_TABLE_NOT_EMPTY error code, 150
 ER_TABLE_NOT_LOCKED error code, 9
 ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 9
 ER_TABLE_NO_PRIMARY_KEY error code, 150
 ER_TABLE_REFERENCED error code, 81

ER_TABLE_SCHEMA_MISMATCH error code, 58
 ER_TABLE_UPGRADE_REQUIRED error code, 266
 ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT error code, 128
 ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS error code, 128
 ER_TABLE_WITHOUT_PK error code, 107
 ER_TABLE_WRONG_KEY_DEFINITION error code, 190
 ER_TARGET_TABLESPACE_UNENCRYPTED error code, 117
 ER_TARGET_TS_UNENCRYPTED error code, 509
 ER_TC_BAD_MAGIC_IN_TC_LOG error code, 212
 ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER error code, 212
 ER_TC_HEURISTIC_RECOVERY_FAILED error code, 213
 ER_TC_HEURISTIC_RECOVERY_MODE error code, 213
 ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY error code, 212
 ER_TC_RECOVERING_AFTER_CRASH_USING error code, 212
 ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS error code, 213
 ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER error code, 213
 ER_TEMPORARY_NAME error code, 43
 ER_TEMP_FILE_WRITE_FAILURE error code, 63
 ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FOR error code, 107
 ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR error code, 38
 ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FOR error code, 107
 ER_TEXTFILE_NOT_READABLE error code, 8
 ER_TF_FORBIDDEN_JOIN_TYPE error code, 99
 ER_TF_MUST_HAVE_ALIAS error code, 98
 ER_THE_USER_ABIDES error code, 169
 ER_THREAD_HANDLING_OOM error code, 163
 ER_THREAD_POOL_ALGORITHM_INVALID error code, 287
 ER_THREAD_POOL_BUFFER_TOO_SMALL error code, 288
 ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGES error code, 592
 ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA error code, 287
 ER_THREAD_POOL_CONNECTION_REPORT error code, 606
 ER_THREAD_POOL_CON_HANDLER_INIT_FAILED error code, 287
 ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID error code, 583
 ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT error code, 288
 ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLE error code, 287

ER_THREAD_POOL_FAILED_TO_CREATE_POOL error code, 288	ER_TOO_LONG_ROUTINE_COMMENT error code, 84
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_ATTRIBUTES error code, 288	ER_TOO_MANY_CONNECTIONS error code, 83
ER_THREAD_POOL_IDLE_CONNECTION_CLOSED error code, 600	ER_TOO_LONG_STRING error code, 14
ER_THREAD_POOL_INIT_FAILED error code, 287	ER_TOO_LONG_TABLESPACE_COMMENT error code, 92
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER error code, 287	ER_TOO_LONG_TABLE_COMMENT error code, 42
ER_THREAD_POOL_INVALID_STALL_LIMIT error code, 287	ER_TOO_LONG_TABLE_PARTITION_COMMENT error code, 56
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED error code, 288	ER_TOO_MANY_CONCURRENT_CLONES error code, 95
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID error code, 287	ER_TOO_MANY_CONCURRENT_TRXS error code, 43
ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM error code, 286	ER_TOO_MANY_FIELDS error code, 11
ER_THREAD_POOL_PFS_TABLES_ADD_FAILED error code, 518	ER_TOO_MANY_KEYS error code, 7
ER_THREAD_POOL_PFS_TABLES_INIT_FAILED error code, 518	ER_TOO_MANY_KEY_PARTS error code, 8
ER_THREAD_POOL_PLUGIN_STARTED error code, 583	ER_TOO_MANY_PARTITIONS_ERROR error code, 35
ER_THREAD_POOL_QUERY_THREADS_PER_GROUP error code, 595	ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR error code, 44
ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT error code, 595	ER_TOO_MANY_ROWS error code, 14
ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS error code, 288	ER_TOO_MANY_STORAGE_ENGINES error code, 179
ER_THREAD_POOL_SIZE_TOO_HIGH error code, 286	ER_TOO_MANY_TABLES error code, 11
ER_THREAD_POOL_SIZE_TOO_LOW error code, 286	ER_TOO_MANY_USER_CONNECTIONS error code, 107
ER_THREAD_POOL_SYSVAR_CHANGE error code, 594	ER_TOO_MANY_VALUES_ERROR error code, 44
ER_THREAD_PRIORITY_IGNORED error code, 264	ER_TOO_MANY_WINDOWS error code, 146
ER_TLS_CONFIGURATION_REUSED error code, 553	ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT error code, 149
ER_TLS_CONFIGURED_FOR_CHANNEL error code, 553	ER_TRACK_VARIABLES_BOGUS error code, 169
ER_TMPDIR_PATH_TOO_LONG error code, 560	ER_TRANSACTION_ROLLBACK_DURING_COMMIT error code, 74
ER_TMP_SESSION_FOR_VAR error code, 592	ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84 error code, 107
ER_TOO_BIG_DISPLAYWIDTH error code, 31	ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED error code, 106
ER_TOO_BIG_ENUM error code, 83	ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84 error code, 107
ER_TOO_BIG_FIELDLLENGTH error code, 8	ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED error code, 106
ER_TOO_BIG_FOR_UNCOMPRESS error code, 20	ER_TRANSPORTS_WHAT_TRANSPORTS error code, 167
ER_TOO_BIG_PRECISION error code, 31	ER_TRANS_CACHE_FULL error code, 16
ER_TOO_BIG_ROWSIZE error code, 11	ER_TREE_CORRUPT_2_CONSECUTIVE_REDS error code, 241
ER_TOO_BIG_SCALE error code, 31	ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT error code, 242
ER_TOO_BIG_SELECT error code, 10	ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT error code, 241
ER_TOO_BIG_SET error code, 9	ER_TREE_CORRUPT_RIGHT_IS_LEFT error code, 242
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT error code, 34	ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK error code, 241
ER_TOO_LONG_BODY error code, 31	ER_TRG_ALREADY_EXISTS error code, 27
ER_TOO_LONG_FIELD_COMMENT error code, 42	ER_TRG_CANT_CHANGE_ROW error code, 27
ER_TOO_LONG_IDENT error code, 7	ER_TRG_CANT_OPEN_TABLE error code, 41
ER_TOO_LONG_INDEX_COMMENT error code, 47	ER_TRG_CANT_PARSE error code, 174
ER_TOO_LONG_KEY error code, 8	

ER_TRG_CORRUPTED_FILE error code, 41
 ER_TRG_CREATION_CTX_NOT_SET error code, 266
 ER_TRG_DOES_NOT_EXIST error code, 27
 ER_TRG_INVALID_CREATION_CTX error code, 41
 ER_TRG_IN_WRONG_SCHEMA error code, 31
 ER_TRG_NO_CLIENT_CHARSET error code, 161
 ER_TRG_NO_CREATION_CTX error code, 41
 ER_TRG_NO_DEFINER error code, 33
 ER_TRG_NO_SUCH_ROW_IN_TRG error code, 27
 ER_TRG_ON_VIEW_OR_TEMP_TABLE error code, 27
 ER_TRG_WITHOUT_DEFINER error code, 161
 ER_TRG_WRONG_ORDER error code, 524
 ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED error code, 288
 ER_TRIGGER_INVALID_VALUE error code, 155
 ER_TRUNCATED_WRONG_VALUE error code, 23
 ER_TRUNCATED_WRONG_VALUE_FOR_FIELD error code, 27
 ER_TRUNCATE_ILLEGAL_FK error code, 48
 ER_TRX_GTID_COLLECT_REJECT error code, 178
 ER_TRX_WRITE_SET_OOM error code, 179
 ER_TURNING_LOGGING_OFF_FOR_THE_DURATION error code, 259
 ER_TURNING_ON_PARTIAL_REVOKES error code, 528
 ER_TX_EXTRACTION_ALGORITHM_FOR_BINLOG_TX error code, 269
 ER_TZ_CANT_BUILD_MKTIME_MAP error code, 192
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE error code, 191
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE error code, 191
 ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE error code, 191
 ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE error code, 191
 ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE error code, 192
 ER_TZ_OOM_INITIALIZING_TIME_ZONES error code, 191
 ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE error code, 191
 ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION error code, 192
 ER_TZ_OOM_WHILE_LOADING_TIME_ZONE error code, 193
 ER_TZ_OOM_WHILE_SETTING_TIME_ZONE error code, 193
 ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE error code, 191
 ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE error code, 192
 ER_TZ_TRANSITION_TABLE_LOAD_ERROR error code, 192
 ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS error code, 192
 ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED error code, 192
 ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR error code, 192
 ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE error code, 192
 ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE error code, 191
 ER_UDF_ALREADY_EXISTS error code, 508
 ER_UDF_CANT_ALLOC_FOR_FUNCTION error code, 177
 ER_UDF_CANT_ALLOC_FOR_STRUCTURES error code, 176
 ER_UDF_CANT_OPEN_FUNCTION_TABLE error code, 177
 ER_UDF_DEREGISTRATION error code, 604
 ER_UDF_DROP_DYNAMICALLY_REGISTERED error code, 94
 ER_UDF_ERROR error code, 82
 ER_UDF_EXEC_FAILURE error code, 604
 ER_UDF_EXEC_FAILURE_REASON error code, 604
 ER_UDF_EXISTS error code, 11
 ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE error code, 177
 ER_UDF_NO_PATHS error code, 11
 ER_UDF_REGISTER_ERROR error code, 559
 ER_UDF_REGISTER_SERVICE_ERROR error code, 559
 ER_UDF_REGISTRATION error code, 604
 ER_UDF_UNREGISTER_ERROR error code, 559
 ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_A error code, 117
 ER_UNABLE_TO_BUILD_HISTOGRAM error code, 94
 ER_UNABLE_TO_COLLECT_LOG_STATUS error code, 104
 ER_UNABLE_TO_DROP_COLUMN_STATISTICS error code, 94
 ER_UNABLE_TO_RESOLVE_HOSTNAME error code, 160
 ER_UNABLE_TO_RESOLVE_IP error code, 160
 ER_UNABLE_TO_SET_OPTION error code, 104
 ER_UNABLE_TO_STORE_COLUMN_STATISTICS error code, 94
 ER_UNABLE_TO_STORE_STATISTICS error code, 86
 ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS error code, 94
 ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN error code, 99
 ER_UNDO_RECORD_TOO_BIG error code, 49
 ER_UNEXPECTED_GEOMETRY_TYPE error code, 84
 ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 35
 ER_UNIT_NOT_FOUND error code, 124
 ER_UNKNOWN_ALTER_ALGORITHM error code, 56
 ER_UNKNOWN_ALTER_LOCK error code, 57
 ER_UNKNOWN_AUTHID error code, 84

ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE error code, 272	ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 24
ER_UNKNOWN_CHARACTER_SET error code, 10	ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 24
ER_UNKNOWN_COLLATION error code, 21	ER_UPDATE_TABLE_USED error code, 9
ER_UNKNOWN_COM_ERROR error code, 6	ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 14
ER_UNKNOWN_ERROR error code, 10	ER_UPDATING_DD_TABLE error code, 83
ER_UNKNOWN_ERROR_DETECTED_IN_SE error code, 277	ER_UPGRADE_NONEXISTENT_SCHEMA error code, 560
ER_UNKNOWN_ERROR_NUMBER error code, 176	ER_UPGRADE_PARSE_ERROR error code, 513
ER_UNKNOWN_EXPLAIN_FORMAT error code, 56	ER_UPGRADE_WITH_PARTITIONED_TABLES_REJECTED error code, 539
ER_UNKNOWN_KEY_CACHE error code, 23	ER_USAGE_DEPRECATED_COUNTER error code, 608
ER_UNKNOWN_LOCALE error code, 44	ER_USERNAME error code, 33
ER_UNKNOWN_NETWORK_NAMESPACE error code, 532	ER_USERNAME_TRUNCATED error code, 554
ER_UNKNOWN_PARTITION error code, 51	ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCK error code, 130
ER_UNKNOWN_PROCEDURE error code, 10	ER_USER_ALREADY_EXISTS error code, 79
ER_UNKNOWN_STMT_HANDLER error code, 20	ER_USER_COLUMN_OLD_LENGTH error code, 81
ER_UNKNOWN_STORAGE_ENGINE error code, 23	ER_USER_DOES_NOT_EXIST error code, 79
ER_UNKNOWN_SYSTEM_VARIABLE error code, 16	ER_USER_LIMIT_REACHED error code, 18
ER_UNKNOWN_TABLE error code, 10	ER_USER_LOCK_DEADLOCK error code, 70
ER_UNKNOWN_TABLESPACE_TYPE error code, 514	ER_USER_LOCK_OVERLONG_NAME error code, 154
ER_UNKNOWN_TABLE_IN_UPGRADE error code, 538	ER_USER_LOCK_WRONG_NAME error code, 70
ER_UNKNOWN_TARGET_BINLOG error code, 28	ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_IN error code, 188
ER_UNKNOWN_TIME_ZONE error code, 23	ER_USER_REFERENCED_AS_DEFINER error code, 136
ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE error code, 162	ER_USER_REGISTRATION_FAILED error code, 142
ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG error code, 508	ER_USER_REQUIRES_ROOT error code, 167
ER_UNRESOLVED_HINT_NAME error code, 76	ER_USER_WHAT_USER error code, 167
ER_UNRESOLVED_TABLE_LOCK error code, 88	ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION error code, 137
ER_UNSUPPORTED_LOG_ENGINE error code, 39	ER_UUID_INVALID error code, 162
ER_UNSUPPORTED_ACTION_ON_DEFAULT_VALUE_GENERATOR error code, 110	ER_UUID_IS error code, 162
ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN error code, 75	ER_UUID_SALT error code, 162
ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE error code, 81	ER_UUID_SCRUB error code, 162
ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN error code, 74	ER_VALGRIND_COUNT_LEAKS error code, 176
ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN error code, 80	ER_VALGRIND_DO_QUICK_LEAK_CHECK error code, 176
ER_UNSUPPORTED_DATE error code, 166	ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTER error code, 154
ER_UNSUPPORTED_ENGINE error code, 50	ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED error code, 371
ER_UNSUPPORTED_EXTENSION error code, 10	ER_VALIDATE_PWD_COULD_BE_NULL error code, 370
ER_UNSUPPORTED_INDEX_ALGORITHM error code, 83	ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED error code, 302
ER_UNSUPPORTED_PS error code, 23	ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED error code, 302
ER_UNSUPPORTED_SQL_MODE error code, 123	ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED error code, 370
ER_UNSUPPORTED_USE_OF_GRANT_AS error code, 117	ER_VALIDATE_PWD_DICT_FILE_TOO_BIG error code, 303
ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE error code, 83	
ER_UNTIL_COND_IGNORED error code, 22	
ER_UPDATE_GTID_PURGED_WITH_GR error code, 125	
ER_UPDATE_INFO error code, 12	

ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CATALOG error code, 303	ER_VIEW_WRONG_SELECT_VARIABLE error code, 27
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CONTEXT error code, 303	ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION error code, 156
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE error code, 303	ER_VIEW_UNPARSABLE error code, 190
ER_VALIDATE_PWD_LENGTH_CHANGED error code, 303	ER_VIEW_WRONG_LIST error code, 27
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED error code, 370	ER_VTOKEN_PLUGIN_TOKEN_MISMATCH error code, 77
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED error code, 370	ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 77
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED error code, 371	ER_WAITING_FOR_NO_CONNECTIONS error code, 608
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED error code, 370	ER_WAITPID_FAILED error code, 283
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED error code, 371	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES error code, 520
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED error code, 371	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID error code, 520
ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED error code, 371	ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 52
ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED error code, 371	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_ERROR error code, 52
ER_VALUES_IS_NOT_INT_TYPE_ERROR error code, 47	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_ERROR error code, 52
ER_VALUE_OUT_OF_RANGE error code, 144	ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID error code, 96
ER_VARIABLE_IS_NOT_STRUCT error code, 21	ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID error code, 520
ER_VARIABLE_IS_READONLY error code, 42	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 140
ER_VARIABLE_NOT_PERSISTED error code, 86	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LIMIT error code, 572
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 54	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE error code, 140
ER_VARIABLE_NOT_SETTABLE_IN_SP error code, 60	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LIMIT error code, 572
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 54	ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 24
ER_VAR_CANT_BE_READ error code, 19	ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE error code, 139
ER_VAR_DOES_NOT_EXIST error code, 93	ER_WARN_AUDIT_LOG_DISABLED error code, 581
ER_VERBOSE_HINT error code, 169	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_ENABLED error code, 141
ER_VERBOSE_REQUIRES_HELP error code, 163	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_ENABLED_LIMIT error code, 573
ER_VIEW_CHECKSUM error code, 29	ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLE error code, 542
ER_VIEW_CHECK_FAILED error code, 28	ER_WARN_BAD_MAX_EXECUTION_TIME error code, 76
ER_VIEW_CREATION_CTX_NOT_SET error code, 266	ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 96
ER_VIEW_DELETE_MERGE_VIEW error code, 29	ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_UPDATES error code, 97
ER_VIEW_FRM_NO_USER error code, 32	ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED error code, 96
ER_VIEW_INVALID error code, 27	ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION error code, 602
ER_VIEW_INVALID_CREATION_CTX error code, 40	ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 581
ER_VIEW_MULTIUPDATE error code, 29	
ER_VIEW_NONUPD_CHECK error code, 28	
ER_VIEW_NO_CREATION_CTX error code, 40	
ER_VIEW_NO_EXPLAIN error code, 26	
ER_VIEW_NO_INSERT_FIELD_LIST error code, 29	
ER_VIEW_OTHER_USER error code, 32	
ER_VIEW_PREVENT_UPDATE error code, 32	
ER_VIEW_RECURSIVE error code, 33	
ER_VIEW_SELECT_CLAUSE error code, 27	
ER_VIEW_SELECT_TMPTABLE error code, 27	

ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES error code, 147	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 46
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 31	ER_WARN_DEPRECATED_SYNTAX_WITH_VER error code, 38
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY error code, 131	ER_WARN_DEPRECATED_SYSVAR_UPDATE error code, 73
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MISSING error code, 601	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL error code, 570
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_WRONG error code, 565	ER_WARN_DEPRECATED_TLS_VERSION_FOR_CHANNEL error code, 140
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE error code, 594	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS error code, 154
ER_WARN_CONFLICTING_HINT error code, 76	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS error code, 60
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POSITION error code, 144	ER_WARN_DEPRECATED_USER_SET_EXPR error code, 110
ER_WARN_DATA_OUT_OF_RANGE error code, 21	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION error code, 514
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 108	ER_WARN_DEPRECATED_UTF8MB3_COLLATION error code, 110
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 108	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION error code, 514
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED error code, 127	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION error code, 514
ER_WARN_DEPRECATED_CHARSET_OPTION error code, 580	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS error code, 131
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION error code, 150	ER_WARN_DEPRECATED_WITH_NOTE error code, 154
ER_WARN_DEPRECATED_COLLATION error code, 145	ER_WARN_DEPRECATED_YEAR_UNSIGNED error code, 130
ER_WARN_DEPRECATED_COLLATION_OPTION error code, 580	ER_WARN_DEPRECATED_ZEROFILL error code, 120
ER_WARN_DEPRECATED_DATETIME_DELIMITER error code, 147	ER_WARN_ENGINE_TRANSACTION_ROLLBACK error code, 42
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT error code, 119	ER_WARN_FIELD_RESOLVED error code, 22
ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 119	ER_WARN_FUNC_INDEX_NOT_APPLICABLE error code, 124
ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 119	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VA error code, 572
ER_WARN_DEPRECATED_FOUND_ROWS error code, 131	ER_WARN_GTID_THRESHOLD_BREACH error code, 563
ER_WARN_DEPRECATED_IDENT error code, 149	ER_WARN_HOSTNAME_WONT_WORK error code, 23
ER_WARN_DEPRECATED_INNER_INTO error code, 131	ER_WARN_HYPERGRAPH_EXPERIMENTAL error code, 135
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 120	ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 528
ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR error code, 130	ER_WARN_INDEX_NOT_APPLICABLE error code, 51
ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX error code, 111	ER_WARN_INVALID_DB_RESTRICTIONS error code, 528
ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER error code, 608	ER_WARN_INVALID_HINT error code, 93
ER_WARN_DEPRECATED_SQLMODE error code, 73	ER_WARN_INVALID_TIMESTAMP error code, 23
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 131	ER_WARN_I_S_SKIPPED_TABLE error code, 46
ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER error code, 147	ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 65
ER_WARN_DEPRECATED_SYNTAX error code, 23	ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY error code, 551

ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 541	ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR error code, 552
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 540	ER_WARN_TOO_FEW_RECORDS error code, 21
ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_REPLICATION error code, 541	ER_WARN_TOO_MANY_RECORDS error code, 21
ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS error code, 577	ER_WARN_TRIGGER_ALREADY_EXISTS error code, 147
ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING error code, 581	ER_WARN_TRIGGER_DOESNT_HAVE_CREATED_AUTO_POS error code, 565
ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 565	ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 540
ER_WARN_NO_SERVERID_SPECIFIED error code, 265	ER_WARN_UNKNOWN_QB_NAME error code, 76
ER_WARN_NO_SPACE_VERSION_COMMENT error code, 154	ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 86
ER_WARN_NULL_TO_NOTNULL error code, 21	ER_WARN_UNSUPPORTED_HINT error code, 84
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS error code, 67	ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 76
ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS error code, 67	ER_WARN_USING_OTHER_HANDLER error code, 21
ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 76	ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 135
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 66	ER_WARN_VIEW_MERGE error code, 27
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 76	ER_WARN_VIEW_WITHOUT_KEY error code, 27
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 528	ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG error code, 540
ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 523	ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 540
ER_WARN_PURGE_LOG_IN_USE error code, 62	ER_WASTEFUL_NET_BUFFER_SIZE error code, 163
ER_WARN_PURGE_LOG_IS_ACTIVE error code, 62	ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND error code, 532
ER_WARN_QC_RESIZE error code, 22	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 89
ER_WARN_REGEX_USING_DEFAULT error code, 145	ER_WINDOW_DUPLICATE_NAME error code, 90
ER_WARN_REMOVED_SQL_MODE error code, 515	ER_WINDOW_EXPLAIN_JSON error code, 91
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_OLD_UUID error code, 571	ER_WINDOW_FRAME_END_ILLEGAL error code, 90
ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON error code, 577	ER_WINDOW_FRAME_ILLEGAL error code, 90
ER_WARN_RESERVED_SRID_RANGE error code, 103	ER_WINDOW_FRAME_START_ILLEGAL error code, 90
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER error code, 542	ER_WINDOW_FUNCTION_IGNORES_FRAME error code, 91
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 542	ER_WINDOW_INVALID_WINDOW_FUNC_ORDER BY error code, 91
ER_WARN_SCHEDULED_TASK_RUN_FAILED error code, 606	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE error code, 91
ER_WARN_SF_UDF_NAME_COLLISION error code, 145	ER_WINDOW_INVALID_WINDOW_FUNC_USE error code, 91
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED error code, 141	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SP error code, 91
ER_WARN_SRS_ID_ALREADY_EXISTS error code, 103	ER_WINDOW_NO_CHILD_PARTITIONING error code, 89
ER_WARN_SRS_NOT_FOUND error code, 84	ER_WINDOW_NO_GROUP_ORDER error code, 91
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 88	ER_WINDOW_NO_GROUP_ORDER_UNUSED error code, 91
	ER_WINDOW_NO_INHERIT_FRAME error code, 90
	ER_WINDOW_NO_REDEFINE_ORDER_BY error code, 90
	ER_WINDOW_NO_SUCH_WINDOW error code, 89
	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT error code, 90
	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE error code, 90

ER_WINDOW_RANGE_FRAME_ORDER_TYPE error code, 90	ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 10
ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE error code, 90	ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 40
ER_WINDOW_ROWS_INTERVAL_USE error code, 91	ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 10
ER_WINDOW_SE_NOT_ACCEPTABLE error code, 91	ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 40
ER_WIN_LISTEN_BUT_HOW error code, 168	ER_WRONG_PARTITION_NAME error code, 39
ER_WIN_LOAD_LIBRARY_FAILED error code, 282	ER_WRONG_PERFSCHEMA_USAGE error code, 46
ER_WL9236_NOW_UNUSED error code, 92	ER_WRONG_SIZE_NUMBER error code, 37
ER_WRITABLE_CONFIG_REMOVED error code, 165	ER_WRONG_SPVAR_TYPE_IN_LIMIT error code, 47
ER_WRITE_ROW_TO_PARTITION_FAILED error code, 272	ER_WRONG_SRID_FOR_COLUMN error code, 96
ER_WRITE_SET_EXCEEDS_LIMIT error code, 82	ER_WRONG_STRING_LENGTH error code, 33
ER_WRONG_ARGUMENTS error code, 17	ER_WRONG_SUB_KEY error code, 9
ER_WRONG_AUTO_KEY error code, 8	ER_WRONG_SUM_SELECT error code, 7
ER_WRONG_COLUMN_NAME error code, 14	ER_WRONG_TABLESPACE_NAME error code, 76
ER_WRONG_COMPRESSION_ALGORITHM_CLIENT error code, 126	ER_WRONG_TABLE_NAME error code, 10
ER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 126	ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 44
ER_WRONG_COUNT_FOR_KEY error code, 242	ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD error code, 281
ER_WRONG_COUNT_FOR_ORIGIN error code, 242	ER_WRONG_TYPE_FOR_VAR error code, 19
ER_WRONG_COUNT_OF_ELEMENTS error code, 242	ER_WRONG_USAGE error code, 18
ER_WRONG_DATETIME_SPEC error code, 165	ER_WRONG_VALUE error code, 37
ER_WRONG_DB_NAME error code, 10	ER_WRONG_VALUE_COUNT error code, 7
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 34	ER_WRONG_VALUE_COUNT_ON_ROW error code, 12
ER_WRONG_FIELD_SPEC error code, 7	ER_WRONG_VALUE_FOR_TYPE error code, 30
ER_WRONG_FIELD_TERMINATORS error code, 8	ER_WRONG_VALUE_FOR_VAR error code, 19
ER_WRONG_FIELD_WITH_GROUP error code, 7	ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART error code, 132
ER_WRONG_FIELD_WITH_GROUP_V2 error code, 73	ER_X509_CANT_CHMOD_KEY error code, 184
ER_WRONG_FILE_NAME error code, 76	ER_X509_CANT_CREATE_CERT error code, 184
ER_WRONG_FK_DEF error code, 19	ER_X509_CANT_READ_CA_CERT error code, 184
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 75	ER_X509_CANT_READ_CA_KEY error code, 184
ER_WRONG_GROUP_FIELD error code, 7	ER_X509_CANT_WRITE_CERT error code, 184
ER_WRONG_JSON_TABLE_VALUE error code, 98	ER_X509_CANT_WRITE_KEY error code, 184
ER_WRONG_KEY_COLUMN error code, 14	ER_X509_CIPHERS_MISMATCH error code, 184
ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX error code, 109	ER_X509_ISSUER_MISMATCH error code, 184
ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 31	ER_X509_NEEDS_RSA_PRIVKEY error code, 184
ER_WRONG_MRG_TABLE error code, 14	ER_X509_SUBJECT_MISMATCH error code, 184
ER_WRONG_MVI_VALUE error code, 124	ER_XAER_DUPID error code, 32
ER_WRONG_NAME_FOR_CATALOG error code, 22	ER_XAER_INVALID error code, 29
ER_WRONG_NAME_FOR_INDEX error code, 22	ER_XAER_NOTA error code, 29
ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 46	ER_XAER_OUTSIDE error code, 29
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 18	ER_XAER_RMERR error code, 29
ER_WRONG_OBJECT error code, 26	ER_XAER_RMFAIL error code, 29
ER_WRONG_OUTER_JOIN error code, 11	ER_XA_CANT_CREATE_MDL_BACKUP error code, 538
ER_WRONG_OUTER_JOIN_UNUSED error code, 11	ER_XA_COMMITTING_XID error code, 177
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 40	ER_XA_IGNOREING_XID error code, 177
	ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER error code, 177
	ER_XA_RBDEADLOCK error code, 41
	ER_XA_RBROLLBACK error code, 29
	ER_XA_RBTIMEOUT error code, 41
	ER_XA_RECOVERY_DONE error code, 178

ER_XA_RECOVER_EXPLANATION error code, 178	ER_XPLUGIN_FAILED_TO_GET_SYS_VAR error code, 314
ER_XA_RECOVER_FOUND_TRX_IN_SE error code, 177	ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION error code, 310
ER_XA_RECOVER_FOUND_XA_TRX error code, 177	ER_XPLUGIN_FAILED_TO_INTERRUPT_SESSION error code, 313
ER_XA_REPLICATION_FILTERS error code, 123	ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION error code, 314
ER_XA_RETRY error code, 82	ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES error code, 309
ER_XA_ROLLING_BACK_XID error code, 177	ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG error code, 315
ER_XA_STARTING_RECOVERY error code, 177	ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT error code, 308
ER_XA_TEMP_TABLE error code, 146	ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS error code, 310
ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED error code, 311	ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG error code, 314
ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED error code, 308	ER_XPLUGIN_FAILED_TO_STOP_SERVICES error code, 499
ER_XPLUGIN_CAPABILITY_CLIENT_INTERACTIVE_FAILED error code, 315	ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT error code, 314
ER_XPLUGIN_CAPABILITY_EXPIRED_PASSWORD error code, 314	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX error code, 513
ER_XPLUGIN_CLIENT_KILL_MSG error code, 313	ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX_TO_ROOT error code, 313
ER_XPLUGIN_CLIENT_RELEASE_TRIGGERED error code, 313	ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF error code, 315
ER_XPLUGIN_CLIENT_SSL_HANDSHAKE_FAILED error code, 310	ER_XPLUGIN_FAILED_TO_USE_SSL_CONF error code, 304
ER_XPLUGIN_CLOSING_CLIENTS_ON_SHUTDOWN error code, 311	ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS error code, 552
ER_XPLUGIN_COMPRESSION_ERROR error code, 540	ER_XPLUGIN_FAIL_TO_GET_RESULT_DATA error code, 314
ER_XPLUGIN_DETECTED_HANGING_CLIENTS error code, 308	ER_XPLUGIN_FORCE_STOP_CLIENT error code, 308
ER_XPLUGIN_EMPTY_ADMIN_CMD error code, 314	ER_XPLUGIN_GET_PEER_ADDRESS_FAILED error code, 315
ER_XPLUGIN_ERROR_MSG error code, 304	ER_XPLUGIN_INVALID_AUTH_METHOD error code, 311
ER_XPLUGIN_ERROR_READING_SOCKET error code, 311	ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT error code, 311
ER_XPLUGIN_ERROR_WRITING_TO_CLIENT error code, 311	ER_XPLUGIN_IPv6_AVAILABLE error code, 313
ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP error code, 309	ER_XPLUGIN_LISTENER_SETUP_FAILED error code, 309
ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER error code, 309	ER_XPLUGIN_LISTENER_STATUS_MSG error code, 312
ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCORRECT_CREDENTIALS error code, 312	ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 312
ER_XPLUGIN_FAILED_AT_SSL_CONF error code, 310	ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED error code, 308
ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT error code, 308	ER_XPLUGIN_MESSAGE_TOO_LONG error code, 310
ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS error code, 553	ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG error code, 311
ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION error code, 313	ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION error code, 311
ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN error code, 310	
ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD error code, 314	
ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT error code, 314	
ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO error code, 314	
ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX error code, 313	

ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_WRONG_NAME error code, 304
 ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOES_NOT_EXIST error code, 309
 ER_XPLUGIN_RETRYING_BIND_ON_PORT error code, 312
 ER_XPLUGIN_SCHEDULER_STARTED error code, 312
 ER_XPLUGIN_SCHEDULER_STOPPED error code, 312
 ER_XPLUGIN_SERVER_EXITED error code, 303
 ER_XPLUGIN_SERVER_EXITING error code, 303
 ER_XPLUGIN_SERVER_STARTS_HANDLING_CONNECTIONS error code, 312
 ER_XPLUGIN_SERVER_STOPPED_HANDLING_CONNECTIONS error code, 313
 ER_XPLUGIN_SHUTDOWN_TRIGGERED error code, 312
 ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED error code, 309
 ER_XPLUGIN_SSL_HANDSHAKE_WITH_SERVER_FAILED error code, 310
 ER_XPLUGIN_STARTUP_FAILED error code, 303
 ER_XPLUGIN_TASK_SCHEDULING_FAILED error code, 309
 ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION error code, 310
 ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT error code, 309
 ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD error code, 309
 ER_XPLUGIN_UNEXPECTED_MSG_DURING_AUTHENTICATION error code, 311
 ER_XPLUGIN_UNINITIALIZED_MESSAGE error code, 310
 ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED error code, 313
 ER_XPLUGIN_USER_ACCOUNT_WITH_ALL_PERMISSIONS error code, 312
 ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX error code, 304
 ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER error code, 304
 ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION error code, 304
 ER_XPLUING_NET_STARTUP_FAILED error code, 310
 ER_YES error code, 3
 ER_ZLIB_Z_BUF_ERROR error code, 20
 ER_ZLIB_Z_DATA_ERROR error code, 20
 ER_ZLIB_Z_MEM_ERROR error code, 20

W

WARN_AES_KEY_SIZE error code, 83
 WARN_COND_ITEM_TRUNCATED error code, 44
 WARN_DATA_TRUNCATED error code, 21
 WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 107

